

Power measurements for
 B8QAC SCT1
 3 button transmitter

Scan	Res.	DUT	Meter	Meter	Antenna	Coax	Amplifier	Measurement	Duty Cycle	3 Meter	Field	Delta
/Div	Bandwidth	Frequency	Frequency	Reading	Factor	Factor	Gain	Distance	Correction	Limit	Strength	Limit
Mhz	Khz	(Mhz)	(Mhz)	(dBm)	(dB)	(dB)	(dB)	(Meters)	(dB)	(uV/M)	(uV/M)	(dB)
0.5	100	390	390	-23.5	21	4	26	3	-10.7	9170	3,890.45	-7.45
0.5	100	390	780	-44.9	27	5.8	28	3	-10.7	917	645.65	-3.05
0.5	1000	390	1170	-46.8	23.7	7.9	36	3	-10.7	500	179.89	-8.88
0.5	1000	390	1560	-56.5	25	9.42	37.4	3	-10.7	500	69.34	-17.16
0.5	1000	390	1950	-64.5	27.3	10.78	37.3	3	-10.7	917	42.56	-26.67
0.5	1000	390	2340	-66.1	28	12	35.4	3	-10.7	500	54.95	-19.18
0.5	1000	390	2730	-66.3	29.5	13.2	35.5	3	-10.7	500	72.44	-16.78
0.5	1000	390	3120	-67.1	31.29	14.3	35.6	3	-10.7	917	91.10	-20.06
0.5	1000	390	3510	-67.2	31.4	15.4	35.6	3	-10.7	917	103.51	-18.95
0.5	1000	390	3900	-67.5	32.85	16.4	35.4	3	-10.7	500	135.68	-11.33