

### #01\_WLAN 2.4G\_802.11b\_Bottom Face\_0cm\_Ch1

**DUT: 331535**

Communication System: 802.11b; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium: MSL\_2450\_130319 Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.855$  mho/m;  $\epsilon_r = 51.932$ ;  $\rho$

$= 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.1 °C; Liquid Temperature : 21.1 °C

DASY5 Configuration:

- Probe: ES3DV3 - SN3270; ConvF(4.17, 4.17, 4.17); Calibrated: 2012/9/28;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2012/8/27
- Phantom: ELI 4.0\_Front; Type: QDOVA001BB; Serial: 1026
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)

**Configuration/Ch1/Area Scan (61x111x1):** Measurement grid: dx=12mm, dy=12mm  
Maximum value of SAR (interpolated) = 0.832 mW/g



**Configuration/Ch1/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 21.070 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 1.370 mW/g

**SAR(1 g) = 0.588 mW/g; SAR(10 g) = 0.284 mW/g**

Maximum value of SAR (measured) = 0.778 mW/g



0 dB = 0.778 mW/g = -2.18 dB mW/g

## #02\_WLAN 2.4G\_802.11b\_Bottom Face\_0cm\_Ch1;curve30

**DUT: 331535**

Communication System: 802.11b; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium: MSL\_2450\_130319 Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.855$  mho/m;  $\epsilon_r = 51.932$ ;  $\rho$

$= 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.1 °C; Liquid Temperature : 21.1 °C

DASY5 Configuration:

- Probe: ES3DV3 - SN3270; ConvF(4.17, 4.17, 4.17); Calibrated: 2012/9/28;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2012/8/27
- Phantom: ELI 4.0\_Front; Type: QDOVA001BB; Serial: 1026
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)

**Configuration/Ch1/Area Scan (61x111x1):** Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 1.29 mW/g


**Configuration/Ch1/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 26.065 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 2.240 mW/g

**SAR(1 g) = 0.895 mW/g; SAR(10 g) = 0.373 mW/g**

Maximum value of SAR (measured) = 1.21 mW/g



0 dB = 1.21 mW/g = 1.66 dB mW/g

### #03\_WLAN 2.4G\_802.11b\_Bottom Face\_0cm\_Ch6;curve30

**DUT: 331535**

Communication System: 802.11b; Frequency: 2437 MHz; Duty Cycle: 1:1

Medium: MSL\_2450\_130319 Medium parameters used:  $f = 2437$  MHz;  $\sigma = 1.887$  mho/m;  $\epsilon_r = 51.868$ ;  $\rho$

$= 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.1 °C; Liquid Temperature : 21.1 °C

DASY5 Configuration:

- Probe: ES3DV3 - SN3270; ConvF(4.17, 4.17, 4.17); Calibrated: 2012/9/28;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2012/8/27
- Phantom: ELI 4.0\_Front; Type: QDOVA001BB; Serial: 1026
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)

**Configuration/Ch6/Area Scan (71x111x1):** Measurement grid: dx=12mm, dy=12mm  
Maximum value of SAR (interpolated) = 1.51 mW/g


**Configuration/Ch6/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 28.438 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 2.745 mW/g

**SAR(1 g) = 1.1 mW/g; SAR(10 g) = 0.457 mW/g**

Maximum value of SAR (measured) = 1.49 mW/g



0 dB = 1.49 mW/g = 3.46 dB mW/g

### #04\_WLAN 2.4G\_802.11b\_Bottom Face\_0cm\_Ch11;curve30

**DUT: 331535**

Communication System: 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: MSL\_2450\_130319 Medium parameters used:  $f = 2462$  MHz;  $\sigma = 1.92$  mho/m;  $\epsilon_r = 51.791$ ;  $\rho =$

$1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.1 °C; Liquid Temperature : 21.1 °C

DASY5 Configuration:

- Probe: ES3DV3 - SN3270; ConvF(4.17, 4.17, 4.17); Calibrated: 2012/9/28;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2012/8/27
- Phantom: ELI 4.0\_Front; Type: QDOVA001BB; Serial: 1026
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)

**Configuration/Ch11/Area Scan (71x111x1):** Measurement grid: dx=12mm, dy=12mm  
Maximum value of SAR (interpolated) = 1.67 mW/g



**Configuration/Ch11/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 29.621 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 2.960 mW/g

**SAR(1 g) = 1.17 mW/g; SAR(10 g) = 0.489 mW/g**

Maximum value of SAR (measured) = 1.60 mW/g



0 dB = 1.60 mW/g = 4.08 dB mW/g

### #07\_WLAN 2.4G\_802.11b\_Bottom Face\_0cm\_Ch11;curve30\_Repeat

**DUT: 331535**

Communication System: 802.11b; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: MSL\_2450\_130321 Medium parameters used:  $f = 2462$  MHz;  $\sigma = 2.037$  mho/m;  $\epsilon_r = 53.921$ ;  $\rho$

$= 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4°C; Liquid Temperature : 21.4°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3792; ConvF(7.1, 7.1, 7.1); Calibrated: 2012/6/21;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2012/6/12
- Phantom: ELI 4.0\_Front; Type: QDOVA001BB; Serial: 1029
- Measurement SW: DASY52, Version 52.8 (3); SEMCAD X Version 14.6.5 (6469)

**Configuration/Ch11/Area Scan (71x111x1):** Measurement grid: dx=12mm, dy=12mm  
Maximum value of SAR (interpolated) = 1.54 mW/g


**Configuration/Ch11/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 27.047 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 2.804 mW/g

**SAR(1 g) = 1.12 mW/g; SAR(10 g) = 0.435 mW/g**

Maximum value of SAR (measured) = 1.86 mW/g



0 dB = 1.86 mW/g = 5.39 dB mW/g

## #05\_WLAN 2.4G\_802.11b\_Edge1\_0cm\_Ch1

**DUT: 331535**

Communication System: 802.11b; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium: MSL\_2450\_130319 Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.855$  mho/m;  $\epsilon_r = 51.932$ ;  $\rho$

$= 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.1 °C; Liquid Temperature : 21.1 °C

DASY5 Configuration:

- Probe: ES3DV3 - SN3270; ConvF(4.17, 4.17, 4.17); Calibrated: 2012/9/28;
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2012/8/27
- Phantom: ELI 4.0\_Front; Type: QDOVA001BB; Serial: 1026
- Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6477)

**Configuration/Ch1/Area Scan (41x101x1):** Measurement grid: dx=12mm, dy=12mm  
Maximum value of SAR (interpolated) = 0.564 mW/g


**Configuration/Ch1/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 17.094 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.863 mW/g

**SAR(1 g) = 0.402 mW/g; SAR(10 g) = 0.190 mW/g**

Maximum value of SAR (measured) = 0.517 mW/g



### #17\_WLAN 2.4G\_802.11b\_Bottom\_0cm\_Ch1

**DUT: 331535**

Communication System: 802.11b; Frequency: 2412 MHz; Duty Cycle: 1:1

Medium: MSL\_2450\_130321 Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.963$  mho/m;  $\epsilon_r = 54.025$ ;  $\rho$

$= 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4°C; Liquid Temperature : 21.4°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3792; ConvF(7.1, 7.1, 7.1); Calibrated: 2012/6/21;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2012/6/12
- Phantom: ELI 4.0\_Front; Type: QDOVA001BB; Serial: 1029
- Measurement SW: DASY52, Version 52.8 (3); SEMCAD X Version 14.6.5 (6469)

**Configuration/Ch1/Area Scan (71x111x1):** Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (interpolated) = 0.0148 mW/g

**Configuration/Ch1/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.817 V/m; Power Drift = -0.18 dB

Peak SAR (extrapolated) = 0.024 mW/g

**SAR(1 g) = 0.011 mW/g; SAR(10 g) = 0.00742 mW/g**

Maximum value of SAR (measured) = 0.0160 mW/g


**Configuration/Ch1/Zoom Scan (7x7x7)/Cube 1:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.817 V/m; Power Drift = -0.18 dB

Peak SAR (extrapolated) = 0.022 mW/g

**SAR(1 g) = 0.011 mW/g; SAR(10 g) = 0.00698 mW/g**

Maximum value of SAR (measured) = 0.0144 mW/g



0 dB = 0.0144 mW/g = -36.83 dB mW/g

### #08\_WLAN5G\_802.11a\_Bottom Face\_0cm\_Ch48

**DUT: 331535**

Communication System: 802.11a; Frequency: 5240 MHz; Duty Cycle: 1:1

Medium: MSL\_5G\_130321 Medium parameters used :  $f = 5240$  MHz;  $\sigma = 5.285$  mho/m;  $\epsilon_r = 47.411$ ;  $\rho =$

$1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5°C; Liquid Temperature : 21.5°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3792; ConvF(4.2, 4.2, 4.2); Calibrated: 2012/6/21;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2012/6/12
- Phantom: ELI 4.0\_Front; Type: QDOVA001BB; Serial: 1029
- Measurement SW: DASY52, Version 52.8 (3); SEMCAD X Version 14.6.5 (6469)

**Configuration/Ch48/Area Scan (71x141x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 0.775 mW/g


**Configuration/Ch48/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 14.454 V/m; Power Drift = -0.1 dB

Peak SAR (extrapolated) = 1.823 mW/g

**SAR(1 g) = 0.381 mW/g; SAR(10 g) = 0.118 mW/g**

Maximum value of SAR (measured) = 0.833 mW/g



0 dB = 0.833 mW/g = -1.59 dB mW/g

### #09\_WLAN5G\_802.11a\_Bottom Face\_0cm\_Ch48;curve30

**DUT: 331535**

Communication System: 802.11a; Frequency: 5240 MHz; Duty Cycle: 1:1

Medium: MSL\_5G\_130321 Medium parameters used :  $f = 5240$  MHz;  $\sigma = 5.285$  mho/m;  $\epsilon_r = 47.411$ ;  $\rho =$

$1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5°C; Liquid Temperature : 21.5°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3792; ConvF(4.2, 4.2, 4.2); Calibrated: 2012/6/21;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2012/6/12
- Phantom: ELI 4.0\_Front; Type: QDOVA001BB; Serial: 1029
- Measurement SW: DASY52, Version 52.8 (3); SEMCAD X Version 14.6.5 (6469)

**Configuration/Ch48/Area Scan (71x141x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 1.70 mW/g


**Configuration/Ch48/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 20.302 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 2.888 mW/g

**SAR(1 g) = 0.658 mW/g; SAR(10 g) = 0.176 mW/g**

Maximum value of SAR (measured) = 1.62 mW/g



0 dB = 1.62 mW/g = 4.19 dB mW/g

## #11\_WLAN5G\_802.11a\_Edge 1\_0cm\_Ch48

**DUT: 331535**

Communication System: 802.11a; Frequency: 5240 MHz; Duty Cycle: 1:1

Medium: MSL\_5G\_130321 Medium parameters used :  $f = 5240$  MHz;  $\sigma = 5.285$  mho/m;  $\epsilon_r = 47.411$ ;  $\rho =$

$1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5°C; Liquid Temperature : 21.5°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3792; ConvF(4.2, 4.2, 4.2); Calibrated: 2012/6/21;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2012/6/12
- Phantom: ELI 4.0\_Front; Type: QDOVA001BB; Serial: 1029
- Measurement SW: DASY52, Version 52.8 (3); SEMCAD X Version 14.6.5 (6469)

**Configuration/Ch48/Area Scan (51x121x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 0.933 mW/g

**Configuration/Ch48/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 16.128 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 1.730 mW/g

**SAR(1 g) = 0.426 mW/g; SAR(10 g) = 0.113 mW/g**

Maximum value of SAR (measured) = 1.05 mW/g


**Configuration/Ch48/Zoom Scan (7x7x7)/Cube 1:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 16.128 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 1.315 mW/g

**SAR(1 g) = 0.301 mW/g; SAR(10 g) = 0.089 mW/g**

Maximum value of SAR (measured) = 0.779 mW/g



0 dB = 0.779 mW/g = -2.17 dB mW/g

### #18\_WLAN5G\_802.11a\_Bottom\_0cm\_Ch48

**DUT: 331535**

Communication System: 802.11a; Frequency: 5240 MHz; Duty Cycle: 1:1

Medium: MSL\_5G\_130321 Medium parameters used:  $f = 5240$  MHz;  $\sigma = 5.285$  mho/m;  $\epsilon_r = 47.411$ ;  $\rho =$

$1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5°C; Liquid Temperature : 21.5°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3792; ConvF(4.2, 4.2, 4.2); Calibrated: 2012/6/21;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2012/6/12
- Phantom: ELI 4.0\_Front; Type: QDOVA001BB; Serial: 1029
- Measurement SW: DASY52, Version 52.8 (3); SEMCAD X Version 14.6.5 (6469)

**Configuration/Ch48/Area Scan (91x171x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 0.00995 mW/g

**Configuration/Ch48/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 1.342 V/m; Power Drift = -0.184 dB

Peak SAR (extrapolated) = 0.076 mW/g

**SAR(1 g) = 0.00611 mW/g; SAR(10 g) = 0.00305 mW/g**

Maximum value of SAR (measured) = 0.0152 mW/g



**Configuration/Ch48/Zoom Scan (7x7x7)/Cube 1:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 1.342 V/m; Power Drift = -0.184 dB

Peak SAR (extrapolated) = 0.070 mW/g

**SAR(1 g) = 0.0053 mW/g; SAR(10 g) = 0.00346 mW/g**

Maximum value of SAR (measured) = 0.0142 mW/g



0 dB = 0.0142 mW/g = -36.95 dB mW/g

### #23\_WLAN5G\_802.11a\_Bottom Face\_0cm\_Ch60

**DUT: 331535**

Communication System: 802.11a; Frequency: 5300 MHz; Duty Cycle: 1:1

Medium: MSL\_5G\_130321 Medium parameters used:  $f = 5300$  MHz;  $\sigma = 5.393$  mho/m;  $\epsilon_r = 47.275$ ;  $\rho =$

$1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4°C; Liquid Temperature : 21.4°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3792; ConvF(4.01, 4.01, 4.01); Calibrated: 2012/6/21;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2012/6/12
- Phantom: ELI 4.0\_Front; Type: QDOVA001BB; Serial: 1029
- Measurement SW: DASY52, Version 52.8 (3); SEMCAD X Version 14.6.5 (6469)

**Configuration/Ch60/Area Scan (71x141x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 0.633 mW/g


**Configuration/Ch60/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 13.082 V/m; Power Drift = -0.19 dB

Peak SAR (extrapolated) = 1.787 mW/g

**SAR(1 g) = 0.328 mW/g; SAR(10 g) = 0.095 mW/g**

Maximum value of SAR (measured) = 0.759 mW/g



0 dB = 0.759 mW/g = -2.40 dB mW/g

### #24\_WLAN5G\_802.11a\_Bottom Face\_0cm\_Ch60;curve30

**DUT: 331535**

Communication System: 802.11a; Frequency: 5300 MHz; Duty Cycle: 1:1

Medium: MSL\_5G\_130321 Medium parameters used:  $f = 5300$  MHz;  $\sigma = 5.393$  mho/m;  $\epsilon_r = 47.275$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4°C; Liquid Temperature : 21.4°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3792; ConvF(4.01, 4.01, 4.01); Calibrated: 2012/6/21;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2012/6/12
- Phantom: ELI 4.0\_Front; Type: QDOVA001BB; Serial: 1029
- Measurement SW: DASY52, Version 52.8 (3); SEMCAD X Version 14.6.5 (6469)

**Configuration/Ch60/Area Scan (71x141x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 1.74 mW/g


**Configuration/Ch60/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 21.210 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 3.300 mW/g

**SAR(1 g) = 0.737 mW/g; SAR(10 g) = 0.210 mW/g**

Maximum value of SAR (measured) = 1.86 mW/g



## #26\_WLAN5G\_802.11a\_Edge 1\_0cm\_Ch60

**DUT: 331535**

Communication System: 802.11a; Frequency: 5300 MHz; Duty Cycle: 1:1

Medium: MSL\_5G\_130321 Medium parameters used:  $f = 5300$  MHz;  $\sigma = 5.393$  mho/m;  $\epsilon_r = 47.275$ ;  $\rho =$

$1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5°C; Liquid Temperature : 21.5°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3792; ConvF(4.01, 4.01, 4.01); Calibrated: 2012/6/21;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2012/6/12
- Phantom: ELI 4.0\_Front; Type: QDOVA001BB; Serial: 1029
- Measurement SW: DASY52, Version 52.8 (3); SEMCAD X Version 14.6.5 (6469)

**Configuration/Ch60/Area Scan (51x121x1):** Measurement grid: dx=10mm, dy=10mm  
 Maximum value of SAR (interpolated) = 0.844 mW/g

**Configuration/Ch60/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 15.437 V/m; Power Drift = -0.142 dB

Peak SAR (extrapolated) = 1.691 mW/g

**SAR(1 g) = 0.399 mW/g; SAR(10 g) = 0.110 mW/g**

Maximum value of SAR (measured) = 1.01 mW/g


**Configuration/Ch60/Zoom Scan (7x7x7)/Cube 1:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 15.437 V/m; Power Drift = -0.142 dB

Peak SAR (extrapolated) = 1.548 mW/g

**SAR(1 g) = 0.337 mW/g; SAR(10 g) = 0.099 mW/g**

Maximum value of SAR (measured) = 0.863 mW/g



0 dB = 0.863 mW/g = -1.28 dB mW/g

## #28\_WLAN5G\_802.11a\_Bottom\_0cm\_Ch60

**DUT: 331535**

Communication System: 802.11a; Frequency: 5300 MHz; Duty Cycle: 1:1

Medium: MSL\_5G\_130321 Medium parameters used:  $f = 5300$  MHz;  $\sigma = 5.393$  mho/m;  $\epsilon_r = 47.275$ ;  $\rho =$

$1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5°C; Liquid Temperature : 21.5°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3792; ConvF(4.01, 4.01, 4.01); Calibrated: 2012/6/21;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2012/6/12
- Phantom: ELI 4.0\_Front; Type: QDOVA001BB; Serial: 1029
- Measurement SW: DASY52, Version 52.8 (3); SEMCAD X Version 14.6.5 (6469)

**Configuration/Ch60/Area Scan (91x171x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 0.0272 mW/g

**Configuration/Ch60/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 2.157 V/m; Power Drift = -0.134 dB

Peak SAR (extrapolated) = 0.100 mW/g

**SAR(1 g) = 0.00885 mW/g; SAR(10 g) = 0.00314 mW/g**

Maximum value of SAR (measured) = 0.0314 mW/g



**Configuration/Ch60/Zoom Scan (7x7x7)/Cube 1:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 2.157 V/m; Power Drift = -0.134 dB

Peak SAR (extrapolated) = 0.085 mW/g

**SAR(1 g) = 0.00801 mW/g; SAR(10 g) = 0.00303 mW/g**

Maximum value of SAR (measured) = 0.0261 mW/g



0 dB = 0.0314 mW/g = -30.06 dB mW/g

### #29\_WLAN5G\_802.11a\_Bottom Face\_0cm\_Ch140

**DUT: 331535**

Communication System: 802.11a; Frequency: 5700 MHz; Duty Cycle: 1:1

Medium: MSL\_5G\_130324 Medium parameters used:  $f = 5700$  MHz;  $\sigma = 5.81$  mho/m;  $\epsilon_r = 46.685$ ;  $\rho =$

$1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4°C; Liquid Temperature : 21.4°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3792; ConvF(3.72, 3.72, 3.72); Calibrated: 2012/6/21;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2012/6/12
- Phantom: ELI 4.0\_Front; Type: QDOVA001BB; Serial: 1029
- Measurement SW: DASY52, Version 52.8 (3); SEMCAD X Version 14.6.5 (6469)

**Configuration/Ch140/Area Scan (71x141x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 1.33 mW/g


**Configuration/Ch140/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 17.616 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 2.282 mW/g

**SAR(1 g) = 0.491 mW/g; SAR(10 g) = 0.134 mW/g**

Maximum value of SAR (measured) = 1.24 mW/g



0 dB = 1.24 mW/g = 1.87 dB mW/g

### #30\_WLAN5G\_802.11a\_Bottom Face\_0cm\_Ch140;curve30

**DUT: 331535**

Communication System: 802.11a; Frequency: 5700 MHz; Duty Cycle: 1:1

Medium: MSL\_5G\_130324 Medium parameters used:  $f = 5700$  MHz;  $\sigma = 5.81$  mho/m;  $\epsilon_r = 46.685$ ;  $\rho =$

$1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4°C; Liquid Temperature : 21.4°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3792; ConvF(3.72, 3.72, 3.72); Calibrated: 2012/6/21;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2012/6/12
- Phantom: ELI 4.0\_Front; Type: QDOVA001BB; Serial: 1029
- Measurement SW: DASY52, Version 52.8 (3); SEMCAD X Version 14.6.5 (6469)

**Configuration/Ch140/Area Scan (71x141x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 2.64 mW/g


**Configuration/Ch140/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 24.700 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 4.965 mW/g

**SAR(1 g) = 1.01 mW/g; SAR(10 g) = 0.250 mW/g**

Maximum value of SAR (measured) = 2.82 mW/g



0 dB = 2.82 mW/g = 9.00 dB mW/g

### #33\_WLAN5G\_802.11a\_Bottom Face\_0cm\_Ch140;curve30\_Repeat

**DUT: 331535**

Communication System: 802.11a; Frequency: 5700 MHz; Duty Cycle: 1:1

Medium: MSL\_5G\_130324 Medium parameters used:  $f = 5700$  MHz;  $\sigma = 5.81$  mho/m;  $\epsilon_r = 46.685$ ;  $\rho =$

$1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4°C; Liquid Temperature : 21.4°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3792; ConvF(3.72, 3.72, 3.72); Calibrated: 2012/6/21;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2012/6/12
- Phantom: ELI 4.0\_Front; Type: QDOVA001BB; Serial: 1029
- Measurement SW: DASY52, Version 52.8 (3); SEMCAD X Version 14.6.5 (6469)

**Configuration/Ch140/Area Scan (71x141x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 2.59 mW/g


**Configuration/Ch140/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 25.699 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 4.965 mW/g

**SAR(1 g) = 1.00 mW/g; SAR(10 g) = 0.247 mW/g**

Maximum value of SAR (measured) = 2.65 mW/g



0 dB = 2.65 mW/g = 8.46 dB mW/g

### #31\_WLAN5G\_802.11a\_Bottom Face\_0cm\_Ch100;curve30

**DUT: 331535**

Communication System: 802.11a; Frequency: 5500 MHz; Duty Cycle: 1:1

Medium: MSL\_5G\_130324 Medium parameters used:  $f = 5500$  MHz;  $\sigma = 5.506$  mho/m;  $\epsilon_r = 47.018$ ;  $\rho =$

$1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4°C; Liquid Temperature : 21.4°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3792; ConvF(3.81, 3.81, 3.81); Calibrated: 2012/6/21;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2012/6/12
- Phantom: ELI 4.0\_Front; Type: QDOVA001BB; Serial: 1029
- Measurement SW: DASY52, Version 52.8 (3); SEMCAD X Version 14.6.5 (6469)

**Configuration/Ch100/Area Scan (71x141x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 1.96 mW/g


**Configuration/Ch100/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 22.102 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 3.948 mW/g

**SAR(1 g) = 0.778 mW/g; SAR(10 g) = 0.202 mW/g**

Maximum value of SAR (measured) = 2.06 mW/g



0 dB = 2.06 mW/g = 6.28 dB mW/g

### #32\_WLAN5G\_802.11a\_Bottom Face\_0cm\_Ch116;curve30

**DUT: 331535**

Communication System: 802.11a; Frequency: 5580 MHz; Duty Cycle: 1:1

Medium: MSL\_5G\_130324 Medium parameters used:  $f = 5580$  MHz;  $\sigma = 5.618$  mho/m;  $\epsilon_r = 46.854$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4°C; Liquid Temperature : 21.4°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3792; ConvF(3.72, 3.72, 3.72); Calibrated: 2012/6/21;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2012/6/12
- Phantom: ELI 4.0\_Front; Type: QDOVA001BB; Serial: 1029
- Measurement SW: DASY52, Version 52.8 (3); SEMCAD X Version 14.6.5 (6469)

**Configuration/Ch116/Area Scan (71x141x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 2.10 mW/g


**Configuration/Ch116/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 22.588 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 3.629 mW/g

**SAR(1 g) = 0.777 mW/g; SAR(10 g) = 0.185 mW/g**

Maximum value of SAR (measured) = 2.17 mW/g



0 dB = 2.17 mW/g = 6.73 dB mW/g

### #34\_WLAN5G\_802.11a\_Edge 1\_0cm\_Ch140

**DUT: 331535**

Communication System: 802.11a; Frequency: 5700 MHz; Duty Cycle: 1:1

Medium: MSL\_5G\_130324 Medium parameters used:  $f = 5700$  MHz;  $\sigma = 5.81$  mho/m;  $\epsilon_r = 46.685$ ;  $\rho =$

$1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4°C; Liquid Temperature : 21.4°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3792; ConvF(3.72, 3.72, 3.72); Calibrated: 2012/6/21;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2012/6/12
- Phantom: ELI 4.0\_Front; Type: QDOVA001BB; Serial: 1029
- Measurement SW: DASY52, Version 52.8 (3); SEMCAD X Version 14.6.5 (6469)

**Configuration/Ch140/Area Scan (41x141x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 1.02 mW/g

**Configuration/Ch140/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 15.723 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 1.894 mW/g

**SAR(1 g) = 0.402 mW/g; SAR(10 g) = 0.114 mW/g**

Maximum value of SAR (measured) = 1.06 mW/g


**Configuration/Ch140/Zoom Scan (7x7x7)/Cube 1:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 15.723 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 1.876 mW/g

**SAR(1 g) = 0.374 mW/g; SAR(10 g) = 0.122 mW/g**

Maximum value of SAR (measured) = 1.08 mW/g



0 dB = 1.08 mW/g = 0.67 dB mW/g

### #36\_WLAN5G\_802.11a\_Bottom\_0cm\_Ch140

**DUT: 331535**

Communication System: 802.11a; Frequency: 5700 MHz; Duty Cycle: 1:1

Medium: MSL\_5G\_130324 Medium parameters used:  $f = 5700$  MHz;  $\sigma = 5.81$  mho/m;  $\epsilon_r = 46.685$ ;  $\rho =$

$1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4°C; Liquid Temperature : 21.4°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3792; ConvF(3.72, 3.72, 3.72); Calibrated: 2012/6/21;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2012/6/12
- Phantom: ELI 4.0\_Front; Type: QDOVA001BB; Serial: 1029
- Measurement SW: DASY52, Version 52.8 (3); SEMCAD X Version 14.6.5 (6469)

**Configuration/Ch140/Area Scan (91x171x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 0.0357 mW/g


**Configuration/Ch140/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 0.994 V/m; Power Drift = -0.16 dB

Peak SAR (extrapolated) = 0.053 mW/g

**SAR(1 g) = 0.00245 mW/g; SAR(10 g) = 0.000943 mW/g**

Maximum value of SAR (measured) = 0.0306 mW/g



0 dB = 0.0306 mW/g = -30.29 dB mW/g

### #19\_WLAN5G\_802.11a\_Bottom Face\_0cm\_Ch149

**DUT: 331535**

Communication System: 802.11a; Frequency: 5745 MHz; Duty Cycle: 1:1

Medium: MSL\_5G\_130321 Medium parameters used :  $f = 5745$  MHz;  $\sigma = 6.085$  mho/m;  $\epsilon_r = 46.7$ ;  $\rho =$

$1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5°C; Liquid Temperature : 21.5°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3792; ConvF(3.89, 3.89, 3.89); Calibrated: 2012/6/21;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2012/6/12
- Phantom: ELI 4.0\_Front; Type: QDOVA001BB; Serial: 1029
- Measurement SW: DASY52, Version 52.8 (3); SEMCAD X Version 14.6.5 (6469)

**Configuration/Ch149/Area Scan (71x141x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 1.61 mW/g


**Configuration/Ch149/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 19.915 V/m; Power Drift = -0.17 dB

Peak SAR (extrapolated) = 2.648 mW/g

**SAR(1 g) = 0.587 mW/g; SAR(10 g) = 0.170 mW/g**

Maximum value of SAR (measured) = 1.45 mW/g



0 dB = 1.45 mW/g = 3.23 dB mW/g

### #13\_WLAN5G\_802.11a\_Bottom Face\_0cm\_Ch149;curve30

**DUT: 331535**

Communication System: 802.11a; Frequency: 5745 MHz; Duty Cycle: 1:1

Medium: MSL\_5G\_130321 Medium parameters used:  $f = 5745$  MHz;  $\sigma = 6.085$  mho/m;  $\epsilon_r = 46.7$ ;  $\rho =$

$1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5°C; Liquid Temperature : 21.5°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3792; ConvF(3.89, 3.89, 3.89); Calibrated: 2012/6/21;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2012/6/12
- Phantom: ELI 4.0\_Front; Type: QDOVA001BB; Serial: 1029
- Measurement SW: DASY52, Version 52.8 (3); SEMCAD X Version 14.6.5 (6469)

**Configuration/Ch149/Area Scan (71x141x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 2.89 mW/g


**Configuration/Ch149/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 27.773 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 5.743 mW/g

**SAR(1 g) = 1.2 mW/g; SAR(10 g) = 0.287 mW/g**

Maximum value of SAR (measured) = 3.26 mW/g



0 dB = 3.26 mW/g = 10.26 dB mW/g

### #14\_WLAN5G\_802.11a\_Bottom Face\_0cm\_Ch157;curve30

**DUT: 331535**

Communication System: 802.11a; Frequency: 5785 MHz; Duty Cycle: 1:1

Medium: MSL\_5G\_130321 Medium parameters used:  $f = 5785$  MHz;  $\sigma = 6.131$  mho/m;  $\epsilon_r = 46.556$ ;  $\rho =$

$1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5°C; Liquid Temperature : 21.5°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3792; ConvF(3.89, 3.89, 3.89); Calibrated: 2012/6/21;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2012/6/12
- Phantom: ELI 4.0\_Front; Type: QDOVA001BB; Serial: 1029
- Measurement SW: DASY52, Version 52.8 (3); SEMCAD X Version 14.6.5 (6469)

**Configuration/Ch157/Area Scan (71x141x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 3.10 mW/g


**Configuration/Ch157/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 28.436 V/m; Power Drift = -0.16 dB

Peak SAR (extrapolated) = 6.055 mW/g

**SAR(1 g) = 1.22 mW/g; SAR(10 g) = 0.306 mW/g**

Maximum value of SAR (measured) = 3.28 mW/g



### #15\_WLAN5G\_802.11a\_Bottom Face\_0cm\_Ch157;curve30\_Repeat

**DUT: 331535**

Communication System: 802.11a; Frequency: 5785 MHz; Duty Cycle: 1:1

Medium: MSL\_5G\_130321 Medium parameters used:  $f = 5785 \text{ MHz}$ ;  $\sigma = 6.131 \text{ mho/m}$ ;  $\epsilon_r = 46.556$ ;  $\rho =$

$1000 \text{ kg/m}^3$

Ambient Temperature :  $22.5^\circ\text{C}$ ; Liquid Temperature :  $21.5^\circ\text{C}$

DASY5 Configuration:

- Probe: EX3DV4 - SN3792; ConvF(3.89, 3.89, 3.89); Calibrated: 2012/6/21;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2012/6/12
- Phantom: ELI 4.0\_Front; Type: QDOVA001BB; Serial: 1029
- Measurement SW: DASY52, Version 52.8 (3); SEMCAD X Version 14.6.5 (6469)

**Configuration/Ch157/Area Scan (71x141x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$   
 Maximum value of SAR (interpolated) =  $3.00 \text{ mW/g}$


**Configuration/Ch157/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:  $dx=4\text{mm}$ ,  $dy=4\text{mm}$ ,  
 $dz=1.4\text{mm}$

Reference Value =  $28.145 \text{ V/m}$ ; Power Drift =  $0.00 \text{ dB}$

Peak SAR (extrapolated) =  $6.080 \text{ mW/g}$

**SAR(1 g) =  $1.2 \text{ mW/g}$ ; SAR(10 g) =  $0.298 \text{ mW/g}$**

Maximum value of SAR (measured) =  $3.27 \text{ mW/g}$



0 dB =  $3.27 \text{ mW/g} = 10.29 \text{ dB mW/g}$

### #16\_WLAN5G\_802.11a\_Bottom Face\_0cm\_Ch161;curve30

**DUT: 331535**

Communication System: 802.11a; Frequency: 5805 MHz; Duty Cycle: 1:1

Medium: MSL\_5G\_130321 Medium parameters used:  $f = 5805$  MHz;  $\sigma = 6.157$  mho/m;  $\epsilon_r = 46.48$ ;  $\rho =$

$1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5°C; Liquid Temperature : 21.5°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3792; ConvF(3.89, 3.89, 3.89); Calibrated: 2012/6/21;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2012/6/12
- Phantom: ELI 4.0\_Front; Type: QDOVA001BB; Serial: 1029
- Measurement SW: DASY52, Version 52.8 (3); SEMCAD X Version 14.6.5 (6469)

**Configuration/Ch161/Area Scan (71x141x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 3.03 mW/g


**Configuration/Ch161/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 27.975 V/m; Power Drift = -0.00 dB

Peak SAR (extrapolated) = 6.190 mW/g

**SAR(1 g) = 1.19 mW/g; SAR(10 g) = 0.303 mW/g**

Maximum value of SAR (measured) = 3.33 mW/g



0 dB = 3.33 mW/g = 10.45 dB mW/g

## #20\_WLAN5G\_802.11a\_Edge 1\_0cm\_Ch149

**DUT: 331535**

Communication System: 802.11a; Frequency: 5745 MHz; Duty Cycle: 1:1

Medium: MSL\_5G\_130321 Medium parameters used :  $f = 5745$  MHz;  $\sigma = 6.085$  mho/m;  $\epsilon_r = 46.7$ ;  $\rho =$

$1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.5°C; Liquid Temperature : 21.5°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3792; ConvF(3.89, 3.89, 3.89); Calibrated: 2012/6/21;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2012/6/12
- Phantom: ELI 4.0\_Front; Type: QDOVA001BB; Serial: 1029
- Measurement SW: DASY52, Version 52.8 (3); SEMCAD X Version 14.6.5 (6469)

**Configuration/Ch149/Area Scan (31x141x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 0.911 mW/g

**Configuration/Ch149/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 16.641 V/m; Power Drift = -0.18 dB

Peak SAR (extrapolated) = 2.014 mW/g

**SAR(1 g) = 0.440 mW/g; SAR(10 g) = 0.127 mW/g**

Maximum value of SAR (measured) = 1.14 mW/g


**Configuration/Ch149/Zoom Scan (7x7x7)/Cube 1:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 16.641 V/m; Power Drift = -0.18 dB

Peak SAR (extrapolated) = 1.476 mW/g

**SAR(1 g) = 0.308 mW/g; SAR(10 g) = 0.088 mW/g**

Maximum value of SAR (measured) = 0.944 mW/g



0 dB = 0.944 mW/g = -0.50 dB mW/g

## #22\_WLAN5G\_802.11a\_Bottom\_0cm\_Ch149

**DUT: 331535**

Communication System: 802.11a; Frequency: 5745 MHz; Duty Cycle: 1:1

Medium: MSL\_5G\_130321 Medium parameters used:  $f = 5745$  MHz;  $\sigma = 6.085$  mho/m;  $\epsilon_r = 46.7$ ;  $\rho =$

$1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.4°C; Liquid Temperature : 21.4°C

DASY5 Configuration:

- Probe: EX3DV4 - SN3792; ConvF(3.89, 3.89, 3.89); Calibrated: 2012/6/21;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2012/6/12
- Phantom: ELI 4.0\_Front; Type: QDOVA001BB; Serial: 1029
- Measurement SW: DASY52, Version 52.8 (3); SEMCAD X Version 14.6.5 (6469)

**Configuration/Ch149/Area Scan (91x161x1):** Measurement grid: dx=10mm, dy=10mm  
Maximum value of SAR (interpolated) = 0.0367 mW/g

**Configuration/Ch149/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 2.811 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 0.114 mW/g

**SAR(1 g) = 0.015 mW/g; SAR(10 g) = 0.00612 mW/g**

Maximum value of SAR (measured) = 0.0567 mW/g


**Configuration/Ch149/Zoom Scan (7x7x7)/Cube 1:** Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 2.811 V/m; Power Drift = -0.12 dB

Peak SAR (extrapolated) = 0.106 mW/g

**SAR(1 g) = 0.014 mW/g; SAR(10 g) = 0.00526 mW/g**

Maximum value of SAR (measured) = 0.0435 mW/g



0 dB = 0.0435 mW/g = -27.23 dB mW/g