



# FCC RF Test Report

**APPLICANT** : Hewlett-Packard Company  
**EQUIPMENT** : Tablet PC  
**BRAND NAME** : HP  
**MODEL NAME** : HSTNN-I19C  
**FCC ID** : B94HNI19CFX468  
**STANDARD** : FCC 47 CFR Part 2, 22(H), 24(E), 27(L)  
**CLASSIFICATION** : PCS Licensed Transmitter (PCB)

The product was received on Apr. 24, 2014 and testing was completed on Jul. 14, 2014. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-C-2004 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

---

Reviewed by: Joseph Lin / Supervisor

---

Approved by: Jones Tsai / Manager



## **SPORTON INTERNATIONAL INC.**

**No. 52, Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.**



# TABLE OF CONTENTS

**REVISION HISTORY..... 3**

**SUMMARY OF TEST RESULT ..... 4**

**1 GENERAL DESCRIPTION ..... 5**

    1.1 Applicant..... 5

    1.2 Manufacturer ..... 5

    1.3 Product Feature of Equipment Under Test ..... 5

    1.4 Product Specification subjective to this standard ..... 6

    1.5 Modification of EUT ..... 6

    1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator ..... 7

    1.7 Testing Location ..... 7

    1.8 Applicable Standards ..... 8

**2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST ..... 9**

    2.1 Test Mode..... 9

    2.2 Connection Diagram of Test System ..... 11

    2.3 Support Unit used in test configuration ..... 12

    2.4 Measurement Results Explanation Example ..... 12

**3 TEST RESULT ..... 13**

    3.1 Conducted Output Power and ERP/EIRP Measurement ..... 13

    3.2 Peak-to-Average Ratio ..... 16

    3.3 99% Occupied Bandwidth and 26dB Bandwidth Measurement..... 36

    3.4 Band Edge Measurement..... 66

    3.5 Conducted Spurious Emission Measurement ..... 76

    3.6 Field Strength of Spurious Radiation Measurement ..... 100

    3.7 Frequency Stability Measurement..... 111

**4 LIST OF MEASURING EQUIPMENT ..... 117**

**5 UNCERTAINTY OF EVALUATION ..... 118**

**APPENDIX A. SETUP PHOTOGRAPHS**





## SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	§2.1046	RSS-132 (5.4) RSS-133 (6.4) RSS-139 (6.4)	Conducted Output Power	Reporting Only	PASS	-
3.1	§22.913(a)(2)	RSS-132(5.4) SRSP-503(5.1.3)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	RSS-133 (6.4) SRSP-510(5.1.2)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
	§27.50(d)(4)	RSS-139 (6.4) SRSP-513(5.1.2)	Equivalent Isotropic Radiated Power	< 1 Watts	PASS	-
3.2	§24.232(d)	RSS-132 (5.4) RSS-133 (6.4) RSS-139 (6.4)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.3	§2.1049 §22.917(b) §24.238(b) §27.53(h)(3)	RSS-GEN(4.6.1) RSS-133(6.5) RSS-139 (6.5)	Occupied Bandwidth	Reporting Only	PASS	-
3.4	§2.1051 §22.917(a) §24.238(a) §27.53(h)	RSS-GEN(4.9) RSS-132 (5.5) RSS-133 (6.5) RSS-139 (6.5)	Band Edge Measurement	< 43+10log <sub>10</sub> (P[Watts])	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a) §27.53(h)	RSS-GEN(4.9) RSS-132 (5.5) RSS-133 (6.5) RSS-139 (6.5)	Conducted Emission	< 43+10log <sub>10</sub> (P[Watts])	PASS	-
3.6	§2.1053 §22.917(a) §24.238(a) §27.53(h)	RSS-GEN(4.9) RSS-132 (5.5) RSS-133 (6.5) RSS-139 (6.5)	Field Strength of Spurious Radiation	< 43+10log <sub>10</sub> (P[Watts])	PASS	Under limit 17.01 dB at 11278.000 MHz
3.7	§2.1055 §22.355 §24.235 §27.54	RSS-GEN(4.7) RSS-132 (5.3) RSS-133 (6.3) RSS-139 (6.3)	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-



# 1 General Description

## 1.1 Applicant

Hewlett-Packard Company  
3000 Hanover Street, Palo Alto, California 94304, USA

## 1.2 Manufacturer

Inventec Corporation  
Inventec Building, No. 66 Hou-Kang Street Shilin District, Taipei 11170, Taiwan

## 1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Tablet PC
Brand Name	HP
Model Name	HSTNN-I19C
FCC ID	B94HNI19CFX468
EUT supports Radios application	CDMA/EV-DO/GSM/EGPRS/WCDMA/HSPA/LTE
EUT Stage	Identical Prototype

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



### 1.4 Product Specification subjective to this standard

Product Specification subjective to this standard	
<b>Tx Frequency</b>	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band IV : 1712.4 MHz ~ 1752.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz CDMA2000 BC0: 824.70 MHz ~ 848.31 MHz CDMA2000 BC1: 1851.25 MHz ~ 1908.75 MHz
<b>Rx Frequency</b>	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band IV : 2112.4 MHz ~ 2152.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz CDMA2000 BC0: 869.70 MHz ~ 893.31 MHz CDMA2000 BC1: 1931.25 MHz ~ 1988.75 MHz
<b>Maximum Output Power to Antenna</b>	GSM850 : 32.92 dBm GSM1900 : 29.50 dBm WCDMA Band V : 22.53 dBm WCDMA Band IV : 22.72 dBm WCDMA Band II : 22.73 dBm CDMA2000 BC0 : 23.82 dBm CDMA2000 BC1 : 24.27 dBm
<b>Antenna Type</b>	PIFA Antenna
<b>Antenna Gain</b>	Cellular Band : -3.60 dBi PCS Band : -0.59 dBi AWS Band : -1.33 dBi
<b>Type of Modulation</b>	GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: QPSK (Uplink) HSDPA: QPSK (Downlink) HSUPA: QPSK (Uplink) CDMA2000 : QPSK CDMA2000 1xEV-DO : QPSK/8PSK

### 1.5 Modification of EUT

No modifications are made to the EUT during all test items.



### 1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22	GSM850 GPRS class 8	GMSK	0.52	0.0084 ppm	246KGXW
Part 22	GSM850 EDGE class 8	8PSK	0.15	0.0096 ppm	246KG7W
Part 22	WCDMA Band V RMC 12.2Kbps	QPSK	0.05	0.0143 ppm	4M20F9W
Part 22	CDMA2000 BC0 1xRTT	QPSK	0.06	0.0108 ppm	1M28F9W
Part 24	GSM1900 GPRS class 8	GMSK	0.78	0.0165 ppm	248KGXW
Part 24	GSM1900 EDGE class 8	8PSK	0.39	0.0043 ppm	248KG7W
Part 24	WCDMA Band II RMC 12.2Kbps	QPSK	0.16	0.0021 ppm	4M18F9W
Part 24	CDMA2000 BC1 1xRTT	QPSK	0.23	0.0048 ppm	1M28F9W
Part 27	WCDMA Band IV RMC 12.2Kbps	QPSK	0.14	0.0035 ppm	4M18F9W

### 1.7 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

<b>Test Site</b>	SPORTON INTERNATIONAL INC.	
<b>Test Site Location</b>	No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	TH02-HY	03CH07-HY



## 1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 22(H), 24(E), 27(L)
- ♦ ANSI / TIA / EIA-603-C-2004
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v02r01
- ♦ FCC KDB 412172 D01 Determining ERP and ERIP v01

**Remark:** All test items were verified and recorded according to the standards and without any deviation during the test.

## 2 Test Configuration of Equipment Under Test

### 2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r01 with maximum output power, and EUT is rotated on three test planes in Tablet PC configurations and one test plane in Tablet PC (with Keyboard) configuration to find out the worst emission.

Radiated emissions were investigated as following frequency range:

1. 30 MHz to 9000 MHz for GSM850, WCDMA Band V, and CDMA2000 BC0.
2. 30 MHz to 18000 MHz for WCDMA Band IV.
3. 30 MHz to 19000 MHz for GSM1900, WCDMA Band II, and CDMA2000 BC1.

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	<ul style="list-style-type: none"> <li>■ GPRS class 8 Link</li> <li>■ EDGE class 8 Link</li> </ul>	<ul style="list-style-type: none"> <li>■ GPRS class 8 Link</li> <li>■ EDGE class 8 Link</li> </ul>
GSM 1900	<ul style="list-style-type: none"> <li>■ GPRS class 8 Link</li> <li>■ EDGE class 8 Link</li> </ul>	<ul style="list-style-type: none"> <li>■ GPRS class 8 Link</li> <li>■ EDGE class 8 Link</li> </ul>
WCDMA Band V	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>
WCDMA Band IV	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>
WCDMA Band II	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>
CDMA2000 BC0	<ul style="list-style-type: none"> <li>■ 1xRTT Link</li> </ul>	<ul style="list-style-type: none"> <li>■ 1xRTT Link</li> </ul>
CDMA2000 BC1	<ul style="list-style-type: none"> <li>■ 1xRTT Link</li> </ul>	<ul style="list-style-type: none"> <li>■ 1xRTT Link</li> </ul>

**Note:** The maximum power levels are chosen to test as the worst case configuration as follows:

GPRS multi-slot class 8 mode for GMSK modulation,

EDGE multi-slot class 8 mode for 8PSK modulation,

RMC 12.2Kbps mode for WCDMA band V, WCDMA band IV, and WCDMA band II,

1xRTT mode for CDMA2000 BC0 and CDMA2000 BC1, only these modes were used for all tests.



Conducted Power Measurement Results:


Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GPRS class 8	32.78	32.92	32.89	29.50	29.18	29.36
GPRS class 10	31.64	31.65	31.52	28.95	28.92	28.90
GPRS class 11	29.00	29.04	29.02	26.95	27.02	26.95
GPRS class 12	28.13	28.14	28.08	24.84	24.88	24.81
EGPRS class 8	27.33	27.41	27.32	26.49	26.30	26.28
EGPRS class 10	26.51	26.52	26.41	25.50	25.30	25.27
EGPRS class 11	26.26	26.28	26.25	25.44	25.30	25.21
EGPRS class 12	24.01	23.97	23.87	23.37	23.28	23.16

Conducted Power (*Unit: dBm)									
Band	WCDMA Band V			WCDMA Band II			WCDMA Band IV		
Channel	4132	4182	4233	9262	9400	9538	1312	1413	1513
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6	1712.4	1732.6	1752.6
RMC 12.2K	22.53	22.51	22.50	22.57	22.73	22.64	22.72	22.53	22.52
HSDPA Subtest-1	21.57	21.47	21.28	21.68	21.90	21.76	22.01	21.66	21.76
HSDPA Subtest-2	21.49	21.44	21.21	21.62	21.84	21.74	21.93	21.62	21.69
HSDPA Subtest-3	21.06	20.92	20.78	21.22	21.40	21.30	21.56	21.14	21.25
HSDPA Subtest-4	21.01	20.88	20.75	21.18	21.33	21.28	21.52	21.09	21.15
HSUPA Subtest-1	21.45	21.30	21.25	21.49	21.88	21.62	21.89	21.65	21.49
HSUPA Subtest-2	20.68	20.54	20.53	21.30	21.49	21.47	21.38	21.10	21.01
HSUPA Subtest-3	19.88	19.77	19.64	20.10	20.25	20.22	20.48	20.15	20.30
HSUPA Subtest-4	19.78	19.62	19.35	19.38	19.80	19.58	20.84	20.66	20.48
HSUPA Subtest-5	21.52	21.45	21.15	21.77	21.93	21.85	21.99	21.71	21.86


Conducted Power (*Unit: dBm)						
Band	CDMA2000 BC0			CDMA2000 BC1		
Channel	1013	384	777	25	600	1175
Frequency	824.7	836.52	848.31	1851.25	1880	1908.75
1xRTT RC1 SO55	23.51	23.77	23.64	24.22	24.22	24.09
1xRTT RC3 SO55	23.54	23.82	23.60	24.18	24.27	24.08
1xEV-DO RTAP 153.6kbps	23.60	23.80	23.66	24.22	24.26	24.11
1xEV-DO RETAP 4096Bits	23.64	23.76	23.80	24.21	24.26	24.00

## 2.2 Connection Diagram of Test System


### <EUT with Adapter for Cellular Band>



### <EUT with Keyboard for PCS Band>



<EUT Standalone for AWS Band>



### 2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	iPod Earphone	Apple	N/A	Verification	Unshielded, 1.0 m	N/A

### 2.4 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

The following shows an offset computation example with RF cable loss 4.2 dB and a 10dB attenuator.

Example :

$$\begin{aligned}
 \text{Offset}(dB) &= \text{RF cable loss}(dB) + \text{attenuator factor}(dB). \\
 &= 4.2 + 10 = 14.2 \text{ (dB)}
 \end{aligned}$$

### 3 Test Result

#### 3.1 Conducted Output Power and ERP/EIRP Measurement

##### 3.1.1 Description of the Conducted Output Power and ERP/EIRP Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for Cellular Band.

The EIRP of mobile transmitters must not exceed 2 Watts for PCS Band.

The EIRP of mobile transmitters must not exceed 1 Watts for AWS Band.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$ ,  $ERP = EIRP - 2.15$ , where

$P_T$  = transmitter output power in dBm

$G_T$  = gain of the transmitting antenna in dBi

$L_C$  = signal attenuation in the connecting cable between the transmitter and antenna in dB


##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

##### 3.1.4 Test Setup





3.1.5 Test Result of Conducted Output Power

Cellular Band ( $G_T - L_C = -3.60$ dB)									
Modes	GSM850 (GPRS class 8)			GSM850 (EDGE class 8)			WCDMA Band V (RMC 12.2Kbps)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8	826.4	836.4	846.6
Conducted Power (dBm)	32.78	32.92	32.89	27.33	27.41	27.32	22.53	22.51	22.50
Conducted Power (Watts)	1.90	1.96	1.95	0.54	0.55	0.54	0.18	0.18	0.18
ERP(dBm)	27.03	27.17	27.14	21.58	21.66	21.57	16.78	16.76	16.75
ERP(Watts)	0.51	0.52	0.52	0.14	0.15	0.14	0.05	0.05	0.05

PCS Band ( $G_T - L_C = -0.59$ dB)									
Modes	GSM1900 (GPRS class 8)			GSM1900 (EDGE class 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Conducted Power (dBm)	29.50	29.18	29.36	26.49	26.30	26.28	22.57	22.73	22.64
Conducted Power (Watts)	0.89	0.83	0.86	0.45	0.43	0.42	0.18	0.19	0.18
EIRP(dBm)	28.91	28.59	28.77	25.90	25.71	25.69	21.98	22.14	22.05
EIRP(Watts)	0.78	0.72	0.75	0.39	0.37	0.37	0.16	0.16	0.16



AWS Band ( $G_T - L_C = -1.33$ dB)			
Modes	WCDMA Band IV (RMC 12.2Kbps)		
Channel	1312(Low)	1413 (Mid)	1513 (High)
Frequency (MHz)	1712.4	1732.6	1752.6
Conducted Power (dBm)	22.72	22.53	22.52
Conducted Power (Watts)	0.19	0.18	0.18
EIRP (dBm)	21.39	21.20	21.19
EIRP (Watts)	0.14	0.13	0.13

Cellular Band ( $G_T - L_C = -3.60$ dB)			
Modes	CDMA 2000 BC0 1xRTT		
Test Status	RC3+SO55		
Channel	1013 (Low)	384 (Mid)	777 (High)
Frequency (MHz)	824.70	836.52	848.31
Conducted Power (dBm)	23.54	23.82	23.60
Conducted Power (Watts)	0.23	0.24	0.23
ERP(dBm)	17.79	18.07	17.85
ERP(Watts)	0.06	0.06	0.06

PCS Band ( $G_T - L_C = -0.59$ dB)			
Modes	CDMA 2000 BC1 1xRTT		
Test Status	RC3+SO55		
Channel	25 (Low)	600 (Mid)	1175 (High)
Frequency (MHz)	1851.25	1880.00	1908.75
Conducted Power (dBm)	24.18	24.27	24.08
Conducted Power (Watts)	0.26	0.27	0.26
EIRP(dBm)	23.59	23.68	23.49
EIRP(Watts)	0.23	0.23	0.22

**Note:**

Maximum burst average power for GPRS, and maximum average power for WCDMA and CDMA2000.

$EIRP = P_T + G_T - L_C$ ,  $ERP = EIRP - 2.15$ , where

$P_T$  = transmitter output power in dBm

$G_T$  = gain of the transmitting antenna in dBi

$L_C$  = signal attenuation in the connecting cable between the transmitter and antenna in dB

## 3.2 Peak-to-Average Ratio

### 3.2.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.


### 3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.2.3 Test Procedures

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. Set EUT to transmit at maximum output power.
3. When the duty cycle is less than 98%, then signal gating will be implemented on the spectrum analyzer by triggering from the system simulator.
4. Set the CCDF (Complementary Cumulative Distribution Function) option of the spectrum analyzer.
5. Record the maximum PAPR level associated with a probability of 0.1%.

### 3.2.4 Test Setup





### 3.2.5 Test Result of Peak-to-Average Ratio

Cellular Band									
Modes	GSM850 (GPRS class 8)			GSM850 (EDGE class 8)			WCDMA Band V (RMC 12.2Kbps)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8	826.4	836.4	846.6
Peak-to-Average Ratio (dB)	0.24	0.20	0.24	3.12	3.04	3.08	2.84	3.04	3.04

PCS Band									
Modes	GSM1900 (GPRS class 8)			GSM1900 (EDGE class 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Peak-to-Average Ratio (dB)	0.24	0.24	0.24	2.96	3.08	2.84	3.36	3.12	2.88

AWS Band			
Modes	WCDMA Band IV (RMC 12.2Kbps)		
Channel	1312(Low)	1413 (Mid)	1513 (High)
Frequency (MHz)	1712.4	1732.6	1752.6
Peak-to-Average Ratio (dB)	3.24	2.68	3.12

Cellular Band			
Modes	CDMA 2000 BC0 1xRTT		
Test Status	RC3+SO55		
Channel	1013 (Low)	384 (Mid)	777 (High)
Frequency (MHz)	824.70	836.52	848.31
Peak-to-Average Ratio (dB)	3.64	4.16	4.12


PCS Band			
Modes	CDMA 2000 BC0 1xRTT		
Test Status	RC3+SO55		
Channel	25 (Low)	600 (Mid)	1175 (High)
Frequency (MHz)	1851.25	1880	1908.75
Peak-to-Average Ratio (dB)	4.32	4.20	3.40



### 3.2.6 Test Result (Plots) of Peak-to-Average Ratio


Band :	GSM 850	Test Mode :	GPRS class 8 Link (GMSK)
--------	---------	-------------	--------------------------

#### Peak-to-Average Ratio on Channel 128 (824.2 MHz)



Date: 1.JUL.2014 16:34:50


#### Peak-to-Average Ratio on Channel 189 (836.4 MHz)



Date: 1.JUL.2014 16:35:33



Peak-to-Average Ratio on Channel 251 (848.8 MHz)



Complementary Cumulative Distribution Function (100000 samples)

Trace 1  
 Mean 32.08 dBm  
 Peak 32.29 dBm  
 Crest 0.21 dB


10 %	0.16 dB
1 %	0.24 dB
.1 %	0.24 dB
.01 %	0.24 dB

Date: 1.JUL.2014 16:36:03



<b>Band :</b>	GSM 850	<b>Test Mode :</b>	EDGE class 8 Link (8PSK)
---------------	---------	--------------------	--------------------------

**Peak-to-Average Ratio on Channel 128 (824.2 MHz)**




Complementary Cumulative Distribution Function (100000 samples)

Trace 1  
Mean 25.94 dBm  
Peak 29.11 dBm  
Crest 3.18 dB

10 %	2.56 dB
1 %	3.04 dB
.1 %	3.12 dB
.01 %	3.20 dB

Date: 1.JUL.2014 17:24:14

**Peak-to-Average Ratio on Channel 189 (836.4 MHz)**



Complementary Cumulative Distribution Function (100000 samples)


Trace 1  
Mean 26.08 dBm  
Peak 29.18 dBm  
Crest 3.10 dB

10 %	2.48 dB
1 %	2.96 dB
.1 %	3.04 dB
.01 %	3.12 dB

Date: 1.JUL.2014 17:26:08



Peak-to-Average Ratio on Channel 251 (848.8 MHz)



Complementary Cumulative Distribution Function (100000 samples)

Trace 1

Mean 26.05 dBm  
 Peak 29.18 dBm  
 Crest 3.14 dB


10 % 2.60 dB  
 1 % 3.00 dB  
 .1 % 3.08 dB  
 .01 % 3.16 dB

Date: 1.JUL.2014 17:27:10




<b>Band :</b>	GSM 1900	<b>Test Mode :</b>	GPRS class 8 Link (GMSK)
---------------	----------	--------------------	--------------------------

**Peak-to-Average Ratio on Channel 512 (1850.2 MHz)**



Date: 1.JUL.2014 19:09:30


**Peak-to-Average Ratio on Channel 661 (1880.0 MHz)**



Date: 1.JUL.2014 19:09:57



Peak-to-Average Ratio on Channel 810 (1909.8 MHz)



Complementary Cumulative Distribution Function (100000 samples)

Trace 1

Mean 29.25 dBm  
 Peak 29.47 dBm  
 Crest 0.22 dB


10 % 0.16 dB  
 1 % 0.24 dB  
 .1 % 0.24 dB  
 .01 % 0.24 dB

Date: 1.JUL.2014 19:11:39



<b>Band :</b>	GSM 1900	<b>Test Mode :</b>	EDGE class 8 Link (8PSK)
---------------	----------	--------------------	--------------------------

**Peak-to-Average Ratio on Channel 512 (1850.2 MHz)**




Complementary Cumulative Distribution Function (100000 samples)

Trace 1  
Mean 25.21 dBm  
Peak 28.20 dBm  
Crest 2.99 dB

10 % 2.56 dB  
1 % 2.88 dB  
.1 % 2.96 dB  
.01 % 3.00 dB

Date: 1.JUL.2014 20:00:07

**Peak-to-Average Ratio on Channel 661 (1880.0 MHz)**



Complementary Cumulative Distribution Function (100000 samples)


Trace 1  
Mean 25.58 dBm  
Peak 28.76 dBm  
Crest 3.18 dB

10 % 2.64 dB  
1 % 3.00 dB  
.1 % 3.08 dB  
.01 % 3.12 dB

Date: 1.JUL.2014 20:01:06



Peak-to-Average Ratio on Channel 810 (1909.8 MHz)



Complementary Cumulative Distribution Function (100000 samples)

Trace 1  
 Mean 25.37 dBm  
 Peak 28.27 dBm  
 Crest 2.90 dB


10 % 2.40 dB  
 1 % 2.76 dB  
 .1 % 2.84 dB  
 .01 % 2.88 dB

Date: 1.JUL.2014 20:01:57



<b>Band :</b>	WCDMA Band V	<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)
---------------	--------------	--------------------	--------------------------

**Peak-to-Average Ratio on Channel 4132 (826.4 MHz)**




Complementary Cumulative Distribution Function (100000 samples)

Trace 1  
Mean 23.45 dBm  
Peak 26.57 dBm  
Crest 3.12 dB

10 %	1.68 dB
1 %	2.44 dB
.1 %	2.84 dB
.01 %	3.00 dB

Date: 2.JUL.2014 09:54:21

**Peak-to-Average Ratio on Channel 4182 (836.4 MHz)**



Complementary Cumulative Distribution Function (100000 samples)


Trace 1  
Mean 23.09 dBm  
Peak 26.50 dBm  
Crest 3.41 dB

10 %	1.72 dB
1 %	2.60 dB
.1 %	3.04 dB
.01 %	3.24 dB

Date: 2.JUL.2014 09:54:48



Peak-to-Average Ratio on Channel 4233 (846.6 MHz)



Complementary Cumulative Distribution Function (100000 samples)

Trace 1

Mean 23.07 dBm  
 Peak 26.50 dBm  
 Crest 3.43 dB


10 % 1.72 dB  
 1 % 2.56 dB  
 .1 % 3.04 dB  
 .01 % 3.24 dB

Date: 2.JUL.2014 09:55:26



<b>Band :</b>	WCDMA Band IV	<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)
---------------	---------------	--------------------	--------------------------

**Peak-to-Average Ratio on Channel 1312 (1712.4 MHz)**




Complementary Cumulative Distribution Function (100000 samples)  
 Trace 1  
 Mean 23.80 dBm  
 Peak 27.49 dBm  
 Crest 3.69 dB

10 %	1.84 dB
1 %	2.76 dB
.1 %	3.24 dB
.01 %	3.48 dB

Date: 2.JUL.2014 09:18:54

**Peak-to-Average Ratio on Channel 1413 (1732.6 MHz)**




Complementary Cumulative Distribution Function (100000 samples)  
 Trace 1  
 Mean 23.43 dBm  
 Peak 26.36 dBm  
 Crest 2.93 dB

10 %	1.68 dB
1 %	2.36 dB
.1 %	2.68 dB
.01 %	2.80 dB

Date: 2.JUL.2014 09:19:38



Peak-to-Average Ratio on Channel 1513 (1752.6 MHz)



Complementary Cumulative Distribution Function (100000 samples)

Trace 1


Mean	23.18 dBm
Peak	26.64 dBm
Crest	3.47 dB
10 %	1.80 dB
1 %	2.64 dB
.1 %	3.12 dB
.01 %	3.32 dB

Date: 2.JUL.2014 09:20:35



<b>Band :</b>	WCDMA Band II	<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)
---------------	---------------	--------------------	--------------------------

**Peak-to-Average Ratio on Channel 9262 (1852.4 MHz)**




Complementary Cumulative Distribution Function (100000 samples)

Trace 1  
Mean 22.41 dBm  
Peak 26.22 dBm  
Crest 3.81 dB

10 %	1.84 dB
1 %	2.80 dB
.1 %	3.36 dB
.01 %	3.64 dB

Date: 1.JUL.2014 21:10:47

**Peak-to-Average Ratio on Channel 9400 (1880.0 MHz)**



Complementary Cumulative Distribution Function (100000 samples)


Trace 1  
Mean 23.38 dBm  
Peak 26.93 dBm  
Crest 3.55 dB

10 %	1.72 dB
1 %	2.60 dB
.1 %	3.12 dB
.01 %	3.40 dB

Date: 1.JUL.2014 21:11:48



Peak-to-Average Ratio on Channel 9538 (1907.6 MHz)



Complementary Cumulative Distribution Function (100000 samples)

Trace 1


Mean	23.08 dBm
Peak	26.36 dBm
Crest	3.28 dB
10 %	1.72 dB
1 %	2.52 dB
.1 %	2.88 dB
.01 %	3.08 dB

Date: 1.JUL.2014 21:12:43



<b>Band :</b>	CDMA2000 BC0	<b>Test Mode :</b>	1xRTT_RC3+SO55 (QPSK)
---------------	--------------	--------------------	-----------------------

Peak-to-Average Ratio on Channel 1013 (824.70 MHz)




Complementary Cumulative Distribution Function (100000 samples)

Trace 1

Mean	23.55 dBm
Peak	27.35 dBm
Crest	3.80 dB
10 %	2.48 dB
1 %	3.36 dB
.1 %	3.64 dB
.01 %	3.76 dB

Date: 3.JUL.2014 09:02:41

Peak-to-Average Ratio on Channel 384 (836.52 MHz)



Complementary Cumulative Distribution Function (100000 samples)


Trace 1

Mean	23.40 dBm
Peak	27.84 dBm
Crest	4.44 dB
10 %	2.52 dB
1 %	3.72 dB
.1 %	4.16 dB
.01 %	4.32 dB

Date: 3.JUL.2014 09:05:26



Peak-to-Average Ratio on Channel 777 (848.31 MHz)



Complementary Cumulative Distribution Function (100000 samples)

Trace 1


Mean	23.64 dBm
Peak	28.06 dBm
Crest	4.42 dB
10 %	2.56 dB
1 %	3.76 dB
.1 %	4.12 dB
.01 %	4.28 dB

Date: 3.JUL.2014 09:05:53



<b>Band :</b>	CDMA2000 BC1	<b>Test Mode :</b>	1xRTT_RC3+SO55 (QPSK)
---------------	--------------	--------------------	-----------------------

Peak-to-Average Ratio on Channel 25 (1851.25 MHz)




Complementary Cumulative Distribution Function (100000 samples)

Trace 1

Mean	22.60 dBm
Peak	27.28 dBm
Crest	4.68 dB
10 %	2.60 dB
1 %	3.88 dB
.1 %	4.32 dB
.01 %	4.52 dB

Date: 3.JUL.2014 10:15:18

Peak-to-Average Ratio on Channel 600 (1880 MHz)



Complementary Cumulative Distribution Function (100000 samples)


Trace 1

Mean	23.63 dBm
Peak	28.27 dBm
Crest	4.64 dB
10 %	2.52 dB
1 %	3.76 dB
.1 %	4.20 dB
.01 %	4.44 dB

Date: 3.JUL.2014 10:16:35



Peak-to-Average Ratio on Channel 1175 (1908.75 MHz)



Complementary Cumulative Distribution Function (100000 samples)

Trace 1	
Mean	23.29 dBm
Peak	26.86 dBm
Crest	3.56 dB
10 %	2.44 dB
1 %	3.24 dB
.1 %	3.40 dB
.01 %	3.48 dB

Date: 3.JUL.2014 10:17:09

### 3.3 99% Occupied Bandwidth and 26dB Bandwidth Measurement

#### 3.3.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


#### 3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.3.3 Test Procedures

1. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
2. The RF output of the EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The 99% occupied bandwidth were measured, set RBW= 1% of span, VBW= 3\*RBW, sample detector, trace maximum hold.
4. The 26dB bandwidth were measured, set RBW= 1% of EBW, VBW= 3\*RBW, peak detector, trace maximum hold.

#### 3.3.4 Test Setup





3.3.5 Test Result of Occupied Bandwidth and 26dB Bandwidth

Cellular Band						
Modes	GSM850 (GPRS class 8)			GSM850 (EDGE class 8)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8
99% OBW (kHz)	246.00	244.00	244.00	242.00	246.00	240.00
26dB BW (kHz)	318.00	314.00	310.00	304.00	308.00	314.00

PCS Band						
Modes	GSM1900 (GPRS class 8)			GSM1900 (EDGE class 8)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8
99% OBW (kHz)	244.00	248.00	246.00	244.00	248.00	248.00
26dB BW (kHz)	310.00	310.00	306.00	298.00	310.00	302.00

Cellular Band			
Modes	WCDMA Band V (RMC 12.2Kbps)		
Channel	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	826.4	836.4	846.6
99% OBW (MHz)	4.18	4.18	4.20
26dB BW (MHz)	4.66	4.66	4.68

AWS Band			
Modes	WCDMA Band IV (RMC 12.2Kbps)		
Channel	1312(Low)	1413 (Mid)	1513 (High)
Frequency (MHz)	1712.4	1732.6	1752.6
99% OBW (MHz)	4.16	4.18	4.18
26dB BW (MHz)	4.68	4.68	4.68



PCS Band			
Modes	WCDMA Band II (RMC 12.2Kbps)		
Channel	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1852.4	1880	1907.6
99% OBW (MHz)	4.18	4.18	4.14
26dB BW (MHz)	4.68	4.68	4.68

Cellular Band			
Test Mode	CDMA 2000 BC0 1xRTT		
Test Status	RC3+SO55		
Channel	1013 (Low)	384 (Mid)	777 (High)
Frequency (MHz)	824.70	836.52	848.31
99% OBW (MHz)	1.28	1.27	1.28
26dB BW (MHz)	1.42	1.41	1.42


PCS Band			
Test Mode	CDMA 2000 BC1 1xRTT		
Test Status	RC3+SO55		
Channel	25 (Low)	600 (Mid)	1175 (High)
Frequency (MHz)	1851.25	1880.00	1908.75
99% OBW (MHz)	1.28	1.28	1.28
26dB BW (MHz)	1.41	1.42	1.42



### 3.3.6 Test Result (Plots) of Occupied Bandwidth and 26dB Bandwidth


Band :	GSM 850	Test Mode :	GPRS class 8 Link (GMSK)
--------	---------	-------------	--------------------------

#### 99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 1.JUL.2014 16:53:27


#### 26dB Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 1.JUL.2014 16:50:31




99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 1.JUL.2014 16:54:04


26dB Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 1.JUL.2014 16:51:08




99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 1.JUL.2014 16:54:48

26dB Bandwidth Plot on Channel 251 (848.8 MHz)




Date: 1.JUL.2014 16:51:49




<b>Band :</b>	GSM 850	<b>Test Mode :</b>	EDGE class 8 Link (8PSK)
---------------	---------	--------------------	--------------------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 1.JUL.2014 18:09:07


26dB Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 1.JUL.2014 17:59:54




99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 1.JUL.2014 18:09:45


26dB Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 1.JUL.2014 18:00:30




99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 1.JUL.2014 18:10:24

26dB Bandwidth Plot on Channel 251 (848.8 MHz)




Date: 1.JUL.2014 18:01:06




<b>Band :</b>	GSM 1900	<b>Test Mode :</b>	GPRS class 8 Link (GMSK)
---------------	----------	--------------------	--------------------------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 1.JUL.2014 20:49:05


26dB Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 1.JUL.2014 20:46:33




99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 1.JUL.2014 20:49:40


26dB Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 1.JUL.2014 20:47:12




### 99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 1.JUL.2014 20:50:16

### 26dB Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 1.JUL.2014 20:47:47




<b>Band :</b>	GSM 1900	<b>Test Mode :</b>	EDGE class 8 Link (8PSK)
---------------	----------	--------------------	--------------------------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 1.JUL.2014 20:21:02


26dB Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 1.JUL.2014 20:18:26




99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 1.JUL.2014 20:21:43


26dB Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 1.JUL.2014 20:19:01




99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 1.JUL.2014 20:22:25

26dB Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 1.JUL.2014 20:19:41




Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	--------------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 4132 (826.4 MHz)



Date: 2.JUL.2014 10:26:02


26dB Bandwidth Plot on Channel 4132 (826.4 MHz)



Date: 2.JUL.2014 10:19:57




99% Occupied Bandwidth Plot on Channel 4182 (836.4 MHz)



Date: 2.JUL.2014 10:26:30


26dB Bandwidth Plot on Channel 4182 (836.4 MHz)



Date: 2.JUL.2014 10:19:25




99% Occupied Bandwidth Plot on Channel 4233 (846.6 MHz)



Date: 2.JUL.2014 10:26:59

26dB Bandwidth Plot on Channel 4233 (846.6 MHz)




Date: 2.JUL.2014 10:18:49




<b>Band :</b>	WCDMA Band IV	<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)
---------------	---------------	--------------------	--------------------------

99% Occupied Bandwidth Plot on Channel 1312 (1712.4 MHz)



Date: 2.JUL.2014 09:36:32


26dB Bandwidth Plot on Channel 1312 (1712.4 MHz)



Date: 2.JUL.2014 09:30:16




99% Occupied Bandwidth Plot on Channel 1413 (1732.6 MHz)



Date: 2.JUL.2014 09:37:00


26dB Bandwidth Plot on Channel 1413 (1732.6 MHz)



Date: 2.JUL.2014 09:34:38




### 99% Occupied Bandwidth Plot on Channel 1513 (1752.6 MHz)



Date: 2.JUL.2014 09:37:29

### 26dB Bandwidth Plot on Channel 1513 (1752.6 MHz)




Date: 2.JUL.2014 09:31:13




Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
--------	---------------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 9262 (1852.4 MHz)



Date: 1.JUL.2014 21:37:34


26dB Bandwidth Plot on Channel 9262 (1852.4 MHz)



Date: 1.JUL.2014 21:32:00




99% Occupied Bandwidth Plot on Channel 9400 (1880.0 MHz)



Date: 1.JUL.2014 21:38:02


26dB Bandwidth Plot on Channel 9400 (1880.0 MHz)



Date: 1.JUL.2014 21:32:28




99% Occupied Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 1.JUL.2014 21:38:31

26dB Bandwidth Plot on Channel 9538 (1907.6 MHz)




Date: 1.JUL.2014 21:32:57




<b>Band :</b>	CDMA2000 BC0	<b>Test Mode :</b>	1xRTT_RC3+SO55 (QPSK)
---------------	--------------	--------------------	-----------------------

99% Occupied Bandwidth Plot on Channel 1013 (824.7 MHz)



Date: 3.JUL.2014 09:51:02


26dB Bandwidth Plot on Channel 1013 (824.7 MHz)



Date: 3.JUL.2014 09:48:46




99% Occupied Bandwidth Plot on Channel 384 (836.52 MHz)



Date: 3.JUL.2014 09:51:31

26dB Bandwidth Plot on Channel 384 (836.52 MHz)




Date: 3.JUL.2014 09:49:14






<b>Band :</b>	CDMA2000 BC1	<b>Test Mode :</b>	1xRTT_RC3+SO55 (QPSK)
---------------	--------------	--------------------	-----------------------

99% Occupied Bandwidth Plot on Channel 25 (1851.25 MHz)



Date: 3.JUL.2014 10:40:15


26dB Bandwidth Plot on Channel 25 (1851.25 MHz)



Date: 3.JUL.2014 10:38:05




### 99% Occupied Bandwidth Plot on Channel 600 (1880.0 MHz)



Date: 3.JUL.2014 10:40:43


### 26dB Bandwidth Plot on Channel 600 (1880.0 MHz)



Date: 3.JUL.2014 10:38:34




99% Occupied Bandwidth Plot on Channel 1175 (1908.75 MHz)



Date: 3.JUL.2014 10:41:12

26dB Bandwidth Plot on Channel 1175 (1908.75 MHz)



Date: 3.JUL.2014 10:39:02

## 3.4 Band Edge Measurement

### 3.4.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.


### 3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.4.3 Test Procedures

1. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The band edges of low and high channels for the highest RF powers were measured.
4. The RBW was replaced by 10 kHz, slightly smaller than the value in (2), due to the spectrum analyzer limitation to set the exact value. A worst case correction factor of  $10 \cdot \log (1\% \text{ emission-BW}/\text{measurement RBW})$  was compensated.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from  $43 + 10 \log (P)$  dB below the transmitter power P(Watts)  
 $= P(W) - [43 + 10 \log (P)]$  (dB)  
 $= [30 + 10 \log (P)]$  (dBm) -  $[43 + 10 \log (P)]$  (dB)  
 $= -13 \text{ dBm}$ .

### 3.4.4 Test Setup






### 3.4.5 Test Result (Plots) of Conducted Band Edge


Band :	GSM850	Test Mode :	GPRS class 8 Link (GMSK)
--------	--------	-------------	--------------------------

#### Lower Band Edge Plot on Channel 128 (824.2 MHz)



Date: 1.JUL.2014 16:45:50

#### Higher Band Edge Plot on Channel 251 (848.8 MHz)




Date: 1.JUL.2014 16:41:32




Band :	GSM850	Test Mode :	EDGE class 8 Link (8PSK)
--------	--------	-------------	--------------------------

Lower Band Edge Plot on Channel 128 (824.2 MHz)



Date: 1.JUL.2014 17:50:36

Higher Band Edge Plot on Channel 251 (848.8 MHz)




Date: 1.JUL.2014 17:45:44



Band :	GSM1900	Test Mode :	GPRS class 8 Link (GMSK)
--------	---------	-------------	--------------------------

Lower Band Edge Plot on Channel 512 (1850.2 MHz)



Date: 1.JUL.2014 19:19:49

Higher Band Edge Plot on Channel 810 (1909.8 MHz)




Date: 1.JUL.2014 19:16:06




Band :	GSM1900	Test Mode :	EDGE class 8 Link (8PSK)
--------	---------	-------------	--------------------------

Lower Band Edge Plot on Channel 512 (1850.2 MHz)



Date: 1.JUL.2014 20:13:32

Higher Band Edge Plot on Channel 810 (1909.8 MHz)




Date: 1.JUL.2014 20:09:06




<b>Band :</b>	WCDMA Band V	<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)
---------------	--------------	--------------------	--------------------------

Lower Band Edge Plot on Channel 4132 (826.4 MHz)



Date: 2.JUL.2014 10:08:35

Higher Band Edge Plot on Channel 4233 (846.6 MHz)




Date: 2.JUL.2014 10:03:39




<b>Band :</b>	WCDMA Band IV	<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)
---------------	---------------	--------------------	--------------------------

Lower Band Edge Plot on Channel 1312 (1712.4 MHz)



Date: 2.JUL.2014 09:28:17

Higher Band Edge Plot on Channel 1513 (1752.6 MHz)




Date: 2.JUL.2014 09:23:20




<b>Band :</b>	WCDMA Band II	<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)
---------------	---------------	--------------------	--------------------------

Lower Band Edge Plot on Channel 9262 (1852.4 MHz)



Date: 1.JUL.2014 21:28:21

Higher Band Edge Plot on Channel 9538 (1907.6 MHz)




Date: 1.JUL.2014 21:18:47




<b>Band :</b>	CDMA2000 BC0	<b>Test Mode :</b>	1xRTT_RC3+SO55 (QPSK)
---------------	--------------	--------------------	-----------------------

Lower Band Edge Plot on Channel 1013 (824.7 MHz)



Date: 3.JUL.2014 09:45:07

Higher Band Edge Plot on Channel 777 (848.31 MHz)




Date: 3.JUL.2014 09:09:31




<b>Band :</b>	CDMA2000 BC1	<b>Test Mode :</b>	1xRTT_RC3+SO55 (QPSK)
---------------	--------------	--------------------	-----------------------

Lower Band Edge Plot on Channel 25 (1851.25 MHz)



Date: 3.JUL.2014 10:30:17

Higher Band Edge Plot on Channel 1175 (1908.75 MHz)



Date: 3.JUL.2014 10:21:06

## 3.5 Conducted Spurious Emission Measurement

### 3.5.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10<sup>th</sup> harmonic.


### 3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.5.3 Test Procedures

1. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)  
 $= P(W) - [43 + 10\log(P)]$  (dB)  
 $= [30 + 10\log(P)]$  (dBm) -  $[43 + 10\log(P)]$  (dB)  
 $= -13\text{dBm}$ .

### 3.5.4 Test Setup






### 3.5.5 Test Result (Plots) of Conducted Spurious Emission


Band :	GSM850	Channel :	CH189
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 1.JUL.2014 17:01:55


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 1.JUL.2014 17:02:06




### Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 1.JUL.2014 17:02:15

### Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 1.JUL.2014 17:02:23




<b>Band :</b>	GSM850	<b>Channel :</b>	CH189
<b>Test Mode :</b>	EDGE class 8 Link (8PSK)	<b>Frequency :</b>	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 1.JUL.2014 18:16:00


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 1.JUL.2014 18:16:12




### Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 1.JUL.2014 18:16:20

### Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 1.JUL.2014 18:16:29




Band :	GSM1900	Channel :	CH661
Test Mode :	GPRS class 8 Link (GMSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 1.JUL.2014 19:31:33

Conducted Spurious Emission Plot between 1GHz ~ 3GHz




Date: 1.JUL.2014 19:31:42





Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 1.JUL.2014 19:32:18




<b>Band :</b>	GSM1900	<b>Channel :</b>	CH661
<b>Test Mode :</b>	EDGE class 8 Link (8PSK)	<b>Frequency :</b>	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 1.JUL.2014 20:29:51


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 1.JUL.2014 20:29:59




### Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 1.JUL.2014 20:30:10


### Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 1.JUL.2014 20:30:18



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 1.JUL.2014 20:30:26




<b>Band :</b>	WCDMA Band V	<b>Channel :</b>	CH4182
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)	<b>Frequency :</b>	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 2.JUL.2014 10:58:36


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 2.JUL.2014 10:58:46




### Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 2.JUL.2014 10:58:55

### Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 2.JUL.2014 10:59:03




<b>Band :</b>	WCDMA Band IV	<b>Channel :</b>	CH1413
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)	<b>Frequency :</b>	1732.6 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 2.JUL.2014 09:37:58


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 2.JUL.2014 09:38:07




### Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 2.JUL.2014 09:38:18


### Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 2.JUL.2014 09:38:27



Conducted Spurious Emission Plot between 13.6GHz ~ 18GHz




Date: 2.JUL.2014 09:38:35




<b>Band :</b>	WCDMA Band II	<b>Channel :</b>	CH9400
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)	<b>Frequency :</b>	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 1.JUL.2014 21:38:58

Conducted Spurious Emission Plot between 1GHz ~ 3GHz




Date: 1.JUL.2014 21:39:07





Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 1.JUL.2014 21:39:36




<b>Band :</b>	CDMA2000 BC0	<b>Channel :</b>	CH384
<b>Test Mode :</b>	1xRTT_RC3+SO55 (QPSK)	<b>Frequency :</b>	836.52 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 3.JUL.2014 10:00:38


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 3.JUL.2014 10:00:19




### Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 3.JUL.2014 10:00:27

### Conducted Spurious Emission Plot between 7GHz ~ 9GHz




Date: 3.JUL.2014 10:00:36




Band :	CDMA2000 BC1	Channel :	CH600
Test Mode :	1xRTT_RC3+SO55 (QPSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 3.JUL.2014 10:43:10


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 3.JUL.2014 10:43:17




### Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 3.JUL.2014 10:43:30


### Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz



Date: 3.JUL.2014 10:43:39



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



Date: 3.JUL.2014 10:43:47



### 3.6 Field Strength of Spurious Radiation Measurement

#### 3.6.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

#### 3.6.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

#### 3.6.3 Test Procedures


1. The EUT was placed on a rotatable wooden table 0.8 meters above the ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10.  $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
11.  $ERP \text{ (dBm)} = EIRP - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
13. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)  
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$   
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$   
 $= -13\text{dBm}.$

### 3.6.4 Test Setup

For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





3.6.5 Test Result of Field Strength of Spurious Radiated

<b>Band :</b>	GSM850					<b>Temperature :</b>	23~25°C		
<b>Test Mode :</b>	GPRS class 8 Link (GMSK)					<b>Relative Humidity :</b>	44~48%		
<b>Test Engineer :</b>	Eric Shih, Kai Wang, and Stan Hsieh					<b>Polarization :</b>	Horizontal		
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-50.04	-13	-37.04	-59.67	-53.91	1.62	5.49	H	Pass
2512	-35.97	-13	-22.97	-48.72	-40.09	2.1	6.22	H	Pass
3345	-53.92	-13	-40.92	-67.49	-58.96	3.03	8.07	H	Pass

<b>Band :</b>	GSM850					<b>Temperature :</b>	23~25°C		
<b>Test Mode :</b>	GPRS class 8 Link (GMSK)					<b>Relative Humidity :</b>	44~48%		
<b>Test Engineer :</b>	Eric Shih, Kai Wang, and Stan Hsieh					<b>Polarization :</b>	Vertical		
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-51.91	-13	-38.91	-62.89	-55.78	1.62	5.49	V	Pass
2512	-35.46	-13	-22.46	-49.28	-39.58	2.1	6.22	V	Pass
3345	-51.05	-13	-38.05	-67.4	-56.09	3.03	8.07	V	Pass



<b>Band :</b>	GSM850				<b>Temperature :</b>	23~25°C			
<b>Test Mode :</b>	EDGE class 8 Link (8PSK)				<b>Relative Humidity :</b>	44~48%			
<b>Test Engineer :</b>	Eric Shih, Kai Wang, and Stan Hsieh				<b>Polarization :</b>	Horizontal			
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-54.75	-13	-41.75	-64.99	-58.62	1.62	5.49	H	Pass
2512	-42.91	-13	-29.91	-55.84	-47.03	2.1	6.22	H	Pass
3345	-53.35	-13	-40.35	-67.61	-58.39	3.03	8.07	H	Pass

<b>Band :</b>	GSM850				<b>Temperature :</b>	23~25°C			
<b>Test Mode :</b>	EDGE class 8 Link (8PSK)				<b>Relative Humidity :</b>	44~48%			
<b>Test Engineer :</b>	Eric Shih, Kai Wang, and Stan Hsieh				<b>Polarization :</b>	Vertical			
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-53.76	-13	-40.76	-66.82	-57.63	1.62	5.49	V	Pass
2512	-44.22	-13	-31.22	-58.12	-48.34	2.1	6.22	V	Pass
3345	-51.17	-13	-38.17	-67.5	-56.21	3.03	8.07	V	Pass



<b>Band :</b>	GSM1900				<b>Temperature :</b>	23~25°C			
<b>Test Mode :</b>	GPRS class 8 Link (GMSK)				<b>Relative Humidity :</b>	44~48%			
<b>Test Engineer :</b>	Eric Shih, Kai Wang, and Stan Hsieh				<b>Polarization :</b>	Horizontal			
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3756	-40.94	-13	-27.94	-56.29	-47.24	2.51	8.81	H	Pass
5639	-37.41	-13	-24.41	-58.1	-45.12	2.99	10.70	H	Pass
7522	-34.80	-13	-21.80	-62.04	-43.33	3.59	12.12	H	Pass
9398	-36.58	-13	-23.58	-63.03	-45.68	4.1	13.20	H	Pass
11278	-30.01	-13	-17.01	-59.48	-39.05	4.27	13.31	H	Pass
13159	-32.57	-13	-19.57	-66	-42.09	4.27	13.79	H	Pass

<b>Band :</b>	GSM1900				<b>Temperature :</b>	23~25°C			
<b>Test Mode :</b>	GPRS class 8 Link (GMSK)				<b>Relative Humidity :</b>	44~48%			
<b>Test Engineer :</b>	Eric Shih, Kai Wang, and Stan Hsieh				<b>Polarization :</b>	Vertical			
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3756	-42.07	-13	-29.07	-58.34	-48.37	2.51	8.81	V	Pass
5639	-33.70	-13	-20.70	-54.26	-41.41	2.99	10.70	V	Pass
7522	-31.34	-13	-18.34	-58.21	-39.87	3.59	12.12	V	Pass
9398	-37.32	-13	-24.32	-63.67	-46.42	4.1	13.20	V	Pass
11280	-33.75	-13	-20.75	-62.4	-42.79	4.27	13.31	V	Pass
13160	-37.14	-13	-24.14	-68.57	-46.66	4.27	13.79	V	Pass



<b>Band :</b>	GSM1900		<b>Temperature :</b>	23~25°C					
<b>Test Mode :</b>	EDGE class 8 Link (8PSK)		<b>Relative Humidity :</b>	44~48%					
<b>Test Engineer :</b>	Eric Shih, Kai Wang, and Stan Hsieh		<b>Polarization :</b>	Horizontal					
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3756	-50.56	-13	-37.56	-65.88	-56.86	2.51	8.81	H	Pass
5639	-42.31	-13	-29.31	-63.09	-50.02	2.99	10.70	H	Pass
7522	-42.61	-13	-29.61	-69.91	-51.14	3.59	12.12	H	Pass

<b>Band :</b>	GSM1900		<b>Temperature :</b>	23~25°C					
<b>Test Mode :</b>	EDGE class 8 Link (8PSK)		<b>Relative Humidity :</b>	44~48%					
<b>Test Engineer :</b>	Eric Shih, Kai Wang, and Stan Hsieh		<b>Polarization :</b>	Vertical					
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3756	-51.28	-13	-38.28	-67.58	-57.58	2.51	8.81	V	Pass
5639	-42.98	-13	-29.98	-63.52	-50.69	2.99	10.70	V	Pass
7522	-40.29	-13	-27.29	-67.41	-48.82	3.59	12.12	V	Pass



<b>Band :</b>	WCDMA Band V					<b>Temperature :</b>	23~25°C		
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)					<b>Relative Humidity :</b>	44~48%		
<b>Test Engineer :</b>	Eric Shih, Kai Wang, and Stan Hsieh					<b>Polarization :</b>	Horizontal		
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-54.52	-13	-41.52	-63.68	-58.39	1.62	5.49	H	Pass
2512	-39.10	-13	-26.10	-52.65	-43.22	2.1	6.22	H	Pass
3345	-53.61	-13	-40.61	-67.49	-58.65	3.03	8.07	H	Pass

<b>Band :</b>	WCDMA Band V					<b>Temperature :</b>	23~25°C		
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)					<b>Relative Humidity :</b>	44~48%		
<b>Test Engineer :</b>	Eric Shih, Kai Wang, and Stan Hsieh					<b>Polarization :</b>	Vertical		
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-53.05	-13	-40.05	-64.92	-56.92	1.62	5.49	V	Pass
2512	-45.93	-13	-32.93	-59.01	-50.05	2.1	6.22	V	Pass
3345	-51.75	-13	-38.75	-67.16	-56.79	3.03	8.07	V	Pass



<b>Band :</b>	WCDMA Band IV		<b>Temperature :</b>	23~25°C					
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)		<b>Relative Humidity :</b>	44~48%					
<b>Test Engineer :</b>	Eric Shih, Kai Wang, and Stan Hsieh		<b>Polarization :</b>	Horizontal					
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3462	-50.67	-13	-37.67	-65.08	-54.5	4.48	8.31	H	Pass
5198	-48.96	-13	-35.96	-67.91	-53.6	5.332	9.98	H	Pass
6934	-38.36	-13	-25.36	-64.66	-43.6	6.1	11.34	H	Pass

<b>Band :</b>	WCDMA Band IV		<b>Temperature :</b>	23~25°C					
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)		<b>Relative Humidity :</b>	44~48%					
<b>Test Engineer :</b>	Eric Shih, Kai Wang, and Stan Hsieh		<b>Polarization :</b>	Vertical					
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3467	-48.47	-13	-35.47	-64.19	-52.3	4.48	8.31	V	Pass
-5193	-48.46	-13	-35.46	-67.35	-53.1	5.332	9.98	V	Pass
6934	-37.96	-13	-24.96	-63.59	-43.2	6.1	11.34	V	Pass



<b>Band :</b>	WCDMA Band II		<b>Temperature :</b>	23~25°C					
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)		<b>Relative Humidity :</b>	44~48%					
<b>Test Engineer :</b>	Eric Shih, Kai Wang, and Stan Hsieh		<b>Polarization :</b>	Horizontal					
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3763	-41.58	-13	-28.58	-56.99	-47.88	2.51	8.81	H	Pass
5646	-44.06	-13	-31.06	-64.76	-51.77	2.99	10.70	H	Pass
7522	-35.43	-13	-22.43	-62.59	-43.96	3.59	12.12	H	Pass

<b>Band :</b>	WCDMA Band II		<b>Temperature :</b>	23~25°C					
<b>Test Mode :</b>	RMC 12.2Kbps Link (QPSK)		<b>Relative Humidity :</b>	44~48%					
<b>Test Engineer :</b>	Eric Shih, Kai Wang, and Stan Hsieh		<b>Polarization :</b>	Vertical					
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3763	-44.00	-13	-31.00	-60.35	-50.3	2.51	8.81	V	Pass
5639	-46.29	-13	-33.29	-66.77	-54	2.99	10.70	V	Pass
7522	-37.54	-13	-24.54	-64.55	-46.07	3.59	12.12	V	Pass



<b>Band :</b>	CDMA2000 BC0	<b>Temperature :</b>	23~25°C						
<b>Test Mode :</b>	1xRTT_RC3+SO55 (QPSK)	<b>Relative Humidity :</b>	44~48%						
<b>Test Engineer :</b>	Eric Shih, Kai Wang, and Stan Hsieh	<b>Polarization :</b>	Horizontal						
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-48.60	-13	-35.60	-57.29	-52.47	1.62	5.49	H	Pass
2509	-49.90	-13	-36.90	-62.98	-54.02	2.1	6.22	H	Pass
3345	-49.76	-13	-36.76	-63.66	-54.80	3.03	8.07	H	Pass

<b>Band :</b>	CDMA2000 BC0	<b>Temperature :</b>	23~25°C						
<b>Test Mode :</b>	1xRTT_RC3+SO55 (QPSK)	<b>Relative Humidity :</b>	44~48%						
<b>Test Engineer :</b>	Eric Shih, Kai Wang, and Stan Hsieh	<b>Polarization :</b>	Vertical						
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1672	-50.66	-13	-37.66	-61.62	-54.53	1.62	5.49	V	Pass
2509	-51.28	-13	-38.28	-64.82	-55.40	2.1	6.22	V	Pass
3345	-51.14	-13	-38.14	-66.54	-56.18	3.03	8.07	V	Pass



<b>Band :</b>	CDMA2000 BC1	<b>Temperature :</b>	23~25°C						
<b>Test Mode :</b>	1xRTT_RC3+SO55 (QPSK)	<b>Relative Humidity :</b>	44~48%						
<b>Test Engineer :</b>	Eric Shih, Kai Wang, and Stan Hsieh	<b>Polarization :</b>	Horizontal						
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3763	-40.76	-13	-27.76	-55.98	-47.06	2.51	8.81	H	Pass
5639	-40.98	-13	-27.98	-61.54	-48.69	2.99	10.70	H	Pass
7522	-36.95	-13	-23.95	-64.02	-45.48	3.59	12.12	H	Pass
11278	-37.89	-13	-24.89	-67.11	-46.93	4.27	13.31	H	Pass

<b>Band :</b>	CDMA2000 BC1	<b>Temperature :</b>	23~25°C						
<b>Test Mode :</b>	1xRTT_RC3+SO55 (QPSK)	<b>Relative Humidity :</b>	44~48%						
<b>Test Engineer :</b>	Eric Shih, Kai Wang, and Stan Hsieh	<b>Polarization :</b>	Vertical						
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.								
Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
3763	-39.48	-13	-26.48	-55.58	-45.78	2.51	8.81	V	Pass
5639	-34.64	-13	-21.64	-55.2	-42.35	2.99	10.70	V	Pass
7522	-35.60	-13	-22.60	-62.46	-44.13	3.59	12.12	V	Pass
11278	-40.36	-13	-27.36	-68.83	-49.40	4.27	13.31	V	Pass

## 3.7 Frequency Stability Measurement

### 3.7.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5\text{ppm}$ ) of the center frequency.

### 3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


### 3.7.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the system simulator.
2. With power OFF, the temperature was decreased to  $-30^{\circ}\text{C}$  and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in  $10^{\circ}\text{C}$  steps up to  $50^{\circ}\text{C}$ . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

### 3.7.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at  $25\pm 5^{\circ}\text{C}$  and connected with the system simulator.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

### 3.7.5 Test Setup





3.7.6 Test Result of Temperature Variation

Band :	GSM 850	Channel :	189
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	GPRS class 8	EDGE class 8	Result
	Deviation (ppm)	Deviation (ppm)	
50	0.0084	0.0096	PASS
40	0.0048	0.0060	
30	0.0024	0.0012	
20(Ref.)	0.0000	0.0000	
10	0.0024	0.0036	
0	0.0012	0.0048	
-10	0.0024	0.0072	
-20	0.0012	0.0048	
-30	0.0036	0.0060	

Band :	GSM 1900	Channel :	661
Limit (ppm) :	2.5	Frequency :	1880.0 MHz

Temperature (°C)	GPRS class 8	EDGE class 8	Result
	Deviation (ppm)	Deviation (ppm)	
50	0.0043	0.0037	PASS
40	0.0021	0.0043	
30	0.0005	0.0027	
20(Ref.)	0.0000	0.0000	
10	0.0011	0.0011	
0	0.0011	0.0016	
-10	0.0165	0.0027	
-20	0.0021	0.0021	
-30	0.0027	0.0032	



<b>Band :</b>	WCDMA Band V	<b>Channel :</b>	4182
<b>Limit (ppm) :</b>	2.5	<b>Frequency :</b>	836.4 MHz

Temperature (°C)	RMC 12.2Kbps	Result
	Deviation (ppm)	
50	0.0060	PASS
40	0.0143	
30	0.0108	
20(Ref.)	0.0000	
10	0.0036	
0	0.0024	
-10	0.0060	
-20	0.0084	
-30	0.0072	

<b>Band :</b>	WCDMA Band IV	<b>Channel :</b>	1413
<b>Limit (ppm) :</b>	2.5	<b>Frequency :</b>	1732.6 MHz

Temperature (°C)	RMC 12.2Kbps	Result
	Deviation (ppm)	
50	0.0017	PASS
40	0.0035	
30	0.0012	
20(Ref.)	0.0000	
10	0.0006	
0	0.0006	
-10	0.0017	
-20	0.0012	
-30	0.0023	



<b>Band :</b>	WCDMA Band II	<b>Channel :</b>	9400
<b>Limit (ppm) :</b>	2.5	<b>Frequency :</b>	1880.0 MHz

Temperature (°C)	RMC 12.2Kbps	Result
	Deviation (ppm)	
50	0.0021	PASS
40	0.0011	
30	0.0005	
20(Ref.)	0.0000	
10	0.0011	
0	0.0005	
-10	0.0005	
-20	0.0000	
-30	0.0016	

<b>Band :</b>	CDMA2000 BC0	<b>Channel :</b>	384
<b>Limit (ppm) :</b>	2.5	<b>Frequency :</b>	836.52 MHz

Temperature (°C)	Deviation (ppm)	Result
	1xRTT_RC3+SO55	
50	0.0108	PASS
40	0.0036	
30	0.0072	
20(Ref.)	0.0000	
10	0.0012	
0	0.0036	
-10	0.0024	
-20	0.0012	
-30	0.0048	



Band :	CDMA2000 BC1	Channel :	600
Limit (ppm) :	2.5	Frequency :	1880.0 MHz

Temperature (°C)	Deviation (ppm)	Result
	1xRTT_RC3+SO55	
50	0.0048	PASS
40	0.0021	
30	0.0011	
20(Ref.)	0.0000	
10	0.0005	
0	0.0005	
-10	0.0011	
-20	0.0032	
-30	0.0016	



3.7.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GPRS class 8	3.47	0.0024	2.5	PASS
		3.30	0.0036		
		BEP	0.0000		
	EDGE class 8	3.47	0.0012		
		3.30	0.0000		
		BEP	0.0000		
GSM 1900 CH661	GPRS class 8	3.47	0.0011		
		3.30	0.0000		
		BEP	0.0027		
	EDGE class 8	3.47	0.0037		
		3.30	0.0021		
		BEP	0.0032		
WCDMA Band V CH4182	RMC 12.2Kbps	3.47	0.0036		
		3.30	0.0120		
		BEP	0.0132		
WCDMA Band IV CH1413	RMC 12.2Kbps	3.47	0.0006		
		3.30	0.0006		
		BEP	0.0012		
WCDMA Band II CH9400	RMC 12.2Kbps	3.47	0.0005		
		3.30	0.0011		
		BEP	0.0005		
CDMA2000 BC0 CH384	1xRTT RC3+SO55	3.47	0.0048		
		3.30	0.0012		
		BEP	0.0012		
CDMA2000 BC1 CH600	1xRTT RC3+SO55	3.47	0.0021		
		3.30	0.0011		
		BEP	0.0016		

Note:

1. Normal Voltage = 3.30V.
2. Battery End Point (BEP) = 3.14 V.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
System Simulator	Rohde & Schwarz	CMU200	117995	N/A	Aug. 01, 2013	Jul. 01, 2014 ~ Jul. 03, 2014	Jul. 31, 2014	Conducted (TH02-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz~40GHz	Jun. 09, 2014	Jul. 01, 2014 ~ Jul. 03, 2014	Jun. 08, 2015	Conducted (TH02-HY)
Thermal Chamber	Ten Billion	TTH-D3SP	TBN-930701	N/A	Jul. 19, 2013	Jul. 01, 2014 ~ Jul. 03, 2014	Jul. 18, 2014	Conducted (TH02-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV30	101749	10Hz ~ 30GHz	Feb. 10, 2014	Jul. 12, 2014 ~ Jul. 14, 2014	Feb. 09, 2015	Radiation (03CH07-HY)
Bilog Antenna	Schaffner	CBL6111C	2726	30MHz ~ 1GHz	Oct. 10, 2013	Jul. 12, 2014 ~ Jul. 14, 2014	Oct. 09, 2014	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	75962	1GHz~18GHz	Aug. 22, 2013	Jul. 12, 2014 ~ Jul. 14, 2014	Aug. 21, 2014	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10 MHz ~ 1000MHz	Mar. 17, 2014	Jul. 12, 2014 ~ Jul. 14, 2014	Mar. 16, 2015	Radiation (03CH07-HY)
Preamplifier	Agilent	8449B	3008A02362	1 GHz~26.5 GHz	Nov. 29, 2013	Jul. 12, 2014 ~ Jul. 14, 2014	Nov. 28, 2014	Radiation (03CH07-HY)
Turn Table	ChainTek	ChainTek 3000	N/A	0 ~ 360 degree	N/A	Jul. 12, 2014 ~ Jul. 14, 2014	N/A	Radiation (03CH07-HY)
Antenna Mast	ChainTek	M-400-0	114/8000604/L	N/A	N/A	Jul. 12, 2014 ~ Jul. 14, 2014	N/A	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170251	15GHz- 40GHz	Oct. 03, 2013	Jul. 12, 2014 ~ Jul. 14, 2014	Oct. 02, 2014	Radiation (03CH07-HY)



## 5 Uncertainty of Evaluation

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.50
---	------