



EMC Test Data

Client:	Hewlett Packard Company	Job Number:	J97665
Model:	SDGOB1503	T-Log Number:	T97680
Contact:	Sachin Sawalapurkar	Project Manager:	-
Standard:	FCC 15.247 / RSS-210 / LP0002	Project Coordinator:	Sheareen Jacobs
		Class:	N/A

Maximum Permissible Exposure

Test Specific Details

Objective: The objective of this test session is to perform final qualification testing of the EUT with respect to the specification listed above.

Date of Test: 4/7/2015
 Test Engineer: Mark Hill

General Test Configuration

Calculation uses the free space transmission formula:

$$S = (PG)/(4 \pi d^2)$$

Where: S is power density (W/m²), P is output power (W), G is antenna gain relative to isotropic, d is separation distance from the transmitting antenna (m).

Summary of Results

Device complies with Power Density requirements at 20cm separation:	Yes
---	-----

Modifications Made During Testing

No modifications were made to the EUT during testing

Deviations From The Standard

No deviations were made from the requirements of the standard.



EMC Test Data

Client:	Hewlett Packard Company	Job Number:	J97665
Model:	SDGOB1503	T-Log Number:	T97680
Contact:	Sachin Sawalapurkar	Project Manager:	-
Standard:	FCC 15.247 / RSS-210 / LP0002	Project Coordinator:	Sheareen Jacobs
		Class:	N/A

Use: General
 Antenna: 2.5dBi

Band	Mode	Output Power		Antenna gain (Max)	EIRP		Channels Available	Channels Used	Total EIRP	
		Peak	Average		dBm	W			W	dBm
2400 - 2483.5	OFDM	-	20.4	2.5	22.9	0.195	11	1	0.195	22.90
2401 - 2483.5	CCK	-	18.5	2.5	21.0	0.126				
2400 - 2483.5	GFSK	1.8	-	2.5	4.3	0.003	79	1	0.003	4.30
Totals:								2	0.198	22.97

EIRP mW	Power Density (S) at 20 cm mW/cm ²	MPE Limit at 20 cm mW/cm ²
198	0.039	1.000