


NOTES:

NO.3

- 1. Surface Material:XF581
- * 2. Surface Material tolerance:0.038±0.003mm
- 3. Surface Material color:white
- 4. printing color is as color defined in artwork
- 5. Adhesive base:Acrylic
- * 6. Adhesive thickness:0.025+/-0.003mm
- * 7. Adhesion to steel (180o磨钢粘着力):1+/-0.3 kg/25mm
- * 8. Initial Tack (初期力):4+/-2 #
- 9. Release Power (90o剥离力):20+/-10 g/25mm
- * 10. Holding Power (持粘力测试法):5+/-2 hr/kg/20mm2
- 11. Package Style:Reel
- 12. This part must comply with ROHs and HF

REV.	MARK	ECR/ECN NO.	DATE	UPDATE DESCRIPTION	SIGNATURE
0			15/08/31	First release	Tao
01			15/09/01	Add Japan RF"201-XXXXXX" and Taiwan NCC"CCAF 15LPXXXXYX"	Tao
02			15/09/21	Update Japan RF:201-XXXXXX to 201-150412	hongjun
03			15/10/29	Remove the FCC DoC logo	hongjun



Ulysses (26*20*R 1.5mm)

Z125
201-150412
ANATEL ID:
XXXX-XX-XXXX

Model Number:SDGOB-1505
FCC ID:B94SDGOB1505
IC:466D-SDGOB1505
CMIIT: 2013DJXXXX

MSIP-CRM-BCM-SDGOB-1505
해당 무선설비는 운용중
전파혼신 가능성이 있음

Product of China

SCALE:2:1

MATERIAL (SPEC.)		XF581		SCALE	2:1													
FINISH				SHEET	1/1													
Select				UNIT	PART NAME													
Dim.	Tol.	A	B	C	EPS	EPE	BAG	CTN	V	Label	USR	MM	PTT label					
0~6	0.05	0.05	0.10	0.20	0.50	0.50	3.00	2.00	0.20									
6~30	0.10	0.15	0.20	0.30	0.50	0.50	5.00	2.00	0.20									
30~120	0.15	0.20	0.30	0.50	0.50	1.00	5.00	2.00	0.25									
120~300	0.20	0.30	0.40	1.00	1.00	10.00	3.00	3.00	0.30									
300~450	0.25	0.40	0.50	2.00	2.00	15.00	5.00	5.00	0.50									
450~600	0.30	0.50	0.60	3.00	3.00	20.00	5.00	5.00	0.80									
DRAFT TOLERANCE				±0.2°		CRITICAL DIM. MARK		*					CUSTOMER MODEL		CUSTOMER PART NO.		APPROVED	
													U98H127.OX		500.xxxxx.005		Tao	

FOXCONN

HON HAI PRECISION IND. CO., LTD.
CNSBG

DESIGNED
Tao

APPROVED