


NOTES:

1. Surface Material:XF581
- * 2. Surface Material tolerance:0.038±0.003mm
3. Surface Material color:white
4. printing color is as color defined in artwork
5. Adhesive base:Acrylic
- * 6. Adhesive thickness:0.025+/-0.003mm
- * 7. Adhesion to steel (180o磨钢粘着力):1+/-0.3 kg/25mm
- * 8. Initial Tack (初期力):4+/-2 #
9. Release Power (90o剥离力):20+/-10 g/25mm
- * 10. Holding Power (持粘力测试法):5+/-2 hr/kg/20mm2
11. Package Style:Reel
12. This part must comply with ROHs and HF

NO.3

REV.	MARK	ECR/ECN NO.	DATE	UPDATE DESCRIPTION	SIGNATURE
0			15/08/31	First release	Tao
01			15/09/01	Add Japan RF"201-XXXXXX" and Taiwan NCC"CCAF 15LPXXXXYX"	Tao
02			05/9/21	Update Japan RF:201-XXXXXX to 201-150420	hongjun
03			05/10/29	Remove the FCC DoC logo	hongjun



UlyssesBlue (26*20*R1.5mm)

Z125
201-150420
ANATEL ID:
XXXX-XX-XXXX

Model Number:SDGOB-1506
FCC ID:B94SDGOB1506
IC:466D-SDGOB1506
CMIIT: 2013DJXXXX

MSIP-CRM-BCM-SDGOB-1506
해당 무선설비는 운용중
전파혼신 가능성이 있음

Product of China

SCALE:2:1

MATERIAL (SPEC.)		XF581		SCALE	2:1												
FINISH				SHEET	1/1												
Select				UNIT	PART NAME												
Dim.	Tol.	A	B	C	EPS	EPE	BAG	CTN	V	Label	USR	MM	PTT label				
0~6		0.05	0.05	0.10						0.20							
6~30		0.10	0.15	0.20	0.50	0.50	3.00			0.20							
30~120		0.15	0.20	0.30	0.50	0.50	5.00	2.00		0.25							
120~300		0.20	0.30	0.40	1.00	1.00	10.00	3.00		0.30							
300~450		0.25	0.40	0.50	2.00	2.00	15.00	5.00		0.50							
450~600		0.30	0.50	0.60	3.00	3.00	20.00	5.00		0.80							
DRAFT TOLERANCE				±0.2°		CRITICAL DIM. MARK		*									
												MODEL		PART NO.		DESIGNED	
												U98H125.OX		500.xxxxx.005		Tao	
												CUSTOMER MODEL		CUSTOMER PART NO.		APPROVED	

FOXCONN

HON HAI PRECISION IND. CO., LTD.
CNSBG

PTT label

U98H125.OX

500.xxxxx.005

Tao

CUSTOMER MODEL

CUSTOMER PART NO.

APPROVED