

Company: HP Inc

Test of: 0960-4025 and 0960-4034

To: FCC 15.247 (DTS) & IC RSS-247

Report No.: MARS11-U2 BLE Rev B WiFi/BT Module

COMPLETE TEST REPORT



COMPLETE TEST REPORT

FROM



Test of: HP Inc 0960-4025 and 0960-4034

to

To: FCC 15.247 (DTS) & IC RSS-247

Test Report Serial No.: MARS11-U2 BLE Rev B WiFi/BT Module

This report supersedes: MARS11-U2 BLE Rev A

Applicant: HP Inc
1115 SE 164th Ave., Suite 210,
Vancouver,
Washington 98683,
USA

Product Function 802.11 a/b/g/n SDIO dual band
with BT/BLE

Issue Date: 27th October 2017

This Test Report is Issued Under the Authority of:

MiCOM Labs, Inc.
575 Boulder Court
Pleasanton California 94566
USA
Phone: +1 (925) 462-0304
Fax: +1 (925) 462-0306
www.micomlabs.com



MiCOM Labs is an ISO 17025 Accredited Testing Laboratory



Table of Contents

1. ACCREDITATION, LISTINGS & RECOGNITION	4
1.1. TESTING ACCREDITATION.....	4
1.2. RECOGNITION	5
1.3. PRODUCT CERTIFICATION	6
2. DOCUMENT HISTORY	7
3. TEST RESULT CERTIFICATE	8
4. REFERENCES AND MEASUREMENT UNCERTAINTY	9
4.1. Normative References	9
4.2. Test and Uncertainty Procedure	10
5. PRODUCT DETAILS AND TEST CONFIGURATIONS	11
5.1. Technical Details	11
5.2. Scope Of Test Program	12
5.3. Equipment Model(s) and Serial Number(s)	13
5.4. Antenna Details	13
5.5. Cabling and I/O Ports	13
5.6. Test Configurations.....	14
5.7. Equipment Modifications	14
5.8. Deviations from the Test Standard	14
6. TEST SUMMARY	15
7. TEST EQUIPMENT CONFIGURATION(S)	16
7.1. Conducted	16
7.2. Radiated Emissions - 3m Chamber.....	18
8. MEASUREMENT AND PRESENTATION OF TEST DATA	21
9. TEST RESULTS	22
9.1. 6 dB & 99% Bandwidth	22
9.2. Conducted Output Power	24
9.3. Power Spectral Density	27
9.4. Emissions	29
9.4.1. <i>Conducted Emissions</i>	29
9.4.1.1. Conducted Spurious Emissions	29
9.4.1.2. Conducted Band-Edge Emissions	31
9.4.2. <i>Radiated Emissions</i>	33
9.4.2.3. TX Spurious & Restricted Band Emissions	33
9.4.2.4. Restricted Edge & Band-Edge Emissions.....	42
9.4.3. <i>Digital Emissions (0.03 - 1 GHz)</i>	48
A. APPENDIX - GRAPHICAL IMAGES	49
A.1. 6 dB & 99% Bandwidth	50
A.2. Power Spectral Density	53
A.3. Emissions	59
A.3.1. <i>Conducted Emissions</i>	59
A.3.1.1. Conducted Spurious Emissions	59
A.3.1.2. Conducted Band-Edge Emissions	63
A.3.2. <i>Radiated Emissions</i>	65
A.3.2.3. TX Spurious & Restricted Band Emissions.....	65
A.3.2.4. Restricted Edge & Band-Edge Emissions	71
A.3.3. <i>Digital Emissions (0.03 - 1 GHz)</i>	75

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

1. ACCREDITATION, LISTINGS & RECOGNITION

1.1. TESTING ACCREDITATION

MiCOM Labs, Inc. is an accredited Electrical testing laboratory per the international standard ISO/IEC 17025:2005. The company is accredited by the American Association for Laboratory Accreditation (A2LA) www.a2la.org test laboratory number 2381.01. MiCOM Labs test schedule is available at the following URL; <http://www.a2la.org/scopepdf/2381-01.pdf>



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 5 of 76

1.2. RECOGNITION

MiCOM Labs, Inc has widely recognized wireless testing capabilities. Our international recognition includes Conformity Assessment Body designation by APEC MRA countries. MiCOM Labs test reports are accepted globally.

Country	Recognition Body	Status	Phase	Identification No.
USA	Federal Communications Commission (FCC)	TCB	-	US0159 Listing #: 102167
Canada	Industry Canada (IC)	FCB	APEC MRA 2	US0159 Listing #: 4143A-2 4143A-3
Japan	MIC (Ministry of Internal Affairs and Communication)	CAB	APEC MRA 2	RCB 210
	VCCI	--	--	A-0012
Europe	European Commission	NB	EU MRA	NB 2280
Australia	Australian Communications and Media Authority (ACMA)	CAB	APEC MRA 1	US0159
Hong Kong	Office of the Telecommunication Authority (OFTA)	CAB	APEC MRA 1	
Korea	Ministry of Information and Communication Radio Research Laboratory (RRL)	CAB	APEC MRA 1	
Singapore	Infocomm Development Authority (IDA)	CAB	APEC MRA 1	
Taiwan	National Communications Commission (NCC) Bureau of Standards, Metrology and Inspection (BSMI)	CAB	APEC MRA 1	
Vietnam	Ministry of Communication (MIC)	CAB	APEC MRA 1	

EU MRA – European Union Mutual Recognition Agreement.

NB – Notified Body

APEC MRA – Asia Pacific Economic Community Mutual Recognition Agreement. Recognition agreement under which test lab is accredited to regulatory standards of the APEC member countries.

Phase I - recognition for product testing

Phase II – recognition for both product testing and certification

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

1.3. PRODUCT CERTIFICATION

MiCOM Labs, Inc. is an accredited Product Certification Body per the international standard ISO/IEC 17065:2012. The company is accredited by the American Association for Laboratory Accreditation (A2LA) www.a2la.org test laboratory number 2381.02. MiCOM Labs test schedule is available at the following URL; <http://www.a2la.org/scopepdf/2381-02.pdf>



United States of America – Telecommunication Certification Body (TCB)
Industry Canada – Certification Body, CAB Identifier – US0159
Europe – Notified Body (NB), NB Identifier - 2280
Japan – Recognized Certification Body (RCB), RCB Identifier - 210



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 7 of 76

2. DOCUMENT HISTORY

Document History		
Revision	Date	Comments
Draft	23rd August 2017	Draft report for client review.
Rev A	11 th October 2017	Initial release.
Rev B	27 th October 2017	Removed module photographs
.		
.		
.		
.		

In the above table the latest report revision will replace all earlier versions.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 8 of 76

3. TEST RESULT CERTIFICATE

Manufacturer: HP Inc 1115 SE 164th Ave., Suite 210, Vancouver, Washington 98683, USA	Tested By: MiCOM Labs, Inc. 575 Boulder Court Pleasanton California 94566 USA
Model: HP Part # 0960-4025 and HP Part # 0960-4034	Telephone: +1 925 462 0304
Type Of Equipment: WLAN BT Radio module	Fax: +1 925 462 0306
S/N's: D80F99748D64, D80F99748D68	
Test Date(s): 28 July - 02 August 2017	Website: www.micomlabs.com

STANDARD(S)	TEST RESULTS
FCC 15.247 (DTS) & IC RSS-247	EQUIPMENT COMPLIES

MiCOM Labs, Inc. tested the equipment mentioned in accordance with the requirements set forth in the above standards. Test results indicate that the equipment tested is capable of demonstrating compliance with the requirements as documented within this report.

Notes:

1. This document reports conditions under which testing was conducted and the results of testing performed.
2. Details of test methods used have been recorded and kept on file by the laboratory.
3. Test results apply only to the item(s) tested.

Approved & Released for MiCOM Labs, Inc. by:



Graeme Grieve
Quality Manager MiCOM Labs, Inc.

Gordon Hurst
President & CEO MiCOM Labs, Inc.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

4. REFERENCES AND MEASUREMENT UNCERTAINTY

4.1. Normative References

REF.	PUBLICATION	YEAR	TITLE
I	KDB 662911 D01 & D02	Oct 31 2013	Guidance for measurement of output emission of devices that employ single transmitter with multiple outputs or systems with multiple transmitters operating simultaneously in the same frequency band
II	KDB 558074 D01 v04	5th April 2017	Guidance for performing compliance measurements on Digital Transmission Systems (DTS) operating under section 15.247.
III	A2LA	June 2015	R105 - Requirement's When Making Reference to A2LA Accreditation Status
IV	ANSI C63.10	2013	American National Standard for Testing Unlicensed Wireless Devices
V	ANSI C63.4	2014	American National Standards for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
VI	CISPR 32	2012	Electromagnetic compatibility of multimedia equipment - Emission requirements
VII	ETSI TR 100 028	2001-12	Parts 1 and 2 Electromagnetic compatibility and Radio Spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics
VIII	FCC 47 CFR Part 15.247	2016	Radio Frequency Devices; Subpart C – Intentional Radiators
IX	ICES-003	Issue 6 Jan 2016	Spectrum Management and Telecommunications; Interference-Causing Equipment Standard. Information Technology Equipment (Including Digital Apparatus) – Limits and methods of measurement.
X	M 3003	Edition 3 Nov.2012	Expression of Uncertainty and Confidence in Measurements
XI	RSS-247 Issue 2	Feb 2017	Digital Transmission Systems (DTSs), Frequency Hopping System (FHSs) and Licence-Exempt Local Area Network (LE-LEN) Devices
XII	RSS-Gen Issue 4	November 2014	General Requirements and Information for the Certification of Radiocommunication Equipment
XIII	KDB 644545 D03 v01	August 14th 2014	Guidance for IEEE 802.11ac New Rules
XIV	FCC 47 CFR Part 2.1033	2016	FCC requirements and rules regarding photographs and test setup diagrams.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 10 of 76

4.2. Test and Uncertainty Procedure

Conducted and radiated emission measurements were conducted in accordance with American National Standards Institute ANSI C63.4, listed in the Normative References section of this report.

Measurement uncertainty figures are calculated in accordance with ETSI TR 100 028 Parts 1 and 2.

Measurement uncertainties stated are based on a standard uncertainty multiplied by a coverage factor $k = 2$, providing a level of confidence of approximately 95 % in accordance with UKAS document M 3003 listed in the Normative References section of this report.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 11 of 76

5. PRODUCT DETAILS AND TEST CONFIGURATIONS

5.1. Technical Details

Details	Description
Purpose:	Test of the HP Inc 0960-4025 and 0960-4034 in BLE mode to FCC 15.247 (DTS) & IC RSS-247.
Applicant:	HP Inc 1115 SE 164th Ave., Suite 210, Vancouver, Washington 98683, USA
Manufacturer:	HP Inc
Laboratory performing the tests:	MiCOM Labs, Inc. 575 Boulder Court Pleasanton California 94566 USA
Test report reference number:	MARS11-U2 BLE Rev B WiFi/BT Module
Date EUT received:	12 th June 2017
Standard(s) applied:	FCC 15.247 (DTS) & IC RSS-247
Dates of test (from - to):	28 July - 02 August 2017
No of Units Tested:	2
Product Family Name:	VCVRA-1712
Model(s):	Model: HP Inc.'s VCVRA-1712 Part numbers: 0960-4025 and 0960-4034
Location for use:	Indoors
Declared Frequency Range(s):	2400 - 2483.5 MHz;
Type of Modulation:	BLE - GFSK
EUT Modes of Operation:	2400 - 2483.5 MHz:GFSK;
Declared Nominal Output Power :	6 dBm:
Transmit/Receive Operation:	Transceiver - Full Duplex
Rated Input Voltage and Current:	3.3V+/-10%, 1A
Operating Temperature Range:	Declared Range 0°C to 70°C
ITU Emission Designator:	1M00G1D
Equipment Dimensions:	37mm x 40mm
Weight:	0.3 oz
Hardware Rev:	V4
Software Rev:	P130

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 12 of 76

5.2. Scope Of Test Program

HP 0960-4025 and 0960-4034

The scope of the test program was to test the HP 0960-4025 and 0960-4034 Bluetooth radio (BLE) in GFSK configurations in the frequency range 2400 - 2483.5 MHz; for compliance against the following specifications:

FCC 15.247 (DTS) & IC RSS-247

Radio Frequency Devices; Subpart C – Intentional Radiators

Industry Canada RSS-247

Digital Transmission Systems (DTSs), Frequency Hopping System (FHSs) and Licence-Exempt Local Area Network (LE-LEN) Devices

The product is available as 2 model variants;-

0960-4025 has U.FL connectors to enable connection to external antennas.

0960-4034 has integral antennas only.

PCB Manufacturing Variation

Testing commenced on Rev 3.1 of the wireless device using VCVRA-1712 pcb's.

For manufacturability, HP agreed to remove an extra set of holes on the digital interface connector. This is designated as the Rev 4 design.

Differences: All traces and pads remained however holes are not drilled on the two extra connections, and thus the connector cannot be loaded into the wrong location.

Verification: The differences between Revision 3.1 and Revision 4 of the VCVRA-1712 radio were reviewed, tested and judged to have no significant effect on device compliance.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 13 of 76

5.3. Equipment Model(s) and Serial Number(s)

Type	Description	Manufacturer	Model	Serial no.	Delivery Date
EUT	802.11 a/b/g/n SDIO dual band 2.4G/5GHz WLAN with BT/BLE	HP	Model: HP Inc.'s VCVRA-1712 Part numbers: 0960-4025 and 0960-4034	D80F99748D64, D80F99748D68	12 th June 2017
Support	Latitude Laptop, Linux	Dell	E6410	654C3Q1	12 th June 2017
Support	STYX SD Adapter Board	HP	AB_W8977_STYX_ADAPTER_V1	-	12 th June 2017

The product is available as 2 model variants;-

0960-4025 has U.FL connectors to enable connection to external antennas.

0960-4034 has integral antennas only.

5.4. Antenna Details

Type	Manufacturer	Model	Family	Gain (dBi)	BF Gain	Dir BW	X-Pol	Frequency Band (MHz)
integral	HP	integral	5	2.5	-	360	-	2400 - 2483.5
external	YAGEO	ANTX300P002B24553	5	0.7	-	360	-	2400 - 2483.5

BF Gain - Beamforming Gain
Dir BW - Directional BeamWidth
X-Pol - Cross Polarization

5.5. Cabling and I/O Ports

Port Type	Max Cable Length	# of Ports	Screened	Conn Type	Data Type	Bit Rate
24	5	1	--	SD	Data	10/100

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 14 of 76

5.6. Test Configurations

Results for the following configurations are provided in this report:

Operational Mode(s) (802.11a/b/g/n/ac)	Data Rate with Highest Power MBit/s	Channel Frequency (MHz)		
		Low	Mid	High
2400 - 2483.5 MHz				
BLE	1	2,402.00	2,440.00	2,480.00

5.7. Equipment Modifications

The following modifications were required to bring the equipment into compliance:

1. NONE

5.8. Deviations from the Test Standard

The following deviations from the test standard were required in order to complete the test program:

1. NONE

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 15 of 76

6. TEST SUMMARY

List of Measurements

Test Header	Result	Data Link
6 dB & 99% Bandwidth	Complies	View Data
Conducted Output Power	Complies	View Data
Power Spectral Density	Complies	View Data
Emissions	Complies	-
(1) Conducted Emissions	Complies	-
(i) Conducted Spurious Emissions	Complies	View Data
(ii) Conducted Band-Edge Emissions	Complies	View Data
(2) Radiated Emissions	Complies	-
(i) TX Spurious & Restricted Band Emissions	Not Tested	View Data
(ii) Restricted Edge & Band-Edge Emissions	Not Tested	View Data
(3) Digital Emissions (0.03 - 1 GHz)	Not Tested	View Data
(4) AC Wireline Emissions	Not Applicable	See Note 1


Note 1: EUT is powered by DC

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

7. TEST EQUIPMENT CONFIGURATION(S)

7.1. Conducted

Conducted RF Emission Test Set-up(s) The following tests were performed using the conducted test set-up shown in the diagram below.



A full system calibration was performed on the test station and any resulting system losses (or gains) were taken into account in the production of all final measurement data.

Asset#	Description	Manufacturer	Model#	Serial#	Calibration Due Date
#3 SA	MiTest Box to SA	Fairview Microwave	SCA1814-0101-72	#3 SA	2 Oct 2017
#3P1	EUT to MiTest box port 1	Fairview Microwave	SCA1814-0101-72	#3P1	2 Oct 2017
#3P2	EUT to MiTest box port 2	Fairview Microwave	SCA1814-0101-72	#3P2	2 Oct 2017
#3P3	EUT to MiTest box port 3	Fairview Microwave	SCA1814-0101-72	#3P3	2 Oct 2017
#3P4	EUT to MiTest box port 4	Fairview Microwave	SCA1812-0101-72	#3P4	2 Oct 2017
158	Barometer/Thermometer	Control Company	4196	E2846	30 Nov 2017
249	Resistance Thermometer	Thermotronics	GR2105-02	9340 #2	23 Oct 2017

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 17 of 76

287	Rohde & Schwarz 40 GHz Receiver	Rhode & Schwarz	ESIB40	100201	2 May 2018
361	Desktop for RF#1, Labview Software installed	Dell	Vostro 220	WS RF#1	Not Required
378	Rohde & Schwarz 40 GHz Receiver with Generator	Rhode & Schwarz	ESIB40	100107/040	4 Nov 2017
390	USB Power Head 50MHz - 24GHz -60 to +20dBm	Agilent	U2002A	MY50000103	17 Oct 2017
398	MiTest RF Conducted Test Software	MiCOM	MiTest ATS	Version 4.1	Not Required
405	DC Power Supply 0-60V	Agilent	6654A	MY4001826	Cal when used
408	USB to GPIB interface	National Instruments	GPIB-USB HS	14C0DE9	Not Required
436	USB Wideband Power Sensor	Boonton	55006	8731	14 Sep 2017
441	USB Wideband Power Sensor	Boonton	55006	9179	25 Sep 2017
443	4x4 RF Switch Box	MiCOM Labs	MiTest 4X4 RF Switch Box	MIC003	2 Oct 2017
445	PoE Injector	D-Link	DPE-101GL	QTAH1E2000625	Not Required
75	Environmental Chamber	Thermatron	SE-300-2-2	27946	24 Nov 2017

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

7.2. Radiated Emissions - 3m Chamber

The following tests were performed using the radiated test set-up shown in the diagram below. Radiated emissions below 1GHz. Radiated Emissions above 1GHz.



This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 19 of 76

A full system calibration was performed on the test station and any resulting system losses (or gains) were taken into account in the production of all final measurement data.

Asset#	Description	Manufacturer	Model#	Serial#	Calibration Due Date
158	Barometer/Thermometer	Control Company	4196	E2846	30 Nov 2017
170	Video System Controller for Semi Anechoic Chamber	Panasonic	WV-CU101	04R08507	Not Required
287	Rohde & Schwarz 40 GHz Receiver	Rhode & Schwarz	ESIB40	100201	2 May 2018
301	5470 to 5725 MHz Notch Filter	Microtronics	RBC50704	001	30 Oct 2017
302	5150 to 5350 MHz Notch Filter	Microtronics	BRC50703	002	30 Oct 2017
303	5725 to 5875 MHz Notch filter	Microtronics	BRC50705	003	30 Oct 2017
330	Variac 0-280 Vac	Staco Energy Co	3PN1020B	0546	Cal when used
338	Sunol 30 to 3000 MHz Antenna	Sunol	JB3	A052907	30 Oct 2017
341	900MHz Notch Filter	EWT	EWT-14-0199	H1	30 Oct 2017
342	2.4 GHz Notch Filter	EWT	EWT-14-0203	H1	30 Oct 2017
343	5.15 GHz Notch Filter	EWT	EWT-14-0200	H1	30 Oct 2017
344	5.35 GHz Notch Filter	EWT	EWT-14-0201	H1	30 Oct 2017
345	5.46 GHz Notch Filter	EWT	EWT-14-0202	H1	30 Oct 2017
373	26III RMS Multimeter	Fluke	Fluke 26 series III	76080720	26 Oct 2017
378	Rohde & Schwarz 40 GHz Receiver with Generator	Rhode & Schwarz	ESIB40	100107/040	4 Nov 2017
393	DC - 1050 MHz Low Pass Filter	Microcircuits	VLFX-1050	N/A	30 Oct 2017
396	2.4 GHz Notch Filter	Microtronics	BRM50701	001	30 Oct 2017
397	Amp 10 - 2500MHz	MiCOM Labs	Amp 10 - 2500 MHz	NA	9 Oct 2017
399	ETS 1-18 GHz Horn Antenna	ETS	3117	00154575	10 Oct 2017
406	Amplifier for Radiated Emissions	MiCOM Labs	40dB 1 to 18GHz Amp	0406	9 Oct 2017
410	Desktop Computer	Dell	Inspiron 620	WS38	Not Required
411	Mast/Turntable Controller	Sunol Sciences	SC98V	060199-1D	Not Required
412	USB to GPIB Interface	National Instruments	GPIB-USB HS	11B8DC2	Not Required
413	Mast Controller	Sunol Science	TWR95-4	030801-3	Not Required
414	DC Power Supply 0-60V	HP	6274	1029A01285	Cal when used

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 20 of 76

415	Turntable Controller	Sunol Sciences	Turntable Controller	None	Not Required
416	Gigabit ethernet filter	ETS-Lingren	Gigafoil 260366	None	Not Required
447	MiTest Rad Emissions Test Software	MiCOM	Rad Emissions Test Software Version 1.0	447	Not Required
462	Schwarzbeck cable from Antenna to Amplifier.	Schwarzbeck	AK 9513	462	30 Oct 2017
463	Schwarzbeck cable from Amplifier to Bulkhead.	Schwarzbeck	AK 9513	463	30 Oct 2017
464	Schwarzbeck cable from Bulkhead to Receiver	Schwarzbeck	AK 9513	464	30 Oct 2017
480	Cable - Bulkhead to Amp	SRC Haverhill	157-3050360	480	30 Oct 2017
481	Cable - Bulkhead to Receiver	SRC Haverhill	151-3050787	481	30 Oct 2017
482	Cable - Amp to Antenna	SRC Haverhill	157-3051574	482	30 Oct 2017
87	Uninterruptible Power Supply	Falcon Electric	ED2000-1/2LC	F3471 02/01	Cal when used
VLF-1700	Low pass filter DC-1700 MHz	Mini Circuits	VLF-1700	None	30 Oct 2017

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.

8. MEASUREMENT AND PRESENTATION OF TEST DATA

The measurement and graphical data presented in this test report was generated automatically using state-of-the-art technology creating an easy to read report structure. Numerical measurement data is separated from supporting graphical data (plots) through hyperlinks. Numerical measurement data can be reviewed without scrolling through numerous graphical pages to arrive at the next data matrix.

Plots have been relegated into the Appendix 'Graphical Data'.

Test and report automation was performed by [MiTest](#). [MiTest](#) is an automated test system developed by MiCOM Labs. [MiTest](#) is the first cloud based modular test system enabling end-to-end automation of regulatory compliance testing for conducted RF testing.



The MiCOM Labs "[MiTest](#)" Automated Test System" (Patent Pending)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 22 of 76

9. TEST RESULTS

9.1. 6 dB & 99% Bandwidth

Conducted Test Conditions for 6 dB and 99% Bandwidth			
Standard:	FCC CFR 47:15.247	Ambient Temp. (°C):	24.0 - 27.5
Test Heading:	6 dB and 99 % Bandwidth	Rel. Humidity (%):	32 - 45
Standard Section(s):	15.247 (a)(2)	Pressure (mBars):	999 - 1001
Reference Document(s):	See Normative References		

Test Procedure for 6 dB and 99% Bandwidth Measurement
The bandwidth at 6 dB and 99 % was measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate center frequency.

Testing was performed under ambient conditions at nominal voltage. Where the device operated with multiple antenna ports i.e. MIMO device, each port was measured and reported.

Test configuration and setup used for the measurement was per the Conducted Test Set-up specified in this document.

Limits for 6 dB and 99% Bandwidth

(a) Operation under the provisions of this Section is limited to frequency hopping and digitally modulated intentional radiators that comply with the following provisions:

(2) Systems using digital modulation techniques may operate in the 902-928 MHz and 2400-2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 23 of 76

Equipment Configuration for 6 dB & 99% Bandwidth

Variant:	GFSK	Duty Cycle (%):	99
Data Rate:	1.00 MBit/s	Antenna Gain (dBi):	Not Applicable
Modulation:	GFSK	Beam Forming Gain (Y)(dB):	Not Applicable
TPC:	Not Applicable	Tested By:	SB
Engineering Test Notes:			

Test Measurement Results

Test Frequency	Measured 6 dB Bandwidth (MHz)				6 dB Bandwidth (MHz)		Limit	Lowest Margin
	Port(s)				Highest	Lowest		
MHz	a	b	c	d	KHz	MHz		
2402.0	0.667				0.667	0.667	≥500.0	-0.17
2440.0	0.697				0.697	0.697	≥500.0	-0.20
2480.0	0.693				0.693	0.693	≥500.0	-0.19

Test Frequency	Measured 99% Bandwidth (MHz)				Maximum 99% Bandwidth (MHz)		
	Port(s)						
MHz	a	b	c	d			
2402.0	1.065				1.065		
2440.0	1.062				1.062		
2480.0	1.070				1.070		

Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: click the links in the above matrix to view the graphical image (plot).

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 24 of 76

9.2. Conducted Output Power

Conducted Test Conditions for Fundamental Emission Output Power			
Standard:	FCC CFR 47:15.247	Ambient Temp. (°C):	24.0 - 27.5
Test Heading:	Output Power	Rel. Humidity (%):	32 - 45
Standard Section(s):	15.247 (b) & (c)	Pressure (mBars):	999 - 1001
Reference Document(s):	See Normative References		

Test Procedure for Fundamental Emission Output Power Measurement
In the case of average power measurements an average power sensor was utilized.

For peak power measurements the spectrum analyzer built-in power function was used to integrate peak power over the 20 dB bandwidth.

Testing was performed under ambient conditions at nominal voltage only. Where the device operated with multiple antenna ports i.e. MIMO device, each port was measured, summed (Σ) and reported.

Test configuration and setup used for the measurement was per the Conducted Test Set-up specified in this document.

Supporting Information

Calculated Power = $A + G + Y + 10 \log(1/x)$ dBm

$A = \text{Total Power } [10 \cdot \text{Log}_{10}(10^{a/10} + 10^{b/10} + 10^{c/10} + 10^{d/10})]$

$G = \text{Antenna Gain}$

$Y = \text{Beamforming Gain}$

$x = \text{Duty Cycle (average power measurements only)}$

Limits for Fundamental Emission Output Power

(b) The maximum peak conducted output power of the intentional radiator shall not exceed the following for non-frequency hopping systems:

(3) For systems using digital modulation in the 902-928 MHz and 2400-2483.5 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(c) Operation with directional antenna gains greater than 6 dBi.

(1) Fixed point-to-point operation:

(i) Systems operating in the 2400-2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

(iii) Fixed, point-to-point operation, as used in paragraphs (c)(1)(i) and (c)(1)(ii) of this section, excludes the use of point-to-multipoint systems, omnidirectional applications, and multiple co-located intentional radiators transmitting the same information. The operator of the spread spectrum or digitally modulated intentional radiator or, if the equipment is professionally installed, the installer is responsible for ensuring that the system is used exclusively for fixed, point-to-point operations. The instruction manual furnished with the intentional radiator shall contain language in the installation

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 25 of 76

instructions informing the operator and the installer of this responsibility.

(2) In addition to the provisions in paragraphs (b)(3), (b)(4) and (c)(1)(i) of this section, transmitters operating in the 2400-2483.5 MHz band that emit multiple directional beams, simultaneously or sequentially, for the purpose of directing signals to individual receivers or to groups of receivers provided the emissions comply with the following:

(i) Different information must be transmitted to each receiver.

(ii) If the transmitter employs an antenna system that emits multiple directional beams but does not do emit multiple directional beams simultaneously, the total output power conducted to the array or arrays that comprise the device, i.e., the sum of the power supplied to all antennas, antenna elements, staves, etc. and summed across all carriers or frequency channels, shall not exceed the limit specified in paragraph (b)(1) or (b)(3) of this section, as applicable. However, the total conducted output power shall be reduced by 1 dB below the specified limits for each 3 dB that the directional gain of the antenna/antenna array exceeds 6 dBi. The directional antenna gain shall be computed as follows:

(A) The directional gain shall be calculated as the sum of 10 log (number of array elements or staves) plus the directional gain of the element or stave having the highest gain.

(B) A lower value for the directional gain than that calculated in paragraph (c)(2)(ii)(A) of this section will be accepted if sufficient evidence is presented, e.g., due to shading of the array or coherence loss in the beamforming.

(iii) If a transmitter employs an antenna that operates simultaneously on multiple directional beams using the same or different frequency channels, the power supplied to each emission beam is subject to the power limit specified in paragraph (c)(2)(ii) of this section. If transmitted beams overlap, the power shall be reduced to ensure that their aggregate power does not exceed the limit specified in paragraph (c)(2)(ii) of this section. In addition, the aggregate power transmitted simultaneously on all beams shall not exceed the limit specified in paragraph (c)(2)(ii) of this section by more than 8 dB.

(iv) Transmitters that emit a single directional beam shall operate under the provisions of paragraph (c)(1) of this section.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 26 of 76

Equipment Configuration for Peak Output Power

Variant:	GFSK	Duty Cycle (%):	99.0
Data Rate:	1.00 MBit/s	Antenna Gain (dBi):	0.70
Modulation:	GFSK	Beam Forming Gain (Y)(dB):	Not Applicable
TPC:	Not Applicable	Tested By:	SB
Engineering Test Notes:			

Test Measurement Results

Test Frequency	Measured Output Power (dBm)				Calculated Total Power Σ Port(s)	Limit	Margin	EUT Power Setting
	Port(s)							
MHz	a	b	c	d	dBm	dBm	dB	
2402.0	7.27				7.27	30.00	-22.73	10.00
2440.0	7.55				7.55	30.00	-22.45	10.00
2480.0	7.51				7.51	30.00	-22.49	10.00

Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-01 MEASURING RF OUTPUT POWER
Measurement Uncertainty:	± 1.33 dB

The above measurements are true pulse readings and therefore a Duty Cycling correction factor is not required.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 27 of 76

9.3. Power Spectral Density

Conducted Test Conditions for Power Spectral Density			
Standard:	FCC CFR 47:15.247	Ambient Temp. (°C):	24.0 - 27.5
Test Heading:	Power Spectral Density	Rel. Humidity (%):	32 - 45
Standard Section(s):	15.247 (e)	Pressure (mBars):	999 - 1001
Reference Document(s):	See Normative References		

Test Procedure for Power Spectral Density

The transmitter output was connected to a spectrum analyzer and the measured made in a 3 kHz resolution bandwidth using the analyzer auto-coupled sweep-time. A peak value was found over the full emission bandwidth and the spectrum downloaded for post processing purposes.

Where the device operated with multiple antenna ports i.e. MIMO device, each port was measured separately. The Peak Power Spectral Density is the highest level found across the emission bandwidth. With multiple antenna port measurements the numerical analyzer data from each port is summed (\hat{a}) and a link to this additional graphic is provided.

Testing was performed under ambient conditions at nominal voltage only.

Test configuration and setup used for the measurement was per the Conducted Test Set-up specified in this document.

Measure and sum the spectra across the outputs. With this technique, spectra are measured at each output of the device at the required resolution bandwidth. The individual spectra are then summed mathematically in linear power units. Unlike in-band power measurements, in which the sum involves a single measured value (output power) from each output, measurements for compliance with PSD limits involve summing entire spectra across corresponding frequency bins on the various outputs. Consistency is maintained for any device with multiple transmitter outputs to be certain the individual outputs are all aligned with the same span and same number of points. In this instance, the linear power spectrum value within the first spectral bin of output 0 is summed with that in the first spectral bin of output 1, and the first spectral bin of output 2, and so on up to the Nth output to obtain the true value for the first frequency bin of the summed spectrum. The summed spectrum value for each frequency bin is computed in this fashion. These summed spectral values were post processed and the resulting numerical and graphical data presented.

NOTE:

It may be observed that the spectrum in some antenna port plots break the limit line however this in itself does NOT constitute a failure. In all cases a spectrum summation plot is provided in order to prove compliance. A failure occurs only after the summation of all spectrum plots have been summed and are found to be greater than the limit line.

Supporting Information

Calculated Power = $A + 10 \log (1/x)$ dBm

$A = \text{Total Power Spectral Density } [10 \text{ Log}_{10} (10^{a/10} + 10^{b/10} + 10^{c/10} + 10^{d/10})]$

$x = \text{Duty Cycle}$

Limits Power Spectral Density

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than +8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 28 of 76

Equipment Configuration for Power Spectral Density - Peak

Variant:	GFSK	Duty Cycle (%):	99.0
Data Rate:	1.00 MBit/s	Antenna Gain (dBi):	0.70
Modulation:	GFSK	Beam Forming Gain (Y)(dB):	Not Applicable
TPC:	Not Applicable	Tested By:	SB
Engineering Test Notes:			

Test Measurement Results

Test Frequency	Measured Power Spectral Density				Amplitude Summation	Limit	Margin
	Port(s) (dBm/3KHz)						
MHz	a	b	c	d	dBm/3KHz	dBm/3KHz	dB
2402.0	4.784				4.784	8.0	-3.2
2440.0	7.552				7.552	8.0	-0.4
2480.0	6.717				6.717	8.0	-1.3

Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-03 MEASURING RF SPECTRUM MASK
Measurement Uncertainty:	±2.81 dB

Note: click the links in the above matrix to view the graphical image (plot).

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 29 of 76

9.4. Emissions

9.4.1. Conducted Emissions

9.4.1.1. Conducted Spurious Emissions

Conducted Test Conditions for Transmitter Conducted Spurious and Band-Edge Emissions			
Standard:	FCC CFR 47:15.247	Ambient Temp. (°C):	24.0 - 27.5
Test Heading:	Max Unwanted Emission Levels	Rel. Humidity (%):	32 - 45
Standard Section(s):	15.247 (d)	Pressure (mBars):	999 - 1001
Reference Document(s):	See Normative References		

Test Procedure for Transmitter Conducted Spurious and Band-Edge Emissions Measurement

Transmitter Conducted Spurious and Band-Edge emissions were measured at a limit of 30 dBc (average detector) or 20 dBc (peak detector) below the highest in-band spectral density measured with a spectrum analyzer connected to the antenna terminal. Measurements were made while EUT was operating in transmit mode of operation at the appropriate centre frequency closest to the band-edge. Emissions were maximized during the measurement and limits derived from the peak spectral power and drawn on each plot.

Where the device operated with multiple antenna ports i.e. MIMO device, each port was measured separately. Testing was performed under ambient conditions at nominal voltage only.

Test configuration and setup used for the measurement was per the Conducted Test Set-up specified in this document.

Limits Transmitter Conducted Spurious and Band-Edge Emissions

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 30 of 76

Equipment Configuration for Conducted Spurious Emissions - Peak

Variant:	GFSK	Duty Cycle (%):	99
Data Rate:	1.00 MBit/s	Antenna Gain (dBi):	Not Applicable
Modulation:	GFSK	Beam Forming Gain (Y):	Not Applicable
TPC:	Not Applicable	Tested By:	SB
Engineering Test Notes:			

Test Measurement Results

Test Frequency	Frequency Range	Conducted Spurious Emissions - Peak (dBm)							
		Port a		Port b		Port c		Port d	
MHz	MHz	SE	Limit	SE	Limit	SE	Limit	SE	Limit
2402.0	30.0 - 26000.0	3.029	-16.97						
2440.0	30.0 - 26000.0	-42.702	-12.09						
2480.0	30.0 - 26000.0	-42.293	-12.63						

Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-05 MEASUREMENT OF SPURIOUS EMISSIONS
Measurement Uncertainty:	<=40 GHz \pm 2.37 dB, > 40 GHz \pm 4.6 dB

Note: click the links in the above matrix to view the graphical image (plot).

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 31 of 76

9.4.1.2. Conducted Band-Edge Emissions

Equipment Configuration for Conducted Low Band-Edge Emissions - Peak

Variant:	GFSK	Duty Cycle (%):	99.0
Data Rate:	1.00 MBit/s	Antenna Gain (dBi):	Not Applicable
Modulation:	GFSK	Beam Forming Gain (Y)(dB):	Not Applicable
TPC:	Not Applicable	Tested By:	SB
Engineering Test Notes:			

Test Measurement Results

Channel Frequency:	2402.0 MHz					
Band-Edge Frequency:	2400.0 MHz					
Test Frequency Range:	2350.0 - 2405.0 MHz					
Port(s)	Band-Edge Markers and Limit			Revised Limit		Margin
	M1 Amplitude (dBm)	Plot Limit (dBm)	M2 Frequency (MHz)	Amplitude (dBm)	M2A Frequency (MHz)	(MHz)
a	-51.70	-16.28	2401.30			-1.300

Traceability to Industry Recognized Test Methodologies	
Work Instruction:	WI-05 MEASUREMENT OF SPURIOUS EMISSIONS
Measurement Uncertainty:	<=40 GHz ±2.37 dB, > 40 GHz ±4.6 dB

Note: click the links in the above matrix to view the graphical image (plot).

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 32 of 76

Equipment Configuration for Conducted High Band-Edge Emissions - Peak

Variant:	GFSK	Duty Cycle (%):	99.0
Data Rate:	1.00 MBit/s	Antenna Gain (dBi):	Not Applicable
Modulation:	GFSK	Beam Forming Gain (Y)(dB):	Not Applicable
TPC:	Not Applicable	Tested By:	SB
Engineering Test Notes:			

Test Measurement Results

Channel Frequency:	2480.0 MHz					
Band-Edge Frequency:	2483.5 MHz					
Test Frequency Range:	2475.0 - 2524.0 MHz					
Port(s)	Band-Edge Markers and Limit			Revised Limit		Margin
	M3 Amplitude (dBm)	Plot Limit (dBm)	M2 Frequency (MHz)	Amplitude (dBm)	M2A Frequency (MHz)	(MHz)
a	-47.78	-11.65	2480.60			-2.900

Traceability to Industry Recognized Test Methodologies

Work Instruction:	WI-05 MEASUREMENT OF SPURIOUS EMISSIONS
Measurement Uncertainty:	<=40 GHz ±2.37 dB, > 40 GHz ±4.6 dB

Note: click the links in the above matrix to view the graphical image (plot).

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 33 of 76

9.4.2. Radiated Emissions

9.4.2.3. TX Spurious & Restricted Band Emissions

Radiated Test Conditions for Radiated Spurious and Band-Edge Emissions (Restricted Bands)			
Standard:	FCC CFR 47 Part 15 Subpart C 15.247 (DTS)	Ambient Temp. (°C):	20.0 - 24.5
Test Heading:	Radiated Spurious and Band-Edge Emissions	Rel. Humidity (%):	32 - 45
Standard Section(s):	15.205, 15.209	Pressure (mBars):	999 - 1001
Reference Document(s):	See Normative References		

Test Procedure for Radiated Spurious and Band-Edge Emissions (Restricted Bands)

Radiated emissions for restricted bands above 1 GHz are measured in the anechoic chamber at a 3-meter distance on every azimuth in both horizontal and vertical polarities. The emissions are recorded and maximized as a function of azimuth by rotation through 360° with a spectrum analyzer in peak hold mode. Depending on the frequency band spanned a notch filter and waveguide filter was used to remove the fundamental frequency. The highest emissions relative to the limit are listed for each frequency spanned. Measurements on any restricted band frequency or frequencies above 1 GHz are based on the use of measurement instrumentation employing peak and average detectors. All measurements were performed using a resolution bandwidth of 1 MHz.

Test configuration and setup for Radiated Spurious and Band-Edge Measurement were per the Radiated Test Set-up specified in this document.

Limits for Restricted Bands

Peak emission: 74 dBuV/m
Average emission: 54 dBuV/m

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Loss, and subtracting Amplifier Gain from the measured reading. All factors are included in the reported data.

$$FS = R + AF + CORR - FO$$

where:

FS = Field Strength
R = Measured Spectrum analyzer Input Amplitude
AF = Antenna Factor
CORR = Correction Factor = CL – AG + NFL
CL = Cable Loss
AG = Amplifier Gain
FO = Distance Falloff Factor
NFL = Notch Filter Loss or Waveguide Loss

Example:

Given receiver input reading of 51.5 dBmV; Antenna Factor of 8.5 dB; Cable Loss of 1.3 dB; Falloff Factor of 0 dB, an Amplifier Gain of 26 dB and Notch Filter Loss of 1 dB. The Field Strength (FS) of the measured emission is:

$$FS = 51.5 + 8.5 + 1.3 - 26.0 + 1 = 36.3 \text{ dBmV/m}$$

Conversion between dBmV/m (or dBmV) and mV/m (or mV) are as follows:

$$\text{Level (dBmV/m)} = 20 * \text{Log (level (mV/m))}$$

$$40 \text{ dBmV/m} = 100 \text{ mV/m}$$

$$48 \text{ dBmV/m} = 250 \text{ mV/m}$$

Restricted Bands of Operation (15.205)

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

Frequency Band

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 34 of 76

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

(b) Except as provided in paragraphs (d) and (e) of this section, the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in §15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in §15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in §15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in §15.35 apply to these measurements.

(c) Except as provided in paragraphs (d) and (e) of this section, regardless of the field strength limits specified elsewhere in this subpart, the provisions of this section apply to emissions from any intentional radiator.

(d) The following devices are exempt from the requirements of this section:

- (1) Swept frequency field disturbance sensors operating between 1.705 and 37 MHz provided their emissions only sweep through the bands listed in paragraph (a) of this section, the sweep is never stopped with the fundamental emission within the bands listed in paragraph (a) of this section, and the fundamental emission is outside of the bands listed in paragraph (a) of this section more than 99% of the time the device is actively transmitting, without compensation for duty cycle.
- (2) Transmitters used to detect buried electronic markers at 101.4 kHz which are employed by telephone companies.
- (3) Cable locating equipment operated pursuant to §15.213.
- (4) Any equipment operated under the provisions of §15.253, 15.255, and 15.256 in the frequency band 75-85 GHz, or §15.257 of this part.
- (5) Biomedical telemetry devices operating under the provisions of §15.242 of this part are not subject to the restricted band 608-614 MHz but are subject to compliance within the other restricted bands.
- (6) Transmitters operating under the provisions of subparts D or F of this part.
- (7) Devices operated pursuant to §15.225 are exempt from complying with this section for the 13.36-13.41 MHz band only.
- (8) Devices operated in the 24.075-24.175 GHz band under §15.245 are exempt from complying with the requirements of this section for the 48.15-48.35 GHz and 72.225-72.525 GHz bands only, and shall not exceed the limits specified in §15.245(b).

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 35 of 76

(9) Devices operated in the 24.0-24.25 GHz band under §15.249 are exempt from complying with the requirements of this section for the 48.0-48.5 GHz and 72.0-72.75 GHz bands only, and shall not exceed the limits specified in §15.249(a).

(e) Harmonic emissions appearing in the restricted bands above 17.7 GHz from field disturbance sensors operating under the provisions of §15.245 shall not exceed the limits specified in §15.245(b).

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 36 of 76

Equipment Configuration for TX Spurious & Restricted Band Emissions

Antenna:	integral	Variant:	GFSK
Antenna Gain (dBi):	2.50	Modulation:	GFSK
Beam Forming Gain (Y):	Not Applicable	Duty Cycle (%):	99
Channel Frequency (MHz):	2402.00	Data Rate:	1.00 MBit/s
Power Setting:	10	Tested By:	JMH

Test Measurement Results

1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	2246.00	64.88	2.63	-12.13	55.38	Max Peak	Vertical	171	268	74.0	-18.6	Pass
#2	2246.00	39.52	2.63	-12.13	30.02	Max Avg	Vertical	171	268	54.0	-24.0	Pass
#3	4803.93	58.23	3.51	-11.12	50.62	Max Peak	Horizontal	102	4	74.0	-23.4	Pass
#4	4803.93	49.74	3.51	-11.12	42.13	Max Avg	Horizontal	102	4	54.0	-11.9	Pass

Test Notes: EUT powered by 5V ps, connected to Laptop via SD slot. 2.4G notch in front of amp to prevent overload

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 37 of 76

Equipment Configuration for TX Spurious & Restricted Band Emissions

Antenna:	integral	Variant:	GFSK
Antenna Gain (dBi):	2.50	Modulation:	GFSK
Beam Forming Gain (Y):	Not Applicable	Duty Cycle (%):	99
Channel Frequency (MHz):	2440.00	Data Rate:	1.00 MBit/s
Power Setting:	10	Tested By:	JMH

Test Measurement Results

1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	2284.01	62.68	2.66	-12.16	53.18	Max Peak	Vertical	180	282	74.0	-20.8	Pass
#2	2284.01	38.08	2.66	-12.16	28.58	Max Avg	Vertical	180	282	54.0	-25.4	Pass
#3	2440.01	55.81	2.72	-11.72	46.81	Fundamental	Vertical	100	0	--	--	
#4	4880.04	59.39	3.61	-11.25	51.75	Max Peak	Horizontal	101	3	74.0	-22.3	Pass
#5	4880.04	51.19	3.61	-11.25	43.55	Max Avg	Horizontal	101	3	54.0	-10.5	Pass
#6	7320.04	51.54	4.26	-7.27	48.53	Max Peak	Horizontal	119	43	74.0	-25.5	Pass
#7	7320.04	38.99	4.26	-7.27	35.98	Max Avg	Horizontal	119	43	54.0	-18.0	Pass

Test Notes: EUT powered by 5V ps, connected to Laptop via SD slot. 2.4G notch in front of amp to prevent overload

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 38 of 76

Equipment Configuration for TX Spurious & Restricted Band Emissions

Antenna:	integral	Variant:	GFSK
Antenna Gain (dBi):	2.50	Modulation:	GFSK
Beam Forming Gain (Y):	Not Applicable	Duty Cycle (%):	99
Channel Frequency (MHz):	2480.00	Data Rate:	1.00 MBit/s
Power Setting:	10	Tested By:	JMH

Test Measurement Results

1000.00 - 18000.00 MHz

Num	Frequency MHz	Raw dB μ V	Cable Loss dB	AF dB	Level dB μ V/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dB μ V/m	Margin dB	Pass /Fail
#1	2479.98	53.07	2.72	-11.65	44.14	Fundamental	Vertical	100	0	--	--	
#2	4960.10	62.55	3.57	-11.49	54.63	Max Peak	Horizontal	115	10	74.0	-19.4	Pass
#3	4960.10	55.07	3.57	-11.49	47.15	Max Avg	Horizontal	115	10	54.0	-6.9	Pass

Test Notes: EUT powered by 5V ps, connected to Laptop via SD slot. 2.4G notch in front of amp to prevent overload

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 39 of 76

Equipment Configuration for TX Spurious & Restricted Band Emissions

Antenna:	YAGEO ANTX300P002B24553	Variant:	GFSK
Antenna Gain (dBi):	0.70	Modulation:	GFSK
Beam Forming Gain (Y):	Not Applicable	Duty Cycle (%):	99
Channel Frequency (MHz):	2402.00	Data Rate:	1.00 MBit/s
Power Setting:	10	Tested By:	JMH

Test Measurement Results

1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	2245.97	62.28	2.64	-12.14	52.78	Max Peak	Vertical	158	68	74.0	-21.2	Pass
#2	2245.97	38.29	2.64	-12.14	28.79	Max Avg	Vertical	158	68	54.0	-25.2	Pass

Test Notes: EUT powered by 5V ps, connected to Laptop via SD slot. 2.4G notch in front of amp to prevent overload.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 40 of 76

Equipment Configuration for TX Spurious & Restricted Band Emissions

Antenna:	YAGEO ANTX300P002B24553	Variant:	GFSK
Antenna Gain (dBi):	0.70	Modulation:	GFSK
Beam Forming Gain (Y):	Not Applicable	Duty Cycle (%):	99
Channel Frequency (MHz):	2440.00	Data Rate:	1.00 MBit/s
Power Setting:	10	Tested By:	JMH

Test Measurement Results

1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	2439.73	55.03	2.72	-11.72	46.03	Fundamental	Vertical	100	0	--	--	

Test Notes: EUT powered by 5V ps, connected to Laptop via SD slot. 2.4G notch in front of amp to prevent overload.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 41 of 76

Equipment Configuration for TX Spurious & Restricted Band Emissions

Antenna:	YAGEO ANTX300P002B24553	Variant:	GFSK
Antenna Gain (dBi):	0.70	Modulation:	GFSK
Beam Forming Gain (Y):	Not Applicable	Duty Cycle (%):	99
Channel Frequency (MHz):	2480.00	Data Rate:	1.00 MBit/s
Power Setting:	10	Tested By:	JMH

Test Measurement Results

1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	2479.86	53.04	2.72	-11.65	44.11	Fundamental	Vertical	151	0	--	--	

Test Notes: EUT powered by 5V ps, connected to Laptop via SD slot. 2.4G notch in front of amp to prevent overload.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 42 of 76

9.4.2.4. Restricted Edge & Band-Edge Emissions

Lower Band Edge.

integral		Band-Edge Freq	Limit 74.0dB μ V/m	Limit 54.0dB μ V/m	Power Setting
Operational Mode	Operating Frequency (MHz)	MHz	dB μ V/m	dB μ V/m	
GFSK	2402.00	2390.00	67.43	39.44	10

YAGEO ANTX300P002B24553		Band-Edge Freq	Limit 74.0dB μ V/m	Limit 54.0dB μ V/m	Power Setting
Operational Mode	Operating Frequency (MHz)	MHz	dB μ V/m	dB μ V/m	
GFSK	2402.00	2390.00	59.71	38.41	10

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 43 of 76

Equipment Configuration for Radiated - Lower Restricted Band-Edge Emissions

Antenna:	integral	Variant:	GFSK
Antenna Gain (dBi):	2.50	Modulation:	GFSK
Beam Forming Gain (Y):	Not Applicable	Duty Cycle (%):	99
Channel Frequency (MHz):	2402.00	Data Rate:	1.00 MBit/s
Power Setting:	10	Tested By:	JMH

Test Measurement Results

2310.00 - 2422.00 MHz

Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	2315.16	5.05	2.67	31.72	39.44	Max Avg	Vertical	159	342	54.0	-14.6	Pass
#2	2387.88	32.72	2.68	32.03	67.43	Max Peak	Vertical	159	342	74.0	-6.6	Pass
#3	2390.00	--	--	--	--	Restricted-Band	--	--	--	--	--	--

Test Notes: EUT powered by 5V ps, connected to Laptop via SD slot.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 44 of 76

Equipment Configuration for Radiated - Lower Restricted Band-Edge Emissions

Antenna:	YAGEO ANTX300P002B24553	Variant:	GFSK
Antenna Gain (dBi):	0.70	Modulation:	GFSK
Beam Forming Gain (Y):	Not Applicable	Duty Cycle (%):	99
Channel Frequency (MHz):	2402.00	Data Rate:	1.00 MBit/s
Power Setting:	10	Tested By:	JMH

Test Measurement Results

2310.00 - 2422.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#1	2314.49	4.02	2.67	31.72	38.41	Max Avg	Vertical	171	320	54.0	-15.6	Pass
#2	2384.52	25.03	2.68	32.00	59.71	Max Peak	Vertical	171	320	74.0	-14.3	Pass
#3	2390.00	--	--	--	--	Restricted-Band	--	--	--	--	--	--

Test Notes: EUT powered by 5V ps, connected to Laptop via SD slot.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 45 of 76

Upper Band Edge

integral		Band-Edge Freq	Limit 74.0dB μ V/m	Limit 54.0dB μ V/m	Power Setting
Operational Mode	Operating Frequency (MHz)	MHz	dB μ V/m	dB μ V/m	
GFSK	2480.00	2483.50	62.45	42.91	10

YAGEO ANTX300P002B24553		Band-Edge Freq	Limit 74.0dB μ V/m	Limit 54.0dB μ V/m	Power Setting
Operational Mode	Operating Frequency (MHz)	MHz	dB μ V/m	dB μ V/m	
GFSK	2480.00	2483.50	57.60	42.18	10

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 46 of 76

Equipment Configuration for Radiated - Upper Restricted Band-Edge Emissions

Antenna:	integral	Variant:	GFSK
Antenna Gain (dBi):	2.50	Modulation:	GFSK
Beam Forming Gain (Y):	Not Applicable	Duty Cycle (%):	99
Channel Frequency (MHz):	2480.00	Data Rate:	1.00 MBit/s
Power Setting:	10	Tested By:	JMH

Test Measurement Results

2452.00 - 2520.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#2	2483.89	27.35	2.73	32.37	62.45	Max Peak	Vertical	136	316	74.0	-11.6	Pass
#3	2487.43	7.81	2.73	32.37	42.91	Max Avg	Vertical	136	316	54.0	-11.1	Pass
#1	2483.50	--	--	--	--	Restricted-Band	--	--	--	--	--	--

Test Notes: EUT powered by 5V ps, connected to Laptop via SD slot.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 47 of 76

Equipment Configuration for Radiated - Upper Restricted Band-Edge Emissions

Antenna:	YAGEO ANTX300P002B24553	Variant:	GFSK
Antenna Gain (dBi):	Not Applicable	Modulation:	GFSK
Beam Forming Gain (Y):	Not Applicable	Duty Cycle (%):	99
Channel Frequency (MHz):	2480.00	Data Rate:	1.00 MBit/s
Power Setting:	10	Tested By:	JMH

Test Measurement Results

2452.00 - 2520.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
#2	2483.75	22.52	2.73	32.35	57.60	Max Peak	Vertical	175	341	74.0	-16.4	Pass
#3	2487.43	7.08	2.73	32.37	42.18	Max Avg	Vertical	175	341	54.0	-11.8	Pass
#1	2483.50	--	--	--	--	Restricted-Band	--	--	--	--	--	--

Test Notes: EUT powered by 5V ps, connected to Laptop via SD slot.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 48 of 76

9.4.3. Digital Emissions (0.03 - 1 GHz)

Equipment Configuration for Radiated Digital Emissions

Antenna:	Yangeo	Variant:	BLE
Antenna Gain (dBi):	Not Applicable	Modulation:	
Beam Forming Gain (Y):	Not Applicable	Duty Cycle (%):	
Channel Frequency (MHz):	2439.00	Data Rate:	1 MBit/s
Power Setting:	10	Tested By:	JMH

Test Measurement Results

[Click here to view measurement data...](#)

Test Notes: EUT powered by 5V ps, connected to Laptop via SD slot. Laptop put in suspend mode to limit 50 MHz harmonics.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 49 of 76

A. APPENDIX - GRAPHICAL IMAGES

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



A.1. 6 dB & 99% Bandwidth



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = POS Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAXH	M1 : 2401.657 MHz : -2.098 dBm M2 : 2401.997 MHz : 3.808 dBm Delta1 : 667 KHz : 0.323 dB T1 : 2401.467 MHz : -9.474 dBm T2 : 2402.527 MHz : -9.543 dBm OBW : 1.065 MHz	Measured 6 dB Bandwidth: 0.667 MHz Limit: ≥500.0 kHz Margin: -0.17 MHz


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



6 dB & 99% BANDWIDTH

Variant: GFSK, Channel: 2440.00 MHz, Chain a, Temp: 20, Voltage: 3.3 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 2439.609 MHz : 2.677 dBm M2 : 2439.978 MHz : 8.815 dBm Delta1 : 697 KHz : 0.454 dB T1 : 2439.453 MHz : -4.431 dBm T2 : 2440.515 MHz : -4.911 dBm OBW : 1.062 MHz	Measured 6 dB Bandwidth: 0.697 MHz Limit: ≥500.0 kHz Margin: -0.20 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 52 of 76



6 dB & 99% BANDWIDTH

Variant: GFSK, Channel: 2480.00 MHz, Chain a, Temp: 20, Voltage: 3.3 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = MAX HOLD	M1 : 2479.613 MHz : 2.261 dBm M2 : 2479.978 MHz : 8.356 dBm Delta1 : 693 KHz : 0.527 dB T1 : 2479.449 MHz : -5.026 dBm T2 : 2480.519 MHz : -5.557 dBm OBW : 1.070 MHz	Measured 6 dB Bandwidth: 0.693 MHz Limit: ≥500.0 kHz Margin: -0.19 MHz


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 53 of 76

A.2. Power Spectral Density



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = POS Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2401.998 MHz : 4.784 dBm	Limit: ≤ 8.000 dBm Margin: -3.22 dB

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 54 of 76



POWER SPECTRAL DENSITY - PEAK

Variant: GFSK, Channel: 2402.00 MHz, SUM, Temp: 20, Voltage: 3.3 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = POS Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEWS	M1 : 2401.998 MHz : 4.784 dBm	Limit: ≤ 8.0 dBm Margin: -3.2 dB

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 55 of 76

POWER SPECTRAL DENSITY - PEAK



Variant: GFSK, Channel: 2440.00 MHz, Chain a, Temp: 20, Voltage: 3.3 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEWS	M1 : 2439.998 MHz : 7.552 dBm	Limit: ≤ 8.000 dBm Margin: -0.45 dB

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 56 of 76



POWER SPECTRAL DENSITY - PEAK

Variant: GFSK, Channel: 2440.00 MHz, SUM, Temp: 20, Voltage: 3.3 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEWS	M1 : 2439.998 MHz : 7.552 dBm	Limit: ≤ 8.0 dBm Margin: -0.4 dB

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 57 of 76

POWER SPECTRAL DENSITY - PEAK



Variant: GFSK, Channel: 2480.00 MHz, Chain a, Temp: 20, Voltage: 3.3 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEWS	M1 : 2479.998 MHz : 6.717 dBm	Limit: ≤ 8.000 dBm Margin: -1.28 dB

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 58 of 76

POWER SPECTRAL DENSITY - PEAK



Variant: GFSK, Channel: 2480.00 MHz, SUM, Temp: 20, Voltage: 3.3 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEWS	M1 : 2479.998 MHz : 6.717 dBm	Limit: ≤ 8.0 dBm Margin: -1.3 dB

[back to matrix](#)


This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



A.3. Emissions

A.3.1. Conducted Emissions

A.3.1.1. Conducted Spurious Emissions



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2371.984 MHz : 3.029 dBm M2 : 2371.984 MHz : 3.029 dBm	Limit: -16.97 dBm Margin: 20.00 dB

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 60 of 76

CONDUCTED SPURIOUS EMISSIONS - PEAK



Variant: GFSK, Channel: 2402.00 MHz, Chain a, Temp: 20, Voltage: 3.3 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEWS	M1 : 2371.984 MHz : 9.177 dBm M2 : 6899.820 MHz : -43.355 dBm	Channel Frequency: 2402.00 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 61 of 76

CONDUCTED SPURIOUS EMISSIONS - PEAK



Variant: GFSK, Channel: 2440.00 MHz, Chain a, Temp: 20, Voltage: 3.3 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEWS	M1 : 2424.028 MHz : 7.910 dBm M2 : 6639.599 MHz : -42.702 dBm	Limit: -12.09 dBm Margin: -30.61 dB

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 62 of 76

CONDUCTED SPURIOUS EMISSIONS - PEAK



Variant: GFSK, Channel: 2480.00 MHz, Chain a, Temp: 20, Voltage: 3.3 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEWS	M1 : 2476.072 MHz : 7.369 dBm M2 : 6535.511 MHz : -42.293 dBm	Limit: -12.63 dBm Margin: -29.66 dB


[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 63 of 76

A.3.1.2. Conducted Band-Edge Emissions



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = POS Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2400.000 MHz : -51.697 dBm M2 : 2401.330 MHz : -18.721 dBm M3 : 2401.980 MHz : 3.721 dBm	Channel Frequency: 2402.00 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 64 of 76

CONDUCTED HIGH BAND-EDGE EMISSION - PEAK



Variant: GFSK, Channel: 2480.00 MHz, Chain a, Temp: 20, Voltage: 3.3 Vdc



Analyzer Setup	Marker:Frequency:Amplitude	Test Results
Detector = MAX PEAK Sweep Count = 0 RF Atten (dB) = 20 Trace Mode = VIEW	M1 : 2480.008 MHz : 8.346 dBm M2 : 2480.597 MHz : -9.905 dBm M3 : 2483.500 MHz : -47.780 dBm	Channel Frequency: 2480.00 MHz

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




A.3.2. Radiated Emissions

A.3.2.3. TX Spurious & Restricted Band Emissions



TX SPURIOUS & RESTRICTED BAND EMISSIONS

Variant: GFSK, Test Freq: 2402.00 MHz, Antenna: integral, Power Setting: 10, Duty Cycle (%): 99



1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	2246.00	64.88	2.63	-12.13	55.38	Max Peak	Vertical	171	268	74.0	-18.6	Pass
2	2246.00	39.52	2.63	-12.13	30.02	Max Avg	Vertical	171	268	54.0	-24.0	Pass
3	4803.93	58.23	3.51	-11.12	50.62	Max Peak	Horizontal	102	4	74.0	-23.4	Pass
4	4803.93	49.74	3.51	-11.12	42.13	Max Avg	Horizontal	102	4	54.0	-11.9	Pass

Test Notes: EUT powered by 5V ps, connected to Laptop via SD slot. 2.4G notch in front of amp to prevent overload

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 66 of 76



TX SPURIOUS & RESTRICTED BAND EMISSIONS

Variant: GFSK, Test Freq: 2440.00 MHz, Antenna: integral, Power Setting: 10, Duty Cycle (%): 99



1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	2284.01	62.68	2.66	-12.16	53.18	Max Peak	Vertical	180	282	74.0	-20.8	Pass
2	2284.01	38.08	2.66	-12.16	28.58	Max Avg	Vertical	180	282	54.0	-25.4	Pass
3	2440.01	55.81	2.72	-11.72	46.81	Fundamental	Vertical	100	0	--	--	
4	4880.04	59.39	3.61	-11.25	51.75	Max Peak	Horizontal	101	3	74.0	-22.3	Pass
5	4880.04	51.19	3.61	-11.25	43.55	Max Avg	Horizontal	101	3	54.0	-10.5	Pass
6	7320.04	51.54	4.26	-7.27	48.53	Max Peak	Horizontal	119	43	74.0	-25.5	Pass
7	7320.04	38.99	4.26	-7.27	35.98	Max Avg	Horizontal	119	43	54.0	-18.0	Pass

Test Notes: EUT powered by 5V ps, connected to Laptop via SD slot. 2.4G notch in front of amp to prevent overload

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 67 of 76



TX SPURIOUS & RESTRICTED BAND EMISSIONS

Variant: GFSK, Test Freq: 2480.00 MHz, Antenna: integral, Power Setting: 10, Duty Cycle (%): 99



1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	2479.98	53.07	2.72	-11.65	44.14	Fundamental	Vertical	100	0	--	--	
2	4960.10	62.55	3.57	-11.49	54.63	Max Peak	Horizontal	115	10	74.0	-19.4	Pass
3	4960.10	55.07	3.57	-11.49	47.15	Max Avg	Horizontal	115	10	54.0	-6.9	Pass

Test Notes: EUT powered by 5V ps, connected to Laptop via SD slot. 2.4G notch in front of amp to prevent overload

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 68 of 76



TX SPURIOUS & RESTRICTED BAND EMISSIONS

Variant: GFSK, Test Freq: 2402.00 MHz, Antenna: YAGEO ANTX300P002B24553, Power Setting: 10, Duty Cycle (%): 99



1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	2245.97	62.28	2.64	-12.14	52.78	Max Peak	Vertical	158	68	74.0	-21.2	Pass
2	2245.97	38.29	2.64	-12.14	28.79	Max Avg	Vertical	158	68	54.0	-25.2	Pass

Test Notes: EUT powered by 5V ps, connected to Laptop via SD slot. 2.4G notch in front of amp to prevent overload.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 69 of 76

TX SPURIOUS & RESTRICTED BAND EMISSIONS



Variant: GFSK, Test Freq: 2440.00 MHz, Antenna: YAGEO ANTX300P002B24553, Power Setting: 10, Duty Cycle (%): 99



1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	2439.73	55.03	2.72	-11.72	46.03	Fundamental	Vertical	100	0	--	--	

Test Notes: EUT powered by 5V ps, connected to Laptop via SD slot. 2.4G notch in front of amp to prevent overload.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 70 of 76



TX SPURIOUS & RESTRICTED BAND EMISSIONS

Variant: GFSK, Test Freq: 2480.00 MHz, Antenna: YAGEO ANTX300P002B24553, Power Setting: 10, Duty Cycle (%): 99



1000.00 - 18000.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	2479.86	53.04	2.72	-11.65	44.11	Fundamental	Vertical	151	0	--	--	

Test Notes: EUT powered by 5V ps, connected to Laptop via SD slot. 2.4G notch in front of amp to prevent overload.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




A.3.2.4. Restricted Edge & Band-Edge Emissions



RADIATED - LOWER RESTRICTED BAND-EDGE EMISSIONS

Variant: GFSK, Test Freq: 2402.00 MHz, Antenna: integral, Power Setting: 10, Duty Cycle (%): 99



2310.00 - 2422.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	2315.16	5.05	2.67	31.72	39.44	Max Avg	Vertical	159	342	54.0	-14.6	Pass
2	2387.88	32.72	2.68	32.03	67.43	Max Peak	Vertical	159	342	74.0	-6.6	Pass
3	2390.00	--	--	--	--	Restricted-Band	--	--	--	--	--	--

Test Notes: EUT powered by 5V ps, connected to Laptop via SD slot.

[back to matrix](#)



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 72 of 76




RADIATED - LOWER RESTRICTED BAND-EDGE EMISSIONS

Variant: GFSK, Test Freq: 2402.00 MHz, Antenna: YAGEO ANT X300P002B24553, Power Setting: 10, Duty Cycle (%): 99

Measurement Distance: 3m

Sweep Time: 10.0 s

RBW: 1 MHz
VBW: 3 MHz



2310.00 - 2422.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
1	2314.49	4.02	2.67	31.72	38.41	Max Avg	Vertical	171	320	54.0	-15.6	Pass
2	2384.52	25.03	2.68	32.00	59.71	Max Peak	Vertical	171	320	74.0	-14.3	Pass
3	2390.00	--	--	--	--	Restricted-Band	--	--	--	--	--	--

Test Notes: EUT powered by 5V ps, connected to Laptop via SD slot.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 73 of 76



RADIATED - UPPER RESTRICTED BAND-EDGE EMISSIONS

Variant: GFSK, Test Freq: 2480.00 MHz, Antenna: integral, Power Setting: 10, Duty Cycle (%): 99



2452.00 - 2520.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
2	2483.89	27.35	2.73	32.37	62.45	Max Peak	Vertical	136	316	74.0	-11.6	Pass
3	2487.43	7.81	2.73	32.37	42.91	Max Avg	Vertical	136	316	54.0	-11.1	Pass
1	2483.50	--	--	--	--	Restricted-Band	--	--	--	--	--	--

Test Notes: EUT powered by 5V ps, connected to Laptop via SD slot.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 74 of 76

RADIATED - UPPER RESTRICTED BAND-EDGE EMISSIONS




Variant: GFSK, Test Freq: 2480.00 MHz, Antenna: YAGEO ANT X300P002B24553, Power Setting: 10, Duty Cycle (%): 99

Measurement Distance: 3m

Sweep Time: 10.0 s

RBW: 1 MHz
VBW: 3 MHz

Date: 09 Aug 2017 -



2452.00 - 2520.00 MHz												
Num	Frequency MHz	Raw dBµV	Cable Loss dB	AF dB	Level dBµV/m	Measurement Type	Pol	Hgt cm	Azt Deg	Limit dBµV/m	Margin dB	Pass /Fail
2	2483.75	22.52	2.73	32.35	57.60	Max Peak	Vertical	175	341	74.0	-16.4	Pass
3	2487.43	7.08	2.73	32.37	42.18	Max Avg	Vertical	175	341	54.0	-11.8	Pass
1	2483.50	--	--	--	--	Restricted-Band	--	--	--	--	--	--

Test Notes: EUT powered by 5V ps, connected to Laptop via SD slot.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.




Title: HP Inc. 0960-4025 and 0960-4034
To: FCC 15.247 (DTS) & IC RSS-247
Serial #: MARS11-U2 BLE Rev B WiFi/BT Module
Issue Date: 27th October 2017
Page: 75 of 76

A.3.3. Digital Emissions (0.03 - 1 GHz)



Variant: FHSS, Test Freq: 2439.00 MHz, Power Setting: 10



There are no emissions found within 6dB of the limit line.

Test Notes: EUT powered by 5V ps, connected to Laptop via SD slot. Laptop put in suspend mode to limit 50 MHz harmonics.

[back to matrix](#)

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



575 Boulder Court
Pleasanton, California 94566, USA
Tel: +1 (925) 462 0304
Fax: +1 (925) 462 0306
www.micomlabs.com