

**CETECOM Inc.**



**CETECOM Inc.**

411 Dixon Landing Road, Milpitas, CA-95035, USA  
Phone: +1 408 586 6200 Fax: +1 408 586 6299  
www.cetecom.com

---

Issued test report consists of 50 Pages

Page 1 (50)

---

**FCC LISTED, REG. NO.: 101450  
&  
RECOGNIZED BY INDUSTRY CANADA  
IC – 3925**

**Test report no.:173FCC/2001\_2BT  
FCC Part 15.247  
FCC ID: B94xt1000bt  
(HP Omnibook xt1000)**

**Table of Contents**

**1 General information**

**1.1 Notes**

**1.2 Testing laboratory**

**1.3 Details of applicant**

**1.4 Application details**

**1.5 Test item**

**1.6 Test standards**

**2 Technical test**

**2.1 Summary of test results**

**2.2 Test report**

**1 General information**

**1.1 Notes**

The test results of this test report relate exclusively to the test item specified in 1.5. The CETECOM Inc. USA does not assume responsibility for any conclusions and generalisations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of the CETECOM Inc USA.

**TEST REPORT PREPARED BY:**

**EMC & Radio Engineer: Harpreet Sidhu**

**1.2 Testing laboratory**

**CETECOM Inc.**

411 Dixon Landing Road, Milpitas, CA-95035, USA

Phone: +1 408 586 6200 Fax: +1 408 586 6299

E-mail: [lothar.schmidt@cetecomusa.com](mailto:lothar.schmidt@cetecomusa.com)

Internet: [www.cetecom.com](http://www.cetecom.com)

**1.3 Details of applicant**

Name : Hewlett Packard  
Street : 19310 Pruneridge Ave.  
City : Cupertino CA  
Country : USA  
Contact : Richard Barbin  
Telephone : 408 343 7972  
Telefax : 408 343 7366  
e-mail : [richard\\_barbin@hp.com](mailto:richard_barbin@hp.com)

:

**1.4 Application details**

Date of receipt of application : 2001-07-10  
Date of receipt of test item : 2001-10-01  
Date of test : 2001-10-01/02/04

**1.5 Test item**

Manufacturer : 3 COM  
Name of EUT : SL-1021 installed into HP Omnibook xt1000  
**Description** : [Bluetooth wireless Module](#)  
Model No. : SL-1021  
Serial No. : N/A  
FCC ID : B94xt1000BT

**Additional information**

Frequency : 2.4 – 2.48 GHz  
Type of modulation : Bluetooth Standard  
Number of channels : 79  
Antenna : Internal  
Power supply : 5V  
Output power : 0 dBm  
Extreme Vol. Limits :  
Extreme Temp. Limits : 0°C - +40°C

**1.6 Test standards: FCC Part 15 §15.247**

**2      Technical test**

**2.1      Summary of test results**

**No deviations from the technical specification(s) were ascertained in the course of the tests performed.**

**Technical responsibility for area of testing :**

**2001-11-07**

**EMC & Radio**

**Lothar Schmidt**



---

**Date**

**Section**

**Name**

**Signature**

**2.2 Testreport**

**TEST REPORT**

**Test report no. : 173FCC/2001\_2BT**  
**FCC ID: B94xt1000BT**  
**(HP Omnibook xt1000)**

**TEST REPORT REFERENCE**

**LIST OF MEASUREMENTS**

<b>Paragraph</b>	<b>PARAMETER TO BE MEASURED</b>	<b>PAGE</b>
	<b>Transmitter parameters</b>	
§ 15.204	Antenna gain	7
§ 15.247 (a)	Carrier frequency separation	8
§ 15.247 (a)	Number of hopping channels	9
§ 15.247 (a)	Time of occupancy (dwell time)	13
§ 15.247 (a)(1)	Spectrum Bandwidth of a FHSS System	16
§ 15.247 (b)(2)	Maximum peak output power	20
§15.247	Band edge compliance	28
§ 15.247 (c)(1)	Emission limitations	30
§ 15.107/207	AC Line Conducted Emission	43
	<b>Receiver parameters</b>	
§ 15.209	Spurious radiations - Radiated	45
	Test equipment listing	50

**Antenna Gain**


**SUBCLAUSE § 15.204**

**The max gain is +1.2dBi**

**(measured effective radiated power – measured conducted power with a temporary RF-connector)**

CARRIER FREQUENCY SEPERATION

§15.247(a)




Date: 4.OCT.01 20:22:07

NUMBER OF HOPPING CHANNELS

§15.247(a)


The number of hopping channels is 79 (see next 4 plots)  
 The right red line corresponds to the left red line from the next plot.

Plot 1: Total 23




Date: 4.OCT.01 20:28:27

Plot 2: Total 25




Date: 4.OCT.01 20:35:41

Plot 3: Total 19



Plot 4: Total 12




TIME OF OCCUPANCY (DWELL TIME) FOR DH1

§15.247(a)

The system makes worst case 1600 hops per second or 1 time slot has a length of 625µs with 79 channels. A DH1 Packet need 1 time slot for transmitting and 1 time slot for receiving. Then the system makes worst case 800 hops per second with 79 channels. So you have each channel 10.13 times per second and so for 30 seconds you have 303.9 times of appearance .

Each Tx-time per appearance is 376.75 µs.

So we have 303.9 \* 376.75 µs = 114.49 ms per 30 seconds.



Date: 4.OCT.01 21:49:03


TIME OF OCCUPANCY (DWELL TIME) FOR DH3

§15.247(a)

A DH3 Packets need 3 time slots for transmit and 1 for receiving, then the system makes worst case 400 hops per second with 79 channels. So you have each channel 5.1 times per second and so for 30 seconds you have 153 times of appearance .

Each Tx-time per appearance is 1.65 ms.

So we have 153 \* 1.65 ms = 252.45 ms per 30 seconds.



Date: 4.OCT.01 21:52:50


TIME OF OCCUPANCY (DWELL TIME) FOR DH5

§15.247(a)

At DH5 Packets you need 5 time slots for transmit and 1 for receiving, then the system makes worst case 266,7 hops per second with 79 channels. So you have each channel 3.36 times per second and so for 30 seconds you have 100,8 times of appearance .

Each tx-time per appearance is 2.89 ms.

So we have 100.8 \* 2.89ms = 291.31 ms per 30 seconds.



**SPECTRUM BANDWIDTH OF FHSS SYSTEM**  
**20 dB bandwidth**

§15.247(a)

TEST CONDITIONS		20 dB BANDWIDTH ( kHz )		
		2402	2441	2480
Frequency (MHz)				
T <sub>nom</sub> ( 23 )° C	V <sub>nom</sub> (5)V	885.77	993.46	868.73
Measurement uncertainty		±3dB		

RBW / VBW as provided in the "Measurement Guidelines" (DA 00-705, March 30, 2000)

**LIMIT**


**SUBCLAUSE §15.247(a) (1)**

The maximum 20dB bandwidth shall be at maximum 1000 KHz

SPECTRUM BANDWIDTH OF FHSS SYSTEM  
20 dB bandwidth

§15.247(a)


Lowest Channel: 2402MHz



**SPECTRUM BANDWIDTH OF FHSS SYSTEM**  
**20 dB bandwidth**

§15.247(a)

**Mid Channel: 2441MHz**




Date: 2.OCT.01 22:30:32

SPECTRUM BANDWIDTH OF FHSS SYSTEM  
20 dB bandwidth

§15.247(a)

Highest Channel: 2480MHz



**MAXIMUM PEAK OUTPUT POWER  
(conducted)**

**SUBCLAUSE § 15.247 (b) (1)**

TEST CONDITIONS		MAXIMUM PEAK OUTPUT POWER (dBm)			
		2402		2441	2480
Frequency (MHz)					
T <sub>nom</sub> ( 23 ) °C	V <sub>nom</sub> (5)V	PK	2.54	3.21	4.39
Measurement uncertainty		±3dB			

**RBW / VBW : 3 MHz**

**LIMIT**


**SUBCLAUSE § 15.247 (b) (1)**

Frequency range	RF power output
2400-2483.5 MHz	1.0 Watt

PEAK OUTPUT POWER (CONDUCTED)

§15.247 (b)


Lowest Channel: 2402MHz



PEAK OUTPUT POWER (CONDUCTED)

§15.247 (b)


Mid Channel: 2441MHz



PEAK OUTPUT POWER (CONDUCTED)

§15.247 (b)

Highest Channel: 2480MHz



**MAXIMUM PEAK OUTPUT POWER  
(RADIATED)**

**SUBCLAUSE § 15.247 (b) (1)**

**EIRP:**

TEST CONDITIONS		MAXIMUM PEAK OUTPUT POWER (dBm)		
		2402	2441	2480
Frequency (MHz)				
T <sub>nom</sub> (23) °C	V <sub>nom</sub> (5)V	4.71	5.50	3.51
Measurement uncertainty		±3dB		

**RBW/VBW : 3 MHz**

**LIMIT**

**SUBCLAUSE § 15.247 (b) (1)**


Frequency range	RF power output
2400-2483.5 MHz	1.0 Watt

**PEAK OUTPUT POWER (RADIATED)**

**§15.247 (b) (1)**

**Lowest Channel: 2402MHz**

**ANALYZER SETTINGS: RBW = 3MHz    VBW = 3MHz**




**PEAK OUTPUT POWER (RADIATED)**

§15.247 (b) (1)

Mid Channel: 2441MHz

ANALYZER SETTINGS: RBW = 3MHz    VBW = 3MHz




**PEAK OUTPUT POWER (RADIATED)**

§15.247 (b) (1)

**Highest Channel: 2480MHz**


**ANALYZER SETTINGS: RBW = 3MHz    VBW = 3MHz**



BAND EDGE COMPLIANCE

§15.247 (c)

Low frequency section  
(valid for both hopping ON & OFF)




Date: 2.OCT.01 22:13:11

**BAND EDGE COMPLIANCE**

§15.247 (c)

high frequency section  
(valid for both hopping ON & OFF)



ANALYZER SETTINGS: RBW = 100KHz    VBW = 200KHz

**EMISSION LIMITATIONS - Conducted (Transmitter)**

**§ 15.247 (c) (1)**

**LIMITS**


**In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).**

**NOTE: Frequency resolution is not fine enough to show the exact frequency of the carrier, refer to plots under EIRP.**

EMISSION LIMITATIONS - Conducted (Transmitter)

§ 15.247 (c) (1)

Lowest Channel(2402MHz): 30MHz - 25 GHz




NOTE: The peak above the limit is the carrier frequency.

EMISSION LIMITATIONS - Conducted (Transmitter)

§ 15.247 (c) (1)

Mid Channel(2441MHz): 30MHz - 25GHz




NOTE: The peak above the limit is the carrier frequency.

EMISSION LIMITATIONS - Conducted (Transmitter)

§ 15.247 (c) (1)

Highest Channel(2480MHz): 30MHz - 25GHz



NOTE: The peak above the limit is the carrier frequency.

**EMISSION LIMITATIONS - Radiated (Transmitter)**

**SUBCLAUSE § 15.247 (c) (1)**

**LIMITS**

**In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).**

**NOTE:**

**1. The radiated emissions were done with different settings, using the relevant pre-amplifiers for the relevant frequency ranges. This is the reason that the graphs show different noise levels. In the range between 18 and 25 GHz very short cable connections to the antenna was used to minimize the noise level.**

**2. Frequency resolution is not fine enough to show the exact frequency of the carrier, refer to plots under EIRP.**


**Results for the radiated measurements below 30MHz according § 15.33**

<b>Frequency</b>	<b>Measured values</b>	<b>Remarks</b>
10KHz-30MHz	No emissions found, caused by the EUT	This is valid for all the tested channels

**EMISSION LIMITATIONS - Radiated (Transmitter)**

**SUBCLAUSE § 15.247 (c) (1)**

**Lowest Channel(2402MHz): 30MHz – 1GHz**




**ANALYZER SETTINGS: RBW = 100KHz    VBW = 100KHz**

EMISSION LIMITATIONS - Radiated (Transmitter)

SUBCLAUSE § 15.247 (c) (1)

Lowest Channel(2402MHz): 1GHz – 8GHz

NOTE: The peak above the limit is the carrier frequency.




ANALYZER SETTINGS: RBW = 1MHz    VBW = 1MHz

EMISSION LIMITATIONS - Radiated (Transmitter)

SUBCLAUSE § 15.247 (c) (1)

Mid Channel(2441MHz): 30MHz – 1GHz




ANALYZER SETTINGS: RBW = 100KHz    VBW = 100KHz



**EMISSION LIMITATIONS - Radiated (Transmitter)**

**SUBCLAUSE § 15.247 (c) (1)**

**Highest Channel(2480MHz): 30MHz – 1GHz**




**ANALYZER SETTINGS: RBW = 100KHz    VBW = 100KHz**

EMISSION LIMITATIONS - Radiated (Transmitter)

SUBCLAUSE § 15.247 (c) (1)

Highest Channel: 1GHz – 8GHz

NOTE: The peak above the limit is the carrier frequency.




ANALYZER SETTINGS: RBW = 1MHz    VBW = 1MHz

**EMISSION LIMITATIONS - Radiated (Transmitter)**

**SUBCLAUSE § 15.247 (c) (1)**

**8GHz – 18GHz**

**(This plot is valid for all three channels)**




**ANALYZER SETTINGS: RBW = 1MHz    VBW = 1MHz**

**EMISSION LIMITATIONS - Radiated (Transmitter)**

**SUBCLAUSE § 15.247 (c) (1)**

**18GHz – 25GHz**

**(This plot is valid for all three channels)**




**ANALYZER SETTINGS: RBW = 1MHz    VBW = 1MHz**

**CONDUCTED EMISSIONS**

§ 15.107/207

Measured with AC/DC power adapter

**Phase: Line**




**Technical specification: 15.107 / 15.207 (Revised as of October 1, 1991)**

**Limit**

0.45 to 30 MHz	250 $\mu$ V / 47.96dB $\mu$ V
----------------	-------------------------------

ANALYZER SETTINGS: RBW = 10KHz      VBW = 10KHz

Phase: Neutral



Technical specification: 15.107 / 15.207 (Revised as of October 1, 1991)

**Limit**

0.45 to 30 MHz	250 $\mu$ V / 47.96dB $\mu$ V
----------------	-------------------------------

ANALYZER SETTINGS: RBW = 10KHz VBW = 10KHz

**RECEIVER SPURIOUS RADIATION****§ 15.209****Limits**

<b>Frequency (MHz)</b>	<b>Field strength (<math>\mu\text{V}/\text{m}</math>)</b>	<b>Measurement distance (m)</b>
<b>0.009 - 0.490</b>	<b>2400/F(kHz)</b>	<b>300</b>
<b>0.490 - 1.705</b>	<b>24000/F(kHz)</b>	<b>30</b>
<b>1.705 - 30.0</b>	<b>30</b>	<b>30</b>
<b>30 - 88</b>	<b>100</b>	<b>3</b>
<b>88 - 216</b>	<b>150</b>	<b>3</b>
<b>216 - 960</b>	<b>200</b>	<b>3</b>
<b>above 960</b>	<b>500</b>	<b>3</b>

**NOTE:**


- 1. The radiated emissions were done with different settings, using the relevant pre-amplifiers for the relevant frequency ranges. This is the reason that the graphs show different noise levels. In the range between 18 and 25 GHz very short cable connections to the antenna was used to minimize the noise level.**
- 2. Measurements were done on low, mid & high channels, but plots depicting the worst case are submitted in the test report.**

**RECEIVER SPURIOUS RADIATION**

**§ 15.209**

**30MHz – 1GHz**

**(This plot is valid for all three channels)**




**ANALYZER SETTINGS: RBW = 100KHz    VBW = 100KHz**

RECEIVER SPURIOUS RADIATION

§ 15.209

1GHz – 8GHz

(This plot is valid for all three channels)




ANALYZER SETTINGS: RBW = 1MHz    VBW = 1MHz

RECEIVER SPURIOUS RADIATION

§ 15.209

8GHz – 18GHz

(This plot is valid for all three channels)




ANALYZER SETTINGS: RBW = 1MHz    VBW = 1MHz

**RECEIVER SPURIOUS RADIATION**

**§ 15.209**

**18GHz – 26GHz**

**(This plot is valid for all three channels)**



**ANALYZER SETTINGS: RBW = 1MHz    VBW = 1MHz**

