



**CONFORMANCE TEST REPORT
FOR
FCC 47 CFR, Part 15 Subpart C**

Report No.: 14-12-MAS-217-03

Client: FUJITSU TEN LIMITED
Product: Car Navigation
Model: FT0044E
FCC ID: BABFT0044E

Manufacturer/supplier: FUJITSU TEN LIMITED
Date test item received: 2014/12/25
Date test campaign completed: 2015/01/21
Date of issue: 2015/01/21

The test result only corresponds to the tested sample. It is not permitted to copy this report, in part or in full, without the permission of the test laboratory.

Total number of pages of this test report: 116 pages

Total number of pages of photos: External photos 3 pages

Internal photos 2 pages

Setup photos 1 pages

Test Engineer	Checked By	Approved By
 Phillip Luo	 Falcon Shi	 James Cheng

ELECTRONICS TESTING CENTER, TAIWAN
No.8, Lane 29, Wenming Rd. Guishan Dist.
Taoyuan City 33383, Taiwan, R.O.C.

TEL: (03) 3276170~4
INT: +886-3-3276170~4
FAX: (03) 3276188
INT: +886-3-3276188



Client : FUJITSU TEN LIMITED
Address : 2-28, Goshō-dori, 1-chome, Hyogo-ku, Kobe 652-8510 Japan
Manufacturer : FUJITSU TEN LIMITED
Address : 2-28, Goshō-dori, 1-chome, Hyogo-ku, Kobe 652-8510 Japan
EUT : Car Navigation
Trade name : ----
Model No. : FT0044E
Power Source : 12Vdc battery

Regulations applied : FCC 47 CFR, Part 15 Subpart C

The testing described in this report has been carried out to the best of our knowledge and ability, and our responsibility is limited to the exercise of reasonable care. This certification is not intended to relieve the sellers from their legal and/or contractual obligations.

The compliance test is only certified for the test equipment and the results of the testing report relate only to the item tested. The compliance test of this report was conducted in accordance with the appropriate standards. It's not intention to assure the quality and performance of the product. This report shall not be reproduced except in full, without the approval of ETC. This report must not be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government.

Laboratory Introduction: Electronics Testing Center, Taiwan is recognized, filed and mutual recognition arrangement as following:

- ① ISO9001: TüV Product Service
- ② ISO/IEC 17025: BSMI, TAF, NCC, NVLAP, ILAC MRA, UL, Compliance
- ③ Filing: FCC, Industry Canada, VCCI
- ④ MRA: Australia, Hong Kong, New Zealand, Singapore, USA, Japan, Korea, China, APLAC through TAF
- ⑤ FCC Registration Number: 91095, 392735, 278818
- ⑥ Industry Canada Site Registration Number: IC 2949A-2



NVLAP Lab Code 200133-0

Table of Contents	Page
1 GENERAL INFORMATION	5
1.1 Product Description.....	5
1.2 Characteristics of Device	5
1.3 Test Methodology	5
1.4 Test Facility.....	5
1.5 Test Summary	6
2 PROVISIONS APPLICABLE.....	7
2.1 Definition	7
2.2 Requirement for Compliance	8
2.3 Restricted Bands of Operation	10
2.4 Labeling Requirement.....	10
2.5 User Information	11
3. SYSTEM TEST CONFIGURATION.....	12
3.1 Devices for Tested System.....	12
3.2 Description of Test modes	13
4 CONDUCTED EMISSION MEASUREMENT	15
5 ANTENNA REQUIREMENT	16
5.1 Standard Applicable.....	16
5.2 Antenna Construction and Directional Gain.....	16
6 EMISSION BANDWIDTH MEASUREMENT	17
6.1 Standard Applicable.....	17
6.2 Measurement Procedure.....	17
6.3 Measurement Equipment	17
6.4 Measurement Data	18
7 OUTPUT POWER MEASUREMENT	30
7.1 Standard Applicable.....	30
7.2 Measurement Procedure.....	30
7.3 Measurement Equipment	30
7.4 Measurement Data	31
8 POWER DENSITY MEASUREMENT.....	34
8.1 Standard Applicable.....	34
8.2 Measurement Procedure.....	34
8.3 Measurement Equipment	34

8.4 Measurement Data 35

9 SPURIOUS EMISSION - RF CONDUCTED MEASUREMENT..... 47

9.1 Standard Applicable 47

9.2 Measurement Procedure..... 47

9.3 Measurement Equipment 47

9.4 Measurement Data 48

10 RADIATED EMISSION MEASUREMENT 91

10.1 Standard Applicable 91

10.2 Measurement Procedure..... 91

10.3 Measuring Instrument 93

10.4 Radiated Emission Data 96

10.5 Field Strength Calculation 115

11. EQUIPMENTS LIST FOR TESTING 116

1 GENERAL INFORMATION

1.1 Product Description

- a) Type of EUT : Car Navigation
- b) Trade Name : ----
- c) Model No. : FT0044E
- d) FCC ID : BABFT0044E

1.2 Characteristics of Device

The EUT is a Car Navigation. It conforms to the IEEE 802.11b/g/n protocol and operates in the unlicensed ISM Band at 2.4 GHz.

RF chain	1T1R
Frequency Range	IEEE 802.11b/g, 802.11gn HT20: 2412MHz~2462MHz
Channel Spacing	IEEE 802.11b/g, 802.11gn HT20: 5MHz
Channel Number	IEEE 802.11b/g, 802.11gn HT20: 11 Channels
Transmit Data Rate	IEEE 802.11b: 11, 5.5, 2, 1 Mbps IEEE 802.11g: 54, 48, 36, 24, 18, 12, 11, 9, 6 Mbps IEEE 802.11gn HT20: 72.2, 65, 58.5, 52, 39, 26, 19.5, 13, 6.5Mbps
Type of Modulation	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11gn HT20: OFDM (64QAM, 16QAM, QPSK, BPSK)

1.3 Test Methodology

All testing were performed according to the procedures in ANSI C63.10 (2009) and FCC CFR 47 Part 2 and Part 15 and KDB 558074 D01 v03r02.

1.4 Test Facility

The semi-anechoic chamber and conducted measurement facility used to collect the radiated and conducted data are located inside the Building at No.8, Lane 29, Wen-ming Road, Lo-shan Tsun, Kweishan Hsiang, Taoyuan, Taiwan, R.O.C.
This site has been accreditation as a FCC filing site.

1.5 Test Summary

Requirement	FCC Paragraph #	Test Pass
Antenna Requirement	15.203	☒
Conducted Emission	15.207	N/A
Emission Bandwidth	15.247 (a)(2)	☒
Output Power Requirement	15.247 (b)	☒
Power Density Requirement	15.247 (e)	☒
Spurious Emissions	15.247 (d)	☒
Radiated Emission	15.247 (d)	☒

Note: The test setup and measurement method for conductive output power measurements shown in this test report is different to the “Peak Output Power” test. Certain measurement uncertainty of peak power may be expected with the use of different power detection method or measuring equipment. Therefore, the conductive output power measurement results provided in this test report may be different to the specification of the device under test.

2 PROVISIONS APPLICABLE

2.1 Definition

Unintentional radiator:

A device that intentionally generates and radio frequency energy for use within the device, or that sends radio frequency signals by conduction to associated equipment via connecting wiring, but which is not intended to emit RF energy by radiation or induction.

Class A Digital Device:

A digital device which is marketed for use in commercial or business environment; exclusive of a device which is market for use by the general public, or which is intended to be used in the home.

Class B Digital Device :

A digital device which is marketed for use in a residential environment notwithstanding use in a commercial, business or industrial environment. Example of such devices that are marketed for the general public.

Note : A manufacturer may also qualify a device intended to be marketed in a commercial, business, or industrial environment as a Class B digital device, and in fact is encouraged to do so, provided the device complies with the technical specifications for a Class B Digital Device. In the event that a particular type of device has been found to repeatedly cause harmful interference to radio communications, the Commission may classify such a digital device as a Class B Digital Device, Regardless of its intended use.

Intentional radiator:

A device that intentionally generates and emits radio frequency energy by radiation or induction.

2.2 Requirement for Compliance

(1) Conducted Emission Requirement

For unintentional device, according to §15.107(a) Line Conducted Emission Limits is as following:

Frequency MHz	Quasi Peak dB μ V	Average dB μ V
0.15 - 0.5	66-56*	56-46*
0.5 - 5.0	56	46
5.0 - 30.0	60	50

*Decreases with the logarithm of the frequency.

For intentional device, according to §15.207(a) Line Conducted Emission Limits is same as above table.

(2) Radiated Emission Requirement

For unintentional device, according to §15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency MHz	Distance Meters	Radiated dB μ V/m	Radiated μ V/m
30 - 88	3	40.0	100
88 - 216	3	43.5	150
216 - 960	3	46.0	200
above 960	3	54.0	500

For intentional radiator device, according to §15.209(a), the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table::

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72MHz, 76-88MHz, 174-216MHz or 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

For intentional device, according to §15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

(3) Antenna Requirement

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

(4) Bandwidth Requirement

According to 15.247 (a)(2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

(5) Output Power Requirement

For systems using digital modulation , according to 15.247(b), the maximum peak output power of the intentional radiator shall not exceed 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(6) Spurious Emissions Measurement

According to 15.247 (d) , in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

(7) Power Density Requirement

According to 15.247 (e) , for digitally modulated systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission..

2.3 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below :

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42-16.423	399.9-410	4.5-5.25
0.495 - 0.505 **	16.69475 - 16.69525	608-614	5.35-5.46
2.1735 - 2.1905	16.80425 - 16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475 - 156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2655-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

** : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

2.4 Labeling Requirement

The device shall bear the following statement in a conspicuous location on the device :

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

2.5 User Information

The users manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual.

The Federal Communications Commission Radio Frequency Interference Statement includes the following paragraph.

This equipment has been tested and found to comply with the limits for a Class B Digital Device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instruction may cause harmful interference to radio communication. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:


- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio / TV technician for help.

3. SYSTEM TEST CONFIGURATION**3.1 Devices for Tested System**

No	Device	Manufacture	Model No.	Cable Description
A	* Car Navigation	FUJITSU TEN LIMITED	FT0044E	----
B	Steering Switch	N/A	N/A	2.8m*1 Unshielded Signal Line
C	Rear Camera	N/A	GP-KD5339RC	2.8m*1 Unshielded Signal Line
D	GPS Antenna	TOYOTA	86860-22090	7.0m*1 Shielded Signal Line
E	USB Adapter	N/A	N/A	2.0m*1 Unshielded Signal Line
F	FM Radio Antenna	N/A	N/A	0.2m*1 Shielded Signal Line
G	Speaker*2	N/A	ECLIPSE	3.0m*1 Unshielded Signal Line
H	USB Dongle	Transcend	NK1939	----
I	DC Power Supply	GW	GPS-3030D	3.7m*1 Unshielded Power Line

Remark

1. “*” means equipment under test.



2.

Test Software:	Tx Batch File		
Power setting:	Mode	Channel	Setting
	b	Low	N/A
		Mid	N/A
		High	N/A
	g	Low	N/A
		Mid	N/A
		High	N/A
	gn HT20	Low	N/A
		Mid	N/A
		High	N/A

3.2 Description of Test modes

3.2.1 IEEE 802.11b, 802.11g, 802.11gn HT20 mode:

There are three channels have been tested as following:

Channel	Frequency (MHz)
Low = 1	2412
Middle = 6	2437
High = 11	2462

IEEE 802.11b mode: 1 Mbps data rate is the worse case for full testing.

IEEE 802.11g mode: 6 Mbps data rate is the worse case for full testing.

IEEE 802.11gn HT20 mode: MCS0 6.5 Mbps data rate is the worse case for full testing.

3.2.2 Test Mode Description

3.2.2.1 Modulation Type

Test Mode	Modulation	Note
A	IEEE 802.11b	-
B	IEEE 802.11g	-
C	IEEE 802.11gn HT20 (note1)	-

Mode	IEEE 802.11b/g/gn HT20
Test Channel	Frequency (MHz)
Channel Low (L)	2412
Channel Mid (M)	2437
Channel High (H)	2462

3.2.2.2 Test Mode and Worse Case Determination

Item	Test Item	Test Mode	Test Frequency (MHz)
1	Conducted Emission	-	-
2	Emission Bandwidth	A , B , C	L , M , H
3	Output Power Requirement	A , B , C	L , M , H
4	Power Density Requirement	A , B , C	L , M , H
5	Spurious Emissions	A , B , C	L , M , H
6	Radiated Emission	A , B , C	L , M , H
6.1	Radiated Emission (below 1GHz)	B (note1)	M (Worse Case1)
6.2	Radiated Emission (above 1GHz)	A , B , C	L , M , H

note:

1. The worse case is determined as the modulation with highest output power.
2. The worse case is determined as the adaptor:1 with highest noise conducted emission.
Choose that for final testing and record the result.

4 CONDUCTED EMISSION MEASUREMENT

This EUT is excused from investigation of conducted emission, for it is powered by battery only. According to §15.207 (d), measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines.

5 ANTENNA REQUIREMENT

5.1 Standard Applicable

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to §15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

5.2 Antenna Construction and Directional Gain

The antennas is a Surface mounting Antenna

Antenna Type	Inverted-F
Peak Antenna Gain	1.47 dBi

The directional gain of antenna doesn't greater than 6 dBi, the power won't be reduced.

6 EMISSION BANDWIDTH MEASUREMENT

6.1 Standard Applicable

According to 15.247(a)(2), system using digital modulation techniques, the minimum 6dB bandwidth shall be at least 500 kHz.

6.2 Measurement Procedure

1. The testing follows FCC KDB 558074 D01 v03r02.
2. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
3. Position the EUT as shown in figure 1. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
4. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
5. Repeat above procedures until all frequencies measured were complete.

Figure 1: Emission bandwidth measurement configuration.



6.3 Measurement Equipment

Equipment	Manufacturer	Model No.
Spectrum Analyzer	Agilent	E4446A

6.4 Measurement Data

6.4.1 IEEE 802.11b

Test Date: Jan. 17, 2015Temperature: 22°CHumidity: 60%

Channel	6dB Bandwidth (MHz)	FCC Limit (kHz)	Chart
L	10.25	500	Page 19
M	10.25	500	Page 20
H	10.25	500	Page 21

Note:

1. Please refer to page 19 to page 21 for chart
2. The estimated measurement uncertainty of the result measurement is 8.25×10^{-7} ($1\text{GHz} \leq f \leq 18\text{GHz}$)


File: FT0044E_B_2015 Data: #1

Date: 2015/1/17

Temperature: 22 °C

Time: AM 10:30:15

Humidity: 60 %



Condition: -4.35dBm

Horizontal

EUT:

Sweep Time: 500ms Att.: 20dB

Model:

RBW: 100 KHz VBW: 300 KHz

Test Mode:

Note: FCC-802.11b Channel 01-6dB EBW

No.	Frequency(MHz)	Level(dBm)
1	2406.83330	-6.98
2	2411.50000	1.65
3	2417.08330	-4.75

No.		Δ Frequency(MHz)	Δ Level(dB)
1	mk3-mk1	10.25	2.23


File: FT0044E_B_2015 Data: #8

Date: 2015/1/17

Temperature: 22 °C

Time: AM 10:44:54

Humidity: 60 %



Condition: -3.91dBm

Horizontal

EUT:

Sweep Time: 500ms Att.: 20dB

Model:

RBW: 100 KHz VBW: 300 KHz

Test Mode:

Note: FCC-802.11b Channel 06-6dB EBW

No.	Frequency(MHz)	Level(dBm)
1	2431.83330	-6.40
2	2437.50000	2.09
3	2442.08330	-4.85

No.		Δ Frequency(MHz)	Δ Level(dB)
1	mk3-mk1	10.25	1.55


File: FT0044E_B_2015 Data: #12

Date: 2015/1/17

Temperature: 22 °C

Time: AM 10:54:10

Humidity: 60 %



Condition: -3.87dBm

Horizontal

EUT:

Sweep Time: 500ms Att.: 20dB

Model:

RBW: 100 KHz VBW: 300 KHz

Test Mode:

Note: FCC-802.11b channel 11-6dB EBW

No.	Frequency(MHz)	Level(dBm)
1	2456.83330	-6.25
2	2461.50000	2.13
3	2467.08330	-5.26

No.		Δ Frequency(MHz)	Δ Level(dB)
1	mk3-mk1	10.25	0.99


6.4.2 IEEE 802.11gTest Date: Jan. 17, 2015Temperature: 22°CHumidity: 60%

Channel	6dB Bandwidth (MHz)	FCC Limit (kHz)	Chart
L	16.5	500	Page 23
M	16.5	500	Page 24
H	16.5	500	Page 25

Note:

1. Please refer to page 23 to page 25 for chart
2. The estimated measurement uncertainty of the result measurement is 8.25×10^{-7} ($1\text{GHz} \leq f \leq 18\text{GHz}$)

File: FT0044E_G_2015 Data: #1 Date: 2015/1/17 Temperature: 22 °C
Time: AM 11:14:51 Humidity: 60 %



Condition: -6.8dBm Horizontal
EUT: Sweep Time: 500ms Att.: 20dB
Model: RBW: 100 KHz VBW: 300 KHz
Test Mode:
Note: FCC-802.11g Channel 01-6dB EBW

No.	Frequency(MHz)	Level(dBm)
1	2403.75000	-8.79
2	2413.25000	-0.80
3	2420.25000	-9.22

No.		Δ Frequency(MHz)	Δ Level(dB)
1	mk3-mk1	16.5	-0.43


File: FT0044E_G_2015 Data: #6

Date: 2015/1/17

Temperature: 22 °C

Time: AM 11:22:32

Humidity: 60 %



Condition: -6.38dBm

Horizontal

EUT:

Sweep Time: 500ms Att.: 20dB

Model:

RBW: 100 KHz VBW: 300 KHz

Test Mode:

Note: FCC-802.11g Channel 06-6dB EBW

No.	Frequency(MHz)	Level(dBm)
1	2428.75000	-8.66
2	2439.50000	-0.38
3	2445.25000	-9.25

No.		Δ Frequency(MHz)	Δ Level(dB)
1	mk3-mk1	16.5	-0.59


File: FT0044E_G_2015 Data: #10

Date: 2015/1/17

Temperature: 22 °C

Time: AM 11:30:54

Humidity: 60 %



Condition: -6.35dBm

Horizontal

EUT:

Sweep Time: 500ms Att.: 20dB

Model:

RBW: 100 KHz VBW: 300 KHz

Test Mode:

Note: FCC-802.11g Channel 11-6dB EBW

No.	Frequency(MHz)	Level(dBm)
1	2453.75000	-8.51
2	2463.25000	-0.35
3	2470.25000	-8.95

No.		Δ Frequency(MHz)	Δ Level(dB)
1	mk3-mk1	16.5	-0.44


6.4.3 IEEE 802.11gn, HT20Test Date: Jan. 17, 2015Temperature: 22°CHumidity: 60%

Channel	6dB Bandwidth (MHz)	FCC Limit (kHz)	Chart
L	16.9167	500	Page 27
M	16.9168	500	Page 28
H	17.1667	500	Page 29

Note:

1. Please refer to page 27 to page 29 for chart
2. The estimated measurement uncertainty of the result measurement is 8.25×10^{-7} ($1\text{GHz} \leq f \leq 18\text{GHz}$)

File: FT0044E_HT20_2015 Data: #1 Date: 2015/1/17 Temperature: 22 °C
Time: AM 11:40:00 Humidity: 60 %



Condition: -6.89dBm Horizontal
EUT: Sweep Time: 500ms Att.: 20dB
Model: RBW: 100 KHz VBW: 300 KHz
Test Mode:
Note: FCC-802.11gn_HT20 Channel 01-6dB EBW

No.	Frequency(MHz)	Level(dBm)
1	2403.50000	-6.92
2	2413.25000	-0.89
3	2420.41670	-7.29

No.		Δ Frequency(MHz)	Δ Level(dB)
1	mk3-mk1	16.9167	-0.37

File: FT0044E_HT20_201 Data: #6


Date: 2015/1/17

Temperature: 22 °C

5

Time: AM 11:47:28

Humidity: 60 %



Condition: -6.27dBm

Horizontal

EUT:

Sweep Time: 500ms Att.: 20dB

Model:

RBW: 100 KHz VBW: 300 KHz

Test Mode:

Note: FCC-802.11gn_HT20 Channel 06-6dB EBW

No.	Frequency(MHz)	Level(dBm)
1	2428.5832	-6.32
2	2439.5000	-0.27
3	2445.5000	-6.41

No.		Δ Frequency(MHz)	Δ Level(dB)
1	mk3-mk1	16.9168	-0.09

File: FT0044E_HT20_201 Data: #10


Date: 2015/1/17

Temperature: 22 °C

5

Time: PM 12:03:58

Humidity: 60 %



Condition: -6.26dBm

Horizontal

EUT:

Sweep Time: 500ms Att.: 20dB

Model:

RBW: 100 KHz VBW: 300 KHz

Test Mode:

Note: FCC-802.11gn_HT20 Channel 11-6dB EBW

No.	Frequency(MHz)	Level(dBm)
1	2453.4166	-6.86
2	2464.5000	-0.26
3	2470.5833	-8.17

No.		ΔFrequency(MHz)	ΔLevel(dB)
1	mk3-mk1	17.1667	-1.31

7 OUTPUT POWER MEASUREMENT

7.1 Standard Applicable

For direct sequence system, according to 15.247(b), the maximum peak output power of the transmitter shall not exceed 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

7.2 Measurement Procedure

1. The testing follows FCC KDB 558074 D01 v03r02.
2. The test is performed in accordance with FCC KDB Publication No. 558074: Guidance on Measurements for Digital Transmission Systems (47 CFR 15.247)
3. Position the EUT as shown in figure 1.

7.3 Measurement Equipment

Equipment	Manufacturer	Model No.
Power Meter	Agilent	N1912A
Wideband Power Sensor	Agilent	N1922A

7.4 Measurement Data

7.4.1 IEEE 802.11b

Test Date: Jan. 17, 2015Temperature: 22°CHumidity: 60%

Channel	Maximum Peak Output Power (dBm)	FCC Limit (dBm)	Chart
L	15.50	30.0	-
M	15.63	30.0	-
H	15.80	30.0	-

Note:

The estimated measurement uncertainty of the result measurement is $\pm 1.5\text{dB}$ ($1\text{GHz} \leq f \leq 18\text{GHz}$)

7.4.2 IEEE 802.11gTest Date: Jan. 17, 2015Temperature: 22°CHumidity: 60%

Channel	Maximum Peak Output Power (dBm)	FCC Limit (dBm)	Chart
L	19.75	30.0	-
M	19.75	30.0	-
H	19.95	30.0	-

Note:

The estimated measurement uncertainty of the result measurement is $\pm 1.5\text{dB}(1\text{GHz} \leq f \leq 18\text{GHz})$

7.4.3 IEEE 802.11gn, HT20Test Date: Jan. 17, 2015Temperature: 22°CHumidity: 60%

Channel	Maximum Peak Output Power (dBm)	FCC Limit (dBm)	Chart
L	19.71	30.0	-
M	19.76	30.0	-
H	19.93	30.0	-

Note:

The estimated measurement uncertainty of the result measurement is $\pm 1.5\text{dB}$ ($1\text{GHz} \leq f \leq 18\text{GHz}$)

8 POWER DENSITY MEASUREMENT

8.1 Standard Applicable

According to 15.247(e), for direct sequence systems, the transmitted power density averaged over any 1 second interval shall not be greater than 8 dBm in any 3 kHz bandwidth within these bands.

8.2 Measurement Procedure

1. The testing follows FCC KDB 558074 D01 v03r02.
2. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
3. Position the EUT as shown in figure 1. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set EUT to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
4. Adjust the center frequency of spectrum analyzer on highest level appearing on spectral display within a 300 kHz frequency span.
5. Set the spectrum analyzer on a 3 kHz resolution bandwidth and 10 kHz video bandwidth as well as max. hold function, then record the measurement result.
6. Repeat above procedures until all measured frequencies were complete.

8.3 Measurement Equipment

Equipment	Manufacturer	Model No.
Spectrum Analyzer	Agilent	E4446A

8.4 Measurement Data

8.4.1 IEEE 802.11b

Test Date: Jan. 17, 2015Temperature: 22°CHumidity: 60%

Channel	Peak Power Spectral Density (dBm)	FCC Limit (dBm)	Chart
L	1.26	8	Page 36
M	1.57	8	Page 37
H	1.64	8	Page 38

Note:

1. Please refer to page 36 to page 38 for chart
2. The estimated measurement uncertainty of the result measurement is $\pm 1.5\text{dB}$ ($1\text{GHz} \leq f \leq 18\text{GHz}$)


File: FT0044E_B_2015 Data: #19

Date: 2015/1/17

Temperature: 22 °C

Time: PM 03:59:37

Humidity: 60 %



Condition:

Horizontal

EUT:

Sweep Time: 3163.2ms Att.: 20dB

Model:

RBW: 3 KHz VBW: 10 KHz

Test Mode:

Note: FCC-802.11b Channel 01-Power Density (PK)

No.	Frequency(MHz)	Level(dBm)
1	2412.7500	1.26


File: FT0044E_B_2015 Data: #18

Date: 2015/1/17

Temperature: 22 °C

Time: PM 03:58:23

Humidity: 60 %



Condition:

Horizontal

EUT:

Sweep Time: 3163.2ms Att.: 20dB

Model:

RBW: 3 KHz VBW: 10 KHz

Test Mode:

Note: FCC-802.11b Channel 06-Power Density (PK)

No.	Frequency(MHz)	Level(dBm)
1	2437.7500	1.57


File: FT0044E_B_2015 Data: #17

Date: 2015/1/17

Temperature: 22 °C

Time: PM 03:57:15

Humidity: 60 %



Condition:

Horizontal

EUT:

Sweep Time: 3163.2ms Att.: 20dB

Model:

RBW: 3 KHz VBW: 10 KHz

Test Mode:

Note: FCC-802.11b Channel 11-Power Density (PK)

No.	Frequency(MHz)	Level(dBm)
1	2462.7500	1.64

8.4.2 IEEE 802.11gTest Date: Jan. 17, 2015Temperature: 22°CHumidity: 60%

Channel	Peak Power Spectral Density (dBm)	FCC Limit (dBm)	Chart
L	-15.32	8	Page 40
M	-14.43	8	Page 41
H	-15.51	8	Page 42

Note:

1. Please refer to page 40 to page 42 for chart
2. The estimated measurement uncertainty of the result measurement is $\pm 1.5\text{dB}$ ($1\text{GHz} \leq f \leq 18\text{GHz}$)


File: FT0044E_G_201 Data: #15
5

Date: 2015/1/17

Temperature: 22 °C

Time: PM 03:45:50

Humidity: 60 %



Condition:

Horizontal

EUT:

Sweep Time: 3163.2ms Att.: 20dB

Model:

RBW: 3 KHz VBW: 10 KHz

Test Mode:

Note: FCC-802.11g Channel 01-Power Density (PK)

No.	Frequency(MHz)	Level(dBm)
1	2417.0000	-15.32


File: FT0044E_G_201 Data: #16
5

Date: 2015/1/17

Temperature: 22 °C

Time: PM 03:49:21

Humidity: 60 %



Condition:

Horizontal

EUT:

Sweep Time: 3163.2ms Att.: 20dB

Model:

RBW: 3 KHz VBW: 10 KHz

Test Mode:

Note: FCC-802.11g Channel 06-Power Density (PK)

No.	Frequency(MHz)	Level(dBm)
1	2442.0000	-14.43


File: FT0044E_G_201 Data: #17
5

Date: 2015/1/17

Temperature: 22 °C

Time: PM 03:50:33

Humidity: 60 %



Condition:

Horizontal

EUT:

Sweep Time: 3163.2ms Att.: 20dB

Model:

RBW: 3 KHz VBW: 10 KHz

Test Mode:

Note: FCC-802.11g Channel 11-Power Density (PK)

No.	Frequency(MHz)	Level(dBm)
1	2464.4500	-15.51

8.4.3 IEEE 802.11gn, HT20Test Date: Jan. 17, 2015Temperature: 22°CHumidity: 60%

Channel	Peak Power Spectral Density (dBm)	FCC Limit (dBm)	Chart
L	-15.83	8	Page 44
M	-15.50	8	Page 45
H	-14.92	8	Page 46

Note:

1. Please refer to page 44 to page 46 for chart
2. The estimated measurement uncertainty of the result measurement is $\pm 1.5\text{dB}(1\text{GHz} \leq f \leq 18\text{GHz})$


File: FT0044E_HT20_201 Data: #17
5

Date: 2015/1/17

Temperature: 22 °C

Time: PM 03:44:06

Humidity: 60 %



Condition:

Horizontal

EUT:

Sweep Time: 3163.2ms Att.: 20dB

Model:

RBW: 3 KHz VBW: 10 KHz

Test Mode:


Note: FCC-802.11gn_HT20 Channel 01-Power Density (PK)

No.	Frequency(MHz)	Level(dBm)
1	2408.3000	-15.83

File: FT0044E_HT20_201 Data: #16
5

Date: 2015/1/17 Temperature: 22 °C

Time: PM 03:42:41 Humidity: 60 %



Condition: Horizontal
EUT: Sweep Time: 3163.2ms Att.: 20dB
Model: RBW: 3 KHz VBW: 10 KHz
Test Mode:
Note: FCC-802.11gn_HT20 Channel 06-Power Density (PK)

No.	Frequency(MHz)	Level(dBm)
1	2433.3000	-15.50


File: FT0044E_HT20_201 Data: #15
5

Date: 2015/1/17

Temperature: 22 °C

Time: PM 03:41:27

Humidity: 60 %



Condition:

Horizontal

EUT:

Sweep Time: 3163.2ms Att.: 20dB

Model:

RBW: 3 KHz VBW: 10 KHz

Test Mode:

Note: FCC-802.11gn_HT20 Channel 11-Power Density (PK)

No.	Frequency(MHz)	Level(dBm)
1	2464.5000	-14.92

9 SPURIOUS EMISSION - RF CONDUCTED MEASUREMENT

9.1 Standard Applicable

According to 12.247 (d) , in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

9.2 Measurement Procedure

1. The testing follows FCC KDB 558074 D01 v03r02.
2. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
3. Position the EUT as shown in figure 1. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
4. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge.
5. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
6. Repeat above procedures until all measured frequencies were complete.

9.3 Measurement Equipment

Equipment	Manufacturer	Model No.
Spectrum Analyzer	Agilent	E4446A

9.4 Measurement Data

9.4.1 IEEE 802.11b

Test Date: Jan. 17, 2015Temperature: 22°CHumidity: 60%Test Date: Jan. 21, 2015Temperature: 22°CHumidity: 60%

Channel	Frequency(MHz)	Chart
1	2412	Page 49, Page 51,52,53,54
6	2437	Page 55,56,57,58
11	2462	Page 50, Page 59,60,61,62

Frequency Band: 2400 MHz ~ 2483.5 MHz

All out-of –band conducted emissions were more than 20dB below the carrier.

Note: 1. Please refer to page 49 to page 62 for chart
2. An external attenuator is used as part of the test system for these measurements, the attenuation introduced by the external attenuator has not been explicitly compensated in the measured power level as it is irrelevant to these specific measurement results.

9.4.2 IEEE 802.11g

Channel	Frequency(MHz)	Chart
1	2412	Page 63, Page 65,66,67,68
6	2437	Page 69,70,71,72
11	2462	Page 64, Page 73,74,75,76

Frequency Band: 2400 MHz ~ 2483.5 MHz

All out-of –band conducted emissions were more than 20dB below the carrier.

Note: 1. Please refer to page 63 to page 76 for chart
2. An external attenuator is used as part of the test system for these measurements, the attenuation introduced by the external attenuator has not been explicitly compensated in the measured power level as it is irrelevant to these specific measurement results.

9.4.3 IEEE 802.11gn, HT20

Channel	Frequency(MHz)	Chart
1	2412	Page 77, Page 79,80,81,82
6	2437	Page 83,84,85,86
11	2462	Page 78, Page 87,88,89,90

Frequency Band: 2400 MHz ~ 2483.5 MHz

All out-of –band conducted emissions were more than 20dB below the carrier.

Note: 1. Please refer to page 77 to page 90 for chart
2. An external attenuator is used as part of the test system for these measurements, the attenuation introduced by the external attenuator has not been explicitly compensated in the measured power level as it is irrelevant to these specific measurement results.

Humidity: 60 %

No.	Frequency(MHz)	Level(dBm)
1	2399.37500	-41.77
2	2411.50000	1.67


File: FT0044E_B_2015 Data: #16

Date: 2015/1/17

Temperature: 22 °C

Time: AM 10:59:35

Humidity: 60 %



Condition: -17.97dBm

Horizontal

EUT:

Sweep Time: 500ms Att.: 10dB

Model:

RBW: 100 KHz VBW: 300 KHz

Test Mode:

Note: FCC-802.11b Channel 11-Bandedge

No.	Frequency(MHz)	Level(dBm)
1	2462.45670	2.03
2	2483.91670	-48.41


Humidity: 60 %

No.	Frequency(MHz)	Level(dBm)
1	901.3833	-60.38

File: FT0044E_B_2015 Data: #23

Date: 2015/1/21
Time: AM 10:09:53

Temperature: 22 °C
Humidity: 60 %



Condition:

Horizontal

EUT:

Sweep Time: 382.28ms Att.: 20dB

Model:

RBW: 100 KHz VBW: 300 KHz

Test Mode:


Note: FCC-802.11b Channel 01-Conducted Spurious-2

No.	Frequency(MHz)	Level(dBm)
1	2480.00000	-39.19
2	4826.66670	-58.87
3	2413.33330	2.16

Humidity: 60 %

No.	Frequency(MHz)	Level(dBm)
1	7041.66670	-56.17


File: FT0044E_B_2015 Data: #25 Date: 2015/1/21 Temperature: 22 °C
Time: AM 10:10:51 Humidity: 60 %



Condition: -17.84 Horizontal
EUT: Sweep Time: 1242.44ms Att.: 20dB
Model: RBW: 100 KHz VBW: 300 KHz
Test Mode:
Note: FCC-802.11b Channel 01-Conducted Spurious-4

No.	Frequency(MHz)	Level(dBm)
1	25000.00000	-52.11

File: FT0044E_B_2015 Data: #26 Date: 2015/1/21 Temperature: 22 °C
Time: AM 10:14:52 Humidity: 60 %




Condition: -16.98 Horizontal
EUT: Sweep Time: 92.72ms Att.: 20dB
Model: RBW: 100 KHz VBW: 300 KHz
Test Mode:
Note: FCC-802.11b Channel 06-Conducted Spurious-1

No.	Frequency(MHz)	Level(dBm)
1	776.9000	-61.25

File: FT0044E_B_2015 Data: #27

Date: 2015/1/21
Time: AM 10:15:27

Temperature: 22 °C
Humidity: 60 %



Condition:

Horizontal

EUT:

Sweep Time: 382.28ms Att.: 20dB

Model:

RBW: 100 KHz VBW: 300 KHz

Test Mode:

Note: FCC-802.11b Channel 06-Conducted Spurious-2

No.	Frequency(MHz)	Level(dBm)
1	2440.00000	3.02
2	2480.00000	-46.64
3	4406.66670	-58.96

Humidity: 60 %

No.	Frequency(MHz)	Level(dBm)
1	7006.66670	-55.51

Humidity: 60 %

No.	Frequency(MHz)	Level(dBm)
1	24328.33330	-51.80

Humidity: 60 %

No.	Frequency(MHz)	Level(dBm)
1	704.1500	-61.28


File: FT0044E_B_2015 Data: #31

Date: 2015/1/21

Temperature: 22 °C

Time: AM 10:20:02

Humidity: 60 %



Condition:

Horizontal

EUT:

Sweep Time: 382.28ms Att.: 20dB

Model:

RBW: 100 KHz VBW: 300 KHz

Test Mode:

Note: FCC-802.11b Channel 11-Conducted Spurious-2

No.	Frequency(MHz)	Level(dBm)
1	2306.66670	-51.28
2	3146.66670	-58.53
3	2460.00000	3.20

Humidity: 60 %

No.	Frequency(MHz)	Level(dBm)
1	7123.33330	-56.21

Humidity: 60 %

No.	Frequency(MHz)	Level(dBm)
1	24285.00000	-51.52


File: FT0044E_G_2015 Data: #5

Date: 2015/1/17

Temperature: 22 °C

Time: AM 11:20:18

Humidity: 60 %



Condition: -20.87dBm

Horizontal

EUT:

Sweep Time: 500ms Att.: 10dB

Model:

RBW: 100 KHz VBW: 300 KHz

Test Mode:

Note: FCC-802.11g Channel 01-Bandedge

No.	Frequency(MHz)	Level(dBm)
1	2398.75000	-32.98
2	2410.75000	-0.87


File: FT0044E_G_2015 Data: #14

Date: 2015/1/17

Temperature: 22 °C

Time: AM 11:36:19

Humidity: 60 %



Condition: -20.23dBm

Horizontal

EUT:

Sweep Time: 500ms Att.: 10dB

Model:

RBW: 100 KHz VBW: 300 KHz

Test Mode:

Note: FCC-802.11g Channel 11-Bandedge

No.	Frequency(MHz)	Level(dBm)
1	2464.43000	-0.23
2	2483.91670	-42.66

Humidity: 60 %

No.	Frequency(MHz)	Level(dBm)
1	631.4000	-61.21


File: FT0044E_G_2015 Data: #19

Date: 2015/1/21

Temperature: 22 °C

Time: AM 10:30:35

Humidity: 60 %



Condition:

Horizontal

EUT:

Sweep Time: 382.28ms Att.: 20dB

Model:

RBW: 100 KHz VBW: 300 KHz

Test Mode:

Note: FCC-802.11g Channel 01-Conducted Spurious-2

No.	Frequency(MHz)	Level(dBm)
1	2413.33330	-0.35
2	2480.00000	-39.07
3	3493.33330	-57.33

Humidity: 60 %

No.	Frequency(MHz)	Level(dBm)
1	7695.00000	-55.51

Humidity: 60 %

No.	Frequency(MHz)	Level(dBm)
1	23570.00000	-52.17

Humidity: 60 %

No.	Frequency(MHz)	Level(dBm)
1	506.9167	-61.65


File: FT0044E_G_2015 Data: #23

Date: 2015/1/21

Temperature: 22 °C

Time: AM 10:35:03

Humidity: 60 %



Condition:

Horizontal

EUT:

Sweep Time: 382.28ms Att.: 20dB

Model:

RBW: 100 KHz VBW: 300 KHz

Test Mode:

Note: FCC-802.11g Channel 06-Conducted Spurious-2

No.	Frequency(MHz)	Level(dBm)
1	2433.33330	-0.65
2	2480.00000	-41.22
3	3106.66670	-57.21

Humidity: 60 %

No.	Frequency(MHz)	Level(dBm)
1	7811.66670	-55.71

Humidity: 60 %

No.	Frequency(MHz)	Level(dBm)
1	24220.00000	-51.10

Humidity: 60 %

No.	Frequency(MHz)	Level(dBm)
1	615.2333	-61.05


File: FT0044E_G_2015 Data: #27

Date: 2015/1/21

Temperature: 22 °C

Time: AM 10:40:12

Humidity: 60 %



Condition:

Horizontal

EUT:

Sweep Time: 382.28ms Att.: 20dB

Model:

RBW: 100 KHz VBW: 300 KHz

Test Mode:


Note: FCC-802.11g Channel 11-Conducted Spurious-2

No.	Frequency(MHz)	Level(dBm)
1	2466.66670	-1.25
2	2693.33330	-49.81
3	4560.00000	-59.36

File: FT0044E_G_2015 Data: #28

Date: 2015/1/21
Time: AM 10:41:02

Temperature: 22 °C
Humidity: 60 %



Condition: -21.25

Horizontal

EUT:

Sweep Time: 669ms Att.: 20dB

Model:

RBW: 100 KHz VBW: 300 KHz

Test Mode:

Note: FCC-802.11g Channel 11-Conducted Spurious-3

No.	Frequency(MHz)	Level(dBm)
1	6995.00000	-56.68

Humidity: 60 %

No.	Frequency(MHz)	Level(dBm)
1	24306.66670	-51.85


File: FT0044E_HT20_2015 Data: #5

Date: 2015/1/17

Temperature: 22 °C

Time: AM 11:45:28

Humidity: 60 %



Condition: -20.78dBm

Horizontal

EUT:

Sweep Time: 500ms Att.: 10dB

Model:

RBW: 100 KHz VBW: 300 KHz

Test Mode:

Note: FCC-802.11gn_HT20 Channel 01-Bandedge

No.	Frequency(MHz)	Level(dBm)
1	2398.75000	-34.31
2	2414.50000	-0.78


File: FT0044E_HT20_2015 Data: #14

Date: 2015/1/17

Temperature: 22 °C

Time: PM 12:09:24

Humidity: 60 %



Condition: -20.69dBm

Horizontal

EUT:

Sweep Time: 500ms Att.: 10dB

Model:


RBW: 100 KHz VBW: 300 KHz

Test Mode:

Note: FCC-802.11gn_HT20 Channel 11-Bandedge

No.	Frequency(MHz)	Level(dBm)
1	2460.73000	-0.69
2	2484.78000	-41.58

File: FT0044E_HT20_2015 Data: #18 Date: 2015/1/21 Temperature: 22 °C
Time: AM 10:49:00 Humidity: 60 %



Condition: -23.35 Horizontal
EUT: Sweep Time: 92.72ms Att.: 20dB
Model: RBW: 100 KHz VBW: 300 KHz
Test Mode:
Note: FCC-802.11g Channel 01-Conducted Spurious-1

No.	Frequency(MHz)	Level(dBm)
1	602.3000	-60.84


File: FT0044E_HT20_2015 Data: #19

Date: 2015/1/21

Temperature: 22 °C

Time: AM 10:49:22

Humidity: 60 %



Condition:

Horizontal

EUT:

Sweep Time: 382.28ms Att.: 20dB

Model:

RBW: 100 KHz


VBW: 300 KHz

Test Mode:

Note: FCC-802.11g Channel 01-Conducted Spurious-2

No.	Frequency(MHz)	Level(dBm)
1	2413.33330	-3.35
2	2480.00000	-39.93
3	3473.33330	-57.74


File: FT0044E_HT20_2015 Data: #20 Date: 2015/1/21 Temperature: 22 °C
Time: AM 10:50:15 Humidity: 60 %



Condition: -23.35 Horizontal
EUT: Sweep Time: 669ms Att.: 20dB
Model: RBW: 100 KHz VBW: 300 KHz
Test Mode:
Note: FCC-802.11g Channel 01-Conducted Spurious-3

No.	Frequency(MHz)	Level(dBm)
1	8616.66660	-55.92

File: FT0044E_HT20_2015 Data: #21 Date: 2015/1/21 Temperature: 22 °C
Time: AM 10:50:51 Humidity: 60 %



Condition: -23.35 Horizontal
EUT: Sweep Time: 1242.44ms Att.: 20dB
Model: RBW: 100 KHz VBW: 300 KHz
Test Mode:
Note: FCC-802.11g Channel 01-Conducted Spurious-4

No.	Frequency(MHz)	Level(dBm)
1	23461.66670	-50.89

Humidity: 60 %

No.	Frequency(MHz)	Level(dBm)
1	463.2667	-61.48


File: FT0044E_HT20_2015 Data: #23

Date: 2015/1/21

Temperature: 22 °C

Time: AM 10:53:44

Humidity: 60 %



Condition:

Horizontal

EUT:

Sweep Time: 382.28ms Att.: 20dB

Model:

RBW: 100 KHz

VBW: 300 KHz

Test Mode:

Note: FCC-802.11g Channel 06-Conducted Spurious-2

No.	Frequency(MHz)	Level(dBm)
1	2440.00000	-3.00
2	2480.00000	-40.63
3	3793.33330	-58.63


File: FT0044E_HT20_2015 Data: #24

Date: 2015/1/21

Temperature: 22 °C

Time: AM 10:54:31

Humidity: 60 %



Condition: -23.0

Horizontal

EUT:

Sweep Time: 669ms Att.: 20dB

Model:


RBW: 100 KHz VBW: 300 KHz

Test Mode:

Note: FCC-802.11g Channel 06-Conducted Spurious-3

No.	Frequency(MHz)	Level(dBm)
1	7753.33330	-55.28


File: FT0044E_HT20_2015 Data: #25 Date: 2015/1/21 Temperature: 22 °C
Time: AM 10:56:20 Humidity: 60 %



Condition: -23.0 Horizontal
EUT: Sweep Time: 1242.44ms Att.: 20dB
Model: RBW: 100 KHz VBW: 300 KHz
Test Mode:
Note: FCC-802.11g Channel 06-Conducted Spurious-4

No.	Frequency(MHz)	Level(dBm)
1	24220.00000	-52.10


File: FT0044E_HT20_2015 Data: #26 Date: 2015/1/21 Temperature: 22 °C
Time: AM 10:58:20 Humidity: 60 %



Condition: -19.92 Horizontal
EUT: Sweep Time: 92.72ms Att.: 20dB
Model: RBW: 100 KHz VBW: 300 KHz
Test Mode:
Note: FCC-802.11g Channel 11-Conducted Spurious-1

No.	Frequency(MHz)	Level(dBm)
1	581.2833	-60.75


File: FT0044E_HT20_2015 Data: #27 Date: 2015/1/21 Temperature: 22 °C
Time: AM 10:58:53 Humidity: 60 %



Condition: Horizontal
EUT: Sweep Time: 382.28ms Att.: 20dB
Model: RBW: 100 KHz VBW: 300 KHz
Test Mode:
Note: FCC-802.11g Channel 11-Conducted Spurious-2

No.	Frequency(MHz)	Level(dBm)
1	2466.66660	0.08
2	2613.33330	-50.31
3	3986.66670	-58.53

File: FT0044E_HT20_2015 Data: #28 Date: 2015/1/21 Temperature: 22 °C
Time: AM 10:59:51 Humidity: 60 %



Condition: -19.92 Horizontal
EUT: Sweep Time: 669ms Att.: 20dB
Model: RBW: 100 KHz VBW: 300 KHz
Test Mode:
Note: FCC-802.11g Channel 11-Conducted Spurious-3

No.	Frequency(MHz)	Level(dBm)
1	7741.66670	-55.91

Humidity: 60 %

No.	Frequency(MHz)	Level(dBm)
1	24350.00000	-51.67

10 RADIATED EMISSION MEASUREMENT

10.1 Standard Applicable

For unintentional radiator, the radiated emission shall comply with §15.109(a).

For intentional radiators, according to §15.247 (a), operation under this provision is limited to frequency hopping and direct sequence spread spectrum, and the out band emission shall be comply with §15.247 (d)

10.2 Measurement Procedure

The testing follows FCC KDB 558074 D01 v03r02.

1. Setup the configuration per figure 1 and 2 for frequencies measured below and above 1 GHz respectively. Turn on EUT and make sure that it is in continuous operating function.
2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a semi-anechoic chamber to determine the accurate frequencies of higher emissions and then each selected frequency is precisely measured. As the same purpose, for emission measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
3. For emission measured below and above 1 GHz, set the spectrum analyzer on a 120 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0 ° to 360 ° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading. A RF test receiver is also used to confirm emissions measured.

Figure 2 : Frequencies measured below 1 GHz configuration





Figure 3 : Frequencies measured above 1 GHz configuration



10.3 Measuring Instrument

The following instrument are used for radiated emissions measurement :

Equipment	Manufacturer	Model No.
EMI Test Receiver	R&S	ESIB7
Spectrum Analyzer	R&S	FSV 40
Horn Antenna	EMCO	3115
BiLog Antenna	ETC	MCTD2786
Horn Antenna	EMCO	3116
Preamplifier	Hewlett-Packard	8449B
Loop Antenna	EMCO	6512
PRE-Amplifier	EMCI	PA303N

Measuring instrument setup in measured frequency band when specified detector function is used :

Frequency Band (MHz)	Instrument	Function	Resolution Bandwidth	Video Bandwidth
30 to 1000	RF Test Receiver	Quasi-Peak	120 kHz	300 kHz
	Spectrum Analyzer	Peak	120 kHz	300 kHz
Above 1000	Spectrum Analyzer	Peak	1 MHz	1 MHz
	Spectrum Analyzer	Average	1 MHz	VBW_avg (Note)

Note:For average measurement

Condition	VBW_avg
Duty cycle is no less than 98 percent	10 Hz
Duty cycle is less than 98 percent, T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation	$\geq \frac{1}{T}$
Current use	10Hz

Duty Cycle Calculation :


Duty Cycle (%) > 98%

The plotted graph of Duty Cycle please see page 94 ~ 95.

Humidity: 60 %



Humidity: 60 %



Horizontal

Sweep Time: 100ms Att.: 30dB

RBW: 1000 KHz VBW: 1000 KHz

Note: **Duty Cycle-2 (100ms)**

10.4 Radiated Emission Data

10.4.1 Harmonic

10.4.1.1 Operation Mode: Tx

10.4.1.1.1 IEEE 802.11b

Test Date: Jan. 07, 2015Temperature: 22°CHumidity: 60%

a) Channel 1

Fundamental Frequency: 2412 MHz

Frequency	Ant Pol	Reading (dBuV/m)@3m		Correct Factor	Result (dBuV/m)@3m		Limit (dBuV/m)@3m		Margin (worse)
(MHz)	H/V	Peak	AVG	(dB)	Peak	AVG	Peak	AVG	(dB)
4824.0000	H	53.5	49.4	-1.99	51.5	47.4	74.0	54.0	-6.6
4824.0000	V	55.2	52.0	-1.99	53.2	50.0	74.0	54.0	-4.0
7236.0000	H	---	---	0.97	---	---	74.0	54.0	---
7236.0000	V	---	---	0.97	---	---	74.0	54.0	---
9648.0000	H	---	---	2.55	---	---	74.0	54.0	---
9648.0000	V	---	---	2.55	---	---	74.0	54.0	---
12060.0000	H	---	---	4.84	---	---	74.0	54.0	---
12060.0000	V	---	---	4.84	---	---	74.0	54.0	---
14472.0000	H	---	---	9.35	---	---	74.0	54.0	---
14472.0000	V	---	---	9.35	---	---	74.0	54.0	---

Note :

1. Item of margin shown in above table refer to average limit.
2. Remark “---” means that the emissions level is too low to be measured.
3. If the peak result is under the average limit, that is deemed to meet the average limit.
4. If there is only peak result, item “Margin” referred to “peak result – average limit”.
5. The radiation emissions have been measured to beyond the tenth harmonic of the fundamental frequency and show the significant frequencies, other means the value is too low to be detected.

b) Channel 6

Fundamental Frequency: 2437 MHz

Frequency	Ant Pol	Reading (dBuV/m)@3m		Correct Factor	Result (dBuV/m)@3m		Limit (dBuV/m)@3m		Margin (worse)
(MHz)	H/V	Peak	AVG	(dB)	Peak	AVG	Peak	AVG	(dB)
4874.0000	H	54.2	50.6	-1.88	52.3	48.7	74.0	54.0	-5.3
4874.0000	V	56.8	53.8	-1.88	54.9	51.9	74.0	54.0	-2.1
7311.0000	H	---	---	1.15	---	---	74.0	54.0	---
7311.0000	V	---	---	1.15	---	---	74.0	54.0	---
9748.0000	H	---	---	2.65	---	---	74.0	54.0	---
9748.0000	V	---	---	2.65	---	---	74.0	54.0	---
12185.0000	H	---	---	4.91	---	---	74.0	54.0	---
12185.0000	V	---	---	4.91	---	---	74.0	54.0	---
14622.0000	H	---	---	8.68	---	---	74.0	54.0	---
14622.0000	V	---	---	8.68	---	---	74.0	54.0	---

Note :

1. Item of margin shown in above table refer to average limit.
2. Remark “---” means that the emissions level is too low to be measured.
3. If the peak result is under the average limit, that is deemed to meet the average limit.
4. If there is only peak result, item “Margin” referred to “peak result – average limit”.
5. The radiation emissions have been measured to beyond the tenth harmonic of the fundamental frequency and show the significant frequencies, other means the value is too low to be detected.

c) Channel 11

Fundamental Frequency: 2462 MHz

Frequency	Ant Pol	Reading (dBuV/m)@3m		Correct Factor	Result (dBuV/m)@3m		Limit (dBuV/m)@3m		Margin (worse)
(MHz)	H/V	Peak	AVG	(dB)	Peak	AVG	Peak	AVG	(dB)
4924.0000	H	53.4	49.5	-1.77	51.6	47.7	74.0	54.0	-6.3
4924.0000	V	56.1	52.2	-1.77	54.3	50.4	74.0	54.0	-3.6
7386.0000	H	---	---	1.33	---	---	74.0	54.0	---
7386.0000	V	---	---	1.33	---	---	74.0	54.0	---
9848.0000	H	---	---	2.75	---	---	74.0	54.0	---
9848.0000	V	---	---	2.75	---	---	74.0	54.0	---
12310.0000	H	---	---	4.99	---	---	74.0	54.0	---
12310.0000	V	---	---	4.99	---	---	74.0	54.0	---
14772.0000	H	---	---	7.93	---	---	74.0	54.0	---
14772.0000	V	---	---	7.93	---	---	74.0	54.0	---

Note :

1. Item of margin shown in above table refer to average limit.
2. Remark “---” means that the emissions level is too low to be measured.
3. If the peak result is under the average limit, that is deemed to meet the average limit.
4. If there is only peak result, item “Margin” referred to “peak result – average limit”.
5. The radiation emissions have been measured to beyond the tenth harmonic of the fundamental frequency and show the significant frequencies, other means the value is too low to be detected.

10.4.1.1.2 IEEE 802.11g

Test Date: Jan. 07, 2015Temperature: 22°CHumidity: 60%

a) Channel 1

Fundamental Frequency: 2412 MHz

Frequency	Ant Pol	Reading (dBuV/m)@3m		Correct Factor	Result (dBuV/m)@3m		Limit (dBuV/m)@3m		Margin (worse)
(MHz)	H/V	Peak	AVG	(dB)	Peak	AVG	Peak	AVG	(dB)
4824.0000	H	53.7	39.9	-1.99	51.7	37.9	74.0	54.0	-16.1
4824.0000	V	57.2	42.0	-1.99	55.2	40.0	74.0	54.0	-14.0
7236.0000	H	---	---	0.97	---	---	74.0	54.0	---
7236.0000	V	---	---	0.97	---	---	74.0	54.0	---
9648.0000	H	---	---	2.55	---	---	74.0	54.0	---
9648.0000	V	---	---	2.55	---	---	74.0	54.0	---
12060.0000	H	---	---	4.84	---	---	74.0	54.0	---
12060.0000	V	---	---	4.84	---	---	74.0	54.0	---
14472.0000	H	---	---	9.35	---	---	74.0	54.0	---
14472.0000	V	---	---	9.35	---	---	74.0	54.0	---

Note :

1. Item of margin shown in above table refer to average limit.
2. Remark “---” means that the emissions level is too low to be measured.
3. If the peak result is under the average limit, that is deemed to meet the average limit.
4. If there is only peak result, item “Margin” referred to “peak result – average limit”.
5. The radiation emissions have been measured to beyond the tenth harmonic of the fundamental frequency and show the significant frequencies, other means the value is too low to be detected.

b) Channel 6

Fundamental Frequency: 2437 MHz

Frequency	Ant Pol	Reading (dBuV/m)@3m		Correct Factor	Result (dBuV/m)@3m		Limit (dBuV/m)@3m		Margin (worse)
(MHz)	H/V	Peak	AVG	(dB)	Peak	AVG	Peak	AVG	(dB)
4874.0000	H	55.4	40.1	-1.88	53.5	38.2	74.0	54.0	-15.8
4874.0000	V	57.0	42.8	-1.88	55.1	40.9	74.0	54.0	-13.1
7311.0000	H	---	---	1.15	---	---	74.0	54.0	---
7311.0000	V	---	---	1.15	---	---	74.0	54.0	---
9748.0000	H	---	---	2.65	---	---	74.0	54.0	---
9748.0000	V	---	---	2.65	---	---	74.0	54.0	---
12185.0000	H	---	---	4.91	---	---	74.0	54.0	---
12185.0000	V	---	---	4.91	---	---	74.0	54.0	---
14622.0000	H	---	---	8.68	---	---	74.0	54.0	---
14622.0000	V	---	---	8.68	---	---	74.0	54.0	---

Note :

1. Item of margin shown in above table refer to average limit.
2. Remark “---” means that the emissions level is too low to be measured.
3. If the peak result is under the average limit, that is deemed to meet the average limit.
4. If there is only peak result, item “Margin” referred to “peak result – average limit”.
5. The radiation emissions have been measured to beyond the tenth harmonic of the fundamental frequency and show the significant frequencies, other means the value is too low to be detected.

c) Channel 11

Fundamental Frequency: 2462 MHz

Frequency	Ant Pol	Reading (dBuV/m)@3m		Correct Factor	Result (dBuV/m)@3m		Limit (dBuV/m)@3m		Margin (worse)
(MHz)	H/V	Peak	AVG	(dB)	Peak	AVG	Peak	AVG	(dB)
4924.0000	H	53.5	38.2	-1.77	51.7	36.4	74.0	54.0	-17.6
4924.0000	V	55.8	41.1	-1.77	54.0	39.3	74.0	54.0	-14.7
7386.0000	H	---	---	1.33	---	---	74.0	54.0	---
7386.0000	V	---	---	1.33	---	---	74.0	54.0	---
9848.0000	H	---	---	2.75	---	---	74.0	54.0	---
9848.0000	V	---	---	2.75	---	---	74.0	54.0	---
12310.0000	H	---	---	4.99	---	---	74.0	54.0	---
12310.0000	V	---	---	4.99	---	---	74.0	54.0	---
14772.0000	H	---	---	7.93	---	---	74.0	54.0	---
14772.0000	V	---	---	7.93	---	---	74.0	54.0	---

Note :

1. Item of margin shown in above table refer to average limit.
2. Remark “---” means that the emissions level is too low to be measured.
3. If the peak result is under the average limit, that is deemed to meet the average limit.
4. If there is only peak result, item “Margin” referred to “peak result – average limit”.
5. The radiation emissions have been measured to beyond the tenth harmonic of the fundamental frequency and show the significant frequencies, other means the value is too low to be detected.

10.4.1.1.3 IEEE 802.11gn, HT20

Test Date: Jan. 07, 2015Temperature: 22°CHumidity: 60%

a) Channel 1

Fundamental Frequency: 2412 MHz

Frequency	Ant Pol	Reading (dBuV/m)@3m		Correct Factor	Result (dBuV/m)@3m		Limit (dBuV/m)@3m		Margin (worse)
(MHz)	H/V	Peak	AVG	(dB)	Peak	AVG	Peak	AVG	(dB)
4824.0000	H	55.0	39.5	-1.99	53.0	37.5	74.0	54.0	-16.5
4824.0000	V	57.4	40.9	-1.99	55.4	38.9	74.0	54.0	-15.1
7236.0000	H	---	---	0.97	---	---	74.0	54.0	---
7236.0000	V	---	---	0.97	---	---	74.0	54.0	---
9648.0000	H	---	---	2.55	---	---	74.0	54.0	---
9648.0000	V	---	---	2.55	---	---	74.0	54.0	---
12060.0000	H	---	---	4.84	---	---	74.0	54.0	---
12060.0000	V	---	---	4.84	---	---	74.0	54.0	---
14472.0000	H	---	---	9.35	---	---	74.0	54.0	---
14472.0000	V	---	---	9.35	---	---	74.0	54.0	---

Note :

1. Item of margin shown in above table refer to average limit.
2. Remark “---” means that the emissions level is too low to be measured.
3. If the peak result is under the average limit, that is deemed to meet the average limit.
4. If there is only peak result, item “Margin” referred to “peak result – average limit”.
5. The radiation emissions have been measured to beyond the tenth harmonic of the fundamental frequency and show the significant frequencies, other means the value is too low to be detected.

b) Channel 6

Fundamental Frequency: 2437 MHz

Frequency	Ant Pol	Reading (dBuV/m)@3m		Correct Factor	Result (dBuV/m)@3m		Limit (dBuV/m)@3m		Margin (worse)
(MHz)	H/V	Peak	AVG	(dB)	Peak	AVG	Peak	AVG	(dB)
4874.0000	H	55.2	39.7	-1.88	53.3	37.8	74.0	54.0	-16.2
4874.0000	V	57.6	42.2	-1.88	55.7	40.3	74.0	54.0	-13.7
7311.0000	H	---	---	1.15	---	---	74.0	54.0	---
7311.0000	V	---	---	1.15	---	---	74.0	54.0	---
9748.0000	H	---	---	2.65	---	---	74.0	54.0	---
9748.0000	V	---	---	2.65	---	---	74.0	54.0	---
12185.0000	H	---	---	4.91	---	---	74.0	54.0	---
12185.0000	V	---	---	4.91	---	---	74.0	54.0	---
14622.0000	H	---	---	8.68	---	---	74.0	54.0	---
14622.0000	V	---	---	8.68	---	---	74.0	54.0	---

Note :

1. Item of margin shown in above table refer to average limit.
2. Remark “---” means that the emissions level is too low to be measured.
3. If the peak result is under the average limit, that is deemed to meet the average limit.
4. If there is only peak result, item “Margin” referred to “peak result – average limit”.
5. The radiation emissions have been measured to beyond the tenth harmonic of the fundamental frequency and show the significant frequencies, other means the value is too low to be detected.

c) Channel 11

Fundamental Frequency: 2462 MHz

Frequency (MHz)	Ant Pol	Reading (dBuV/m)@3m		Correct Factor (dB)	Result (dBuV/m)@3m		Limit (dBuV/m)@3m		Margin (worse) (dB)
		Peak	AVG		Peak	AVG	Peak	AVG	
4924.0000	H	53.3	37.4	-1.77	51.5	35.6	74.0	54.0	-18.4
4924.0000	V	56.3	40.1	-1.77	54.5	38.3	74.0	54.0	-15.7
7386.0000	H	---	---	1.33	---	---	74.0	54.0	---
7386.0000	V	---	---	1.33	---	---	74.0	54.0	---
9848.0000	H	---	---	2.75	---	---	74.0	54.0	---
9848.0000	V	---	---	2.75	---	---	74.0	54.0	---
12310.0000	H	---	---	4.99	---	---	74.0	54.0	---
12310.0000	V	---	---	4.99	---	---	74.0	54.0	---
14772.0000	H	---	---	7.93	---	---	74.0	54.0	---
14772.0000	V	---	---	7.93	---	---	74.0	54.0	---

Note :

1. Item of margin shown in above table refer to average limit.
2. Remark “---” means that the emissions level is too low to be measured.
3. If the peak result is under the average limit, that is deemed to meet the average limit.
4. If there is only peak result, item “Margin” referred to “peak result – average limit”.
5. The radiation emissions have been measured to beyond the tenth harmonic of the fundamental frequency and show the significant frequencies, other means the value is too low to be detected.

10.4.2 Spurious Emission

Operation Mode: Tx

10.4.2.1 30MHz to 1GHz


File: FT0044E_15C_Below Data: #4
1G_2015

Date: 2015/1/7

Temperature: 22 °C

Time: AM 11:24:33

Humidity: 60 %



Condition: FCC Class B 3M Radiation

Polarization: Horizontal

EUT:

Distance:

No.	Frequency (MHz)	Reading (dBuV/m)	Detector	Corrected dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	123.1200	16.74	peak	14.15	30.89	43.50	-12.61
2	209.4500	25.13	peak	12.55	37.68	43.50	-5.82
3	215.9734	28.80	QP	12.66	41.46	43.50	-2.04
4	216.0760	30.14	QP	12.66	42.80	46.00	-3.20
5	246.3100	20.88	peak	14.91	35.79	46.00	-10.21
6	457.7700	15.91	peak	20.29	36.20	46.00	-9.80
7	482.9900	17.36	peak	20.79	38.15	46.00	-7.85
8	507.2400	19.58	peak	21.24	40.82	46.00	-5.18
9	532.4600	16.77	peak	21.72	38.49	46.00	-7.51


File: FT0044E_15C_Below Data: #3
1G_2015

Date: 2015/1/7

Temperature: 22 °C

Time: AM 11:18:09

Humidity: 60 %



Condition: FCC Class B 3M Radiation

Polarization: Vertical

EUT:

Distance:

No.	Frequency (MHz)	Reading (dBuV/m)	Detector	Corrected dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
1	110.5100	14.18	peak	13.75	27.93	43.50	-15.57
2	209.4500	19.54	peak	12.55	32.09	43.50	-11.41
3	216.2400	24.17	peak	12.66	36.83	46.00	-9.17
4	246.3100	16.18	peak	14.91	31.09	46.00	-14.91
5	867.1100	9.22	peak	25.53	34.75	46.00	-11.25
6	904.9400	10.54	peak	25.98	36.52	46.00	-9.48
7	977.6900	9.20	peak	26.78	35.98	54.00	-18.02

10.4.2.2 above 1GHz

10.4.2.2.1 IEEE 802.11b

10.4.2.2.1.1 Fundamental Frequency: 2412 MHz

Frequency	Ant Pol	Reading (dBuV/m)@3m		Correct Factor	Result (dBuV/m)@3m		Limit (dBuV/m)@3m		Margin (worse)
(MHz)	H/V	Peak	AVG	(dB)	Peak	AVG	Peak	AVG	(dB)
1087.5000	H	49.5	---	-13.95	35.6	---	74	54	-18.4
1123.3974	V	49.1	---	-13.78	35.3	---	74	54	-18.7
1141.3461	H	49.1	---	-13.69	35.4	---	74	54	-18.6
1152.5641	V	52.0	---	-13.64	38.4	---	74	54	-15.6
1883.9744	H	52.5	---	-9.91	42.6	---	74	54	-11.4
1883.9744	V	51.0	---	-9.91	41.1	---	74	54	-12.9
3130.0207	H	48.3	---	-5.43	42.9	---	74	54	-11.1
3378.6826	V	48.5	---	-4.74	43.8	---	74	54	-10.2

10.4.2.2.1.2 Fundamental Frequency: 2437 MHz

Frequency	Ant Pol	Reading (dBuV/m)@3m		Correct Factor	Result (dBuV/m)@3m		Limit (dBuV/m)@3m		Margin (worse)
(MHz)	H/V	Peak	AVG	(dB)	Peak	AVG	Peak	AVG	(dB)
1123.3974	H	49.2	---	-13.78	35.4	---	74	54	-18.6
1143.5896	V	49.3	---	-13.68	35.6	---	74	54	-18.4
1791.9872	H	48.5	---	-10.38	38.1	---	74	54	-15.9
1883.9744	H	51.6	---	-9.91	41.7	---	74	54	-12.3
1883.9744	V	49.5	---	-9.91	39.6	---	74	54	-14.4
1951.2820	V	48.1	---	-9.56	38.5	---	74	54	-15.5
1978.2050	V	48.1	---	-9.41	38.7	---	74	54	-15.3
3055.4223	V	48.5	---	-5.65	42.9	---	74	54	-11.1
3130.0207	V	50.2	---	-5.43	44.8	---	74	54	-9.2
3403.5488	V	48.4	---	-4.67	43.7	---	74	54	-10.3

10.4.2.2.1.3 Fundamental Frequency: 2462 MHz

Frequency	Ant Pol	Reading (dBuV/m)@3m		Correct Factor	Result (dBuV/m)@3m		Limit (dBuV/m)@3m		Margin (worse)
(MHz)	H/V	Peak	AVG	(dB)	Peak	AVG	Peak	AVG	(dB)
1087.5000	H	52.6	---	-13.95	38.7	---	74	54	-15.3
1105.4486	H	52.7	---	-13.87	38.8	---	74	54	-15.2
1141.3461	H	52.7	---	-13.69	39.0	---	74	54	-15.0
1161.5385	H	52.1	---	-13.60	38.5	---	74	54	-15.5
1385.8974	V	51.5	---	-12.48	39.0	---	74	54	-15.0
1787.5000	V	51.8	---	-10.40	41.4	---	74	54	-12.6
1827.8846	V	52.5	---	-10.19	42.3	---	74	54	-11.7
1866.0255	V	51.9	---	-9.99	41.9	---	74	54	-12.1
1958.0127	H	50.8	---	-9.52	41.3	---	74	54	-12.7
2980.8236	V	51.5	---	-5.88	45.6	---	74	54	-8.4
3130.0207	H	50.9	---	-5.43	45.5	---	74	54	-8.5
3254.3517	V	50.9	---	-5.09	45.8	---	74	54	-8.2
3453.2813	H	51.0	---	-4.53	46.5	---	74	54	-7.5

- Note: 1. Place of Measurement: Measuring site of the ETC.
2. Item of margin shown in above table refer to average limit.
3. Remark “---” means that the emissions level is too low to be measured.
4. If the peak result is under the average limit, that is deemed to meet the average limit.
5. If there is only peak result, item “Margin” referred to “peak result – average limit”.
6. The radiation emissions have been measured to beyond the tenth harmonic of the fundamental frequency and show the significant frequencies, other means the value is too low to be detected.
7. The estimated measurement uncertainty of the result measurement is
- ±4.2dB ($9\text{kHz} \leq f \leq 30\text{MHz}$)
 - ±4.6dB ($30\text{MHz} \leq f < 300\text{MHz}$).
 - ±4.4dB ($300\text{MHz} \leq f < 1000\text{MHz}$).
 - ±2.9dB ($1\text{GHz} \leq f < 18\text{GHz}$).
 - ±3.5dB ($18\text{GHz} \leq f \leq 40\text{GHz}$).

10.4.2.2.2 IEEE 802.11g

10.4.2.2.2.1 Fundamental Frequency: 2412 MHz

Frequency	Ant Pol	Reading (dBuV/m)@3m		Correct Factor	Result (dBuV/m)@3m		Limit (dBuV/m)@3m		Margin (worse)
(MHz)	H/V	Peak	AVG	(dB)	Peak	AVG	Peak	AVG	(dB)
1087.5000	H	51.3	---	-13.95	37.4	---	74	54	-16.6
1123.3974	H	52.5	---	-13.78	38.7	---	74	54	-15.3
1143.5896	H	51.7	---	-13.68	38.0	---	74	54	-16.0
1179.4872	V	50.9	---	-13.51	37.4	---	74	54	-16.6
1385.8974	V	51.1	---	-12.48	38.6	---	74	54	-15.4
1800.9614	V	51.3	---	-10.34	41.0	---	74	54	-13.0
1818.9103	V	51.2	---	-10.24	41.0	---	74	54	-13.0
1845.8333	H	50.2	---	-10.10	40.1	---	74	54	-13.9
1848.0770	V	50.4	---	-10.09	40.3	---	74	54	-13.7
1958.0127	H	51.1	---	-9.52	41.6	---	74	54	-12.4
1987.1794	V	51.7	---	-9.37	42.3	---	74	54	-11.7
2707.2957	V	49.9	---	-6.86	43.0	---	74	54	-11.0
2806.7604	H	50.6	---	-6.50	44.1	---	74	54	-9.9
3130.0207	V	51.0	---	-5.43	45.6	---	74	54	-8.4
3453.2813	V	53.7	---	-4.53	49.2	---	74	54	-4.8
4248.9992	H	49.0	---	-2.60	46.4	---	74	54	-7.6

10.4.2.2.2 Fundamental Frequency: 2437 MHz

Frequency	Ant Pol	Reading (dBuV/m)@3m		Correct Factor	Result (dBuV/m)@3m		Limit (dBuV/m)@3m		Margin (worse)
(MHz)	H/V	Peak	AVG	(dB)	Peak	AVG	Peak	AVG	(dB)
1035.8974	H	51.4	---	-14.23	37.2	---	74	54	-16.8
1087.5000	H	51.9	---	-13.95	38.0	---	74	54	-16.0
1105.4486	H	51.6	---	-13.87	37.7	---	74	54	-16.3
1123.3974	H	51.6	---	-13.78	37.8	---	74	54	-16.2
1143.5896	H	51.4	---	-13.68	37.7	---	74	54	-16.3
1161.5385	H	51.2	---	-13.60	37.6	---	74	54	-16.4
1385.8974	V	51.9	---	-12.48	39.4	---	74	54	-14.6
1818.9103	V	51.6	---	-10.24	41.4	---	74	54	-12.6
1850.3205	V	51.2	---	-10.08	41.1	---	74	54	-12.9
1924.3590	V	51.4	---	-9.70	41.7	---	74	54	-12.3
1955.7691	V	50.3	---	-9.53	40.8	---	74	54	-13.2
1980.4486	V	51.2	---	-9.40	41.8	---	74	54	-12.2
2856.4927	H	50.6	---	-6.32	44.3	---	74	54	-9.7
3130.0207	H	49.8	---	-5.43	44.4	---	74	54	-9.6
3130.0207	V	52.8	---	-5.43	47.4	---	74	54	-6.6
3428.4151	V	53.8	---	-4.60	49.2	---	74	54	-4.8

10.4.2.2.2.3 Fundamental Frequency: 2462 MHz

Frequency	Ant Pol	Reading (dBuV/m)@3m		Correct Factor	Result (dBuV/m)@3m		Limit (dBuV/m)@3m		Margin (worse)
(MHz)	H/V	Peak	AVG	(dB)	Peak	AVG	Peak	AVG	(dB)
1123.3974	H	51.5	---	-13.78	37.7	---	74	54	-16.3
1143.5896	H	52.6	---	-13.68	38.9	---	74	54	-15.1
1143.5896	V	52.6	---	-13.68	38.9	---	74	54	-15.1
1161.5385	H	52.1	---	-13.60	38.5	---	74	54	-15.5
1385.8974	V	51.6	---	-12.48	39.1	---	74	54	-14.9
1796.4744	V	52.3	---	-10.35	42.0	---	74	54	-12.0
1818.9103	H	50.6	---	-10.24	40.4	---	74	54	-13.6
1818.9103	V	51.9	---	-10.24	41.7	---	74	54	-12.3
1951.2820	H	50.4	---	-9.56	40.8	---	74	54	-13.2
1987.1794	V	53.7	---	-9.37	44.3	---	74	54	-9.7
2000.6410	V	52.1	---	-9.30	42.8	---	74	54	-11.2
2308.0127	H	50.1	---	-8.25	41.9	---	74	54	-12.1
2906.2251	H	50.5	---	-6.14	44.4	---	74	54	-9.6
3130.0207	H	50.7	---	-5.43	45.3	---	74	54	-8.7
3130.0207	V	51.9	---	-5.43	46.5	---	74	54	-7.5
3403.5488	V	53.6	---	-4.67	48.9	---	74	54	-5.1

- Note: 1. Place of Measurement: Measuring site of the ETC.
 2. Item of margin shown in above table refer to average limit.
 3. Remark “---” means that the emissions level is too low to be measured.
 4. If the peak result is under the average limit, that is deemed to meet the average limit.
 5. If there is only peak result, item “Margin” referred to “peak result – average limit”.
 6. The radiation emissions have been measured to beyond the tenth harmonic of the fundamental frequency and show the significant frequencies, other means the value is too low to be detected.
 7. The estimated measurement uncertainty of the result measurement is
 $\pm 4.2\text{dB}$ ($9\text{kHz} \leq f \leq 30\text{MHz}$)
 $\pm 4.6\text{dB}$ ($30\text{MHz} \leq f < 300\text{MHz}$)
 $\pm 4.4\text{dB}$ ($300\text{MHz} \leq f < 1000\text{MHz}$)
 $\pm 2.9\text{dB}$ ($1\text{GHz} \leq f < 18\text{GHz}$)
 $\pm 3.5\text{dB}$ ($18\text{GHz} \leq f \leq 40\text{GHz}$).

10.4.2.2.3 IEEE 802.11gn, HT20

10.4.2.2.3.1 Fundamental Frequency: 2412 MHz

Frequency	Ant Pol	Reading (dBuV/m)@3m		Correct Factor	Result (dBuV/m)@3m		Limit (dBuV/m)@3m		Margin (worse)
(MHz)	H/V	Peak	AVG	(dB)	Peak	AVG	Peak	AVG	(dB)
1105.4486	H	51.5	---	-13.87	37.6	---	74	54	-16.4
1141.3461	H	52.0	---	-13.69	38.3	---	74	54	-15.7
1287.1794	H	50.7	---	-12.97	37.7	---	74	54	-16.3
1385.8974	V	51.7	---	-12.48	39.2	---	74	54	-14.8
1484.6153	H	50.4	---	-11.98	38.4	---	74	54	-15.6
1796.4744	V	51.9	---	-10.35	41.6	---	74	54	-12.4
1816.6666	V	50.5	---	-10.25	40.3	---	74	54	-13.7
1875.0000	V	50.6	---	-9.95	40.7	---	74	54	-13.3
1955.7691	V	51.2	---	-9.53	41.7	---	74	54	-12.3
1982.6922	V	54.2	---	-9.40	44.8	---	74	54	-9.2
2881.3590	H	50.1	---	-6.23	43.9	---	74	54	-10.1
3130.0207	H	49.9	---	-5.43	44.5	---	74	54	-9.5
3130.0207	V	52.2	---	-5.43	46.8	---	74	54	-7.2
3428.4151	V	52.3	---	-4.60	47.7	---	74	54	-6.3
3453.2813	H	49.7	---	-4.53	45.2	---	74	54	-8.8

10.4.2.2.3.2 Fundamental Frequency: 2437 MHz

Frequency	Ant Pol	Reading (dBuV/m)@3m		Correct Factor	Result (dBuV/m)@3m		Limit (dBuV/m)@3m		Margin (worse)
(MHz)	H/V	Peak	AVG	(dB)	Peak	AVG	Peak	AVG	(dB)
1031.4103	H	51.3	---	-14.24	37.1	---	74	54	-16.9
1087.5000	H	51.6	---	-13.95	37.7	---	74	54	-16.3
1143.5896	H	52.2	---	-13.68	38.5	---	74	54	-15.5
1385.8974	V	52.5	---	-12.48	40.0	---	74	54	-14.0
1818.9103	V	51.4	---	-10.24	41.2	---	74	54	-12.8
1827.8846	V	51.0	---	-10.19	40.8	---	74	54	-13.2
1942.3077	V	50.5	---	-9.60	40.9	---	74	54	-13.1
1980.4486	V	50.8	---	-9.40	41.4	---	74	54	-12.6
1993.9103	H	51.7	---	-9.33	42.4	---	74	54	-11.6
2403.5488	H	50.5	---	-7.93	42.6	---	74	54	-11.4
2732.1620	V	49.4	---	-6.77	42.6	---	74	54	-11.4
2806.7604	H	49.9	---	-6.50	43.4	---	74	54	-10.6
3080.2885	V	53.0	---	-5.57	47.4	---	74	54	-6.6
3130.0207	H	50.9	---	-5.43	45.5	---	74	54	-8.5
3378.6826	V	49.7	---	-4.74	45.0	---	74	54	-9.0

10.4.2.2.3.3 Fundamental Frequency: 2462 MHz

Frequency (MHz)	Ant Pol	Reading (dBuV/m)@3m		Correct Factor (dB)	Result (dBuV/m)@3m		Limit (dBuV/m)@3m		Margin (worse) (dB)
		Peak	AVG		Peak	AVG	Peak	AVG	
1087.5000	H	51.0	---	-13.95	37.1	---	74	54	-16.9
1143.5896	H	52.3	---	-13.68	38.6	---	74	54	-15.4
1300.6410	H	51.0	---	-12.90	38.1	---	74	54	-15.9
1311.8590	V	51.0	---	-12.85	38.2	---	74	54	-15.8
1385.8974	V	50.9	---	-12.48	38.4	---	74	54	-15.6
1484.6153	H	50.4	---	-11.98	38.4	---	74	54	-15.6
1783.0127	V	50.9	---	-10.43	40.5	---	74	54	-13.5
1818.9103	V	51.5	---	-10.24	41.3	---	74	54	-12.7
1987.1794	V	51.0	---	-9.37	41.6	---	74	54	-12.4
2002.8846	H	52.3	---	-9.29	43.0	---	74	54	-11.0
2139.7435	V	49.1	---	-8.82	40.3	---	74	54	-13.7
2707.2957	V	49.9	---	-6.86	43.0	---	74	54	-11.0
2757.0280	H	49.7	---	-6.68	43.0	---	74	54	-11.0
3179.7532	V	52.4	---	-5.29	47.1	---	74	54	-6.9

- Note: 1. Place of Measurement: Measuring site of the ETC.
2. Item of margin shown in above table refer to average limit.
3. Remark “---” means that the emissions level is too low to be measured.
4. If the peak result is under the average limit, that is deemed to meet the average limit.
5. If there is only peak result, item “Margin” referred to “peak result – average limit”.
6. The radiation emissions have been measured to beyond the tenth harmonic of the fundamental frequency and show the significant frequencies, other means the value is too low to be detected.
7. The estimated measurement uncertainty of the result measurement is
- ±4.2dB ($9\text{kHz} \leq f \leq 30\text{MHz}$)
 - ±4.6dB ($30\text{MHz} \leq f < 300\text{MHz}$).
 - ±4.4dB ($300\text{MHz} \leq f < 1000\text{MHz}$).
 - ±2.9dB ($1\text{GHz} \leq f < 18\text{GHz}$).
 - ±3.5dB ($18\text{GHz} \leq f \leq 40\text{GHz}$).

10.4.3 Radiated Measurement at Bandedge with Fundamental Frequencies and co-locationTest Date: Jan. 07, 2015Temperature: 22°CHumidity: 60%**10.4.3.1 Operation Mode: Tx****10.4.3.1.1 IEEE 802.11b**

Operation Channel	Frequenc	Reading @3m (dBuV/m)				Factor	Result		Limit @3m		Margin (worse)	
		H		V			(dBuV/m)		(dBuV/m)		(dB)	
	(MHz)	Peak	Ave	Peak	Ave	(dB)	Peak	Ave	Peak	Ave	Peak	Ave
Low	2390.000	40.4	15.5	38.7	14.3	29.8	70.2	45.3	74	54	-3.8	-8.8
High	2483.500	39.4	14.8	36.3	13.6	29.8	69.2	44.6	74	54	-4.8	-9.4

10.4.3.1.2 IEEE 802.11g

Operation Channel	Frequenc	Reading @3m (dBuV/m)				Factor	Result		Limit @3m		Margin (worse)	
		H		V			(dBuV/m)		(dBuV/m)		(dB)	
	(MHz)	Peak	Ave	Peak	Ave	(dB)	Peak	Ave	Peak	Ave	Peak	Ave
Low	2390.000	35.8	19.3	34.1	17.6	29.8	65.6	49.1	74	54	-8.4	-4.9
High	2483.500	37.9	20.1	34.7	17.9	29.8	67.7	49.9	74	54	-6.3	-4.1

10.4.3.1.3 IEEE 802.11gn, HT20

Operation Channel	Frequenc	Reading @3m (dBuV/m)				Factor	Result		Limit @3m		Margin (worse)	
		H		V			(dBuV/m)		(dBuV/m)		(dB)	
	(MHz)	Peak	Ave	Peak	Ave	(dB)	Peak	Ave	Peak	Ave	Peak	Ave
Low	2390.000	39.1	19.8	34.9	16.2	29.8	68.9	49.6	74	54	-5.1	-4.4
High	2483.500	39.7	20.4	35.7	16.9	29.8	69.5	50.2	74	54	-4.5	-3.8

Note :

1. Remark “---” means that the emissions level is too low to be measured.
2. The result is the highest value of radiated emission from restrict band of 2310 ~ 2390 MHz and 2483.5 ~ 2500 MHz.

10.5 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor, High Pass Filter Loss(if used) and Cable Loss, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

where

$$\text{Corrected Factor} = \text{Antenna Factor} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$

11. EQUIPMENTS LIST FOR TESTING

Equipment	Manufacturer	Model No.	S/N	Calibration Date	Next Cal. Due
Spectrum Analyzer	Agilent	E4446A	13052013-001	10/07/2014	10/06/2015
Power Meter	Agilent	N1922A	13053523-001	12/04/2014	12/05/2015
Peak Power Sensor	Agilent	N1912A	13050625-001	12/04/2014	12/05/2015
EMI Receiver	R&S	ESIB 7	13054414-001	07/20/2014	07/19/2015
Spectrum Analyzer	R&S	FSV 40	13052017-001	02/07/2014	02/06/2015
Horn Antenna	EMCO	3115	13059201-001	07/22/2014	07/21/2015
BiLog Antenna	ETC	MCTD2786	BL09D01004	02/07/2014	02/06/2015
Hom Antenna	EMCO	3116	13059202-001	08/22/2014	08/21/2015
PRE-Amplifier	Agilent	8449B	13040709-001	11/21/2014	11/20/2015
Loop Antenna	EMCO	6512	13054104-001	07/01/2014	06/30/2015
PRE-Amplifier	EMCI	PA303N	13040720-001	07/03/2014	07/02/2015