



849 NW STATE ROAD 45  
NEWBERRY, FL 32669 USA  
PH: 888.472.2424 OR  
352.472.5500  
FAX: 352.472.2030  
EMAIL: [INFO@TIMCOENGR.COM](mailto:INFO@TIMCOENGR.COM)  
[HTTP://WWW.TIMCOENGR.COM](http://WWW.TIMCOENGR.COM)

---

## RF Exposure Evaluation Report

<b>APPLICANT</b>	COBRA ELECTRONICS CORPORATION
	6500 WEST CORTLAND STREET CHICAGO IL 60707 USA
<b>FCC ID</b>	BBO29BT2K17
<b>IC</b>	906A-29BT2K17
<b>MODEL NUMBER</b>	RB106
<b>PRODUCT DESCRIPTION</b>	BLUE TOOTH MODULE
<b>STANDARD APPLIED</b>	CFR 47 Part 2.1091
<b>PREPARED BY</b>	Cory Leverett

We, TIMCO ENGINEERING, INC. would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and meets the requirements.

The attached report shall not be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

## GENERAL REMARKS

### Attestations

This equipment has been evaluated in accordance with the standards identified in this report. To the best of my knowledge and belief, these evaluations were performed using the procedures described in this report.

I attest that the necessary evaluations were made, under my supervision, at:

**Timco Engineering Inc.**  
**849 NW State Road 45**  
**Newberry, FL 32669**

### Authorized Signatory Name:

Cory Leverett

Engineering Project Manager

**Date: 10/31/2016**

A handwritten signature in black ink is written over a purple circular stamp. The stamp contains the text "TIMCO ENGINEERING, INC." around the perimeter and "2016" at the bottom. The signature is written in a cursive style.

## RF Exposure Requirements

### General information

Device type: **BLUETOOTH MODULE**

100 MHz to 6 GHz at separation distance less than or equal to 50 mm

#### SAR Test Exclusion Calculator for Portable Devices

Insert values in yellow highlighted boxes to determine SAR Exclusion

Max Power **2.2** mW

Min Separ **5** mm

Frequency **2.48** GHz

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Answer **0.7** Must be less than or equal to 3.0 for SAR Exclusion

KDB 388624 D02 Permit But Ask List v15, Item II. A. 5.

PBA is required if:

**General Population:** The Answer is equal to or greater than 24 (8x threshold)

**Controlled Use:** The Answer is equal to or greater than 60 (20x threshold)

**and**, when published RF exposure KDB procedures are not established for SAR testing or

Please also note the following: [FCC KDB quote] These test exclusion conditions are based on source-based time-

**Results: EUT meets requirements for standalone SAR exclusion**