

RF Exposure / SAR Statement

No. : 30GE0098-YK-A-R1

Applicant : RICOH COMPANY, LTD.
Type of Equipment : Option(s) for Radiocommunications
Model No. : R-WL54C1N
FCC ID : BBP-WLRWL542

RICOH COMPANY, LTD. declares that Model : Option(s) for Radiocommunications complies with FCC radiation exposure requirement specified in the FCC Rules 2.1091. The "R-WL54C1N" has 155.6 mW of conducted Peak Output power and 195.88 mW of EIRP. This equipment is considered as a mobile device so that SAR testing is excluded. The Following calculation is the reference data for 20cm distance.

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided with the "R-WL54C1N" as calculated from FCC OET Bulletin 65 Appendix A, Table (B) Limits for General Population / Uncontrolled Exposure. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0mW/cm² uncontrolled exposure limit. The Friis formula used was:

$$S = (P * G) / (4 * \pi * r^2)$$

Where

P = 155.60 mW (Maximum peak output power)
G = 1.26 Numerical Antenna gain; equal to 1.00 dBi
r = 20.0 cm

For: R-WL54C1N

$$S = 0.03897 \text{ mW/cm}^2$$

UL Japan, Inc.

Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone: +81 463 50 6400

Facsimile: +81 463 50 6401