

APPENDIX E: MULTI-TX AND ANTENNA SAR CONSIDERATIONS

E.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D04v01 and IEEE 1528-2013 Section 6.3.4.1.2 are applicable to devices with built-in unlicensed transmitters such as 802.11 and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

E.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore, simultaneous transmission analysis is required. Per FCC KDB Publication 447498 D04v01 and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1g SAR for all the simultaneous transmitting antennas in a specific physical test configuration is ≤ 1.6 W/kg. The different test positions in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1g or 10g SAR. Alternatively, simultaneous transmission SAR test exclusion may be evaluated using Total Exposure Ratio (TER).

E.3 Exposure Ratios

Exposure ratio (ER) for different transmitters is calculated as following:

$$ER_{SAR,n} = \frac{SAR_n}{SAR_{limit,n}}$$

Where:

- SAR_n is the SAR value for the n-th transmitter/test frequency
- $SAR_{limit,n}$ is the basic restriction limit that is applicable to the n-th transmitter/test frequency

E.4 Extremity SAR Simultaneous Transmission Analysis

For TER summation, the highest reported TER across all housing and wristband types was used as a conservative evaluation for simultaneous transmission analysis.

Table E-1
Simultaneous Transmission Scenario with 2.4 GHz WIFI and NFC (Extremity at 0.0 cm)

Exposure Condition	Configuration	2.4 GHz WIFI ER	NFC ER	Σ ER
		1	2	1+2
Extremity SAR	Back	0.005	0.000	0.005

Table E-2
Simultaneous Transmission Scenario with 2.4 GHz Bluetooth and NFC (Extremity at 0.0 cm)

Exposure Condition	Configuration	2.4 GHz Bluetooth ER	NFC ER	Σ ER
		1	2	1+2
Extremity SAR	Back	0.004	0.000	0.004

FCC ID: BCG-A3325	RF EXPOSURE REPORT	Approved by: Technical Manager
DUT Type: Watch		APPENDIX E: Page 1 of 2

E.5 Simultaneous Transmission Conclusion

The above numerical summed TER results for all the worst-case simultaneous transmission conditions were below the TER limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D04v01.

FCC ID: BCG-A3325	RF EXPOSURE REPORT	Approved by: Technical Manager
DUT Type: Watch		APPENDIX E: Page 2 of 2