

APPENDIX E: MULTI-TX AND ANTENNA SAR CONSIDERATIONS

E.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D04v01 are applicable to devices with built-in unlicensed transmitters such as 802.11 and Bluetooth devices which may simultaneously transmit.

E.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore, simultaneous transmission analysis is required. Per FCC KDB Publication 447498 D04v01 4.3.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1g SAR for all the simultaneous transmitting antennas in a specific physical test configuration is ≤ 1.6 W/kg. The different test positions in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1g or 10g SAR.

Note: In cases where simultaneous transmission scenarios overlap with the same power level (for example, cellular band + 2.4 GHz WIFI and cellular band + 2.4 GHz WIFI + 802.15.4 ab-NB), the most conservative SAR summation scenario was evaluated.

E.3 Head SAR Simultaneous Transmission Analysis

For SAR summation, the highest reported SAR across all housing and wristband types was used as a conservative evaluation for simultaneous transmission analysis.

Table E-1
Simultaneous Transmission Scenario with 2.4 GHz WLAN and 802.15.4 ab-NB (Head at 1.0 cm)

Exposure Condition	2.4 GHz WIFI ER	802.15.4 ab-NB ER	Σ ER
	1	2	1+2
Head SAR	0.212	0.008	0.220

Table E-2
Simultaneous Transmission Scenario with 2.4 GHz Bluetooth and 5 GHz WIFI (Head at 1.0 cm)

Exposure Condition	2.4 GHz Bluetooth ER	5 GHz WIFI ER	Σ ER
	1	2	1+2
Head SAR	0.132	0.089	0.221

Table E-3
Simultaneous Transmission Scenario with 2.4 GHz Bluetooth and 802.15.4 ab-NB (Head at 1.0 cm)

Exposure Condition	2.4 GHz Bluetooth ER	802.15.4 ab-NB ER	Σ ER
	1	2	1+2
Head SAR	0.132	0.008	0.140

FCC ID: BCG-A3331	RF EXPOSURE REPORT	Approved by: Technical Manager
DUT Type: Watch		APPENDIX E: Page 1 of 2

E.4 Extremity SAR Simultaneous Transmission Analysis

For SAR summation, the highest reported SAR across all housing and wristband types was used as a conservative evaluation for simultaneous transmission analysis.

Table E-4
Simultaneous Transmission Scenario with 2.4 GHz WLAN, 802.15.4 ab-NB, and NFC (Extremity at 0.0 cm)

Exposure Condition	2.4 GHz WIFI ER	802.15.4 ab-NB ER	NFC ER	Σ ER
	1	2	3	1+2+3
Extremity SAR	0.006	0.000	0.000	0.006

Table E-5
Simultaneous Transmission Scenario with 2.4 GHz Bluetooth, 5 GHz WIFI, and NFC (Extremity at 0.0 cm)

Exposure Condition	2.4 GHz Bluetooth ER	5 GHz WIFI ER	NFC ER	Σ ER
	1	2	3	1+2+3
Extremity SAR	0.003	0.004	0.000	0.007

Table E-6
Simultaneous Transmission Scenario with 2.4 GHz Bluetooth, 802.15.4 ab-NB, and NFC (Extremity at 0.0 cm)

Exposure Condition	2.4 GHz Bluetooth ER	802.15.4 ab-NB ER	NFC ER	Σ ER
	1	2	3	1+2+3
Extremity SAR	0.003	0.000	0.000	0.003

E.5 Simultaneous Transmission Conclusion

The above numerical summed SAR results for all the worst-case simultaneous transmission conditions were below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D04v01.

FCC ID: BCG-A3331	RF EXPOSURE REPORT	Approved by: Technical Manager
DUT Type: Watch		APPENDIX E: Page 2 of 2