






8.5.3. LTE BAND 7






8.5.4. LTE BAND 12







8.5.5. LTE BAND 13



8.5.6. LTE BAND 14



8.5.7. LTE BAND 17





8.5.8. LTE BAND 25






8.5.9. LTE BAND 26 (PART 90S)





8.5.10. LTE BAND 30




8.5.11. LTE BAND 41


ID:	39004	Date:	3/8/18
-----	-------	-------	--------

Band	Bandwidth (MHz)	Frequency (MHz)	RB Allocation	RB OffSet	Modulation	Conducted Power (dBm)		Peak-to-Average Power Ratio (dB)
						Peak	Average	
Band 41	5MHz	2593.0	25	0	QPSK	32.32	22.21	3.12
					16QAM	32.29	21.21	4.09
	10MHz		50	0	QPSK	32.32	22.24	3.09
					16QAM	32.39	21.31	4.09
	15MHz		75	0	QPSK	32.44	22.25	3.20
					16QAM	32.44	21.34	4.11
	20MHz		100	0	QPSK	32.51	22.27	3.25
					16QAM	32.52	21.32	4.21
Duty Cycle Correction Factor (dB) =			6.99					
Peak-to-Average Power Ratio= Peak Reading - Average Reading - Duty Cycle Correction Factor								

8.5.12. LTE BAND 66








8.5.13. LTE BAND 71





9. RADIATED TEST RESULTS

RULE PART(S)

§2.1053, §22.917, §24.238, §27.53, §90.691 and §90.543

LIMIT

§22.917(a), §24.238(a), §27.53 (g), (h), §90.691

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.

§27.53 (Band 13)

(c) The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.

(f) Emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals. (-70 dBW/MHz = -40 dBm/MHz).

§90.543(Band 14)

(e) (3) On any frequency between 775-788 MHz, above 805 MHz, and below 758 MHz, by at least $43 + 10 \log (P)$ dB.

(f) For operations in the 758-775 MHz and 788-805 MHz bands, all emissions including harmonics in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

§27.53 (a) (Band 30, Band 40)

For mobile and portable stations operating in the 2305-2315 MHz: by a factor of not less than $43 + 10 \log (P)$ dB on all frequencies between 2360 and 2365 MHz, and not less than $70 + 10 \log (P)$ dB above 2365 MHz.

§27.53 (m) (Band 7, 41)

At least $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section.

TEST PROCEDURE

KDB 971168 v03r01/ D02 v02r01

MODES TESTED

- LTE Band 2
- LTE Band 5
- LTE Band 7
- LTE Band 12
- LTE Band 13
- LTE Band 14
- LTE Band 17
- LTE Band 25
- LTE Band 26
- LTE Band 30
- LTE Band 41
- LTE Band 66
- LTE Band 71

RESULTS

