



CERTIFICATION TEST REPORT

Report Number. : 12204447-E12V3

Applicant : APPLE INC.
1 APPLE PARK WAY
CUPERTINO, CA. 95014, U.S.A.

Model : A2097

FCC ID : BCG-E3232A

IC : 579C-E3232A

EUT Description : SMARTPHONE

Test Standard(s) : FCC 47 CFR PART 15 SUBPART C
ISED RSS-247 ISSUE 2
ISED RSS-GEN ISSUE 5

Date Of Issue:
August 10, 2018

Prepared by:
UL Verification Services Inc.
47173 Benicia Street
Fremont, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888



NVLAP LAB CODE 200065-0

REPORT REVISION HISTORY

Rev.	Issue Date	Revisions	Revised By
V1	7/13/2018	Initial Issue	Chin Pang
V2	7/17/2018	Address TCB's Questions	Chin Pang
V3	8/10/2018	Address TCB's Questions	Jingang Li

TABLE OF CONTENTS

REPORT REVISION HISTORY	2
TABLE OF CONTENTS	3
1. ATTESTATION OF TEST RESULTS	5
2. TEST METHODOLOGY	6
3. FACILITIES AND ACCREDITATION	6
4. CALIBRATION AND UNCERTAINTY	7
4.1. MEASURING INSTRUMENT CALIBRATION	7
4.2. SAMPLE CALCULATION	7
4.3. MEASUREMENT UNCERTAINTY.....	7
5. EQUIPMENT UNDER TEST	8
5.1. EUT DESCRIPTION	8
5.2. MAXIMUM OUTPUT POWER.....	8
5.3. DESCRIPTION OF AVAILABLE ANTENNAS	8
5.4. SOFTWARE AND FIRMWARE.....	8
5.5. WORST-CASE CONFIGURATION AND MODE	9
5.6. DESCRIPTION OF TEST SETUP.....	10
6. MEASUREMENT METHOD.....	15
7. TEST AND MEASUREMENT EQUIPMENT	16
8. ANTENNA PORT TEST RESULTS	17
8.1. ON TIME AND DUTY CYCLE	17
8.2. 99% BANDWIDTH.....	20
8.2.1. HIGH POWER HDR4.....	21
8.2.2. HIGH POWER HDR8.....	23
8.2.3. LOW POWER HDR4	25
8.2.4. LOW POWER HDR8	27
8.3. 6 dB BANDWIDTH.....	29
8.3.1. HIGH POWER HDR4.....	30
8.3.2. HIGH POWER HDR8.....	32
8.3.3. LOW POWER HDR4	34
8.3.4. LOW POWER HDR8	36
8.4. OUTPUT POWER.....	38
8.4.1. HIGH POWER HDR4.....	39
8.4.2. HIGH POWER HDR8.....	40
8.4.3. LOW POWER HDR4	41
8.4.4. LOW POWER HDR8	42

8.5.	AVERAGE POWER	43
8.5.1.	HIGH POWER HDR4.....	44
8.5.2.	HIGH POWER HDR8.....	45
8.5.3.	LOW POWER HDR4	46
8.5.4.	LOW POWER HDR8	47
8.6.	POWER SPECTRAL DENSITY	48
8.6.1.	HIGH POWER HDR4.....	49
8.6.2.	HIGH POWER HDR8.....	51
8.6.3.	LOW POWER HDR4	53
8.6.4.	LOW POWER HDR8	55
8.7.	CONDUCTED SPURIOUS EMISSIONS.....	57
8.7.1.	HIGH POWER HDR4.....	58
8.7.2.	HIGH POWER HDR8.....	60
8.7.3.	LOW POWER HDR4	62
8.7.4.	LOW POWER HDR8	64
9.	RADIATED TEST RESULTS.....	66
9.1.	LIMITS AND PROCEDURE	66
9.2.	TRANSMITTER ABOVE 1 GHz	67
9.2.1.	HIGH POWER HDR4.....	67
9.2.2.	HIGH POWER HDR8.....	87
9.2.3.	LOW POWER HDR4	107
9.2.4.	LOW POWER HDR8	127
9.3.	Worst Case below 1 GHz.....	147
9.4.	Worst Case 18-26 GHz.....	149
10.	AC POWER LINE CONDUCTED EMISSIONS	151
10.1.1.	AC Power Line Host.....	152
10.1.2.	AC Power Line Norm.....	154
11.	SETUP PHOTOS	156

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: APPLE, INC.
1 APPLE PARK WAY
CUPERTINO, CA 95014, U.S.A.

EUT DESCRIPTION: SMARTPHONE

MODEL: A2097

SERIAL NUMBER: C39WP04UK95F

DATE TESTED: APRIL 18, 2018 – JULY 17, 2018

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart C	Complies
ISED RSS-247 Issue 2	Complies
ISED RSS-GEN Issue 5	Complies

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of the U.S. government.

Approved & Released For
UL Verification Services Inc. By:



Prepared By:



Chin Pang
CONSUMER TECHNOLOGY DIVISION
PROJECT LEAD
UL Verification Services Inc.

Jingang Li
CONSUMER TECHNOLOGY DIVISION
TEST ENGINEER
UL Verification Services Inc.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with FCC CFR 47 Part 2, FCC CFR 47 Part 15, KDB 558074 D01 v04, ANSI C63.10-2013, RSS-GEN Issue 5, and RSS-247 Issue 2.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 and 47266 Benicia Street, Fremont, California, USA. Line conducted emissions are measured only at the 47173 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

47173 Benicia Street	47266 Benicia Street
☐ Chamber A (ISED:2324B-1)	☒ Chamber D (ISED:22541-1)
☐ Chamber B (ISED:2324B-2)	☒ Chamber E (ISED:22541-2)
☐ Chamber C (ISED:2324B-3)	☐ Chamber F (ISED:22541-3)
	☐ Chamber G (ISED:22541-4)
	☐ Chamber H (ISED:22541-5)

The above test sites and facilities are covered under FCC Test Firm Registration # 208313. Chambers A through C is covered under ISED company address code 2324B with site numbers 2324B -1 through 2324B-3, respectively. Chambers D through H are covered under ISED company address code 22541 with site numbers 22541 -1 through 22541-5, respectively.

The above test sites and facilities are covered under FCC Test Firm Registration # 208313. UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at [NVLAP Lab Search](#).

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned} \text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m} \end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Worst Case Conducted Disturbance, 9KHz to 0.15 MHz	3.84 dB
Worst Case Conducted Disturbance, 0.15 to 30 MHz	3.65 dB
Worst Case Radiated Disturbance, 9KHz to 30 MHz	3.15 dB
Worst Case Radiated Disturbance, 30 to 1000 MHz	5.36 dB
Worst Case Radiated Disturbance, 1000 to 18000 MHz	4.32 dB
Worst Case Radiated Disturbance, 18000 to 26000 MHz	4.45 dB
Worst Case Radiated Disturbance, 26000 to 40000 MHz	5.24 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. EUT DESCRIPTION

The Apple iPhone, is a smartphone with multimedia functions (music, application support, and video), cellular GSM, GPRS, EGPRS, UMTS, LTE, TD-SCDMA, CDMA, IEEE 802.11a/b/g/n/ac, Bluetooth, GPS and NFC. All models support at least one UICC based SIM. The second SIM is either UICC based, electronic SIM (e-SIM), or second SIM is not present. The device has a built-in inductive charging receiver which is not user accessible. The rechargeable battery is not user accessible.

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak conducted output power as follows:

Antenna	Configuration	Frequency Range (MHz)	Mode	Output Power (dBm)	Output Power (mW)
Ant 4	Pstandalone	2404 - 2478	HDR4	18.63	72.95
	Plow			10.59	11.46
	Pstandalone		HDR8	18.42	69.50
	Plow			10.71	11.78
Ant 3	Pstandalone	2404 - 2478	HDR4	18.72	74.47
	Plow			10.72	11.80
	Pstandalone		HDR8	18.68	73.79
	Plow			10.59	11.46

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

Frequency Range (GHz)	Antenna 4 (dBi)	Antenna 3 (dBi)
2.4	-2.8	-4.1

5.4. SOFTWARE AND FIRMWARE

The EUT firmware installed during testing was v16.1.69.1066

5.5. WORST-CASE CONFIGURATION AND MODE

The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z on Ant 4 (Antenna 4) and Ant 3 (Antenna 3), it was determined that Z (Portrait) orientation was the worst-case orientation for both Ant 4 and Ant 3..

Pstandalone is high power, Plow is low power.

Radiated band edge, harmonic, and spurious emissions from 1GHz to 18GHz were performed with the EUT was set to transmit at highest power on Low/Middle/High channels.

Radiated emissions below 30MHz, below 1GHz, 18-26GHz and power line conducted emissions were performed with the EUT transmits at the channel with the highest output power as worst-case scenario.

For below 1GHz tests were performed with EUT connected to AC power adapter as the worst case; and for above 1GHz, the worst-case configuration reported was tested with EUT only. There were no emissions found below 30MHz within 20dB of the limit . For AC line conducted emission, test was investigated with AC power adapter and with laptop

There are two vendors of the WiFi/Bluetooth radio modules: variant 1 and variant 2. The Wi-Fi/Bluetooth radio modules have the same mechanical outline (e.g., the same package dimension and pin-out layout), use the same on-board antenna matching circuit, have an identical antenna structure, and are built and tested to conform to the same specifications and to operate within the same tolerances.

Baseline testing was performed on the two variants to determine the worst case on all conducted power and radiated emissions.

5.6. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Description	Manufacturer	Model	Serial Number	FCC ID
Laptop	Apple	MacBook Pro	HRP007154	FCC Doc
AC/DC adapter	Delta Electronic	A1343	ADP-85EBT V85	NA
EUT AC Adapter	Apple	A1385	D293062F3WVDHLHCF	NA

I/O CABLES (CONDUCTED TEST)

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	Antenna	1	SMA	Un-Shielded	0.2	To spectrum Analyzer
2	USB	1	USB	Shielded	1	N/A
3	AC	1	AC	Un-shielded	2	N/A

I/O CABLES (RADIATED ABOVE 1 GHZ)

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
None Used						


I/O CABLES (BELOW 1GHz AND AC POWER LINE TEST WITH ADAPTER AND LAPTOP)

I/O Cable List						
Cable No	Port	# of identical	Connector Type	Cable Type	Cable Length (m)	Remarks
1	AC	1	AC	Un-shielded	2	N/A
2	USB	1	USB	Un-shielded	1	N/A


TEST SETUP

The EUT is connected to a test laptop during the tests. Test software exercised the EUT.


SETUP DIAGRAM FOR CONDUCTED TESTS




SETUP DIAGRAM FOR RADIATED TESTS Above 1GHz



SETUP DIAGRAM FOR Below 1GHz and AC LINE CONDUCTED TEST



TEST SETUP- AC LINE CONDUCTED: LAPTOP CONFIGURATION



6. MEASUREMENT METHOD

On Time and Duty Cycle: KDB 558074 D01 v04, Section 6.

6 dB BW: KDB 558074 D01 v04, Section 8.1.

Output Power: KDB 558074 D01 v04, Section 9.1.3.

Power Spectral Density: KDB 558074 D01 v04, Section 10.2.

Out-of-band emissions in non-restricted bands: KDB 558074 D01 v04, Section 11.0.

Out-of-band emissions in restricted bands: KDB 558074 D01 v04, Section 12.1.

Band-edge: KDB 558074 D01 v04, Section 12.1.

AC Power Line Conducted Emissions: ANSI C63.10-2013, Section 6.2.

7. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Description	Manufacturer	Model	ID Num	Cal Due
**Antenna, Horn 1-18GHz	ETS Lindgren	3117	T136	06/26/2018
Antenna, Broadband Hybrid, 30MHz to 2000MHz	Sunol Sciences	JB3	T477	07/07/2018
**Amplifier, 10KHz to 1GHz, 32dB	Sonoma	310N	T286	06/2/2018
Amplifier, 1 to 18GHz	Miteq	AFS42-00101800-25-S-42	T740	12/30/2018
Spectrum Analyzer, PXA 3Hz to 44GHz	Keysight	N9030A	T340	12/15/2018
Antenna, Horn 1-18GHz	ETS Lindgren	3117	T346	02/08/2019
Amplifier, 1 to 18GHz	Miteq	AFS42-00101800-25-S-42	T741	12/30/2018
Spectrum Analyzer, PXA 3Hz to 44GHz	Keysight	N9030A	T906	02/16/2019
Antenna, Horn 1-18GHz	ETS Lindgren	3117	T119	4/03/2019
Amplifier, 1 to 18GHz	Miteq	AFS42-00101800-25-S-42	T491	6/01/2018
Spectrum Analyzer, PXA 3Hz to 44GHz	Keysight	N9030A-544	T341	11/12/2018
Pre-Amp 18-26GHz	Agilent Technology	8449B	T404	07/23/2018
Spectrum Analyzer, PXA, 3Hz to 44GHz	Agilent (Keysight) Technologies	N9030A	T1454	01/08/2019
**Antenna Horn 18 to 26.5GHz	ARA	MWH-1826/B	T449	06/12/2018
Power Meter, P-series single channel	Keysight	N1912A	T1272	05/1/2019
Power Sensor	Keysight	N1921A	T1225	04/10/2019
Antenna, Active Loop 9KHz to 30MHz	ETS-Lindgren	6502	T757	9/14/2018
Spectrum Analyzer, PXA, 3Hz to 44GHz	Agilent (Keysight) Technologies	N9030A	T342	02/22/2019
AC Line Conducted				
EMI Test Receiver 9KHz-7GHz	Rohde & Schwarz	ESCI7	T1436	01/25/2019
**LISN for Conducted Emissions CISPR-16	Fischer	50/250-25-2-01	T1310	06/15/2018
Power Cable, Line Conducted Emissions	UL	PG1	T861	08/31/2018
**LISN for Conducted Emissions *CISPR-16	Fischer	50/250-25-2-01	T1310	06/15/2018
UL AUTOMATION SOFTWARE				
*Radiated Software	UL	UL EMC	Ver 9.5, April 26, 2016	
*Conducted Software	UL	UL EMC	Ver 5.4, October 13, 2016	
*AC Line Conducted Software	UL	UL EMC	Ver 9.5, May 26, 2015	

Note: * indicates automation software version used in the compliance certification testing

**Testing is completed before equipment expiration date.

8. ANTENNA PORT TEST RESULTS

8.1. ON TIME AND DUTY CYCLE

LIMITS

None; for reporting purposes only.


PROCEDURE


KDB 558074 D01 v04, Section 6

ON TIME AND DUTY CYCLE RESULTS

Mode	ON Time B (msec)	Period (msec)	Duty Cycle x (linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/B Minimum VBW (kHz)
2.4GHz Band						
HDR4	1.000	1.000	1.000	100.00%	0.00	0.010
HDR8	1.000	1.000	1.000	100.00%	0.00	0.010

DUTY CYCLE PLOTS





8.2. 99% BANDWIDTH

LIMITS



None; for reporting purposes only.

RESULTS

8.2.1. HIGH POWER HDR4

Antenna 4

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2404	2.3000
Middle	2441	2.2823
High	2478	2.3280



Antenna 3


Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2404	2.2844
Middle	2441	2.2866
High	2478	2.3045



8.2.2. HIGH POWER HDR8


Antenna 4

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2404	4.7475
Middle	2441	4.7149
High	2478	4.7482



Antenna 3



Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2404	4.7445
Middle	2441	4.6801
High	2478	4.7848



8.2.3. LOW POWER HDR4


Antenna 4

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2404	2.2660
Middle	2441	2.3146
High	2478	2.2693



Antenna 3


Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2404	2.2683
Middle	2441	2.3041
High	2478	2.3032



8.2.4. LOW POWER HDR8


Antenna 4

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2404	4.7219
Middle	2441	4.7476
High	2478	4.7519



Antenna 3

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2404	4.7538
Middle	2441	4.7530
High	2478	4.8151



8.3. 6 dB BANDWIDTH

LIMITS

FCC §15.407 (e)

RSS-247 5.2 (a)




The minimum 6 dB bandwidth shall be at least 500 kHz.

RESULTS

8.3.1. HIGH POWER HDR4


Antenna 4

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2404	2.0850	0.5
Middle	2441	2.0610	0.5
High	2478	2.0820	0.5



Antenna 3


Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2404	2.0640	0.5
Middle	2441	2.1000	0.5
High	2478	2.0820	0.5



8.3.2. HIGH POWER HDR8



Antenna 4

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2404	4.0440	0.5
Middle	2441	4.0200	0.5
High	2478	4.0620	0.5



Antenna 3


Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2404	4.0620	0.5
Middle	2441	4.0560	0.5
High	2478	4.1040	0.5



8.3.3. LOW POWER HDR4




Antenna 4

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2404	2.0800	0.5
Middle	2441	2.0760	0.5
High	2478	2.0680	0.5



Antenna 3




Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2404	2.0360	0.5
Middle	2441	2.0600	0.5
High	2478	2.0480	0.5



8.3.4. LOW POWER HDR8


Antenna 4

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2404	4.0110	0.5
Middle	2441	4.0250	0.5
High	2478	4.0180	0.5



Antenna 3

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2404	4.0530	0.5
Middle	2441	4.0320	0.5
High	2478	3.9760	0.5



8.4. OUTPUT POWER

LIMITS

FCC §15.247 (b) (3)

RSS-247 5.4 (d)

The maximum antenna gain is less than or equal to 6 dBi, therefore the limit is 30 dBm.

TEST PROCEDURE

The transmitter output is connected to a wideband gated peak/average power meter.

The cable assembly insertion loss of 10.5 dB (including 10 dB pad and 0.5 dB cable) was entered as an offset in the power meter to allow for a gated peak reading of power.

RESULTS

8.4.1. HIGH POWER HDR4

Antenna 4

Tested By:	44353
Date:	5/4/2018

Channel	Frequency (MHz)	Peak Power Reading (dBm)	Limit (dBm)	Margin (dB)
Low	2404	17.86	30	-12.140
Middle	2441	18.63	30	-11.370
High	2478	17.77	30	-12.230

Antenna 3

Tested By:	44353
Date:	5/4/2018

Channel	Frequency (MHz)	Peak Power Reading (dBm)	Limit (dBm)	Margin (dB)
Low	2404	17.90	30	-12.100
Middle	2441	18.72	30	-11.280
High	2478	17.81	30	-12.190

8.4.2. HIGH POWER HDR8

Antenna 4

Tested By:	44353
Date:	5/4/2018

Channel	Frequency (MHz)	Peak Power Reading (dBm)	Limit (dBm)	Margin (dB)
Low	2404	17.89	30	-12.110
Middle	2441	18.42	30	-11.580
High	2478	17.72	30	-12.280

Antenna 3

Tested By:	44353
Date:	5/4/2018

Channel	Frequency (MHz)	Peak Power Reading (dBm)	Limit (dBm)	Margin (dB)
Low	2404	18.09	30	-11.910
Middle	2441	18.68	30	-11.320
High	2478	17.84	30	-12.160

8.4.3. LOW POWER HDR4

Antenna 4

Tested By:	44353
Date:	5/4/2018

Channel	Frequency (MHz)	Peak Power Reading (dBm)	Limit (dBm)	Margin (dB)
Low	2404	10.12	30	-19.880
Middle	2441	10.59	30	-19.410
High	2478	10.47	30	-19.530

Antenna 3

Tested By:	44353
Date:	5/4/2018

Channel	Frequency (MHz)	Peak Power Reading (dBm)	Limit (dBm)	Margin (dB)
Low	2404	10.40	30	-19.600
Middle	2441	10.72	30	-19.280
High	2478	10.49	30	-19.510

8.4.4. LOW POWER HDR8

Antenna 4

Tested By:	44353
Date:	5/4/2018

Channel	Frequency (MHz)	Peak Power Reading (dBm)	Limit (dBm)	Margin (dB)
Low	2404	8.89	30	-21.110
Middle	2441	10.71	30	-19.290
High	2478	10.21	30	-19.790

Antenna 3

Tested By:	44353
Date:	5/4/2018

Channel	Frequency (MHz)	Peak Power Reading (dBm)	Limit (dBm)	Margin (dB)
Low	2404	9.46	30	-20.540
Middle	2441	10.59	30	-19.410
High	2478	10.24	30	-19.760

8.5. AVERAGE POWER

LIMITS

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to a power meter.

The cable assembly insertion loss of 10.5 dB (including 10 dB pad and 0.5 dB cable) was entered as an offset in the power meter to allow for a gated average reading of power.

RESULTS

8.5.1. HIGH POWER HDR4

Antenna 4

Tested By:	44353
Date:	5/4/2018

Channel	Frequency (MHz)	AV power (dBm)
Low	2404	15.23
Middle	2441	15.97
High	2478	15.19

Antenna 3

Tested By:	44353
Date:	5/4/2018

Channel	Frequency (MHz)	AV power (dBm)
Low	2404	15.27
Middle	2441	16.00
High	2478	15.16

8.5.2. HIGH POWER HDR8

Antenna 4

Tested By:	44353
Date:	5/4/2018

Channel	Frequency (MHz)	AV power (dBm)
Low	2404	15.31
Middle	2441	15.99
High	2478	15.11

Antenna 3

Tested By:	44353
Date:	5/4/2018

Channel	Frequency (MHz)	AV power (dBm)
Low	2404	15.43
Middle	2441	15.98
High	2478	15.27

8.5.3. LOW POWER HDR4

Antenna 4

Tested By:	44353
Date:	5/4/2018

Channel	Frequency (MHz)	AV power (dBm)
Low	2404	7.60
Middle	2441	7.95
High	2478	7.81

Antenna 3

Tested By:	44353
Date:	5/4/2018

Channel	Frequency (MHz)	AV power (dBm)
Low	2404	7.71
Middle	2441	8.00
High	2478	7.82

8.5.4. LOW POWER HDR8

Antenna 4

Tested By:	44353
Date:	5/4/2018

Channel	Frequency (MHz)	AV power (dBm)
Low	2404	6.27
Middle	2441	7.99
High	2478	7.55

Antenna 3

Tested By:	44353
Date:	5/4/2018

Channel	Frequency (MHz)	AV power (dBm)
Low	2404	6.75
Middle	2441	7.97
High	2478	7.76

8.6. POWER SPECTRAL DENSITY

LIMITS

FCC §15.247 (e)

RSS-247 (5.2) (b)


The power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

RESULTS

8.6.1. HIGH POWER HDR4


Antenna 4

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Margin (dB)
Low	2404	-2.77	8	-10.77
Middle	2441	-1.48	8	-9.48
High	2478	-2.82	8	-10.82



Antenna 3


Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Margin (dB)
Low	2404	-1.88	8	-9.88
Middle	2441	-0.92	8	-8.92
High	2478	-2.18	8	-10.18



8.6.2. HIGH POWER HDR8


Antenna 4

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Margin (dB)
Low	2404	-4.91	8	-12.91
Middle	2441	-3.54	8	-11.54
High	2478	-4.87	8	-12.87



Antenna 3


Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Margin (dB)
Low	2404	-4.13	8	-12.13
Middle	2441	-3.14	8	-11.14
High	2478	-4.27	8	-12.27



8.6.3. LOW POWER HDR4

Antenna 4

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Margin (dB)
Low	2404	-9.63	8	-17.63
Middle	2441	-8.33	8	-16.33
High	2478	-8.73	8	-16.73



Antenna 3

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Margin (dB)
Low	2404	-9.27	8	-17.27
Middle	2441	-8.54	8	-16.54
High	2478	-7.90	8	-15.90

