

Apple Computer Inc.
FCC ID: BCGA1044
Request for Limited Modular Approval (LMA)

Transmitter Module Characteristics per FCC public notice DA 00-1407 requirements

Item	Requirements	EUT
1	Have its own RF shielding	Device is equipped with Metal shielding to cover RF section. Refer to external photos
2	Have buffered modulation/data inputs (if such inputs are provided),	All inputs to the modules are buffered through logic or microprocessor inputs.
3	Have it own power supply regulation	Internal 3.3V power regulator. Refer to Block diagram and Technical description file
4	Meet the antenna requirements of Section 15.203	Device is equipped with unique antenna connector. Refer to external photos
5	Be tested in a stand-alone configuration, i.e., the antenna, AC or DC power and data input/output lines must be connected to the module but, the module must not be inside another case during testing	Device was tested outside the host computer as stand-alone configuration. Refer to setup photos.
6	Be labeled with its own FCC ID number, and if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module.	Two proposed FCC ID label format are included in the filing. One of label is to be placed on the module and the other label is to be placed on the outside of system. Refer to FCC ID label format and location file.
7	The modular transmitter must comply with any specific rule or operating requirements applicable to the transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization. For example, there are very strict operational and timing requirements that must be met before a transmitter is authorized for operation under	Transmitter module will only be installed by Apple Computer or Apple's authorized OEM installer. This device will not be sold as module transmitter.

	Section 15.231. For instance, data transmission is prohibited, except for operation under Section 15.231(e), in which case there are separate field strength level and timing requirements. Compliance with these requirements must be assured.	
8	Address compliance with the Commission's RF exposure limits in Sections 1.1310 and 2.1093. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF exposure compliance in accordance with Section 15.247(b)(4).	The max. output power measured is 7.37dBm. This device will be installed in Apple Computer's portable product line. SAR evaluation is performed with the EUT as stand alone and the separation distance to the phantom is 0 cm (direct contact) to simulate the worst case end-used application.