**MEASUREMENT REPORT****FCC PART 15.247 / ISCED RSS-247 Bluetooth (HDR)****Applicant Name:**

Apple Inc.

One Apple Park Way

Cupertino, CA 95014

United States

Date of Testing:

7/26/2018-10/12/2018

Test Site/Location:

PCTEST Lab. Morgan Hill, CA, USA

Test Report Serial No.:

1C1806050011-06.BCG

FCC ID:**BCGA2014****IC:****579C-A2014****APPLICANT:****Apple Inc.****Application Type:**

Certification

Model/HVIN:

A2014

EUT Type:

Tablet Device

Max. RF Output Power:

14.723 mW (11.68 dBm) Peak Conducted Power

Frequency Range:

2404 – 2478MHz

FCC Classification:

Digital Transmission System (DTS)

FCC Rule Part(s):

Part 15 Subpart C (15.247)

ISED Specification:

RSS-247 Issue 2

Test Procedure(s):

ANSI C63.10-2013, KDB 558074 D01 v05

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013 and KDB 558074 D01 v05. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.


Randy Ortanez
President

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 1 of 112

TABLE OF CONTENTS

1.0	INTRODUCTION	3
1.1	Scope	3
1.2	PCTEST Test Location.....	3
1.3	Test Facility / Accreditations.....	3
2.0	PRODUCT INFORMATION.....	4
2.1	Equipment Description	4
2.2	Device Capabilities.....	4
2.3	Antenna Description	5
2.4	Test Support Equipment.....	5
2.5	Test Configuration	5
2.6	Software and Firmware	6
2.7	EMI Suppression Device(s)/Modifications	6
3.0	DESCRIPTION OF TESTS	7
3.1	Evaluation Procedure	7
3.2	AC Line Conducted Emissions	7
3.3	Radiated Emissions.....	8
3.4	Environmental Conditions.....	8
4.0	ANTENNA REQUIREMENTS	9
5.0	MEASUREMENT UNCERTAINTY	10
6.0	TEST EQUIPMENT CALIBRATION DATA	11
7.0	TEST RESULTS.....	12
7.1	Summary.....	12
7.2	6dB Bandwidth Measurement – Bluetooth (HDR)	13
7.3	Output Power Measurement – Bluetooth (HDR)	26
7.3.1	Peak Output Power Measurement - Bluetooth (HDR)	27
7.3.2	Average Output Power Measurement - Bluetooth (HDR)	30
7.4	Power Spectral Density – Bluetooth (HDR)	33
7.5	Conducted Emissions at the Band Edge	55
7.6	Conducted Spurious Emissions.....	62
7.7	Radiated Spurious Emission Measurements - Above 1GHz	73
7.8	Radiated Restricted Band Edge Measurements.....	92
7.9	Radiated Spurious Emissions Measurements – Below 1GHz	104
7.10	AC Line-Conducted Test Data.....	108
8.0	CONCLUSION.....	112

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 2 of 112

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 18855 Adams Court, Morgan Hill, CA 95037. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014 and KDB 414788 D01 v01.

1.3 Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Morgan Hill, CA 95037, U.S.A.

- PCTEST is an ISO 17025-2005 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.02 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISSED Standards (RSS).
- PCTEST facility is a registered (22831) test laboratory with the site description on file with ISSED.

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 3 of 112

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Apple Tablet Device FCC ID: BCGA2014**. The data found in this test report was taken with the EUT operating in Bluetooth HDR mode. While in HDR mode, the Bluetooth transmitter hops pseudo-randomly between 75 channels.

Test Device Serial No.: DLXX303FKNQK, DLXX502EKYD1

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1700/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n WLAN, 802.11a/n/ac UNII, Bluetooth (1x, EDR, LE, HDR4, HDR8)

Ch.	Frequency (MHz)
1	2404
:	:
38	2441
:	:
75	2478

Table 2-1. Frequency / Channel Operations

Maximum Achievable Duty Cycles		
HDR Mode		Duty Cycle (%)
4Mbps	ePA	100.0
	iPA	100.0
8Mbps	ePA	100.0
	iPA	100.0

Table 2-2. Measured Duty Cycle

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 4 of 112

2.3 Antenna Description

Following antenna was used for the testing.

Frequency [GHz]	Antenna Gain (dBi)		
	Antenna 0	Antenna 1	Antenna 2
2.4	-2.3	-0.4	-15.4

Table 2-3. Antenna Peak Gain

Note: This device is capable of operating in hopping and non-hopping mode. The EUT can hop between 75 different channels in the 2404 – 2478MHz band.

2.4 Test Support Equipment

1	Apple MacBook	Model: A1398	S/N: C2QKP008F6F3
	w/AC/DC Adapter	Model: A1435	S/N: C04325505K1F288BG
2	Apple USB-C Cable	Model: Chimp	S/N: 300C44
3	USB-C Cable	Model: A146	S/N: N/A
	w/ AC Adapter	Model: A1720	S/N: C3D8257A2EPGKVP2C
4	USB-C to 3.5mm Aux Adapter	Model: A2049	S/N: DWH413100GJJLT12
5	DC Power Supply	Model: KPS3010D	S/N: N/A

Table 2-4. Test Support Equipment Used

2.5 Test Configuration

The EUT was tested per the guidance of ANSI C63.10-2013 and KDB 558074 D01 v05. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See Sections 3.2 for AC line conducted emissions test setups, 3.3 for radiated emissions test setups, and 7.2, 7.3, 7.4, 7.5, and 7.6 for antenna port conducted emissions test setups.

There are two vendors of the WiFi/Bluetooth radio modules, variant 1 and variant 2. Both radio modules have the same mechanical outline, same on-board antenna matching circuit, identical antenna structure, and are built and tested to conform to the same specifications and to operate within the same tolerances. The worst case configuration was found between the two variants. The EUT was also investigated with and without charger.

The emissions below 1GHz and above 18GHz were tested with the highest transmitting power channel and the worst case configuration.

The EUT was manipulated through three orthogonal planes of X-orientation (flatbed), Y-orientation (landscape), and Z-orientation (portrait) during the testing. Only the worst case emissions were reported in this test report.

For AC line conducted and radiated test below 1GHz, following configuration were investigated and worst case was reported.

- EUT powered by AC/DC adaptor via USB-C cable with wire charger
- EUT powered by host PC via USB-C cable with wire charger

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 5 of 112

2.6 Software and Firmware

The test was conducted with firmware version 16B64 installed on the EUT.

2.7 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 6 of 112

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013) and the guidance provided in KDB 558074 D01 v05 were used in the measurement of the EUT.

Deviation from measurement procedure.....None

3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 7m x 3.66m x 2.7m shielded enclosure. The shielded enclosure is manufactured by AP Americas. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-6. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is EPCOS 2X60A Power Line Filter (100dB Attenuation, 14kHz-18GHz) and the two EPCOs 2X48A filters (100dB Minimum Insertion Loss, 14kHz - 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 7.10. Automated test software was used to perform the AC line conducted emissions testing. Automated measurement software utilized is Rohde & Schwarz EMC32, Version 10.20.01.

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 7 of 112

3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33 depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 8 of 112

4.0 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna(s) of the EUT are **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The EUT complies with the requirement of §15.203.

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 9 of 112

5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ($\pm$ dB)
Conducted Bench Top Measurements	1.13
Line Conducted Disturbance	3.09
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 10 of 112

6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Anritsu	ML2495A	Power Meter	11/28/2017	Annual	11/28/2018	1039008
Anritsu	MA2411B	Power Sensor 10MHz-40GHz	11/28/2017	Annual	11/28/2018	1027293
ATM	180-442A-KF	20dB Nominal Gain Horn Antenna	3/13/2018	Annual	3/13/2019	T058601-02
COM-POWER	LIN-120A	LISN	3/7/2018	Annual	3/7/2019	241296
Keysight Technologies	N9030A	3Hz-44GHz PXA Signal Analyzer	2/27/2018	Annual	2/27/2019	MY49430244
Rohde & Schwarz	FSV40	Signal Analyzer (10Hz-40GHz)	2/6/2018	Annual	2/6/2019	101619
Rohde & Schwarz	ESW44	EMI Test Receiver	12/20/2017	Annual	12/20/2018	101668
Rohde & Schwarz	ESW44	EMI Test Receiver	11/16/2017	Annual	11/16/2018	101570
Rohde & Schwarz	SFUNIT-RX	Shielded Filter Unit	7/5/2018	Annual	7/5/2019	102137
Rohde & Schwarz	SFUNIT-RX	Shielded Filter Unit	12/11/2017	Annual	12/11/2018	102136
Rohde & Schwarz	TS-PR1840	Pre-Amplifier (18GHz - 40GHz)	6/11/2018	Annual	6/11/2019	100051
Rohde & Schwarz	TS-PR8	Pre-Amplifier (30MHz - 8GHz)	1/25/2018	Annual	1/25/2019	102333
Rohde & Schwarz	HL562E	Ultra Broadband Antenna (30MHz - 6GHz)	6/8/2018	Annual	6/8/2019	100810
Rohde & Schwarz	TC-TA18	Cross Polarized Vivaldi Antenna (400MHz-18GHz)	11/13/2017	Annual	11/13/2018	101057
Rohde & Schwarz	TC-TA18	Cross Polarized Vivaldi Antenna (400MHz-18GHz)	11/29/2017	Annual	11/29/2018	101063
Rohde & Schwarz	HFH2-Z2	Loop Antenna	3/13/2018	Annual	3/13/2019	100519

Table 6-1. Annual Test Equipment Calibration Schedule

Note:

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 11 of 112

7.0 TEST RESULTS

7.1 Summary

Company Name: Apple Inc.
 FCC ID: BCGA2014
 FCC Classification: Digital Transmission System (DTS)
 Number of Channels: 75

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.247(a)(2)	RSS-247 [5.2]	6dB Bandwidth	> 500kHz	CONDUCTED	PASS	Section 7.2
15.247(b)(3)	RSS-247 [5.4(4)]	Transmitter Output Power	< 1 Watt		PASS	Sections 7.3
15.247(e)	RSS-247 [5.2]	Transmitter Power Spectral Density	< 8dBm / 3kHz Band		PASS	Section 7.4
15.247(d)	RSS-247 [5.5]	Band Edge / Out-of-Band Emissions	≥ 20dBc		PASS	Sections 7.5, 7.6
15.205 15.209	RSS-Gen [8.9]	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-Gen [8.9])	RADIATED	PASS	Sections 7.7, 7.8, 7.9
15.207	RSS-Gen [8.8]	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 limits (RSS-Gen[8.8])	LINE CONDUCTED	PASS	Section 7.10

Table 7-1. Summary of Test Results

Notes:

- All modes of operation were investigated. The test results shown in the following sections represent the worst case emissions.
- The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
- For radiated band edge, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST “Chamber Automation,” Version 1.3.0.

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 12 of 112

7.2 6dB Bandwidth Measurement – Bluetooth (HDR)

§15.247(a.2); RSS-247 [5.2]

Test Overview and Limit

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the transmitter antenna terminal of the EUT while the EUT is operating at maximum power and at the appropriate frequencies. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible 6dB bandwidth is 500 kHz.

Test Procedure Used

ANSI C63.10-2013 – Section 11.8.2 Option 2
KDB 558074 D01 v05 – Section 8.2

Test Settings

1. The signal analyzers' automatic bandwidth measurement capability of the spectrum analyzer was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 6$. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 100kHz
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-1. Test Instrument & Measurement Setup

Test Notes

Both power schemes were investigated and only the worst case is reported.


FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 13 of 112

Antenna 0


Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Bluetooth Mode	Measured Bandwidth [kHz]	Minimum Bandwidth [kHz]	Pass / Fail
2404	4.0	GFSK	ePA	1	HDR4	2093	500	Pass
2441	4.0	GFSK	ePA	38	HDR4	2094	500	Pass
2478	4.0	GFSK	ePA	75	HDR4	2098	500	Pass
2404	8.0	GFSK	ePA	1	HDR8	4046	500	Pass
2441	8.0	GFSK	ePA	38	HDR8	3986	500	Pass
2478	8.0	GFSK	ePA	75	HDR8	4043	500	Pass

Table 7-2. Conducted Bandwidth Measurements ANT0

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 14 of 112




Plot 7-1. 6dB Bandwidth Plot ANT0 (Bluetooth (HDR4, ePA), 4Mbps – Ch. 1)




Plot 7-2. 6dB Bandwidth Plot ANT0 (Bluetooth (HDR4, ePA), 4Mbps – Ch. 38)

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 15 of 112




Plot 7-3. 6dB Bandwidth Plot ANT0 (Bluetooth (HDR4, ePA), 4Mbps – Ch. 75)




Plot 7-4. 6dB Bandwidth Plot ANT0 (Bluetooth (HDR8, ePA), 8Mbps – Ch. 1)

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 16 of 112



Plot 7-5. 6dB Bandwidth Plot ANT0 (Bluetooth (HDR8, ePA), 8Mbps – Ch. 38)



Plot 7-6. 6dB Bandwidth Plot ANT0 (Bluetooth (HDR8, ePA), 8Mbps – Ch. 75)


FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 17 of 112

Antenna 1


Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Bluetooth Mode	Measured Bandwidth [kHz]	Minimum Bandwidth [kHz]	Pass / Fail
2404	4.0	GFSK	ePA	1	HDR4	2087	500	Pass
2441	4.0	GFSK	ePA	38	HDR4	2088	500	Pass
2478	4.0	GFSK	ePA	75	HDR4	2095	500	Pass
2404	8.0	GFSK	ePA	1	HDR8	4051	500	Pass
2441	8.0	GFSK	ePA	38	HDR8	4026	500	Pass
2478	8.0	GFSK	ePA	75	HDR8	3979	500	Pass

Table 7-3. Conducted Bandwidth Measurements ANT1

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 18 of 112




Plot 7-7. 6dB Bandwidth Plot ANT1 (Bluetooth (HDR4, ePA), 4Mbps – Ch. 1)




Plot 7-8. 6dB Bandwidth Plot ANT1 (Bluetooth (HDR4, ePA), 4Mbps – Ch. 38)

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 19 of 112




Plot 7-9. 6dB Bandwidth Plot ANT1 (Bluetooth (HDR4, ePA), 4Mbps – Ch. 75)




Plot 7-10. 6dB Bandwidth Plot ANT1 (Bluetooth (HDR8, ePA), 8Mbps – Ch. 1)

FCC ID: BCGA2014	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 20 of 112



Plot 7-11. 6dB Bandwidth Plot ANT1 (Bluetooth (HDR8, ePA), 8Mbps – Ch. 38)



Plot 7-12. 6dB Bandwidth Plot ANT1 (Bluetooth (HDR8, ePA), 8Mbps – Ch. 75)


FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 21 of 112

Antenna 2


Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Bluetooth Mode	Measured Bandwidth [kHz]	Minimum Bandwidth [kHz]	Pass / Fail
2404	4.0	GFSK	ePA	1	HDR4	2090	500	Pass
2441	4.0	GFSK	ePA	38	HDR4	2092	500	Pass
2478	4.0	GFSK	ePA	75	HDR4	2096	500	Pass
2404	8.0	GFSK	ePA	1	HDR8	4046	500	Pass
2441	8.0	GFSK	ePA	38	HDR8	4029	500	Pass
2478	8.0	GFSK	ePA	75	HDR8	4039	500	Pass

Table 7-4. Conducted Bandwidth Measurements ANT2

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 22 of 112




Plot 7-13. 6dB Bandwidth Plot ANT2 (Bluetooth (HDR4, ePA), 4Mbps – Ch. 1)




Plot 7-14. 6dB Bandwidth Plot ANT2 (Bluetooth (HDR4, ePA), 4Mbps – Ch. 38)

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 23 of 112




Plot 7-15. 6dB Bandwidth Plot ANT2 (Bluetooth (HDR4, ePA), 4Mbps – Ch. 75)




Plot 7-16. 6dB Bandwidth Plot ANT2 (Bluetooth (HDR8, ePA), 8Mbps – Ch. 1)

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 24 of 112



Plot 7-17. 6dB Bandwidth Plot ANT2 (Bluetooth (HDR8, ePA), 8Mbps – Ch. 38)



Plot 7-18. 6dB Bandwidth Plot ANT2 (Bluetooth (HDR8, ePA), 8Mbps – Ch. 75)

FCC ID: BCGA2014	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 25 of 112

7.3 Output Power Measurement – Bluetooth (HDR)

§15.247(b.3); RSS-247 [5.4(4)]

Test Overview and Limits

The transmitter antenna terminal of the EUT is connected to the input of a spectrum analyzer. Measurements are made while the EUT is operating at maximum power and at the appropriate frequencies.

The maximum permissible conducted output power is 1 Watt.

Test Procedure Used

ANSI C63.10-2013 – Section 11.9.1.3
ANSI C63.10-2013 – Section 11.9.2.3.2
KDB 558074 D01 v05 – Section 8.3.1.3

Test Settings

Method PKPM1 (Peak Power Measurement)

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

Method AVGP-M-G (Average Power Measurement)

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-2. Test Instrument & Measurement Setup for Peak and Average Power Measurement

Test Notes

None

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 26 of 112

7.3.1 Peak Output Power Measurement - Bluetooth (HDR)

Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Bluetooth Mode	Peak Conducted Power	
						[dBm]	[mW]
2404	4.0	GFSK	ePA	1	HDR4	11.11	12.912
2441	4.0	GFSK	ePA	38	HDR4	11.68	14.723
2478	4.0	GFSK	ePA	75	HDR4	11.65	14.622
2404	4.0	GFSK	iPA	1	HDR4	6.28	4.246
2441	4.0	GFSK	iPA	38	HDR4	6.21	4.178
2478	4.0	GFSK	iPA	75	HDR4	6.40	4.365
2404	8.0	GFSK	ePA	1	HDR8	11.50	14.125
2441	8.0	GFSK	ePA	38	HDR8	11.33	13.583
2478	8.0	GFSK	ePA	75	HDR8	11.53	14.223
2404	8.0	GFSK	iPA	1	HDR8	6.69	4.667
2441	8.0	GFSK	iPA	38	HDR8	6.69	4.667
2478	8.0	GFSK	iPA	75	HDR8	6.92	4.920

Table 7-5. ANT0 Peak Conducted Output Power Measurements (Bluetooth (HDR))

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 27 of 112

Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Bluetooth Mode	Peak Conducted Power	
						[dBm]	[mW]
2404	4.0	GFSK	ePA	1	HDR4	8.16	6.546
2441	4.0	GFSK	ePA	38	HDR4	8.58	7.211
2478	4.0	GFSK	ePA	75	HDR4	8.23	6.653
2404	4.0	GFSK	iPA	1	HDR4	4.30	2.692
2441	4.0	GFSK	iPA	38	HDR4	4.12	2.582
2478	4.0	GFSK	iPA	75	HDR4	4.07	2.553
2404	8.0	GFSK	ePA	1	HDR8	8.11	6.471
2441	8.0	GFSK	ePA	38	HDR8	8.40	6.918
2478	8.0	GFSK	ePA	75	HDR8	8.49	7.063
2404	8.0	GFSK	iPA	1	HDR8	4.67	2.931
2441	8.0	GFSK	iPA	38	HDR8	4.53	2.838
2478	8.0	GFSK	iPA	75	HDR8	4.48	2.805

Table 7-6. ANT1 Peak Conducted Output Power Measurements (Bluetooth (HDR))

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 28 of 112

Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Bluetooth Mode	Peak Conducted Power	
						[dBm]	[mW]
2404	4.0	GFSK	ePA	1	HDR4	8.65	7.328
2441	4.0	GFSK	ePA	38	HDR4	8.86	7.691
2478	4.0	GFSK	ePA	75	HDR4	8.59	7.228
2404	4.0	GFSK	iPA	1	HDR4	4.17	2.612
2441	4.0	GFSK	iPA	38	HDR4	4.07	2.553
2478	4.0	GFSK	iPA	75	HDR4	4.46	2.793
2404	8.0	GFSK	ePA	1	HDR8	8.89	7.745
2441	8.0	GFSK	ePA	38	HDR8	9.11	8.147
2478	8.0	GFSK	ePA	75	HDR8	8.86	7.691
2404	8.0	GFSK	iPA	1	HDR8	4.52	2.831
2441	8.0	GFSK	iPA	38	HDR8	4.43	2.773
2478	8.0	GFSK	iPA	75	HDR8	4.26	2.667

Table 7-7. ANT2 Peak Conducted Output Power Measurements (Bluetooth (HDR))

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 29 of 112

7.3.2 Average Output Power Measurement - Bluetooth (HDR)

Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Bluetooth Mode	Average Conducted Power	
						[dBm]	[mW]
2404	4.0	GFSK	ePA	1	HDR4	8.45	6.998
2441	4.0	GFSK	ePA	38	HDR4	8.50	7.586
2478	4.0	GFSK	ePA	75	HDR4	8.49	7.691
2404	4.0	GFSK	iPA	1	HDR4	3.50	2.286
2441	4.0	GFSK	iPA	38	HDR4	3.48	2.275
2478	4.0	GFSK	iPA	75	HDR4	3.49	2.301
2404	8.0	GFSK	ePA	1	HDR8	8.43	6.966
2441	8.0	GFSK	ePA	38	HDR8	8.36	6.855
2478	8.0	GFSK	ePA	75	HDR8	8.34	6.823
2404	8.0	GFSK	iPA	1	HDR8	3.46	2.344
2441	8.0	GFSK	iPA	38	HDR8	3.50	2.350
2478	8.0	GFSK	iPA	75	HDR8	3.48	2.388

Table 7-8. ANT0 Average Conducted Output Power Measurements (Bluetooth (HDR))

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 30 of 112

Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Bluetooth Mode	Average Conducted Power	
						[dBm]	[mW]
2404	4.0	GFSK	ePA	1	HDR4	5.97	4.093
2441	4.0	GFSK	ePA	38	HDR4	6.00	4.236
2478	4.0	GFSK	ePA	75	HDR4	5.95	4.083
2404	4.0	GFSK	iPA	1	HDR4	1.50	1.469
2441	4.0	GFSK	iPA	38	HDR4	1.48	1.406
2478	4.0	GFSK	iPA	75	HDR4	1.46	1.400
2404	8.0	GFSK	ePA	1	HDR8	5.80	3.802
2441	8.0	GFSK	ePA	38	HDR8	5.83	3.802
2478	8.0	GFSK	ePA	75	HDR8	6.00	4.111
2404	8.0	GFSK	iPA	1	HDR8	1.50	1.503
2441	8.0	GFSK	iPA	38	HDR8	1.48	1.439
2478	8.0	GFSK	iPA	75	HDR8	1.49	1.416

Table 7-9. ANT1 Average Conducted Output Power Measurements (Bluetooth (HDR))

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 31 of 112

Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Bluetooth Mode	Average Conducted Power	
						[dBm]	[mW]
2404	4.0	GFSK	ePA	1	HDR4	6.47	4.581
2441	4.0	GFSK	ePA	38	HDR4	6.50	4.613
2478	4.0	GFSK	ePA	75	HDR4	6.49	4.395
2404	4.0	GFSK	iPA	1	HDR4	1.48	1.419
2441	4.0	GFSK	iPA	38	HDR4	1.46	1.390
2478	4.0	GFSK	iPA	75	HDR4	1.50	1.500
2404	8.0	GFSK	ePA	1	HDR8	6.49	4.677
2441	8.0	GFSK	ePA	38	HDR8	6.50	4.688
2478	8.0	GFSK	ePA	75	HDR8	6.48	4.446
2404	8.0	GFSK	iPA	1	HDR8	1.50	1.449
2441	8.0	GFSK	iPA	38	HDR8	1.46	1.419
2478	8.0	GFSK	iPA	75	HDR8	1.23	1.327

Table 7-10. ANT2 Average Conducted Output Power Measurements (Bluetooth (HDR))

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 32 of 112

7.4 Power Spectral Density – Bluetooth (HDR)

§15.247(e); RSS-247 [5.2]

Test Overview and Limit

The peak power density is measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power and at the appropriate frequencies.

The maximum permissible power spectral density is 8 dBm in any 3 kHz band.

Test Procedure Used

ANSI C63.10-2013 – Section 11.10.2 Method PKPSD
KDB 558074 D01 v05

Test Settings

1. Analyzer was set to the center frequency of the DTS channel under investigation
2. Span = 1.5 times the DTS channel bandwidth
3. RBW = 3kHz
4. VBW = 1MHz
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-3. Test Instrument & Measurement Setup

Test Notes

None


FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 33 of 112

Antenna 0


Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Bluetooth Mode	Measured Power Spectral Density [dBm]	Maximum Permissible Power Density [dBm / 3kHz]	Margin [dB]
2404	4.0	GFSK	ePA	1	HDR4	-2.12	8.0	-10.12
2441	4.0	GFSK	ePA	38	HDR4	-1.01	8.0	-9.01
2478	4.0	GFSK	ePA	75	HDR4	-3.99	8.0	-11.99
2404	4.0	GFSK	iPA	1	HDR4	-8.79	8.0	-16.79
2441	4.0	GFSK	iPA	38	HDR4	-7.09	8.0	-15.09
2478	4.0	GFSK	iPA	75	HDR4	-9.63	8.0	-17.63
2404	8.0	GFSK	ePA	1	HDR8	-4.69	8.0	-12.69
2441	8.0	GFSK	ePA	38	HDR8	-3.58	8.0	-11.58
2478	8.0	GFSK	ePA	75	HDR8	-6.31	8.0	-14.31
2404	8.0	GFSK	iPA	1	HDR8	-11.35	8.0	-19.35
2441	8.0	GFSK	iPA	38	HDR8	-9.56	8.0	-17.56
2478	8.0	GFSK	iPA	75	HDR8	-11.97	8.0	-19.97

Table 7-11. Conducted Power Density Measurements (HDR) ANT0

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 34 of 112




Plot 7-19. Power Spectral Density Plot ANT0 (Bluetooth (HDR4, ePA), 4Mbps – Ch. 1)




Plot 7-20. Power Spectral Density Plot ANT0 (Bluetooth (HDR4, ePA), 4Mbps – Ch. 38)

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 35 of 112




Plot 7-21. Power Spectral Density Plot ANT0 (Bluetooth (HDR4, ePA), 4Mbps – Ch. 75)




Plot 7-22. Power Spectral Density Plot ANT0 (Bluetooth (HDR4, iPA), 4Mbps – Ch. 1)

FCC ID: BCGA2014	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 36 of 112




Plot 7-23. Power Spectral Density Plot ANT0 (Bluetooth (HDR4, iPA), 4Mbps – Ch. 38)




Plot 7-24. Power Spectral Density Plot ANT0 (Bluetooth (HDR4, iPA), 4Mbps – Ch. 75)

FCC ID: BCGA2014	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 37 of 112




Plot 7-25. Power Spectral Density Plot ANT0 (Bluetooth (HDR8, ePA), 8Mbps – Ch. 1)




Plot 7-26. Power Spectral Density Plot ANT0 (Bluetooth (HDR8, ePA), 8Mbps – Ch. 38)

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 38 of 112




Plot 7-27. Power Spectral Density Plot ANT0 (Bluetooth (HDR8, ePA), 8Mbps – Ch. 75)




Plot 7-28. Power Spectral Density Plot ANT0 (Bluetooth (HDR8, iPA), 8Mbps – Ch. 1)

FCC ID: BCGA2014	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 39 of 112



Plot 7-29. Power Spectral Density Plot ANT0 (Bluetooth (HDR8, iPA), 8Mbps – Ch. 38)



Plot 7-30. Power Spectral Density Plot ANT0 (Bluetooth (HDR8, iPA), 8Mbps – Ch. 75)


FCC ID: BCGA2014	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 40 of 112

Antenna 1


Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Bluetooth Mode	Measured Power Spectral Density [dBm]	Maximum Permissible Power Density [dBm / 3kHz]	Margin [dB]
2404	4.0	GFSK	ePA	1	HDR4	-3.82	8.0	-11.82
2441	4.0	GFSK	ePA	38	HDR4	-2.47	8.0	-10.47
2478	4.0	GFSK	ePA	75	HDR4	-5.27	8.0	-13.27
2404	4.0	GFSK	iPA	1	HDR4	-10.00	8.0	-18.00
2441	4.0	GFSK	iPA	38	HDR4	-8.89	8.0	-16.89
2478	4.0	GFSK	iPA	75	HDR4	-10.40	8.0	-18.40
2404	8.0	GFSK	ePA	1	HDR8	-6.46	8.0	-14.46
2441	8.0	GFSK	ePA	38	HDR8	-4.94	8.0	-12.94
2478	8.0	GFSK	ePA	75	HDR8	-7.57	8.0	-15.57
2404	8.0	GFSK	iPA	1	HDR8	-12.60	8.0	-20.60
2441	8.0	GFSK	iPA	38	HDR8	-11.45	8.0	-19.45
2478	8.0	GFSK	iPA	75	HDR8	-12.82	8.0	-20.82

Table 7-12. Conducted Power Density Measurements (HDR) ANT1

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 41 of 112




Plot 7-31. Power Spectral Density Plot ANT1 (Bluetooth (HDR4, ePA), 4Mbps – Ch. 1)




Plot 7-32. Power Spectral Density Plot ANT1 (Bluetooth (HDR4, ePA), 4Mbps – Ch. 38)

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 42 of 112




Plot 7-33. Power Spectral Density Plot ANT1 (Bluetooth (HDR4, ePA), 4Mbps – Ch. 75)




Plot 7-34. Power Spectral Density Plot ANT1 (Bluetooth (HDR4, iPA), 4Mbps – Ch. 1)

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 43 of 112




Plot 7-35. Power Spectral Density Plot ANT1 (Bluetooth (HDR4, iPA), 4Mbps – Ch. 38)




Plot 7-36. Power Spectral Density Plot ANT1 (Bluetooth (HDR4, iPA), 4Mbps – Ch. 75)

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 44 of 112




Plot 7-37. Power Spectral Density Plot ANT1 (Bluetooth (HDR8, ePA), 8Mbps – Ch. 1)




Plot 7-38. Power Spectral Density Plot ANT1 (Bluetooth (HDR8, ePA), 8Mbps – Ch. 38)

FCC ID: BCGA2014	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 45 of 112




Plot 7-39. Power Spectral Density Plot ANT1 (Bluetooth (HDR8, ePA), 8Mbps – Ch. 75)




Plot 7-40. Power Spectral Density Plot ANT1 (Bluetooth (HDR8, iPA), 8Mbps – Ch. 1)

FCC ID: BCGA2014	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 46 of 112



Plot 7-41. Power Spectral Density Plot ANT1 (Bluetooth (HDR8, iPA), 8Mbps – Ch. 38)



Plot 7-42. Power Spectral Density Plot ANT1 (Bluetooth (HDR8, iPA), 8Mbps – Ch. 75)


FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 47 of 112

Antenna 2


Frequency [MHz]	Data Rate [Mbps]	Mod.	Power Scheme	Channel No.	Bluetooth Mode	Measured Power Spectral Density [dBm]	Maximum Permissible Power Density [dBm / 3kHz]	Margin [dB]
2404	4.0	GFSK	ePA	1	HDR4	-4.18	8.0	-12.18
2441	4.0	GFSK	ePA	38	HDR4	-3.02	8.0	-11.02
2478	4.0	GFSK	ePA	75	HDR4	-5.54	8.0	-13.54
2404	4.0	GFSK	iPA	1	HDR4	-10.27	8.0	-18.27
2441	4.0	GFSK	iPA	38	HDR4	-9.39	8.0	-17.39
2478	4.0	GFSK	iPA	75	HDR4	-10.72	8.0	-18.72
2404	8.0	GFSK	ePA	1	HDR8	-6.74	8.0	-14.74
2441	8.0	GFSK	ePA	38	HDR8	-5.51	8.0	-13.51
2478	8.0	GFSK	ePA	75	HDR8	-7.80	8.0	-15.80
2404	8.0	GFSK	iPA	1	HDR8	-12.76	8.0	-20.76
2441	8.0	GFSK	iPA	38	HDR8	-11.83	8.0	-19.83
2478	8.0	GFSK	iPA	75	HDR8	-12.99	8.0	-20.99

Table 7-13. Conducted Power Density Measurements (HDR) ANT2

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 48 of 112




Plot 7-43. Power Spectral Density Plot ANT2 (Bluetooth (HDR4, ePA), 4Mbps – Ch. 1)




Plot 7-44. Power Spectral Density Plot ANT2 (Bluetooth (HDR4, ePA), 4Mbps – Ch. 38)

FCC ID: BCGA2014	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 49 of 112




Plot 7-45. Power Spectral Density Plot ANT2 (Bluetooth (HDR4, ePA), 4Mbps – Ch. 75)




Plot 7-46. Power Spectral Density Plot ANT2 (Bluetooth (HDR4, iPA), 4Mbps – Ch. 1)

FCC ID: BCGA2014	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 50 of 112




Plot 7-47. Power Spectral Density Plot ANT2 (Bluetooth (HDR4, iPA), 4Mbps – Ch. 38)




Plot 7-48. Power Spectral Density Plot ANT2 (Bluetooth (HDR4, iPA), 4Mbps – Ch. 75)

FCC ID: BCGA2014	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 51 of 112




Plot 7-49. Power Spectral Density Plot ANT2 (Bluetooth (HDR8, ePA), 8Mbps – Ch. 1)




Plot 7-50. Power Spectral Density Plot ANT2 (Bluetooth (HDR8, ePA), 8Mbps – Ch. 38)

FCC ID: BCGA2014	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 52 of 112




Plot 7-51. Power Spectral Density Plot ANT2 (Bluetooth (HDR8, ePA), 8Mbps – Ch. 75)




Plot 7-52. Power Spectral Density Plot ANT2 (Bluetooth (HDR8, iPA), 8Mbps – Ch. 1)

FCC ID: BCGA2014	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 53 of 112



Plot 7-53. Power Spectral Density Plot ANT2 (Bluetooth (HDR8, iPA), 8Mbps – Ch. 38)



Plot 7-54. Power Spectral Density Plot ANT2 (Bluetooth (HDR8, iPA), 8Mbps – Ch. 75)

FCC ID: BCGA2014	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 54 of 112

7.5 Conducted Emissions at the Band Edge

§15.247(d); RSS-247 [5.5]

Test Overview and Limit

For the following out of band conducted spurious emissions plots at the band edge, the EUT was set to transmit at maximum power with the largest packet size available. These settings produced the worst-case emissions.

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth.

Test Procedure Used

ANSI C63.10-2013 – Section 11.11.3
KDB 558074 D01 v05 – Section 8.7.2

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW = 100kHz
4. VBW = 300kHz
5. Detector = Peak
6. Number of sweep points $\geq 2 \times \text{Span/RBW}$
7. Trace mode = max hold
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-4. Test Instrument & Measurement Setup

Test Notes

Both power schemes were investigated and only the worst case is reported.

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 55 of 112

Antenna 0




Plot 7-55. Band Edge Plot ANT0 (Bluetooth (HDR4, ePA), 4Mbps – Ch. 1)



Plot 7-56. Band Edge Plot ANT0 (Bluetooth (HDR4, ePA), 4Mbps – Ch. 75)

FCC ID: BCGA2014	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 56 of 112




Plot 7-57. Band Edge Plot ANT0 (Bluetooth (HDR8, ePA), 8Mbps - Ch. 1)



Plot 7-58. Band Edge Plot ANT0 (Bluetooth (HDR8, ePA), 8Mbps - Ch. 75)

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 57 of 112

Antenna 1




Plot 7-59. Band Edge Plot ANT1 (Bluetooth (HDR4, ePA), 4Mbps - Ch. 1)




Plot 7-60. Band Edge Plot ANT1 (Bluetooth (HDR4, ePA), 4Mbps - Ch. 75)

FCC ID: BCGA2014	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 58 of 112




Plot 7-61. Band Edge Plot ANT1 (Bluetooth (HDR8, ePA), 8Mbps – Ch. 1)




Plot 7-62. Band Edge Plot ANT1 (Bluetooth (HDR8, ePA), 8Mbps – Ch. 75)

FCC ID: BCGA2014	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 59 of 112

Antenna 2




Plot 7-63. Band Edge Plot ANT2 (Bluetooth (HDR4, ePA), 4Mbps - Ch. 1)



Plot 7-64. Band Edge Plot ANT2 (Bluetooth (HDR4, ePA), 4Mbps - Ch. 75)

FCC ID: BCGA2014	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 60 of 112



Plot 7-65. Band Edge Plot ANT2 (Bluetooth (HDR8, ePA), 8Mbps - Ch. 1)



Plot 7-66. Band Edge Plot ANT2 (Bluetooth (HDR8, ePA), 8Mbps - Ch. 75)

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 61 of 112

7.6 Conducted Spurious Emissions

§15.247(d); RSS-247 [5.5]

Test Overview and Limit

For the following out of band conducted spurious emissions plots, the EUT was set to transmit at maximum power with the largest packet size available. The worst case spurious emissions were found in this configuration.

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the procedure in Section 8.5 of KDB 558074 D01 v05 and Section 11.11.3 of ANSI C63.10-2013.

Test Procedure Used

ANSI C63.10-2013 – Section 11.11.3

KDB 558074 D01 v05 – Section 8.5

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 25GHz (separated into two plots per channel)
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-5. Test Instrument & Measurement Setup


FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 62 of 112

Test Notes


1. RBW was set to 1MHz rather than 100kHz in order to increase the measurement speed.
2. The display line shown in the following plots denotes the limit at 20dB below the fundamental emission level measured in a 100kHz bandwidth. However, since the traces in the following plots are measured with a 1MHz RBW, the display line may not necessarily appear to be 20dB below the level of the fundamental in a 1MHz bandwidth.
3. For plots showing conducted spurious emissions near the limit, the frequencies were investigated with a reduced RBW to ensure that no emissions were present.
4. Both power schemes were investigated and only the worst case is reported.

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 63 of 112

Antenna 0




Plot 7-67. Conducted Spurious Plot ANT0 (Bluetooth (HDR4, ePA), 4Mbps – Ch. 1)




Plot 7-68. Conducted Spurious Plot ANT0 (Bluetooth (HDR4, ePA), 4Mbps – Ch. 1)

FCC ID: BCGA2014	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 64 of 112




Plot 7-69. Conducted Spurious Plot ANT0 (Bluetooth (HDR4, ePA), 4Mbps – Ch. 38)




Plot 7-70. Conducted Spurious Plot ANT0 (Bluetooth (HDR4, ePA), 4Mbps – Ch. 38)

FCC ID: BCGA2014	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 65 of 112




Plot 7-71. Conducted Spurious Plot ANT0 (Bluetooth (HDR4, ePA), 4Mbps – Ch. 75)




Plot 7-72. Conducted Spurious Plot ANT0 (Bluetooth (HDR4, ePA), 4Mbps – Ch. 75)

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 66 of 112

Antenna 1




Plot 7-73. Conducted Spurious Plot ANT1 (Bluetooth (HDR4, ePA), 4Mbps – Ch. 1)




Plot 7-74. Conducted Spurious Plot ANT1 (Bluetooth (HDR4, ePA), 4Mbps – Ch. 1)

FCC ID: BCGA2014	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 67 of 112




Plot 7-75. Conducted Spurious Plot ANT1 (Bluetooth (HDR4, ePA), 4Mbps – Ch. 38)




Plot 7-76. Conducted Spurious Plot ANT1 (Bluetooth (HDR4, ePA), 4Mbps – Ch. 38)

FCC ID: BCGA2014	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 68 of 112



Plot 7-77. Conducted Spurious Plot ANT1 (Bluetooth (HDR4, ePA), 4Mbps – Ch. 75)



Plot 7-78. Conducted Spurious Plot ANT1 (Bluetooth (HDR4, ePA), 4Mbps – Ch. 75)

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-06.BCG	Test Dates: 7/26/2018-10/12/2018	EUT Type: Tablet Device	Page 69 of 112