



Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 2467MHz
Channel: 12



Plot 7-156. Radiated Restricted Upper Band Edge Measurement SISO CORE0 (Average & Peak)

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 2472MHz
Channel: 13



Plot 7-157. Radiated Restricted Upper Band Edge Measurement SISO CORE0 (Average & Peak)


FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 118 of 142

7.7.7 SISO Core1 Primary Radiated Restricted Band Edge Measurements

§15.205 §15.209; RSS-Gen [8.9]


The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting.

Worst Case Mode: 802.11b
Worst Case Transfer Rate: 1Mbps
Distance of Measurements: 3 Meters
Operating Frequency: 2412MHz
Channel: 1



Plot 7-158. Radiated Restricted Lower Band Edge Measurement SISO CORE1 PRIMARY (Average & Peak)


Worst Case Mode: 802.11b
Worst Case Transfer Rate: 1Mbps
Distance of Measurements: 3 Meters
Operating Frequency: 2467MHz
Channel: 12



Plot 7-159. Radiated Restricted Upper Band Edge Measurement SISO CORE1 PRIMARY (Average & Peak)


FCC ID: BCGA2014	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 119 of 142

Worst Case Mode: 802.11b
Worst Case Transfer Rate: 1Mbps
Distance of Measurements: 3 Meters
Operating Frequency: 2472MHz
Channel: 13



Plot 7-160. Radiated Restricted Upper Band Edge Measurement SISO CORE1 PRIMARY (Average & Peak)


Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 2412MHz
Channel: 1



Plot 7-161. Radiated Restricted Lower Band Edge Measurement SISO CORE1 PRIMARY (Average & Peak)


FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 120 of 142

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 2417MHz
Channel: 2



Plot 7-162. Radiated Restricted Lower Band Edge Measurement SISO CORE1 PRIMARY (Average & Peak)


Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 2457MHz
Channel: 10



Plot 7-163. Radiated Restricted Upper Band Edge Measurement SISO CORE1 PRIMARY (Average & Peak)


FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 121 of 142

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 2462MHz
Channel: 11



Plot 7-164. Radiated Restricted Upper Band Edge Measurement SISO CORE1 PRIMARY (Average & Peak)


Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 2467MHz
Channel: 12



Plot 7-165. Radiated Restricted Upper Band Edge Measurement SISO CORE1 PRIMARY (Average & Peak)

FCC ID: BCGA2014	PCTEST ENGINEERING LABORATORY, INC.		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device		Page 122 of 142

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 2472MHz
Channel: 13



Plot 7-166. Radiated Restricted Upper Band Edge Measurement SISO CORE1 PRIMARY (Average & Peak)


FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 123 of 142

7.7.8 SISO Core1 Diversity Radiated Restricted Band Edge Measurements

§15.205 §15.209; RSS-Gen [8.9]


The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting.

Worst Case Mode: 802.11b
Worst Case Transfer Rate: 1Mbps
Distance of Measurements: 3 Meters
Operating Frequency: 2412MHz
Channel: 1



Plot 7-167. Radiated Restricted Lower Band Edge Measurement SISO CORE1 DIVERSITY (Average & Peak)


Worst Case Mode: 802.11b
Worst Case Transfer Rate: 1Mbps
Distance of Measurements: 3 Meters
Operating Frequency: 2472MHz
Channel: 13



Plot 7-168. Radiated Restricted Upper Band Edge Measurement SISO CORE1 DIVERSITY (Average & Peak)


FCC ID: BCGA2014	PCTEST ENGINEERING LABORATORY, INC.		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device		Page 124 of 142

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 2412MHz
Channel: 1



Plot 7-169. Radiated Restricted Lower Band Edge Measurement SISO CORE1 DIVERSITY (Average & Peak)


Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 2457MHz
Channel: 10



Plot 7-170. Radiated Restricted Upper Band Edge Measurement SISO CORE1 DIVERSITY (Average & Peak)


FCC ID: BCGA2014	PCTEST ENGINEERING LABORATORY, INC.		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device		Page 125 of 142

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 2462MHz
Channel: 11



Plot 7-171. Radiated Restricted Upper Band Edge Measurement SISO CORE1 DIVERSITY (Average & Peak)


Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 2467MHz
Channel: 12



Plot 7-172. Radiated Restricted Upper Band Edge Measurement SISO CORE1 DIVERSITY (Average & Peak)

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 126 of 142

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 2472MHz
Channel: 13



Plot 7-173. Radiated Restricted Upper Band Edge Measurement SISO CORE1 DIVERSITY (Average & Peak)


FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 127 of 142

7.7.9 CDD Primary Radiated Restricted Band Edge Measurements

§15.205 §15.209; RSS-Gen [8.9]


The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting.

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 2412MHz
Channel: 1



Plot 7-174. Radiated Restricted Lower Band Edge Measurement CDD PRIMARY (Average & Peak)


Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 2417MHz
Channel: 2



Plot 7-175. Radiated Restricted Lower Band Edge Measurement CDD PRIMARY (Average & Peak)


FCC ID: BCGA2014	PCTEST ENGINEERING LABORATORY, INC.		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device		Page 128 of 142

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 2457MHz
Channel: 10



Plot 7-176. Radiated Restricted Upper Band Edge Measurement CDD PRIMARY (Average & Peak)


Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 2462MHz
Channel: 11



Plot 7-177. Radiated Restricted Upper Band Edge Measurement CDD PRIMARY (Average & Peak)


FCC ID: BCGA2014	PCTEST ENGINEERING LABORATORY, INC.		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device		Page 129 of 142

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MSC0
Distance of Measurements: 3 Meters
Operating Frequency: 2467MHz
Channel: 12



Plot 7-178. Radiated Restricted Upper Band Edge Measurement CDD PRIMARY (Average & Peak)

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 2472MHz
Channel: 13



Plot 7-179. Radiated Restricted Upper Band Edge Measurement CDD PRIMARY (Average & Peak)


FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 130 of 142

7.7.10 CDD Diversity Radiated Restricted Band Edge Measurements

§15.205 §15.209; RSS-Gen [8.9]


The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting.

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 2412MHz
Channel: 1



Plot 7-180. Radiated Restricted Lower Band Edge Measurement CDD DIVERSITY (Average & Peak)


Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 2417MHz
Channel: 2



Plot 7-181. Radiated Restricted Lower Band Edge Measurement CDD DIVERSITY (Average & Peak)


FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 131 of 142

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 2457MHz
Channel: 10



Plot 7-182. Radiated Restricted Upper Band Edge Measurement CDD DIVERSITY (Average & Peak)


Worst Case Mode: 802.11n
Worst Case Transfer Rate: MSC0
Distance of Measurements: 3 Meters
Operating Frequency: 2462MHz
Channel: 11



Plot 7-183. Radiated Restricted Upper Band Edge Measurement CDD DIVERSITY (Average & Peak)


FCC ID: BCGA2014	PCTEST ENGINEERING LABORATORY, INC.		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device		Page 132 of 142

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MSC0
Distance of Measurements: 3 Meters
Operating Frequency: 2467MHz
Channel: 12



Plot 7-184. Radiated Restricted Upper Band Edge Measurement CDD DIVERSITY (Average & Peak)

Worst Case Mode: 802.11n
Worst Case Transfer Rate: MCS0
Distance of Measurements: 3 Meters
Operating Frequency: 2472MHz
Channel: 13



Plot 7-185. Radiated Restricted Upper Band Edge Measurement CDD DIVERSITY (Average & Peak)

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 133 of 142

7.8 Radiated Spurious Emissions Measurements – Below 1GHz

§15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 6 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-40 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-40. Radiated Limits

Test Procedures Used

ANSI C63.10-2013

Test Settings

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 100kHz (for emissions from 30MHz – 1GHz)
3. VBW = 300kHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 134 of 142

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.




Figure 7-7. Radiated Test Setup < 30MHz




Figure 7-8. Radiated Test Setup < 1GHz

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 135 of 142


Test Notes

1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen(8.10) are below the limit shown in Table 7-40.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. There were no emissions detected in the 30MHz – 1GHz frequency range, as shown in the subsequent plots.

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 136 of 142

Radiated Spurious Emissions Measurements (Below 1GHz)

§15.209; RSS-Gen [8.9]



Plot 7-186. Radiated Spurious Plot below 1GHz CDD Primary (802.11n – Ch. 6)

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
30.24	Quasi-Peak	V	100	288	-9.90	34.73	40.00	-5.27
46.83	Peak	V	100	99	-19.76	31.91	40.00	-8.09
59.10	Peak	V	100	252	-23.37	13.10	40.00	-26.90
111.04	Peak	V	100	300	-17.98	16.73	43.52	-26.79
187.53	Peak	H	100	247	-20.00	23.39	43.52	-20.13
276.67	Peak	H	100	311	-16.90	20.18	46.02	-25.84

Table 7-41. Radiated Spurious Emissions below 1GHz CDD Primary (802.11n – Ch. 6)

FCC ID: BCGA2014	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 137 of 142

7.9 AC Line-Conducted Test Data

§15.207; RSS-Gen [8.8]

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.207 and RSS-Gen (8.8).

Frequency of emission (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-42. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10-2013, Section 6.2

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: BCGA2014	 MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 138 of 142

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-9. Test Instrument & Measurement Setup

Test Notes

1. All modes of operation were investigated and the worst-case emissions are reported using mid channel. The emissions found were not affected by the choice of channel used during testing.
2. The limit for an intentional radiator from 150kHz to 30MHz are specified in Part 15.207 and RSS-Gen(8.8).
3. $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
4. $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Corr. (dB)}$
5. $\text{Margin (dB)} = \text{QP/AV Limit (dB}\mu\text{V)} - \text{QP/AV Level (dB}\mu\text{V)}$
6. Traces shown in plot are made using a peak detector.
7. Deviations to the Specifications: None.

FCC ID: BCGA2014	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 139 of 142




Plot 7-187. Line Conducted Plot with CDD Primary 802.11n – Ch. 6 (L1, with Adapter)

Frequency MHz	Process State	QuasiPeak dBμV	Average dBμV	Limit dBμV	Margin dB	Bandwidth kHz	Line	PE
0.197	FINAL	—	36.86	53.74	-16.88	9.00	L1	GND
0.199	FINAL	46.54	—	63.65	17.11	9.00	L1	GND
0.291	FINAL	38.83	—	60.50	-21.67	9.00	L1	GND
0.300	FINAL	—	26.10	50.24	-24.14	9.00	L1	GND
0.582	FINAL	—	23.92	46.00	-22.08	9.00	L1	GND
0.582	FINAL	39.45	—	56.00	-16.55	9.00	L1	GND
3.040	FINAL	17.52	—	56.00	-38.48	9.00	L1	GND
3.041	FINAL	—	10.58	46.00	-35.42	9.00	L1	GND
7.743	FINAL	19.59	—	60.00	-40.41	9.00	L1	GND
7.748	FINAL	—	13.34	50.00	-36.66	9.00	L1	GND
16.703	FINAL	—	13.34	50.00	-36.66	9.00	L1	GND
16.713	FINAL	19.05	—	60.00	-40.95	9.00	L1	GND

Table 7-43. Line Conducted Data with CDD Primary 802.11n – Ch. 6 (L1, with Adapter)

FCC ID: BCGA2014	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 140 of 142



Plot 7-188. Line Conducted Plot with CDD Primary 802.11n – Ch. 6 (N, with Adapter)

Frequency MHz	Process State	QuasiPeak dBμV	Average dBμV	Limit dBμV	Margin dB	Bandwidth kHz	Line	PE
0.237	FINAL	—	22.97	52.20	-29.23	9.00	N	GND
0.237	FINAL	35.70	—	62.20	-26.50	9.00	N	GND
0.291	FINAL	37.56	—	60.50	-22.94	9.00	N	GND
0.299	FINAL	—	25.04	50.27	-25.23	9.00	N	GND
0.583	FINAL	—	24.65	46.00	-21.35	9.00	N	GND
0.586	FINAL	38.54	—	56.00	-17.46	9.00	N	GND
3.192	FINAL	15.05	—	56.00	-40.95	9.00	N	GND
3.192	FINAL	—	9.04	46.00	-36.96	9.00	N	GND
6.648	FINAL	—	6.79	50.00	-43.21	9.00	N	GND
6.666	FINAL	12.59	—	60.00	-47.41	9.00	N	GND
17.436	FINAL	15.99	—	60.00	-44.01	9.00	N	GND
17.469	FINAL	—	9.69	50.00	-40.31	9.00	N	GND

Table 7-44. Line Conducted Data with CDD Primary 802.11n – Ch. 6 (N, with Adapter)

FCC ID: BCGA2014	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 141 of 142

8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Apple Tablet Device FCC ID: BCGA2014** is in compliance with Part 15 Subpart C (15.247) of the FCC Rules and RSS-247 of the Innovation, Science and Economic Development Canada Rules.

FCC ID: BCGA2014		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1C1806050011-05-R1.BCG	Test Dates: 7/26/2018-10/10/2018	EUT Type: Tablet Device	Page 142 of 142