

APPENDIX H: IEEE 802.11AX RU SAR EXCLUSION

FCC ID: BCGA2435	SAR EVALUATION REPORT	Reviewed by: Technical Manager
DUT Type: Tablet Device		APPENDIX H: Page 1 of 21

H.1 IEEE 802.11ax RU SAR Exclusion

To make the most efficient use of the additional available subcarriers (data tones), IEEE 802.11ax can utilize Orthogonal Frequency-Division Multiple Access (OFDMA) which divides the existing 802.11 channels into smaller subchannels called Resource Units (RUs). Possible RU sizes are: 26T, 52T, 106T, 242T, 484T and 996T.

Per FCC Guidance, 802.11ax was considered a higher order 802.11 mode when compared to a/b/g/n/ac to apply KDB Publication 248227 D01v02r02 for OFDM mode selection. Therefore, SAR tests were not required for 802.11ax based on the maximum allowed output powers of OFDM modes and the reported SAR values. Per FCC Guidance, maximum conducted powers were performed for each RU size to demonstrate that the output powers would not be higher than the other OFDM 802.11 modes.

H.2 IEEE 802.11ax RU Target Powers

H.2.1 Maximum 802.11ax RU Time-Averaged Output Power

Mode	IEEE 802.11ax RU (Maximum in dBm) - Antenna 4a Tolerance (+0/-3.00 dB)								
	Channel	SISO				MIMO			
		Tones							
		26T	52T	106T	242T	26T	52T	106T	242T
2.4 GHz WIFI 20 MHz Bandwidth	1	12.00	12.50	12.50	12.50	12.00	12.50	12.50	12.50
	2	12.00	12.50	12.50	12.50	12.00	12.50	12.50	12.50
	3	12.00	12.50	12.50	12.50	12.00	12.50	12.50	12.50
	4	12.00	12.50	12.50	12.50	12.00	12.50	12.50	12.50
	5	12.00	12.50	12.50	12.50	12.00	12.50	12.50	12.50
	6	12.00	12.50	12.50	12.50	12.00	12.50	12.50	12.50
	7	12.00	12.50	12.50	12.50	12.00	12.50	12.50	12.50
	8	12.00	12.50	12.50	12.50	12.00	12.50	12.50	12.50
	9	12.00	12.50	12.50	12.50	12.00	12.50	12.50	12.50
	10	12.00	12.50	12.50	12.50	12.00	12.50	12.50	12.50
	11	12.00	12.50	12.50	12.50	12.00	12.50	12.50	12.50
	12	11.50	11.50	11.50	11.50	11.50	11.50	11.50	11.50
	13	NS	NS	NS	NS	NS	NS	NS	NS

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.

Mode	IEEE 802.11ax RU (Maximum in dBm) - Antenna 2a Tolerance (+0/-3.00 dB)								
	Channel	SISO				MIMO			
		Tones							
		26T	52T	106T	242T	26T	52T	106T	242T
2.4 GHz WIFI 20 MHz Bandwidth	1	12.00	13.00	13.00	13.00	12.00	13.00	13.00	13.00
	2	12.00	13.00	13.00	13.00	12.00	13.00	13.00	13.00
	3	12.00	13.00	13.00	13.00	12.00	13.00	13.00	13.00
	4	12.00	13.00	13.00	13.00	12.00	13.00	13.00	13.00
	5	12.00	13.00	13.00	13.00	12.00	13.00	13.00	13.00
	6	12.00	13.00	13.00	13.00	12.00	13.00	13.00	13.00
	7	12.00	13.00	13.00	13.00	12.00	13.00	13.00	13.00
	8	12.00	13.00	13.00	13.00	12.00	13.00	13.00	13.00
	9	12.00	13.00	13.00	13.00	12.00	13.00	13.00	13.00
	10	12.00	13.00	13.00	13.00	12.00	13.00	13.00	13.00
	11	12.00	13.00	13.00	13.00	12.00	12.50	12.50	12.50
	12	11.50	11.50	11.50	11.50	11.50	11.50	11.50	11.50
	13	NS	NS	NS	NS	NS	NS	NS	NS

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.

FCC ID: BCGA2435	SAR EVALUATION REPORT	Reviewed by: Technical Manager
DUT Type: Tablet Device		APPENDIX H: Page 2 of 21

Mode	Channel	IEEE 802.11ax RU (Maximum in dBm) - Antenna 5b Tolerance (+0/-3.00 dB)																					
		SISO						MIMO CDD						MIMO SDM									
		26T	52T	106T	242T	484T	996T	996x2T	26T	52T	106T	242T	484T	996T	996x2T	26T	52T	106T	242T	484T	996T	996x2T	
5 GHz WiFi 20 MHz Bandwidth	36	10.50	13.50	15.50	15.50				8.75	11.75	14.75	15.50				9.00	12.00	15.00	15.50				
	40	10.50	13.50	16.50	16.50				8.75	11.75	14.75	16.50				9.00	12.00	15.00	16.50				
	44	10.50	13.50	16.50	16.50				8.75	11.75	14.75	16.50				9.00	12.00	15.00	16.50				
	48	10.50	13.50	16.50	16.50				8.75	11.75	14.75	16.50				9.00	12.00	15.00	16.50				
	52	NS	13.50	16.50	16.50				NS	11.75	14.75	16.50				NS	12.00	15.00	16.50				
	56	NS	13.50	16.50	16.50				NS	11.75	14.75	16.50				NS	12.00	15.00	16.50				
	60	NS	13.50	16.50	16.50				NS	11.75	14.75	16.50				NS	12.00	15.00	16.50				
	64	NS	13.50	16.50	16.50				NS	11.75	14.75	16.50				NS	12.00	15.00	16.50				
	100	NS	13.50	15.00	15.00				NS	12.00	14.50	14.50				NS	12.00	14.50	14.50				
	104	NS	13.50	15.00	15.00				NS	12.00	15.00	15.00				NS	12.00	15.00	15.00				
	108	NS	13.50	15.00	15.00				NS	12.00	15.00	15.00				NS	12.00	15.00	15.00				
	112	NS	13.50	15.00	15.00				NS	12.00	15.00	15.00				NS	12.00	15.00	15.00				
	116	NS	13.50	15.00	15.00				NS	12.00	15.00	15.00				NS	12.00	15.00	15.00				
	120	NS	13.50	15.00	15.00				NS	12.00	15.00	15.00				NS	12.00	15.00	15.00				
	124	NS	13.50	15.00	15.00				NS	12.00	15.00	15.00				NS	12.00	15.00	15.00				
	128	NS	13.50	15.00	15.00				NS	12.00	15.00	15.00				NS	12.00	15.00	15.00				
	132	NS	13.50	15.00	15.00				NS	12.00	15.00	15.00				NS	12.00	15.00	15.00				
	136	NS	13.50	15.00	15.00				NS	12.00	15.00	15.00				NS	12.00	15.00	15.00				
	140	NS	10.00	13.25	13.25				NS	8.50	13.25	13.25				NS	8.50	13.25	13.25				
	144	NS	13.50	15.00	15.00				NS	12.00	15.00	15.00				NS	12.00	15.00	15.00				
	148	10.50	13.50	15.50	15.50				10.50	13.50	15.50	15.50				10.50	13.50	15.50	15.50				
153	10.50	13.50	15.50	15.50				10.50	13.50	15.50	15.50				10.50	13.50	15.50	15.50					
157	10.50	13.50	15.50	15.50				10.50	13.50	15.50	15.50				10.50	13.50	15.50	15.50					
161	10.50	13.50	15.50	15.50				10.50	13.50	15.50	15.50				10.50	13.50	15.50	15.50					
165	10.50	13.50	15.50	15.50				10.50	13.50	15.50	15.50				10.50	13.50	15.50	15.50					
38	10.50	12.50	12.50	12.50		12.50		8.75	11.75	12.00	12.00		12.00		9.00	12.00	12.00	12.00		12.00			
46	10.50	13.50	16.50	16.50		16.50		8.75	11.75	14.75	16.50		16.50		9.00	12.00	15.00	16.50		16.50			
5 GHz WiFi 40 MHz Bandwidth	54	NS	13.50	16.50	16.50		16.50		NS	11.75	14.75	16.50		16.50		NS	12.00	15.00	16.50		16.50		
	62	NS	13.50	13.50	13.50		13.50		NS	11.75	13.00	13.00		13.00		NS	12.00	13.00	13.00		13.00		
	102	NS	11.50	11.50	11.50		11.50		NS	11.50	11.50	11.50		11.50		NS	11.50	11.50	11.50		11.50		
	110	NS	13.50	15.00	15.00		15.00		NS	12.00	15.00	15.00		15.00		NS	12.00	15.00	15.00		15.00		
	118	NS	13.50	15.00	15.00		15.00		NS	12.00	15.00	15.00		15.00		NS	12.00	15.00	15.00		15.00		
	126	NS	13.50	15.00	15.00		15.00		NS	12.00	15.00	15.00		15.00		NS	12.00	15.00	15.00		15.00		
	134	NS	13.50	15.00	15.00		15.00		NS	11.00	14.50	14.50		14.50		NS	11.00	14.50	14.50		14.50		
	142	NS	13.50	15.00	13.25		15.00		NS	12.00	15.00	13.25		15.00		NS	12.00	15.00	13.25		15.00		
	151	10.50	13.50	15.50	15.50		15.50		10.50	13.50	15.50	15.50		15.50		10.50	13.50	15.50	15.50		15.50		
	159	10.50	13.50	15.50	15.50		15.50		10.50	13.50	15.50	15.50		15.50		10.50	13.50	15.50	15.50		15.50		
	5 GHz WiFi 80 MHz Bandwidth	42	10.50	11.50	11.50	11.50		11.50		8.75	11.50	11.50	11.50		11.50		9.00	11.50	11.50	11.50		11.50	
		58	NS	13.00	13.00	13.00		13.00		NS	11.75	13.00	13.00		13.00		NS	12.00	13.00	13.00		13.00	
		106	NS	11.50	11.50	11.50		11.50		NS	11.00	11.00	11.00		11.00		NS	11.00	11.00	11.00		11.00	
		122	NS	13.50	15.00	15.00		15.00		NS	12.00	15.00	15.00		15.00		NS	12.00	15.00	15.00		15.00	
		138	NS	13.50	15.00	15.00		15.00		NS	12.00	15.00	15.00		14.50		NS	12.00	15.00	15.00		14.50	
		155	10.50	13.50	15.50	15.50		15.50		10.50	13.50	15.50	15.50		15.50		10.50	13.50	15.50	15.50		15.50	
	5 GHz WiFi 160 MHz Bandwidth	50	NS	8.00	8.00	8.00		8.00	8.00	NS	7.50	7.50	7.50		7.50	7.50	NS	7.50	7.50	7.50		7.50	7.50
114	NS	6.50	6.50	6.50		6.50	6.50	NS	6.50	6.50	6.50		6.50	6.50	NS	6.50	6.50	6.50		6.50	6.50		

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.

Note: 802.11a supports up to 20MHz, 802.11n supports up to 40MHz, 802.11ac/ax support up to 160MHz

Mode	Channel	IEEE 802.11ax RU (Maximum in dBm) - Antenna 4a Tolerance (+0/-3.00 dB)																															
		SISO											MIMO CDD											MIMO SDM									
		26T	52T	106T	242T	484T	996T	996x2T	26T	52T	106T	242T	484T	996T	996x2T	26T	52T	106T	242T	484T	996T	996x2T											
5 GHz WiFi 20 MHz Bandwidth	36	9.25	9.25	9.25	9.25	9.25			8.75	9.25	9.25	9.25	9.25			9.00	9.25	9.25	9.25	9.25													
	40	9.25	9.25	9.25	9.25	9.25			8.75	9.25	9.25	9.25	9.25			9.00	9.25	9.25	9.25	9.25													
	44	9.25	9.25	9.25	9.25	9.25			8.75	9.25	9.25	9.25	9.25			9.00	9.25	9.25	9.25	9.25													
	48	9.25	9.25	9.25	9.25	9.25			8.75	9.25	9.25	9.25	9.25			9.00	9.25	9.25	9.25	9.25													
	52	NS	8.50	8.50	8.50				NS	8.50	8.50	8.50				NS	8.50	8.50	8.50														
	56	NS	8.50	8.50	8.50				NS	8.50	8.50	8.50				NS	8.50	8.50	8.50														
	60	NS	8.50	8.50	8.50				NS	8.50	8.50	8.50				NS	8.50	8.50	8.50														
	64	NS	8.50	8.50	8.50				NS	8.50	8.50	8.50				NS	8.50	8.50	8.50														
	100	NS	9.25	9.25	9.25	9.25				NS	9.25	9.25	9.25				NS	9.25	9.25	9.25													
	104	NS	9.25	9.25	9.25				NS	9.25	9.25	9.25				NS	9.25	9.25	9.25														
	108	NS	9.25	9.25	9.25				NS	9.25	9.25	9.25				NS	9.25	9.25	9.25														
	112	NS	9.25	9.25	9.25				NS	9.25	9.25	9.25				NS	9.25	9.25	9.25														
	116	NS	9.25	9.25	9.25				NS	9.25	9.25	9.25				NS	9.25	9.25	9.25														
	120	NS	9.25	9.25	9.25				NS	9.25	9.25	9.25				NS	9.25	9.25	9.25														
	124	NS	9.25	9.25	9.25				NS	9.25	9.25	9.25				NS	9.25	9.25	9.25														
	128	NS	9.25	9.25	9.25				NS	9.25	9.25	9.25				NS	9.25	9.25	9.25														
	132	NS	9.25	9.25	9.25				NS	9.25	9.25	9.25				NS	9.25	9.25	9.25														
136	NS	9.25	9.25	9.25				NS	9.25	9.25	9.25				NS	9.25	9.25	9.25															
140	NS	9.25	9.25	9.25				NS	8.50	9.25	9.25				NS	8.50	9.25	9.25															
144	NS	9.25	9.25	9.25				NS	9.25	9.25	9.25				NS	9.25	9.25	9.25															
149	9.00	9.00	9.00	9.00				9.00	9.00	9.00	9.00				9.00	9.00	9.00	9.00															
153	9.00	9.00	9.00	9.00				9.00	9.00	9.00	9.00				9.00	9.00	9.00	9.00															
157	9.00	9.00	9.00	9.00				9.00	9.00	9.00	9.00				9.00	9.00	9.00	9.00															
161	9.00	9.00	9.00	9.00				9.00	9.00	9.00	9.00				9.00	9.00	9.00	9.00															
165	9.00	9.00	9.00	9.00				9.00	9.00	9.00	9.00				9.00	9.00	9.00	9.00															
169	8.25	9.25	9.25	9.25	9.25			8.75	9.25	9.25	9.25	9.25			9.00	9.25	9.25	9.25	9.25														
46	8.25	9.25	9.25	9.25	9.25			8.75	9.25	9.25	9.25	9.25			9.00	9.25	9.25	9.25	9.25														
54	NS	8.50	8.50	8.50	8.50			NS	8.50	8.50	8.50	8.50			NS	8.50	8.50	8.50	8.50														
62	NS	8.50	8.50	8.50	8.50			NS	8.50	8.50	8.50	8.50			NS	8.50	8.50	8.50	8.50														
102	NS	9.25	9.25	9.25	9.25			NS	9.25	9.25	9.25	9.25			NS	9.25	9.25	9.25	9.25														
110	NS	9.25	9.25	9.25	9.25			NS	9.25	9.25	9.25	9.25			NS	9.25	9.25	9.25	9.25														
118	NS	9.25	9.25	9.25	9.25			NS	9.25	9.25	9.25	9.25			NS	9.25	9.25	9.25	9.25														
126	NS	9.25	9.25	9.25	9.25			NS	9.25	9.25	9.25	9.25			NS	9.25	9.25	9.25	9.25														
134	NS	9.25	9.25	9.25	9.25			NS	9.25	9.25	9.25	9.25			NS	9.25	9.25	9.25	9.25														
142	NS	9.25	9.25	9.25	9.25			NS	9.25	9.25	9.25	9.25			NS	9.25	9.25	9.25	9.25														
151	9.00	9.00	9.00	9.00	9.00			9.00	9.00	9.00	9.00	9.00			9.00	9.00	9.00	9.00	9.00														
159	9.00	9.00	9.00	9.00	9.00			9.00	9.00	9.00	9.00	9.00			9.00	9.00	9.00	9.00	9.00														
42	9.25	9.25	9.25	9.25	9.25	9.25		8.75	9.25	9.25	9.25	9.25	9.25		9.00	9.25	9.25	9.25	9.25	9.25													
58	NS	8.50	8.50	8.50	8.50	8.50		NS	8.50	8.50	8.50	8.50	8.50		NS	8.50	8.50	8.50	8.50	8.50													
106	NS	9.25	9.25	9.25	9.25	9.25		NS	9.25	9.25	9.25	9.25	9.25		NS	9.25	9.25	9.25	9.25	9.25													
122	NS	9.25	9.25	9.25	9.25	9.25		NS	9.25	9.25	9.25	9.25	9.25		NS	9.25	9.25	9.25	9.25	9.25													
138	NS	9.25	9.25	9.25	9.25	9.25	9.25	9.25	9.25	9.25	9.25	9.25	9.25		NS	9.25	9.25	9.25	9.25	9.25													
155	9.00	9.00	9.00	9.00	9.00	9.00		9.00	9.00	9.00	9.00	9.00	9.00		9.00	9.00	9.00	9.00	9.00	9.00													
163	NS	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50		9.00	9.00	9.00	9.00	9.00	9.00	9.00												
167	NS	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50		9.00	9.00	9.00	9.00	9.00	9.00	9.00												
171	NS	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50		9.00	9.00	9.00	9.00	9.00	9.00	9.00												
175	NS	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50		9.00	9.00	9.00	9.00	9.00	9.00	9.00												
179	NS	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50		9.00	9.00	9.00	9.00	9.00	9.00	9.00												
183	NS	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50		9.00	9.00	9.00	9.00	9.00	9.00	9.00												
187	NS	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50		9.00	9.00	9.00	9.00	9.00	9.00	9.00												
191	NS	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50		9.00	9.00	9.00	9.00	9.00	9.00	9.00												
195	NS	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50		9.00	9.00	9.00	9.00	9.00	9.00	9.00												
199	NS	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50		9.00	9.00	9.00	9.00	9.00	9.00	9.00												
203	NS	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50		9.00	9.00	9.00	9.00	9.00	9.00	9.00												
207	NS	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50		9.00	9.00	9.00	9.00	9.00	9.00	9.00												
211	NS	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50		9.00	9.00	9.00	9.00	9.00	9.00	9.00												
215	NS	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50		9.00	9.00	9.00	9.00	9.00	9.00	9.00												
219	NS	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50		9.00	9.00	9.00	9.00	9.00	9.00	9.00												
223	NS	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50		9.00	9.00	9.00	9.00	9.00	9.00	9.00												
227	NS	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50		9.00	9.00	9.00	9.00	9.00	9.00	9.00												
231	NS	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50		9.00	9.00	9.00	9.00	9.00	9.00	9.00												
235	NS	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50		9.00	9.00	9.00	9.00	9.00	9.00	9.00												
239	NS	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50		9.00	9.00	9.00	9.00	9.00	9.00	9.00												
243	NS	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50		9.00	9.00	9.00	9.00	9.00	9.00	9.00												
247	NS	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50		9.00	9.00	9.00	9.00	9.00	9.00	9.00												
251	NS	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50		9.00	9.00	9.00	9.00	9.00	9.00	9.00												
255	NS	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50		9.00	9.00	9.00	9.00	9.00	9.00	9.00												
259	NS	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50		9.00	9.00	9.00	9.00	9.00	9.00	9.00												
263	NS	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50		9.00	9.00	9.00	9.00	9.00	9.00	9.00												
267	NS	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50	8.50		9.00	9.00	9.00	9.00	9.0														

Mode	Channel	IEEE 802.11ax RU(Maximum in dBm) - Ant 5b (Tolerance +0/-3.00dB)																				
		SISO						MIMO CDD						MIMO SDM								
		26T	52T	106T	242T	484T	996T	996T*2	26T	52T	106T	242T	484T	996T	996T*2	26T	52T	106T	242T	484T	996T	996T*2
6 GHz WiFi (20MHz BW)	1	-4.75	-1.75	1.25	3.25				NS	-5.75	-2.75	-0.75				-6.00	-3.00	0.00	2.00			
	5	-4.75	-1.75	1.25	3.25				NS	-5.75	-2.75	-0.75				-6.00	-3.00	0.00	2.00			
	9-29	-4.75	-1.75	1.25	3.25				NS	-5.75	-2.75	-0.75				-6.00	-3.00	0.00	2.00			
	33-61	-4.75	-1.75	1.25	3.25				NS	-6.25	-3.25	-1.25				-6.25	-3.25	-0.25	1.75			
	65-85	-4.75	-1.75	1.25	3.25				NS	-6.50	-3.50	-1.50				-6.50	-3.50	-0.50	1.50			
	89	-4.75	-1.75	1.25	3.25				NS	-6.50	-3.50	-1.50				-6.50	-3.50	-0.50	1.50			
	93	-4.75	-1.75	1.25	3.25				NS	-6.50	-3.50	-1.50				-6.50	-3.50	-0.50	1.50			
	97-113	-5.00	-2.00	1.00	3.00				NS	-6.50	-3.50	-1.50				-6.75	-3.75	-0.75	1.25			
	117-181	-5.25	-2.25	0.75	2.75				NS	-6.25	-3.25	-1.25				-6.50	-3.50	-0.50	1.50			
	185	-5.25	-2.25	0.75	2.75				NS	-6.25	-3.25	-1.25				-6.50	-3.50	-0.50	1.50			
	189-225	-4.75	-1.75	1.25	3.25				-7.75	-4.75	-1.75	0.25				-5.50	-2.50	0.50	2.50			
	229	-4.75	-1.75	1.25	3.25				-7.75	-4.75	-1.75	0.25				-5.50	-2.50	0.50	2.50			
233	NS	NS	NS	NS				NS	NS	NS	NS				NS	NS	NS	NS				
6 GHz WiFi (40MHz BW)	3	-4.75	-1.75	1.25	3.25	6.25			NS	-5.75	-2.75	-0.75	2.25			-6.00	-3.00	0.00	2.00	5.00		
	11	-4.75	-1.75	1.25	3.25	6.25			NS	-5.75	-2.75	-0.75	2.25			-6.00	-3.00	0.00	2.00	5.00		
	19-27	-4.75	-1.75	1.25	3.25	6.25			NS	-5.75	-2.75	-0.75	2.25			-6.00	-3.00	0.00	2.00	5.00		
	35-59	-4.75	-1.75	1.25	3.25	6.25			NS	-6.25	-3.25	-1.25	1.75			-6.25	-3.25	-0.25	1.75	4.75		
	67-75	-4.75	-1.75	1.25	3.25	6.25			NS	-6.50	-3.50	-1.50	1.50			-6.50	-3.50	-0.50	1.50	4.50		
	83	-4.75	-1.75	1.25	3.25	6.25			NS	-6.50	-3.50	-1.50	1.50			-6.50	-3.50	-0.50	1.50	4.50		
	91	-4.75	-1.75	1.25	3.25	6.25			NS	-6.50	-3.50	-1.50	1.50			-6.50	-3.50	-0.50	1.50	4.50		
	99-107	-5.00	-2.00	1.00	3.00	6.00			NS	-6.50	-3.50	-1.50	1.50			-6.75	-3.75	-0.75	1.25	4.25		
	115	-5.25	-2.25	0.75	2.75	5.75			NS	-6.50	-3.50	-1.50	1.50			-6.75	-3.75	-0.75	1.25	4.25		
	123-179	-5.25	-2.25	0.75	2.75	5.75			NS	-6.25	-3.25	-1.25	1.75			-6.50	-3.50	-0.50	1.50	4.50		
	187	-5.25	-2.25	0.75	2.75	5.75			NS	-6.25	-3.25	-1.25	1.75			-6.50	-3.50	-0.50	1.50	4.50		
	195-219	-4.75	-1.75	1.25	3.25	6.25			-7.75	-4.75	-1.75	0.25	3.25			-5.50	-2.50	0.50	2.50	5.50		
227	-4.75	-1.75	1.25	3.25	6.25			-7.75	-4.75	-1.75	0.25	3.25			-5.50	-2.50	0.50	2.50	5.50			
6 GHz WiFi (80MHz BW)	7	-4.75	-1.75	1.25	3.25	6.25	9.25		NS	-5.75	-2.75	-0.75	2.25	5.25		-6.00	-3.00	0.00	2.00	5.00	8.00	
	23	-4.75	-1.75	1.25	3.25	6.25	9.25		NS	-5.75	-2.75	-0.75	2.25	5.25		-6.00	-3.00	0.00	2.00	5.00	8.00	
	39-55	-4.75	-1.75	1.25	3.25	6.25	9.25		NS	-6.25	-3.25	-1.25	1.75	4.75		-6.25	-3.25	-0.25	1.75	4.75	7.75	
	71	-4.75	-1.75	1.25	3.25	6.25	9.25		NS	-6.50	-3.50	-1.50	1.50	4.50		-6.50	-3.50	-0.50	1.50	4.50	7.50	
	87	-4.75	-1.75	1.25	3.25	6.25	9.25		NS	-6.50	-3.50	-1.50	1.50	4.50		-6.50	-3.50	-0.50	1.50	4.50	7.50	
	103	-5.00	-2.00	1.00	3.00	6.00	9.00		NS	-6.50	-3.50	-1.50	1.50	4.50		-6.75	-3.75	-0.75	1.25	4.25	7.25	
	119	-5.25	-2.25	0.75	2.75	5.75	8.75		NS	-6.50	-3.50	-1.50	1.50	4.50		-6.75	-3.75	-0.75	1.25	4.25	7.25	
	135-167	-5.25	-2.25	0.75	2.75	5.75	8.75		NS	-6.25	-3.25	-1.25	1.75	4.75		-6.50	-3.50	-0.50	1.50	4.50	7.50	
	183	-5.25	-2.25	0.75	2.75	5.75	8.75		NS	-6.25	-3.25	-1.25	1.75	4.75		-6.50	-3.50	-0.50	1.50	4.50	7.50	
	199	-4.75	-1.75	1.25	3.25	6.25	9.25		-7.75	-4.75	-1.75	0.25	3.25	6.25		-5.50	-2.50	0.50	2.50	5.50	8.50	
	215	-4.75	-1.75	1.25	3.25	6.25	9.25		-7.75	-4.75	-1.75	0.25	3.25	6.25		-5.50	-2.50	0.50	2.50	5.50	8.50	
	6 GHz WiFi (160MHz BW)	15	-4.75	-1.75	1.25	3.25	6.25	9.25	12.75	NS	-5.75	-2.75	-0.75	2.25	5.25	8.75	-6.00	-3.00	0.00	2.00	5.00	8.00
47		-4.75	-1.75	1.25	3.25	6.25	9.25	13.00	NS	-6.25	-3.25	-1.25	1.75	4.75	8.75	-6.25	-3.25	-0.25	1.75	4.75	7.75	11.75
79		-4.75	-1.75	1.25	3.25	6.25	9.25	12.00	NS	-6.50	-3.50	-1.50	1.50	4.50	8.50	-6.50	-3.50	-0.50	1.50	4.50	7.50	11.50
111		-5.25	-2.25	0.75	2.75	5.75	8.75	12.25	NS	-6.50	-3.50	-1.50	1.50	4.50	8.50	-6.75	-3.75	-0.75	1.25	4.25	7.25	11.25
143		-5.25	-2.25	0.75	2.75	5.75	8.75	11.50	NS	-6.25	-3.25	-1.25	1.75	4.75	8.75	-6.50	-3.50	-0.50	1.50	4.50	7.50	11.50
175		-5.25	-2.25	0.75	2.75	5.75	8.75	11.50	NS	-6.25	-3.25	-1.25	1.75	4.75	8.75	-6.50	-3.50	-0.50	1.50	4.50	7.50	11.50
207	-4.75	-1.75	1.25	3.25	6.25	9.25	11.75	-7.75	-4.75	-1.75	0.25	3.25	6.25	9.75	-5.50	-2.50	0.50	2.50	5.50	8.50	11.75	

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.

FCC ID: BCGA2435	SAR EVALUATION REPORT	Reviewed by: Technical Manager
DUT Type: Tablet Device		APPENDIX H: Page 4 of 21

Mode	Channel	IEEE 802.11ax RU (Maximum in dBm) - Ant 4a (Tolerance +/-3.00dB)																				
		SISO						MIMO CDD						MIMO SDM								
		26T	52T	106T	242T	484T	996T	996T*2	26T	52T	106T	242T	484T	996T	996T*2	26T	52T	106T	242T	484T	996T	996T*2
6 GHz WiFi (20MHz BW)	1	-4.75	-1.75	1.25	3.25				NS	-5.75	-2.75	-0.75				-6.00	-3.00	0.00	2.00			
	5	-4.75	-1.75	1.25	3.25				NS	-5.75	-2.75	-0.75				-6.00	-3.00	0.00	2.00			
	9-29	-4.75	-1.75	1.25	3.25				NS	-5.75	-2.75	-0.75				-6.00	-3.00	0.00	2.00			
	33-61	-4.75	-1.75	1.25	3.25				NS	-6.25	-3.25	-1.25				-6.25	-3.25	-0.25	1.75			
	65-85	-4.75	-1.75	1.25	3.25				NS	-6.50	-3.50	-1.50				-6.50	-3.50	-0.50	1.50			
	89	-4.75	-1.75	1.25	3.25				NS	-6.50	-3.50	-1.50				-6.50	-3.50	-0.50	1.50			
	93	-4.75	-1.75	1.25	3.25				NS	-6.50	-3.50	-1.50				-6.50	-3.50	-0.50	1.50			
	97-113	-5.00	-2.00	1.00	3.00				NS	-6.50	-3.50	-1.50				-6.75	-3.75	-0.75	1.25			
	117-181	-5.25	-2.25	0.75	2.75				NS	-6.25	-3.25	-1.25				-6.50	-3.50	-0.50	1.50			
	185	-5.25	-2.25	0.75	2.75				NS	-6.25	-3.25	-1.25				-6.50	-3.50	-0.50	1.50			
6 GHz WiFi (40MHz BW)	189-225	-4.75	-1.75	1.25	3.25				-7.75	-4.75	-1.75	0.25				-5.50	-2.50	0.50	2.50			
	229	-4.75	-1.75	1.25	3.25				-7.75	-4.75	-1.75	0.25				-5.50	-2.50	0.50	2.50			
	233	NS	NS	NS	NS				NS	NS	NS	NS				NS	NS	NS	NS			
	3	-4.75	-1.75	1.25	3.25	6.25			NS	-5.75	-2.75	-0.75	2.25			-6.00	-3.00	0.00	2.00	5.00		
	11	-4.75	-1.75	1.25	3.25	6.25			NS	-5.75	-2.75	-0.75	2.25			-6.00	-3.00	0.00	2.00	5.00		
	19-27	-4.75	-1.75	1.25	3.25	6.25			NS	-5.75	-2.75	-0.75	2.25			-6.00	-3.00	0.00	2.00	5.00		
	35-59	-4.75	-1.75	1.25	3.25	6.25			NS	-6.25	-3.25	-1.25	1.75			-6.25	-3.25	-0.25	1.75	4.75		
	67-75	-4.75	-1.75	1.25	3.25	6.25			NS	-6.50	-3.50	-1.50	1.50			-6.50	-3.50	-0.50	1.50	4.50		
	83	-4.75	-1.75	1.25	3.25	6.25			NS	-6.50	-3.50	-1.50	1.50			-6.50	-3.50	-0.50	1.50	4.50		
	91	-4.75	-1.75	1.25	3.25	6.25			NS	-6.50	-3.50	-1.50	1.50			-6.50	-3.50	-0.50	1.50	4.50		
6 GHz WiFi (80MHz BW)	99-107	-5.00	-2.00	1.00	3.00	6.00			NS	-6.50	-3.50	-1.50	1.50			-6.75	-3.75	-0.75	1.25	4.25		
	115	-5.25	-2.25	0.75	2.75	5.75			NS	-6.50	-3.50	-1.50	1.50			-6.75	-3.75	-0.75	1.25	4.25		
	123-179	-5.25	-2.25	0.75	2.75	5.75			NS	-6.25	-3.25	-1.25	1.75			-6.50	-3.50	-0.50	1.50	4.50		
	187	-5.25	-2.25	0.75	2.75	5.75			NS	-6.25	-3.25	-1.25	1.75			-6.50	-3.50	-0.50	1.50	4.50		
	195-219	-4.75	-1.75	1.25	3.25	6.25			-7.75	-4.75	-1.75	0.25	3.25			-5.50	-2.50	0.50	2.50	5.50		
	227	-4.75	-1.75	1.25	3.25	6.25			-7.75	-4.75	-1.75	0.25	3.25			-5.50	-2.50	0.50	2.50	5.50		
	7	-4.75	-1.75	1.25	3.25	6.25	8.00		NS	-5.75	-2.75	-0.75	2.25	5.25		-6.00	-3.00	0.00	2.00	5.00	8.00	
	23	-4.75	-1.75	1.25	3.25	6.25	8.00		NS	-5.75	-2.75	-0.75	2.25	5.25		-6.00	-3.00	0.00	2.00	5.00	8.00	
	39-55	-4.75	-1.75	1.25	3.25	6.25	8.00		NS	-6.25	-3.25	-1.25	1.75	4.75		-6.25	-3.25	-0.25	1.75	4.75	7.75	
	71	-4.75	-1.75	1.25	3.25	6.25	8.00		NS	-6.50	-3.50	-1.50	1.50	4.50		-6.50	-3.50	-0.50	1.50	4.50	7.50	
6 GHz WiFi (160MHz BW)	87	-4.75	-1.75	1.25	3.25	6.25	8.00		NS	-6.50	-3.50	-1.50	1.50	4.50		-6.50	-3.50	-0.50	1.50	4.50	7.50	
	103	-5.00	-2.00	1.00	3.00	6.00	9.00		NS	-6.50	-3.50	-1.50	1.50	4.50		-6.75	-3.75	-0.75	1.25	4.25	7.25	
	119	-5.25	-2.25	0.75	2.75	5.75	8.75		NS	-6.50	-3.50	-1.50	1.50	4.50		-6.75	-3.75	-0.75	1.25	4.25	7.25	
	135-167	-5.25	-2.25	0.75	2.75	5.75	8.75		NS	-6.25	-3.25	-1.25	1.75	4.75		-6.50	-3.50	-0.50	1.50	4.50	7.50	
	183	-5.25	-2.25	0.75	2.75	5.75	8.75		NS	-6.25	-3.25	-1.25	1.75	4.75		-6.50	-3.50	-0.50	1.50	4.50	7.50	
	199	-4.75	-1.75	1.25	3.25	6.25	9.25		-7.75	-4.75	-1.75	0.25	3.25	6.25		-5.50	-2.50	0.50	2.50	5.50	8.50	
	215	-4.75	-1.75	1.25	3.25	6.25	9.25		-7.75	-4.75	-1.75	0.25	3.25	6.25		-5.50	-2.50	0.50	2.50	5.50	8.50	
	15	-4.75	-1.75	1.25	3.25	6.25	9.25	10.00	NS	-5.75	-2.75	-0.75	2.25	5.25	7.75	-6.00	-3.00	0.00	2.00	5.00	8.00	10.00
	47	-4.75	-1.75	1.25	3.25	6.25	9.25	9.00	NS	-6.25	-3.25	-1.25	1.75	4.75	7.25	-6.25	-3.25	-0.25	1.75	4.75	7.75	9.00
	79	-4.75	-1.75	1.25	3.25	6.25	9.25	8.50	NS	-6.50	-3.50	-1.50	1.50	4.50	7.00	-6.50	-3.50	-0.50	1.50	4.50	7.50	8.50
6 GHz WiFi (160MHz BW)	111	-5.25	-2.25	0.75	2.75	5.75	8.75	8.50	NS	-6.50	-3.50	-1.50	1.50	4.50	7.00	-6.75	-3.75	-0.75	1.25	4.25	7.25	8.50
	143	-5.25	-2.25	0.75	2.75	5.75	8.75	8.50	NS	-6.25	-3.25	-1.25	1.75	4.75	7.25	-6.50	-3.50	-0.50	1.50	4.50	7.50	8.50
	175	-5.25	-2.25	0.75	2.75	5.75	8.75	11.00	NS	-6.25	-3.25	-1.25	1.75	4.75	7.25	-6.50	-3.50	-0.50	1.50	4.50	7.50	11.00
	207	-4.75	-1.75	1.25	3.25	6.25	9.25	12.00	-7.75	-4.75	-1.75	0.25	3.25	6.25	8.75	-5.50	-2.50	0.50	2.50	5.50	8.50	12.00

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.

FCC ID: BCGA2435	SAR EVALUATION REPORT	Reviewed by: Technical Manager
DUT Type: Tablet Device		APPENDIX H: Page 5 of 21

H.2.2 Reduced 802.11ax RU Time-Averaged Output Power

Below table is applicable in the following conditions:

- Simultaneous conditions with Licensed Bands Antenna 4a active
- Simultaneous conditions with Inter-Band ULCA active

Mode	IEEE 802.11ax RU (Maximum in dBm) - Antenna 4a Tolerance (+0/-3.00 dB)								
	Channel	SISO				MIMO			
		Tones							
		26T	52T	106T	242T	26T	52T	106T	242T
2.4 GHz WIFI 20 MHz Bandwidth	1	7.50	7.50	7.50	7.50	7.50	7.50	7.50	7.50
	2	7.50	7.50	7.50	7.50	7.50	7.50	7.50	7.50
	3	7.50	7.50	7.50	7.50	7.50	7.50	7.50	7.50
	4	7.50	7.50	7.50	7.50	7.50	7.50	7.50	7.50
	5	7.50	7.50	7.50	7.50	7.50	7.50	7.50	7.50
	6	7.50	7.50	7.50	7.50	7.50	7.50	7.50	7.50
	7	7.50	7.50	7.50	7.50	7.50	7.50	7.50	7.50
	8	7.50	7.50	7.50	7.50	7.50	7.50	7.50	7.50
	9	7.50	7.50	7.50	7.50	7.50	7.50	7.50	7.50
	10	7.50	7.50	7.50	7.50	7.50	7.50	7.50	7.50
	11	7.50	7.50	7.50	7.50	7.50	7.50	7.50	7.50
	12	7.50	7.50	7.50	7.50	7.50	7.50	7.50	7.50
	13	NS	NS	NS	NS	NS	NS	NS	NS

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.

Below table is applicable in the following conditions:

- Simultaneous conditions with Licensed Bands Antenna 2a/2b active
- Simultaneous conditions with Inter-Band ULCA active

Mode	IEEE 802.11ax RU (Maximum in dBm) - Antenna 2a Tolerance (+0/-3.00 dB)								
	Channel	SISO				MIMO			
		Tones							
		26T	52T	106T	242T	26T	52T	106T	242T
2.4 GHz WIFI 20 MHz Bandwidth	1	9.50	9.50	9.50	9.50	9.50	9.50	9.50	9.50
	2	9.50	9.50	9.50	9.50	9.50	9.50	9.50	9.50
	3	9.50	9.50	9.50	9.50	9.50	9.50	9.50	9.50
	4	9.50	9.50	9.50	9.50	9.50	9.50	9.50	9.50
	5	9.50	9.50	9.50	9.50	9.50	9.50	9.50	9.50
	6	9.50	9.50	9.50	9.50	9.50	9.50	9.50	9.50
	7	9.50	9.50	9.50	9.50	9.50	9.50	9.50	9.50
	8	9.50	9.50	9.50	9.50	9.50	9.50	9.50	9.50
	9	9.50	9.50	9.50	9.50	9.50	9.50	9.50	9.50
	10	9.50	9.50	9.50	9.50	9.50	9.50	9.50	9.50
	11	9.50	9.50	9.50	9.50	9.50	9.50	9.50	9.50
	12	9.50	9.50	9.50	9.50	9.50	9.50	9.50	9.50
	13	NS	NS	NS	NS	NS	NS	NS	NS

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.

FCC ID: BCGA2435	SAR EVALUATION REPORT	Reviewed by: Technical Manager
DUT Type: Tablet Device		APPENDIX H: Page 6 of 21

Below table is applicable in the following conditions:

-Simultaneous conditions with Licensed Bands for Antenna 2a/2b active

-Simultaneous conditions with Inter-Band ULCA active

Mode	Channel	IEEE 802.11ax RU (Maximum in dBm) - Antenna 5b Tolerance (+0/-3.00 dB)																					
		SISO						MIMO CDD						MIMO SDM									
		26T	52T	106T	242T	484T	996T	996x2T	26T	52T	106T	242T	484T	996T	996x2T	26T	52T	106T	242T	484T	996T	996x2T	
5 GHz WiFi 20 MHz Bandwidth	36	10.50	12.50	12.50	12.50				8.75	11.75	12.50	12.50				9.00	12.00	12.50	12.50				
	40	10.50	12.50	12.50	12.50				8.75	11.75	12.50	12.50				9.00	12.00	12.50	12.50				
	44	10.50	12.50	12.50	12.50				8.75	11.75	12.50	12.50				9.00	12.00	12.50	12.50				
	48	10.50	12.50	12.50	12.50				8.75	11.75	12.50	12.50				9.00	12.00	12.50	12.50				
	52	NS	12.50	12.50	12.50				NS	11.75	12.50	12.50				NS	12.00	12.50	12.50				
	56	NS	12.50	12.50	12.50				NS	11.75	12.50	12.50				NS	12.00	12.50	12.50				
	60	NS	12.50	12.50	12.50				NS	11.75	12.50	12.50				NS	12.00	12.50	12.50				
	64	NS	12.50	12.50	12.50				NS	11.75	12.50	12.50				NS	12.00	12.50	12.50				
	100	NS	11.00	11.00	11.00				NS	11.00	11.00	11.00				NS	11.00	11.00	11.00				
	104	NS	11.00	11.00	11.00				NS	11.00	11.00	11.00				NS	11.00	11.00	11.00				
	108	NS	11.00	11.00	11.00				NS	11.00	11.00	11.00				NS	11.00	11.00	11.00				
	112	NS	11.00	11.00	11.00				NS	11.00	11.00	11.00				NS	11.00	11.00	11.00				
	116	NS	11.00	11.00	11.00				NS	11.00	11.00	11.00				NS	11.00	11.00	11.00				
	120	NS	11.00	11.00	11.00				NS	11.00	11.00	11.00				NS	11.00	11.00	11.00				
	124	NS	11.00	11.00	11.00				NS	11.00	11.00	11.00				NS	11.00	11.00	11.00				
	128	NS	11.00	11.00	11.00				NS	11.00	11.00	11.00				NS	11.00	11.00	11.00				
	132	NS	11.00	11.00	11.00				NS	11.00	11.00	11.00				NS	11.00	11.00	11.00				
	136	NS	11.00	11.00	11.00				NS	11.00	11.00	11.00				NS	11.00	11.00	11.00				
	140	NS	10.00	11.00	11.00	11.00				NS	8.50	11.00	11.00				NS	8.50	11.00	11.00			
	144	NS	11.00	11.00	11.00	11.00				NS	11.00	11.00	11.00				NS	11.00	11.00	11.00			
	148	10.50	12.00	12.00	12.00	12.00				10.50	12.00	12.00	12.00				10.50	12.00	12.00	12.00			
	152	10.50	12.00	12.00	12.00	12.00				10.50	12.00	12.00	12.00				10.50	12.00	12.00	12.00			
	156	10.50	12.00	12.00	12.00	12.00				10.50	12.00	12.00	12.00				10.50	12.00	12.00	12.00			
	160	10.50	12.00	12.00	12.00	12.00				10.50	12.00	12.00	12.00				10.50	12.00	12.00	12.00			
165	10.50	12.00	12.00	12.00	12.00				10.50	12.00	12.00	12.00				10.50	12.00	12.00	12.00				
5 GHz WiFi 40 MHz Bandwidth	36	10.50	12.50	12.50	12.50	12.50			8.75	11.75	12.00	12.00	12.00	12.00		9.00	12.00	12.00	12.00	12.00			
	40	10.50	12.50	12.50	12.50	12.50			8.75	11.75	12.50	12.50	12.50		9.00	12.00	12.50	12.50	12.50				
	44	NS	12.50	12.50	12.50	12.50			NS	11.75	12.50	12.50	12.50		NS	12.00	12.50	12.50	12.50				
	48	NS	12.50	12.50	12.50	12.50			NS	11.75	12.50	12.50	12.50		NS	12.00	12.50	12.50	12.50				
	52	NS	11.00	11.00	11.00	11.00			NS	11.00	11.00	11.00	11.00		NS	11.00	11.00	11.00	11.00				
	56	NS	11.00	11.00	11.00	11.00			NS	11.00	11.00	11.00	11.00		NS	11.00	11.00	11.00	11.00				
	60	NS	11.00	11.00	11.00	11.00			NS	11.00	11.00	11.00	11.00		NS	11.00	11.00	11.00	11.00				
	64	NS	11.00	11.00	11.00	11.00			NS	11.00	11.00	11.00	11.00		NS	11.00	11.00	11.00	11.00				
	100	NS	11.00	11.00	11.00	11.00			NS	11.00	11.00	11.00	11.00		NS	11.00	11.00	11.00	11.00				
	104	NS	11.00	11.00	11.00	11.00			NS	11.00	11.00	11.00	11.00		NS	11.00	11.00	11.00	11.00				
	108	NS	11.00	11.00	11.00	11.00			NS	11.00	11.00	11.00	11.00		NS	11.00	11.00	11.00	11.00				
	112	NS	11.00	11.00	11.00	11.00			NS	11.00	11.00	11.00	11.00		NS	11.00	11.00	11.00	11.00				
116	NS	11.00	11.00	11.00	11.00			NS	11.00	11.00	11.00	11.00		NS	11.00	11.00	11.00	11.00					
120	NS	11.00	11.00	11.00	11.00			NS	11.00	11.00	11.00	11.00		NS	11.00	11.00	11.00	11.00					
124	NS	11.00	11.00	11.00	11.00			NS	11.00	11.00	11.00	11.00		NS	11.00	11.00	11.00	11.00					
128	NS	11.00	11.00	11.00	11.00			NS	11.00	11.00	11.00	11.00		NS	11.00	11.00	11.00	11.00					
132	NS	11.00	11.00	11.00	11.00			NS	11.00	11.00	11.00	11.00		NS	11.00	11.00	11.00	11.00					
136	NS	11.00	11.00	11.00	11.00			NS	11.00	11.00	11.00	11.00		NS	11.00	11.00	11.00	11.00					
140	NS	11.00	11.00	11.00	11.00			NS	11.00	11.00	11.00	11.00		NS	11.00	11.00	11.00	11.00					
144	NS	11.00	11.00	11.00	11.00			NS	11.00	11.00	11.00	11.00		NS	11.00	11.00	11.00	11.00					
148	NS	11.00	11.00	11.00	11.00			NS	11.00	11.00	11.00	11.00		NS	11.00	11.00	11.00	11.00					
152	10.50	12.00	12.00	12.00	12.00	12.00			10.50	12.00	12.00	12.00	12.00	12.00		10.50	12.00	12.00	12.00	12.00	12.00		
156	10.50	12.00	12.00	12.00	12.00	12.00			10.50	12.00	12.00	12.00	12.00	12.00		10.50	12.00	12.00	12.00	12.00	12.00		
160	10.50	12.00	12.00	12.00	12.00	12.00			10.50	12.00	12.00	12.00	12.00	12.00		10.50	12.00	12.00	12.00	12.00	12.00		
5 GHz WiFi 80 MHz Bandwidth	42	10.50	11.50	11.50	11.50	11.50	11.50		8.75	11.50	11.50	11.50	11.50	11.50	11.50	9.00	11.50	11.50	11.50	11.50	11.50	11.50	
	46	NS	12.50	12.50	12.50	12.50	12.50		NS	11.75	12.50	12.50	12.50	12.50	12.50	NS	12.00	12.50	12.50	12.50	12.50		
	50	NS	11.00	11.00	11.00	11.00	11.00		NS	11.00	11.00	11.00	11.00	11.00	11.00	NS	11.00	11.00	11.00	11.00	11.00		
	54	NS	11.00	11.00	11.00	11.00	11.00		NS	11.00	11.00	11.00	11.00	11.00	11.00	NS	11.00	11.00	11.00	11.00	11.00		
	58	NS	11.00	11.00	11.00	11.00	11.00		NS	11.00	11.00	11.00	11.00	11.00	11.00	NS	11.00	11.00	11.00	11.00	11.00		
	62	NS	11.00	11.00	11.00	11.00	11.00		NS	11.00	11.00	11.00	11.00	11.00	11.00	NS	11.00	11.00	11.00	11.00	11.00		
	66	NS	11.00	11.00	11.00	11.00	11.00		NS	11.00	11.00	11.00	11.00	11.00	11.00	NS	11.00	11.00	11.00	11.00	11.00		
	70	NS	11.00	11.00	11.00	11.00	11.00		NS	11.00	11.00	11.00	11.00	11.00	11.00	NS	11.00	11.00	11.00	11.00	11.00		
5 GHz WiFi 160 MHz Bandwidth	100	NS	11.00	11.00	11.00	11.00	11.00		NS	11.00	11.00	11.00	11.00	11.00	11.00	NS	11.00	11.00	11.00	11.00	11.00		
	104	NS	11.00	11.00	11.00	11.00	11.00		NS	11.00	11.00	11.00	11.00	11.00	11.00	NS	11.00	11.00	11.00	11.00	11.00		
	108	NS	11.00	11.00	11.00	11.00	11.00		NS	11.00	11.00	11.00	11.00	11.00	11.00	NS	11.00	11.00	11.00	11.00	11.00		
	112	NS	11.00	11.00	11.00	11.00	11.00		NS	11.00	11.00	11.00	11.00	11.00	11.00	NS	11.00	11.00	11.00	11.00	11.00		
	116	NS	11.00	11.00	11.00	11.00	11.00		NS	11.00	11.00	11.00	11.00	11.00	11.00	NS	11.00	11.00	11.00	11.00	11.00		
	120	NS	11.00	11.00	11.00	11.00	11.00		NS	11.00	11.00	11.00	11.00	11.00	11.00	NS	11.00	11.00	11.00	11.00	11.00		
	124	NS	11.00	11.00	11.00	11.00	11.00		NS	11.00	11.00	11.00	11.00	11.00	11.00	NS	11.00	11.00	11.00	11.00	11.00		
	128	NS	11.00	11.00	11.00	11.00	11.00		NS	11.00	11.00	11.00	11.00	11.00	11.00	NS	11.00	11.00	11.00	11.00	11.00		
5 GHz WiFi 160 MHz Bandwidth	132	NS	11.00	11.00	11.00	11.00	11.00		NS	11.00	11.00	11.00	11.00	11.00	11.00	NS	11.00	11.00	11.00	11.00	11.00		
	136	NS	11.00	11.00	11.00	11.00	11.00		NS	11.00	11.00	11.00	11.00	11.00	11.00	NS	11.00	11.00	11.00	11.00	11.00		
	140	NS	11.00	11.00	11.00	11.00	11.00		NS	11.00	11.00	11.00	11.00	11.00									

Below table is applicable in the following conditions:

-Simultaneous conditions with Licensed Bands Antenna 4b active

-Simultaneous conditions with Inter-Band ULCA active

Mode	Channel	IEEE 802.11ax RU (Maximum in dBm) - Antenna 4a Tolerance (+0/-3.00 dB)																				
		SISO						MIMO CDD						MIMO SDM								
		26T	52T	106T	242T	484T	996T	996x2T	26T	52T	106T	242T	484T	996T	996x2T	26T	52T	106T	242T	484T	996T	996x2T
5 GHz WiFi 20 MHz Bandwidth	36	3.75	3.75	3.75	3.75	3.75			3.75	3.75	3.75	3.75				3.75	3.75	3.75	3.75			
	40	3.75	3.75	3.75	3.75				3.75	3.75	3.75	3.75				3.75	3.75	3.75	3.75			
	44	3.75	3.75	3.75	3.75				3.75	3.75	3.75	3.75				3.75	3.75	3.75	3.75			
	48	3.75	3.75	3.75	3.75				3.75	3.75	3.75	3.75				3.75	3.75	3.75	3.75			
	52	NS	3.00	3.00	3.00				NS	3.00	3.00	3.00				NS	3.00	3.00	3.00			
	56	NS	3.00	3.00	3.00				NS	3.00	3.00	3.00				NS	3.00	3.00	3.00			
	60	NS	3.00	3.00	3.00				NS	3.00	3.00	3.00				NS	3.00	3.00	3.00			
	64	NS	3.00	3.00	3.00				NS	3.00	3.00	3.00				NS	3.00	3.00	3.00			
	100	NS	3.75	3.75	3.75	3.75			NS	3.75	3.75	3.75				NS	3.75	3.75	3.75			
	104	NS	3.75	3.75	3.75	3.75			NS	3.75	3.75	3.75				NS	3.75	3.75	3.75			
	108	NS	3.75	3.75	3.75	3.75			NS	3.75	3.75	3.75				NS	3.75	3.75	3.75			
	112	NS	3.75	3.75	3.75	3.75			NS	3.75	3.75	3.75				NS	3.75	3.75	3.75			
	116	NS	3.75	3.75	3.75	3.75			NS	3.75	3.75	3.75				NS	3.75	3.75	3.75			
	120	NS	3.75	3.75	3.75	3.75			NS	3.75	3.75	3.75				NS	3.75	3.75	3.75			
	124	NS	3.75	3.75	3.75	3.75			NS	3.75	3.75	3.75				NS	3.75	3.75	3.75			
	128	NS	3.75	3.75	3.75	3.75			NS	3.75	3.75	3.75				NS	3.75	3.75	3.75			
132	NS	3.75	3.75	3.75	3.75			NS	3.75	3.75	3.75				NS	3.75	3.75	3.75				
136	NS	3.75	3.75	3.75	3.75			NS	3.75	3.75	3.75				NS	3.75	3.75	3.75				
140	NS	3.75	3.75	3.75	3.75			NS	3.75	3.75	3.75				NS	3.75	3.75	3.75				
144	NS	3.75	3.75	3.75	3.75			NS	3.75	3.75	3.75				NS	3.75	3.75	3.75				
148	3.50	3.50	3.50	3.50				3.50	3.50	3.50	3.50				3.50	3.50	3.50	3.50				
153	3.50	3.50	3.50	3.50				3.50	3.50	3.50	3.50				3.50	3.50	3.50	3.50				
157	3.50	3.50	3.50	3.50				3.50	3.50	3.50	3.50				3.50	3.50	3.50	3.50				
161	3.50	3.50	3.50	3.50				3.50	3.50	3.50	3.50				3.50	3.50	3.50	3.50				
165	3.50	3.50	3.50	3.50				3.50	3.50	3.50	3.50				3.50	3.50	3.50	3.50				
38	3.75	3.75	3.75	3.75	3.75			3.75	3.75	3.75	3.75	3.75			3.75	3.75	3.75	3.75	3.75			
46	3.75	3.75	3.75	3.75	3.75	3.75			3.75	3.75	3.75	3.75	3.75			3.75	3.75	3.75	3.75	3.75		
54	NS	3.00	3.00	3.00	3.00	3.00			NS	3.00	3.00	3.00	3.00			NS	3.00	3.00	3.00	3.00		
62	NS	3.00	3.00	3.00	3.00	3.00			NS	3.00	3.00	3.00	3.00			NS	3.00	3.00	3.00	3.00		
102	NS	3.75	3.75	3.75	3.75	3.75			NS	3.75	3.75	3.75	3.75			NS	3.75	3.75	3.75	3.75		
110	NS	3.75	3.75	3.75	3.75	3.75			NS	3.75	3.75	3.75	3.75			NS	3.75	3.75	3.75	3.75		
118	NS	3.75	3.75	3.75	3.75	3.75			NS	3.75	3.75	3.75	3.75			NS	3.75	3.75	3.75	3.75		
126	NS	3.75	3.75	3.75	3.75	3.75			NS	3.75	3.75	3.75	3.75			NS	3.75	3.75	3.75	3.75		
134	NS	3.75	3.75	3.75	3.75	3.75			NS	3.75	3.75	3.75	3.75			NS	3.75	3.75	3.75	3.75		
142	NS	3.75	3.75	3.75	3.75	3.75			NS	3.75	3.75	3.75	3.75			NS	3.75	3.75	3.75	3.75		
151	3.50	3.50	3.50	3.50	3.50	3.50			3.50	3.50	3.50	3.50	3.50			3.50	3.50	3.50	3.50	3.50		
159	3.50	3.50	3.50	3.50	3.50	3.50			3.50	3.50	3.50	3.50	3.50			3.50	3.50	3.50	3.50	3.50		
42	3.75	3.75	3.75	3.75	3.75	3.75			3.75	3.75	3.75	3.75	3.75	3.75		3.75	3.75	3.75	3.75	3.75	3.75	
58	NS	3.00	3.00	3.00	3.00	3.00			NS	3.00	3.00	3.00	3.00	3.00		NS	3.00	3.00	3.00	3.00	3.00	
106	NS	3.75	3.75	3.75	3.75	3.75	3.75		NS	3.75	3.75	3.75	3.75	3.75		NS	3.75	3.75	3.75	3.75	3.75	
122	NS	3.75	3.75	3.75	3.75	3.75	3.75		NS	3.75	3.75	3.75	3.75	3.75		NS	3.75	3.75	3.75	3.75	3.75	
138	NS	3.75	3.75	3.75	3.75	3.75	3.75		NS	3.75	3.75	3.75	3.75	3.75		NS	3.75	3.75	3.75	3.75	3.75	
155	3.50	3.50	3.50	3.50	3.50	3.50	3.50		3.50	3.50	3.50	3.50	3.50	3.50		3.50	3.50	3.50	3.50	3.50	3.50	
50	NS	4.00	4.00	4.00	4.00	4.00	4.00	4.00	NS	3.50	3.50	3.50	3.50	3.50	3.50	3.50	NS	3.50	3.50	3.50	3.50	3.50
114	NS	4.00	4.00	4.00	4.00	4.00	4.00	4.00	NS	3.50	3.50	3.50	3.50	3.50	3.50	3.50	NS	3.50	3.50	3.50	3.50	3.50

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.

Note: 802.11a supports up to 20MHz, 802.11n supports up to 40MHz, 802.11ac/ax support up to 160MHz

FCC ID: BCGA2435	SAR EVALUATION REPORT	Reviewed by: Technical Manager
DUT Type: Tablet Device		APPENDIX H: Page 8 of 21

Below table is applicable in the following conditions:

-Simultaneous conditions with Licensed Bands Antenna 2a/2b active

-Simultaneous conditions with Inter-Band ULCA active

Mode	Channel	IEEE 802.11ax RU (Maximum in dBm) - Ant 5b (Tolerance +0/-3.00dB)																				
		SISO						MIMO CDD						MIMO SDM								
		26T	52T	106T	242T	484T	996T	996T*2	26T	52T	106T	242T	484T	996T	996T*2	26T	52T	106T	242T	484T	996T	996T*2
6 GHz WiFi (20MHz BW)	1	-4.75	-1.75	1.25	3.25				NS	-5.75	-2.75	-0.75				-6.00	-3.00	0.00	2.00			
	5	-4.75	-1.75	1.25	3.25				NS	-5.75	-2.75	-0.75				-6.00	-3.00	0.00	2.00			
	9-29	-4.75	-1.75	1.25	3.25				NS	-5.75	-2.75	-0.75				-6.00	-3.00	0.00	2.00			
	33-61	-4.75	-1.75	1.25	3.25				NS	-6.25	-3.25	-1.25				-6.25	-3.25	-0.25	1.75			
	65-85	-4.75	-1.75	1.25	3.25				NS	-6.50	-3.50	-1.50				-6.50	-3.50	-0.50	1.50			
	89	-4.75	-1.75	1.25	3.25				NS	-6.50	-3.50	-1.50				-6.50	-3.50	-0.50	1.50			
	93	-4.75	-1.75	1.25	3.25				NS	-6.50	-3.50	-1.50				-6.50	-3.50	-0.50	1.50			
	97-113	-5.00	-2.00	1.00	3.00				NS	-6.50	-3.50	-1.50				-6.75	-3.75	-0.75	1.25			
	117-181	-5.25	-2.25	0.75	2.75				NS	-6.25	-3.25	-1.25				-6.50	-3.50	-0.50	1.50			
	185	-5.25	-2.25	0.75	2.75				NS	-6.25	-3.25	-1.25				-6.50	-3.50	-0.50	1.50			
6 GHz WiFi (40MHz BW)	189-225	-4.75	-1.75	1.25	3.25				-7.75	-4.75	-1.75	0.25				-5.50	-2.50	0.50	2.50			
	229	-4.75	-1.75	1.25	3.25				-7.75	-4.75	-1.75	0.25				-5.50	-2.50	0.50	2.50			
	233	NS	NS	NS	NS				NS	NS	NS	NS				NS	NS	NS	NS			
	3	-4.75	-1.75	1.25	3.25	6.25			NS	-5.75	-2.75	-0.75	2.25			-6.00	-3.00	0.00	2.00	5.00		
	11	-4.75	-1.75	1.25	3.25	6.25			NS	-5.75	-2.75	-0.75	2.25			-6.00	-3.00	0.00	2.00	5.00		
	19-27	-4.75	-1.75	1.25	3.25	6.25			NS	-5.75	-2.75	-0.75	2.25			-6.00	-3.00	0.00	2.00	5.00		
	35-59	-4.75	-1.75	1.25	3.25	6.25			NS	-6.25	-3.25	-1.25	1.75			-6.25	-3.25	-0.25	1.75	4.75		
	67-75	-4.75	-1.75	1.25	3.25	6.25			NS	-6.50	-3.50	-1.50	1.50			-6.50	-3.50	-0.50	1.50	4.50		
	83	-4.75	-1.75	1.25	3.25	6.25			NS	-6.50	-3.50	-1.50	1.50			-6.50	-3.50	-0.50	1.50	4.50		
	91	-4.75	-1.75	1.25	3.25	6.25			NS	-6.50	-3.50	-1.50	1.50			-6.50	-3.50	-0.50	1.50	4.50		
6 GHz WiFi (80MHz BW)	99-107	-5.00	-2.00	1.00	3.00	6.00			NS	-6.50	-3.50	-1.50	1.50			-6.75	-3.75	-0.75	1.25	4.25		
	115	-5.25	-2.25	0.75	2.75	5.75			NS	-6.50	-3.50	-1.50	1.50			-6.75	-3.75	-0.75	1.25	4.25		
	123-179	-5.25	-2.25	0.75	2.75	5.75			NS	-6.25	-3.25	-1.25	1.75			-6.50	-3.50	-0.50	1.50	4.50		
	187	-5.25	-2.25	0.75	2.75	5.75			NS	-6.25	-3.25	-1.25	1.75			-6.50	-3.50	-0.50	1.50	4.50		
	195-219	-4.75	-1.75	1.25	3.25	6.25			-7.75	-4.75	-1.75	0.25	3.25			-5.50	-2.50	0.50	2.50	5.50		
	227	-4.75	-1.75	1.25	3.25	6.25			-7.75	-4.75	-1.75	0.25	3.25			-5.50	-2.50	0.50	2.50	5.50		
	7	-4.75	-1.75	1.25	3.25	6.25	9.00		NS	-5.75	-2.75	-0.75	2.25	5.25		-6.00	-3.00	0.00	2.00	5.00	8.00	
	23	-4.75	-1.75	1.25	3.25	6.25	9.00		NS	-5.75	-2.75	-0.75	2.25	5.25		-6.00	-3.00	0.00	2.00	5.00	8.00	
6 GHz WiFi (160MHz BW)	39-55	-4.75	-1.75	1.25	3.25	6.25	9.00		NS	-6.25	-3.25	-1.25	1.75	4.75		-6.25	-3.25	-0.25	1.75	4.75	7.75	
	71	-4.75	-1.75	1.25	3.25	6.25	9.00		NS	-6.50	-3.50	-1.50	1.50	4.50		-6.50	-3.50	-0.50	1.50	4.50	7.50	
	87	-4.75	-1.75	1.25	3.25	6.25	9.00		NS	-6.50	-3.50	-1.50	1.50	4.50		-6.50	-3.50	-0.50	1.50	4.50	7.50	
	103	-5.00	-2.00	1.00	3.00	6.00	8.25		NS	-6.50	-3.50	-1.50	1.50	4.50		-6.75	-3.75	-0.75	1.25	4.25	7.25	
	119	-5.25	-2.25	0.75	2.75	5.75	7.50		NS	-6.50	-3.50	-1.50	1.50	4.50		-6.75	-3.75	-0.75	1.25	4.25	7.25	
	135-167	-5.25	-2.25	0.75	2.75	5.75	7.50		NS	-6.25	-3.25	-1.25	1.75	4.75		-6.50	-3.50	-0.50	1.50	4.50	7.50	
	183	-5.25	-2.25	0.75	2.75	5.75	7.50		NS	-6.25	-3.25	-1.25	1.75	4.75		-6.50	-3.50	-0.50	1.50	4.50	7.50	
	199	-4.75	-1.75	1.25	3.25	6.25	7.75		-7.75	-4.75	-1.75	0.25	3.25	6.25		-5.50	-2.50	0.50	2.50	5.50	7.75	
6 GHz WiFi (160MHz BW)	215	-4.75	-1.75	1.25	3.25	6.25	7.75		-7.75	-4.75	-1.75	0.25	3.25	6.25		-5.50	-2.50	0.50	2.50	5.50	7.75	
	15	-4.75	-1.75	1.25	3.25	6.25	9.00	9.00	NS	-5.75	-2.75	-0.75	2.25	5.25	8.75	-6.00	-3.00	0.00	2.00	5.00	8.00	9.00
	47	-4.75	-1.75	1.25	3.25	6.25	9.00	9.00	NS	-6.25	-3.25	-1.25	1.75	4.75	8.75	-6.25	-3.25	-0.25	1.75	4.75	7.75	9.00
	79	-4.75	-1.75	1.25	3.25	6.25	9.00	9.00	NS	-6.50	-3.50	-1.50	1.50	4.50	8.50	-6.50	-3.50	-0.50	1.50	4.50	7.50	9.00
	111	-5.25	-2.25	0.75	2.75	5.75	8.25	8.25	NS	-6.50	-3.50	-1.50	1.50	4.50	8.25	-6.75	-3.75	-0.75	1.25	4.25	7.25	8.25
	143	-5.25	-2.25	0.75	2.75	5.75	7.50	7.50	NS	-6.25	-3.25	-1.25	1.75	4.75	7.50	-6.50	-3.50	-0.50	1.50	4.50	7.50	7.50
	175	-5.25	-2.25	0.75	2.75	5.75	7.50	7.50	NS	-6.25	-3.25	-1.25	1.75	4.75	7.50	-6.50	-3.50	-0.50	1.50	4.50	7.50	7.50
207	-4.75	-1.75	1.25	3.25	6.25	7.75	7.75	-7.75	-4.75	-1.75	0.25	3.25	6.25	7.75	-5.50	-2.50	0.50	2.50	5.50	7.75	7.75	

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.

FCC ID: BCGA2435	SAR EVALUATION REPORT	Reviewed by: Technical Manager
DUT Type: Tablet Device		APPENDIX H: Page 9 of 21

Below table is applicable in the following conditions:

-Simultaneous conditions with Licensed Bands Antenna 4b active

-Simultaneous conditions with Inter-Band ULCA active

Mode	Channel	IEEE 802.11ax RU (Maximum in dBm) - Ant 4a (Tolerance +0/-3.00dB)																				
		SISO						MIMO CDD						MIMO SDM								
		26T	52T	106T	242T	484T	996T	996T*2	26T	52T	106T	242T	484T	996T	996T*2	26T	52T	106T	242T	484T	996T	996T*2
6 GHz WiFi (20MHz BW)	1	-4.75	-1.75	1.25	3.25				NS	-5.75	-2.75	-0.75				-6.00	-3.00	0.00	2.00			
	5	-4.75	-1.75	1.25	3.25				NS	-5.75	-2.75	-0.75				-6.00	-3.00	0.00	2.00			
	9-29	-4.75	-1.75	1.25	3.25				NS	-5.75	-2.75	-0.75				-6.00	-3.00	0.00	2.00			
	33-61	-4.75	-1.75	1.25	3.25				NS	-6.25	-3.25	-1.25				-6.25	-3.25	-0.25	1.75			
	65-85	-4.75	-1.75	1.25	3.25				NS	-6.50	-3.50	-1.50				-6.50	-3.50	-0.50	1.50			
	89	-4.75	-1.75	1.25	3.25				NS	-6.50	-3.50	-1.50				-6.50	-3.50	-0.50	1.50			
	93	-4.75	-1.75	1.25	3.25				NS	-6.50	-3.50	-1.50				-6.50	-3.50	-0.50	1.50			
	97-113	-5.00	-2.00	1.00	3.00				NS	-6.50	-3.50	-1.50				-6.75	-3.75	-0.75	1.25			
	117-181	-5.25	-2.25	0.75	2.75				NS	-6.25	-3.25	-1.25				-6.50	-3.50	-0.50	1.50			
	185	-5.25	-2.25	0.75	2.75				NS	-6.25	-3.25	-1.25				-6.50	-3.50	-0.50	1.50			
	189-225	-4.75	-1.75	1.25	3.25				-7.75	-4.75	-1.75	0.25				-5.50	-2.50	0.50	2.50			
	229	-4.75	-1.75	1.25	3.25				-7.75	-4.75	-1.75	0.25				-5.50	-2.50	0.50	2.50			
233	NS	NS	NS	NS				NS	NS	NS	NS				NS	NS	NS	NS				
6 GHz WiFi (40MHz BW)	3	-4.75	-1.75	1.25	3.25	4.50			NS	-5.75	-2.75	-0.75	2.25			-6.00	-3.00	0.00	2.00	4.50		
	11	-4.75	-1.75	1.25	3.25	4.50			NS	-5.75	-2.75	-0.75	2.25			-6.00	-3.00	0.00	2.00	4.50		
	19-27	-4.75	-1.75	1.25	3.25	4.50			NS	-5.75	-2.75	-0.75	2.25			-6.00	-3.00	0.00	2.00	4.50		
	35-59	-4.75	-1.75	1.25	3.25	4.50			NS	-6.25	-3.25	-1.25	1.75			-6.25	-3.25	-0.25	1.75	4.50		
	67-75	-4.75	-1.75	1.25	3.25	4.50			NS	-6.50	-3.50	-1.50	1.50			-6.50	-3.50	-0.50	1.50	4.50		
	83	-4.75	-1.75	1.25	3.25	4.50			NS	-6.50	-3.50	-1.50	1.50			-6.50	-3.50	-0.50	1.50	4.50		
	91	-4.75	-1.75	1.25	3.25	4.50			NS	-6.50	-3.50	-1.50	1.50			-6.50	-3.50	-0.50	1.50	4.50		
	99-107	-5.00	-2.00	1.00	3.00	3.50			NS	-6.50	-3.50	-1.50	1.50			-6.75	-3.75	-0.75	1.25	3.50		
	115	-5.25	-2.25	0.75	2.75	3.50			NS	-6.50	-3.50	-1.50	1.50			-6.75	-3.75	-0.75	1.25	3.50		
	123-179	-5.25	-2.25	0.75	2.75	5.50			NS	-6.25	-3.25	-1.25	1.75			-6.50	-3.50	-0.50	1.50	4.50		
	187	-5.25	-2.25	0.75	2.75	5.75			NS	-6.25	-3.25	-1.25	1.75			-6.50	-3.50	-0.50	1.50	4.50		
	195-219	-4.75	-1.75	1.25	3.25	6.25			-7.75	-4.75	-1.75	0.25	3.25			-5.50	-2.50	0.50	2.50	5.50		
227	-4.75	-1.75	1.25	3.25	6.25			-7.75	-4.75	-1.75	0.25	3.25			-5.50	-2.50	0.50	2.50	5.50			
6 GHz WiFi (80MHz BW)	7	-4.75	-1.75	1.25	3.25	4.50	4.50		NS	-5.75	-2.75	-0.75	2.25	4.50		-6.00	-3.00	0.00	2.00	4.50	4.50	
	23	-4.75	-1.75	1.25	3.25	4.50	4.50		NS	-5.75	-2.75	-0.75	2.25	4.50		-6.00	-3.00	0.00	2.00	4.50	4.50	
	39-55	-4.75	-1.75	1.25	3.25	4.50	4.50		NS	-6.25	-3.25	-1.25	1.75	4.50		-6.25	-3.25	-0.25	1.75	4.50	4.50	
	71	-4.75	-1.75	1.25	3.25	4.50	4.50		NS	-6.50	-3.50	-1.50	1.50	4.50		-6.50	-3.50	-0.50	1.50	4.50	4.50	
	87	-4.75	-1.75	1.25	3.25	4.50	4.50		NS	-6.50	-3.50	-1.50	1.50	4.50		-6.50	-3.50	-0.50	1.50	4.50	4.50	
	103	-5.00	-2.00	1.00	3.00	3.50	3.50		NS	-6.50	-3.50	-1.50	1.50	3.50		-6.75	-3.75	-0.75	1.25	3.50	3.50	
	119	-5.25	-2.25	0.75	2.75	5.50	5.50		NS	-6.50	-3.50	-1.50	1.50	4.50		-6.75	-3.75	-0.75	1.25	4.25	5.50	
	135-167	-5.25	-2.25	0.75	2.75	5.50	5.50		NS	-6.25	-3.25	-1.25	1.75	4.75		-6.50	-3.50	-0.50	1.50	4.50	5.50	
	183	-5.25	-2.25	0.75	2.75	5.50	5.50		NS	-6.25	-3.25	-1.25	1.75	4.75		-6.50	-3.50	-0.50	1.50	4.50	5.50	
	199	-4.75	-1.75	1.25	3.25	6.25	6.50		-7.75	-4.75	-1.75	0.25	3.25	6.25		-5.50	-2.50	0.50	2.50	5.50	6.50	
	215	-4.75	-1.75	1.25	3.25	6.25	6.50		-7.75	-4.75	-1.75	0.25	3.25	6.25		-5.50	-2.50	0.50	2.50	5.50	6.50	
	6 GHz WiFi (160MHz BW)	15	-4.75	-1.75	1.25	3.25	4.50	4.50	4.50	NS	-5.75	-2.75	-0.75	2.25	4.50	4.50	-6.00	-3.00	0.00	2.00	4.50	4.50
47		-4.75	-1.75	1.25	3.25	4.50	4.50	4.50	NS	-6.25	-3.25	-1.25	1.75	4.50	4.50	-6.25	-3.25	-0.25	1.75	4.50	4.50	4.50
79		-4.75	-1.75	1.25	3.25	4.50	4.50	4.50	NS	-6.50	-3.50	-1.50	1.50	4.50	4.50	-6.50	-3.50	-0.50	1.50	4.50	4.50	4.50
111		-5.25	-2.25	0.75	2.75	3.50	3.50	3.50	NS	-6.50	-3.50	-1.50	1.50	3.50	3.50	-6.75	-3.75	-0.75	1.25	3.50	3.50	3.50
143		-5.25	-2.25	0.75	2.75	5.50	5.50	5.50	NS	-6.25	-3.25	-1.25	1.75	4.75	5.50	-6.50	-3.50	-0.50	1.50	4.50	5.50	5.50
175		-5.25	-2.25	0.75	2.75	5.50	5.50	5.50	NS	-6.25	-3.25	-1.25	1.75	4.75	5.50	-6.50	-3.50	-0.50	1.50	4.50	5.50	5.50
207		-4.75	-1.75	1.25	3.25	6.25	6.50	6.50	-7.75	-4.75	-1.75	0.25	3.25	6.25	6.50	-5.50	-2.50	0.50	2.50	5.50	6.50	6.50

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.

FCC ID: BCGA2435	SAR EVALUATION REPORT	Reviewed by: Technical Manager
DUT Type: Tablet Device		APPENDIX H: Page 10 of 21

H.3 IEEE 802.11ax Measured Powers

Table H-1
Maximum 2.4 GHz 802.11ax RU Time-Averaged WLAN Output Power – Ant 4a

Freq [MHz]	Channel	Tones	RU Index	Avg Conducted Powers (dBm)	Freq [MHz]	Channel	Tones	RU Index	Avg Conducted Powers (dBm)
2412	1	26T	0	10.93	2412	1	52T	37	11.36
			4	11.04				38	11.42
			8	11.10				40	11.61
2437	6	26T	0	11.07	2437	6	52T	37	11.64
			4	10.88				38	11.49
			8	11.01				40	11.39
2462	11	26T	0	11.11	2462	11	52T	37	11.50
			4	10.96				38	11.59
			8	10.99				40	11.56
Freq [MHz]	Channel	Tones	RU Index	Avg Conducted Powers (dBm)					
2412	1	106T	53	11.52	Freq [MHz]	Channel	Tones	RU Index	Avg Conducted Powers (dBm)
			54	11.45					
2437	6	106T	53	11.60	2437	6	242T	61	11.54
			54	11.54					
2462	11	106T	53	11.53					
			54	11.58					

Table H-2
Maximum 2.4 GHz 802.11ax RU Time-Averaged WLAN Output Power – Ant 2a

Freq [MHz]	Channel	Tones	RU Index	Avg Conducted Powers (dBm)	Freq [MHz]	Channel	Tones	RU Index	Avg Conducted Powers (dBm)
2412	1	26T	0	10.95	2412	1	52T	37	12.08
			4	10.91				38	12.02
			8	11.01				40	12.12
2437	6	26T	0	11.02	2437	6	52T	37	12.10
			4	10.98				38	11.96
			8	11.03				40	12.06
2462	11	26T	0	10.99	2462	11	52T	37	12.11
			4	11.05				38	11.95
			8	11.07				40	12.01
Freq [MHz]	Channel	Tones	RU Index	Avg Conducted Powers (dBm)					
2412	1	106T	53	12.09	Freq [MHz]	Channel	Tones	RU Index	Avg Conducted Powers (dBm)
			54	11.92					
2437	6	106T	53	11.98	2412	1	242T	61	12.07
			54	11.90	2437	6	242T	61	11.95
2462	11	106T	53	11.93	2462	11	242T	61	11.94
			54	12.01					

Table H-3
Maximum 5 GHz 802.11ax RU Time-Averaged WLAN Output Power – Ant 5b

20MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					0	4	8
20MHz BW	1	5180	36	26T	9.40	9.46	9.42
		5200	40	26T	9.50	9.37	9.52
		5220	44	26T	9.37	9.49	9.56
		5240	48	26T	9.44	9.51	9.55
	2A	5745	149	26T	9.64	9.37	9.39
		5785	157	26T	9.53	9.47	9.46
		5825	165	26T	9.41	9.43	9.40
	3	5180	36	26T	9.40	9.46	9.42
		5200	40	26T	9.50	9.37	9.52
		5220	44	26T	9.37	9.49	9.56
		5240	48	26T	9.44	9.51	9.55
20MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					53	54	N/A
20MHz BW	1	5180	36	106T	14.44	14.53	
		5200	40	106T	15.52	15.56	
		5220	44	106T	15.43	15.44	
		5240	48	106T	15.58	15.47	
	2A	5260	52	106T	15.61	15.53	
		5280	56	106T	15.55	15.42	
		5300	60	106T	15.59	15.54	
		5320	64	106T	15.49	15.57	
	2C	5500	100	106T	14.08	14.03	
		5600	120	106T	14.01	13.98	
		5620	124	106T	13.89	13.97	
		5720	144	106T	13.95	14.10	
20MHz BW	1	5180	36	242T	14.45		
		5200	40	242T	15.56		
		5220	44	242T	15.52		
		5240	48	242T	15.49		
	2A	5260	52	242T	15.58		
		5280	56	242T	15.44		
		5300	60	242T	15.47		
		5320	64	242T	15.53		
	2C	5500	100	242T	14.06		
		5600	120	242T	14.07		
		5620	124	242T	14.01		
		5720	144	242T	13.94		
40MHz BW	1	5190	38	52T	11.45	11.52	11.71
		5230	46	52T	12.36	12.58	12.61
		5270	54	52T	12.44	12.73	12.53
		5310	62	52T	12.58	12.56	12.56
	2A	5510	102	52T	10.62	10.38	10.41
		5590	118	52T	12.38	12.41	12.69
		5630	126	52T	12.52	12.37	12.54
		5710	142	52T	12.55	12.58	12.49
	2C	5755	151	52T	12.47	12.61	12.66
		5795	159	52T	12.64	12.44	12.57
	3	5190	38	242T	11.55	11.48	
		5230	46	242T	15.57	15.52	
		5270	54	242T	15.41	15.56	
		5310	62	242T	12.55	12.64	
40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					53	54	56
40MHz BW	1	5190	38	106T	11.44	11.65	11.48
		5230	46	106T	15.52	15.46	15.56
		5270	54	106T	15.55	15.43	15.38
		5310	62	106T	12.60	12.51	12.41
	2A	5510	102	106T	10.51	10.57	10.44
		5590	118	106T	14.05	13.94	14.04
		5670	126	106T	14.02	14.06	14.18
		5710	142	106T	13.93	14.08	14.02
	2C	5755	151	106T	14.56	14.38	14.53
		5795	159	106T	14.58	14.62	14.50
	3	5190	38	242T	11.55	11.48	
		5230	46	242T	15.57	15.52	
		5270	54	242T	15.41	15.56	
		5310	62	242T	12.55	12.64	
40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					61	62	N/A
40MHz BW	1	5190	38	242T	11.55	11.48	
		5230	46	242T	15.57	15.52	
		5270	54	242T	15.41	15.56	
		5310	62	242T	12.55	12.64	
	2A	5510	102	242T	10.47	10.45	
		5590	118	242T	13.99	14.06	
		5670	126	242T	13.92	14.03	
		5710	142	242T	12.29	12.33	
	2C	5755	151	242T	14.64	14.56	
		5795	159	242T	14.44	14.50	
	3	5190	38	242T	11.55	11.48	
		5230	46	242T	15.57	15.52	
		5270	54	242T	15.41	15.56	
		5310	62	242T	12.55	12.64	

40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					65	N/A	N/A
	1	5190	38	484T	11.45		
		5230	46	484T	15.61		
		5270	54	484T	15.53		
	2A	5310	62	484T	12.44		
		5510	102	484T	10.59		
		5590	118	484T	14.02		
	2C	5630	126	484T	14.08		
		5710	142	484T	13.98		
		5755	151	484T	14.56		
	3	5795	159	484T	14.54		
80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					37	44	52
	1	5210	42	52T	10.60	10.51	10.54
	2A	5290	58	52T	11.94	11.96	12.03
	2C	5530	106	52T	10.41	10.52	10.55
		5610	122	52T	12.43	12.44	12.62
		5690	138	52T	12.49	12.42	12.57
	3	5775	155	52T	12.45	12.50	12.46
80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					53	56	60
	1	5210	42	106T	10.56	10.43	10.48
	2A	5290	58	106T	12.11	12.00	12.07
	2C	5530	106	106T	10.45	10.64	10.53
		5610	122	106T	13.91	13.84	14.08
		5690	138	106T	13.87	14.04	13.96
	3	5775	155	106T	14.52	14.40	14.46
80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					61	62	64
	1	5210	42	242T	10.57	10.52	10.56
	2A	5290	58	242T	11.97	12.06	11.93
	2C	5530	106	242T	10.51	10.41	10.53
		5610	122	242T	13.92	14.07	14.08
		5690	138	242T	14.56	14.59	14.48
	3	5775	155	242T	14.89	14.95	15.04
80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					67	N/A	N/A
	1	5210	42	996T	10.58		
	2A	5290	58	996T	11.89		
	2C	5530	106	996T	11.44		
		5610	122	996T	13.95		
		5690	138	996T	13.91		
	3	5775	155	996T	14.60		
160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					53	56	60
	1	5250	50	106T	7.08	7.02	6.94
	2C	5570	114	106T	5.53	5.43	5.25
160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					65	66	N/A
	1	5250	50	484T	6.97	7.25	
	2C	5570	114	484T	5.51	5.67	
160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					67	N/A	N/A
	1	5250	50	996T	7.11		
	2C	5570	114	996T	5.40		

FCC ID: BCGA2435	SAR EVALUATION REPORT	Reviewed by: Technical Manager
DUT Type: Tablet Device		APPENDIX H: Page 14 of 21

Table H-4
Maximum 5 GHz 802.11ax RU Time-Averaged WLAN Output Power – Ant 4a

20MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					0	4	8
20MHz BW	1	5180	36	26T	8.21	8.17	8.26
		5200	40	26T	8.32	8.24	8.27
		5220	44	26T	8.26	8.28	8.31
		5240	48	26T	8.22	8.19	8.21
	2A	5260	52	26T	8.01	8.07	8.10
		5280	56	26T	8.02	7.98	7.94
		5300	60	26T	7.92	8.01	8.05
		5320	64	26T			
	2C	5500	100	26T			
		5600	120	26T			
		5580	124	26T			
		5720	144	26T			
20MHz BW	3	5745	149	26T			
		5785	157	26T			
		5825	165	26T			
20MHz BW	1	5180	36	106T	8.33	8.21	
		5200	40	106T	8.31	8.26	
		5220	44	106T	8.27	8.29	
		5240	48	106T	8.32	8.23	
	2A	5260	52	106T	7.54	7.60	
		5280	56	106T	7.55	7.42	
		5300	60	106T	7.51	7.41	
		5320	64	106T	7.58	7.59	
	2C	5500	100	106T	8.26	8.31	
		5600	120	106T	8.32	8.28	
		5620	124	106T	8.22	8.27	
		5720	144	106T	8.24	8.19	
20MHz BW	3	5745	149	106T	8.04	8.01	
		5785	157	106T	8.06	7.92	
		5825	165	106T	8.10	7.91	
40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					0	8	17
40MHz BW	1	5190	38	26T	8.26	8.33	8.29
		5230	46	26T	8.30	8.18	8.21
		5270	54	26T	7.93	8.01	8.04
		5795	159	26T	8.11	8.03	7.97
40MHz BW	2A	5310	62	26T			
		5510	102	26T			
		5590	118	26T			
		5630	126	26T			
40MHz BW	2C	5710	142	26T			
		5755	151	26T			
		5795	159	26T			
40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					53	54	56
40MHz BW	1	5190	38	106T	8.21	8.40	8.32
		5230	46	106T	8.27	8.19	8.23
		5270	54	106T	7.46	7.42	7.55
		5310	62	106T	7.49	7.60	7.52
40MHz BW	2A	5510	102	106T	8.34	8.22	8.29
		5590	118	106T	8.19	8.29	8.23
		5670	126	106T	8.22	8.14	8.20
		5710	142	106T	8.17	8.25	8.36
40MHz BW	2C	5755	151	106T	8.03	7.92	7.97
		5795	159	106T	8.09	8.05	7.94
40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					61	62	N/A
40MHz BW	1	5190	38	242T	8.29	8.38	
		5230	46	242T	8.21	8.24	
		5270	54	242T	7.42	7.50	
		5310	62	242T	7.54	7.61	
40MHz BW	2A	5510	102	242T	8.30	8.22	
		5590	118	242T	8.23	8.35	
		5630	126	242T	8.29	8.33	
		5670	134	242T	8.18	8.27	
40MHz BW	2C	5755	151	242T	7.94	8.03	
		5795	159	242T	8.02	8.07	

FCC ID: BCGA2435	SAR EVALUATION REPORT	Reviewed by: Technical Manager
DUT Type: Tablet Device		APPENDIX H: Page 15 of 21

40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					65	N/A	N/A
	1	5190	38	484T	8.29		
		5230	46	484T	8.32		
		5270	54	484T	7.41		
	2A	5310	62	484T	7.55		
		5510	102	484T	8.24		
		5590	118	484T	8.26		
	2C	5630	126	484T	8.31		
		5710	142	484T	8.28		
		5755	151	484T	8.07		
	3	5795	159	484T	7.96		
80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					37	44	52
	1	5210	42	52T	8.29	8.21	8.34
	2A	5290	58	52T	7.41	7.55	7.47
		5530	106	52T	8.22	8.34	8.24
		5610	122	52T	8.19	8.23	8.26
	2C	5690	138	52T	8.21	8.22	8.17
		5775	155	52T	8.02	7.94	8.06
80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					61	62	64
	1	5210	42	242T	8.32	8.18	8.29
	2A	5290	58	242T	7.48	7.59	7.51
		5530	106	242T	8.27	8.23	8.31
		5610	122	242T	8.35	8.31	8.24
	2C	5690	138	242T	8.33	8.36	8.28
		5775	155	242T	7.94	7.99	8.02
80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					67	N/A	N/A
	1	5210	42	996T	8.19		
	2A	5290	58	996T	8.30		
		5530	106	996T	8.23		
		5610	122	996T	8.27		
	2C	5690	138	996T	8.22		
		5775	155	996T	7.95		
160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					53	56	60
	1	5250	50	106T	7.17	7.14	7.07
	2C	5570	114	106T	5.56	5.35	5.27
160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					65	66	N/A
	1	5250	50	484T	6.88	7.02	
	2C	5570	114	484T	5.59	5.49	
160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					67	N/A	N/A
	1	5250	50	996T	6.95		
	2C	5570	114	996T	5.47		

FCC ID: BCGA2435	SAR EVALUATION REPORT	Reviewed by: Technical Manager
DUT Type: Tablet Device		APPENDIX H: Page 16 of 21

Table H-5
Maximum 6 GHz 802.11ax RU Time-Averaged WLAN Output Power – Ant 5b

20MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)			20MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index								RU Index		
					0	4	8						37	39	40
20MHz BW	5	5955	1	26T	-6.06	-5.56	-6.02	20MHz BW	5	5955	1	52T	-2.86	-2.55	-2.85
		6175	45	26T	-5.80	-5.36	-5.90			6175	45	52T	-2.61	-2.40	-2.72
		6415	93	26T	-5.96	-5.40	-5.82			6415	93	52T	-3.07	-2.69	-2.96
	6	6435	97	26T	-6.33	-5.78	-6.17		6	6435	97	52T	-3.16	-2.70	-3.02
		6475	105	26T	-6.00	-5.50	-5.95			6475	105	52T	-3.11	-2.79	-3.02
		6515	113	26T	-6.18	-5.79	-6.28			6515	113	52T	-2.94	-2.66	-2.95
	7	6535	117	26T	-6.32	-5.93	-6.46		7	6535	117	52T	-3.35	-3.16	-3.46
		6695	149	26T	-6.48	-6.07	-6.60			6695	149	52T	-3.45	-3.28	-3.66
		6875	185	26T	-6.11	-5.77	-6.25			6875	185	52T	-3.37	-3.05	-3.32
	8	6895	189	26T	-5.71	-5.35	-5.85		8	6895	189	52T	-2.68	-2.50	-2.85
		6995	209	26T	-5.65	-5.50	-6.34			6995	209	52T	-2.70	-2.85	-3.29
		7115	233	26T	NS	NS	NS			7115	233	52T	NS	NS	NS
20MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)			20MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index								RU Index		
					53	54	N/A						61	N/A	N/A
20MHz BW	5	5955	1	106T	0.49	0.48		20MHz BW	5	5955	1	242T	2.21		
		6175	45	106T	0.33	0.22				6175	45	242T	2.12		
		6415	93	106T	-0.73	-0.63				6415	93	242T	2.02		
	6	6435	97	106T	-0.55	-0.48			6	6435	97	242T	2.01		
		6475	105	106T	-0.33	-0.24				6475	105	242T	1.99		
		6515	113	106T	0.33	0.34				6515	113	242T	1.94		
	7	6535	117	106T	-0.23	-0.58			7	6535	117	242T	2.17		
		6695	149	106T	-0.58	-0.65				6695	149	242T	2.16		
		6875	185	106T	-0.55	-0.56				6875	185	242T	1.97		
	8	6895	189	106T	0.07	-0.03			8	6895	189	242T	2.03		
		6995	209	106T	0.41	-0.02				6995	209	242T	1.93		
		7115	233	106T	NS	NS				7115	233	242T	NS		
40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)			40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index								RU Index		
					0	8	17						37	40	44
40MHz BW	5	5965	3	26T	-6.22	-5.48	-6.16	40MHz BW	5	5965	3	52T	-3.01	-2.69	-2.89
		6165	43	26T	-5.82	-5.20	-6.03			6165	43	52T	-2.94	-2.55	-2.78
		6405	91	26T	-6.49	-5.58	-6.12			6405	91	52T	-2.86	-2.45	-2.63
	6	6445	99	26T	-6.43	-5.52	-6.09		6	6445	99	52T	-3.31	-3.05	-3.23
		6485	107	26T	-6.27	-5.48	-6.01			6485	107	52T	-3.26	-2.94	-3.19
		6525	115	26T	-6.29	-5.55	-6.11			6525	115	52T	-3.38	-3.16	-3.30
	7	6565	123	26T	-6.44	-5.93	-6.26		7	6565	123	52T	-3.40	-3.23	-3.31
		6725	155	26T	-6.34	-5.88	-6.35			6725	155	52T	-3.34	-3.18	-3.42
		6845	179	26T	-6.40	-5.92	-6.31			6845	179	52T	-3.45	-3.29	-3.32
	8	6885	187	26T	-6.60	-6.31	-6.52		8	6885	187	52T	-3.41	-3.19	-3.29
		7005	211	26T	-5.73	-5.30	-5.61			7005	211	52T	-2.90	-2.72	-2.79
		7085	227	26T	-5.81	-5.46	-5.73			7085	227	52T	-2.92	-2.74	-2.86
40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)			40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index								RU Index		
					53	54	56						61	62	N/A
40MHz BW	5	5965	3	106T	0.36	0.16	0.23	40MHz BW	5	5965	3	242T	2.27	2.10	
		6165	43	106T	0.40	0.02	0.13			6165	43	242T	2.15	2.20	
		6405	91	106T	0.13	0.40	0.02			6405	91	242T	2.23	2.08	
	6	6445	99	106T	0.23	-0.17	-0.02		6	6445	99	242T	2.18	2.26	
		6485	107	106T	0.29	0.03	0.11			6485	107	242T	2.23	2.16	
		6525	115	106T	-0.36	-0.50	-0.30			6525	115	242T	2.16	2.22	
	7	6565	123	106T	-0.40	-0.56	-0.43		7	6565	123	242T	2.10	2.13	
		6725	155	106T	-0.31	-0.44	-0.22			6725	155	242T	1.97	2.02	
		6845	179	106T	-0.29	-0.39	-0.24			6845	179	242T	2.09	2.21	
	8	6885	187	106T	-0.31	-0.46	-0.26		8	6885	187	242T	2.12	2.05	
		7005	211	106T	0.34	0.08	0.28			7005	211	242T	2.11	2.19	
		7085	227	106T	0.34	0.10	0.21			7085	227	242T	2.04	1.98	

FCC ID: BCGA2435	SAR EVALUATION REPORT	Reviewed by: Technical Manager
DUT Type: Tablet Device		APPENDIX H: Page 17 of 21

40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					65	N/A	N/A
5	5	5965	3	484T	5.23		
		6165	43	484T	5.22		
		6405	91	484T	5.29		
	6	6445	99	484T	4.99		
		6485	107	484T	5.02		
		6525	115	484T	4.78		
7	7	6565	123	484T	4.84		
		6725	155	484T	4.62		
		6845	179	484T	4.60		
	8	6885	187	484T	4.63		
		7005	211	484T	5.29		
		7085	227	484T	5.25		
80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					37	44	52
5	5	5985	7	52T	-2.73	-2.61	-2.69
		6145	39	52T	-2.80	-2.66	-2.78
		6385	87	52T	-2.76	-2.64	-2.71
	6	6465	103	52T	-3.12	-2.88	-3.01
		6545	119	52T	-3.34	-3.21	-3.31
		6705	151	52T	-3.43	-3.28	-3.36
7	7	6865	183	52T	-2.79	-2.71	-2.81
		6945	199	52T	-2.79	-2.71	-2.81
		7025	215	52T	-2.96	-2.79	-2.84
80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					61	62	64
5	5	5985	7	242T	2.43	2.76	2.16
		6145	39	242T	2.38	2.61	2.31
		6385	87	242T	2.24	2.54	2.28
	6	6465	103	242T	2.18	2.36	2.25
		6545	119	242T	2.10	2.21	2.16
		6705	151	242T	2.19	2.40	2.23
7	7	6865	183	242T	2.24	2.55	2.16
		6945	199	242T	2.30	2.05	2.26
		7025	215	242T	2.15	1.98	2.21
80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					61	62	64
5	5	5985	7	996T	8.21		
		6145	39	996T	8.13		
		6385	87	996T	8.18		
	6	6465	103	996T	7.92		
		6545	119	996T	7.77		
		6705	151	996T	7.80		
7	7	6865	183	996T	7.74		
		6945	199	996T	8.28		
		7025	215	996T	8.31		
160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					37	44	52
5	5	6025	15	52T	-2.84	-2.69	-2.81
		6185	47	52T	-2.89	-2.71	-2.78
		6345	79	52T	-2.79	-2.65	-2.77
	6	6505	111	52T	-3.27	-3.07	-3.19
		6665	143	52T	-3.28	-3.11	-3.23
		6825	175	52T	-3.36	-3.20	-3.31
7	7	6985	207	52T	-2.87	-2.72	-2.79
160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					61	62	64
5	5	6025	15	242T	2.34	2.48	2.29
		6185	47	242T	2.37	2.53	2.31
		6345	79	242T	2.39	2.44	2.36
	6	6505	111	242T	2.26	2.30	2.21
		6665	143	242T	2.23	2.34	2.27
		6825	175	242T	2.18	2.29	2.22
7	7	6985	207	242T	2.06	2.15	1.97
160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					65	66	N/A
5	5	6025	15	106T	0.32	0.17	0.29
		6185	47	106T	0.33	0.15	0.23
		6345	79	106T	0.28	0.11	0.20
	6	6505	111	106T	-0.33	-0.13	-0.26
		6665	143	106T	-0.29	-0.04	-0.24
		6825	175	106T	-0.32	-0.15	-0.31
7	7	6985	207	106T	0.34	0.19	0.32
80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					53	56	60
5	5	5985	7	106T	0.26	0.10	0.19
		6145	39	106T	0.36	0.16	0.31
		6385	87	106T	0.37	0.15	0.21
	6	6465	103	106T	0.11	-0.12	-0.03
		6545	119	106T	-0.35	-0.26	-0.31
		6705	151	106T	-0.40	-0.18	-0.29
7	7	6865	183	106T	-0.37	-0.21	-0.33
		6945	199	106T	0.37	0.18	0.31
		7025	215	106T	0.39	0.11	0.24
80MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					65	66	N/A
5	5	5985	7	484T	5.21	5.28	
		6145	39	484T	5.26	5.31	
		6385	87	484T	5.18	5.25	
	6	6465	103	484T	5.10	5.03	
		6545	119	484T	4.82	4.86	
		6705	151	484T	4.77	4.85	
7	7	6865	183	484T	4.79	4.87	
		6945	199	484T	5.32	5.28	
		7025	215	484T	5.36	5.24	
160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					65	66	N/A
5	5	6025	15	484T	5.15	5.16	
		6185	47	484T	5.26	5.29	
		6345	79	484T	5.37	5.30	
	6	6505	111	484T	4.81	4.77	
		6665	143	484T	4.78	4.74	
		6825	175	484T	4.82	4.78	
7	7	6985	207	484T	5.33	5.29	

FCC ID: BCGA2435	SAR EVALUATION REPORT	Reviewed by: Technical Manager
DUT Type: Tablet Device		APPENDIX H: Page 18 of 21

160MHz BW 1st	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					67(L)	N/A	N/A
5		6025	15	996T	8.22		
		6185	47	996T	8.24		
		6345	79	996T	8.25		
6		6505	111	996T	7.72		
		6665	143	996T	7.78		
7		6825	175	996T	7.80		
		6985	207	996T	8.16		
160MHz BW 2nd	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					67(H)	N/A	N/A
5		6025	15	996T	11.60		
		6185	47	996T	11.85		
		6345	79	996T	10.94		
6		6505	111	996T	11.37		
		6665	143	996T	10.62		
7		6825	175	996T	10.57		
		6985	207	996T	10.87		

Table H-6
Maximum 6 GHz 802.11ax RU Time-Averaged WLAN Output Power – Ant 4a

20MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					0	4	8
5		5955	1	26T	-5.81	-5.69	-5.77
		6175	45	26T	-5.78	-5.61	-5.73
		6415	93	26T	-5.85	-5.71	-5.91
6		6435	97	26T	-6.12	-5.88	-6.03
		6475	105	26T	-6.01	-5.71	-5.92
		6515	113	26T	-6.04	-5.87	-5.98
7		6535	117	26T	-6.37	-6.16	-6.21
		6695	149	26T	-6.43	-6.28	-6.35
		6875	185	26T	-6.36	-6.21	-6.31
8		6895	189	26T	-5.91	-5.71	-5.90
		6995	209	26T	-5.85	-5.59	-5.81
		7115	233	26T	NS	NS	NS
20MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					53	54	N/A
5		5955	1	106T	0.06	0.13	
		6175	45	106T	0.20	0.28	
		6415	93	106T	0.12	0.06	
6		6435	97	106T	0.20	0.11	
		6475	105	106T	0.01	-0.05	
		6515	113	106T	0.16	0.03	
7		6535	117	106T	-0.24	-0.30	
		6695	149	106T	-1.15	-1.24	
		6875	185	106T	-0.33	-0.34	
8		6895	189	106T	0.02	0.01	
		6995	209	106T	0.17	-0.01	
		7115	233	106T	NS	NS	
20MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					37	39	40
5		5955	1	52T	-2.81	-2.63	-2.78
		6175	45	52T	-2.89	-2.70	-2.79
		6415	93	52T	-2.92	-2.62	-2.85
6		6435	97	52T	-3.21	-2.87	-3.09
		6475	105	52T	-3.16	-2.91	-3.11
		6515	113	52T	-3.09	-2.82	-3.02
7		6535	117	52T	-3.34	-3.22	-3.36
		6695	149	52T	-3.40	-3.18	-3.31
		6875	185	52T	-3.43	-3.28	-3.39
8		6895	189	52T	-2.96	-2.76	-2.89
		6995	209	52T	-2.91	-2.79	-2.85
		7115	233	52T	NS	NS	NS
40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					8	17	
5		5965	3	26T	-5.79	-5.60	-6.00
		6165	43	26T	-5.88	-5.13	-6.18
		6405	91	26T	-5.75	-5.16	-5.58
6		6445	99	26T	-6.09	-5.48	-6.29
		6485	107	26T	-6.03	-5.51	-6.39
		6525	115	26T	-6.53	-5.92	-6.78
7		6565	123	26T	-6.47	-5.95	-6.75
		6725	155	26T	-6.48	-5.93	-6.80
		6845	179	26T	-6.24	-5.64	-6.16
8		6885	187	26T	-6.63	-5.99	-6.67
		7005	211	26T	-5.86	-5.41	-6.40
		7085	227	26T	-5.54	-5.29	-6.69
40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					53	54	56
5		5965	3	106T	-0.09	0.44	0.23
		6165	43	106T	0.06	0.63	0.19
		6405	91	106T	-0.25	0.25	-0.42
6		6445	99	106T	-0.35	0.10	-0.66
		6485	107	106T	-0.18	0.18	-0.50
		6525	115	106T	-0.46	-0.10	-0.74
7		6565	123	106T	-0.36	0.00	-0.52
		6725	155	106T	-0.70	-0.21	-0.90
		6845	179	106T	-0.45	0.01	-0.42
8		6885	187	106T	-0.30	0.22	-0.33
		7005	211	106T	0.30	0.62	-0.21
		7085	227	106T	0.49	0.72	-0.33
40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					61	62	N/A
5		5965	3	242T	2.67	2.61	
		6165	43	242T	2.56	2.59	
		6405	91	242T	2.51	2.60	
6		6445	99	242T	2.49	2.55	
		6485	107	242T	2.44	2.46	
		6525	115	242T	2.39	2.27	
7		6565	123	242T	2.45	2.41	
		6725	155	242T	2.48	2.62	
		6845	179	242T	2.58	2.74	
8		6885	187	242T	2.64	2.71	
		7005	211	242T	3.09	3.02	
		7085	227	242T	3.19	3.16	

FCC ID: BCGA2435	SAR EVALUATION REPORT	Reviewed by: Technical Manager
DUT Type: Tablet Device		APPENDIX H: Page 19 of 21

40MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					65	N/A	N/A
	5	5965	3	484T	5.36		
80MHz BW	5	6165	43	484T	5.26		
		6405	91	484T	5.15		
		6445	99	484T	5.05		
	6	6485	107	484T	5.12		
80MHz BW	6	6525	115	484T	4.68		
		6565	123	484T	4.70		
		6725	155	484T	4.73		
	7	6845	179	484T	4.83		
80MHz BW	7	6885	187	484T	4.87		
		7005	211	484T	5.29		
		7085	227	484T	5.36		
80MHz BW	8						
80MHz BW	5	5985	7	52T	-3.50	-2.21	-3.01
		6145	39	52T	-3.25	-1.93	-2.78
		6385	87	52T	-2.60	-1.90	-3.21
80MHz BW	6	6465	103	52T	-2.78	-2.20	-3.62
		6545	119	52T	-3.08	-2.40	-3.80
		6705	151	52T	-3.30	-2.66	-4.04
	7	6865	183	52T	-3.52	-2.55	-3.60
80MHz BW	8	6945	199	52T	-2.93	-2.10	-3.39
		7025	215	52T	-2.64	-2.05	-3.66
80MHz BW	5	5985	7	242T	2.80	3.23	2.67
		6145	39	242T	2.75	3.15	2.70
		6385	87	242T	2.89	3.23	2.67
80MHz BW	6	6465	103	242T	2.88	2.92	2.76
		6545	119	242T	2.68	2.63	2.66
		6705	151	242T	2.48	2.69	2.39
	7	6865	183	242T	0.80	1.16	0.76
80MHz BW	8	6945	199	242T	2.91	2.89	2.85
		7025	215	242T	2.88	3.07	2.92
80MHz BW	5	5985	7	996T	7.03		
		6145	39	996T	7.06		
		6385	87	996T	7.08		
80MHz BW	6	6465	103	996T	7.95		
		6545	119	996T	7.60		
		6705	151	996T	7.84		
	7	6865	183	996T	7.82		
80MHz BW	8	6945	199	996T	8.23		
		7025	215	996T	8.18		
80MHz BW	5	5985	7	106T	-0.13	1.04	0.95
		6145	39	106T	0.02	0.90	0.15
		6385	87	106T	-0.27	0.90	-0.38
80MHz BW	6	6465	103	106T	-0.14	0.52	-0.90
		6545	119	106T	-0.30	0.33	-1.03
		6705	151	106T	-0.08	0.67	-0.90
	7	6865	183	106T	-0.39	0.58	-0.55
80MHz BW	8	6945	199	106T	0.05	0.47	-0.30
		7025	215	106T	0.30	0.85	-0.73
160MHz BW	5	6025	15	26T	-6.70	-5.45	-4.80
		6185	47	26T	-6.65	-5.61	-5.02
		6345	79	26T	-6.22	-5.65	-5.63
160MHz BW	6	6505	111	26T	-6.49	-6.12	-6.30
		6665	143	26T	-7.18	-6.75	-6.77
		6825	175	26T	-6.25	-5.74	-5.57
	8	6985	207	26T	-6.09	-5.35	-5.00

FCC ID: BCGA2435	SAR EVALUATION REPORT	Reviewed by: Technical Manager
DUT Type: Tablet Device		APPENDIX H: Page 20 of 21

160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					37	44	52
5	6025	15	52T		-3.69	-2.84	-1.85
		47	52T		-3.46	-2.52	-1.99
		79	52T		-2.97	-2.55	-2.52
	6	6505	111	52T	-3.02	-2.85	-2.89
7	6665	143	52T		-3.07	-2.67	-2.76
	6825	175	52T		-3.99	-3.51	-3.36
8	6985	207	52T		-2.77	-2.12	-1.85
160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					61	62	64
5	6025	15	242T		2.75	3.21	2.63
		47	242T		2.90	3.16	2.75
		79	242T		2.69	2.95	2.66
6	6505	111	242T		1.24	1.54	1.49
7	6665	143	242T		2.56	2.70	2.42
	6825	175	242T		2.46	2.59	2.40
8	6985	207	242T		3.09	3.21	2.93
160MHz BW	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					65	66	N/A
5	6025	15	484T		5.33	5.38	
		47	484T		5.24	5.28	
		79	484T		5.39	5.30	
6	6505	111	484T		4.58	4.50	
7	6665	143	484T		4.40	4.36	
	6825	175	484T		4.38	4.40	
8	6985	211	484T		5.37	5.34	
160MHz BW 1st	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					67(L)	N/A	N/A
5	6025	15	996T		4.24		
		47	996T		3.79		
		79	996T		3.43		
6	6505	111	996T		3.42		
7	6665	143	996T		3.78		
	6825	175	996T		3.67		
8	6985	207	996T		5.24		
160MHz BW 2nd	Band	Freq [MHz]	Channel	Tones	Avg Conducted Power (dBm)		
					RU Index		
					67(H)	N/A	N/A
5	6025	15	996T		8.95		
		47	996T		8.09		
		79	996T		7.60		
6	6505	111	996T		7.61		
7	6665	143	996T		7.39		
	6825	175	996T		9.88		
8	6985	207	996T		10.90		

FCC ID: BCGA2435	SAR EVALUATION REPORT	Reviewed by: Technical Manager
DUT Type: Tablet Device		APPENDIX H: Page 21 of 21