



SAR EVALUATION REPORT

Applicant Name:
Apple, Inc.
One Apple Park Way
Cupertino, CA 95014 USA

Date of Testing:
12/14/2021 – 01/10/2022
Test Site/Location:
PCTEST Lab, Morgan Hill, CA, USA
Document Serial No.:
1C2111150078-11.BCG (Rev 2)

FCC ID: **BCGA2588**
APPLICANT: **APPLE, INC.**

DUT Type: Tablet Device
Application Type: Certification
FCC Rule Part(s): CFR §2.1093
Model: A2588

Equipment Class	Band & Mode	Tx Frequency	SAR
			1g Body (W/kg)
DTS	2.4 GHz WLAN	2412 - 2472 MHz	1.17
NII	U-NII-1	5180 - 5240 MHz	N/A
NII	U-NII-2A	5260 - 5320 MHz	1.17
NII	U-NII-2C	5500 - 5720 MHz	1.19
NII	U-NII-3	5745 - 5825 MHz	1.15
DSS/DTS	Bluetooth	2402 - 2480 MHz	1.04
Simultaneous SAR per KDB 690783 D01v01r03:			1.46

Note: This revised Test Report supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.7 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.



RJ Ortanez
Executive Vice President



The SAR Tick is an initiative of the Mobile & Wireless Forum (MWF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MWF. Further details can be obtained by emailing: sartick@mwfai.info.

FCC ID: BCGA2588	 SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device
		Page 1 of 52

T A B L E O F C O N T E N T S

1	DEVICE UNDER TEST	3
2	INTRODUCTION	16
3	DOSIMETRIC ASSESSMENT	17
4	TEST CONFIGURATION POSITIONS	18
5	RF EXPOSURE LIMITS	19
6	FCC MEASUREMENT PROCEDURES.....	20
7	RF CONDUCTED POWERS	23
8	SYSTEM VERIFICATION.....	37
9	SAR DATA SUMMARY	39
10	FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS.....	44
11	SAR MEASUREMENT VARIABILITY	47
12	EQUIPMENT LIST	48
13	MEASUREMENT UNCERTAINTIES.....	49
14	CONCLUSION.....	50
15	REFERENCES	51
APPENDIX A: SAR TEST PLOTS		
APPENDIX B: SAR DIPOLE VERIFICATION PLOTS		
APPENDIX C: SAR TISSUE SPECIFICATIONS		
APPENDIX D: SAR SYSTEM VALIDATION		
APPENDIX E: DUT ANTENNA DIAGRAM & SAR TEST SETUP PHOTOGRAPHS		
APPENDIX F: IEEE 802.11AX RU SAR EXCLUSION		
APPENDIX G: WIFI TIME-AVERAGED SAR VERIFICATION		
APPENDIX H: PROBE AND DIPOLE CALIBRATION CERTIFICATES		

FCC ID: BCGA2588	 PCTEST Proud to be part of Element	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 2 of 52

1 DEVICE UNDER TEST

1.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
2.4 GHz WLAN	Voice/Data	2412 - 2472 MHz
U-NII-1	Voice/Data	5180 - 5240 MHz
U-NII-2A	Voice/Data	5260 - 5320 MHz
U-NII-2C	Voice/Data	5500 - 5720 MHz
U-NII-3	Voice/Data	5745 - 5825 MHz
Bluetooth	Data	2402 - 2480 MHz

1.2 Power Reduction for SAR

This device utilizes an independent single step power reduction mechanism for Bluetooth operations. When Bluetooth is operating simultaneously with 5 GHz WLAN, the output power of Bluetooth is reduced for the duration of simultaneous operation. SAR evaluation was additionally performed at the maximum allowed output power for Bluetooth which is applicable for all other use cases.

This device used an independent mechanism that limits WIFI powers to a time-averaged output power. For the purposes of this test report, all SAR measurements were performed with the algorithm disabled at the maximum time-averaged output power level. Appendix G includes verification data for this time-averaged SAR mechanism.

1.3 Nominal and Maximum Output Power Specifications

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D01v06.

1.3.1 Maximum Time-Averaged Output Power

Note: Targets for 802.11ax RU operations can be found in Appendix F.

Mode/ Band			IEEE 802.11b (2.4 GHz)		IEEE 802.11g (2.4 GHz)		IEEE 802.11n (2.4 GHz)		IEEE 802.11ax SU (2.4 GHz)	
		Channel	Maximum	Nominal	Maximum	Nominal	Maximum	Nominal	Maximum	Nominal
Modulated Average - Single Tx Chain (dBm) - Antenna WF8	20 MHz Bandwidth	1	20.00	18.50	15.25	13.75	15.25	13.75	15.00	13.50
		2	21.50	20.00	19.00	17.50	19.00	17.50	18.25	16.75
		3	21.50	20.00	20.50	19.00	20.50	19.00	19.50	18.00
		4	21.50	20.00	21.25	19.75	21.25	19.75	20.75	19.25
		5	21.50	20.00	21.50	20.00	21.50	20.00	21.50	20.00
		6	21.50	20.00	21.50	20.00	21.50	20.00	21.50	20.00
		7	21.50	20.00	21.50	20.00	21.50	20.00	21.50	20.00
		8	21.50	20.00	21.50	20.00	21.50	20.00	20.50	19.00
		9	21.50	20.00	20.75	19.25	20.75	19.25	20.50	19.00
		10	21.50	20.00	20.25	18.75	20.25	18.75	18.50	17.00
		11	21.50	20.00	18.00	16.50	18.00	16.50	16.50	15.00
		12	20.00	18.50	14.50	13.00	14.50	13.00	13.00	11.50
		13	18.50	17.00	11.50	10.00	11.50	10.00	N/A	N/A

FCC ID: BCGA2588	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 3 of 52

Mode/ Band			IEEE 802.11g (2.4 GHz)		IEEE 802.11n (2.4 GHz)		IEEE 802.11ax SU (2.4 GHz)	
		Channel	Maximum	Nominal	Maximum	Nominal	Maximum	Nominal
Modulated Average - 2 Tx Chain (dBm) - Antenna WF8	20 MHz Bandwidth	1	14.25	12.75	14.25	12.75	14.00	12.50
		2	18.50	17.00	18.50	17.00	17.25	15.75
		3	20.00	18.50	20.00	18.50	19.00	17.50
		4	20.75	19.25	20.75	19.25	20.00	18.50
		5	21.50	20.00	21.50	20.00	20.50	19.00
		6	21.50	20.00	21.50	20.00	21.50	20.00
		7	21.50	20.00	21.50	20.00	21.00	19.50
		8	20.50	19.00	20.50	19.00	20.00	18.50
		9	20.00	18.50	20.00	18.50	19.50	18.00
		10	19.00	17.50	19.00	17.50	18.00	16.50
		11	16.50	15.00	16.50	15.00	15.50	14.00
		12	13.00	11.50	13.00	11.50	12.00	10.50
		13	9.00	7.50	9.00	7.50	N/A	N/A

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.

Mode/ Band			IEEE 802.11b (2.4 GHz)		IEEE 802.11g (2.4 GHz)		IEEE 802.11n (2.4 GHz)		IEEE 802.11ax SU (2.4 GHz)	
		Channel	Maximum	Nominal	Maximum	Nominal	Maximum	Nominal	Maximum	Nominal
Modulated Average - Single Tx Chain (dBm) - Antenna WF7b	20 MHz Bandwidth	1	20.00	18.50	15.25	13.75	15.25	13.75	15.00	13.50
		2	20.50	19.00	19.00	17.50	19.00	17.50	18.25	16.75
		3	20.50	19.00	20.50	19.00	20.50	19.00	19.50	18.00
		4	20.50	19.00	20.50	19.00	20.50	19.00	20.50	19.00
		5	20.50	19.00	20.50	19.00	20.50	19.00	20.50	19.00
		6	20.50	19.00	20.50	19.00	20.50	19.00	20.50	19.00
		7	20.50	19.00	20.50	19.00	20.50	19.00	20.50	19.00
		8	20.50	19.00	20.50	19.00	20.50	19.00	20.50	19.00
		9	20.50	19.00	20.50	19.00	20.50	19.00	20.50	19.00
		10	20.50	19.00	20.25	18.75	20.25	18.75	18.50	17.00
		11	20.50	19.00	18.00	16.50	18.00	16.50	16.50	15.00
		12	20.00	18.50	14.50	13.00	14.50	13.00	13.00	11.50
		13	18.50	17.00	11.50	10.00	11.50	10.00	N/A	N/A

Mode/ Band			IEEE 802.11g (2.4 GHz)		IEEE 802.11n (2.4 GHz)		IEEE 802.11ax SU (2.4 GHz)	
		Channel	Maximum	Nominal	Maximum	Nominal	Maximum	Nominal
Modulated Average - 2 Tx Chain (dBm) - Antenna WF7b	20 MHz Bandwidth	1	14.25	12.75	14.25	12.75	14.00	12.50
		2	18.50	17.00	18.50	17.00	17.25	15.75
		3	20.00	18.50	20.00	18.50	19.00	17.50
		4	20.50	19.00	20.50	19.00	20.00	18.50
		5	20.50	19.00	20.50	19.00	20.50	19.00
		6	20.50	19.00	20.50	19.00	20.50	19.00
		7	20.50	19.00	20.50	19.00	20.50	19.00
		8	20.50	19.00	20.50	19.00	20.00	18.50
		9	20.00	18.50	20.00	18.50	19.50	18.00
		10	19.00	17.50	19.00	17.50	18.00	16.50
		11	16.50	15.00	16.50	15.00	15.50	14.00
		12	13.00	11.50	13.00	11.50	12.00	10.50
		13	9.00	7.50	9.00	7.50	N/A	N/A

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.

FCC ID: BCGA2588	 PCTEST Proud to be part of Element		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device		Page 4 of 52

Mode/ Band			IEEE 802.11a (5 GHz)		IEEE 802.11n (5 GHz)		IEEE 802.11ac (5 GHz)		IEEE 802.11ax SU (5 GHz)	
		Channel	Maximum	Nominal	Maximum	Nominal	Maximum	Nominal	Maximum	Nominal
Modulated Average - Single Tx Chain (dBm) 5GHz Antenna WF8	20 MHz Bandwidth	36	17.25	15.75	17.25	15.75	17.25	15.75	17.25	15.75
		40	17.25	15.75	17.25	15.75	17.25	15.75	17.25	15.75
		44	17.25	15.75	17.25	15.75	17.25	15.75	17.25	15.75
		48	17.25	15.75	17.25	15.75	17.25	15.75	17.25	15.75
		52	18.50	17.00	18.50	17.00	18.50	17.00	18.50	17.00
		56	18.50	17.00	18.50	17.00	18.50	17.00	18.50	17.00
		60	18.50	17.00	18.50	17.00	18.50	17.00	18.50	17.00
		64	18.50	17.00	18.50	17.00	18.50	17.00	17.50	16.00
		100	17.75	16.25	17.75	16.25	17.75	16.25	17.00	15.50
		104	17.75	16.25	17.75	16.25	17.75	16.25	17.75	16.25
		108	17.75	16.25	17.75	16.25	17.75	16.25	17.75	16.25
		112	17.75	16.25	17.75	16.25	17.75	16.25	17.75	16.25
		116	17.75	16.25	17.75	16.25	17.75	16.25	17.75	16.25
		120	17.75	16.25	17.75	16.25	17.75	16.25	17.75	16.25
		124	17.75	16.25	17.75	16.25	17.75	16.25	17.75	16.25
		128	17.75	16.25	17.75	16.25	17.75	16.25	17.75	16.25
		132	17.75	16.25	17.75	16.25	17.75	16.25	17.75	16.25
		136	17.75	16.25	17.75	16.25	17.75	16.25	17.75	16.25
		140	15.75	14.25	15.75	14.25	15.75	14.25	15.75	14.25
		144	17.75	16.25	17.75	16.25	17.75	16.25	17.75	16.25
		149	17.75	16.25	17.75	16.25	17.75	16.25	17.75	16.25
		153	17.75	16.25	17.75	16.25	17.75	16.25	17.75	16.25
		157	17.75	16.25	17.75	16.25	17.75	16.25	17.75	16.25
		161	17.75	16.25	17.75	16.25	17.75	16.25	17.75	16.25
		165	17.75	16.25	17.75	16.25	17.75	16.25	17.75	16.25
	40 MHz Bandwidth	38			16.50	15.00	16.50	15.00	14.00	12.50
		46			17.25	15.75	17.25	15.75	17.25	15.75
		54			18.50	17.00	18.50	17.00	18.50	17.00
		62			16.50	15.00	16.50	15.00	15.00	13.50
		102			15.50	14.00	15.50	14.00	13.75	12.25
		110			17.75	16.25	17.75	16.25	17.75	16.25
		118			17.75	16.25	17.75	16.25	17.75	16.25
		126			17.75	16.25	17.75	16.25	17.75	16.25
		134			17.75	16.25	17.75	16.25	15.75	14.25
		142			17.75	16.25	17.75	16.25	17.75	16.25
		151			17.75	16.25	17.75	16.25	17.75	16.25
		159			17.75	16.25	17.75	16.25	17.75	16.25
	80 MHz Bandwidth	42					14.50	13.00	13.00	11.50
		58					15.00	13.50	14.00	12.50
		106					14.00	12.50	13.75	12.25
		122					17.75	16.25	17.75	16.25
		138					17.75	16.25	17.75	16.25
		155					17.75	16.25	17.75	16.25

FCC ID: BCGA2588	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 5 of 52

Mode/ Band			IEEE 802.11a (5 GHz)		IEEE 802.11n (5 GHz)		IEEE 802.11ac (5 GHz)		IEEE 802.11ax SU (5 GHz)	
		Channel	Maximum	Nominal	Maximum	Nominal	Maximum	Nominal	Maximum	Nominal
Modulated Average - 2 Tx Chain (dBm) CDD - 5GHz Antenna WF8	20 MHz Bandwidth	36	16.25	14.75	16.25	14.75	16.25	14.75	15.50	14.00
		40	16.25	14.75	16.25	14.75	16.25	14.75	16.25	14.75
		44	16.25	14.75	16.25	14.75	16.25	14.75	16.25	14.75
		48	16.25	14.75	16.25	14.75	16.25	14.75	16.25	14.75
		52	16.50	15.00	16.50	15.00	16.50	15.00	16.50	15.00
		56	16.50	15.00	16.50	15.00	16.50	15.00	16.50	15.00
		60	16.50	15.00	16.50	15.00	16.50	15.00	16.50	15.00
		64	16.50	15.00	16.50	15.00	16.50	15.00	16.25	14.75
		100	16.00	14.50	16.00	14.50	16.00	14.50	16.00	14.50
		104	16.00	14.50	16.00	14.50	16.00	14.50	16.00	14.50
		108	16.00	14.50	16.00	14.50	16.00	14.50	16.00	14.50
		112	16.00	14.50	16.00	14.50	16.00	14.50	16.00	14.50
		116	16.00	14.50	16.00	14.50	16.00	14.50	16.00	14.50
		120	16.00	14.50	16.00	14.50	16.00	14.50	16.00	14.50
		124	16.00	14.50	16.00	14.50	16.00	14.50	16.00	14.50
		128	16.00	14.50	16.00	14.50	16.00	14.50	16.00	14.50
		132	16.00	14.50	16.00	14.50	16.00	14.50	16.00	14.50
		136	16.00	14.50	16.00	14.50	16.00	14.50	16.00	14.50
		140	15.00	13.50	15.00	13.50	15.00	13.50	13.25	11.75
		144	16.00	14.50	16.00	14.50	16.00	14.50	16.00	14.50
		149	17.75	16.25	17.75	16.25	17.75	16.25	17.75	16.25
		153	17.75	16.25	17.75	16.25	17.75	16.25	17.75	16.25
		157	17.75	16.25	17.75	16.25	17.75	16.25	17.75	16.25
		161	17.75	16.25	17.75	16.25	17.75	16.25	17.75	16.25
		165	17.75	16.25	17.75	16.25	17.75	16.25	17.75	16.25
	40 MHz Bandwidth	38			13.50	12.00	13.50	12.00	10.75	9.25
		46			17.25	15.75	17.25	15.75	17.25	15.75
		54			18.50	17.00	18.50	17.00	18.50	17.00
		62			14.25	12.75	14.25	12.75	12.75	11.25
		102			14.00	12.50	14.00	12.50	12.00	10.50
		110			17.75	16.25	17.75	16.25	17.75	16.25
		118			17.75	16.25	17.75	16.25	17.75	16.25
		126			17.75	16.25	17.75	16.25	17.75	16.25
		134			17.50	16.00	17.50	16.00	15.50	14.00
		142			17.75	16.25	17.75	16.25	17.75	16.25
		151			17.75	16.25	17.75	16.25	17.75	16.25
		159			17.75	16.25	17.75	16.25	17.75	16.25
	80 MHz Bandwidth	42					11.50	10.00	10.50	9.00
		58					12.25	10.75	11.75	10.25
		106					12.50	11.00	11.00	9.50
		122					17.75	16.25	17.25	15.75
		138					17.75	16.25	17.75	16.25
		155					17.75	16.25	17.50	16.00

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.

FCC ID: BCGA2588	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 6 of 52

Mode/ Band			IEEE 802.11n (5 GHz)		IEEE 802.11ac (5 GHz)		IEEE 802.11ax SU (5 GHz)	
		Channel	Maximum	Nominal	Maximum	Nominal	Maximum	Nominal
Modulated Average - 2 Tx Chain (dBm) SDM 5GHz Antenna WF8	20 MHz Bandwidth	36	16.50	15.00	16.50	15.00	15.50	14.00
		40	17.00	15.50	17.00	15.50	17.00	15.50
		44	17.00	15.50	17.00	15.50	17.00	15.50
		48	17.00	15.50	17.00	15.50	17.00	15.50
		52	17.00	15.50	17.00	15.50	17.00	15.50
		56	17.00	15.50	17.00	15.50	17.00	15.50
		60	17.00	15.50	17.00	15.50	17.00	15.50
		64	17.00	15.50	17.00	15.50	16.25	14.75
		100	17.00	15.50	17.00	15.50	16.50	15.00
		104	17.00	15.50	17.00	15.50	17.00	15.50
		108	17.00	15.50	17.00	15.50	17.00	15.50
		112	17.00	15.50	17.00	15.50	17.00	15.50
		116	17.00	15.50	17.00	15.50	17.00	15.50
		120	17.00	15.50	17.00	15.50	17.00	15.50
		124	17.00	15.50	17.00	15.50	17.00	15.50
		128	17.00	15.50	17.00	15.50	17.00	15.50
		132	17.00	15.50	17.00	15.50	17.00	15.50
		136	17.00	15.50	17.00	15.50	17.00	15.50
		140	15.00	13.50	15.00	13.50	13.25	11.75
		144	17.00	15.50	17.00	15.50	17.00	15.50
		149	17.75	16.25	17.75	16.25	17.75	16.25
	40 MHz Bandwidth	153	17.75	16.25	17.75	16.25	17.75	16.25
		157	17.75	16.25	17.75	16.25	17.75	16.25
		161	17.75	16.25	17.75	16.25	17.75	16.25
		165	17.75	16.25	17.75	16.25	17.75	16.25
		38	13.50	12.00	13.50	12.00	10.75	9.25
		46	17.25	15.75	17.25	15.75	17.25	15.75
		54	18.50	17.00	18.50	17.00	18.50	17.00
		62	14.25	12.75	14.25	12.75	12.75	11.25
		102	14.00	12.50	14.00	12.50	12.00	10.50
		110	17.75	16.25	17.75	16.25	17.75	16.25
	80 MHz Bandwidth	118	17.75	16.25	17.75	16.25	17.75	16.25
		126	17.75	16.25	17.75	16.25	17.75	16.25
		134	17.50	16.00	17.50	16.00	15.50	14.00
		142	17.75	16.25	17.75	16.25	17.75	16.25
		151	17.75	16.25	17.75	16.25	17.75	16.25
		159	17.75	16.25	17.75	16.25	17.75	16.25
		42			11.50	10.00	10.50	9.00
		58			12.25	10.75	11.75	10.25
		106			12.50	11.00	11.00	9.50
		122			17.75	16.25	17.25	15.75
		138			17.75	16.25	17.75	16.25
		155			17.75	16.25	17.50	16.00

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.

FCC ID: BCGA2588	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 7 of 52

Mode/ Band			IEEE 802.11a (5 GHz)		IEEE 802.11n (5 GHz)		IEEE 802.11ac (5 GHz)		IEEE 802.11ax SU (5 GHz)	
		Channel	Maximum	Nominal	Maximum	Nominal	Maximum	Nominal	Maximum	Nominal
Modulated Average - Single Tx Chain (dBm) 5GHz Antenna WF7a	20 MHz Bandwidth	36	16.25	14.75	16.25	14.75	16.25	14.75	16.25	14.75
		40	16.25	14.75	16.25	14.75	16.25	14.75	16.25	14.75
		44	16.25	14.75	16.25	14.75	16.25	14.75	16.25	14.75
		48	16.25	14.75	16.25	14.75	16.25	14.75	16.25	14.75
		52	17.00	15.50	17.00	15.50	17.00	15.50	17.00	15.50
		56	17.00	15.50	17.00	15.50	17.00	15.50	17.00	15.50
		60	17.00	15.50	17.00	15.50	17.00	15.50	17.00	15.50
		64	17.00	15.50	17.00	15.50	17.00	15.50	17.00	15.50
		100	15.50	14.00	15.50	14.00	15.50	14.00	15.50	14.00
		104	15.50	14.00	15.50	14.00	15.50	14.00	15.50	14.00
		108	15.50	14.00	15.50	14.00	15.50	14.00	15.50	14.00
		112	15.50	14.00	15.50	14.00	15.50	14.00	15.50	14.00
		116	15.50	14.00	15.50	14.00	15.50	14.00	15.50	14.00
		120	15.50	14.00	15.50	14.00	15.50	14.00	15.50	14.00
		124	15.50	14.00	15.50	14.00	15.50	14.00	15.50	14.00
		128	15.50	14.00	15.50	14.00	15.50	14.00	15.50	14.00
		132	15.50	14.00	15.50	14.00	15.50	14.00	15.50	14.00
		136	15.50	14.00	15.50	14.00	15.50	14.00	15.50	14.00
		140	15.50	14.00	15.50	14.00	15.50	14.00	15.50	14.00
		144	15.50	14.00	15.50	14.00	15.50	14.00	15.50	14.00
		149	16.50	15.00	16.50	15.00	16.50	15.00	16.50	15.00
	40 MHz Bandwidth	153	16.50	15.00	16.50	15.00	16.50	15.00	16.50	15.00
		157	16.50	15.00	16.50	15.00	16.50	15.00	16.50	15.00
		161	16.50	15.00	16.50	15.00	16.50	15.00	16.50	15.00
		165	16.50	15.00	16.50	15.00	16.50	15.00	16.50	15.00
		38			16.25	14.75	16.25	14.75	14.00	12.50
		46			16.25	14.75	16.25	14.75	16.25	14.75
		54			17.00	15.50	17.00	15.50	17.00	15.50
		62			16.50	15.00	16.50	15.00	15.00	13.50
		102			15.50	14.00	15.50	14.00	13.75	12.25
		110			15.50	14.00	15.50	14.00	15.50	14.00
		118			15.50	14.00	15.50	14.00	15.50	14.00
		126			15.50	14.00	15.50	14.00	15.50	14.00
	80 MHz Bandwidth	134			15.50	14.00	15.50	14.00	15.50	14.00
		142			15.50	14.00	15.50	14.00	15.50	14.00
		151			16.50	15.00	16.50	15.00	16.50	15.00
		159			16.50	15.00	16.50	15.00	16.50	15.00
		42					14.50	13.00	13.00	11.50
		58					15.00	13.50	14.00	12.50
		106					14.00	12.50	13.75	12.25
		122					15.50	14.00	15.50	14.00
		138					15.50	14.00	15.50	14.00
		155					16.50	15.00	16.50	15.00

FCC ID: BCGA2588	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 8 of 52

Mode/ Band			IEEE 802.11a (5 GHz)		IEEE 802.11n (5 GHz)		IEEE 802.11ac (5 GHz)		IEEE 802.11ax SU (5 GHz)		
		Channel	Maximum	Nominal	Maximum	Nominal	Maximum	Nominal	Maximum	Nominal	
Modulated Average - 2 Tx Chain (dBm) CDD - 5GHz Antenna WF7a	20 MHz Bandwidth	36	16.25	14.75	16.25	14.75	16.25	14.75	15.50	14.00	
		40	16.25	14.75	16.25	14.75	16.25	14.75	16.25	14.75	
		44	16.25	14.75	16.25	14.75	16.25	14.75	16.25	14.75	
		48	16.25	14.75	16.25	14.75	16.25	14.75	16.25	14.75	
		52	16.50	15.00	16.50	15.00	16.50	15.00	16.50	15.00	
		56	16.50	15.00	16.50	15.00	16.50	15.00	16.50	15.00	
		60	16.50	15.00	16.50	15.00	16.50	15.00	16.50	15.00	
		64	16.50	15.00	16.50	15.00	16.50	15.00	16.25	14.75	
		100	15.50	14.00	15.50	14.00	15.50	14.00	15.50	14.00	
		104	15.50	14.00	15.50	14.00	15.50	14.00	15.50	14.00	
		108	15.50	14.00	15.50	14.00	15.50	14.00	15.50	14.00	
		112	15.50	14.00	15.50	14.00	15.50	14.00	15.50	14.00	
		116	15.50	14.00	15.50	14.00	15.50	14.00	15.50	14.00	
		120	15.50	14.00	15.50	14.00	15.50	14.00	15.50	14.00	
		124	15.50	14.00	15.50	14.00	15.50	14.00	15.50	14.00	
		128	15.50	14.00	15.50	14.00	15.50	14.00	15.50	14.00	
		132	15.50	14.00	15.50	14.00	15.50	14.00	15.50	14.00	
		136	15.50	14.00	15.50	14.00	15.50	14.00	15.50	14.00	
		140	15.00	13.50	15.00	13.50	15.00	13.50	13.25	11.75	
		144	15.50	14.00	15.50	14.00	15.50	14.00	15.50	14.00	
		149	16.50	15.00	16.50	15.00	16.50	15.00	16.50	15.00	
		153	16.50	15.00	16.50	15.00	16.50	15.00	16.50	15.00	
		157	16.50	15.00	16.50	15.00	16.50	15.00	16.50	15.00	
		161	16.50	15.00	16.50	15.00	16.50	15.00	16.50	15.00	
		165	16.50	15.00	16.50	15.00	16.50	15.00	16.50	15.00	
	40 MHz Bandwidth	38				13.50	12.00	13.50	12.00	10.75	9.25
		46				16.25	14.75	16.25	14.75	16.25	14.75
		54				17.00	15.50	17.00	15.50	17.00	15.50
		62				14.25	12.75	14.25	12.75	12.75	11.25
		102				14.00	12.50	14.00	12.50	12.00	10.50
		110				15.50	14.00	15.50	14.00	15.50	14.00
		118				15.50	14.00	15.50	14.00	15.50	14.00
		126				15.50	14.00	15.50	14.00	15.50	14.00
		134				15.50	14.00	15.50	14.00	15.50	14.00
		142				15.50	14.00	15.50	14.00	15.50	14.00
		151				16.50	15.00	16.50	15.00	16.50	15.00
		159				16.50	15.00	16.50	15.00	16.50	15.00
	80 MHz Bandwidth	42						11.50	10.00	10.50	9.00
		58						12.25	10.75	11.75	10.25
		106						12.50	11.00	11.00	9.50
		122						15.50	14.00	15.50	14.00
		138						15.50	14.00	15.50	14.00
		155						16.50	15.00	16.50	15.00

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.

FCC ID: BCGA2588	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 9 of 52

Mode/ Band		Channel	IEEE 802.11n (5 GHz)		IEEE 802.11ac (5 GHz)		IEEE 802.11ax SU (5 GHz)	
			Maximum	Nominal	Maximum	Nominal	Maximum	Nominal
Modulated Average - 2 Tx Chain (dBm) SDM- 5GHz Antenna WF7a	20 MHz Bandwidth	36	16.25	14.75	16.25	14.75	15.50	14.00
		40	16.25	14.75	16.25	14.75	16.25	14.75
		44	16.25	14.75	16.25	14.75	16.25	14.75
		48	16.25	14.75	16.25	14.75	16.25	14.75
		52	17.00	15.50	17.00	15.50	17.00	15.50
		56	17.00	15.50	17.00	15.50	17.00	15.50
		60	17.00	15.50	17.00	15.50	17.00	15.50
		64	17.00	15.50	17.00	15.50	16.25	14.75
		100	15.50	14.00	15.50	14.00	15.50	14.00
		104	15.50	14.00	15.50	14.00	15.50	14.00
		108	15.50	14.00	15.50	14.00	15.50	14.00
		112	15.50	14.00	15.50	14.00	15.50	14.00
		116	15.50	14.00	15.50	14.00	15.50	14.00
		120	15.50	14.00	15.50	14.00	15.50	14.00
		124	15.50	14.00	15.50	14.00	15.50	14.00
		128	15.50	14.00	15.50	14.00	15.50	14.00
		132	15.50	14.00	15.50	14.00	15.50	14.00
		136	15.50	14.00	15.50	14.00	15.50	14.00
		140	15.00	13.50	15.00	13.50	13.25	11.75
		144	15.50	14.00	15.50	14.00	15.50	14.00
		149	16.50	15.00	16.50	15.00	16.50	15.00
	40 MHz Bandwidth	153	16.50	15.00	16.50	15.00	16.50	15.00
		157	16.50	15.00	16.50	15.00	16.50	15.00
		161	16.50	15.00	16.50	15.00	16.50	15.00
		165	16.50	15.00	16.50	15.00	16.50	15.00
		38	13.50	12.00	13.50	12.00	10.75	9.25
		46	16.25	14.75	16.25	14.75	16.25	14.75
		54	17.00	15.50	17.00	15.50	17.00	15.50
		62	14.25	12.75	14.25	12.75	12.75	11.25
		102	14.00	12.50	14.00	12.50	12.00	10.50
		110	15.50	14.00	15.50	14.00	15.50	14.00
	80 MHz Bandwidth	118	15.50	14.00	15.50	14.00	15.50	14.00
		126	15.50	14.00	15.50	14.00	15.50	14.00
		134	15.50	14.00	15.50	14.00	15.50	14.00
		142	15.50	14.00	15.50	14.00	15.50	14.00
		151	16.50	15.00	16.50	15.00	16.50	15.00
		159	16.50	15.00	16.50	15.00	16.50	15.00
		42			11.50	10.00	10.50	9.00
		58			12.25	10.75	11.75	10.25
		106			12.50	11.00	11.00	9.50
		122			15.50	14.00	15.50	14.00
		138			15.50	14.00	15.50	14.00
		155			16.50	15.00	16.50	15.00

Note: In MIMO operations, each antenna transmits at maximum allowed powers as indicated above.

FCC ID: BCGA2588	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 10 of 52

1.3.2 Bluetooth Maximum Output Power

Mode / Band		Modulated Average - Single Tx Chain (dBm) - Antenna WF8
Bluetooth BDR/LE	Maximum	19.50
	Nominal	18.00
Bluetooth EDR	Maximum	15.00
	Nominal	13.50
Bluetooth HDR	Maximum	14.00
	Nominal	12.50

Mode / Band		Modulated Average - TxBF (dBm) - Antenna WF8
Bluetooth BDR/LE	Maximum	17.00
	Nominal	15.50
Bluetooth EDR	Maximum	13.50
	Nominal	12.00
Bluetooth HDR	Maximum	14.00
	Nominal	12.50

Note: In TxBF operations, each antenna transmits at maximum allowed powers as indicated above.

Mode / Band		Modulated Average - Single Tx Chain (dBm) - Antenna WF7b
Bluetooth BDR/LE	Maximum	20.00
	Nominal	18.50
Bluetooth EDR	Maximum	15.00
	Nominal	13.50
Bluetooth HDR	Maximum	14.00
	Nominal	12.50

FCC ID: BCGA2588	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 11 of 52

Mode / Band		Modulated Average -TxBF (dBm) - Antenna WF7b
Bluetooth BDR/LE	Maximum	17.00
	Nominal	15.50
Bluetooth EDR	Maximum	13.50
	Nominal	12.00
Bluetooth HDR	Maximum	14.00
	Nominal	12.50

Note: In TxBF operations, each antenna transmits at maximum allowed powers as indicated above.

1.3.3 Bluetooth Reduced Output Power

Note: Below table is applicable in the following conditions:
-Simultaneous conditions with 5 GHz WLAN active

Mode / Band		Modulated Average - Single Tx Chain (dBm) - Antenna WF8
Bluetooth BDR/LE Reduced	Maximum	12.50
	Nominal	11.00
Bluetooth EDR Reduced	Maximum	12.50
	Nominal	11.00
Bluetooth HDR Reduced	Maximum	12.50
	Nominal	11.00

Note: Below table is applicable in the following conditions:
-Simultaneous conditions with 5 GHz WLAN active

Mode / Band		Modulated Average - TxBF (dBm) - Antenna WF8
Bluetooth BDR/LE Reduced	Maximum	10.00
	Nominal	8.50
Bluetooth EDR Reduced	Maximum	10.00
	Nominal	8.50
Bluetooth HDR Reduced	Maximum	10.00
	Nominal	8.50

Note: In TxBF operations, each antenna transmits at maximum allowed powers as indicated above.

FCC ID: BCGA2588	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 12 of 52

Note: Below table is applicable in the following conditions:
 -Simultaneous conditions with 5 GHz WLAN active

Mode / Band		Modulated Average - Single Tx Chain (dBm) - Antenna WF7b
Bluetooth BDR/LE Reduced	Maximum	13.00
	Nominal	11.50
Bluetooth EDR Reduced	Maximum	13.00
	Nominal	11.50
Bluetooth HDR Reduced	Maximum	13.00
	Nominal	11.50

Note: Below table is applicable in the following conditions:
 -Simultaneous conditions with 5 GHz WLAN active

Mode / Band		Modulated Average - TxBF (dBm) - Antenna WF7b
Bluetooth BDR/LE Reduced	Maximum	10.00
	Nominal	8.50
Bluetooth EDR Reduced	Maximum	10.00
	Nominal	8.50
Bluetooth HDR Reduced	Maximum	10.00
	Nominal	8.50

Note: In TxBF operations, each antenna transmits at maximum allowed powers as indicated above.

FCC ID: BCGA2588	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 13 of 52

1.4 DUT Antenna Locations

The overall dimensions of this device are > 200mm. A diagram showing the location of the device antennas can be found in Appendix E. Exact antenna dimensions and separation are shown in the Technical Descriptions in the FCC filings.

Table 1-1
Device Edges/Sides for SAR Testing

Device Sides/Edges for SAR Testing						
Mode	Back	Front	Top	Bottom	Right	Left
2.4 GHz WLAN Antenna WF8	Yes	No	Yes	No	Yes	No
2.4 GHz WLAN Antenna WF7b	Yes	No	Yes	No	No	Yes
5 GHz WLAN Antenna WF8	Yes	No	Yes	No	Yes	No
5 GHz WLAN Antenna WF7a	Yes	No	Yes	No	No	Yes
Bluetooth Antenna WF8	Yes	No	Yes	No	Yes	No
Bluetooth Antenna WF7b	Yes	No	Yes	No	No	Yes

Note: Per FCC KDB Publication 616217 D04v01r01, particular edges were not required to be evaluated for SAR based on the SAR exclusion threshold in KDB 447498 D01V06. Additional edges may have been evaluated for simultaneous transmission analysis.

1.5 Simultaneous Transmission Capabilities

According to FCC KDB Publication 447498 D01v06, transmitters are considered to be operating simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds.

This device contains multiple transmitters that may operate simultaneously, and therefore requires a simultaneous transmission analysis according to FCC KDB Publication 447498 D01v06 4.3.2 procedures.

Table 1-2
Simultaneous Transmission Scenarios

No.	Capable Transmit Configuration	Body
1	2.4 GHz Wi-Fi MIMO	Yes
2	2.4 GHz Bluetooth TxBF	Yes
3	5GHz Wi-Fi MIMO	Yes
4	2.4 GHz Bluetooth Antenna WF7b + 2.4 GHz Wi-Fi Antenna WF8	Yes
5	2.4 GHz Bluetooth + 5 GHz Wi-Fi	Yes
6	2.4 GHz Bluetooth + 5 GHz Wi-Fi MIMO	Yes
7	2.4 GHz Bluetooth TxBF + 5 GHz Wi-Fi	Yes
8	2.4 GHz Bluetooth TxBF + 5 GHz Wi-Fi MIMO	Yes

1. Wi-Fi 2.4 GHz and Bluetooth 2.4 GHz can transmit simultaneously on separate antennas. 2.4 GHz WLAN Antenna WF8 can only transmit simultaneously with 2.4 GHz Bluetooth Antenna WF7b. In this scenario Wi-Fi max powers will not exceed minimum of (13.5dBm, SAR max cap, Reg max cap) power.
2. 2.4GHz WLAN and 5 GHz WLAN cannot transmit simultaneously.
3. This device supports 2x2 MIMO Tx for WLAN 802.11a/g/n/ac/ax. 802.11a/g/n/ac/ax supports CDD and STBC and 802.11n/ac/ax additionally supports SDM. Each WLAN antenna can transmit independently or together when operating with MIMO.
4. This device supports VOWIFI.

FCC ID: BCGA2588	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 14 of 52

1.6 Miscellaneous SAR Test Considerations

(A) WIFI/BT

Based on the maximum allowed power for the respective antennas, U-NII-2A was evaluated for Antenna WF8 and Antenna 7a SAR. Additional testing for U-NII-1 Antenna WF8 and Antenna WF7a SAR was not required since all reported SAR was less than 1.2 W/kg per FCC KDB Publication 248227 D01v02r02.

The WLAN/Bluetooth chipset in this device is produced by two different suppliers. The electrically identical modules are manufactured with the identical mechanical structure to meet the same specifications and functions. Two device variants are referenced as Variant 1 and Variant 2 in this report. WLAN/Bluetooth SAR worst case configuration was spot-checked on Variant 1 and Variant 2.

This device supports channel 1-13 for 2.4 GHz WLAN. However, because channel 12/13 targets are not higher than that of channels 1-11, default channels for SAR testing are determined per FCC KDB 248227 D01V02r02.

This device supports IEEE 802.11ac with the following features:

- a) Up to 80 MHz Bandwidth only
- b) No aggregate channel configurations
- c) 2 Tx antenna output
- d) 256 QAM is supported
- e) TDWR and Band gap channels are supported

This device supports IEEE 802.11ax with the following features:

- a) Up to 80 MHz Bandwidth only for 5 GHz
- b) Up to 20 MHz Bandwidth only for 2.4 GHz
- c) No aggregate channel configurations
- d) 2 Tx antenna output
- e) Up to 1024 QAM is supported
- f) TDWR and Band gap channels are supported for 5 GHz
- g) MU-MIMO UL Operations are not supported

Per April 2019 TCB Workshop Notes, SAR testing was not required for 802.11ax when applying the initial test configuration procedures of KDB 248227, with 802.11ax considered a higher order 802.11 mode.

1.7 Guidance Applied

- IEEE 1528-2013
- FCC KDB Publication 248227 D01v02r02 (SAR Considerations for 802.11 Devices)
- FCC KDB Publication 447498 D01v06 (General SAR Guidance)
- FCC KDB Publication 865664 D01v01r04, D02v01r02 (SAR Measurements up to 6 GHz)
- FCC KDB Publication 616217 D04v01r02 (Tablet)
- April 2019 TCB Workshop Notes (IEEE 802.11ax)

1.8 Device Serial Numbers

Several samples with identical hardware were used to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units. The serial numbers used for each test are indicated alongside the results in Section 9.

FCC ID: BCGA2588	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C211150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 15 of 52

2 INTRODUCTION

The FCC and Innovation, Science, and Economic Development Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields,” Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

2.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 2-1).

Equation 2-1
SAR Mathematical Equation

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dv} \right)$$

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- σ = conductivity of the tissue-simulating material (S/m)
- ρ = mass density of the tissue-simulating material (kg/m³)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

FCC ID: BCGA2588	 PCTEST Proud to be part of Element	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 16 of 52

3 DOSIMETRIC ASSESSMENT

3.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface, and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01r04 (See Table 3-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01r04 (See Table 3-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual online for more details):
 - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 3-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
 - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the “Not a knot” condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.




Figure 3-1 point
Sample SAR Area
Scan

Table 3-1
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01r04*

Frequency	Maximum Area Scan Resolution (mm) ($\Delta x_{\text{area}}, \Delta y_{\text{area}}$)	Maximum Zoom Scan Resolution (mm) ($\Delta x_{\text{zoom}}, \Delta y_{\text{zoom}}$)	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid	Graded Grid		
			$\Delta z_{\text{zoom}}(n)$	$\Delta z_{\text{zoom}}(1)^*$	$\Delta z_{\text{zoom}}(n>1)^*$	
≤ 2 GHz	≤ 15	≤ 8	≤ 5	≤ 4	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 30
2-3 GHz	≤ 12	≤ 5	≤ 5	≤ 4	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 30
3-4 GHz	≤ 12	≤ 5	≤ 4	≤ 3	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 28
4-5 GHz	≤ 10	≤ 4	≤ 3	≤ 2.5	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 25
5-6 GHz	≤ 10	≤ 4	≤ 2	≤ 2	≤ 1.5* $\Delta z_{\text{zoom}}(n-1)$	≥ 22

*Also compliant to IEEE 1528-2013 Table 6

FCC ID: BCGA2588	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 17 of 52

4 TEST CONFIGURATION POSITIONS

4.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$.

4.2 SAR Testing for Tablet per KDB Publication 616217 D04v01r02

Per FCC KDB Publication 616217 D04v01r02, the back surface and edges of the tablet should be tested for SAR compliance with the tablet touching the phantom. The SAR Exclusion Threshold in KDB 447498 D01v06 can be applied to determine SAR test exclusion for adjacent edge configurations. The closest distance from the antenna to an adjacent tablet edge is used to determine if SAR testing is required for the adjacent edges, with the adjacent edge positioned against the phantom and the edge containing the antenna positioned perpendicular to the phantom.

FCC ID: BCGA2588	 PCTEST Proud to be part of  Element	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 18 of 52

5 RF EXPOSURE LIMITS

5.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

5.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 5-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
Peak Spatial Average SAR Head	1.6	8.0
Whole Body SAR	0.08	0.4
Peak Spatial Average SAR Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: BCGA2588	 PCTEST Proud to be part of Element		Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 19 of 52

6 FCC MEASUREMENT PROCEDURES

6.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D01v06, when SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r03.

6.2 SAR Testing with 802.11 Transmitters

The normal network operating configurations of 802.11 transmitters are not suitable for SAR measurements. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable. See KDB Publication 248227 D01v02r02 for more details.

6.2.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters.

A periodic duty factor is required for current generation SAR systems to measure SAR. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. The reported SAR is scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

6.2.2 U-NII-1 and U-NII-2A

For devices that operate in both U-NII-1 and U-NII-2A bands, when the same maximum output power is specified for both bands, SAR measurement using OFDM SAR test procedures is not required for U-NII-1 unless the highest reported SAR for U-NII-2A is > 1.2 W/kg. When different maximum output powers are specified for the bands, SAR measurement for the U-NII band with the lower maximum output power is not required unless the highest reported SAR for the U-NII band with the higher maximum output power, adjusted by the ratio of lower to higher specified maximum output power for the two bands, is > 1.2 W/kg.

6.2.3 U-NII-2C and U-NII-3

The frequency range covered by U-NII-2C and U-NII-3 is 380 MHz (5.47 – 5.85 GHz), which requires a minimum of at least two SAR probe calibration frequency points to support SAR measurements. When Terminal Doppler Weather Radar (TDWR) restriction applies, the channels at 5.60 – 5.65 GHz in U-NII-2C band must be disabled with acceptable mechanisms and documented in the equipment certification. Unless band gap channels are permanently disabled, SAR must be considered for these channels. Each band is tested independently according to the normally required OFDM SAR measurement and probe calibration frequency points requirements.

FCC ID: BCGA2588	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 20 of 52

6.2.4 2.4 GHz SAR Test Requirements

SAR is measured for 2.4 GHz 802.11b DSSS using either the fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- 1) When the reported SAR of the highest measured maximum output power channel for the exposure configuration is ≤ 0.8 W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- 2) When the reported SAR is > 0.8 W/kg, SAR is required for that position using the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel, i.e., all channels require testing.

2.4 GHz 802.11 g/n/ax OFDM are additionally evaluated for SAR if the highest reported SAR for 802.11b, adjusted by the ratio of the OFDM to DSSS specified maximum output power, is > 1.2 W/kg. When SAR is required for OFDM modes in 2.4 GHz band, the Initial Test Configuration Procedures should be followed.

6.2.5 OFDM Transmission Mode and SAR Test Channel Selection

When the same maximum output power was specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration with the largest channel bandwidth, lowest order modulation and lowest data rate. When the maximum output power of a channel is the same for equivalent OFDM configurations; for example, 802.11a, 802.11n and 802.11ac or 802.11g and 802.11n with the same channel bandwidth, modulation, and data rate etc., the lower order 802.11 mode i.e., 802.11a, then 802.11n and 802.11ac or 802.11g then 802.11n, is used for SAR measurement. Per April 2019 TCB Workshop guidance, 802.11ax was considered the highest order 802.11 mode. When the maximum output power are the same for multiple test channels, either according to the default or additional power measurement requirements, SAR is measured using the channel closest to the middle of the frequency band or aggregated band. When there are multiple channels with the same maximum output power, SAR is measured using the higher number channel.

6.2.6 Initial Test Configuration Procedure

For OFDM, an initial test configuration is determined for each frequency band and aggregated band, according to the transmission mode with the highest maximum output power specified for SAR measurements. When the same maximum output power is specified for multiple OFDM transmission mode configurations in a frequency band or aggregated band, SAR is measured using the configuration(s) with the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order IEEE 802.11 mode. The channel of the transmission mode with the highest average RF output conducted power will be the initial test configuration.

When the reported SAR is ≤ 0.8 W/kg, no additional measurements on other test channels are required. Otherwise, SAR is evaluated using the subsequent highest average RF output channel until the reported SAR result is ≤ 1.2 W/kg or all channels are measured. When there are multiple untested channels having the same subsequent highest average RF output power, the channel with higher frequency from the lowest 802.11 mode is considered for SAR measurements (See Section 6.2.5).

FCC ID: BCGA2588	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 21 of 52

6.2.7 Subsequent Test Configuration Procedures

For OFDM configurations in each frequency band and aggregated band, SAR is evaluated for initial test configuration using the fixed test position or the initial test position procedure. When the highest reported SAR (for the initial test configuration), adjusted by the ratio of the specified maximum output power of the subsequent test configuration to initial test configuration, is ≤ 1.2 W/kg, no additional SAR tests for the subsequent test configurations are required.

6.2.8 MIMO SAR considerations

Per KDB Publication 248227 D01v02r02, the simultaneous SAR provisions in KDB Publication 447498 D01v06 should be applied to determine simultaneous transmission SAR test exclusion for WIFI MIMO. If the sum of 1g single transmission chain SAR measurements is < 1.6 W/kg, no additional SAR measurements for MIMO are required. Alternatively, SAR for MIMO can be measured with all antennas transmitting simultaneously at the specified maximum output power of MIMO operation.

FCC ID: BCGA2588	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 22 of 52

7 RF CONDUCTED POWERS

7.1 WLAN Conducted Powers

Table 7-1
2.4 GHz WLAN Maximum Average RF Power – Ant WF8, Variant 1

2.4GHz Conducted Power [dBm]					
Freq [MHz]	Channel	IEEE Transmission Mode			
		802.11b	802.11g	802.11n	802.11ax (SU)
		Average	Average	Average	Average
2412	1	19.10	14.35	14.33	13.51
2417	2	20.16	N/A	N/A	N/A
2437	6	20.17	20.42	20.55	20.36
2462	11	20.11	16.15	16.22	15.48

Table 7-2
2.4 GHz WLAN Maximum Average RF Power – Ant WF8, Variant 2

2.4GHz Conducted Power [dBm]					
Freq [MHz]	Channel	IEEE Transmission Mode			
		802.11b	802.11g	802.11n	802.11ax (SU)
		Average	Average	Average	Average
2412	1	19.00	14.23	14.21	13.56
2417	2	20.18	N/A	N/A	N/A
2437	6	20.02	20.40	20.35	20.10
2462	11	19.83	16.25	16.23	15.40

FCC ID: BCGA2588	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 23 of 52

Table 7-3
2.4 GHz WLAN Maximum Average RF Power – Ant WF7b, Variant 1

2.4GHz Conducted Power [dBm]					
Freq [MHz]	Channel	IEEE Transmission Mode			
		802.11b	802.11g	802.11n	802.11ax (SU)
		Average	Average	Average	Average
2412	1	18.70	14.17	14.20	13.64
2417	2	18.83	N/A	N/A	N/A
2437	6	19.01	19.43	19.41	19.35
2462	11	18.87	16.20	16.18	15.43

Table 7-4
2.4 GHz WLAN Maximum Average RF Power – Ant WF7b, Variant 2

2.4GHz Conducted Power [dBm]					
Freq [MHz]	Channel	IEEE Transmission Mode			
		802.11b	802.11g	802.11n	802.11ax (SU)
		Average	Average	Average	Average
2412	1	18.72	14.18	14.16	13.70
2417	2	19.05	N/A	N/A	N/A
2437	6	18.98	19.42	19.40	19.43
2462	11	19.15	16.16	16.20	15.49

Table 7-5
5 GHz WLAN Maximum Average RF Power – Ant WF8, Variant 1

5GHz (40MHz) Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11n	802.11ac	802.11ax (SU)
		Average	Average	Average
5190	38	15.14	15.28	12.90
5230	46	16.33	16.22	16.17
5270	54	17.59	17.55	17.45
5310	62	15.00	15.15	14.10

5GHz (80MHz) Conducted Power [dBm]			
Freq [MHz]	Channel	IEEE Transmission Mode	
		802.11ac	802.11ax (SU)
		Average	Average
5530	106	13.04	12.63
5610	122	16.10	16.70
5690	138	15.82	16.72
5775	155	16.42	16.61

FCC ID: BCGA2588	 PCTEST Proud to be part of Element	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 24 of 52

Table 7-6
5 GHz WLAN Maximum Average RF Power – Ant WF8, Variant 2

5GHz (40MHz) Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11n	802.11ac	802.11ax (SU)
		Average	Average	Average
5190	38	14.94	15.25	12.95
5230	46	16.20	16.17	16.12
5270	54	17.35	17.23	17.46
5310	62	15.13	15.37	14.09

5GHz (80MHz) Conducted Power [dBm]			
Freq [MHz]	Channel	IEEE Transmission Mode	
		802.11ac	802.11ax (SU)
		Average	Average
5530	106	13.00	12.76
5610	122	15.81	16.65
5690	138	15.85	16.70
5775	155	16.30	16.76

Table 7-7
5 GHz WLAN Maximum Average RF Power – Ant WF7a, Variant 1

5GHz (40MHz) Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11n	802.11ac	802.11ax (SU)
		Average	Average	Average
5190	38	14.91	15.21	12.98
5230	46	15.23	15.29	15.08
5270	54	15.47	15.66	16.06
5310	62	15.09	15.11	13.97

5GHz (80MHz) Conducted Power [dBm]			
Freq [MHz]	Channel	IEEE Transmission Mode	
		802.11ac	802.11ax (SU)
		Average	Average
5530	106	13.33	12.60
5610	122	14.55	14.40
5690	138	14.44	14.51
5775	155	14.95	15.55

FCC ID: BCGA2588	 PCTEST Proud to be part of Element	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 25 of 52

Table 7-8
5 GHz WLAN Maximum Average RF Power – Ant WF7a, Variant 2

5GHz (40MHz) Conducted Power [dBm]				
Freq [MHz]	Channel	IEEE Transmission Mode		
		802.11n	802.11ac	802.11ax (SU)
		Average	Average	Average
5190	38	15.00	15.15	12.93
5230	46	15.14	15.22	15.27
5270	54	15.48	15.73	15.84
5310	62	15.05	15.32	13.90

5GHz (80MHz) Conducted Power [dBm]			
Freq [MHz]	Channel	IEEE Transmission Mode	
		802.11ac	802.11ax (SU)
		Average	Average
5530	106	13.37	12.70
5610	122	14.60	14.50
5690	138	14.50	14.55
5775	155	15.02	15.40

Table 7-9
5 GHz WLAN Maximum Average RF Power – Ant WF8 and Ant WF7a MIMO, Variant 1

5GHz (40MHz) 802.11n Conducted Power [dBm]				
Freq [MHz]	Channel	ANT WF8	ANT WF7a	MIMO
5190	38	12.02	11.99	15.02
5230	46	16.33	15.21	18.82
5270	54	17.55	16.18	19.93
5310	62	12.96	13.10	16.04

5GHz (80MHz) 802.11ac Conducted Power [dBm]				
Freq [MHz]	Channel	ANT WF8	ANT WF7a	MIMO
5530	106	11.63	11.43	14.54
5610	122	16.69	14.41	18.71
5690	138	16.71	14.44	18.73
5775	155	16.70	15.53	19.16

FCC ID: BCGA2588	 PCTEST Proud to be part of Element	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 26 of 52

Table 7-10
5 GHz WLAN Maximum Average RF Power – Ant WF8 and Ant WF7a MIMO, Variant 2

5GHz (40MHz) 802.11n Conducted Power [dBm]				
Freq [MHz]	Channel	ANT WF8	ANT WF7a	MIMO
5190	38	12.02	11.91	14.98
5230	46	16.25	15.27	18.80
5270	54	17.65	16.15	19.97
5310	62	13.12	13.09	16.12
5GHz (80MHz) 802.11ac Conducted Power [dBm]				
Freq [MHz]	Channel	ANT WF8	ANT WF7a	MIMO
5530	106	11.64	11.50	14.58
5610	122	16.72	14.49	18.76
5690	138	16.79	14.53	18.82
5775	155	16.76	15.81	19.32

7.1.1 Notes for WLAN

Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02:

- Power measurements were performed for the transmission mode configuration with the highest maximum output power specified for production units.
- For transmission modes with the same maximum output power specification, powers were measured for the largest channel bandwidth, lowest order modulation and lowest data rate.
- For transmission modes with identical maximum specified output power, channel bandwidth, modulation and data rates, power measurements were required for all identical configurations.
- For each transmission mode configuration, powers were measured for the highest and lowest channels; and at the mid-band channel(s) when there were at least 3 channels supported. For configurations with multiple mid-band channels, due to an even number of channels, both channels were measured.
- The WLAN chipset in this device is produced by two different suppliers. The electrically identical modules are manufactured with the identical mechanical structure to meet the same specifications and functions. Two device variants are referenced as Variant 1 and Variant 2 in this report.
- The worst case configurations were evaluated for both variant 1 and variant 2.




Figure 7-1
Power Measurement Setup

FCC ID: BCGA2588	 PCTEST Proud to be part of Element	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device		Page 27 of 52

7.2 Bluetooth Conducted Powers

Table 7-11
Maximum Bluetooth Average RF Power – Antenna WF8, Variant 1

Frequency [MHz]	Modulation	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
				[dBm]	[mW]
2402	GFSK	1.0	0	18.76	75.162
2441	GFSK	1.0	39	18.90	77.625
2480	GFSK	1.0	78	18.97	78.886

Table 7-12
Maximum Bluetooth Average RF Power – Antenna WF8, Variant 2

Frequency [MHz]	Modulation	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
				[dBm]	[mW]
2402	GFSK	1.0	0	18.88	77.268
2441	GFSK	1.0	39	19.02	79.799
2480	GFSK	1.0	78	19.20	83.176

FCC ID: BCGA2588	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 28 of 52

Table 7-13
Maximum Bluetooth Average RF Power – Antenna WF7b, Variant 1

Frequency [MHz]	Modulation	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
				[dBm]	[mW]
2402	GFSK	1.0	0	19.05	80.353
2441	GFSK	1.0	39	19.16	82.414
2480	GFSK	1.0	78	18.93	78.163

Table 7-14
Maximum Bluetooth Average RF Power – Antenna WF7b, Variant 2

Frequency [MHz]	Modulation	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
				[dBm]	[mW]
2402	GFSK	1.0	0	19.22	83.560
2441	GFSK	1.0	39	19.19	82.985
2480	GFSK	1.0	78	19.12	81.658

FCC ID: BCGA2588	 PCTEST Proud to be part of Element	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 29 of 52

Table 7-15
Reduced Bluetooth Average RF Power – Antenna WF8, Variant 1

Frequency [MHz]	Modulation	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
				[dBm]	[mW]
2402	GFSK	1.0	0	11.84	15.276
2441	GFSK	1.0	39	11.98	15.776
2480	GFSK	1.0	78	11.93	15.596

Table 7-16
Reduced Bluetooth Average RF Power – Antenna WF8, Variant 2

Frequency [MHz]	Modulation	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
				[dBm]	[mW]
2402	GFSK	1.0	0	12.20	16.596
2441	GFSK	1.0	39	12.38	17.298
2480	GFSK	1.0	78	12.40	17.378

FCC ID: BCGA2588	 PCTEST Proud to be part of Element	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 30 of 52

Table 7-17
Reduced Bluetooth Average RF Power – Antenna WF7b, Variant 1

Frequency [MHz]	Modulation	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
				[dBm]	[mW]
2402	GFSK	1.0	0	11.99	15.812
2441	GFSK	1.0	39	11.96	15.704
2480	GFSK	1.0	78	12.00	15.849

Table 7-18
Reduced Bluetooth Average RF Power – Antenna WF7b, Variant 2

Frequency [MHz]	Modulation	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
				[dBm]	[mW]
2402	GFSK	1.0	0	12.09	16.181
2441	GFSK	1.0	39	11.91	15.524
2480	GFSK	1.0	78	12.11	16.255

FCC ID: BCGA2588	 PCTEST Proud to be part of Element	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 31 of 52

7.3.2 Maximum Bluetooth Transmission Antenna WF8 Variant 2




Figure 7-3
Bluetooth Transmission Plot – Antenna WF8, Variant 2

Equation 7-2
Bluetooth Duty Cycle Calculation – Antenna WF8, Variant 2

$$\text{Duty Cycle} = \frac{\text{Pulse Width}}{\text{Period}} * 100\% = \frac{2.880 \text{ ms}}{3.750 \text{ ms}} * 100\% = 76.8\%$$

FCC ID: BCGA2588	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 33 of 52

7.3.3 Maximum Bluetooth Transmission Antenna WF7b Variant 1




Figure 7-4
Bluetooth Transmission Plot – Antenna WF7b, Variant 1

Equation 7-3 Bluetooth Duty Cycle Calculation – Antenna WF7b, Variant 1

$$\text{Duty Cycle} = \frac{\text{Pulse Width}}{\text{Period}} * 100\% = \frac{2.880 \text{ ms}}{3.750 \text{ ms}} * 100\% = 76.8\%$$

FCC ID: BCGA2588	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 34 of 52

7.3.4 Maximum Bluetooth Transmission Antenna WF7b Variant 2




Figure 7-5
Bluetooth Transmission Plot – Antenna WF7b, Variant 2

Equation 7-4
Bluetooth Duty Cycle Calculation – Antenna WF7b, Variant 2

$$\text{Duty Cycle} = \frac{\text{Pulse Width}}{\text{Period}} * 100\% = \frac{2.880 \text{ ms}}{3.750 \text{ ms}} * 100\% = 76.8\%$$

FCC ID: BCGA2588	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 35 of 52

7.4 Bluetooth Power Reduction Verification Summary

Antenna	Mode/Band	Condition (s)	Maximum Target Power [dBm]	Reduced Target Power [dBm]	Maximum Measured Power	Reduced Measured Power	Verdict
			(Tolerance [dB])	(Tolerance [dB])	[dBm]	[dBm]	
WF8	2.4 GHz Bluetooth	5 GHz WLAN ON Antenna WF8	18.00 (+1.5/-2)	11.00 (+1.5/-2)	19.49	12.46	Pass
	2.4 GHz Bluetooth	5 GHz WLAN ON Antenna WF7a	18.00 (+1.5/-2)	11.00 (+1.5/-2)	19.49	12.49	Pass
	2.4 GHz Bluetooth	5 GHz WLAN ON ANT WF8 & WF7a	18.00 (+1.5/-2)	11.00 (+1.5/-2)	19.49	12.49	Pass
WF7b	2.4 GHz Bluetooth	5 GHz WLAN ON Antenna WF8	18.50 (+1.5/-2)	11.50 (+1.5/-2)	19.77	12.63	Pass
	2.4 GHz Bluetooth	5 GHz WLAN ON Antenna WF7a	18.50 (+1.5/-2)	11.50 (+1.5/-2)	19.77	12.42	Pass
	2.4 GHz Bluetooth	5 GHz WLAN ON ANT WF8 & WF7a	18.50 (+1.5/-2)	11.50 (+1.5/-2)	19.77	12.42	Pass

Conducted powers were measured for each Mode/Band and applied condition. All conducted power measurements were verified to be within tolerance.

7.5 Notes for Bluetooth

- The Bluetooth chipset in this device is produced by two different suppliers. The electrically identical modules are manufactured with the identical mechanical structure to meet the same specifications and functions. Two device variants are referenced as Variant 1 and Variant 2 in this report.
- Bluetooth SAR worst case configuration was spotchecked on Variant 1 and Variant 2.
- Full power measurements were performed for Variant 1 and Variant 2 per FCC KDB Procedures 248227.




Figure 7-6
Power Measurement Setup

FCC ID: BCGA2588	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 36 of 52

8 SYSTEM VERIFICATION

8.1 Tissue Verification

Table 8-1
Measured Tissue Properties

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
12/14/2021	2450 Body	20.5	2300	1.833	55.054	1.809	52.900	1.33%	4.07%
			2310	1.843	55.047	1.816	52.887	1.49%	4.08%
			2320	1.853	55.038	1.826	52.873	1.48%	4.09%
			2400	1.932	54.961	1.902	52.767	1.58%	4.16%
			2450	1.982	54.896	1.950	52.700	1.64%	4.17%
			2480	2.013	54.864	1.993	52.662	1.00%	4.18%
			2500	2.034	54.848	2.021	52.636	0.64%	4.20%
			2510	2.044	54.838	2.035	52.623	0.44%	4.21%
			2535	2.070	54.800	2.071	52.592	-0.05%	4.20%
			2550	2.086	54.775	2.092	52.573	-0.29%	4.19%
			2560	2.097	54.761	2.106	52.560	-0.43%	4.19%
			2600	2.142	54.718	2.163	52.509	-0.97%	4.21%
			2650	2.195	54.628	2.234	52.445	-1.75%	4.16%
			2680	2.229	54.579	2.277	52.407	-2.11%	4.14%
			2700	2.250	54.542	2.305	52.382	-2.39%	4.12%
			2300	1.818	52.742	1.809	52.900	0.50%	-0.30%
			2310	1.831	52.703	1.816	52.887	0.53%	-0.35%
			2320	1.844	52.663	1.826	52.873	0.99%	-0.40%
			2400	1.952	52.342	1.902	52.767	2.63%	-0.81%
			2450	2.015	52.138	1.950	52.700	3.33%	-1.07%
01/05/2022	2450 Body	23.0	2480	2.057	52.016	1.993	52.662	3.21%	-1.23%
			2500	2.083	51.947	2.021	52.636	3.07%	-1.31%
			2510	2.097	51.912	2.035	52.623	3.05%	-1.35%
			2535	2.129	51.812	2.071	52.592	2.80%	-1.48%
			2550	2.149	51.749	2.092	52.573	2.72%	-1.57%
			2560	2.163	51.710	2.106	52.560	2.71%	-1.62%
			2600	2.219	51.561	2.163	52.509	2.39%	-1.81%
			2650	2.288	51.355	2.234	52.445	2.42%	-2.08%
			2680	2.332	51.241	2.277	52.407	2.42%	-2.22%
			2700	2.359	51.163	2.305	52.382	2.34%	-2.33%
			5180	5.261	48.150	5.276	49.041	-0.28%	-1.82%
			5190	5.274	48.133	5.288	49.028	-0.26%	-1.83%
			5200	5.285	48.117	5.299	49.014	-0.26%	-1.83%
			5210	5.298	48.090	5.311	49.001	-0.24%	-1.86%
			5220	5.311	48.059	5.323	48.987	-0.23%	-1.89%
			5240	5.340	47.990	5.346	48.960	-0.11%	-1.98%
			5250	5.354	47.965	5.359	48.947	-0.07%	-2.00%
			5260	5.370	47.931	5.369	48.933	0.02%	-2.05%
			5270	5.384	47.902	5.381	48.919	0.06%	-2.08%
			5280	5.397	47.886	5.393	48.906	0.07%	-2.09%
01/10/2022	5200-5800 Body	20.9	5290	5.408	47.879	5.404	48.892	0.07%	-2.07%
			5300	5.420	47.877	5.416	48.879	0.07%	-2.05%
			5310	5.435	47.860	5.428	48.865	0.13%	-2.06%
			5320	5.453	47.824	5.439	48.851	0.26%	-2.10%
			5500	5.736	47.528	5.650	48.607	1.52%	-2.22%
			5510	5.752	47.513	5.661	48.594	1.61%	-2.22%
			5520	5.766	47.501	5.673	48.580	1.64%	-2.22%
			5530	5.774	47.486	5.685	48.566	1.57%	-2.22%
			5540	5.789	47.465	5.696	48.553	1.63%	-2.24%
			5550	5.808	47.431	5.708	48.539	1.75%	-2.28%
			5560	5.829	47.406	5.720	48.526	1.91%	-2.31%
			5580	5.855	47.399	5.743	48.499	1.95%	-2.27%
			5600	5.879	47.379	5.766	48.471	1.96%	-2.25%
			5610	5.889	47.358	5.778	48.458	1.92%	-2.27%
			5620	5.899	47.324	5.790	48.444	1.88%	-2.31%
			5640	5.932	47.260	5.813	48.417	2.05%	-2.39%
			5660	5.964	47.220	5.837	48.390	2.18%	-2.42%
			5670	5.973	47.212	5.848	48.376	2.14%	-2.41%
			5680	5.984	47.203	5.860	48.363	2.12%	-2.40%
			5690	5.995	47.178	5.872	48.349	2.09%	-2.42%
			5700	6.005	47.148	5.883	48.336	2.07%	-2.46%
			5710	6.016	47.117	5.895	48.322	2.05%	-2.49%
			5720	6.027	47.062	5.907	48.309	2.03%	-2.58%
			5745	6.066	47.005	5.936	48.275	2.19%	-2.63%
			5750	6.074	47.004	5.942	48.268	2.22%	-2.62%
			5755	6.083	47.002	5.947	48.261	2.29%	-2.61%
			5765	6.099	46.992	5.959	48.248	2.35%	-2.60%
			5775	6.108	46.973	5.971	48.234	2.29%	-2.61%
			5785	6.122	46.955	5.982	48.220	2.34%	-2.62%
			5795	6.137	46.912	5.994	48.207	2.39%	-2.69%
			5800	6.146	46.895	6.000	48.200	2.43%	-2.71%
			5805	6.153	46.875	6.006	48.193	2.45%	-2.73%
			5825	6.178	46.803	6.029	48.166	2.47%	-2.83%
			5835	6.192	46.784	6.042	48.130	2.48%	-2.80%
			5845	6.209	46.763	6.054	48.110	2.56%	-2.76%
			5865	6.248	46.763	6.077	48.080	2.81%	-2.74%
			5875	6.267	46.735	6.088	48.067	2.94%	-2.77%
			5885	6.286	46.712	6.100	48.053	3.05%	-2.79%
			5905	6.313	46.678	6.122	48.027	3.12%	-2.81%

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 D01v01r04 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

FCC ID: BCGA2588	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 37 of 52

8.2 Test System Verification

Prior to SAR assessment, the system is verified to $\pm 10\%$ of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix D.

Table 8-2
System Verification Results – 1g

System Verification TARGET & MEASURED												
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Source SN	Probe SN	Measured SAR _{1g} (W/kg)	1 W Target SAR _{1g} (W/kg)	1 W Normalized SAR _{1g} (W/kg)	Deviation _{1g} (%)
AM1	2450	BODY	12/14/2021	20.7	19.2	0.10	750	3837	4.830	51.000	48.300	-5.29%
AM6	2450	BODY	01/05/2022	23.1	21.9	0.10	750	7416	5.180	51.000	51.800	1.57%
AM2	5250	BODY	01/10/2022	21.9	20.6	0.05	1163	7532	3.750	76.300	75.000	-1.70%
AM2	5600	BODY	01/10/2022	21.9	20.6	0.05	1163	7532	3.990	79.600	79.800	0.25%
AM2	5750	BODY	01/10/2022	21.9	20.6	0.05	1163	7532	3.720	76.300	74.400	-2.49%




Figure 8-1
System Verification Setup Diagram



Figure 8-2
System Verification Setup Photo

FCC ID: BCGA2588	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 38 of 52

9 SAR DATA SUMMARY

9.1 Standalone Body SAR Data

Table 9-1
2.4 GHz WLAN Body SAR Data – Antenna WF8

MEASUREMENT RESULTS																					
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Variant	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (1g) (W/kg)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.																	(W/kg)	(W/kg)	(W/kg)	
2437	6	802.11b	DSSS	22	21.50	20.17	-0.07	0 mm	Ant WF8	V1	DYD1QHGMV6	1	back	99.7	0.106	1.358	1.003	0.144	0.056	0.076	A1
2417	2	802.11b	DSSS	22	21.50	20.16	0.02	0 mm	Ant WF8	V1	DYD1QHGMV6	1	top	99.7	0.858	1.361	1.003	1.171	0.374	0.511	
2417	2	802.11b	DSSS	22	21.50	20.18	0.00	0 mm	Ant WF8	V2	NN6CYM/Q22	1	top	99.7	0.765	1.355	1.003	1.040	0.341	0.463	
2437	6	802.11b	DSSS	22	21.50	20.17	0.02	0 mm	Ant WF8	V1	DYD1QHGMV6	1	top	99.7	0.812	1.358	1.003	1.106	0.363	0.494	
2462	11	802.11b	DSSS	22	21.50	20.11	-0.01	0 mm	Ant WF8	V1	DYD1QHGMV6	1	top	99.7	0.821	1.377	1.003	1.134	0.366	0.505	
2437	6	802.11b	DSSS	22	21.50	20.17	-0.12	0 mm	Ant WF8	V1	DYD1QHGMV6	1	bottom	99.7	0.011	1.358	1.003	0.015	0.004	0.005	
2437	6	802.11b	DSSS	22	21.50	20.17	-0.01	0 mm	Ant WF8	V1	DYD1QHGMV6	1	right	99.7	0.029	1.358	1.003	0.040	0.015	0.020	
2437	6	802.11b	DSSS	22	21.50	20.17	-0.14	0 mm	Ant WF8	V1	DYD1QHGMV6	1	left	99.7	0.003	1.358	1.003	0.004	0.000	0.000	
2417	2	802.11b	DSSS	22	21.50	20.16	0.00	0 mm	Ant WF8	V1	DYD1QHGMV6	1	top	99.7	0.848	1.361	1.003	1.158	0.368	0.502	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body													
Spatial Peak								1.6 W/kg (mW/g)													
Uncontrolled Exposure/General Population								averaged over 1 gram													

Note: Blue entry indicates variability measurement.

Table 9-2
2.4 GHz WLAN Body SAR Data – Antenna WF7b

MEASUREMENT RESULTS																					
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Variant	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.														(W/kg)			(W/kg)		(W/kg)	
2437	6	802.11b	DSSS	22	20.50	19.01	0.01	0 mm	Ant WF7b	V1	R39RQP9FH6	1	back	99.7	0.110	1.409	1.003	0.155	0.057	0.081	
2417	2	802.11b	DSSS	22	20.50	18.83	0.01	0 mm	Ant WF7b	V1	R39RQP9FH6	1	top	99.7	0.734	1.469	1.003	1.081	0.308	0.454	
2437	6	802.11b	DSSS	22	20.50	19.01	0.00	0 mm	Ant WF7b	V1	R39RQP9FH6	1	top	99.7	0.769	1.409	1.003	1.087	0.331	0.468	
2462	11	802.11b	DSSS	22	20.50	18.87	0.20	0 mm	Ant WF7b	V1	R39RQP9FH6	1	top	99.7	0.785	1.455	1.003	1.146	0.333	0.486	
2462	11	802.11b	DSSS	22	20.50	19.15	0.00	0 mm	Ant WF7b	V2	NN6CYM/Q22	1	top	99.7	0.742	1.365	1.003	1.016	0.315	0.431	
2437	6	802.11b	DSSS	22	20.50	19.01	-0.05	0 mm	Ant WF7b	V1	R39RQP9FH6	1	bottom	99.7	0.007	1.409	1.003	0.010	0.002	0.003	
2437	6	802.11b	DSSS	22	20.50	19.01	-0.20	0 mm	Ant WF7b	V1	R39RQP9FH6	1	right	99.7	0.015	1.409	1.003	0.021	0.005	0.007	
2417	2	802.11b	DSSS	22	20.50	18.83	-0.02	0 mm	Ant WF7b	V1	R39RQP9FH6	1	left	99.7	0.622	1.469	1.003	0.916	0.266	0.392	
2437	6	802.11b	DSSS	22	20.50	19.01	0.00	0 mm	Ant WF7b	V1	R39RQP9FH6	1	left	99.7	0.651	1.409	1.003	0.920	0.283	0.400	
2462	11	802.11b	DSSS	22	20.50	18.87	0.01	0 mm	Ant WF7b	V1	R39RQP9FH6	1	left	99.7	0.608	1.455	1.003	0.887	0.267	0.390	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body													
Spatial Peak								1.6 W/kg (mW/g)													
Uncontrolled Exposure/General Population								averaged over 1 gram													

FCC ID: BCGA2588	 PCTEST Proud to be part of Element		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 39 of 52	

Table 9-3
5 GHz WLAN Body SAR Data – Antenna WF8

MEASUREMENT RESULTS																					
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Variant	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.														(W/kg)			(W/kg)	(W/kg)		
5270	54	802.11n	OFDM	40	18.50	17.59	-0.09	0 mm	Ant WF8	V1	JL9W2R3Q76	13.5	back	97.9	0.088	1.233	1.021	0.111	0.035	0.044	
5270	54	802.11n	OFDM	40	18.50	17.59	0.03	0 mm	Ant WF8	V1	JL9W2R3Q76	13.5	top	97.9	0.882	1.233	1.021	1.110	0.276	0.347	
5270	54	802.11n	OFDM	40	18.50	17.35	0.00	0 mm	Ant WF8	V2	H94J6TMQXF	13.5	top	97.9	0.744	1.303	1.021	0.990	0.234	0.311	
5310	62	802.11n	OFDM	40	16.50	15.00	0.03	0 mm	Ant WF8	V1	JL9W2R3Q76	13.5	top	97.9	0.465	1.413	1.021	0.671	0.146	0.211	
5270	54	802.11n	OFDM	40	18.50	17.59	-0.07	0 mm	Ant WF8	V1	JL9W2R3Q76	13.5	bottom	97.9	0.021	1.233	1.021	0.026	0.003	0.004	
5270	54	802.11n	OFDM	40	18.50	17.59	0.20	0 mm	Ant WF8	V1	JL9W2R3Q76	13.5	right	97.9	0.027	1.233	1.021	0.034	0.006	0.008	
5270	54	802.11n	OFDM	40	18.50	17.59	0.10	0 mm	Ant WF8	V1	JL9W2R3Q76	13.5	left	97.9	0.001	1.233	1.021	0.001	0.000	0.000	
5690	138	802.11ac	OFDM	80	17.75	15.85	0.20	0 mm	Ant WF8	V2	H94J6TMQXF	29.3	back	95.4	0.046	1.549	1.048	0.075	0.016	0.026	
5530	106	802.11ac	OFDM	80	14.00	13.04	0.05	0 mm	Ant WF8	V1	R39RQP9FH6	29.3	top	95.4	0.353	1.247	1.048	0.461	0.104	0.136	
5610	122	802.11ac	OFDM	80	17.75	16.10	0.00	0 mm	Ant WF8	V1	R39RQP9FH6	29.3	top	95.4	0.742	1.462	1.048	1.137	0.219	0.336	
5690	138	802.11ac	OFDM	80	17.75	15.82	0.03	0 mm	Ant WF8	V1	R39RQP9FH6	29.3	top	95.4	0.725	1.560	1.048	1.185	0.214	0.350	
5690	138	802.11ac	OFDM	80	17.75	15.85	-0.05	0 mm	Ant WF8	V2	H94J6TMQXF	29.3	top	95.4	0.622	1.549	1.048	1.010	0.176	0.286	
5690	138	802.11ac	OFDM	80	17.75	15.85	0.20	0 mm	Ant WF8	V2	H94J6TMQXF	29.3	bottom	95.4	0.013	1.549	1.048	0.021	0.000	0.000	
5690	138	802.11ac	OFDM	80	17.75	15.85	-0.20	0 mm	Ant WF8	V2	H94J6TMQXF	29.3	right	95.4	0.020	1.549	1.048	0.032	0.002	0.003	
5690	138	802.11ac	OFDM	80	17.75	15.85	0.12	0 mm	Ant WF8	V2	H94J6TMQXF	29.3	left	95.4	0.000	1.549	1.048	0.000	0.000	0.000	
5775	155	802.11ac	OFDM	80	17.75	16.30	-0.20	0 mm	Ant WF8	V2	H94J6TMQXF	29.3	back	95.4	0.045	1.396	1.048	0.066	0.009	0.013	
5775	155	802.11ac	OFDM	80	17.75	16.42	-0.06	0 mm	Ant WF8	V1	R39RQP9FH6	29.3	top	95.4	0.808	1.358	1.048	1.150	0.224	0.319	
5775	155	802.11ac	OFDM	80	17.75	16.30	0.05	0 mm	Ant WF8	V2	H94J6TMQXF	29.3	top	95.4	0.692	1.396	1.048	1.012	0.197	0.288	
5775	155	802.11ac	OFDM	80	17.75	16.30	0.13	0 mm	Ant WF8	V2	H94J6TMQXF	29.3	bottom	95.4	0.010	1.396	1.048	0.015	0.002	0.003	
5775	155	802.11ac	OFDM	80	17.75	16.30	-0.10	0 mm	Ant WF8	V2	H94J6TMQXF	29.3	right	95.4	0.023	1.396	1.048	0.034	0.005	0.007	
5775	155	802.11ac	OFDM	80	17.75	16.30	-0.12	0 mm	Ant WF8	V2	H94J6TMQXF	29.3	left	95.4	0.002	1.396	1.048	0.003	0.000	0.000	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body													
Spatial Peak								1.6 W/kg (mW/g)													
Uncontrolled Exposure/General Population								averaged over 1 gram													

Table 9-4
5 GHz WLAN Body SAR Data – Antenna WF7a

MEASUREMENT RESULTS																					
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Variant	Device Serial Number	Data Rate [Mbps]	Side	Duty Cycle (%)	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.														(W/kg)			(W/kg)		(W/kg)	
5270	54	802.11n	OFDM	40	17.00	15.48	0.04	0 mm	Ant WF7a	V2	TX76GKGXF7	13.5	back	97.9	0.107	1.419	1.021	0.155	0.046	0.067	
5270	54	802.11n	OFDM	40	17.00	15.47	0.02	0 mm	Ant WF7a	V1	JL9W2R3Q76	13.5	top	97.9	0.803	1.422	1.021	1.166	0.279	0.405	
5270	54	802.11n	OFDM	40	17.00	15.48	0.04	0 mm	Ant WF7a	V2	TX76GKGXF7	13.5	top	97.9	0.801	1.419	1.021	1.160	0.274	0.397	
5310	62	802.11n	OFDM	40	16.50	15.09	0.00	0 mm	Ant WF7a	V1	JL9W2R3Q76	13.5	top	97.9	0.727	1.384	1.021	1.027	0.255	0.360	
5270	54	802.11n	OFDM	40	17.00	15.48	0.10	0 mm	Ant WF7a	V2	TX76GKGXF7	13.5	bottom	97.9	0.003	1.419	1.021	0.004	0.000	0.000	
5270	54	802.11n	OFDM	40	17.00	15.48	0.15	0 mm	Ant WF7a	V2	TX76GKGXF7	13.5	right	97.9	0.000	1.419	1.021	0.000	0.000	0.000	
5270	54	802.11n	OFDM	40	17.00	15.48	-0.15	0 mm	Ant WF7a	V2	TX76GKGXF7	13.5	left	97.9	0.016	1.419	1.021	0.023	0.003	0.004	
5610	122	802.11ac	OFDM	80	15.50	14.60	-0.14	0 mm	Ant WF7a	V2	H6154QQWGF	29.3	back	95.4	0.060	1.230	1.048	0.077	0.021	0.027	
5530	106	802.11ac	OFDM	80	14.00	13.37	0.02	0 mm	Ant WF7a	V2	H6154QQWGF	29.3	top	95.4	0.655	1.156	1.048	0.794	0.211	0.256	
5610	122	802.11ac	OFDM	80	15.50	14.55	-0.01	0 mm	Ant WF7a	V1	JL9W2R3Q76	29.3	top	95.4	0.787	1.245	1.048	1.027	0.255	0.333	
5610	122	802.11ac	OFDM	80	15.50	14.60	0.00	0 mm	Ant WF7a	V2	H6154QQWGF	29.3	top	95.4	0.887	1.230	1.048	1.143	0.303	0.391	
5690	138	802.11ac	OFDM	80	15.50	14.50	-0.11	0 mm	Ant WF7a	V2	H6154QQWGF	29.3	top	95.4	0.719	1.259	1.048	0.949	0.224	0.296	
5610	122	802.11ac	OFDM	80	15.50	14.60	0.13	0 mm	Ant WF7a	V2	H6154QQWGF	29.3	bottom	95.4	0.002	1.230	1.048	0.003	0.000	0.000	
5610	122	802.11ac	OFDM	80	15.50	14.60	0.15	0 mm	Ant WF7a	V2	H6154QQWGF	29.3	right	95.4	0.007	1.230	1.048	0.009	0.000	0.000	
5610	122	802.11ac	OFDM	80	15.50	14.60	0.10	0 mm	Ant WF7a	V2	H6154QQWGF	29.3	left	95.4	0.023	1.230	1.048	0.030	0.004	0.005	
5775	155	802.11ac	OFDM	80	16.50	15.02	-0.19	0 mm	Ant WF7a	V2	TX76GKGXF7	29.3	back	95.4	0.069	1.406	1.048	0.102	0.022	0.032	
5775	155	802.11ac	OFDM	80	16.50	14.95	-0.02	0 mm	Ant WF7a	V1	JL9W2R3Q76	29.3	top	95.4	0.758	1.429	1.048	1.135	0.237	0.355	
5775	155	802.11ac	OFDM	80	16.50	15.02	0.04	0 mm	Ant WF7a	V2	TX76GKGXF7	29.3	top	95.4	0.753	1.406	1.048	1.110	0.230	0.339	
5775	155	802.11ac	OFDM	80	16.50	15.02	-0.18	0 mm	Ant WF7a	V2	TX76GKGXF7	29.3	bottom	95.4	0.001	1.406	1.048	0.001	0.000	0.000	
5775	155	802.11ac	OFDM	80	16.50	15.02	0.18	0 mm	Ant WF7a	V2	TX76GKGXF7	29.3	right	95.4	0.000	1.406	1.048	0.000	0.000	0.000	
5775	155	802.11ac	OFDM	80	16.50	15.02	-0.20	0 mm	Ant WF7a	V2	TX76GKGXF7	29.3	left	95.4	0.009	1.406	1.048	0.013	0.000	0.000	
5610	122	802.11ac	OFDM	80	15.50	14.60	0.02	0 mm	Ant WF7a	V2	H6154QQWGF	29.3	top	95.4	0.875	1.230	1.048	1.128	0.283	0.365	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body													
Spatial Peak								1.6 W/kg (mW/g)													
Uncontrolled Exposure/General Population								averaged over 1 gram													

Note: Blue entry indicates variability measurement.

FCC ID: BCGA2588	 PCTEST Proud to be part of Element	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C211150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 40 of 52

Table 9-5
5 GHz WLAN Body SAR Data – MIMO

MEASUREMENT RESULTS																						
FREQUENCY		Mode	Service	Bandwidth [MHz]	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Cube	Power Drift [dB]	Spacing	Antenna Config.	Variant	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (1g)	Scaling Factor (Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.															(W/kg)			(W/kg)	(W/kg)		
5270	54	802.11n	OFDM	40	17.00	16.18	1	-0.02	0 mm	MIMO	V1	JL9W2R3Q76	13.5	top	97.9	0.960	1.208	1.021	1.184	0.341	0.421	
					18.50	17.55	2	0.08							97.9	0.837	1.245	1.021	1.064	0.272	0.346	
5270	54	802.11n	OFDM	40	17.00	16.15	1	0.08	0 mm	MIMO	V2	TX76GKGXF7	13.5	top	97.9	0.957	1.216	1.021	1.188	0.341	0.423	
					18.50	17.65	2	-0.03							97.9	0.899	1.216	1.021	1.116	0.298	0.370	
5310	62	802.11n	OFDM	40	14.25	13.09	1	-0.07	0 mm	MIMO	V2	TX76GKGXF7	13.5	top	97.9	0.479	1.306	1.021	0.639	0.167	0.223	
					14.25	13.12	2	0.00							97.9	0.309	1.297	1.021	0.409	0.101	0.134	
5530	106	802.11ac	OFDM	80	12.50	11.50	1	0.05	0 mm	MIMO	V2	TX76GKGXF7	29.3	top	95.4	0.344	1.259	1.048	0.454	0.112	0.148	
					12.50	11.64	2	-0.04							95.4	0.189	1.219	1.048	0.241	0.061	0.078	
5610	122	802.11ac	OFDM	80	15.50	14.49	1	-0.04	0 mm	MIMO	V2	TX76GKGXF7	29.3	top	95.4	0.803	1.262	1.048	1.062	0.262	0.347	
					17.75	16.72	2	-0.05							95.4	0.636	1.268	1.048	0.845	0.210	0.279	
5690	138	802.11ac	OFDM	80	15.50	14.44	1	0.00	0 mm	MIMO	V1	JL9W2R3Q76	29.3	top	95.4	0.727	1.276	1.048	0.972	0.237	0.317	
					17.75	16.71	2	0.00							95.4	0.696	1.271	1.048	0.927	0.222	0.296	
5690	138	802.11ac	OFDM	80	15.50	14.53	1	-0.03	0 mm	MIMO	V2	TX76GKGXF7	29.3	top	95.4	0.768	1.250	1.048	1.006	0.251	0.329	
					17.75	16.79	2	-0.02							95.4	0.624	1.247	1.048	0.815	0.198	0.259	
5775	155	802.11ac	OFDM	80	16.50	15.53	1	-0.03	0 mm	MIMO	V1	JL9W2R3Q76	29.3	top	95.4	0.884	1.250	1.048	1.158	0.285	0.373	
					17.75	16.70	2	0.01							95.4	0.811	1.274	1.048	1.083	0.253	0.338	
5775	155	802.11ac	OFDM	80	16.50	15.81	1	0.00	0 mm	MIMO	V2	TX76GKGXF7	29.3	top	95.4	0.968	1.172	1.048	1.189	0.307	0.377	A2
					17.75	16.76	2	-0.02							95.4	0.822	1.256	1.048	1.082	0.254	0.334	
5270	54	802.11n	OFDM	40	17.00	16.18	1	-0.01	0 mm	MIMO	V1	JL9W2R3Q76	13.5	top	97.9	0.936	1.208	1.021	1.154	0.325	0.401	
					18.50	17.55	2	0.01							97.9	0.803	1.245	1.021	1.021	0.263	0.334	
5775	155	802.11ac	OFDM	80	16.50	15.81	1	0.02	0 mm	MIMO	V2	TX76GKGXF7	29.3	top	95.4	0.966	1.172	1.048	1.186	0.316	0.388	
					17.75	16.76	2	-0.02							95.4	0.753	1.256	1.048	0.991	0.237	0.312	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT																						
Spatial Peak									1.6 W/kg (mW/g)													
Uncontrolled Exposure/General Population									averaged over 1 gram													

Note: Blue entry indicates variability measurement.

Due to the spatial separation of Antenna WF7a and Antenna WF8, two measurement cubes were evaluated during MIMO SAR testing. Cube 1 and 2 are located over the SAR distributions produced by Antenna WF7a and WF8, respectively. Due to the spatial separation of the distributions, the conducted power of each antenna was individually considered for each measurement cube to determine the reported SAR.

Table 9-6
Bluetooth Body SAR Data – Antenna WF8

MEASUREMENT RESULTS																				
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Variant	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (1g)	Scaling Factor (Cond Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.													(W/kg)			(W/kg)	(W/kg)		
2480	78	Bluetooth	FHSS	19.50	18.97	-0.08	0 mm	Ant WF8	V1	JL9W2R3Q76	1	back	76.8	0.071	1.130	1.009	0.081	0.037	0.042	
2402	0	Bluetooth	FHSS	19.50	18.76	0.02	0 mm	Ant WF8	V1	JL9W2R3Q76	1	top	76.8	0.425	1.186	1.009	0.509	0.191	0.229	
2441	39	Bluetooth	FHSS	19.50	18.90	-0.03	0 mm	Ant WF8	V1	JL9W2R3Q76	1	top	76.8	0.491	1.148	1.009	0.569	0.217	0.251	
2480	78	Bluetooth	FHSS	19.50	18.97	-0.01	0 mm	Ant WF8	V1	JL9W2R3Q76	1	top	76.8	0.561	1.130	1.009	0.640	0.243	0.277	
2480	78	Bluetooth	FHSS	19.50	19.20	0.00	0 mm	Ant WF8	V2	TX76GKGXF7	1	top	76.8	0.497	1.072	1.009	0.538	0.216	0.234	
2480	78	Bluetooth	FHSS	19.50	18.97	0.15	0 mm	Ant WF8	V1	JL9W2R3Q76	1	bottom	76.8	0.006	1.130	1.009	0.007	0.002	0.002	
2480	78	Bluetooth	FHSS	19.50	18.97	-0.13	0 mm	Ant WF8	V1	JL9W2R3Q76	1	right	76.8	0.015	1.130	1.009	0.017	0.005	0.006	
2480	78	Bluetooth	FHSS	19.50	18.97	-0.19	0 mm	Ant WF8	V1	JL9W2R3Q76	1	left	76.8	0.000	1.130	1.009	0.000	0.000	0.000	
2441	39	Bluetooth	FHSS	12.50	11.98	-0.02	0 mm	Ant WF8	V1	JL9W2R3Q76	1	top	76.8	0.094	1.127	1.009	0.107	0.042	0.048	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body												
Spatial Peak								1.6 W/kg (mW/g)												
Uncontrolled Exposure/General Population								averaged over 1 gram												

Note: The reported SAR was scaled to the 77.5% transmission duty factor to determine compliance since the duty factor of the device is permanently limited to 77.5% per the manufacturer.

FCC ID: BCGA2588	 PCTEST Proud to be part of Element	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 41 of 52

Table 9-7
Bluetooth Body SAR Data – Antenna WF7b

MEASUREMENT RESULTS																				
FREQUENCY		Mode	Service	Maximum Allowed Power [dBm]	Conducted Power [dBm]	Power Drift [dB]	Spacing	Antenna Config.	Variant	Device Serial Number	Data Rate (Mbps)	Side	Duty Cycle (%)	SAR (1g)	Scaling Factor (Cond Power)	Scaling Factor (Duty Cycle)	Reported SAR (1g)	SAR (10g)	Reported SAR (10g)	Plot #
MHz	Ch.													(W/kg)			(W/kg)	(W/kg)		
2441	39	Bluetooth	FHSS	20.00	19.16	0.01	0 mm	Ant WF7b	V1	R39RQP9FH6	1	back	76.8	0.103	1.213	1.009	0.126	0.052	0.064	A3
2402	0	Bluetooth	FHSS	20.00	19.05	0.00	0 mm	Ant WF7b	V1	R39RQP9FH6	1	top	76.8	0.781	1.245	1.009	0.981	0.342	0.430	
2441	39	Bluetooth	FHSS	20.00	19.16	-0.01	0 mm	Ant WF7b	V1	R39RQP9FH6	1	top	76.8	0.819	1.213	1.009	1.002	0.349	0.427	
2480	78	Bluetooth	FHSS	20.00	18.93	-0.02	0 mm	Ant WF7b	V1	R39RQP9FH6	1	top	76.8	0.806	1.279	1.009	1.040	0.342	0.441	
2480	78	Bluetooth	FHSS	20.00	19.12	0.03	0 mm	Ant WF7b	V2	RRHXV56277	1	top	76.8	0.680	1.225	1.009	0.840	0.286	0.354	
2441	39	Bluetooth	FHSS	20.00	19.16	0.20	0 mm	Ant WF7b	V1	R39RQP9FH6	1	bottom	76.8	0.008	1.213	1.009	0.010	0.003	0.004	
2441	39	Bluetooth	FHSS	20.00	19.16	-0.18	0 mm	Ant WF7b	V1	R39RQP9FH6	1	right	76.8	0.017	1.213	1.009	0.021	0.007	0.009	
2441	39	Bluetooth	FHSS	20.00	19.16	0.00	0 mm	Ant WF7b	V1	R39RQP9FH6	1	left	76.8	0.640	1.213	1.009	0.783	0.282	0.345	
2480	78	Bluetooth	FHSS	13.00	12.00	0.05	0 mm	Ant WF7b	V1	R39RQP9FH6	1	back	76.8	0.016	1.259	1.009	0.020	0.006	0.008	
2480	78	Bluetooth	FHSS	13.00	12.00	-0.03	0 mm	Ant WF7b	V1	R39RQP9FH6	1	top	76.8	0.129	1.259	1.009	0.164	0.052	0.066	
2480	78	Bluetooth	FHSS	13.00	12.00	-0.09	0 mm	Ant WF7b	V1	R39RQP9FH6	1	left	76.8	0.092	1.259	1.009	0.117	0.040	0.051	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT							Body													
Spatial Peak							1.6 W/kg (mW/g)													
Uncontrolled Exposure/General Population							averaged over 1 gram													

Note: The reported SAR was scaled to the 77.5% transmission duty factor to determine compliance since the duty factor of the device is permanently limited to 77.5% per the manufacturer.

9.2 SAR Test Notes

General Notes:

- The test data reported are the worst-case SAR values according to test procedures specified in FCC KDB Publication 616217 D04v01r02 and FCC KDB Publication 447498 D01v06.
- Batteries are fully charged at the beginning of the SAR measurements.
- Liquid tissue depth was at least 15.0 cm for all frequencies.
- The manufacturer has confirmed that the device(s) tested have the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.
- SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D01v06.
- Per FCC KDB 865664 D01v01r04, variability SAR tests were performed when the measured SAR results for a frequency band were greater than or equal to 0.8 W/kg. Repeated SAR measurements are highlighted in the tables above for clarity. Please see Section 11 for variability analysis.
- FCC KDB Publication 616217 D04v01r02 Section 4.3, SAR tests are required for the back surface and edges of the tablet with the tablet touching the phantom. The SAR Exclusion Threshold in FCC KDB 447498 D01v06 was applied to determine SAR test exclusion for adjacent edge configurations.
- This device utilizes power reduction for some wireless modes and technologies, as outlined in Section 1.2. The maximum output power allowed for each transmitter and exposure condition was evaluated for SAR compliance based on expected use conditions and simultaneous transmission scenarios.
- The orange highlights throughout the report represent the highest scaled SAR per equipment class.

WLAN Notes:

- Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 2.4 GHz WIFI single transmission chain operations, the highest measured maximum output power channel for DSSS was selected for SAR measurement. SAR for OFDM modes (2.4 GHz 802.11g/n/ax) was not required due to the maximum allowed powers and the highest reported DSSS SAR. See Section 6.2.4 for more information.
- Justification for test configurations for WLAN per KDB Publication 248227 D01v02r02 for 5 GHz WIFI single transmission chain operations, the initial test configuration was selected according to the

FCC ID: BCGA2588	 PCTEST Proud to be part of Element	SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 42 of 52

transmission mode with the highest maximum allowed powers. Other transmission modes were not investigated since the highest reported SAR for initial test configuration adjusted by the ratio of maximum output powers is less than 1.2 W/kg for 1g evaluations. See Section 6.2.5 for more information.

3. Per KDB Publication 248227 D01v02r02, SAR for MIMO was evaluated by following the simultaneous SAR provisions from KDB Publication 447498 D01v06 by either evaluating the sum of the 1g SAR values of each antenna transmitting independently or making a SAR measurement with both antennas transmitting simultaneously. Please see Section 10 for complete analysis.
4. When the maximum reported 1g averaged SAR is ≤ 0.8 W/kg, SAR testing on additional channels was not required. Otherwise, SAR for the next highest output power channel was required until the reported SAR result was ≤ 1.20 W/kg for 1g evaluations or all test channels were measured.
5. The device was configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools. The reported SAR was scaled to the 100% transmission duty factor to determine compliance. Procedures used to measure the duty factor are identical to that in the associated EMC test reports.
6. The time-averaged mechanism for WLAN operations was disabled for the above SAR measurements. The SAR was scaled to the maximum time-averaged output power.

Bluetooth Notes

1. Bluetooth SAR was evaluated with a test mode with hopping disabled with DH5 operation. The reported SAR was scaled to the 77.5% transmission duty factor to determine compliance since the duty factor of the device is limited to 77.5% per the manufacturer. See Section 7.3 for the time domain plot and calculation for the duty factor of the device.

FCC ID: BCGA2588	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 43 of 52

10 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

10.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v06 are applicable to devices with built-in unlicensed transmitters such as 802.11 and Bluetooth devices which may simultaneously transmit together.

10.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore, simultaneous transmission analysis is required. Per FCC KDB Publication 447498 D01v06 4.3.2 and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1g SAR for all the simultaneous transmitting antennas in a specific physical test configuration is ≤ 1.6 W/kg. The different test positions in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1g or 10g SAR.

Note:

*The SAR distributions for at least one of the antennas are spatially separated from the other antennas per FCC KDB Publication 248227 Section 6.1 procedures. Therefore, the simultaneous transmission were treated independently for this configuration. See section 10.4 for more information about the Spatial Separation Analysis.

10.3 Body SAR Simultaneous Transmission Analysis

Table 10-1
Simultaneous Transmission Scenario with 2.4 GHz WLAN

Simult Tx	Configuration	2.4 GHz WLAN Ant WF8 SAR (W/kg)	2.4 GHz WLAN Ant WF7b SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body SAR	Back	0.144	0.155	0.299
	Top	1.171	1.146	1.171*
	Bottom	0.015	0.010	0.025
	Right	0.040	0.021	0.061
	Left	0.004	0.920	0.924

Table 10-2
Simultaneous Transmission Scenario with 2.4 GHz Bluetooth

Simult Tx	Configuration	Bluetooth Ant WF8 SAR (W/kg)	Bluetooth Ant WF7b SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body SAR	Back	0.081	0.126	0.207
	Top	0.640	1.040	1.040*
	Bottom	0.007	0.010	0.017
	Right	0.017	0.021	0.038
	Left	0.000	0.783	0.783

FCC ID: BCGA2588	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 44 of 52

Table 10-3
Simultaneous Transmission Scenario with 2.4 GHz WLAN and Bluetooth

Simult Tx	Configuration	2.4 GHz WLAN Ant WF8 SAR (W/kg)	Bluetooth Ant WF7b SAR (W/kg)	Σ SAR (W/kg)
		1	2	1+2
Body SAR	Back	0.144	0.126	0.270
	Top	1.171	1.040	1.171*
	Bottom	0.015	0.010	0.025
	Right	0.040	0.021	0.061
	Left	0.004	0.783	0.787

Note: In this scenario Wi-Fi max power will not exceed minimum of (13.5dBm, SAR max cap, Reg max cap) power. However, 2.4 GHz WLAN Antenna WF8 at 21.5 dBm was used for simultaneous analysis with 2.4 GHz Bluetooth Antenna WF7b as it is more conservative.

Table 10-4
Simultaneous Transmission Scenario with Bluetooth (TxBF) and 5 GHz MIMO

Simult Tx	Configuration	Bluetooth Ant WF8 at 12.5 dBm SAR (W/kg)	Bluetooth Ant WF7b at 13 dBm SAR (W/kg)	5 GHz WLAN Ant WF8 SAR (W/kg)	5 GHz WLAN Ant WF7a SAR (W/kg)	Σ SAR (W/kg)
		1	2	3	4	1+2+3+4
Body SAR	Back	0.081	0.020	0.111	0.155	0.367
	Top	0.107	0.164	1.185	1.166	see table below
	Bottom	0.007	0.010	0.026	0.004	0.047
	Right	0.017	0.021	0.034	0.009	0.081
	Left	0.000	0.117	0.003	0.030	0.150

Simult Tx	Configuration	Bluetooth Ant WF8 at 12.5 dBm SAR (W/kg)	Bluetooth Ant WF7b at 13 dBm SAR (W/kg)	5 GHz WLAN MIMO SAR (W/kg)	Σ SAR (W/kg)
		1	2	3	1+2+3
Body	Top	0.107	0.164	1.189	1.460

10.4 Spatial Separation Analysis

Per FCC KDB Publication 248227, antennas may be considered spatially separated when the aggregate SAR from multiple antennas at any location in the combined SAR distribution is either ≤ 1.2 W/kg where at least 90% of the SAR is attributed to a single SAR distribution or ≤ 0.4 W/kg where no more than one SAR distribution is contributing > 0.1 W/kg.

Spatial separation was determined by inspection of the area scan SAR distributions to confirm that at all locations, SAR was < 1.2 W/kg, where at least 90% of the SAR is attributed to a single SAR distribution. See below for illustrations of the spatial separated antennas considered.

FCC ID: BCGA2588	 PCTEST Proud to be part of Element	SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device		Page 45 of 52

10.4.1 Top Edge Spatial Separation Analysis




Figure 10-1
Top Edge Spatial Separation for Antenna WF8 and Antenna WF7b

10.5 Simultaneous Transmission Conclusion

The above numerical summed SAR results for all the worst-case simultaneous transmission conditions were below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v06 and IEEE 1528-2013 Section 6.3.4.1.2.

FCC ID: BCGA2588	 PCTEST Proud to be part of Element		SAR EVALUATION REPORT	Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device		Page 46 of 52

11 SAR MEASUREMENT VARIABILITY

11.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01r04, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

- 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg (~ 10% from the 1g SAR limit).
- 3) A third repeated measurement was performed only if the original, first, or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
- 4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg

Table 11-1
Body SAR Measurement Variability Results

BODY VARIABILITY RESULTS															
Band	FREQUENCY		Mode	Service	Antenna	Data Rate (Mbps)	Side	Spacing	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio	2nd Repeated SAR (1g)	Ratio	3rd Repeated SAR (1g)	Ratio
	MHz	Ch.							(W/kg)	(W/kg)		(W/kg)			
2450	2417.00	2	802.11b, 22 MHz Bandwidth	DSSS	Ant WF8	1	top	0 mm	0.858	0.848	1.01	N/A	N/A	N/A	N/A
5250	5270.00	54	802.11n, 40 MHz Bandwidth	OFDM	MIMO Cube 1 (Ant WF7a)	13.5	top	0 mm	0.960	0.936	1.03	N/A	N/A	N/A	N/A
5600	5610.00	122	802.11ac, 80 MHz Bandwidth	OFDM	Ant WF7a	29.3	top	0 mm	0.887	0.875	1.01	N/A	N/A	N/A	N/A
5750	5775.00	155	802.11ac, 80 MHz Bandwidth	OFDM	MIMO Cube 1 (Ant WF7a)	29.3	top	0 mm	0.968	0.966	1.00	N/A	N/A	N/A	N/A
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Body 1.6 W/kg (mW/g) averaged over 1 gram						

11.2 Measurement Uncertainty

The measured SAR was < 1.5 W/kg for 1g for all frequency bands. Therefore, per KDB Publication 865664 D01v01r04, the extended measurement uncertainty analysis per IEEE 1528-2013 was not required.

FCC ID: BCGA2588	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 47 of 52

12 EQUIPMENT LIST

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	8753ES	S-Parameter Network Analyzer	04/14/2021	Annual	04/14/2022	US39170118
Agilent	E4438C	ESG Vector Signal Generator	10/17/2021	Annual	10/17/2022	MY45093852
Agilent	E4440A	PSA Series Spectrum Analyzer	01/29/2021	Annual	01/29/2022	MY46186272
Agilent	N5182A	MXG Vector Signal Generator	11/17/2021	Annual	11/17/2022	US46240505
Amplifier Research	15S1G6	Amplifier	CBT	N/A	CBT	343972
Amplifier Research	15S1G6	Amplifier	CBT	N/A	CBT	343971
Anritsu	MA24106A	USB Power Sensor	09/21/2021	Annual	09/21/2022	1244515
Anritsu	MA24106A	USB Power Sensor	09/27/2021	Annual	09/27/2022	1248508
Anritsu	MA24106A	USB Power Sensor	02/25/2021	Annual	02/25/2022	1520503
Anritsu	MA24106A	USB Power Sensor	02/25/2021	Annual	02/25/2022	1520501
Anritsu	MA2411B	Pulse Power Sensor	03/08/2021	Annual	03/08/2022	1339007
Anritsu	ML2496A	Power Meter	02/19/2021	Annual	02/19/2022	1138001
Control Company	4040	Therm./ Clock/ Humidity Monitor	03/12/2021	Biennial	03/12/2023	210202151
Control Company	4040	Therm./ Clock/ Humidity Monitor	02/19/2021	Biennial	02/19/2023	210114805
Control Company	4353	Long Stem Thermometer	10/28/2020	Biennial	10/28/2022	200670623
Control Company	4353	Long Stem Thermometer	10/28/2020	Biennial	10/28/2022	200670633
Control Company	4353	Long Stem Thermometer	10/28/2020	Biennial	10/28/2022	200670635
Control Company	4353	Long Stem Thermometer	10/28/2020	Biennial	10/28/2022	200670646
Control Company	4353	Long Stem Thermometer	10/28/2020	Biennial	10/28/2022	200670653
Insize	1108-150	Digital Caliper	01/17/2020	Biennial	01/17/2022	409193536
MCL	BW-N6W5+	6dB Attenuator	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-1.9+	Low Pass Filter	CBT	N/A	CBT	N/A
Mini-Circuits	PWR-4GHS	USB Power Sensor	05/24/2021	Annual	05/24/2022	12010120004
Mini-Circuits	VLF-6000+	Low Pass Filter	CBT	N/A	CBT	N/A
Mini-Circuits	ZHDC-16-63-S+	50-6000MHz Bidirectional Coupler	CBT	N/A	CBT	N/A
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	N/A
Seekonk	TSF-100	Torque Wrench	07/08/2021	Annual	07/08/2022	47639-29
SPEAG	D2450V2	2450 MHz SAR Dipole	06/14/2019	Triennial	06/14/2022	750
SPEAG	D5GHzV2	5 GHz SAR Dipole	06/09/2021	Annual	06/09/2022	1163
SPEAG	DAE4	Dasy Data Acquisition Electronics	01/13/2021	Annual	01/13/2022	793
SPEAG	DAE4	Dasy Data Acquisition Electronics	04/13/2021	Annual	04/13/2022	501
SPEAG	DAE4	Dasy Data Acquisition Electronics	05/11/2021	Annual	05/11/2022	701
SPEAG	DAK-3.5	Dielectric Assessment Kit	05/12/2021	Annual	05/12/2022	1070
SPEAG	EX3DV4	SAR Probe	05/18/2021	Annual	05/18/2022	7416
SPEAG	EX3DV4	SAR Probe	01/18/2021	Annual	01/18/2022	3837
SPEAG	EX3DV4	SAR Probe	04/19/2021	Annual	04/19/2022	7532
SPEAG	MAIA	Modulation and Audio Interference Analyzer	CBT	N/A	CBT	1324
SPEAG	MAIA	Modulation and Audio Interference Analyzer	CBT	N/A	CBT	1260

Note: CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.

FCC ID: BCGA2588	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 48 of 52

13 MEASUREMENT UNCERTAINTIES

a	b	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	IEEE 1528 Sec.	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System									
Probe Calibration	E.2.1	7	N	1	1	1	7.0	7.0	∞
Axial Isotropy	E.2.2	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	E.2.2	1.3	N	1	0.7	0.7	0.9	0.9	∞
Boundary Effect	E.2.3	2	R	1.732	1	1	1.2	1.2	∞
Linearity	E.2.4	0.3	N	1	1	1	0.3	0.3	∞
System Detection Limits	E.2.4	0.25	R	1.732	1	1	0.1	0.1	∞
Modulation Response	E.2.5	4.8	R	1.732	1	1	2.8	2.8	∞
Readout Electronics	E.2.6	0.3	N	1	1	1	0.3	0.3	∞
Response Time	E.2.7	0.8	R	1.732	1	1	0.5	0.5	∞
Integration Time	E.2.8	2.6	R	1.732	1	1	1.5	1.5	∞
RF Ambient Conditions - Noise	E.6.1	3	R	1.732	1	1	1.7	1.7	∞
RF Ambient Conditions - Reflections	E.6.1	3	R	1.732	1	1	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	E.6.2	0.8	R	1.732	1	1	0.5	0.5	∞
Probe Positioning w/ respect to Phantom	E.6.3	6.7	R	1.732	1	1	3.9	3.9	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	E.5	4	R	1.732	1	1	2.3	2.3	∞
Test Sample Related									
Test Sample Positioning	E.4.2	3.12	N	1	1	1	3.1	3.1	35
Device Holder Uncertainty	E.4.1	1.67	N	1	1	1	1.7	1.7	5
Output Power Variation - SAR drift measurement	E.2.9	5	R	1.732	1	1	2.9	2.9	∞
SAR Scaling	E.6.5	0	R	1.732	1	1	0.0	0.0	∞
Phantom & Tissue Parameters									
Phantom Uncertainty (Shape & Thickness tolerances)	E.3.1	7.6	R	1.73	1.0	1.0	4.4	4.4	∞
Liquid Conductivity - measurement uncertainty	E.3.3	4.3	N	1	0.78	0.71	3.3	3.0	76
Liquid Permittivity - measurement uncertainty	E.3.3	4.2	N	1	0.23	0.26	1.0	1.1	75
Liquid Conductivity - Temperature Uncertainty	E.3.4	3.4	R	1.732	0.78	0.71	1.5	1.4	∞
Liquid Permittivity - Temperature Uncertainty	E.3.4	0.6	R	1.732	0.23	0.26	0.1	0.1	∞
Liquid Conductivity - deviation from target values	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Permittivity - deviation from target values	E.3.2	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Combined Standard Uncertainty (k=1)							RSS	12.2	12.0
Expanded Uncertainty							k=2	24.4	24.0
(95% CONFIDENCE LEVEL)									

The above measurement uncertainties are according to IEEE Std. 1528-2013

FCC ID: BCGA2588	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 49 of 52

14 CONCLUSION

14.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Innovation, Science, and Economic Development Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

FCC ID: BCGA2588	 PCTEST Proud to be part of 		Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 50 of 52

15 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2013, IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 1 -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

FCC ID: BCGA2588	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 51 of 52

- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz), July 2016.
- [21] Innovation, Science, Economic Development Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 5, March 2015.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2015
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement Guidance for IEEE 802.11 Transmitters, KDB Publication 248227 D01
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D03-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

FCC ID: BCGA2588	 SAR EVALUATION REPORT		Approved by: Quality Manager
Document S/N: 1C2111150078-11.BCG (Rev 2)	Test Dates: 12/14/2021 – 01/10/2022	DUT Type: Tablet Device	Page 52 of 52