




Plot 7-65. Radiated Spurious Emissions 1-18GHz Antenna 5b (BDR – 5789MHz)

Mode: BDR

Data Rate: 1Mbps

Power Scheme: ePA

Distance of Measurements: 3 Meters


Operating Frequency: 5789MHz

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
* 11578.00	Average	H	150	192	-79.58	13.71	41.13	53.98	-12.85
* 11578.00	Peak	H	150	192	-69.77	13.71	50.94	73.98	-23.04
17367.00	Peak	H	-	-	-70.50	17.12	54.22	68.20	-13.98

Table 7-20. Radiated Spurious Emissions Measurements Antenna 5b

FCC ID: BCGA2435		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090025-16.BCG	Test Dates: 6/7/2022 - 9/24/2022	EUT Type: Tablet Device	Page 69 of 101

V 10.5 12/15/2021



Plot 7-66. Radiated Spurious Emissions 1-18GHz Antenna 5b (BDR – 5844MHz)


Mode:	BDR
Data Rate:	1Mbps
Power Scheme:	ePA
Distance of Measurements:	3 Meters
Operating Frequency:	5844MHz

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
*	11688.00	Average	H	157	222	-78.05	13.57	42.52	53.98	-11.46
*	11688.00	Peak	H	157	222	-68.61	13.57	51.96	73.98	-22.02
	17532.00	Peak	H	-	-	-69.99	17.94	54.95	68.20	-13.25

Table 7-21. Radiated Spurious Emissions Measurements Antenna 5b

FCC ID: BCGA2435		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090025-16.BCG	Test Dates: 6/7/2022 - 9/24/2022	EUT Type: Tablet Device	Page 70 of 101

7.6.2 Antenna 4a Radiated Spurious Emission



Plot 7-67. Radiated Spurious Emissions 1-18GHz Antenna 4a (BDR – 5162MHz)


Mode:	BDR
Data Rate:	1Mbps
Power Scheme:	ePA
Distance of Measurements:	3 Meters
Operating Frequency:	5162MHz

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
10324.00	Peak	H	-	-	-68.30	11.73	50.43	68.20	-17.77
* 15486.00	Average	H	-	-	-83.14	16.51	40.37	53.98	-13.61
* 15486.00	Peak	H	-	-	-70.87	16.51	52.64	73.98	-21.34

Table 7-22. Radiated Spurious Emissions Measurements Antenna 4a

FCC ID: BCGA2435		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090025-16.BCG	Test Dates: 6/7/2022 - 9/24/2022	EUT Type: Tablet Device	Page 71 of 101

V 10.5 12/15/2021



Plot 7-68. Radiated Spurious Emissions 1-18GHz Antenna 4a (BDR – 5204MHz)

Mode: BDR

Data Rate: 1Mbps

Power Scheme: ePA

Distance of Measurements: 3 Meters


Operating Frequency: 5204MHz

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
10408.00	Peak	V	198	214	-70.77	12.26	48.49	68.20	-19.71
* 15612.00	Average	H	-	-	-83.14	15.80	39.66	53.98	-14.32
* 15612.00	Peak	H	-	-	-72.13	15.80	50.67	73.98	-23.31

Table 7-23. Radiated Spurious Emissions Measurements Antenna 4a

FCC ID: BCGA2435		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2205090025-16.BCG	Test Dates: 6/7/2022 - 9/24/2022	EUT Type: Tablet Device		Page 72 of 101

V 10.5 12/15/2021



Plot 7-69. Radiated Spurious Emissions 1-18GHz Antenna 4a (BDR - 5245MHz)

Mode: BDR

Data Rate: 1Mbps

Power Scheme: ePA

Distance of Measurements: 3 Meters


Operating Frequency: 5245MHz

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
10490.00	Peak	H	-	-	-71.24	12.44	48.20	68.20	-20.00
* 15735.00	Average	V	114	38	-81.33	16.72	42.39	53.98	-11.59
* 15735.00	Peak	V	114	38	-70.73	16.72	52.99	73.98	-20.99

Table 7-24. Radiated Spurious Emissions Measurements Antenna 4a

FCC ID: BCGA2435		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090025-16.BCG	Test Dates: 6/7/2022 - 9/24/2022	EUT Type: Tablet Device	Page 73 of 101

V 10.5 12/15/2021



Plot 7-70. Radiated Spurious Emissions 1-18GHz Antenna 4a (BDR - 5733MHz)


Mode:	BDR
Data Rate:	1Mbps
Power Scheme:	ePA
Distance of Measurements:	3 Meters
Operating Frequency:	5733MHz

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
*	11466.00	Average	H	-	-	-83.72	13.30	36.58	53.98	-17.40
*	11466.00	Peak	H	-	-	-72.48	13.30	47.82	73.98	-26.16
	17199.00	Peak	H	-	-	-73.42	22.01	55.59	68.20	-12.61

Table 7-25. Radiated Spurious Emissions Measurements Antenna 4a

FCC ID: BCGA2435		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090025-16.BCG	Test Dates: 6/7/2022 - 9/24/2022	EUT Type: Tablet Device	Page 74 of 101

V 10.5 12/15/2021



Plot 7-71. Radiated Spurious Emissions 1-18GHz Antenna 4a (BDR - 5789MHz)

Mode: BDR

Data Rate: 1Mbps

Power Scheme: ePA

Distance of Measurements: 3 Meters


Operating Frequency: 5789MHz

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
*	11578.00	Average	V	250	280	-83.98	13.45	36.47	53.98	-17.51
*	11578.00	Peak	V	250	280	-71.37	13.45	49.08	73.98	-24.90
	17367.00	Peak	H	-	-	-72.93	22.80	56.87	68.20	-11.33

Table 7-26. Radiated Spurious Emissions Measurements Antenna 4a

FCC ID: BCGA2435		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090025-16.BCG	Test Dates: 6/7/2022 - 9/24/2022	EUT Type: Tablet Device	Page 75 of 101

V 10.5 12/15/2021



Plot 7-72. Radiated Spurious Emissions 1-18GHz Antenna 4a (BDR - 5844MHz)

Mode: BDR

Data Rate: 1Mbps

Power Scheme: ePA

Distance of Measurements: 3 Meters

Operating Frequency: 5844MHz


	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
*	11688.00	Average	H	-	-	-83.94	13.74	36.80	53.98	-17.18
*	11688.00	Peak	H	-	-	-72.23	13.74	48.51	73.98	-25.47
	17532.00	Peak	H	-	-	-74.01	23.75	56.74	68.20	-11.46

Table 7-27. Radiated Spurious Emissions Measurements Antenna 4a

FCC ID: BCGA2435		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090025-16.BCG	Test Dates: 6/7/2022 - 9/24/2022	EUT Type: Tablet Device	Page 76 of 101

V 10.5 12/15/2021

7.6.3 TxBF Radiated Spurious Emission



Plot 7-73. Radiated Spurious Emissions 1-18GHz TxBF (BDR – 5162MHz)

Mode: BDR

Data Rate: 1Mbps

Power Scheme: ePA

Distance of Measurements: 3 Meters


Operating Frequency: 5162MHz

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
10324.00	Peak	H	-	-	-72.48	12.61	47.13	68.20	-21.07
15486.00	Average	H	-	-	-85.25	18.42	40.17	53.98	-13.81
* 15486.00	Peak	H	-	-	-73.55	18.42	51.87	73.98	-22.11

Table 7-28. Radiated Spurious Emissions Measurements TxBF

FCC ID: BCGA2435		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2205090025-16.BCG	Test Dates: 6/7/2022 - 9/24/2022	EUT Type: Tablet Device		Page 77 of 101

V 10.5 12/15/2021



Plot 7-74. Radiated Spurious Emissions 1-18GHz TxBF (BDR – 5204MHz)


Mode: BDR
Data Rate: 1Mbps
Power Scheme: ePA
Distance of Measurements: 3 Meters
Operating Frequency: 5204MHz

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
10408.00	Peak	H	-	-	-73.16	12.47	46.31	68.20	-21.89
* 15612.00	Average	H	-	-	-85.41	18.40	39.99	53.98	-13.99
* 15612.00	Peak	H	-	-	-74.60	18.40	50.80	73.98	-23.18

Table 7-29. Radiated Spurious Emissions Measurements TxBF

FCC ID: BCGA2435		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090025-16.BCG	Test Dates: 6/7/2022 - 9/24/2022	EUT Type: Tablet Device	Page 78 of 101

V 10.5 12/15/2021



Plot 7-75. Radiated Spurious Emissions 1-18GHz TxBF (BDR - 5245MHz)

Mode: BDR

Data Rate: 1Mbps

Power Scheme: ePA

Distance of Measurements: 3 Meters

Operating Frequency: 5245MHz

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
10490.00	Peak	H	-	-	-72.86	12.68	46.82	68.20	-21.38
* 15735.00	Average	H	-	-	-85.42	18.96	40.54	53.98	-13.44
* 15735.00	Peak	H	-	-	-74.49	18.96	51.47	73.98	-22.51


Table 7-30. Radiated Spurious Emissions Measurements TxBF

FCC ID: BCGA2435		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Technical Manager
Test Report S/N: 1C2205090025-16.BCG	Test Dates: 6/7/2022 - 9/24/2022	EUT Type: Tablet Device		Page 79 of 101


V 10.5 12/15/2021



Radiated Spurious Emission (Above 18GHz)



Plot 7-76. Radiated Spurious Emissions Above 18GHz TxBF (BDR – 5245MHz Pol. H)




Plot 7-77. Radiated Spurious Emissions Above 18GHz TxBF (BDR – 5245MHz Pol. V)

FCC ID: BCGA2435		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090025-16.BCG	Test Dates: 6/7/2022 - 9/24/2022	EUT Type: Tablet Device	Page 80 of 101

V 10.5 12/15/2021

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Washington DC LLC. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.



Plot 7-78. Radiated Spurious Emissions 1-18GHz TxBF (BDR – 5733MHz)

Mode: BDR

Data Rate: 1Mbps

Power Scheme: ePA


Distance of Measurements: 3 Meters

Operating Frequency: 5733MHz

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
* 11466.00	Peak	H	-	-	-83.44	13.30	36.86	53.98	-17.12
* 11466.00	Peak	H	-	-	-72.94	13.30	47.36	73.98	-26.62
17199.00	Peak	H	-	-	-73.79	22.01	55.22	68.20	-12.98

Table 7-31. Radiated Spurious Emissions Measurements TxBF

FCC ID: BCGA2435		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090025-16.BCG	Test Dates: 6/7/2022 - 9/24/2022	EUT Type: Tablet Device	Page 81 of 101



Plot 7-79. Radiated Spurious Emissions 1-18GHz TxBF (BDR - 5789MHz)

Mode: BDR

Data Rate: 1Mbps

Power Scheme: ePA

Distance of Measurements: 3 Meters


Operating Frequency: 5789MHz

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
* 11578.00	Average	H	-	-	-84.31	13.45	36.14	53.98	-17.84
* 11578.00	Peak	H	-	-	-73.98	19.43	52.45	73.98	-21.53
17367.00	Peak	H	-	-	-73.14	25.58	59.44	68.20	-8.76

Table 7-32. Radiated Spurious Emissions Measurements TxBF

FCC ID: BCGA2435		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090025-16.BCG	Test Dates: 6/7/2022 - 9/24/2022	EUT Type: Tablet Device	Page 82 of 101

V 10.5 12/15/2021




Plot 7-80. Radiated Spurious Emissions 1-18GHz TxBF (BDR – 5844MHz)

Mode:	BDR
Data Rate:	1Mbps
Power Scheme:	ePA
Distance of Measurements:	3 Meters
Operating Frequency:	5844MHz

	Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
*	11688.00	Average	H	-	-	-83.98	13.74	36.76	53.98	-17.22
*	11688.00	Peak	H	-	-	-73.59	13.74	47.15	73.98	-26.83
	17532.00	Peak	H	-	-	-73.69	23.75	57.06	68.20	-11.14


Table 7-33. Radiated Spurious Emissions Measurements TxBF

FCC ID: BCGA2435		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090025-16.BCG	Test Dates: 6/7/2022 - 9/24/2022	EUT Type: Tablet Device	Page 83 of 101



23:13:43 21.08.2022

Plot 7-81. Radiated Spurious Emissions Above 18GHz TxBF (BDR – 5844MHz Pol. H)



23:11:19 21.08.2022

Plot 7-82. Radiated Spurious Emissions Above 18GHz TxBF (BDR – 5844MHz Pol. V)

FCC ID: BCGA2435		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090025-16.BCG	Test Dates: 6/7/2022 - 9/24/2022	EUT Type: Tablet Device	Page 84 of 101

V 10.5 12/15/2021

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Washington DC LLC. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

7.6.4 Radiated Band Edge Measurements


§15.407(b.1)(b.2) §15.205 §15.209

Antenna 5b

The amplitude offset shown in the following plots for average measurements was calculated using the formula:

Offset (dB) = (Antenna Factor + Cable Loss + Attenuator) – Preamplifier Gain

Mode:	BDR
Power Scheme:	ePA
Measurement Distance:	3 Meters
Operating Frequency:	5162MHz




Plot 7-83. Radiated Lower Band Edge Measurement Antenna 5b

FCC ID: BCGA2435		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090025-16.BCG	Test Dates: 6/7/2022 - 9/24/2022	EUT Type: Tablet Device	Page 85 of 101


V 10.5 12/15/2021

Mode: BDR
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 5733MHz



Plot 7-84. Radiated Lower Band Edge Measurement Antenna 5b

Mode: BDR
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 5844MHz



Plot 7-85. Radiated Upper Band Edge Measurement Antenna 5b

FCC ID: BCGA2435		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090025-16.BCG	Test Dates: 6/7/2022 - 9/24/2022	EUT Type: Tablet Device	Page 86 of 101

V 10.5 12/15/2021

Radiated Band Edge Measurements


§15.407(b.1)(b.2) §15.205 §15.209

Antenna 4a

The amplitude offset shown in the following plots for average measurements was calculated using the formula:

$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + \text{Attenuator}) - \text{Preamplifier Gain}$$

Mode:	BDR
Power Scheme:	ePA
Measurement Distance:	3 Meters
Operating Frequency:	5162MHz




Plot 7-86. Radiated Lower Band Edge Measurement Antenna 4a

FCC ID: BCGA2435		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090025-16.BCG	Test Dates: 6/7/2022 - 9/24/2022	EUT Type: Tablet Device	Page 87 of 101


V 10.5 12/15/2021

Mode: BDR
Power Scheme: ePA
Measurement Distance: 3 Meters
Operating Frequency: 5733MHz



Plot 7-87. Radiated Lower Band Edge Measurement Antenna 4a

Mode: BDR
Power Scheme: ePA
Measurement Distance: 3 Meters
Operating Frequency: 5844MHz



Plot 7-88. Radiated Upper Band Edge Measurement Antenna 4a

FCC ID: BCGA2435		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090025-16.BCG	Test Dates: 6/7/2022 - 9/24/2022	EUT Type: Tablet Device	Page 88 of 101

Radiated Band Edge Measurements


§15.407(b.1)(b.2) §15.205 §15.209

TxBF

The amplitude offset shown in the following plots for average measurements was calculated using the formula:

Offset (dB) = (Antenna Factor + Cable Loss + Attenuator) – Preamplifier Gain

Mode:	BDR
Power Scheme:	ePA
Measurement Distance:	3 Meters
Operating Frequency:	5162MHz




Plot 7-89. Radiated Lower Band Edge Measurement TxBF

FCC ID: BCGA2435		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090025-16.BCG	Test Dates: 6/7/2022 - 9/24/2022	EUT Type: Tablet Device	Page 89 of 101


V 10.5 12/15/2021

Mode: BDR
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 5733MHz



Plot 7-90. Radiated Lower Band Edge Measurement TxBF

Mode: BDR
 Power Scheme: ePA
 Measurement Distance: 3 Meters
 Operating Frequency: 5844MHz



Plot 7-91. Radiated Upper Band Edge Measurement TxBF

FCC ID: BCGA2435		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090025-16.BCG	Test Dates: 6/7/2022 - 9/24/2022	EUT Type: Tablet Device	Page 90 of 101

7.7 Radiated Spurious Emissions – Below 1GHz

§15.209

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table 7-34 per Section 15.209.

Frequency	Field Strength [μV/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-34. Radiated Limits

Test Procedures Used

ANSI C63.10-2013

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120kHz (for emissions from 30MHz – 1GHz)
3. VBW = 300kHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: BCGA2435		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090025-16.BCG	Test Dates: 6/7/2022 - 9/24/2022	EUT Type: Tablet Device	Page 91 of 101

V 10.5 12/15/2021

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.




Figure 7-6. Radiated Test Setup < 30MHz




Figure 7-7. Radiated Test Setup < 1GHz

FCC ID: BCGA2435		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090025-16.BCG	Test Dates: 6/7/2022 - 9/24/2022	EUT Type: Tablet Device	Page 92 of 101

V 10.5 12/15/2021

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Washington DC LLC. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Test Notes

1. All emissions lying in restricted bands specified in §15.205 are below the limit shown in Table 7-34.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes. For below 30MHz the loop antenna was positioned in 3 orthogonal planes (X front, Y side, Z top) to determine the orientation resulting in the worst case emissions.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector for emissions within 6dB of the limit.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30MHz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. All supported modulation, antenna (including TxBF mode) and power schemes have been tested on the unit and only worst case configuration is reported.
10. Both configurations below were investigated, and the worst case has been reported.
 - a. EUT powered by AC/DC adaptor via USB-C cable with wire charger
 - b. EUT powered by host PC via USB-C cable with wire charger

Sample Calculations

Determining Spurious Emissions Levels


- Field Strength Level $_{[dB\mu V/m]} = \text{Analyzer Level }_{[dBm]} + 107 + \text{AFCL }_{[dB/m]}$
- $\text{AFCL }_{[dB/m]} = \text{Antenna Factor }_{[dB/m]} + \text{Cable Loss }_{[dB]} - \text{Preamplifier Gain }_{[dB]}$
- $\text{Margin }_{[dB]} = \text{Field Strength Level }_{[dB\mu V/m]} - \text{Limit }_{[dB\mu V/m]}$

FCC ID: BCGA2435		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090025-16.BCG	Test Dates: 6/7/2022 - 9/24/2022	EUT Type: Tablet Device	Page 93 of 101

V 10.5 12/15/2021

TxBF Radiated Spurious Emissions (Below 1GHz)

§15.209



Plot 7-92. RSE 30MHz - 1GHz TxBF (BDR GFSK ePA – 5245MHz), with AC/DC Adapter

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
38.20	Max Peak	V	100	15	-58.10	-17.91	30.99	40.00	-9.01
47.99	Max Peak	V	100	143	-61.24	-15.44	30.32	40.00	-9.68
106.48	Max Peak	V	100	328	-66.52	-18.56	21.92	43.52	-21.60
166.58	Max Peak	V	100	94	-63.38	-20.21	23.41	43.52	-20.11
205.33	Max Peak	V	100	138	-66.36	-18.18	22.46	43.52	-21.06
322.84	Max Peak	H	100	240	-70.39	-14.48	22.13	46.02	-23.89

Table 7-35. RSE 30MHz - 1GHz TxBF (BDR GFSK ePA – Ch. 84 – 5245MHz), with AC/DC Adapter

FCC ID: BCGA2435		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090025-16.BCG	Test Dates: 6/7/2022 - 9/24/2022	EUT Type: Tablet Device	Page 94 of 101

V 10.5 12/15/2021

7.8 AC Line Conducted Emissions Measurement

§15.207

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for AC Line conducted spurious emissions. All data rates and modes were investigated for AC Line conducted spurious emissions.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.207.

Frequency of emission (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-36. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10-2013, Subclause 6.2

Test Settings

Quasi-Peak Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Average Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9kHz (for emissions from 150kHz – 30MHz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: BCGA2435		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090025-16.BCG	Test Dates: 6/7/2022 - 9/24/2022	EUT Type: Tablet Device	Page 95 of 101

V 10.5 12/15/2021

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-8. Test Instrument & Measurement Setup

Test Notes

1. All modes of operation were investigated and the worst-case emissions are reported. The emissions found were not affected by the choice of channel used during testing.
2. Both configurations below were investigated, and the worst case has been reported.
 - a. EUT powered by AC/DC adaptor via USB-C cable with wire charger
 - b. EUT powered by host PC via USB-C cable with wire charger
3. The limit for an intentional radiator from 150kHz to 30MHz are specified in 15.207.
4. $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
5. $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Correction Factor (dB)}$
6. $\text{Margin (dB)} = \text{QP/AV Level (dB}\mu\text{V)} - \text{QP/AV Limit (dB}\mu\text{V)}$
7. Traces shown in plots are made using quasi-peak and average detectors.
8. Deviations to the Specifications: None.

FCC ID: BCGA2435		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090025-16.BCG	Test Dates: 6/7/2022 - 9/24/2022	EUT Type: Tablet Device	Page 96 of 101

V 10.5 12/15/2021




Plot 7-93. AC Line Conducted Plot (BDR GFSK ePA – 5245MHz) (L1) with AC/DC Adapter.

Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.159	FINAL	—	34.34	55.52	-21.18	L1	GND
0.159	FINAL	45.3	—	65.52	-20.22	L1	GND
0.236	FINAL	43.5	—	62.25	-18.77	L1	GND
0.238	FINAL	—	30.46	52.17	-21.71	L1	GND
0.548	FINAL	—	21.69	46.00	-24.31	L1	GND
0.548	FINAL	36.7	—	56.00	-19.33	L1	GND
0.861	FINAL	33.9	—	56.00	-22.07	L1	GND
0.863	FINAL	—	19.27	46.00	-26.73	L1	GND
1.799	FINAL	23.0	—	56.00	-32.99	L1	GND
1.802	FINAL	—	12.70	46.00	-33.30	L1	GND
4.664	FINAL	32.9	—	56.00	-23.08	L1	GND
4.758	FINAL	—	19.95	46.00	-26.05	L1	GND

Table 7-37. AC Line Conducted (BDR GFSK ePA – 5245MHz) (L1) with AC/DC Adapter

FCC ID: BCGA2435		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090025-16.BCG	Test Dates: 6/7/2022 - 9/24/2022	EUT Type: Tablet Device	Page 97 of 101

V 10.5 12/15/2021



Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.159	FINAL	—	34.94	55.52	-20.58	N	GND
0.161	FINAL	45.9	—	65.40	-19.47	N	GND
0.236	FINAL	43.8	—	62.25	-18.48	N	GND
0.238	FINAL	—	30.61	52.17	-21.57	N	GND
0.548	FINAL	36.2	—	56.00	-19.76	N	GND
0.551	FINAL	—	20.79	46.00	-25.21	N	GND
0.861	FINAL	33.5	—	56.00	-22.48	N	GND
0.863	FINAL	—	18.86	46.00	-27.14	N	GND
1.934	FINAL	—	10.19	46.00	-35.81	N	GND
1.939	FINAL	20.0	—	56.00	-36.00	N	GND
4.657	FINAL	32.1	—	56.00	-23.94	N	GND
4.664	FINAL	—	17.76	46.00	-28.24	N	GND

Table 7-38. AC Line Conducted (BDR GFSK ePA – 5245MHz) (N) with AC/DC Adapter

FCC ID: BCGA2435		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090025-16.BCG	Test Dates: 6/7/2022 - 9/24/2022	EUT Type: Tablet Device	Page 98 of 101

V 10.5 12/15/2021

8.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Apple Tablet Device FCC ID: BCGA2435** is in compliance with is in compliance with Part 15 Subpart E (15.407) of the FCC Rules.

FCC ID: BCGA2435		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090025-16.BCG	Test Dates: 6/7/2022 - 9/24/2022	EUT Type: Tablet Device	Page 99 of 101

V 10.5 12/15/2021

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Washington DC LLC. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

9.0 APPENDIX A

Antenna gains provided by manufacturer.

Frequency (MHz)	Horizontal (dBi)	Vertical (dBi)
5180	3.7	1.0
5260	3.6	0.9
5320	3.4	1.0
5500	3.1	0.4
5600	3.3	-0.4
5700	3.5	0.2
5745	3.7	0.5
5785	3.7	1.0
5825	4.0	1.8
5955	4.2	2.4
6075	3.9	1.9
6135	3.9	1.5
6255	4.1	1.9
6375	4.2	1.8
6435	4.3	2.0
6555	3.4	1.4
6675	4.2	2.8
6735	4.1	3.3
6855	4.7	2.4
6975	4.2	2.0
7035	4.1	2.4
7115	4.1	3.0

Table 9-1. Antenna 5b Antenna Gain

FCC ID: BCGA2435		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090025-16.BCG	Test Dates: 6/7/2022 - 9/24/2022	EUT Type: Tablet Device	Page 100 of 101

V 10.5 12/15/2021

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element Washington DC LLC. If you have any questions about this or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact ct.info@element.com.

Frequency (MHz)	Horizontal (dBi)	Vertical (dBi)
5180	1.5	2.4
5260	1.4	2.3
5320	2.0	2.8
5500	0.1	0.7
5600	-0.5	-0.1
5700	-1.0	0.1
5745	-1.1	0.3
5785	-1.1	-0.2
5825	-2.1	-0.1
5955	-4.0	-0.7
6075	-3.7	-0.9
6135	-2.3	-0.6
6255	-1.1	0.6
6375	-0.5	1.0
6435	-0.3	1.2
6555	-0.7	-0.3
6675	-1.9	-1.6
6735	-1.9	-1.5
6855	-2.4	-2.7
6975	-3.3	-4.8
7035	-4.9	-5.9
7115	-4.9	-6.2

Table 9-2. Antenna 4a Antenna Gain

FCC ID: BCGA2435		MEASUREMENT REPORT (CERTIFICATION)	Approved by: Technical Manager
Test Report S/N: 1C2205090025-16.BCG	Test Dates: 6/7/2022 - 9/24/2022	EUT Type: Tablet Device	Page 101 of 101

V 10.5 12/15/2021