



ELEMENT MATERIALS TECHNOLOGY

(Formerly PCTEST)
18855 Adams Court, Morgan Hill, CA 95037, USA
Tel. +1.408.538.5600
<http://www.element.com>



SAR EVALUATION REPORT

Applicant Name:
Apple Inc.
One Apple Park Way
Cupertino, CA 95014 USA

Date of Testing:
07/08/2024 – 07/24/2024
Test Report Issue Date:
12/05/2024
Test Site/Location:
Element, Morgan Hill, CA, USA
Document Serial No.:
1C2405230028-01.BCG-R1

FCC ID: BCGA3158
APPLICANT: APPLE, INC.

DUT Type: Wireless Earbud
Application Type: Certification
FCC Rule Part(s): CFR §2.1093
Model: A3158

Equipment Class	Band & Mode	Tx Frequency	SAR	
			1g Head (W/kg)	1g Body-Worn (W/kg)
DSS/DTS	2.4 GHz Bluetooth	2402 - 2480 MHz	0.19	1.14
NII	NB U-NII 1	5157 - 5245 MHz	0.12	1.09
NII	NB U-NII 3	5731 - 5844 MHz	0.14	1.09
6VL	NB U-NII 5	6108 - 6420 MHz	N/A	N/A

Note: This revised Test Report supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in Section 1.8 of this report; for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.

RJ Ortanez
Executive Vice President



The SAR Tick is an initiative of the Mobile & Wireless Forum (MWF). While a product may be considered eligible, use of the SAR Tick logo requires an agreement with the MWF. Further details can be obtained by emailing: sartick@mwfi.info.

FCC ID: BCGA3158	SAR EVALUATION REPORT	Approved by: Technical Manager
Document S/N: 1C2405230028-01.BCG-R1	DUT Type: Wireless Earbud	Page 1 of 28

REV 23.0
07/10/2024

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

TABLE OF CONTENTS

1	DEVICE UNDER TEST	3
2	INTRODUCTION	6
3	DOSIMETRIC ASSESSMENT	7
4	TEST CONFIGURATION POSITIONS.....	8
5	RF EXPOSURE LIMITS	9
6	FCC MEASUREMENT PROCEDURES.....	10
7	RF CONDUCTED POWERS.....	11
8	SYSTEM VERIFICATION.....	19
9	SAR DATA SUMMARY	21
10	SAR MEASUREMENT VARIABILITY	23
11	EQUIPMENT LIST	24
12	MEASUREMENT UNCERTAINTIES.....	25
13	CONCLUSION.....	26
14	REFERENCES	27
APPENDIX A: SAR TEST PLOTS		
APPENDIX B: SAR DIPOLE VERIFICATION PLOTS		
APPENDIX C: PROBE AND DIPOLE CALIBRATION CERTIFICATES		
APPENDIX D: SAR TISSUE SPECIFICATIONS		
APPENDIX E: SAR SYSTEM VALIDATION		
APPENDIX F: DUT ANTENNA DIAGRAM & SAR TEST SETUP PHOTOGRAPHS		

FCC ID: BCGA3158	SAR EVALUATION REPORT	Approved by: Technical Manager
Document S/N: 1C2405230028-01.BCG-R1	DUT Type: Wireless Earbud	Page 2 of 28

REV 23.0
07/10/2024

1 DEVICE UNDER TEST

1.1 Device Overview

Band & Mode	Operating Modes	Tx Frequency
2.4 GHz Bluetooth	Data	2402 - 2480 MHz
NB U-NII 1	Data	5157 - 5245 MHz
NB U-NII 3	Data	5731 - 5844 MHz
NB U-NII 5	Data	6108 - 6420 MHz

1.2 Power Reduction for SAR

There is no power reduction used for any band/mode implemented in this device for SAR purposes.

1.3 Nominal and Maximum Output Power Specifications

This device operates using the following maximum and nominal output power specifications. SAR values were scaled to the maximum allowed power to determine compliance per KDB Publication 447498 D04v01.

1.3.1 Maximum Output Power

Mode / Band	Duty Cycle	Modulated Average (dBm)	
2.4 GHz Bluetooth BDR	34%	Maximum	15.50
		Nominal	14.50
2.4 GHz Bluetooth EDR	77%	Maximum	11.00
		Nominal	10.00
2.4 GHz Bluetooth HDR4/8	77%	Maximum	11.00
		Nominal	10.00
2.4 GHz Bluetooth HDRp4/8	100%	Maximum	11.00
		Nominal	10.00
2.4 GHz Bluetooth LE1M	100%	Maximum	9.00
		Nominal	8.00
2.4 GHz Bluetooth LE2M	15%	Maximum	9.00
		Nominal	8.00

Mode / Band	Duty Cycle	Modulated Average (dBm)	
NB UNII-1 BDR	34%	Maximum	10.00
		Nominal	9.00
NB UNII-1 HDR4/8 1-Slot	34%	Maximum	10.50
		Nominal	9.50
NB UNII-1 HDR4/8 3/5-Slot	77%	Maximum	7.50
		Nominal	6.50
NB UNII-1 HDRp4/8	100%	Maximum	7.50
		Nominal	6.50
NB UNII-1 LE2M	15%	Maximum	11.00
		Nominal	10.00

FCC ID: BCGA3158	SAR EVALUATION REPORT	Approved by: Technical Manager
Document S/N: 1C2405230028-01.BCG-R1	DUT Type: Wireless Earbud	Page 3 of 28

REV 23.0
07/10/2024

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

Mode / Band	Duty Cycle	Modulated Average (dBm)	
NB UNII-3 BDR	34%	Maximum	11.50
		Nominal	10.50
NB UNII-3 HDR4/8 1-Slot	34%	Maximum	10.50
		Nominal	9.50
NB UNII-3 HDR4/8 3/5-Slot	77%	Maximum	7.00
		Nominal	6.00
NB UNII-3 HDRp4/8	100%	Maximum	7.00
		Nominal	6.00
NB UNII-3 LE2M	15%	Maximum	13.50
		Nominal	12.50

Mode / Band	Duty Cycle	Modulated Average (dBm)	
NB UNII-5 BDR	34%	Maximum	-6.00
		Nominal	-7.00
NB UNII-5 HDRp4	100%	Maximum	-3.50
		Nominal	-4.50
NB UNII-5 HDRp8	100%	Maximum	-1.00
		Nominal	-2.00
NB UNII-5 HDR4 1-Slot	34%	Maximum	-3.50
		Nominal	-4.50
NB UNII-5 HDR4 3/5-Slot	77%	Maximum	-3.50
		Nominal	-4.50
NB UNII-5 HDR8 1-Slot	34%	Maximum	-1.00
		Nominal	-2.00
NB UNII-5 HDR8 3/5-Slot	77%	Maximum	-1.00
		Nominal	-2.00
NB UNII-5 LEM	100%	Maximum	-6.00
		Nominal	-7.00
NB UNII-5 LE2M	15%	Maximum	-5.00
		Nominal	-6.00

1.4 DUT Antenna Locations

Based on the expected use conditions, Head SAR was evaluated. Per manufacturer request, Body-Worn SAR was evaluated as an additional conservative SAR test condition. The antenna is located inside BCGA3158 which is a wireless Bluetooth earbud for the Left ear. A diagram showing the location of the device antenna can be found in the DUT Antenna Diagram & SAR Test Setup Photographs Appendix. More information about the configurations evaluated for SAR can be found in Section 4.2 and Section 4.3.

1.5 Simultaneous Transmission Capabilities

This Device does not support any Simultaneous transmission Scenarios.

1.6 Miscellaneous SAR Test Considerations

The Bluetooth/NB UNII chipset in this device is produced by two different suppliers. The electrically identical modules are manufactured with identical mechanical structures to meet the same specifications and functions. Two device variants are referenced as Variant 1 and Variant 2 in this report. Bluetooth/NB UNII SAR worst case configuration was spot checked on Variant 1 and Variant 2.

FCC ID: BCGA3158	SAR EVALUATION REPORT	Approved by: Technical Manager
Document S/N: 1C2405230028-01.BCG-R1	DUT Type: Wireless Earbud	Page 4 of 28

REV 23.0
07/10/2024

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

1.7 1-mW Test Exemption

Max Output Power= -1 dBm or 0.79 mW; Frequency Range= 6108-6420 MHz. This 2.1093 portable device under Part 15c Subpart E requires SAR head and body-worn testing with a test separation of 0 mm as allowed in KDB Pub. 447498.

Per FCC KDB 447498 D04v01 Section 2.1.2, if the available maximum time-averaged power is no more than 1 mW, then a single RF source is exempt from the requirement to show data demonstrating compliance to RF exposure limits. Since the maximum output power for NB UNII-5 is less than 1 mW and there are no simultaneous transmission scenarios supported for this device, then, it qualifies for the standalone test exemption.

1.8 Guidance Applied

- FCC KDB Publication 447498 D04v01 (General SAR Guidance)
- FCC KDB Publication 865664 D01v01r04, D02v01r02 (SAR Measurements up to 6 GHz)

1.9 Device Serial Numbers

Several samples with identical hardware were used to support SAR testing. The manufacturer has confirmed that the device(s) tested have the same physical, mechanical, and thermal characteristics and are within operational tolerances expected for production units. The serial numbers used for each test are indicated alongside the results in Section 9.

FCC ID: BCGA3158	SAR EVALUATION REPORT	Approved by: Technical Manager
Document S/N: 1C2405230028-01.BCG-R1	DUT Type: Wireless Earbud	Page 5 of 28

REV 23.0
07/10/2024

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

2 INTRODUCTION

The FCC and Innovation, Science, and Economic Development Canada have adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996, and Health Canada Safety Code 6 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [22]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields,” Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

2.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Equation 2-1).

Equation 2-1
SAR Mathematical Equation

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dv} \right)$$

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- σ = conductivity of the tissue-simulating material (S/m)
- ρ = mass density of the tissue-simulating material (kg/m³)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

FCC ID: BCGA3158	SAR EVALUATION REPORT	Approved by: Technical Manager
Document S/N: 1C2405230028-01.BCG-R1	DUT Type: Wireless Earbud	Page 6 of 28

REV 23.0
07/10/2024

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

3 DOSIMETRIC ASSESSMENT

3.1 Measurement Procedure

The evaluation was performed using the following procedure compliant to FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013:

1. The SAR distribution at the exposed side of the head or body was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the device-head and body interface, and the horizontal grid resolution was determined per FCC KDB Publication 865664 D01v01r04 (See Table 3-3-1) and IEEE 1528-2013.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during the 1g/10g cube evaluation. SAR at this fixed point was measured and used as a reference value.
3. Based on the area scan data, the peak of the region with maximum SAR was determined by spline interpolation. Around this point, a volume was assessed according to the measurement resolution and volume size requirements of FCC KDB Publication 865664 D01v01r04 (See Table 3-3-1) and IEEE 1528-2013. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the cDASY6 manual online for more details):
 - a. SAR values at the inner surface of the phantom are extrapolated from the measured values along the line away from the surface with spacing no greater than that in Table 3-3-1. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
 - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the “Not a knot” condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete to calculate the SAR drift. If the drift deviated by more than 5%, the SAR test and drift measurements were repeated.




Figure 3-1
Sample SAR Area
Scan

Table 3-3-1
Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01v01r04*

Frequency	Maximum Area Scan Resolution (mm) ($\Delta x_{\text{area}}, \Delta y_{\text{area}}$)	Maximum Zoom Scan Resolution (mm) ($\Delta x_{\text{zoomTV}}, \Delta y_{\text{zoom}}$)	Maximum Zoom Scan Spatial Resolution (mm)			Minimum Zoom Scan Volume (mm) (x,y,z)
			Uniform Grid	Graded Grid		
				$\Delta z_{\text{zoom}}(n)$	$\Delta z_{\text{zoom}}(1)^*$	
≤2 GHz	≤15	≤8	≤5	≤4	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥30
2-3 GHz	≤12	≤5	≤5	≤4	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥30
3-4 GHz	≤12	≤5	≤4	≤3	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥28
4-5 GHz	≤10	≤4	≤3	≤2.5	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥25
5-6 GHz	≤10	≤4	≤2	≤2	≤1.5* $\Delta z_{\text{zoom}}(n-1)$	≥22

*Also compliant to IEEE 1528-2013 Table 6

FCC ID: BCGA3158	SAR EVALUATION REPORT	Approved by: Technical Manager
Document S/N: 1C2405230028-01.BCG-R1	DUT Type: Wireless Earbud	Page 7 of 28

REV 23.0
07/10/2024

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

4 TEST CONFIGURATION POSITIONS

4.1 Device Holder

The device holder is made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$.

4.2 Positioning for Head

This device is a wireless Bluetooth earbud for the left ear which is designed to be used in the ear canal. The antenna is located inside the earbud. SAR was evaluated with a separation distance of 0 mm between the earbud (the ear tip facing the phantom) and the flat phantom. The phantom is filled with head tissue equivalent medium.

4.3 Body-Worn Exposure Conditions

Per manufacturer request, Body-Worn SAR was evaluated as an additional conservative SAR test condition for the left earbud. The DUT was evaluated with a separation distance of 0 mm between the back side (logo) of the earbud and the flat phantom. The button side, non-button side, and bottom side were additionally evaluated. The phantom is filled with head tissue equivalent medium.

FCC ID: BCGA3158	SAR EVALUATION REPORT	Approved by: Technical Manager
Document S/N: 1C2405230028-01.BCG-R1	DUT Type: Wireless Earbud	Page 8 of 28

REV 23.0
07/10/2024

5 RF EXPOSURE LIMITS

5.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

5.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e., as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 5-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
Peak Spatial Average SAR Head	1.6	8.0
Whole Body SAR	0.08	0.4
Peak Spatial Average SAR Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: BCGA3158	SAR EVALUATION REPORT	Approved by: Technical Manager
Document S/N: 1C2405230028-01.BCG-R1	DUT Type: Wireless Earbud	Page 9 of 28

REV 23.0
07/10/2024

6 FCC MEASUREMENT PROCEDURES

6.1 Measured and Reported SAR

Per FCC KDB Publication 447498 D04v01, when SAR is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance. For simultaneous transmission, the measured aggregate SAR must be scaled according to the sum of the differences between the maximum tune-up tolerance and actual power used to test each transmitter. When SAR is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as *reported* SAR. The highest *reported* SAR results are identified on the grant of equipment authorization according to procedures in KDB 690783 D01v01r03.

FCC ID: BCGA3158	SAR EVALUATION REPORT	Approved by: Technical Manager
Document S/N: 1C2405230028-01.BCG-R1	DUT Type: Wireless Earbud	Page 10 of 28

REV 23.0
07/10/2024

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

7 RF CONDUCTED POWERS

7.1 Bluetooth/NB UNII Conducted Powers

Table 7-1
Bluetooth Maximum Average RF Power – Variant 1

Frequency [MHz]	Modulation	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
				[dBm]	[mW]
2404	HDRp4	4.0	1	10.25	10.593
2440	HDRp4	4.0	37	9.98	9.954
2476	HDRp4	4.0	73	9.95	9.886

Bluetooth Maximum Average RF Power – Variant 2

Frequency [MHz]	Modulation	Data Rate [Mbps]	Channel No.	Avg Conducted Power	
				[dBm]	[mW]
2404	HDRp4	4.0	1	10.59	11.455
2440	HDRp4	4.0	37	10.30	10.715
2476	HDRp4	4.0	73	10.26	10.617

Table 7-2
NB UNII Maximum Average RF Power – Variant 1

Type	Band	Frequency	Channel	Average
HDRp4	U-NII 1	5157	Low	6.92
		5201	Mid	7.00
		5245	High	7.05
HDRp4	U-NII 3	5731	Low	6.20
		5788	Mid	6.48
		5844	High	6.52

NB UNII Maximum Average RF Power – Variant 2

Type	Band	Frequency	Channel	Average
HDRp4	U-NII 1	5157	Low	7.23
		5201	Mid	7.27
		5245	High	7.20
HDRp4	U-NII 3	5731	Low	6.74
		5788	Mid	6.73
		5844	High	6.75

FCC ID: BCGA3158	SAR EVALUATION REPORT	Approved by: Technical Manager
Document S/N: 1C2405230028-01.BCG-R1	DUT Type: Wireless Earbud	Page 11 of 28

REV 23.0
07/10/2024

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

7.2 Bluetooth/NB UNII Duty Cycle Plots




Figure 7-1
2.4 GHz Bluetooth Transmission Plot - Variant 1

Equation 7-1
2.4 GHz Bluetooth Duty Cycle Calculation

$$Duty\ Cycle = \frac{Pulse\ Width}{Period} * 100\% = \frac{8.745\ ms}{10.01\ ms} * 100\% = 87.36\%$$

FCC ID: BCGA3158	SAR EVALUATION REPORT	Approved by: Technical Manager
Document S/N: 1C2405230028-01.BCG-R1	DUT Type: Wireless Earbud	Page 12 of 28




Figure 7-2
2.4 GHz Bluetooth Transmission Plot - Variant 2

Equation 7-2
2.4 GHz Bluetooth Duty Cycle Calculation

$$\text{Duty Cycle} = \frac{\text{Pulse Width}}{\text{Period}} * 100\% = \frac{8.745 \text{ ms}}{10.01 \text{ ms}} * 100\% = 87.36\%$$

FCC ID: BCGA3158	SAR EVALUATION REPORT	Approved by: Technical Manager
Document S/N: 1C2405230028-01.BCG-R1	DUT Type: Wireless Earbud	Page 13 of 28

REV 23.0
07/10/2024




Figure 7-3
NB UNII-1 Transmission Plot - Variant 1

Equation 7-3
NB UNII-1 Bluetooth Duty Cycle Calculation

$$\text{Duty Cycle} = \frac{\text{Pulse Width}}{\text{Period}} * 100\% = \frac{8.745 \text{ ms}}{10.01 \text{ ms}} * 100\% = 87.36\%$$

FCC ID: BCGA3158	SAR EVALUATION REPORT	Approved by: Technical Manager
Document S/N: 1C2405230028-01.BCG-R1	DUT Type: Wireless Earbud	Page 14 of 28

REV 23.0
07/10/2024




Figure 7-4
NB UNII-1 Transmission Plot - Variant 2

Equation 7-4
NB UNII-1 Duty Cycle Calculation

$$\text{Duty Cycle} = \frac{\text{Pulse Width}}{\text{Period}} * 100\% = \frac{8.745 \text{ ms}}{10.01 \text{ ms}} * 100\% = 87.36\%$$

FCC ID: BCGA3158	SAR EVALUATION REPORT	Approved by: Technical Manager
Document S/N: 1C2405230028-01.BCG-R1	DUT Type: Wireless Earbud	Page 15 of 28

REV 23.0
07/10/2024

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.




Figure 7-6
NB UNII-3 Transmission Plot - Variant 2

Equation 7-6
NB UNII-3 Duty Cycle Calculation

$$\text{Duty Cycle} = \frac{\text{Pulse Width}}{\text{Period}} * 100\% = \frac{8.745 \text{ ms}}{10.01 \text{ ms}} * 100\% = 87.36\%$$

FCC ID: BCGA3158	SAR EVALUATION REPORT	Approved by: Technical Manager
Document S/N: 1C2405230028-01.BCG-R1	DUT Type: Wireless Earbud	Page 17 of 28

REV 23.0
07/10/2024

7.7 Notes for Bluetooth/NB UNII

- The Bluetooth/NB UNII chipset in this device is produced by two different suppliers. The electrically identical modules are manufactured with identical mechanical structures to meet the same specifications and functions. Two device variants are referenced as Variant 1 and Variant 2 in this report.
- Bluetooth/NB UNII SAR worst case configuration was spot checked on Variant 1 and Variant 2.
- Full power measurements were performed for Variant 1 and Variant 2 per FCC KDB Procedures 248227.




Figure 7-7
Power Measurement Setup

FCC ID: BCGA3158	SAR EVALUATION REPORT	Approved by: Technical Manager
Document S/N: 1C2405230028-01.BCG-R1	DUT Type: Wireless Earbud	Page 18 of 28

REV 23.0
07/10/2024

8 SYSTEM VERIFICATION

8.1 Tissue Verification

Table 8-1
Measured Head Tissue Properties

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
07/24/2024	2450 Head	24.6	2300	1.635	38.759	1.670	39.500	-2.10%	-1.88%
			2310	1.646	38.721	1.679	39.480	-1.97%	-1.92%
			2320	1.658	38.684	1.687	39.460	-1.72%	-1.97%
			2400	1.752	38.416	1.756	39.289	-0.23%	-2.22%
			2450	1.803	38.219	1.800	39.200	0.17%	-2.50%
			2480	1.838	38.102	1.833	39.162	0.27%	-2.71%
			2500	1.864	38.031	1.855	39.136	0.49%	-2.82%
			2510	1.878	38.003	1.866	39.123	0.64%	-2.86%
			2535	1.910	37.934	1.893	39.092	0.90%	-2.96%
			2550	1.925	37.883	1.909	39.073	0.84%	-3.05%
			2560	1.934	37.841	1.920	39.060	0.73%	-3.12%
			2600	1.974	37.639	1.964	39.009	0.51%	-3.51%
			2650	2.045	37.462	2.018	38.945	1.34%	-3.81%
			2680	2.075	37.355	2.051	38.907	1.17%	-3.99%
			2700	2.095	37.266	2.073	38.882	1.06%	-4.16%
07/08/2024	5200-5800 Head	20.0	5150	4.616	35.153	4.604	36.043	0.26%	-2.47%
			5160	4.632	35.135	4.614	36.031	0.38%	-2.49%
			5170	4.647	35.118	4.624	36.020	0.51%	-2.50%
			5180	4.659	35.113	4.635	36.009	0.52%	-2.49%
			5190	4.669	35.108	4.645	35.998	0.52%	-2.47%
			5200	4.679	35.095	4.655	35.986	0.52%	-2.48%
			5210	4.689	35.075	4.666	35.975	0.49%	-2.50%
			5220	4.697	35.054	4.676	35.963	0.45%	-2.53%
			5240	4.714	35.007	4.696	35.940	0.38%	-2.60%
			5250	4.725	34.981	4.706	35.929	0.40%	-2.64%
			5260	4.739	34.962	4.717	35.917	0.47%	-2.66%
			5270	4.752	34.954	4.727	35.906	0.53%	-2.65%
			5280	4.764	34.952	4.737	35.894	0.57%	-2.62%
			5290	4.774	34.940	4.748	35.883	0.55%	-2.63%
			5300	4.784	34.921	4.758	35.871	0.55%	-2.65%
			5310	4.795	34.894	4.768	35.860	0.57%	-2.69%
			5320	4.806	34.872	4.778	35.849	0.59%	-2.73%
			5500	4.993	34.572	4.963	35.643	0.60%	-3.00%
			5510	5.005	34.562	4.973	35.632	0.64%	-3.00%
			5520	5.017	34.559	4.983	35.620	0.68%	-2.98%
			5530	5.032	34.549	4.994	35.609	0.76%	-2.98%
			5540	5.049	34.531	5.004	35.597	0.90%	-2.99%
			5550	5.060	34.510	5.014	35.586	0.92%	-3.02%
			5560	5.066	34.497	5.024	35.574	0.84%	-3.03%
			5580	5.081	34.460	5.045	35.551	0.71%	-3.07%
			5600	5.107	34.406	5.065	35.529	0.83%	-3.16%
			5610	5.119	34.394	5.076	35.518	0.85%	-3.16%
			5620	5.132	34.383	5.086	35.506	0.90%	-3.16%
			5640	5.155	34.352	5.106	35.483	0.96%	-3.19%
			5660	5.180	34.326	5.127	35.460	1.03%	-3.20%
			5670	5.190	34.311	5.137	35.449	1.03%	-3.21%
			5680	5.198	34.293	5.147	35.437	0.99%	-3.23%
			5690	5.205	34.274	5.158	35.426	0.91%	-3.25%
			5700	5.215	34.252	5.168	35.414	0.91%	-3.28%
			5710	5.229	34.242	5.178	35.403	0.98%	-3.28%
			5720	5.243	34.229	5.188	35.391	1.06%	-3.28%
			5745	5.272	34.180	5.214	35.363	1.11%	-3.35%
			5750	5.278	34.170	5.219	35.357	1.13%	-3.36%
			5755	5.284	34.162	5.224	35.351	1.15%	-3.36%
			5765	5.297	34.145	5.234	35.340	1.20%	-3.38%
			5775	5.308	34.131	5.245	35.329	1.20%	-3.39%
			5795	5.328	34.107	5.265	35.305	1.20%	-3.39%
			5800	5.335	34.102	5.270	35.300	1.23%	-3.39%
			5805	5.341	34.093	5.275	35.294	1.25%	-3.40%
			5825	5.363	34.050	5.296	35.271	1.27%	-3.46%
			5835	5.372	34.034	5.305	35.230	1.26%	-3.39%
			5850	5.388	34.014	5.320	35.200	1.28%	-3.37%
			5865	5.403	33.989	5.336	35.190	1.26%	-3.41%
			5875	5.414	33.967	5.347	35.183	1.25%	-3.46%
			5885	5.425	33.947	5.357	35.177	1.27%	-3.50%
			5905	5.453	33.917	5.379	35.163	1.38%	-3.54%

The above measured tissue parameters were used in the cDASY6 software. The cDASY6 software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 D01v01r04 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

FCC ID: BCGA3158	SAR EVALUATION REPORT	Approved by: Technical Manager
Document S/N: 1C2405230028-01.BCG-R1	DUT Type: Wireless Earbud	Page 19 of 28

REV 23.0
07/10/2024

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

8.2 Test System Verification

Prior to SAR assessment, the system is verified to $\pm 10\%$ of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in the SAR System Validation Appendix.

Table 8-2
System Verification Results – 1g

System Verification TARGET & MEASURED													
SAR System	Tissue Frequency (MHz)	Tissue Type	Date	Amb. Temp. (C)	Liquid Temp. (C)	Input Power (W)	Source SN	Probe SN	DAE	Measured SAR 1g (W/kg)	1W Target SAR 1g (W/kg)	1W Normalized SAR 1g (W/kg)	Deviation 1g (%)
AM6	2450	HEAD	07/24/2024	20.0	23.7	0.10	750	7499	1644	5.040	52.600	50.400	-4.18%
AM8	5250	HEAD	07/08/2024	22.8	19.0	0.05	1066	7427	467	3.900	80.300	78.000	-2.86%
AM8	5600	HEAD	07/08/2024	22.8	19.0	0.05	1066	7427	467	4.120	83.900	82.400	-1.79%
AM8	5750	HEAD	07/08/2024	22.8	19.0	0.05	1066	7427	467	3.780	79.500	75.600	-4.91%
AM8	5850	HEAD	07/08/2024	22.8	19.0	0.05	1066	7427	467	3.970	82.200	79.400	-3.41%




Figure 8-1
System Verification Setup Diagram



Figure 8-2
System Verification Setup Photo

FCC ID: BCGA3158	SAR EVALUATION REPORT	Approved by: Technical Manager
Document S/N: 1C2405230028-01.BCG-R1	DUT Type: Wireless Earbud	Page 20 of 28

REV 23.0
07/10/2024

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

9

SAR DATA SUMMARY

9.1 2.4 GHz Bluetooth SISO Standalone Head SAR

Table 9-1

Exposure	Band / Mode	Earbud	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Max Allowed Power [dBm]	Conducted Power [dBm]	Test Position	Spacing [mm]	Add'l Info	Measured 1g SAR [W/kg]	Power Scaling Factor	Duty Cycle Scaling Factor	Reported 1g SAR [W/kg]	Plot #
Head	2.4 GHz Bluetooth	Left	HJ4H71000LP0000UEB	87.36	-0.21	2404	1	4	11.00	10.25	Front	0	V1	0.110	1.189	1.145	0.150	
Head	2.4 GHz Bluetooth	Left	HJ4H72000LX0000UEB	87.36	-0.04	2440	37	4	11.00	10.30	Front	0	V2	0.131	1.175	1.145	0.176	
Head	2.4 GHz Bluetooth	Left	HJ4H71000LP0000UEB	87.36	-0.06	2440	37	4	11.00	9.98	Front	0	V1	0.132	1.265	1.145	0.191	A1
Head	2.4 GHz Bluetooth	Left	HJ4H71000LP0000UEB	87.36	0.08	2476	73	4	11.00	9.95	Front	0	V1	0.095	1.274	1.145	0.139	
ANSI/IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population											Head 1.6 W/kg (mW/g) averaged over 1 gram							

Note: The reported SAR was scaled to 100% transmission duty factor.

9.2 5 GHz NB U-NII 1 Standalone Head SAR

Table 9-2

Exposure	Band / Mode	Earbud	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Max Allowed Power [dBm]	Conducted Power [dBm]	Test Position	Spacing [mm]	Add'l Info	Measured 1g SAR [W/kg]	Power Scaling Factor	Duty Cycle Scaling Factor	Reported 1g SAR [W/kg]	Plot #
Head	NB U-NII 1	Left	HJ4H6V000V00000UEB	87.36	-0.19	5245	High	4	7.50	7.05	Front	0	V1	0.095	1.109	1.145	0.121	
Head	NB U-NII 1	Left	HJ4H6V000V00000UEB	87.36	-0.00	5157	Low	4	7.50	6.92	Front	0	V1	0.074	1.143	1.145	0.097	
Head	NB U-NII 1	Left	HJ4H6V000V00000UEB	87.36	-0.07	5201	Mid	4	7.50	7.00	Front	0	V1	0.096	1.122	1.145	0.123	
Head	NB U-NII 1	Left	HJ4H72000LX0000UEB	87.36	0.05	5201	Mid	4	7.50	7.27	Front	0	V2	0.089	1.054	1.145	0.107	
ANSI/IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population											Head 1.6 W/kg (mW/g) averaged over 1 gram							

Note: The reported SAR was scaled to 100% transmission duty factor.

9.3 5 GHz NB U-NII 3 Standalone Head SAR

Table 9-3

Exposure	Band / Mode	Earbud	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Max Allowed Power [dBm]	Conducted Power [dBm]	Test Position	Spacing [mm]	Add'l Info	Measured 1g SAR [W/kg]	Power Scaling Factor	Duty Cycle Scaling Factor	Reported 1g SAR [W/kg]	Plot #
Head	NB U-NII 3	Left	HJ4H6V000V00000UEB	87.36	0.03	5844	High	4	7.00	6.52	Front	0	V1	0.081	1.117	1.145	0.104	
Head	NB U-NII 3	Left	HJ4H6V000V00000UEB	87.36	0.02	5731	Low	4	7.00	6.20	Front	0	V1	0.098	1.202	1.145	0.135	
Head	NB U-NII 3	Left	HJ4H72000LX0000UEB	87.36	-0.12	5731	Low	4	7.00	6.74	Front	0	V2	0.110	1.062	1.145	0.134	A2
Head	NB U-NII 3	Left	HJ4H6V000V00000UEB	87.36	0.03	5788	Mid	4	7.00	6.48	Front	0	V1	0.092	1.127	1.145	0.119	
ANSI/IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population											Head 1.6 W/kg (mW/g) averaged over 1 gram							

Note: The reported SAR was scaled to 100% transmission duty factor.

9.4 2.4 GHz Bluetooth SISO Standalone Body-Worn SAR

Table 9-4

Exposure	Band / Mode	Earbud	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Max Allowed Power [dBm]	Conducted Power [dBm]	Test Position	Spacing [mm]	Add'l Info	Measured 1g SAR [W/kg]	Power Scaling Factor	Duty Cycle Scaling Factor	Reported 1g SAR [W/kg]	Plot #
Body-worn	2.4 GHz Bluetooth	Left	HJ4H71000LP0000UEB	87.36	-0.02	2404	1	4	11.00	10.25	Bottom	0	V1	0.072	1.189	1.145	0.098	
Body-worn	2.4 GHz Bluetooth	Left	HJ4H71000LP0000UEB	87.36	0.05	2404	1	4	11.00	10.25	Logo	0	V1	0.530	1.189	1.145	0.721	
Body-worn	2.4 GHz Bluetooth	Left	HJ4H71000LP0000UEB	87.36	-0.02	2404	1	4	11.00	10.25	Button	0	V1	0.455	1.189	1.145	0.619	
Body-worn	2.4 GHz Bluetooth	Left	HJ4H72000LX0000UEB	87.36	-0.05	2404	1	4	11.00	10.59	Non-Button	0	V2	0.799	1.099	1.145	1.005	
Body-worn	2.4 GHz Bluetooth	Left	HJ4H71000LP0000UEB	87.36	-0.09	2404	1	4	11.00	10.25	Non-Button	0	V1	0.837	1.189	1.145	1.139	A3
Body-worn	2.4 GHz Bluetooth	Left	HJ4H71000LP0000UEB	87.36	-0.08	2404	1	4	11.00	10.25	Non-Button	0	V1	0.818	1.189	1.145	1.127	
Body-worn	2.4 GHz Bluetooth	Left	HJ4H71000LP0000UEB	87.36	0.05	2440	37	4	11.00	9.98	Non-Button	0	V1	0.719	1.265	1.145	1.041	
Body-worn	2.4 GHz Bluetooth	Left	HJ4H71000LP0000UEB	87.36	0.02	2476	73	4	11.00	9.95	Non-Button	0	V1	0.583	1.274	1.145	0.850	
ANSI/IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population											Body 1.6 W/kg (mW/g) averaged over 1 gram							

Note: Blue entry represents variability measurement

Note: The reported SAR was scaled to 100% transmission duty factor.

FCC ID: BCGA3158	SAR EVALUATION REPORT	Approved by: Technical Manager
Document S/N: 1C2405230028-01.BCG-R1	DUT Type: Wireless Earbud	Page 21 of 28

REV 23.0
07/10/2024

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

9.5 5 GHz NB U-NII 1 Standalone Body-Worn SAR

Table 9-5

Exposure	Band / Mode	Earbud	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Max Allowed Power [dBm]	Conducted Power [dBm]	Test Position	Spacing [mm]	Add'l Info	Measured 1g SAR [W/kg]	Power Scaling Factor	Duty Cycle Scaling Factor	Reported 1g SAR [W/kg]	Plot #
Body-worn	NB U-NII 1	Left	HJ4H6V000V/D0000UEB	87.36	-0.03	5245	High	4	7.5	7.05	Bottom	0	V1	0.111	1.109	1.145	0.141	
Body-worn	NB U-NII 1	Left	HJ4H6V000V/D0000UEB	87.36	-0.06	5245	High	4	7.5	7.05	Logo	0	V1	0.857	1.109	1.145	1.088	
Body-worn	NB U-NII 1	Left	HJ4H72000Z/00000UEB	87.36	0.06	5245	High	4	7.5	7.20	Logo	0	V2	0.764	1.072	1.145	0.938	
Body-worn	NB U-NII 1	Left	HJ4H6V000V/D0000UEB	87.36	-0.07	5245	High	4	7.5	7.05	Logo	0	V1	0.837	1.109	1.145	1.056	
Body-worn	NB U-NII 1	Left	HJ4H6V000V/D0000UEB	87.36	-0.02	5245	High	4	7.5	7.05	Button	0	V1	0.800	1.109	1.145	1.016	
Body-worn	NB U-NII 1	Left	HJ4H6V000V/D0000UEB	87.36	0.01	5245	High	4	7.5	7.05	Non-Button	0	V1	0.275	1.109	1.145	0.349	
Body-worn	NB U-NII 1	Left	HJ4H6V000V/D0000UEB	87.36	0.03	5157	Low	4	7.5	6.92	Logo	0	V1	0.721	1.143	1.145	0.943	
Body-worn	NB U-NII 1	Left	HJ4H6V000V/D0000UEB	87.36	-0.06	5157	Low	4	7.5	6.92	Button	0	V1	0.830	1.143	1.145	1.086	
Body-worn	NB U-NII 1	Left	HJ4H6V000V/D0000UEB	87.36	0.00	5201	Mid	4	7.5	7.00	Logo	0	V1	0.736	1.122	1.145	0.945	
Body-worn	NB U-NII 1	Left	HJ4H6V000V/D0000UEB	87.36	-0.02	5201	Mid	4	7.5	7.00	Button	0	V1	0.841	1.122	1.145	1.080	
ANSI/IEEE C95.1 1992 - SAFETY LIMIT														Body 1.6 W/kg (mW/g) averaged over 1 gram				
Spatial Peak Uncontrolled Exposure/General Population																		

Note: Blue entry represents variability measurement

Note: The reported SAR was scaled to 100% transmission duty factor.

9.6 5 GHz NB U-NII 3 Standalone Body-Worn SAR

Table 9-6

Exposure	Band / Mode	Earbud	Serial Number	Duty Cycle [%]	Power Drift [dB]	Frequency [MHz]	Channel #	Data Rate [Mbps]	Max Allowed Power [dBm]	Conducted Power [dBm]	Test Position	Spacing [mm]	Add'l Info	Measured 1g SAR [W/kg]	Power Scaling Factor	Duty Cycle Scaling Factor	Reported 1g SAR [W/kg]	Plot #
Body-worn	NB U-NII 3	Left	HJ4H71000V/Y0000UEB	87.36	0.01	5844	High	4	7.00	6.52	Bottom	0	V1	0.072	1.117	1.145	0.092	
Body-worn	NB U-NII 3	Left	HJ4H71000V/Y0000UEB	87.36	-0.02	5844	High	4	7.00	6.52	Logo	0	V1	0.577	1.117	1.145	0.738	
Body-worn	NB U-NII 3	Left	HJ4H71000V/Y0000UEB	87.36	0.00	5844	High	4	7.00	6.52	Button	0	V1	0.850	1.117	1.145	1.087	
Body-worn	NB U-NII 3	Left	HJ4H72000Z/00000UEB	87.36	-0.01	5844	High	4	7.00	6.75	Button	0	V2	0.869	1.059	1.145	1.053	A4
Body-worn	NB U-NII 3	Left	HJ4H71000V/Y0000UEB	87.36	-0.13	5844	High	4	7.00	6.52	Non-Button	0	V1	0.184	1.117	1.145	0.235	
Body-worn	NB U-NII 3	Left	HJ4H72000Z/00000UEB	87.36	-0.03	5844	High	4	7.00	6.75	Button	0	V2	0.786	1.059	1.145	0.953	
Body-worn	NB U-NII 3	Left	HJ4H71000V/Y0000UEB	87.36	-0.01	5731	Low	4	7.00	6.20	Button	0	V1	0.784	1.202	1.145	1.079	
Body-worn	NB U-NII 3	Left	HJ4H71000V/Y0000UEB	87.36	-0.12	5788	Mid	4	7.00	6.48	Button	0	V1	0.785	1.127	1.145	1.013	
ANSI/IEEE C95.1 1992 - SAFETY LIMIT														Body 1.6 W/kg (mW/g) averaged over 1 gram				
Spatial Peak Uncontrolled Exposure/General Population																		

Note: Blue entry represents variability measurement

Note: The reported SAR was scaled to 100% transmission duty factor.

9.7 SAR Test Notes

General Notes:

- Batteries are fully charged at the beginning of the SAR measurements.
- Liquid tissue depth was at least 15.0 cm for all frequencies.
- The manufacturer has confirmed that the device(s) tested have the same physical, mechanical, and thermal characteristics and are within operational tolerances expected for production units.
- SAR results were scaled to the maximum allowed power to demonstrate compliance per FCC KDB Publication 447498 D04v01.
- To demonstrate compliance for Head, SAR testing was performed on a flat phantom filled with head tissue equivalent medium.
- Per manufacturer request, Body-Worn SAR was additionally evaluated as a conservative SAR test condition for the left earbud (BCGA3158).
- Per FCC KDB 865664 D01v01r04, variability SAR tests were performed when the measured SAR results for a frequency band were greater than or equal to 0.8 W/kg. Repeated SAR measurements are highlighted in the tables above for clarity. Please see Section 10 for variability analysis.
- The orange highlights throughout the report represent the highest scaled SAR per Equipment Class.

Bluetooth/NB UNII Notes

- Bluetooth/NB UNII SAR was evaluated with a test mode with hopping disabled with DH5 operation. The reported SAR was scaled to the 100% transmission duty factor to determine compliance for a more conservative exposure analysis. See section 7.2 for the time domain plot and calculation for the duty factor of the device.

FCC ID: BCGA3158	SAR EVALUATION REPORT	Approved by: Technical Manager
Document S/N: 1C2405230028-01.BCG-R1	DUT Type: Wireless Earbud	Page 22 of 28

REV 23.0
07/10/2024

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

10 SAR MEASUREMENT VARIABILITY

10.1 Measurement Variability

Per FCC KDB Publication 865664 D01v01r04, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

- 1) When the original highest measured SAR is ≥ 0.80 W/kg, the measurement was repeated once.
- 2) A second repeated measurement was performed only if the ratio of largest to smallest SAR for the original and first repeated measurements was > 1.20 or when the original or repeated measurement was ≥ 1.45 W/kg (~ 10% from the 1g SAR limit).
- 3) A third repeated measurement was performed only if the original, first or second repeated measurement was ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .
- 4) Repeated measurements are not required when the original highest measured SAR is < 0.80 W/kg
- 5) When 10g SAR measurement is considered, a factor of 2.5 is applied to the thresholds above.

Table 10-1
Body SAR Measurement Variability Results

BODY VARIABILITY RESULTS											
Band	FREQUENCY		Mode	Service	Earbud	Data Rate (Mbps)	Side	Spacing	Measured SAR (1g)	1st Repeated SAR (1g)	Ratio
	MHz	Ch.							(W/kg)	(W/kg)	
2450	2404	1	2.4 GHz Bluetooth	HDRp4	Left	4	Non-Button	0 mm	0.837	0.828	1.01
5250	5245	High	NB U-NII 1	HDRp4	Left	4	Logo	0 mm	0.857	0.832	1.03
5850	5844	High	NB U-NII 3	HDRp4	Left	4	Button	0 mm	0.869	0.786	1.11
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population									Body 1.6 W/kg (mW/g) averaged over 1 gram		

10.2 Measurement Uncertainty

The measured SAR was <1.5 W/kg for 1g and <3.75 W/kg for 10g for all frequency bands. Therefore, per KDB Publication 865664 D01v01r04, the extended measurement uncertainty analysis per IEEE 1528-2013 was not required.

FCC ID: BCGA3158	SAR EVALUATION REPORT	Approved by: Technical Manager
Document S/N: 1C2405230028-01.BCG-R1	DUT Type: Wireless Earbud	Page 23 of 28

REV 23.0
07/10/2024

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

11 EQUIPMENT LIST

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	E4404B	Spectrum Analyzer	N/A	N/A	N/A	MY45113242
Agilent	E4438C	ESG Vector Signal Generator	11/14/2023	Annual	11/14/2024	MY45093852
Agilent	E4438C	ESG Vector Signal Generator	11/15/2023	Annual	11/15/2024	MY45092078
Agilent	N5182A	MXG Vector Signal Generator	10/12/2023	Annual	10/12/2024	MY47400015
Agilent	N5182A	MXG Vector Signal Generator	3/7/2024	Annual	3/7/2025	MY47420603
Agilent	8753ES	S-Parameter Vector Network Analyzer	1/10/2024	Annual	1/10/2025	MY40001472
Amplifier Research	15S1G6	Amplifier	CBT	N/A	CBT	433973
Amplifier Research	15S1G6	Amplifier	CBT	N/A	CBT	433974
Amplifier Research	150A100C	Amplifier	CBT	N/A	CBT	350132
Anritsu	MN8110B	I/O Adaptor	CBT	N/A	CBT	6261747881
Anritsu	ML2496A	Power Meter	6/24/2024	Annual	6/24/2025	1840005
Anritsu	ML2495A	Power Meter	7/8/2024	Annual	7/8/2025	1039008
Anritsu	MA2411B	Pulse Power Sensor	8/22/2023	Annual	8/22/2024	1726262
Anritsu	MA2411B	Pulse Power Sensor	11/8/2023	Annual	11/8/2024	1027293
Anritsu	MA24106A	USB Power Sensor	12/4/2023	Annual	12/4/2024	1520501
Anritsu	MA24106A	USB Power Sensor	4/15/2024	Annual	4/15/2025	1827528
Mini-Circuits	PWR-4GHS	USB Power Sensor	6/12/2024	Annual	6/12/2025	12001070013
Control Company	4052	Long Stem Thermometer	2/27/2024	Biennial	2/27/2026	240174346
Control Company	4052	Long Stem Thermometer	2/27/2024	Biennial	2/27/2026	240171096
Control Company	4052	Long Stem Thermometer	2/27/2024	Biennial	2/27/2026	240171059
Control Company	4040	Therm./ Clock/ Humidity Monitor	4/15/2024	Biennial	4/15/2026	240310280
Control Company	4040	Therm./ Clock/ Humidity Monitor	4/15/2024	Biennial	4/15/2026	240310282
Control Company	S66279	Therm./ Clock/ Humidity Monitor	2/16/2024	Biennial	2/16/2026	240140051
Mitutoyo	500-196-30	CD-6" ASX 6inch Digital Caliper	2/16/2022	Triennial	2/16/2025	A20238413
MCL	BW-N6W5+	6dB Attenuator	CBT	N/A	CBT	1139
Mini-Circuits	VLF-6000+	Low Pass Filter DC to 6000 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	BW-N20W5	Power Attenuator	CBT	N/A	CBT	1226
Mini-Circuits	ZUDC10-83-S+	Directional Coupler	CBT	N/A	CBT	2050
Narda	4772-3	Attenuator (3dB)	CBT	N/A	CBT	9406
Narda	BW-S3W2	Attenuator (3dB)	CBT	N/A	CBT	120
Seekonk	NC-100	Torque Wrench	4/2/2024	Biennial	4/2/2026	1262
SPEAG	D2450V2	2450 MHz SAR Dipole	5/11/2022	Triennial	5/11/2025	750
SPEAG	D5GHzV2	5 GHz SAR Dipole	11/17/2022	Biennial	11/17/2024	1066
SPEAG	DAE4	Dasy Data Acquisition Electronics	12/7/2023	Annual	12/7/2024	1644
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/9/2024	Annual	2/9/2025	467
SPEAG	EX3DV4	SAR Probe	2/9/2024	Annual	2/9/2025	7427
SPEAG	EX3DV4	SAR Probe	1/16/2024	Annual	1/16/2025	7499

Note: CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler, or filter were connected to a calibrated source (i.e., a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.

FCC ID: BCGA3158	SAR EVALUATION REPORT	Approved by: Technical Manager
Document S/N: 1C2405230028-01.BCG-R1	DUT Type: Wireless Earbud	Page 24 of 28

REV 23.0
07/10/2024

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

12 MEASUREMENT UNCERTAINTIES

a	b	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	IEEE 1528 Sec.	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System									
Probe Calibration	E2.1	7	N	1	1	1	7.0	7.0	∞
Axial Isotropy	E2.2	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	E2.2	1.3	N	1	0.7	0.7	0.9	0.9	∞
Boundary Effect	E2.3	2	R	1.732	1	1	1.2	1.2	∞
Linearity	E2.4	0.3	N	1	1	1	0.3	0.3	∞
System Detection Limits	E2.4	0.25	R	1.732	1	1	0.1	0.1	∞
Modulation Response	E2.5	4.8	R	1.732	1	1	2.8	2.8	∞
Readout Electronics	E2.6	0.3	N	1	1	1	0.3	0.3	∞
Response Time	E2.7	0.8	R	1.732	1	1	0.5	0.5	∞
Integration Time	E2.8	2.6	R	1.732	1	1	1.5	1.5	∞
RF Ambient Conditions - Noise	E6.1	3	R	1.732	1	1	1.7	1.7	∞
RF Ambient Conditions - Reflections	E6.1	3	R	1.732	1	1	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	E6.2	0.8	R	1.732	1	1	0.5	0.5	∞
Probe Positioning w/ respect to Phantom	E6.3	6.7	R	1.732	1	1	3.9	3.9	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	E5	4	R	1.732	1	1	2.3	2.3	∞
Test Sample Related									
Test Sample Positioning	E4.2	3.12	N	1	1	1	3.1	3.1	35
Device Holder Uncertainty	E4.1	1.67	N	1	1	1	1.7	1.7	5
Output Power Variation - SAR drift measurement	E2.9	5	R	1.732	1	1	2.9	2.9	∞
SAR Scaling	E6.5	0	R	1.732	1	1	0.0	0.0	∞
Phantom & Tissue Parameters									
Phantom Uncertainty (Shape & Thickness tolerances)	E3.1	7.6	R	1.73	1.0	1.0	4.4	4.4	∞
Liquid Conductivity - measurement uncertainty	E3.3	4.3	N	1	0.78	0.71	3.3	3.0	76
Liquid Permittivity - measurement uncertainty	E3.3	4.2	N	1	0.23	0.26	1.0	1.1	75
Liquid Conductivity - Temperature Uncertainty	E3.4	3.4	R	1.732	0.78	0.71	1.5	1.4	∞
Liquid Permittivity - Temperature Uncertainty	E3.4	0.6	R	1.732	0.23	0.26	0.1	0.1	∞
Liquid Conductivity - deviation from target values	E3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Permittivity - deviation from target values	E3.2	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Combined Standard Uncertainty (k=1)							RSS	12.2	12.0
Expanded Uncertainty (95% CONFIDENCE LEVEL)							k=2	24.4	24.0

The above measurement uncertainties are according to IEEE Std. 1528-2013

FCC ID: BCGA3158	SAR EVALUATION REPORT	Approved by: Technical Manager
Document S/N: 1C2405230028-01.BCG-R1	DUT Type: Wireless Earbud	Page 25 of 28

REV 23.0
07/10/2024

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

13 CONCLUSION

13.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Innovation, Science, and Economic Development Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g., ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g., age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

FCC ID: BCGA3158	SAR EVALUATION REPORT	Approved by: Technical Manager
Document S/N: 1C2405230028-01.BCG-R1	DUT Type: Wireless Earbud	Page 26 of 28

REV 23.0
07/10/2024

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

14 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2013, IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 1 -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.

FCC ID: BCGA3158	SAR EVALUATION REPORT	Approved by: Technical Manager
Document S/N: 1C2405230028-01.BCG-R1	DUT Type: Wireless Earbud	Page 27 of 28

REV 23.0
07/10/2024

Unless otherwise specified, no part of this report may be reproduced or utilized in any part, form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from Element. If you have any questions or have an enquiry about obtaining additional rights to this report or assembly of contents thereof, please contact CT.INFO@ELEMENT.COM.

- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz), July 2016.
- [21] Innovation, Science, Economic Development Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 5, March 2015.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2015
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPC Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement Guidance for IEEE 802.11 Transmitters, KDB Publication 248227 D01
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D03-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.

FCC ID: BCGA3158	SAR EVALUATION REPORT	Approved by: Technical Manager
Document S/N: 1C2405230028-01.BCG-R1	DUT Type: Wireless Earbud	Page 28 of 28

REV 23.0
07/10/2024