



Nemko Test Report: 28188RUS1

Applicant: Andrew Corporation
108 Rand Park Drive
Garner, NC 27529
USA

**Equipment Under Test:
(E.U.T.)** MR1918

FCC Identifier: BCR-MR1918

In Accordance With: **CFR 47, Part 24, Subpart E**
Broadband PCS Repeaters

Tested By: Nemko USA, Inc.
802 N. Kealy
Lewisville, TX 75057-3136

TESTED BY:

David Light, Senior Wireless Engineer

DATE: 27 April, 2009

APPROVED BY:

Tom Tidwell, Telecom Direct

DATE: 4 May, 2009

Number of Pages: 61

Table of Contents

SECTION 1.	SUMMARY OF TEST RESULTS	3
SECTION 2.	GENERAL EQUIPMENT SPECIFICATION	5
SECTION 3.	RF POWER OUTPUT	7
SECTION 4.	OCCUPIED BANDWIDTH	8
SECTION 5.	SPURIOUS EMISSIONS AT ANTENNA TERMINALS	17
SECTION 6.	FIELD STRENGTH OF SPURIOUS	38
SECTION 7.	TEST EQUIPMENT LIST	51
ANNEX A - TEST DETAILS		52
ANNEX B - TEST DIAGRAMS		58

EQUIPMENT: MR1918

Section 1. Summary of Test Results

Manufacturer: Andrew Corporation

Model No.: MR1918

Serial No.: 10

General: **All measurements are traceable to national standards.**

These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with CFR 47, Part 24, Subpart E.



New Submission



Production Unit



Class II Permissive Change



Pre-Production Unit

THIS TEST REPORT RELATES ONLY TO THE ITEM(S) TESTED.

THE FOLLOWING DEVIATIONS FROM, ADDITIONS TO, OR EXCLUSIONS FROM THE TEST SPECIFICATIONS HAVE BEEN MADE.

See "Summary of Test Data".



Nemko USA Inc. authorizes the above named company to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. This report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government. Nemko USA, Inc. is a NVLAP accredited laboratory.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko USA Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report. This report applies only to the items tested.

Summary Of Test Data

NAME OF TEST	PARA. NO.	SPEC.	RESULT
RF Power Output	24.232	100W	Complies
Occupied Bandwidth	2.1049	Input/Output	Complies
Spurious Emissions at Antenna Terminals	24.238(a)	-13 dBm	Complies
Field Strength of Spurious Emissions	24.238(a)	-13 dBm E.I.R.P.	Complies
Frequency Stability	24.235		NA


Footnotes:

Section 2. General Equipment Specification

Supply Voltage Input:		120 Vac		
Frequency Range:	Downlink:	1930 to 1990 MHz		
Frequency Range:	Uplink:	1850 to 1910 MHz		
Type of Modulation and Designator:	CDMA (G7W)	GSM (GXW)	EDGE (G7W)	W-CDMA (G7W)
Output Impedance:		50 ohms		
RF Output (Rated):	Downlink	22 dBm (158 mW)		
RF Output (Rated):	Uplink	22 dBm (158 mW)		
Frequency Translation:	F1-F1 ☒	F1-F2 ☐	N/A ☐	
Band Selection:	Software ☒	Duplexer Change ☐	Fullband Coverage ☐	

Description of EUT

The MR1918 is a bi-directional amplifier used to enhance signals between a mobile and a base station in a wireless network. It has been designed to increase signal strength in small and medium sized areas such as offices, shops, basements and manufacturing facilities.

System Diagram

Section 3. RF Power Output

NAME OF TEST: RF Power Output	PARA. NO.: 24.232
TESTED BY: David Light	DATE: 24 April 2009

Test Results: Complies.**Measurement Data:**

	Modulation	Output per Channel (dBm)	Composite Power (dBm)	Composite Power (mW)
Uplink	CDMA	19	22	158.4
Uplink	EDGE	19	22	158.4
Uplink	GSM	19	22	158.4
Uplink	W-CDMA	19	22	158.4
Downlink	CDMA	19	22	158.4
Downlink	EDGE	19	22	158.4
Downlink	GSM	19	22	158.4
Downlink	W-CDMA	19	22	158.4

Equipment Used: 1767-1470-1469-1082**Measurement Uncertainty:** +/- 1.7 dB**Temperature:** 22 °C**Relative Humidity:** 32 %

EQUIPMENT: MR1918

Section 4. Occupied Bandwidth

NAME OF TEST: Occupied Bandwidth	PARA. NO.: 24.238
TESTED BY: David Light	DATE: 24 April 2009

Test Results: Complies.

Test Data: See attached plot(s).

Equipment Used: 1767-1470-1469-1082

Measurement Uncertainty: 1X10⁻⁷ ppm

Temperature: 22 °C

Relative Humidity: 32 %

EQUIPMENT: MR1918


Test Data – Occupied Bandwidth

Downlink
CDMA - Output



Ref Lvl
40 dBm

RBW	30 kHz	RF Att	30 dB
VBW	30 kHz	Mixer	-10 dBm
SWT	14 ms	Unit	dBm



Date: 24.APR.2009 08:19:51

EQUIPMENT: MR1918


Test Data – Occupied Bandwidth

Downlink
CDMA - Input



Ref Lvl
-4.9 dBm

RBW	30 kHz	RF Att	10 dB
VBW	30 kHz	Mixer	-10 dBm
SWT	14 ms	Unit	dBm



Date: 24.APR.2009 08:21:10

EQUIPMENT: MR1918


Test Data – Occupied Bandwidth

Downlink
EDGE - Output



Ref Lvl
30 dBm

RBW	3 kHz	RF Att	20 dB
VBW	3 kHz	Mixer	-10 dBm
SWT	280 ms	Unit	dBm



Date: 24.APR.2009 09:02:43

EQUIPMENT: MR1918


Test Data – Occupied Bandwidth

Downlink
EDGE - Input



Ref Lvl
-14.9 dBm

RBW	3 kHz	RF Att	10 dB
VBW	3 kHz	Mixer	-10 dBm
SWT	280 ms	Unit	dBm



Date: 24.APR.2009 09:03:45

EQUIPMENT: MR1918


Test Data – Occupied Bandwidth

Downlink
GSM - Output



Ref Lvl
40 dBm

RBW	3 kHz	RF Att	30 dB
VBW	3 kHz	Mixer	-10 dBm
SWT	280 ms	Unit	dBm




Date: 24.APR.2009 08:39:12

EQUIPMENT: MR1918

Test Data – Occupied Bandwidth

Downlink
GSM - InputRef Lvl
-14.9 dBm

RBW	3 kHz	RF Att	10 dB
VBW	3 kHz	Mixer	-10 dBm
SWT	280 ms	Unit	dBm



Date: 24.APR.2009 08:40:07

EQUIPMENT: MR1918


Test Data – Occupied Bandwidth

Downlink
W-CDMA - Output



Ref Lvl
30 dBm

RBW	50 kHz	RF Att	20 dB
VBW	50 kHz	Mixer	-10 dBm
SWT	12 ms	Unit	dBm



Date: 24.APR.2009 09:16:27

EQUIPMENT: MR1918


Test Data – Occupied Bandwidth

Downlink
W-CDMA - Input



Ref Lvl
-14.9 dBm

RBW	50 kHz	RF Att	10 dB
VBW	50 kHz	Mixer	-10 dBm
SWT	12 ms	Unit	dBm



Date: 24.APR.2009 09:18:34

EQUIPMENT: MR1918


Test Data – Occupied Bandwidth

Uplink
CDMA - Output



Ref Lvl
30 dBm

RBW	30 kHz	RF Att	20 dB
VBW	30 kHz	Mixer	-10 dBm
SWT	14 ms	Unit	dBm




Date: 24.APR.2009 06:55:06

EQUIPMENT: MR1918

Test Data – Occupied Bandwidth

Uplink
CDMA - InputRef Lvl
-4.9 dBm

RBW	30 kHz	RF Att	10 dB
VBW	30 kHz	Mixer	-10 dBm
SWT	14 ms	Unit	dBm



Date: 24.APR.2009 06:56:21

EQUIPMENT: MR1918


Test Data – Occupied Bandwidth

Uplink
EDGE - Output



Ref Lvl
30 dBm

RBW	3 kHz	RF Att	20 dB
VBW	3 kHz	Mixer	-10 dBm
SWT	280 ms	Unit	dBm



Date: 24.APR.2009 08:57:15

EQUIPMENT: MR1918


Test Data – Occupied Bandwidth

Uplink
EDGE - Input



Ref Lvl
-14.9 dBm

RBW	3 kHz	RF Att	10 dB
VBW	3 kHz	Mixer	-10 dBm
SWT	280 ms	Unit	dBm



Date: 24.APR.2009 08:58:14

EQUIPMENT: MR1918


Test Data – Occupied Bandwidth

Uplink
GSM - Output



Ref Lvl
30 dBm

RBW	3 kHz	RF Att	20 dB
VBW	3 kHz	Mixer	-10 dBm
SWT	280 ms	Unit	dBm



Date: 24.APR.2009 08:50:11

EQUIPMENT: MR1918


Test Data – Occupied Bandwidth

Uplink
GSM - Input



Ref Lvl
-14.9 dBm

RBW	3 kHz	RF Att	10 dB
VBW	3 kHz	Mixer	-10 dBm
SWT	280 ms	Unit	dBm



Date: 24.APR.2009 08:51:20

EQUIPMENT: MR1918


Test Data – Occupied Bandwidth

Uplink
W-CDMA - Output



Ref Lvl
30 dBm

RBW	50 kHz	RF Att	20 dB
VBW	50 kHz	Mixer	-10 dBm
SWT	12 ms	Unit	dBm



Date: 24.APR.2009 10:55:57

EQUIPMENT: MR1918


Test Data – Occupied Bandwidth

Uplink
W-CDMA - Input



Ref Lvl
-14.9 dBm

RBW	50 kHz	RF Att	10 dB
VBW	50 kHz	Mixer	-10 dBm
SWT	12 ms	Unit	dBm



Date: 24.APR.2009 11:03:07

Section 5. Spurious Emissions at Antenna Terminals

NAME OF TEST: Spurious Emissions @ Antenna Terminals	PARA. NO.: 24.238
TESTED BY: David Light	DATE: 24 April 09

Test Results: Complies.

Test Data: See attached plot(s).

Equipment Used: 1767-1470-1469-1082

Measurement Uncertainty: +/- 1.7 dB

Temperature: 22 °C

Relative Humidity: 32 %

EQUIPMENT: MR1918

Test Data – Spurious Emissions at Antenna Terminals


Downlink

Lower Bandedge Intermodulation

CDMA

Ref Lvl
30 dBm

RBW	30 kHz	RF Att	20 dB
VBW	30 kHz	Mixer	-10 dBm
SWT	14 ms	Unit	dBm



Date: 24.APR.2009 07:02:19

EQUIPMENT: MR1918

Test Data – Spurious Emissions at Antenna Terminals

Downlink
Upper Bandedge Intermodulation
CDMA



Ref Lvl
30 dBm

RBW	30 kHz	RF Att	20 dB
VBW	30 kHz	Mixer	-10 dBm
SWT	14 ms	Unit	dBm




Date: 24.APR.2009 09:38:15

EQUIPMENT: MR1918

Test Data – Spurious Emissions at Antenna Terminals

Downlink
Spurs – CDMA



Date: 24.APR.2009 08:16:00

EQUIPMENT: MR1918

Test Data – Spurious Emissions at Antenna Terminals


Downlink

Lower Bandedge Intermodulation

EDGE

Ref Lvl
30 dBm


RBW	3 kHz	RF Att	20 dB
VBW	3 kHz	Mixer	-10 dBm
SWT	560 ms	Unit	dBm



Date: 24.APR.2009 09:01:02

EQUIPMENT: MR1918


Test Data – Spurious Emissions at Antenna Terminals

Downlink
Upper Bandedge Intermodulation
EDGE

Date: 24.APR.2009 09:31:30

EQUIPMENT: MR1918

Test Data – Spurious Emissions at Antenna Terminals

Downlink
Spurs – EDGE

Date: 24.APR.2009 09:02:16

EQUIPMENT: MR1918

Test Data – Spurious Emissions at Antenna Terminals


Downlink

Lower Bandedge Intermodulation

GSM

Ref Lvl
40 dBm

RBW	3 kHz	RF Att	30 dB
VBW	3 kHz	Mixer	-10 dBm
SWT	560 ms	Unit	dBm



Date: 24.APR.2009 08:36:57

EQUIPMENT: MR1918

Test Data – Spurious Emissions at Antenna Terminals


Downlink

Upper Bandedge Intermodulation

GSM

Ref Lvl
30 dBm

RBW	3 kHz	RF Att	20 dB
VBW	3 kHz	Mixer	-10 dBm
SWT	560 ms	Unit	dBm




Date: 24.APR.2009 09:33:05

EQUIPMENT: MR1918

Test Data – Spurious Emissions at Antenna Terminals

Downlink
Spurs – GSM




Date: 24.APR.2009 08:38:17

EQUIPMENT: MR1918

Test Data – Spurious Emissions at Antenna Terminals

Downlink
Lower Bandedge Intermodulation
W-CDMARef Lvl
30 dBm

RBW	50 kHz	RF Att	20 dB
VBW	50 kHz	Mixer	-10 dBm
SWT	12 ms	Unit	dBm




Date: 24.APR.2009 09:14:40

EQUIPMENT: MR1918

Test Data – Spurious Emissions at Antenna Terminals

Downlink
Upper Bandedge Intermodulation
W-CDMARef Lvl
30 dBm


RBW	50 kHz	RF Att	20 dB
VBW	50 kHz	Mixer	-10 dBm
SWT	12 ms	Unit	dBm



Date: 24.APR.2009 09:28:29

EQUIPMENT: MR1918

Test Data – Spurious Emissions at Antenna Terminals

Downlink
Spurs – W-CDMA -

Date: 24.APR.2009 09:17:09

EQUIPMENT: MR1918

Test Data – Spurious Emissions at Antenna Terminals

Uplink

Lower Bandedge Intermodulation

CDMA



Ref Lvl
30 dBm

RBW	30 kHz	RF Att	20 dB
VBW	30 kHz	Mixer	-10 dBm
SWT	14 ms	Unit	dBm



Date: 24.APR.2009 06:51:38

EQUIPMENT: MR1918

Test Data – Spurious Emissions at Antenna Terminals

Uplink
Upper Bandedge Intermodulation
CDMARef Lvl
30 dBm


RBW	30 kHz	RF Att	20 dB
VBW	30 kHz	Mixer	-10 dBm
SWT	14 ms	Unit	dBm



Date: 24.APR.2009 10:41:20

EQUIPMENT: MR1918

Test Data – Spurious Emissions at Antenna Terminals

Uplink
Spurs – CDMA

Date: 24.APR.2009 06:53:29


EQUIPMENT: MR1918

Test Data – Spurious Emissions at Antenna Terminals

Uplink

Lower Bandedge Intermodulation

EDGE



Date: 24.APR.2009 08:55:14

EQUIPMENT: MR1918

Test Data – Spurious Emissions at Antenna Terminals

Uplink

Upper Bandedge Intermodulation

EDGE

Ref Lvl
30 dBm


RBW	3 kHz	RF Att	20 dB
VBW	3 kHz	Mixer	-10 dBm
SWT	560 ms	Unit	dBm



Date: 24.APR.2009 10:44:50

EQUIPMENT: MR1918

Test Data – Spurious Emissions at Antenna Terminals

Uplink
Spurs – EDGE

Date: 24.APR.2009 08:56:44

EQUIPMENT: MR1918

Test Data – Spurious Emissions at Antenna Terminals


Uplink

Lower Bandedge Intermodulation

GSM

Ref Lvl
30 dBm

RBW	3 kHz	RF Att	20 dB
VBW	3 kHz	Mixer	-10 dBm
SWT	560 ms	Unit	dBm




Date: 24.APR.2009 08:47:53

EQUIPMENT: MR1918

Test Data – Spurious Emissions at Antenna Terminals


Uplink
Upper Bandedge Intermodulation
GSM



Date: 24.APR.2009 10:43:16

EQUIPMENT: MR1918

Test Data – Spurious Emissions at Antenna Terminals

Uplink
Spurs – GSM

Date: 24.APR.2009 08:49:09

EQUIPMENT: MR1918

Test Data – Spurious Emissions at Antenna Terminals

Uplink

Lower Bandedge Intermodulation

W-CDMA

Ref Lvl
30 dBm

RBW	50 kHz	RF Att	20 dB
VBW	50 kHz	Mixer	-10 dBm
SWT	12 ms	Unit	dBm



Date: 24.APR.2009 10:54:19

EQUIPMENT: MR1918

Test Data – Spurious Emissions at Antenna Terminals

Uplink
Upper Bandedge Intermodulation
W-CDMARef Lvl
30 dBm


RBW	50 kHz	RF Att	20 dB
VBW	50 kHz	Mixer	-10 dBm
SWT	12 ms	Unit	dBm



Date: 24.APR.2009 10:48:24

EQUIPMENT: MR1918

Test Data – Spurious Emissions at Antenna Terminals

Uplink
Spurs – W-CDMA -

Date: 24.APR.2009 10:56:50

Section 6. Field Strength of Spurious

NAME OF TEST: Field Strength of Spurious Emissions	PARA. NO.: 24.238
TESTED BY: David Light	DATE: 24 April 2009

Test Results: Complies.**Test Data:** The spectrum was searched from 30 MHz to the tenth harmonic of the carrier. There were no emissions detected above the noise floor which was at least 20 dB below the specification limit.**Equipment Used:** 1767-1484-1485-1016-993-791-1763**Measurement Uncertainty:** +/-1.7 dB**Temperature:** 20 °C**Relative Humidity:** 30 %

RBW=VBW=100 kHz below 1000 MHz

RBW=VBW=1 MHz above 1000 MHz

Peak detector

EQUIPMENT: MR1918

Section 7. Test Equipment List

Nemko ID	Description	Manufacturer Model Number	Serial Number	Calibration Date	Calibration Due
1767	MI Test Receiver 20Hz - 26.5 GHz - 150 - +30 dBm LC	ROHDE & SCHWARZ ESIB26	837491/0002	09/20/07	09/20/09
1016	Pre-Amp	HEWLETT PACKARD 8449A	2749A00159	05/07/08	05/07/09
791	PREAMP, 25dB	Nemko USA, Inc. LNA25	398	05/07/08	05/07/09
1484	Cable	Storm PR90-010-072	N/A	05/07/08	05/07/09
1485	Cable	Storm PR90-010-216	N/A	05/07/08	05/07/09
1763	Bilog Antenna	Schaffner CBL 6111D	22926	11/04/08	11/04/09
993	Horn antenna	A.H. Systems SAS-200/571	XXX	08/31/07	08/31/09
1470	10 db Attenuator DC 18 Ghz	MCL Inc. BW-S10W2 10db-2WDC	NONE	CBU	N/A
1469	10 db Attenuator DC 18 Ghz	MCL Inc. BW-S10W2 10db-2WDC	NONE	CBU	N/A
1082	CABLE 2m	Astrolab 32027-2-29094-72TC	N/A	CBU	N/A

ANNEX A - TEST DETAILS

NAME OF TEST: RF Power Output**PARA. NO.: 2.1046**

Minimum Standard: Para. No.24.232. Base stations are limited to 1640 watts peak E.I.R.P. with an antenna height up to 300 meters HAAT. In no case may the peak output power of a base station transmitter exceed 100 watts.

Method Of Measurement:Detachable Antenna:

The peak power at antenna terminals is measured using an in-line peak power meter or spectrum analyzer. Power output is measured with the maximum rated input level.

Integral Antenna:

The antenna substitution method is used to determine the equivalent radiated power at spurious frequencies. The spurious emissions are measured at a distance of 3 meters. The EUT is then replaced with a reference substitution antenna with a known gain referenced to an isotropic radiator. This antenna is fed with a signal at the spurious frequency. The level of the signal is adjusted to repeat the previously measured level. The resulting eirp is the signal level fed to the reference antenna corrected for gain referenced to an isotropic radiator.

NAME OF TEST: Occupied Bandwidth

PARA. NO.: 2.1049

Minimum Standard: Input/Output

Method Of Measurement:

CDMA

Spectrum analyzer settings:

RBW=VBW=30 kHz

Span: 5 MHz

Sweep: Auto

GSM / EDGE

RBW=VBW= 3 kHz

Span: 1 MHz

Sweep: Auto

TDMA

RBW=VBW= 1 kHz

Span: 1 MHz

Sweep: Auto

W-CDMA

RBW=VBW= 100 kHz

Span: 10 MHz

Sweep: Auto

NAME OF TEST: Spurious Emission at Antenna Terminals PARA. NO.: 24.238**Minimum Standard:**

Para. No.24.238(a). On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power by at least $43 + 10 \log (P)$ dB.

Method Of Measurement:

Spectrum analyzer settings:

CDMA

RBW: 1 MHz (> 1 MHz from Band Edge)
RBW: 30 kHz (< 1MHz from Band Edge)
VBW: $\geq$ RBW
Sweep: Auto
Video Avg: 6 Sweeps

GSM / EDGE

RBW: 1 MHz (> 1 MHz from Band Edge)
RBW: 3 kHz (< 1 MHz from Band Edge)
VBW: $\geq$ RBW
Sweep: Auto
Video Avg: Disabled

TDMA

RBW: 1 MHz (> 1 MHz from Band Edge)
RBW: 3 kHz (< 1 MHz from Band Edge)
VBW: $\geq$ RBW
Sweep: Auto
Video Avg: Disabled

W-CDMA

RBW: 1 MHz (> 1 MHz from Band Edge)
RBW: 100 kHz (< 1MHz from Band Edge)
VBW: $\geq$ RBW
Sweep: Auto
Video Avg: 6 Sweeps

To demonstrate compliance at band edges the frequency of the input signal is set to the lowest and highest assigned channel and the center frequency of the spectrum analyzer is set to the upper and lower edges of the appropriate frequency block.

NAME OF TEST: Field Strength of Spurious Radiation PARA. NO.: 24.238

Minimum Standard: Para. No.24.238(a). On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power by at least $43 + 10 \log (P)$ dB.

Method of Measurement TIA/EIA-603-1992

The antenna substitution method is used to determine the equivalent radiated power at spurious frequencies. The spurious emissions are measured at a distance of 3 meters. The EUT is then replaced with a reference substitution antenna with a known gain referenced to an isotropic radiator. This antenna is fed with a signal at the spurious frequency. The level of the signal is adjusted to repeat the previously measured level. The resulting eirp is the signal level fed to the reference antenna corrected for gain referenced to an isotropic radiator.

NAME OF TEST: Frequency Stability**PARA. NO.: 2.1055**

Minimum Standard: Para. No. 24.235. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Method Of Measurement:Frequency Stability With Voltage Variation


The E.U.T. is placed in an environmental chamber and allowed to stabilize at +20 degrees Celsius for at least 15 minutes. The frequency counter and signal generator are phase locked with the same 10 MHz reference frequency by connecting the 10 MHz ref. out of the counter to the 10 MHz ref, in of the signal generator. With the voltage input to the E.U.T. set to 85% S.T.V., the frequency is measured in 30 second intervals for a period of 5 minutes. This procedure is repeated at 100% S.T.V. and 115% S.T.V.

Frequency Stability With Temperature Variation


The input voltage to the E.U.T. is set to S.T.V. and the temperature of the environmental chamber is varied in 10 degree steps from -30 degrees C to +50 degrees C. The E.U.T. is allowed to stabilize at each temperature and the frequency is measured in 30 second intervals for a period of 5 minutes.

ANNEX B - TEST DIAGRAMS



Para. No. 2.985 - R.F. Power Output




Para. No. 2.989 - Occupied Bandwidth



Para. No. 2.991 Spurious Emissions at Antenna Terminals



Para. No. 2.993 - Field Strength of Spurious Radiation



Para. No. 2.995 - Frequency Stability

