Maximum Permissive Exposure

FCC ID: BEJ-PD261

Product Name: Pocket Photo

Model No: (1)PD261 (2)PD261W (3)PD261P

Pursuant to KDB 447498 D01 v05r02 that SAR testing is not required when EUT has output power related to distance satisfy with following table.

MHz	5	10	15	20	25	mm		
150	39	77	116	155	194			
300	27	55	82	110	137			
450	22	45	67	89	112			
835	16	33	49	66	82			
900	16	32	47	63	79			
1500	12	24	37	49	61	SAR Test		
1900	11	22	33	44	54	Exclusion Threshold (mW)		
2450	10	19	29	38	48			
3600	8	16	24	32	40			
5200	7	13	20	26	33			
5400	6	13	19	26	32			
5800	6	12	19	25	31			
MHz	30	35	40	45	50	mm		
150	232	271	310	349	387			
300	164	192	219	246	274			
450	134	157	179	201	224			
835	98	115	131	148	164			
900	95	111	126	142	158	G 4 D		
1500	73	86	98	110	122	SAR Test Exclusion		
1900	65	76	87	98	109	Threshold (mW)		
2450	57	67	77	86	96			
2430								
3600	47	55	63	71	79			
	47 39	55 46	63 53	71 59	79 66			
3600								

This application FCC ID: BEJ-PD261 is equipped a dielectric chip antenna. Thus the most closely distance from antenna to user is 5 mm(indicates in next page) and the max output power (e.i.r.p.) is 6.663 dBm (4.637 mW) which is satisfy with the exclusion level 10 mW.

Ī	Max Output Power(dBm)	Antenna Gain (dBi)	e.i.r.p. in dBm	e.i.r.p. in mW
ŀ	1 ,	\ /	<u> </u>	
	6.883	-0.22	6.663	4.637

Sincerely Yours,

Mr. Ben Cheng

Manager

AUDIX Technology Corporation



