

FCC EVALUATION REPORT FOR CERTIFICATION

FCC Class B (Class II Permissive Change)

Applicant: LG Electronics Inc.

19-1, Cheongho-ri, Jinwi-myeon,

Pyeongteak-si, Gyeonggi-do, Korea.

Attn: Mr. Do-Hyung Kim, Chief research engineer

Date of Issue: September 21, 2011

Order Number: GETEC-C1-11-214

Test Report Number: GETEC-E3-11-107

Test Site: Gumi College EMC Center

FCC Registration Number: (100749, 443957)

FCC ID. : BEJ42LW5300UC

Applicant : LG Electronics Inc.

Rule Part(s)	: FCC Part 15 Subpart B
Equipment Class	: Class B computing device peripheral (JBP)
EUT Type	: LED LCD TV/Monitor
Type of Authority	: Certification
Model Name	: 42LW5300-UC
Trade Name	: LG
Class II Change(s)	: With alternate power board and panel module

This equipment has been shown to be in compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003 / Canadian standard ICES-003

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Tested by,

Reviewed by,



Hyun Kim, Engineer
GUMI College EMC center



Jae-Hoon Jeong, Senior Engineer
GUMI College EMC center



CONTENTS

1. GENERAL INFORMATION	3
2. INTRODUCTION	4
3. PRODUCT INFORMATION	5
3.1 DESCRIPTION OF EUT.....	5
3.2 SUPPORT EQUIPMENT / CABLES USED	6
3.3 MODIFICATION ITEM(S)	7
4. DESCRIPTION OF TESTS.....	8
4.1 TEST CONDITION.....	8
4.2 CONDUCTED EMISSION	9
4.3 RADIATED EMISSION.....	10
5. CONDUCTED EMISSION.....	11
5.1 OPERATING ENVIRONMENT	11
5.2 TEST SET-UP	11
5.3 MEASUREMENT UNCERTAINTY.....	11
5.4 LIMIT	12
5.5 TEST EQUIPMENT USED.....	12
5.6 TEST DATA FOR CONDUCTED EMISSION	12
6. RADIATED EMISSION	21
6.1 OPERATING ENVIRONMENT	21
6.2 TEST SET-UP	21
6.3 MEASUREMENT UNCERTAINTY.....	21
6.4 LIMIT	22
6.5 TEST EQUIPMENT USED.....	22
6.6 TEST DATA FOR RADIATED EMISSION	22
7. SAMPLE CALCULATIONS.....	27
7.1 EXAMPLE 1 :	27
7.2 EXAMPLE 2 :	27
8. RECOMMENDATION & CONCLUSION.....	28

APPENDIX A – INFORMATION

APPENDIX B – TEST SET-UP PHOTOGRAPHS

APPENDIX C – EXTERNAL PHOTOGRAPHS

APPENDIX D – INTERNAL PHOTOGRAPHS



Scope: Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and / or unintentional radiators for compliance with technical rules and regulations of the Federal Communications Commission.

1. General Information

Applicant: LG Electronics Inc.

Applicant Address: 19-1, Cheongho-ri, Jinwi-myeon, Pyeongteak-si, Gyeonggi-do, Korea.

Manufacturer: LG Electronics Inc.

Manufacturer Address: 19-1, Cheongho-ri, Jinwi-myeon, Pyeongteak-si, Gyeonggi-do, Korea.

Contact Person: Mr. Do-Hyung Kim, Chief research engineer

Tel Number: +82-31-610-9623

- **FCC ID.** BEJ42LW5300UC
- **EUT Type** LED LCD TV/Monitor
- **Model Name** 42LW5300-UC
- **Trade Name** LG
- **Serial Number** Prototype
- **Rule Part(s)** FCC Part 15 Subpart B
- **Type of Authority** Certification
- **Test Procedure(s)** ANSI C63.4 (2003) / Canadian standard ICES-003
- **Dates of Test** September 9 ~ 14, 2011
- **Place of Test** **Gumi College EMC Center** (FCC Registration Number: 100749, 443957)
407, Bugok-dong, Gumi-si, Gyeongbuk, Korea.
- **Test Report Number** GETEC-E3-11-107
- **Dates of Issue** September 21, 2011
- **Class II Change(s)** With alternate power board and panel module



2. Introduction

The measurement procedure described in American National Standard for Methods of Measurement of Radio-Nose Emissions From Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz (ASNI C63.4-2003) was used in determining radiated and conducted emissions emanating from **LG Electronics Inc. LED LCD TV/Monitor (Model Name: 42LW5300-UC)**

These measurement tests were conducted at **Gumi College EMC Center**.

The site address is 407, Bugok-dong, Gumi-si, Gyeongbuk, Korea.

This test site is one of the highest point of Gumi 1 college at about 200 km away from Seoul city and 40 km away from Daegu city. It is located in the valley surrounded by mountains in all directions where ambient radio signal conditions are quiet and a favorable area to measure the radio frequency interference on open field test site for the computing and ISM devices manufactures. The detailed description of the measurement facility was found to be in compliance with the requirements of §2.948 according to ANSI C63.4 (2003)



GUMI COLLEGE EMC CENTER
407, Bugok-dong, Gumi-si,
Gyeongbuk 730-711, Korea.
Tel: +82-54-440-1195
Fax: +82-54-440-1199

Fig 1. The map above shows the Gumi College in vicinity area.



3. Product Information

3.1 Description of EUT

The Equipment under Test (EUT) is the **LG Electronics Inc. LED LCD TV/Monitor (Model Name: 42LW5300-UC) FCC ID.: BEJ42LW5300UC**

MODELS		42LW5000 (42LW5000-UC)
		42LW5300 (42LW5300-UC)
Dimensions (W x H x D)	With stand	998.0 mm x 684.0 mm x 256.0 mm (39.2 inch x 26.9 inch x 10.0 inch)
	Without stand	998.0 mm x 615.0 mm x 30.4 mm (39.2 inch x 24.2 inch x 1.1 inch)
Weight	With stand	15.5 kg (34.1 lbs)
	Without stand	13.3 kg (29.3 lbs)
Current Value / Power consumption		1.1 A / 110 W
Power requirement		USA, Canada, Mexico: AC 120 V ~ 50 / 60 Hz Other Country: AC 100 - 240 V ~ 50 / 60 Hz
Television System		NTSC-M, ATSC, 64 & 256 QAM
Program Coverage		VHF 2-13, UHF 14-69, CATV 1-135, DTV 2-69, CADTV 1-135
External Antenna Impedance		75 Ω
Environment condition	Operating Temperature	0 - 40 °C
	Operating Humidity	Less than 80 %
	Storage Temperature	-20 - 60 °C
	Storage Humidity	Less than 85 %

-. Maximum Frequency Range :667 MHz



3.2 Support Equipment / Cables used

3.2.1 Used Support Equipment

Description	Manufacturer	Model Name	S/N & FCC ID.
PC(Main board)	ASROCK	770iCafe	S/N: 0AM0X3097310 FCC ID.: DoC
Video card	Rextechnology Co., Ltd.	HD4850	S/N: L5H041947 FCC ID.: DoC
PS2 keyboard	COMPAQ	166516-AD6	S/N: B13BBOR391006D FCC ID.: AQ6-23K15
USB mouse	Great Pleasure Electronics Co., Ltd.	GP-M3100UE	S/N: 14036766 FCC ID.: DoC
DVD player	LG Electronics Inc.	LC-954	S/N: 3850R-Z674K FCC ID.: Verification
BD player	LG Electronics Inc.	BD645	S/N: 104INWA122881 FCC ID.: Verification
IR remote controller	HANSUNG ELECTRONICS	AKB73375501	S/N: None. FCC ID.: N/A
USB memory stick	SAMSUNG	SUM-PSB4	S/N: TBBB202478F FCC ID.: DoC
Headset	PHILIPS	SBC HL140	S/N: None. FCC ID.: N/A
TV signal generator	FLUKE	54200M01	S/N: 831011 FCC ID.: DoC

See “Appendix B– Test Setup Photographs” for actual system test set-up

3.2.2 System configuration

Description	Manufacturer	Model Name	S/N & FCC ID.
IR remote controller	OHNSUNG ELECTRONICS CO., LTD.	AKB72915280	S/N: None. FCC ID.: N/A



3.2.3 Used Cable(s)

Cable Name	Condition	Description
Power cable	Connected to the EUT	1.80 m unshielded
RGB(Analog) cable	Connected to the EUT and PC	1.80 m shielded with two ferrite cores
HDMI/DVI(Digital) cable	Connected to the EUT and PC	2.00 m shielded
RS-232C (Control & service) cable	Connected to the EUT and PC	1.80 m shielded
Audio(RGB/DVI) in cable	Connected to the EUT and PC	1.50 m shielded
AV in cable	Connected to the EUT and DVD player	3.00 m shielded
AV 2 in cable	Connected to the EUT and BD player	0.90 m shielded
Component in cable	Connected to the EUT and DVD player	3.00 m shielded
Headset cable	Connected to the EUT and headset	1.20 m shielded
Antenna cable	Connected to the EUT and TV signal generator	10.00 m shielded

3.3 Modification Item(s)

- None



4. Description of tests

4.1 Test Condition

The EUT was installed, arranged and operated in a manner that is most representative of equipment as typically used. The measurements were carried out while varying operating modes and cable positions within typically arrangement to determine maximum emission level.

The representative and worst test mode(s) were noted in the test report.

- Test Voltage / Frequency : AC 120 V / 60 Hz
- Test Mode(s)

- . Monitor mode

Radiated emission: 1 920 × 1 080 / 60 Hz (RGB: Analog, HDMI/DVI: Digital)

Conducted emission: 1 920 × 1 080 / 60 Hz (RGB: Analog, HDMI/DVI: Digital)

1 024 × 768 / 60 Hz (RGB: Analog), 640 × 480 / 60 Hz (RGB: Analog)

◆ Operating test pattern

- . "H" character scrolling mode (Font size: 10)
- . Black background white character
- . Brightness and contrast was adjusted as maximum level
- . Continuous playback of 1 kHz audio file with winamp player
- . USB memory stick was connected to the USB port

"The verification report for TV/AV mode would be issued by LG Electronics Inc."



4.2 Conducted Emission

The Line conducted emission test facility is inside a 4 m × 8 m × 2.5 m shielded enclosure. (FCC Registration No.: 100749)

The EUT was placed on a non-conducting 1.0 m by 1.5 m table, which is 0.8 m in height and 0.4 m away from the vertical wall of the shielded enclosure.

The EUT is powered from the Rohde & Schwarz LISN (ESH2-Z5) and the support equipment is powered from the Rohde & Schwarz LISN (ESH3-Z5). Powers to the LISN are filtered by high-current high insertion loss power line filter.

Sufficient time for EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition.

The RF output of the LISN was connected to the EMI test receiver (Rohde & Schwarz, ESCS30).

The EMI test receiver was scanned from 150 kHz to 30 MHz with 20 ms sweep time to determine the frequency producing the maximum EME from the EUT. The frequency producing the maximum level was re-examined using Quasi-Peak mode of the EMI test receiver.

The bandwidth of Quasi-peak mode was set to 9 kHz. Each emission was maximized consistent with typical applications by varying the configuration of the test sample. Interface cables were connected to the available interface ports of the test unit. The effect of varying the position of cables was investigated to find the configuration that produces maximum diagram emission. Excess cable lengths were bundled at center with 30 cm ~ 40 cm.

Each EME reported was calibrated using the R/S signal generator




Fig 2. Impedance of LISN



4.3 Radiated Emission

Preliminary measurements were conducted 3 m semi anechoic chamber using broadband antennas to determine the frequency producing the maximum EME. Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The technology configuration, mode of operation and turntable azimuth with respect to antenna was note for each frequency found.

Final measurements were made 3 m chamber (FCC registration No.: 443957) and/or 10 m OATS (FCC registration No.: 100749).

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition.

Each frequency found during pre-scan measurements was re-examined and investigated using EMI test receiver. The detector function was set to CISPR quasi-peak mode average mode and the bandwidth of the receiver was set to 120 kHz or 1 MHz depending on the frequency or type of signal.

The EUT, support equipment and interconnecting cables were reconfigured to the setup producing the maximum emission for the frequency and were placed on top of a 0.8 m high non-metallic 1.0 m × 1.5 m table.

The turntable containing the test sample was rotated; the antenna height was varied 1 to 4 meter and stopped at the azimuth or height producing the maximum emission.

Each EME reported was calibrated using the R/S signal generator




Fig 3. Dimensions of test site



5. Conducted Emission

5.1 Operating Environment

Temperature : 24.0 °C
Relative Humidity : 51.0 % R.H.

5.2 Test Set-up

The conducted emission measurements were performed in the shielded room.

The EUT was placed on wooden table, 0.8 m heights above the floor, 0.4 m from the reference ground plane (GRP) wall and 0.8 m from AMN & ISN.

AMN is bonded on horizontal reference ground plane.

The ground plane, which was electrically bonded to the shield room, ground system and all power lines entering the shield room, were filtered.

5.3 Measurement Uncertainty

The measurement uncertainty was calculated in accordance with ISO "Guide to the expression of uncertainty in measurement."

The measurement uncertainty was given with a confidence of 95 %.

Test Items	Uncertainty	Remark
Conducted emission (9 kHz ~ 150 kHz)	± 2.71 dB	Confidence levels of 95 % ($k = 2$)
Conducted emission (150 kHz ~ 30 MHz)	± 3.34 dB	Confidence levels of 95 % ($k = 2$)



5.4 Limit

RFI Conducted	FCC Limit(dB μ V/m) Class B	
Freq. Range	Quasi-Peak	Average
150 kHz ~ 0.5 MHz	66 ~ 56*	56 ~ 46*
0.5 MHz ~ 5 MHz	56	46
5 MHz ~ 30 MHz	60	50
*Limits decreases linearly with the logarithm of frequency.		

5.5 Test Equipment used

Model Name	Manufacturer	Description	Serial Number	Due to Calibration
■ - ESCS30	Rohde & Schwarz	EMI Test Receiver	839809/003	12. 10. 2011
■ - ESH3-Z5	Rohde & Schwarz	LISN	838979/020	12. 10. 2011
■ - ESH2-Z5	Rohde & Schwarz	LISN	829991/009	12. 10. 2011
□ - ISN T8	TESEQ. GmbH	ISN	24568	11. 09. 2011


5.6 Test data for Conducted Emission

-. Test Date : September 7, 2011
-. Resolution Bandwidth : 9 kHz
-. Frequency Range : 0.15 MHz ~ 30 MHz



◆ Operating condition: 1 920 × 1 080 / 60 Hz (RGB: Analog)

Voltage with 4-Line-LISN_L1



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.220000	33.9	1000.000	9.000	GND	L1	10.1	28.7	62.6	
0.236000	33.8	1000.000	9.000	GND	L1	10.1	28.2	62.0	
1.152000	22.0	1000.000	9.000	GND	L1	10.1	34.0	56.0	
2.176000	19.8	1000.000	9.000	GND	L1	10.2	36.2	56.0	
4.940000	36.5	1000.000	9.000	GND	L1	10.3	19.5	56.0	
11.728000	48.6	1000.000	9.000	GND	L1	10.6	11.4	60.0	
13.328000	39.8	1000.000	9.000	GND	L1	10.7	20.2	60.0	


Final Measurement Detector 2

Frequency (MHz)	CAverage (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.252000	28.3	1000.000	9.000	GND	L1	10.1	23.1	51.4	
0.548000	14.5	1000.000	9.000	GND	L1	10.1	31.5	46.0	
1.304000	14.6	1000.000	9.000	GND	L1	10.1	31.4	46.0	
4.800000	29.8	1000.000	9.000	GND	L1	10.3	16.2	46.0	
11.980000	40.8	1000.000	9.000	GND	L1	10.7	9.2	50.0	
13.372000	36.0	1000.000	9.000	GND	L1	10.7	14.0	50.0	

< Fig 4. Conducted emission result (Live line) >



Voltage with 4-Line-LISN_N



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.222000	34.2	1000.000	9.000	GND	N	10.1	28.4	62.6	
0.242000	34.7	1000.000	9.000	GND	N	10.1	27.1	61.8	
0.762000	21.9	1000.000	9.000	GND	N	10.1	34.1	56.0	
1.290000	22.3	1000.000	9.000	GND	N	10.1	33.7	56.0	
4.850000	35.0	1000.000	9.000	GND	N	10.3	21.0	56.0	
11.318000	48.3	1000.000	9.000	GND	N	10.6	11.7	60.0	
13.374000	42.4	1000.000	9.000	GND	N	10.7	17.6	60.0	

Final Measurement Detector 2


Frequency (MHz)	CAverage (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.218000	24.2	1000.000	9.000	GND	N	10.1	28.5	52.7	
0.254000	28.7	1000.000	9.000	GND	N	10.1	22.7	51.4	
0.546000	16.7	1000.000	9.000	GND	N	10.1	29.3	46.0	
1.234000	15.0	1000.000	9.000	GND	N	10.1	31.0	46.0	
4.798000	30.2	1000.000	9.000	GND	N	10.3	15.8	46.0	
11.798000	43.9	1000.000	9.000	GND	N	10.6	6.1	50.0	
13.366000	37.5	1000.000	9.000	GND	N	10.7	12.5	50.0	

< Fig 5. Conducted emission result (Neutral line) >



◆ Operating condition: 1 024 × 768 / 60 Hz (RGB: Analog)

Voltage with 4-Line-LISN_L1



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.220000	33.6	1000.000	9.000	GND	L1	10.1	29.0	62.6	
0.224000	33.7	1000.000	9.000	GND	L1	10.1	28.8	62.5	
0.764000	21.5	1000.000	9.000	GND	L1	10.1	34.5	56.0	
2.172000	20.0	1000.000	9.000	GND	L1	10.2	36.0	56.0	
4.800000	37.9	1000.000	9.000	GND	L1	10.3	18.1	56.0	
11.176000	49.1	1000.000	9.000	GND	L1	10.6	10.9	60.0	
13.372000	40.1	1000.000	9.000	GND	L1	10.7	19.9	60.0	


Final Measurement Detector 2

Frequency (MHz)	CAverage (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.252000	28.0	1000.000	9.000	GND	L1	10.1	23.4	51.4	
0.824000	15.3	1000.000	9.000	GND	L1	10.1	30.7	46.0	
1.300000	15.1	1000.000	9.000	GND	L1	10.1	30.9	46.0	
4.800000	30.1	1000.000	9.000	GND	L1	10.3	15.9	46.0	
10.972000	41.5	1000.000	9.000	GND	L1	10.6	8.5	50.0	
13.372000	35.3	1000.000	9.000	GND	L1	10.7	14.7	50.0	

< Fig 6. Conducted emission result (Live line) >



Voltage with 4-Line-LISN_N



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.218000	34.0	1000.000	9.000	GND	N	10.1	28.7	62.7	
0.246000	34.9	1000.000	9.000	GND	N	10.1	26.8	61.7	
0.546000	24.2	1000.000	9.000	GND	N	10.1	31.8	56.0	
1.370000	23.6	1000.000	9.000	GND	N	10.1	32.4	56.0	
4.798000	38.2	1000.000	9.000	GND	N	10.3	17.8	56.0	
11.382000	49.3	1000.000	9.000	GND	N	10.6	10.7	60.0	
13.354000	40.6	1000.000	9.000	GND	N	10.7	19.4	60.0	

Final Measurement Detector 2


Frequency (MHz)	CAverage (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.218000	24.1	1000.000	9.000	GND	N	10.1	28.6	52.7	
0.254000	28.7	1000.000	9.000	GND	N	10.1	22.7	51.4	
0.546000	17.0	1000.000	9.000	GND	N	10.1	29.0	46.0	
1.302000	15.0	1000.000	9.000	GND	N	10.1	31.0	46.0	
4.798000	31.0	1000.000	9.000	GND	N	10.3	15.0	46.0	
12.002000	43.5	1000.000	9.000	GND	N	10.6	6.5	50.0	
13.374000	36.4	1000.000	9.000	GND	N	10.7	13.6	50.0	

< Fig 7. Conducted emission result (Neutral line) >



◆ Operating condition: 640 × 480 / 60 Hz (RGB: Analog)

Voltage with 4-Line-LISN_L1



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.220000	33.8	1000.000	9.000	GND	L1	10.1	28.8	62.6	
0.808000	23.6	1000.000	9.000	GND	L1	10.1	32.4	56.0	
2.580000	21.5	1000.000	9.000	GND	L1	10.2	34.5	56.0	
4.936000	40.6	1000.000	9.000	GND	L1	10.3	15.4	56.0	
11.652000	46.3	1000.000	9.000	GND	L1	10.6	13.7	60.0	
13.376000	39.9	1000.000	9.000	GND	L1	10.7	20.2	60.0	


Final Measurement Detector 2

Frequency (MHz)	CAverage (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.252000	27.8	1000.000	9.000	GND	L1	10.1	23.6	51.4	
0.256000	27.7	1000.000	9.000	GND	L1	10.1	23.6	51.3	
0.820000	15.7	1000.000	9.000	GND	L1	10.1	30.3	46.0	
2.648000	18.3	1000.000	9.000	GND	L1	10.2	27.7	46.0	
4.872000	35.1	1000.000	9.000	GND	L1	10.3	10.9	46.0	
12.072000	41.6	1000.000	9.000	GND	L1	10.7	8.4	50.0	
13.368000	35.7	1000.000	9.000	GND	L1	10.7	14.3	50.0	

< Fig 8. Conducted emission result (Live line) >



Voltage with 4-Line-LISN_N



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.226000	33.4	1000.000	9.000	GND	N	10.1	29.0	62.4	
0.238000	34.1	1000.000	9.000	GND	N	10.1	27.9	62.0	
0.646000	21.7	1000.000	9.000	GND	N	10.1	34.3	56.0	
2.630000	22.2	1000.000	9.000	GND	N	10.2	33.8	56.0	
4.802000	40.5	1000.000	9.000	GND	N	10.3	15.5	56.0	
11.246000	51.4	1000.000	9.000	GND	N	10.6	8.6	60.0	
13.374000	41.4	1000.000	9.000	GND	N	10.7	18.6	60.0	

Final Measurement Detector 2


Frequency (MHz)	CAverage (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.218000	23.8	1000.000	9.000	GND	N	10.1	28.9	52.7	
0.254000	28.2	1000.000	9.000	GND	N	10.1	23.2	51.4	
0.546000	17.0	1000.000	9.000	GND	N	10.1	29.0	46.0	
2.630000	17.1	1000.000	9.000	GND	N	10.2	28.9	46.0	
4.798000	35.9	1000.000	9.000	GND	N	10.3	10.1	46.0	
11.866000	42.9	1000.000	9.000	GND	N	10.6	7.1	50.0	
13.374000	36.6	1000.000	9.000	GND	N	10.7	13.4	50.0	

< Fig 9. Conducted emission result (Neutral line) >



◆ Operating condition: 1 920 × 1 080 / 60 Hz (HDMI/DVI: Digital)

Voltage with 4-Line-LISN_L1



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.178000	50.6	1000.000	9.000	GND	L1	10.1	13.9	64.5	
0.536000	23.2	1000.000	9.000	GND	L1	10.1	32.8	56.0	
0.548000	23.8	1000.000	9.000	GND	L1	10.1	32.2	56.0	
1.268000	22.8	1000.000	9.000	GND	L1	10.1	33.2	56.0	
4.848000	34.8	1000.000	9.000	GND	L1	10.3	21.2	56.0	
10.976000	48.8	1000.000	9.000	GND	L1	10.6	11.2	60.0	
14.612000	31.9	1000.000	9.000	GND	L1	10.8	28.1	60.0	


Final Measurement Detector 2

Frequency (MHz)	CAverage (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.178000	46.7	1000.000	9.000	GND	L1	10.1	7.8	54.5	
0.332000	19.2	1000.000	9.000	GND	L1	10.1	30.0	49.2	
0.544000	15.5	1000.000	9.000	GND	L1	10.1	30.5	46.0	
1.232000	15.9	1000.000	9.000	GND	L1	10.1	30.1	46.0	
4.804000	29.8	1000.000	9.000	GND	L1	10.3	16.2	46.0	
10.908000	41.8	1000.000	9.000	GND	L1	10.6	8.2	50.0	
13.380000	35.3	1000.000	9.000	GND	L1	10.7	14.7	50.0	

< Fig 10. Conducted emission result (Live line) >



Voltage with 4-Line-LISN_N



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.178000	51.8	1000.000	9.000	GND	N	10.1	12.7	64.5	
0.342000	24.8	1000.000	9.000	GND	N	10.1	34.2	59.0	
0.522000	23.6	1000.000	9.000	GND	N	10.1	32.4	56.0	
1.258000	21.8	1000.000	9.000	GND	N	10.1	34.2	56.0	
4.938000	38.2	1000.000	9.000	GND	N	10.3	17.8	56.0	
11.042000	48.6	1000.000	9.000	GND	N	10.5	11.4	60.0	
13.346000	40.8	1000.000	9.000	GND	N	10.7	19.2	60.0	

Final Measurement Detector 2

Frequency (MHz)	CAverage (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.178000	46.1	1000.000	9.000	GND	N	10.1	8.4	54.5	
0.330000	20.1	1000.000	9.000	GND	N	10.1	29.1	49.2	
0.550000	15.2	1000.000	9.000	GND	N	10.1	30.8	46.0	
1.234000	15.6	1000.000	9.000	GND	N	10.1	30.4	46.0	
4.802000	30.2	1000.000	9.000	GND	N	10.3	15.8	46.0	
11.250000	42.8	1000.000	9.000	GND	N	10.6	7.2	50.0	
16.010000	38.1	1000.000	9.000	GND	N	10.8	11.9	50.0	

< Fig 11. Conducted emission result (Neutral line) >



6. Radiated Emission

6.1 Operating Environment

Temperature : 25.0 °C
Relative Humidity : 45.0 % R.H.

6.2 Test Set-up

A preliminary and final measurement was at 3 m anechoic chamber.

The EUT was placed on a non-conductive turntable approximately 0.8 m above the ground plane.

The turntable with EUT was rotated 360°, and the antenna was varied in height between 1.0 m and 4.0 m in order to determine the maximum emission levels.

This procedure was performed for both horizontal and vertical polarization of the receiving antenna.

6.3 Measurement Uncertainty

The measurement uncertainty was calculated in accordance with ISO “Guide to the expression of uncertainty in measurement”.

The measurement uncertainty was given with a confidence of 95 %.

Test Items(Anechoic Chamber)	Uncertainty	Remark
Radiated emission (30 MHz ~ 300 MHz, 3 m, Vertical)	± 4.38 dB	Confidence levels of 95 % ($k = 2$)
Radiated emission (30 MHz ~ 300 MHz, 3 m, Horizontal)	± 3.50 dB	Confidence levels of 95 % ($k = 2$)
Radiated emission (300 MHz ~ 1 000 MHz, 3 m, Vertical)	± 3.75 dB	Confidence levels of 95 % ($k = 2$)
Radiated emission (300 MHz ~ 1 000 MHz, 3 m, Horizontal)	± 3.59 dB	Confidence levels of 95 % ($k = 2$)



6.4 Limit

Frequency (MHz)	FCC Limit @ 3 m. dB μ V/m	CISPR Limit @ 10 m. dB μ V/m
30 ~ 88	40.0	30.0
88 ~ 216	43.5	30.0
216 ~ 230	46.0	30.0
230 ~ 960	46.0	37.0
960 ~ 1 000	54.0	37.0
> 1 000	54.0	No Specified limit

6.5 Test Equipment used


Model Name	Manufacturer	Description	Serial Number	Due to Calibration
■ - ESIB26	Rohde & Schwarz	EMI Test Receiver	830482/010	12. 11. 2011
■ - VULB9160	Schwarzbeck	Broadband Test Antenna	3193	03. 15. 2012
■ - BBHA9120D	Schwarzbeck	Horn ANT	207	12. 22. 2011
■ - MCU066	maturo GmbH	Position Controller	1390306	N/A
■ - TT2.5SI	maturo GmbH	Turntable	1390307	N/A
■ - AM 4.0	maturo GmbH	Antenna Mast	1390308	N/A
■ - AFS 44 00101800-25-10P-44	MITEQ	Preamplifier	1258943	11. 12. 2011

6.6 Test data for Radiated Emission

- Test Date : September 9 ~ 15, 2011
- Resolution Bandwidth : 120 kHz/1 MHz
- Frequency Range : 30 MHz ~ 5 000 MHz
- Measurement Distance : 3 m
- Note : The highest frequency of the internal source of the EUT is between 500 MHz and 1 000 MHz (677 MHz). The measurement was made up to 5 000 MHz



- ◆ Operating Condition: 1 920 × 1 080 / 60 Hz (RGB: Analog)
Red trace: Vertical polarization, Blue trace: Horizontal polarization




Final Result 1

Frequency (MHz)	QuasiPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
36.871250	22.0	1000.0	120.000	114.0	V	222.0	12.5	18.0	40.0
56.311250	18.1	1000.0	120.000	100.0	V	146.0	12.9	21.9	40.0
82.501250	35.2	1000.0	120.000	150.0	V	216.0	9.0	4.8	40.0
112.693750	35.4	1000.0	120.000	100.0	V	359.0	11.7	8.1	43.5
165.032500	38.5	1000.0	120.000	150.0	H	228.0	13.9	5.0	43.5
181.562500	34.2	1000.0	120.000	121.0	H	249.0	12.9	9.3	43.5
247.563750	41.9	1000.0	120.000	100.0	H	224.0	13.2	4.1	46.0
396.095000	41.5	1000.0	120.000	100.0	H	242.0	17.6	4.5	46.0
663.167500	34.4	1000.0	120.000	100.0	H	207.0	24.1	11.6	46.0
796.705000	31.4	1000.0	120.000	100.0	V	318.0	26.5	14.6	46.0

< Fig 12. Radiated emission result (30 MHz ~ 1 000 MHz) >



- ◆ Operating Condition: 1 920 × 1 080 / 60 Hz (HDMI/DVI: Digital)
Red trace: Vertical polarization, Blue trace: Horizontal polarization




Final Result 1

Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)
36.426250	21.9	1000.0	120.000	100.0	V	180.0	12.5	18.1	40.0
60.191250	17.3	1000.0	120.000	100.0	V	164.0	12.8	22.7	40.0
82.501250	36.0	1000.0	120.000	146.0	V	224.0	9.0	4.0	40.0
111.277500	35.9	1000.0	120.000	100.0	V	342.0	11.6	7.6	43.5
165.032500	36.5	1000.0	120.000	150.0	H	276.0	13.9	7.0	43.5
181.562500	33.8	1000.0	120.000	100.0	V	17.0	12.9	9.7	43.5
247.563750	42.1	1000.0	120.000	100.0	V	36.0	13.2	3.9	46.0
396.095000	42.1	1000.0	120.000	100.0	H	239.0	17.6	3.9	46.0
601.290000	35.7	1000.0	120.000	100.0	H	197.0	23.1	10.3	46.0
890.997500	38.2	1000.0	120.000	100.0	H	112.0	27.6	7.8	46.0

< Fig 13. Radiated emission result (30 MHz ~ 1 000 MHz) >



- ◆ Operating Condition: 1 920 × 1 080 / 60 Hz (RGB: Analog)
Green marker: Average detector, Blue marker: Peak detector
Radiated emission_above 1GHz-6GHz



Final Result 1

Frequency (MHz)	MaxPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
1055.496192	52.0	1000.0	1000.000	100.0	V	2.0	-14.4	22.0	74.0
1188.168738	51.7	1000.0	1000.000	150.0	H	124.0	-14.1	22.3	74.0
1497.945892	52.6	1000.0	1000.000	100.0	V	12.0	-13.2	21.4	74.0
1701.994790	56.2	1000.0	1000.000	165.0	V	-12.0	-12.5	17.8	74.0
2184.140681	38.6	1000.0	1000.000	129.0	V	336.0	-10.5	35.4	74.0
2792.975150	42.2	1000.0	1000.000	126.0	V	332.0	-7.6	31.8	74.0
3089.984369	51.2	1000.0	1000.000	100.0	V	0.0	-6.4	22.8	74.0
5000.000000	48.2	1000.0	1000.000	100.0	V	97.0	-0.8	25.8	74.0

Final Result 2

Frequency (MHz)	CAverage (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
1055.496192	28.1	1000.0	1000.000	100.0	V	2.0	-14.4	25.9	54.0
1188.168738	29.7	1000.0	1000.000	150.0	H	124.0	-14.1	24.3	54.0
1497.945892	28.7	1000.0	1000.000	100.0	V	12.0	-13.2	25.3	54.0
1701.994790	30.9	1000.0	1000.000	165.0	V	-12.0	-12.5	23.1	54.0
2184.140681	27.2	1000.0	1000.000	129.0	V	336.0	-10.5	26.8	54.0
2792.975150	28.4	1000.0	1000.000	126.0	V	332.0	-7.6	25.6	54.0
3089.984369	32.6	1000.0	1000.000	100.0	V	0.0	-6.4	21.4	54.0
5000.000000	40.3	1000.0	1000.000	100.0	V	97.0	-0.8	13.7	54.0


< Fig 14. Radiated emission result (1 000 MHz ~ 5 000 MHz) >



◆ Operating Condition: 1 920 × 1 080 / 60 Hz (HDMI/DVI: Digital)

Green marker: Average detector, Blue marker: Peak detector

Radiated emission_above 1GHz-6GHz



Final Result 1

Frequency (MHz)	MaxPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
1054.696192	51.7	1000.0	1000.000	100.0	V	-1.0	-14.4	22.3	74.0
1187.768738	51.0	1000.0	1000.000	150.0	H	183.0	-14.1	23.0	74.0
1592.986373	53.4	1000.0	1000.000	100.0	V	175.0	-12.7	20.6	74.0
1702.410822	55.0	1000.0	1000.000	150.0	V	-5.0	-12.5	19.0	74.0
2174.156713	41.7	1000.0	1000.000	100.0	V	340.0	-10.6	32.3	74.0
2585.326253	43.9	1000.0	1000.000	100.0	V	32.0	-8.5	30.1	74.0
2808.207214	43.1	1000.0	1000.000	126.0	V	340.0	-7.5	30.9	74.0
3091.184369	49.7	1000.0	1000.000	100.0	V	-1.0	-6.4	24.3	74.0

Final Result 2

Frequency (MHz)	CAverage (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
1054.696192	27.7	1000.0	1000.000	100.0	V	-1.0	-14.4	26.3	54.0
1187.768738	30.5	1000.0	1000.000	150.0	H	183.0	-14.1	23.5	54.0
1592.986373	38.4	1000.0	1000.000	100.0	V	175.0	-12.7	15.6	54.0
1702.410822	30.5	1000.0	1000.000	150.0	V	-5.0	-12.5	23.5	54.0
2174.156713	26.6	1000.0	1000.000	100.0	V	340.0	-10.6	27.4	54.0
2585.326253	30.1	1000.0	1000.000	100.0	V	32.0	-8.5	23.9	54.0
2808.207214	28.9	1000.0	1000.000	126.0	V	340.0	-7.5	25.1	54.0
3091.184369	32.7	1000.0	1000.000	100.0	V	-1.0	-6.4	21.3	54.0

< Fig 15. Radiated emission result (1 000 MHz ~ 5 000 MHz) >



7. Sample Calculations

$$\begin{aligned} \text{dB}\mu\text{V} &= 20 \text{ Log}_{10}(\mu\text{V}/\text{m}) \\ \text{dB}\mu\text{V} &= \text{dBm} + 107 \\ \mu\text{V} &= 10^{(\text{dB}\mu\text{V}/20)} \end{aligned}$$

7.1 Example 1 :

■ 20.3 MHz

Class B Limit	= 250 μV = 48 dB μV
Reading	= 39.2 dB μV
$10^{(39.2\text{dB}\mu\text{V}/20)}$	= 91.2 μV
Margin	= 48 dB μV - 39.2 dB μV = 8.8 dB

7.2 Example 2 :

■ 66.7 MHz

Class B Limit	= 100 $\mu\text{V}/\text{m}$ = 40.0 dB $\mu\text{V}/\text{m}$
Reading	= 31.0 dB μV
Antenna Factor + Cable Loss = 5.8 dB	
Total	= 36.8 dB $\mu\text{V}/\text{m}$
Margin	= 40.0 dB $\mu\text{V}/\text{m}$ - 36.8 dB $\mu\text{V}/\text{m}$ = 3.2 dB



8. Recommendation & Conclusion

The data collected shows that the **LG Electronics Inc. LED LCD TV/Monitor (Model Name: 42LW5300-UC)** was complies with §15.107 and 15.109 of the FCC Rules.