



FCC EVALUATION REPORT FOR CERTIFICATION

Applicant : LG Electronics Inc.

19-1, Cheongho-ri, Jinwi-myeon,

Pyeongteak-si, Gyeonggi-do, Korea.

Attn: Mr. Sang-Wook Lee, Chief research engineer

Date of Issue : April 6, 2010

Order Number: GETEC-C1-10-078

Test Report Number: GETEC-E3-10-036

Test Site: Gumi College EMC Center

FCC Registration Number: (100749, 443957)

FCC ID.: BEJ47LE5300UC

Applicant: LG Electronics Inc.

Rule Part(s)	: FCC Part 15 Subpart B
Equipment Class	: Class B computing device peripheral (JBP)
EUT Type	: LED LCD TV/Monitor
Type of Authority	: Certification
Model Name	: 47LE5300-UC
Trade Name	: LG

This equipment has been shown to be in compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003 / Canadian standard ICES-003

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Tested by,

Reviewed by,

Soon-Hoon Jeong, Engineer
GUMI College EMC center

Jae-Hoon Jeong, Senior Engineer
GUMI College EMC center



CONTENTS

1. GENERAL INFORMATION	3
2. INTRODUCTION	4
3. PRODUCT INFORMATION	5
3.1 DESCRIPTION OF EUT.....	5
3.2 SUPPORT EQUIPMENT / CABLES USED	6
3.3 MODIFICATION ITEM(S).....	7
4. DESCRIPTION OF TESTS.....	8
4.1 TEST CONDITION.....	8
4.2 CONDUCTED EMISSION	9
4.3 RADIATED EMISSION.....	10
5. CONDUCTED EMISSION.....	11
5.1 OPERATING ENVIRONMENT	11
5.2 TEST SET-UP	11
5.3 MEASUREMENT UNCERTAINTY.....	11
5.4 LIMIT	12
5.5 TEST EQUIPMENT USED.....	12
5.6 TEST DATA FOR CONDUCTED EMISSION	12
6. RADIATED EMISSION	23
6.1 OPERATING ENVIRONMENT	23
6.2 TEST SET-UP	23
6.3 MEASUREMENT UNCERTAINTY.....	23
6.4 LIMIT	24
6.5 TEST EQUIPMENT USED.....	24
6.6 TEST DATA FOR RADIATED EMISSION.....	24
7. SAMPLE CALCULATIONS.....	31
7.1 EXAMPLE 1 :	31
7.2 EXAMPLE 2 :	31
8. RECOMMENDATION & CONCLUSION.....	32
APPENDIX A – ATTESTATION STATEMENT	
APPENDIX B – ID SAMPLE LABEL & LOCATION	
APPENDIX C – BLOCK DIAGRAM	
APPENDIX D – TEST SET-UP PHOTOGRAPHS	
APPENDIX E – EXTERNAL PHOTOGRAPHS	
APPENDIX F – INTERNAL PHOTOGRAPHS	
APPENDIX G – USER’S MANUAL	



Scope: Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and / or unintentional radiators for compliance with technical rules and regulations of the Federal Communications Commission.

1. General Information

Applicant: LG Electronics Inc.

Applicant Address: 19-1, Cheongho-ri, Jinwi-myeon, Pyeongteak-si, Gyeonggi-do, Korea.

Manufacturer: LG Electronics Inc.

Manufacturer Address: 19-1, Cheongho-ri, Jinwi-myeon, Pyeongteak-si, Gyeonggi-do, Korea.

Contact Person: Mr. Sang-Wook Lee, Chief research engineer

Tel Number: +82-31-610-9623

- **FCC ID.** BEJ47LE5300UC
- **EUT Type** LED LCD TV/Monitor
- **Model Name** 47LE5300-UC
- **Trade Name** LG
- **Serial Number** Prototype
- **Rule Part(s)** FCC Part 15 Subpart B
- **Type of Authority** Certification
- **Test Procedure(s)** ANSI C63.4 (2003) / Canadian standard ICES-003
- **Dates of Test** March 30, 2010
- **Place of Test** **Gumi College EMC Center** (FCC Registration Number: 100749, 443957)
407, Bugok-dong, Gumi-si, Gyeongbuk, Korea.
- **Test Report Number** GETEC-E3-10-036
- **Dates of Issue** April 6, 2010




2. Introduction

The measurement procedure described in American National Standard for Methods of Measurement of Radio-Nose Emissions From Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz (ASNI C63.4-2003) was used in determining radiated and conducted emissions emanating from **LG Electronics Inc. LED LCD TV/Monitor (Model Name: 47LE5300-UC)**

These measurement tests were conducted at **Gumi College EMC Center**.

The site address is 407, Bugok-dong, Gumi-si, Gyeongbuk, Korea.

This test site is one of the highest point of Gumi 1 college at about 200 km away from Seoul city and 40 km away from Daegu city. It is located in the valley surrounded by mountains in all directions where ambient radio signal conditions are quiet and a favorable area to measure the radio frequency interference on open field test site for the computing and ISM devices manufactures. The detailed description of the measurement facility was found to be in compliance with the requirements of §2.948 according to ANSI C63.4 (2003)



GUMI COLLEGE EMC CENTER
407, Bugok-dong, Gumi-si,
Gyeongbuk 730-711, Korea.
Tel: +82-54-440-1195
Fax: +82-54-440-1199

Fig 1. The map above shows the Gumi College in vicinity area.



3. Product Information

3.1 Description of EUT

The Equipment under Test (EUT) is the **LG Electronics Inc. LED LCD TV/Monitor (Model Name: 47LE5300-UC) FCC ID.: BEJ47LE5300UC**

MODELS		42LE5300 (42LE5300-UC)	47LE5300 (47LE5300-UC)
Dimensions (Width x Height x Depth)	With stand	1016.0 mm x 692.0 mm x 270.0 mm (40.0 inch x 27.2 inch x 10.6 inch)	1126.6 mm x 757.9 mm x 284.4 mm (44.3 inch x 29.8 inch x 11.1 inch)
	Without stand	1016.0 mm x 630.0 mm x 29.3 mm (40.0 inch x 24.8 inch x 1.1 inch)	1126.6 mm x 692.0 mm x 29.3 mm (44.3 inch x 27.2 inch x 1.1 inch)
Weight	With stand	19.5 kg (42.9 lbs)	22.6 kg (49.8 lbs)
	Without stand	16.7 kg (36.8 lbs)	19.6 kg (43.2 lbs)
Power Requirement		AC 120 V ~ 50 / 60 Hz	
Television System		NTSC-M, ATSC, 64 & 256 QAM	
Program Coverage		VHF 2-13, UHF 14-69, CATV 1-135, DTV 2-69, CADTV 1-135	
External Antenna Impedance		75 Ω	
Environment condition	Operating Temperature	0 °C to 40 °C (32 °F to 104 °F)	
	Operating Humidity	Less than 80 %	
	Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)	
	Storage Humidity	Less than 85 %	

-. Maximum Frequency range : 666 MHz



3.2 Support Equipment / Cables used

3.2.1 Used Support Equipment

Description	Manufacturer	Model Name	S/N & FCC ID.
PC	Hewlett Packard	D530	S/N: CNG34800PY FCC ID.: DoC
Video card	ATI	ATI RV360(9600)	S/N: SN0402017176 FCC ID.: DoC
Key board	COMPAQ	16516-AD6	S/N: B13BBOR391006D FCC ID.: AQ6-23K15
PS2 mouse	LOGITECH	M-S69	S/N: 334684-108 FCC ID.: JNZ211443
Joy stick	MICROSOFT	X05-92626	S/N: 9262600296169 FCC ID.: DoC
DVD player	LG Electronics Inc.	LC-954	S/N: 3850R-Z674K FCC ID.: DoC
Headset	GOWOONSORI	GW-500M	S/N: N/A FCC ID.: DoC
Printer	Hewlett Packard	970CXI	S/N: MY9B01F1FG FCC ID.: DoC
TV signal generator	FLUKE	54200	S/N: 831011 FCC ID.: DoC
USB memory stick	SM Electronics	UDD-32M	S/N: N/A FCC ID.: DoC

See “Appendix D – Test Setup Photographs” for actual system test set-up

3.2.2 System configuration

Description	Manufacturer	Model Name	S/N & FCC ID.
None	-	-	-



3.2.3 Used Cable(s)

Cable Name	Condition	Description
Power cable	Connected to the EUT	1.80 m unshielded
RGB(Analog) cable	Connected to the EUT and PC	1.80 m shielded with two ferrite cores
HDMI/DVI(Digital) cable	Connected to the EUT and PC	2.00 m shielded
Audio(RGB/DVI) in cable	Connected to the EUT and PC	1.80 m shielded
RS-232C in (Control & Service) cable	Connected to the EUT and PC	1.80 m shielded
Component cable	Connected to the EUT and DVD player	2.00 m shielded
Component sound cable	Connected to the EUT and DVD player	3.00 m shielded
AV in cable	Connected to the EUT and DVD player	3.00 m shielded
Antenna cable	Connected to the EUT and TV signal generator	10.00 m shielded
Headphone cable	Connected to the EUT and Headset	2.75 m shielded
Component in 2 cable	Connected to the EUT and DVD player	2.10 m shielded
AV in 2 cable	Connected to the EUT and DVD player	3.10 m shielded

3.3 Modification Item(s)

- None



4. Description of tests

4.1 Test Condition

The EUT was installed, arranged and operated in a manner that is most representative of equipment as typically used. The measurements were carried out while varying operating modes and cable positions within typically arrangement to determine maximum emission level.

The representative and worst test mode(s) were noted in the test report.

- Test Voltage / Frequency : AC 120 V / 60 Hz

- Test Mode(s)

- . **Monitor mode**

Radiated emission: 1 920 × 1 080 / 60 Hz (RGB: Analog, HDMI/DVI: Digital)

Conducted emission: 1 920 × 1 080 / 60 Hz (RGB: Analog, HDMI/DVI: Digital)

1 024 × 768 / 60 Hz (RGB: Analog), 640 × 480 / 60 Hz (RGB: Analog)

◆ Operating test pattern

- . “H” character scrolling mode (Font size: 10)
- . Black background white character
- . Brightness and contrast was adjusted as maximum level
- . 1 kHz sound tone with winamp player

- . **USB memory stick play mode**

◆ Operating test pattern

- . Continuous playback mode with video files

“The verification report for TV/AV mode would be issued by LG Electronics Inc.”



4.2 Conducted Emission

The Line conducted emission test facility is inside a 4 m × 8 m × 2.5 m shielded enclosure. (FCC Registration No.: 100749)

The EUT was placed on a non-conducting 1.0 m by 1.5 m table, which is 0.8 m in height and 0.4 m away from the vertical wall of the shielded enclosure.

The EUT is powered from the Rohde & Schwarz LISN (ESH2-Z5) and the support equipment is powered from the Rohde & Schwarz LISN (ESH3-Z5). Powers to the LISN are filtered by high-current high insertion loss power line filter.

Sufficient time for EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition.

The RF output of the LISN was connected to the EMI test receiver (Rohde & Schwarz, ESCS30).

The EMI test receiver was scanned from 150 kHz to 30 MHz with 20 ms sweep time to determine the frequency producing the maximum EME from the EUT. The frequency producing the maximum level was re-examined using Quasi-Peak mode of the EMI test receiver.

The bandwidth of Quasi-peak mode was set to 9 kHz. Each emission was maximized consistent with typical applications by varying the configuration of the test sample. Interface cables were connected to the available interface ports of the test unit. The effect of varying the position of cables was investigated to find the configuration that produces maximum diagram emission. Excess cable lengths were bundled at center with 30 cm ~ 40 cm.

Each EME reported was calibrated using the R/S signal generator




Fig 2. Impedance of LISN



4.3 Radiated Emission

Preliminary measurements were conducted 3 m semi anechoic chamber using broadband antennas to determine the frequency producing the maximum EME. Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The technology configuration, mode of operation and turntable azimuth with respect to antenna was note for each frequency found.

Final measurements were made 3 m chamber (FCC registration No.: 443957) and/or 10 m OATS (FCC registration No.: 100749).

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition.

Each frequency found during pre-scan measurements was re-examined and investigated using EMI test receiver. The detector function was set to CISPR quasi-peak mode average mode and the bandwidth of the receiver was set to 120 kHz or 1 MHz depending on the frequency or type of signal.

The EUT, support equipment and interconnecting cables were reconfigured to the setup producing the maximum emission for the frequency and were placed on top of a 0.8 m high non-metallic 1.0 m × 1.5 m table.

The turntable containing the test sample was rotated; the antenna height was varied 1 to 4 meter and stopped at the azimuth or height producing the maximum emission.

Each EME reported was calibrated using the R/S signal generator




Fig 3. Dimensions of test site.



5. Conducted Emission

5.1 Operating Environment

Temperature : 27 °C
Relative Humidity : 41 % R.H.

5.2 Test Set-up

The conducted emission measurements were performed in the shielded room.

The EUT was placed on wooden table, 0.8 m heights above the floor, 0.4 m from the reference ground plane (GRP) wall and 0.8 m from AMN.

AMN is bonded on horizontal reference ground plane.

The ground plane, which was electrically bonded to the shield room, ground system and all power lines entering the shield room, were filtered.

5.3 Measurement Uncertainty

The measurement uncertainty was calculated in accordance with ISO "Guide to the expression of uncertainty in measurement."

The measurement uncertainty was given with a confidence of 95 %.

Test Items	Uncertainty	Remark
Conducted emission (9 kHz ~ 150 kHz)	± 2.69 dB	Confidence levels of 95 % ($k = 2$)
Conducted emission (150 kHz ~ 30 MHz)	± 4.16 dB	Confidence levels of 95 % ($k = 2$)



5.4 Limit

RFI Conducted	FCC Limit(dB μ V/m) Class B	
Freq. Range	Quasi-Peak	Average
150 kHz ~ 0.5 MHz	66 ~ 56*	56 ~ 46*
0.5 MHz ~ 5 MHz	56	46
5 MHz ~ 30 MHz	60	50
*Limits decreases linearly with the logarithm of frequency.		

5.5 Test Equipment used

Model Name	Manufacturer	Description	Serial Number	Due to Calibration
■ - ESCS30	Rohde & Schwarz	EMI Test Receiver	839809/003	12. 10. 2010
■ - ESH3-Z5	Rohde & Schwarz	LISN	838979/020	12. 10. 2010
■ - ESH2-Z5	Rohde & Schwarz	LISN	829991/009	12. 10. 2010
□ - ISN T8	TESEQ. GmbH	Impedance Network	24568	10. 16. 2010


5.6 Test data for Conducted Emission

-. Test Date : March 30, 2010
-. Resolution Bandwidth : 9 kHz
-. Frequency Range : 0.15 MHz ~ 30 MHz



◆ Operating condition: 1 920 × 1 080 / 60 Hz (RGB: Analog)

Voltage with 4-Line-LISN_L1



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.150000	49.5	1000.000	9.000	GND	L1	10.0	16.5	66.0	
0.315000	49.8	1000.000	9.000	GND	L1	10.0	9.8	59.6	
0.345000	48.1	1000.000	9.000	GND	L1	10.0	10.8	58.9	
0.570000	40.3	1000.000	9.000	GND	L1	10.0	15.7	56.0	
0.675000	40.4	1000.000	9.000	GND	L1	10.0	15.6	56.0	
0.945000	39.8	1000.000	9.000	GND	L1	10.0	16.2	56.0	
1.365000	40.4	1000.000	9.000	GND	L1	10.1	15.6	56.0	
2.235000	39.5	1000.000	9.000	GND	L1	10.1	16.5	56.0	
2.400000	38.5	1000.000	9.000	GND	L1	10.1	17.5	56.0	
4.080000	40.7	1000.000	9.000	GND	L1	10.2	15.3	56.0	


Final Measurement Detector 2

Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.210000	39.8	1000.000	9.000	GND	L1	10.0	13.2	53.0	
0.315000	45.6	1000.000	9.000	GND	L1	10.0	4.0	49.6	
0.345000	37.8	1000.000	9.000	GND	L1	10.0	11.1	48.9	
0.525000	38.6	1000.000	9.000	GND	L1	10.0	7.4	46.0	
0.735000	35.9	1000.000	9.000	GND	L1	10.0	10.1	46.0	
1.155000	32.5	1000.000	9.000	GND	L1	10.1	13.5	46.0	
1.170000	33.0	1000.000	9.000	GND	L1	10.1	13.0	46.0	
2.235000	30.8	1000.000	9.000	GND	L1	10.1	15.2	46.0	
2.415000	30.4	1000.000	9.000	GND	L1	10.1	15.6	46.0	
3.945000	32.9	1000.000	9.000	GND	L1	10.2	13.1	46.0	

< Fig 4. Conducted emission result (Live line)>



Voltage with 4-Line-LISN_N



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.150000	47.8	1000.000	9.000	GND	N	10.0	18.2	66.0	
0.315000	48.4	1000.000	9.000	GND	N	10.0	11.2	59.6	
0.405000	45.2	1000.000	9.000	GND	N	10.0	12.4	57.6	
0.645000	40.7	1000.000	9.000	GND	N	10.0	15.3	56.0	
1.155000	39.6	1000.000	9.000	GND	N	10.1	16.4	56.0	
1.380000	40.4	1000.000	9.000	GND	N	10.1	15.6	56.0	
2.220000	40.0	1000.000	9.000	GND	N	10.1	16.0	56.0	
3.735000	40.0	1000.000	9.000	GND	N	10.2	16.0	56.0	
3.960000	42.8	1000.000	9.000	GND	N	10.2	13.2	56.0	
6.150000	34.0	1000.000	9.000	GND	N	10.2	26.0	60.0	

Final Measurement Detector 2


Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.150000	34.3	1000.000	9.000	GND	N	10.0	21.7	56.0	
0.210000	38.7	1000.000	9.000	GND	N	10.0	14.3	53.0	
0.315000	44.1	1000.000	9.000	GND	N	10.0	5.5	49.6	
0.360000	32.9	1000.000	9.000	GND	N	10.0	15.6	48.5	
0.525000	36.5	1000.000	9.000	GND	N	10.0	9.5	46.0	
0.960000	34.8	1000.000	9.000	GND	N	10.0	11.2	46.0	
1.170000	32.7	1000.000	9.000	GND	N	10.1	13.3	46.0	
2.460000	31.9	1000.000	9.000	GND	N	10.1	14.1	46.0	
3.900000	31.1	1000.000	9.000	GND	N	10.2	14.9	46.0	
3.960000	33.7	1000.000	9.000	GND	N	10.2	12.3	46.0	

< Fig 5. Conducted emission result (Neutral line)>



◆ Operating condition: 1 024 × 768 / 60 Hz (RGB: Analog)

Voltage with 4-Line-LISN_L1



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.150000	50.5	1000.000	9.000	GND	L1	10.0	15.5	66.0	
0.315000	49.8	1000.000	9.000	GND	L1	10.0	9.8	59.6	
0.345000	47.9	1000.000	9.000	GND	L1	10.0	11.0	58.9	
0.465000	44.6	1000.000	9.000	GND	L1	10.0	12.0	56.6	
0.660000	41.7	1000.000	9.000	GND	L1	10.0	14.4	56.0	
0.960000	40.4	1000.000	9.000	GND	L1	10.0	15.6	56.0	
1.395000	41.3	1000.000	9.000	GND	L1	10.1	14.7	56.0	
2.220000	39.6	1000.000	9.000	GND	L1	10.1	16.4	56.0	
2.445000	39.1	1000.000	9.000	GND	L1	10.1	16.9	56.0	
3.540000	40.4	1000.000	9.000	GND	L1	10.2	15.6	56.0	


Final Measurement Detector 2

Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.225000	38.8	1000.000	9.000	GND	L1	10.0	13.6	52.4	
0.315000	44.4	1000.000	9.000	GND	L1	10.0	5.2	49.6	
0.345000	37.6	1000.000	9.000	GND	L1	10.0	11.3	48.9	
0.525000	35.6	1000.000	9.000	GND	L1	10.0	10.4	46.0	
0.750000	36.2	1000.000	9.000	GND	L1	10.0	9.8	46.0	
0.960000	34.9	1000.000	9.000	GND	L1	10.0	11.1	46.0	
1.605000	32.8	1000.000	9.000	GND	L1	10.1	13.2	46.0	
2.220000	31.3	1000.000	9.000	GND	L1	10.1	14.7	46.0	
2.250000	32.9	1000.000	9.000	GND	L1	10.1	13.1	46.0	
3.960000	32.3	1000.000	9.000	GND	L1	10.2	13.7	46.0	

< Fig 6. Conducted emission result (Live line)>



Voltage with 4-Line-LISN_N



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.150000	50.5	1000.000	9.000	GND	N	10.0	15.5	66.0	
0.315000	48.2	1000.000	9.000	GND	N	10.0	11.4	59.6	
0.360000	46.0	1000.000	9.000	GND	N	10.0	12.6	58.6	
0.750000	41.6	1000.000	9.000	GND	N	10.0	14.4	56.0	
0.810000	39.8	1000.000	9.000	GND	N	10.0	16.2	56.0	
1.590000	39.3	1000.000	9.000	GND	N	10.1	16.7	56.0	
2.220000	39.6	1000.000	9.000	GND	N	10.1	16.4	56.0	
3.900000	41.6	1000.000	9.000	GND	N	10.2	14.4	56.0	
4.005000	39.6	1000.000	9.000	GND	N	10.2	16.4	56.0	
6.135000	33.4	1000.000	9.000	GND	N	10.2	26.6	60.0	

Final Measurement Detector 2


Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.150000	37.8	1000.000	9.000	GND	N	10.0	18.2	56.0	
0.210000	37.0	1000.000	9.000	GND	N	10.0	16.0	53.0	
0.315000	43.1	1000.000	9.000	GND	N	10.0	6.5	49.6	
0.435000	31.2	1000.000	9.000	GND	N	10.0	15.9	47.1	
0.525000	35.2	1000.000	9.000	GND	N	10.0	10.8	46.0	
0.960000	34.4	1000.000	9.000	GND	N	10.0	11.6	46.0	
1.395000	33.1	1000.000	9.000	GND	N	10.1	12.9	46.0	
2.250000	33.0	1000.000	9.000	GND	N	10.1	13.0	46.0	
3.480000	32.8	1000.000	9.000	GND	N	10.1	13.2	46.0	
3.960000	31.8	1000.000	9.000	GND	N	10.2	14.2	46.0	

< Fig 7. Conducted emission result (Neutral line)>



◆ Operating condition: 640 × 480 / 60 Hz (RGB: Analog)

Voltage with 4-Line-LISN_L1



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.150000	50.5	1000.000	9.000	GND	L1	10.0	15.6	66.0	
0.315000	49.8	1000.000	9.000	GND	L1	10.0	9.8	59.6	
0.345000	48.0	1000.000	9.000	GND	L1	10.0	10.9	58.9	
0.540000	43.6	1000.000	9.000	GND	L1	10.0	12.4	56.0	
0.690000	40.9	1000.000	9.000	GND	L1	10.0	15.1	56.0	
1.155000	38.5	1000.000	9.000	GND	L1	10.1	17.5	56.0	
1.605000	40.2	1000.000	9.000	GND	L1	10.1	15.8	56.0	
2.205000	37.3	1000.000	9.000	GND	L1	10.1	18.7	56.0	
2.550000	36.8	1000.000	9.000	GND	L1	10.1	19.2	56.0	
3.930000	39.9	1000.000	9.000	GND	L1	10.2	16.1	56.0	


Final Measurement Detector 2

Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.225000	38.7	1000.000	9.000	GND	L1	10.0	13.7	52.4	
0.315000	44.3	1000.000	9.000	GND	L1	10.0	5.3	49.6	
0.330000	38.9	1000.000	9.000	GND	L1	10.0	10.3	49.2	
0.525000	35.2	1000.000	9.000	GND	L1	10.0	10.8	46.0	
0.750000	35.8	1000.000	9.000	GND	L1	10.0	10.2	46.0	
0.960000	34.2	1000.000	9.000	GND	L1	10.0	11.8	46.0	
1.395000	33.7	1000.000	9.000	GND	L1	10.1	12.3	46.0	
1.815000	31.0	1000.000	9.000	GND	L1	10.1	15.0	46.0	
2.250000	32.0	1000.000	9.000	GND	L1	10.1	14.0	46.0	
3.540000	31.9	1000.000	9.000	GND	L1	10.2	14.1	46.0	

< Fig 8. Conducted emission result (Live line)>



Voltage with 4-Line-LISN_N



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.150000	50.4	1000.000	9.000	GND	N	10.0	15.6	66.0	
0.315000	47.9	1000.000	9.000	GND	N	10.0	11.7	59.6	
0.390000	45.4	1000.000	9.000	GND	N	10.0	12.5	57.9	
0.750000	41.3	1000.000	9.000	GND	N	10.0	14.7	56.0	
0.795000	39.1	1000.000	9.000	GND	N	10.0	16.9	56.0	
1.395000	41.3	1000.000	9.000	GND	N	10.1	14.7	56.0	
2.040000	39.0	1000.000	9.000	GND	N	10.1	17.0	56.0	
3.915000	39.9	1000.000	9.000	GND	N	10.2	16.1	56.0	
3.975000	40.4	1000.000	9.000	GND	N	10.2	15.6	56.0	
6.600000	32.2	1000.000	9.000	GND	N	10.3	27.8	60.0	

Final Measurement Detector 2


Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.150000	37.5	1000.000	9.000	GND	N	10.0	18.5	56.0	
0.210000	36.8	1000.000	9.000	GND	N	10.0	16.2	53.0	
0.315000	42.9	1000.000	9.000	GND	N	10.0	6.7	49.6	
0.465000	30.0	1000.000	9.000	GND	N	10.0	16.5	46.5	
0.750000	35.9	1000.000	9.000	GND	N	10.0	10.1	46.0	
0.960000	34.3	1000.000	9.000	GND	N	10.0	11.7	46.0	
1.395000	33.3	1000.000	9.000	GND	N	10.1	12.7	46.0	
2.250000	32.1	1000.000	9.000	GND	N	10.1	13.9	46.0	
3.750000	32.3	1000.000	9.000	GND	N	10.2	13.7	46.0	
3.960000	32.3	1000.000	9.000	GND	N	10.2	13.7	46.0	

< Fig 9. Conducted emission result (Neutral line)>



◆ Operating condition: 1 920 × 1 080 / 60 Hz (HDMI/DVI: Digital)

Voltage with 4-Line-LISN_L1



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.150000	50.2	1000.000	9.000	GND	L1	10.0	15.8	66.0	
0.315000	49.8	1000.000	9.000	GND	L1	10.0	9.8	59.6	
0.390000	46.0	1000.000	9.000	GND	L1	10.0	11.9	57.9	
0.465000	44.8	1000.000	9.000	GND	L1	10.0	11.8	56.6	
0.675000	39.6	1000.000	9.000	GND	L1	10.0	16.4	56.0	
0.945000	39.6	1000.000	9.000	GND	L1	10.0	16.4	56.0	
1.590000	39.8	1000.000	9.000	GND	L1	10.1	16.2	56.0	
2.220000	39.7	1000.000	9.000	GND	L1	10.1	16.3	56.0	
2.250000	40.7	1000.000	9.000	GND	L1	10.1	15.3	56.0	
3.930000	41.3	1000.000	9.000	GND	L1	10.2	14.7	56.0	


Final Measurement Detector 2

Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.225000	39.1	1000.000	9.000	GND	L1	10.0	13.3	52.4	
0.315000	44.9	1000.000	9.000	GND	L1	10.0	4.7	49.6	
0.330000	38.7	1000.000	9.000	GND	L1	10.0	10.5	49.2	
0.525000	35.9	1000.000	9.000	GND	L1	10.0	10.1	46.0	
0.750000	35.2	1000.000	9.000	GND	L1	10.0	10.8	46.0	
0.960000	34.3	1000.000	9.000	GND	L1	10.0	11.7	46.0	
1.605000	32.9	1000.000	9.000	GND	L1	10.1	13.1	46.0	
2.220000	30.3	1000.000	9.000	GND	L1	10.1	15.7	46.0	
2.250000	32.7	1000.000	9.000	GND	L1	10.1	13.3	46.0	
3.960000	32.4	1000.000	9.000	GND	L1	10.2	13.6	46.0	

< Fig 10. Conducted emission result (Live line)>



Voltage with 4-Line-LISN_N



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.150000	50.2	1000.000	9.000	GND	N	10.0	15.8	66.0	
0.315000	48.1	1000.000	9.000	GND	N	10.0	11.5	59.6	
0.360000	45.8	1000.000	9.000	GND	N	10.0	12.8	58.6	
0.750000	41.6	1000.000	9.000	GND	N	10.0	14.4	56.0	
0.810000	39.9	1000.000	9.000	GND	N	10.0	16.1	56.0	
1.380000	40.5	1000.000	9.000	GND	N	10.1	15.5	56.0	
2.010000	39.3	1000.000	9.000	GND	N	10.1	16.7	56.0	
3.510000	39.5	1000.000	9.000	GND	N	10.2	16.6	56.0	
3.960000	42.1	1000.000	9.000	GND	N	10.2	13.9	56.0	
6.030000	34.3	1000.000	9.000	GND	N	10.2	25.7	60.0	

Final Measurement Detector 2


Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.150000	38.3	1000.000	9.000	GND	N	10.0	17.7	56.0	
0.210000	37.5	1000.000	9.000	GND	N	10.0	15.5	53.0	
0.315000	43.4	1000.000	9.000	GND	N	10.0	6.2	49.6	
0.435000	31.2	1000.000	9.000	GND	N	10.0	15.9	47.1	
0.525000	35.8	1000.000	9.000	GND	N	10.0	10.2	46.0	
0.960000	34.4	1000.000	9.000	GND	N	10.0	11.6	46.0	
1.605000	32.7	1000.000	9.000	GND	N	10.1	13.3	46.0	
2.250000	32.7	1000.000	9.000	GND	N	10.1	13.3	46.0	
3.750000	32.4	1000.000	9.000	GND	N	10.2	13.6	46.0	
3.960000	32.3	1000.000	9.000	GND	N	10.2	13.7	46.0	

< Fig 11. Conducted emission result (Neutral line)>



◆ Operating condition: USB play mode

Voltage with 4-Line-LISN_L1



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.210000	42.5	1000.000	9.000	GND	L1	10.0	20.5	63.0	
0.315000	50.3	1000.000	9.000	GND	L1	10.0	9.3	59.6	
0.345000	47.9	1000.000	9.000	GND	L1	10.0	11.0	58.9	
0.480000	44.5	1000.000	9.000	GND	L1	10.0	11.8	56.3	
0.675000	41.8	1000.000	9.000	GND	L1	10.0	14.2	56.0	
0.945000	40.4	1000.000	9.000	GND	L1	10.0	15.6	56.0	
1.605000	40.5	1000.000	9.000	GND	L1	10.1	15.5	56.0	
2.220000	39.5	1000.000	9.000	GND	L1	10.1	16.5	56.0	
2.445000	39.0	1000.000	9.000	GND	L1	10.1	17.0	56.0	
3.690000	40.2	1000.000	9.000	GND	L1	10.2	15.8	56.0	


Final Measurement Detector 2

Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.225000	38.7	1000.000	9.000	GND	L1	10.0	13.7	52.4	
0.315000	45.5	1000.000	9.000	GND	L1	10.0	4.1	49.6	
0.330000	38.7	1000.000	9.000	GND	L1	10.0	10.5	49.2	
0.525000	37.1	1000.000	9.000	GND	L1	10.0	8.9	46.0	
0.750000	34.1	1000.000	9.000	GND	L1	10.0	11.9	46.0	
0.960000	34.4	1000.000	9.000	GND	L1	10.0	11.6	46.0	
1.170000	32.3	1000.000	9.000	GND	L1	10.1	13.7	46.0	
1.815000	31.4	1000.000	9.000	GND	L1	10.1	14.6	46.0	
2.415000	30.8	1000.000	9.000	GND	L1	10.1	15.2	46.0	
3.960000	33.4	1000.000	9.000	GND	L1	10.2	12.6	46.0	

< Fig 12. Conducted emission result (Live line)>



Voltage with 4-Line-LISN_N



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.150000	50.2	1000.000	9.000	GND	N	10.0	15.8	66.0	
0.345000	45.8	1000.000	9.000	GND	N	10.0	13.1	58.9	
0.390000	45.3	1000.000	9.000	GND	N	10.0	12.6	57.9	
0.690000	40.3	1000.000	9.000	GND	N	10.0	15.8	56.0	
0.795000	39.4	1000.000	9.000	GND	N	10.0	16.6	56.0	
1.380000	40.4	1000.000	9.000	GND	N	10.1	15.6	56.0	
2.445000	39.4	1000.000	9.000	GND	N	10.1	16.6	56.0	
3.900000	41.6	1000.000	9.000	GND	N	10.2	14.4	56.0	
3.960000	42.6	1000.000	9.000	GND	N	10.2	13.4	56.0	
6.090000	33.7	1000.000	9.000	GND	N	10.2	26.3	60.0	

Final Measurement Detector 2

Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.150000	38.6	1000.000	9.000	GND	N	10.0	17.4	56.0	
0.210000	38.5	1000.000	9.000	GND	N	10.0	14.5	53.0	
0.315000	44.0	1000.000	9.000	GND	N	10.0	5.6	49.6	
0.360000	33.8	1000.000	9.000	GND	N	10.0	14.7	48.5	
0.525000	37.1	1000.000	9.000	GND	N	10.0	8.9	46.0	
0.960000	34.5	1000.000	9.000	GND	N	10.0	11.5	46.0	
1.605000	32.7	1000.000	9.000	GND	N	10.1	13.3	46.0	
2.460000	31.9	1000.000	9.000	GND	N	10.1	14.1	46.0	
3.480000	31.6	1000.000	9.000	GND	N	10.1	14.4	46.0	
3.960000	33.2	1000.000	9.000	GND	N	10.2	12.8	46.0	

< Fig 13. Conducted emission result (Neutral line)>



6. Radiated Emission

6.1 Operating Environment

Temperature : 23 °C
Relative Humidity : 40 % R.H.

6.2 Test Set-up

A preliminary and final measurement was at 3 m anechoic chamber.

The EUT was placed on a non-conductive turntable approximately 0.8 m above the ground plane.

The turntable with EUT was rotated 360°, and the antenna was varied in height between 1.0 m and 4.0 m in order to determine the maximum emission levels.

This procedure was performed for both horizontal and vertical polarization of the receiving antenna.

6.3 Measurement Uncertainty

The measurement uncertainty was calculated in accordance with ISO “Guide to the expression of uncertainty in measurement”.

The measurement uncertainty was given with a confidence of 95 %.

Test Items(Chamber)	Uncertainty	Remark
Radiated emission (30 MHz ~ 300 MHz, 3 m, Vertical)	± 4.32 dB	Confidence levels of 95 % ($k = 2$)
Radiated emission (30 MHz ~ 300 MHz, 3 m, Horizontal)	± 4.21 dB	Confidence levels of 95 % ($k = 2$)
Radiated emission (300 MHz ~ 1 000 MHz, 3 m, Vertical)	± 3.96 dB	Confidence levels of 95 % ($k = 2$)
Radiated emission (300 MHz ~ 1 000 MHz, 3 m, Horizontal)	± 3.97 dB	Confidence levels of 95 % ($k = 2$)



6.4 Limit

Frequency (MHz)	FCC Limit @ 3 m. dB μ V/m	CISPR Limit @ 10 m. dB μ V/m
30 ~ 88	40.0	30.0
88 ~ 216	43.5	30.0
216 ~ 230	46.0	30.0
230 ~ 960	46.0	37.0
960 ~ 1 000	54.0	37.0
> 1 000	54.0	No Specified limit

6.5 Test Equipment used


Model Name	Manufacturer	Description	Serial Number	Due to Calibration
■ - ESIB26	Rohde & Schwarz	EMI Test Receiver	830482/010	12. 11. 2010
■ - VULB9160	Schwarzbeck	Broadband Test Antenna	3193	03. 11. 2012
■ - BBHA9120D	Schwarzbeck	Horn ANT	207	12. 22. 2011
■ - MCU066	maturo GmbH	Position Controller	1390306	N/A
■ - TT2.5SI	maturo GmbH	Turntable	1390307	N/A
■ - AM 4.0	maturo GmbH	Antenna Mast	1390308	N/A
■ - AFS 44 00101800-25-10P-44	MITEQ	Preamplifier	1258943	11. 12. 2010

6.6 Test data for Radiated Emission

- . Test Date : March 30, 2010
- . Resolution Bandwidth : 120 kHz/1 MHz
- . Frequency Range : 30 MHz ~ 5 000 MHz
- . Measurement Distance : 3 m
- . Note : The highest frequency of the internal source of the EUT is between 500 MHz and 1 000 MHz (666 MHz). The measurement was made up to 5 000 MHz.



- ◆ Operating Condition: 1 920 × 1 080 / 60 Hz (RGB: Analog)
Red trace: Vertical polarization, Blue trace: Horizontal polarization




Final Result 1

Frequency (MHz)	QuasiPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
59.378317	34.8	1000.0	120.000	100.0	V	297.0	13.4	5.2	40.0
74.249419	32.3	1000.0	120.000	297.0	H	328.0	10.7	7.7	40.0
147.333267	31.6	1000.0	120.000	100.0	V	288.0	14.8	11.9	43.5
299.740401	37.1	1000.0	120.000	112.0	H	319.0	16.3	8.9	46.0
329.378717	32.7	1000.0	120.000	158.0	V	24.0	17.1	13.3	46.0
449.819760	37.5	1000.0	120.000	100.0	V	15.0	20.8	8.5	46.0
594.027455	37.3	1000.0	120.000	162.0	H	175.0	24.4	8.7	46.0
636.712986	39.1	1000.0	120.000	100.0	H	355.0	25.2	6.9	46.0
720.020160	36.4	1000.0	120.000	153.0	H	228.0	26.7	9.6	46.0
957.694469	33.4	1000.0	120.000	100.0	V	157.0	31.0	12.6	46.0

< Fig 14. Radiated emission result (30 MHz ~ 1 000 MHz)>



- ◆ Operating Condition: 1 920 × 1 080 / 60 Hz (HDMI/DVI: Digital)
Red trace: Vertical polarization, Blue trace: Horizontal polarization




Final Result 1

Frequency (MHz)	QuasiPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
59.618317	33.4	1000.0	120.000	150.0	V	321.0	13.4	6.6	40.0
74.249419	32.5	1000.0	120.000	311.0	H	319.0	10.7	7.5	40.0
122.966613	30.2	1000.0	120.000	100.0	V	0.0	13.4	13.3	43.5
147.573267	37.2	1000.0	120.000	100.0	V	42.0	14.8	6.3	43.5
295.068737	38.7	1000.0	120.000	124.0	H	321.0	16.1	7.3	46.0
329.922605	36.7	1000.0	120.000	145.0	V	2.0	17.1	9.3	46.0
451.083647	36.6	1000.0	120.000	100.0	V	0.0	20.8	9.4	46.0
593.947455	36.1	1000.0	120.000	256.0	H	120.0	24.4	9.9	46.0
642.808537	39.2	1000.0	120.000	100.0	H	327.0	25.3	6.8	46.0
958.158357	32.4	1000.0	120.000	106.0	V	180.0	31.0	13.6	46.0

< Fig 15. Radiated emission result (30 MHz ~ 1 000 MHz)>



- ◆ Operating Condition: USB play mode
Red trace: Vertical polarization, Blue trace: Horizontal polarization




Final Result 1

Frequency (MHz)	QuasiPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)
30.120000	23.5	1000.0	120.000	153.0	V	300.0	12.9	16.5	40.0
59.642204	36.0	1000.0	120.000	103.0	V	173.0	13.4	4.0	40.0
147.437154	31.7	1000.0	120.000	111.0	V	0.0	14.8	11.8	43.5
299.900401	38.9	1000.0	120.000	100.0	H	336.0	16.3	7.1	46.0
449.859760	33.2	1000.0	120.000	106.0	V	0.0	20.8	12.8	46.0
636.592986	41.9	1000.0	120.000	100.0	H	0.0	25.2	4.1	46.0
954.486693	39.9	1000.0	120.000	127.0	H	230.0	31.0	6.1	46.0

< Fig 16. Radiated emission result (30 MHz ~ 1 000 MHz)>



- ◆ Operating Condition: 1 920 × 1 080 / 60 Hz (RGB: Analog)
Green trace: Average detector, Blue trace: Peak detector



Final Result 1

Frequency (MHz)	MaxPeak-MaxHold (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
1593.186373	54.4	256.0	V	337.0	-13.7	19.5	73.9	


Final Result 2

Frequency (MHz)	Average-MaxHold (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
1184.368738	35.4	120.0	V	359.0	-15.1	18.5	53.9	
2659.318637	36.8	145.0	H	26.0	-9.7	17.1	53.9	
3196.392786	33.9	162.0	V	50.0	-7.4	20.0	53.9	
4046.092184	36.1	151.0	V	1.0	-3.1	17.8	53.9	
4719.438878	36.2	234.0	H	272.0	-2.9	17.7	53.9	

< Fig 17. Radiated emission result (1 000 MHz ~ 5 000 MHz)>



- ◆ Operating Condition: 1 920 × 1 080 / 60 Hz (HDMI/DVI: Digital)
Green trace: Average detector, Blue trace: Peak detector



Final Result 1

Frequency (MHz)	MaxPeak-MaxHold (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
1585.170000	53.4	255.0	V	337.0	-13.7	20.5	73.9	


Final Result 2

Frequency (MHz)	Average-MaxHold (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
1184.368738	35.3	100.0	V	359.0	-15.1	18.6	53.9	
1400.801603	33.9	100.0	H	186.0	-14.5	20.0	53.9	
2659.318637	36.5	100.0	H	26.0	-9.7	17.4	53.9	
4046.092184	36.1	254.0	V	27.0	-3.1	17.8	53.9	
4591.182365	36.2	169.0	H	38.0	-3.2	17.7	53.9	

< Fig 18. Radiated emission result (1 000 MHz ~ 5 000 MHz)>



- ◆ Operating Condition: USB play mode
Green trace: Average detector, Blue trace: Peak detector



Final Result 1

Frequency (MHz)	MaxPeak-MaxHold (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
2659.318637	54.8	100.0	H	172.0	-9.7	19.1	73.9	

Final Result 2

Frequency (MHz)	Average-MaxHold (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
2659.318637	36.6	100.0	H	25.0	-9.7	17.3	53.9	
3180.360721	34.3	153.0	V	0.0	-7.5	19.6	53.9	
4054.108216	36.1	107.0	V	221.0	-3.1	17.8	53.9	
4607.214429	36.4	259.0	H	0.0	-3.1	17.5	53.9	

< Fig 19. Radiated emission result (1 000 MHz ~ 5 000 MHz)>



7. Sample Calculations

$$\begin{aligned}\text{dB}\mu\text{V} &= 20 \text{ Log}_{10}(\mu\text{V}/\text{m}) \\ \text{dB}\mu\text{V} &= \text{dBm} + 107 \\ \mu\text{V} &= 10^{(\text{dB}\mu\text{V}/20)}\end{aligned}$$

7.1 Example 1 :

■ 20.3 MHz

Class B Limit	= 250 μV = 48 dB μV
Reading	= 39.2 dB μV
$10^{(39.2\text{dB}\mu\text{V}/20)}$	= 91.2 μV
Margin	= 48 dB μV - 39.2 dB μV = 8.8 dB

7.2 Example 2 :

■ 66.7 MHz

Class B Limit	= 100 $\mu\text{V}/\text{m}$ = 40.0 dB $\mu\text{V}/\text{m}$
Reading	= 31.0 dB μV
Antenna Factor + Cable Loss = 5.8 dB	
Total	= 36.8 dB $\mu\text{V}/\text{m}$
Margin	= 40.0 dB $\mu\text{V}/\text{m}$ – 36.8 dB $\mu\text{V}/\text{m}$ = 3.2 dB



8. Recommendation & Conclusion

The data collected shows that the **LG Electronics Inc. LED LCD TV/Monitor (Model Name: 47LE5300-UC)** was complies with §15.107 and 15.109 of the FCC Rules.