

Maximum Permissive Exposure

FCC ID: BEJ9SD751TVDA

Product Name: WIRELESS HIGHBAY SENSOR

Model No: 9SD751TVDA

1. According to FCC CFR 47 §1.1310, the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b).

Table 1 Limits for Maximum Permissible Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits For Occupational / Control Exposures (f = frequency)				
30-300	61.4	0.163	1.0	6
300-1500	...	...	f/300	6
1500-100,000	...	...	5.0	6
(B) Limits For General Population / Uncontrolled Exposure (f = frequency)				
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

2. MPE Calculation

LG Electronics Inc. declares that the product described above has been evaluated and found to comply with the RF exposure limits for humans, as specified based on ANSI/FCC recommendation.

Based on safety distance 20cm, the antenna gain is 0.9073 dBi, and the power output is 6.561mW, the power density is 0.0016mW/cm²

RF Exposure Calculations:

$$S = (P * G) / (4 * \pi * r^2) \text{ or } r = \sqrt{(P * G) / (4 * \pi * S)}$$

Where S = Power Density in mW/cm²

P=8.17dBm=6.561mw

G =0.9073 dBi=1.232 Numerical

r = 20cm

$$S = 6.561 * 1.232 / 4 * \pi * 20^2 = 0.0016 \text{ mW/cm}^2$$

Sincerely Yours,



Mr. Ben Cheng

Manager

AUDIX Technology Corporation