

Application for FCC Certificate
On Behalf of
LG Electronics U.S.A., Inc.

LCD Monitor

Model No.: E2742VA, 27EA33VA

Serial No.: E12091172-01/01

FCC ID : BEJE2742VA

Prepared For : LG Electronics U.S.A., Inc.
1000 Sylvan Avenue, Englewood Cliffs,
NJ 07632, United States

Prepared By : Audix Technology (Shanghai) Co., Ltd.
3F and 4F, 34Bldg 680 Guiping Rd,
Caohejing Hi-Tech Park,
Shanghai 200233, China

Tel: +86-21-64955500
Fax: +86-21-64955491

Report No. : ACI-F12027A3
Date of Test : Oct 23 – 24, 2012
Date of Report : Oct 25, 2012

TABLE OF CONTENTS

	Page
1 SUMMARY OF STANDARDS AND RESULTS.....	4
1.1 Description of Standards and Results.....	4
2 GENERAL INFORMATION.....	5
2.1 Description of Equipment Under Test.....	5
2.2 Peripherals.....	6
2.3 Description of Test Facility	8
2.4 Measurement Uncertainty	8
3 CONDUCTED EMISSION TEST	9
3.1 Test Equipment.....	9
3.2 Block Diagram of Test Setup	9
3.3 Conducted Emission Limit [FCC Part 15 Subpart B 15.107(a)].....	10
3.4 Test Configuration.....	10
3.5 Operating Condition of EUT	11
3.6 Test Procedures	12
3.7 Test Results	12
4 RADIATED EMISSION TEST	20
4.1 Test Equipment.....	20
4.2 Block Diagram of Test Setup	20
4.3 Radiated Emission Limit [FCC Part 15 Subpart B 15.109(a)].....	22
4.4 Test Configuration.....	22
4.5 Operating Condition of EUT	22
4.6 Test Procedures	23
4.7 Test Results	24
5 DEVIATION TO TEST SPECIFICATIONS	33

TEST REPORT FOR FCC CERTIFICATE

Applicant : LG Electronics U.S.A., Inc.
Manufacturer : LG Electronics Nanjing Display Co., Ltd.
EUT Description : LCD Monitor
(A) Model No. : E2742VA, 27EA33VA
(B) Serial No. : E12091172-01/01
(C) Power Supply : 120V/60Hz

Test Procedure Used:

*FCC RULES AND REGULATIONS PART 15 SUBPART B CLASS B OCTOBER 2011
AND ANSI C63.4-2003*

The device described above is tested by Audix Technology (Shanghai) Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart B (Class B) and ICES-003, Issue 4 February 2004 (CISPR 22:2002) limits both radiated and conducted emissions.

The test results are contained in this test report and Audix Technology (Shanghai) Co., Ltd. is assumed full responsibility for the accuracy and completeness of these measurements. This report shows that the EUT (M/N: E2742VA, 27EA33VA; S/N: E12091172-01/01) which was tested in 3m anechoic chamber Oct 23 – 24, 2012 is technically compliance with the FCC official limits also.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of Audix Technology (Shanghai) Co., Ltd.

This report contains data that are not covered by the NVLAP accreditation.

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

Date of Test : Oct 23 – 24, 2012 Date of Report : Oct 25, 2012

Producer : Yenny Yu
YENNY YU / Assistant

Review : Dio Yang
DIO YANG / Assistant Manager

AUDIX® For and on behalf of
Audix Technology (Shanghai) Co., Ltd.

Signatory : Sammy Chen
Authorized Signature EMC SAMMY CHEN / Deputy Manager

1 SUMMARY OF STANDARDS AND RESULTS

1.1 Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Description of Test Item	Standard	Limits	Results
EMISSION			
Conducted Disturbance at the Mains Terminal	FCC RULES AND REGULATIONS PART 15 SUBPART B OCTOBER 2011 AND ANSI C63.4-2003	15.107(a) Class B	Pass
Radiated Disturbance	FCC RULES AND REGULATIONS PART 15 SUBPART B OCTOBER 2011 AND ANSI C63.4-2003	15.109(a) Class B	Pass

2 GENERAL INFORMATION

2.1 Description of Equipment Under Test

Description : LCD Monitor

Model No. : E2742VA, 27EA33VA

Serial No. : E12091172-01/01

Real Power : 29.50W

Note #1 : The different list for all the models are as follows:

Report No.	Model No.	Rev. Summary	Edition No.	Data of Rev.
ACI-F12027	E2742VA	Original Report	0	Feb 27, 2012
ACI-F12027A1	E2742VA	To add a new panel.	Rev.A1	Mar 26, 2012
ACI-F12027A2	E2742VA, 27EA33VA	1.To add a new model. 2.To add a new panel. 3.To update the standards.	Rev.A2	Sep 04, 2012
ACI-F12027A3	E2742VA, 27EA33VA	To add a new adapter.	Rev.A3	Oct 22, 2012

Note #2 : E2742VA and 27EA33VA are all the same except for the model name.
E2742VA was tested and recorded in the report.

AC Adapter : Manufacturer : LG
Model Number : LCAP21B
Input : 100-240V~, 50-60Hz 1.1A
Output : 19V  2.10A
Output Cable : Unshielded, Undetachable, 1.8m with one core

Applicant : LG Electronics U.S.A., Inc.
No.346, YaoXin Road Economic&Technical Development Zone,
Nanjing, China

Manufacturer : LG Electronics Nanjing Display Co., Ltd.
No.346, YaoXin Road Economic&Technical Development Zone,
Nanjing, China

LCD Panel	:	Original Panel	Rev. A1 added Panel
	:	Manufacturer : CHI MEI OPTOELECTRONICS	Manufacturer : LG Display
	:	M/N : M270HGE	M/N : LM270WF2
	:	Rev. A2 added Panel	--
	:	Manufacturer : LG Display	--
	:	M/N : LM270WF5	

Note #3 : We evaluated and selected the original panel(M/N: M270HGE) to test and record in the report.

Max Resolution : 1920*1080@60Hz

D-Sub Cable #1 : Shielded, Detachable, 1.85m, with two cores on cable

D-Sub Cable #2 : Shielded, Detachable, 1.50m, with two cores in connector

DVI Cable #1 : Shielded, Detachable, 1.85m, with two cores on cable

DVI Cable #2 : Shielded, Detachable, 1.50m, with two cores in connector

Power Cord : Unshielded, Detachable, 1.50m

Note : The D-Sub cable #2 and DVI cable #2 were selected to be used in the test.

Remark:

The EUT is a LCD Monitor which input/output ports as follows:

- (1) One D-Sub Port : Connected with PC
- (2) One DVI Port : Connected with PC
- (3) One HDMI Port : Connected with PC / DVD PLAYER
- (4) One Earphone Port : Connected with Earphone
- (5) One DC In Port : Connected with Adapter

2.2 Peripherals

2.2.1 PC

Manufacturer : HP
 Model Number : dx7200MT
 Serial Number : CNG622017W
 Power Cord : Unshielded, Detachable, 1.8m
 Certificate : FCC DoC; CE/EMC; VCCI; C-Tick; UL
 BSMI (R33001) 3C (A000111)
 MIC (E-A011-04-2659(B))

2.2.2 Graphics Card (Used in PC)

Manufacturer : Asus
Model Number : EAH6670
Output port : DVI, D-Sub, HDMI

2.2.3 Printer

Manufacturer : HP
Model Number : C3990A
Serial Number : JPZX020487
Data Cable : Shielded, Detachable, 1.5m
Certificate : GS, CE/EMC, C-Tick, FCC DoC

2.2.4 Keyboard

Manufacturer : Microsoft
Model Number : RT2300
Serial Number : 7668200662248
Data Cable : Shielded, Undetachable, 1.8m
Certificate : CE/EMC, FCC DoC, VCCI, MIC, C-Tick, BSMI

2.2.5 Mouse

Manufacturer : Microsoft
Model Number : RT2300
Serial Number : 6965712071551
Data Cable : Shielded, Undetachable, 1.8m.
Certificate : CE/EMC, FCC DoC, VCCI, MIC, C-Tick, BSMI

2.2.6 Modem

Manufacturer : TP-LINK
Model Number : TM-EC5658V
Serial Number : 07123301053
Data Cable : Shielded, Detachable, 1.8m
Certificate : FCC DoC, CE/EMC, CCC

2.2.7 DVD PLAYER

Manufacturer : PHILIPS
Model Number : DVP3986K/93
Serial Number : KX1A0902120108
Data Cable : Shielded, Detachable, 1.80m
Certificate : FCC DoC, CE/EMC, CCC

2.2.8 Earphone

Manufacturer : SONY
Model Number : MDR-E808
Serial Number : 1808030805305506
Data Cable : Shielded, Detachable, 1.8m

2.3 Description of Test Facility

Site Description (Semi-Anechoic Chamber) : Sept. 17, 1998 file on
Apr 29, 2009 Renewed
Federal Communications Commission
FCC Engineering Laboratory
7435 Oakland Mills Road
Columbia, MD 21046, USA

Name of Firm : Audix Technology (Shanghai) Co., Ltd.

Site Location : 3F 34Bldg 680 Guiping Rd,
Caohejing Hi-Tech Park,
Shanghai 200233, China

NVLAP Lab Code : 200371-0

2.4 Measurement Uncertainty

Conducted Emission Expanded Uncertainty: U = 3.42 dB

Radiated Emission Expanded Uncertainty (30-200MHz):
U = 4.14 dB (Horizontal)
U = 4.28 dB (Vertical)

Radiated Emission Expanded Uncertainty (200M-1GHz):
U = 4.18 dB (Horizontal)
U = 4.26 dB (Vertical)

Radiated Emission Expanded Uncertainty (Above 1GHz):
U= 4.50 dB (Horizontal)
U= 4.16 dB (Vertical)

3 CONDUCTED EMISSION TEST


3.1 Test Equipment

The following test equipments are used during the conducted emission test in a shielded room:

Item	Type	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1.	Test Receiver	R&S	ESCI	100841	Mar 22, 2012	Mar 22, 2013
2.	Artificial Mains Network (AMN #1)	R&S	ESH2-Z5	843890/011	Feb 13, 2012	Feb 13, 2013
3.	Artificial Mains Network (AMN #2)	R&S	ENV4200	100125	Mar 22, 2012	Mar 22, 2013
4.	50 Ω Coaxial Switch	Anritsu	MP59B	6200426389	Sep 18, 2012	Mar 18, 2013
5.	50 Ω Terminator	Anritsu	BNC	001	Mar 22, 2012	Mar 22, 2013
6.	Software	Audix	E3	SET00200 9804M592	--	--


3.2 Block Diagram of Test Setup

3.2.1 EUT & Peripherals



■ : Ferrite core

3.2.2 Conducted Disturbance Test Setup



3.3 Conducted Emission Limit [FCC Part 15 Subpart B 15.107(a)]

Frequency Range (MHz)	Limits dB (μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66~56	56~46
0.5 ~ 5	56	46
5 ~ 30	60	50
NOTE 1 – The lower limit shall apply at the transition frequencies. NOTE 2 – The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz~0.50 MHz		

3.4 Test Configuration

The EUT (listed in Sec.2.1) and the peripherals (listed in Sec 2.2) were installed as shown on Sec.3.2 to meet FCC requirement and operating in a manner that tends to maximize its emission level in a normal application.

3.5 Operating Condition of EUT

3.5.1 Setup the EUT and peripherals as shown in Sec. 3.2.

3.5.2 Turn on the power of all equipments and the EUT.

3.5.3 Set the contrast & brightness of EUT to maximum.

3.5.4 PC system ran the self-test program "EMC Test" by windows XP and sent "H" characters to EUT through graphic card (we use white letters on a black background to represent all colors), the EUT's screen displayed and filled with "H" pattern by its resolution (Via D-Sub/DVI Input).

3.5.5 In HDMI mode, the EUT connected to PC or DVD PLAYER through HDMI port.

3.5.6 Repeat above procedure from 3.5.3 to 3.5.5 for difference test mode.

3.5.7 The other peripherals devices were driven and operated during the test.

3.5.8 The test modes are as follows:

Test Mode
D-Sub 1920*1080@60Hz
DVI 1920*1080@60Hz
HDMI 1920*1080@60Hz
HDMI 1080P
DVI 1680*1050@60Hz
DVI 1280*1024@75Hz
DVI 640*480@60Hz

3.6 Test Procedures

The EUT and peripherals were connected to the power mains through an Artificial Mains Network (AMN). This provided a 50 ohm coupling impedance for the measuring equipment.

Both sides of AC line (Line & Neutral) were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables were changed or manipulated according to ANSI C63.4:2003 during conducted emission test.

The bandwidth of R&S Test Receiver ESCI was set at 9 kHz.

The frequency range from 150 kHz to 30 MHz was checked.

The test modes were done on conducted disturbance test and all the test results are listed in Sec. 3.7.

3.7 Test Results

< **PASS** >

The frequency and amplitude of the highest conducted emission relative to the limit is reported. All emissions not reported below are too low against the prescribed limits.

Test Mode	Page
D-Sub 1920*1080@60Hz	P13
DVI 1920*1080@60Hz	P14
HDMI 1920*1080@60Hz	P15
HDMI 1080P	P16
DVI 1680*1050@60Hz	P17
DVI 1280*1024@75Hz	P18
DVI 640*480@60Hz	P19

NOTE 1 – The **bold test mode** listed above means the worst test mode.

NOTE 2 – Factor = Cable Loss + AMN Factor.

NOTE 3 – Emission Level = Meter Reading + Factor.

NOTE 4 – “QP” means “Quasi-Peak” values, “AV” means “Average” values.

NOTE 5 – The worst case is for DVI 1920*1080@60Hz test mode. The worst emission is detected at 0.150 MHz (Quasi-Peak Value) with corrected signal level of 60.85 dB (μV) (limit is 66.00 dB (μV)), when the Line of the EUT is connected to AMN.

EUT : LCD Monitor Temperature : 22°C

Model No. : E2742VA Humidity : 48%RH

Serial No. : E12091172-01/01 Date of Test : Oct 23, 2012

Test Mode : D-Sub 1920*1080@60Hz

Test Line	Frequency (MHz)	Meter Reading dB(μV)	Factor (dB)	Emission Level dB(μV)	Limits dB(μV)	Margin (dB)	Remark
Line	0.152	59.64	0.23	59.87	65.91	6.04	QP
	0.242	43.68	0.25	43.93	62.04	18.11	
	0.561	25.27	0.32	25.59	56.00	30.41	
	4.622	32.22	0.50	32.72	56.00	23.28	
	5.419	21.38	0.52	21.90	60.00	38.10	
	15.552	32.82	0.84	33.66	60.00	26.34	
	0.152	48.30	0.23	48.53	55.91	7.38	AV
	0.242	33.00	0.25	33.25	52.04	18.79	
	0.561	15.30	0.32	15.62	46.00	30.38	
	4.622	22.10	0.50	22.60	46.00	23.40	
	5.419	11.20	0.52	11.72	50.00	38.28	
	15.552	22.60	0.84	23.44	50.00	26.56	
Neutral	0.150	59.79	0.13	59.92	66.00	6.08	QP
	0.242	44.34	0.11	44.45	62.04	17.59	
	0.564	27.43	0.17	27.60	56.00	28.40	
	4.721	31.58	0.42	32.00	56.00	24.00	
	5.419	21.58	0.44	22.02	60.00	37.98	
	15.885	33.42	0.74	34.16	60.00	25.84	
	0.150	48.90	0.13	49.03	56.00	6.97	AV
	0.242	34.20	0.11	34.31	52.04	17.73	
	0.564	17.21	0.17	17.38	46.00	28.62	
	4.721	21.19	0.42	21.61	46.00	24.39	
	5.419	11.30	0.44	11.74	50.00	38.26	
	15.885	23.20	0.74	23.94	50.00	26.06	

TEST ENGINEER: SAWEN LI

EUT : LCD Monitor Temperature : 22°C

Model No. : E2742VA Humidity : 48%RH

Serial No. : E12091172-01/01 Date of Test : Oct 23, 2012

Test Mode : DVI 1920*1080@60Hz

Test Line	Frequency (MHz)	Meter Reading dB(μV)	Factor (dB)	Emission Level dB(μV)	Limits dB(μV)	Margin (dB)	Remark
Line	0.150	60.62	0.23	60.85	66.00	5.15	QP
	0.237	43.85	0.25	44.10	62.22	18.12	
	0.561	26.15	0.32	26.47	56.00	29.53	
	4.672	32.36	0.50	32.86	56.00	23.14	
	5.419	21.47	0.52	21.99	60.00	38.01	
	15.552	33.86	0.84	34.70	60.00	25.30	
	0.150	50.10	0.23	50.33	56.00	5.67	AV
	0.237	33.60	0.25	33.85	52.22	18.37	
	0.561	16.00	0.32	16.32	46.00	29.68	
	4.672	22.10	0.50	22.60	46.00	23.40	
	5.419	11.60	0.52	12.12	50.00	37.88	
	15.552	22.90	0.84	23.74	50.00	26.26	
Neutral	0.150	60.57	0.13	60.70	66.00	5.30	QP
	0.239	44.13	0.11	44.24	62.13	17.89	
	0.564	26.91	0.17	27.08	56.00	28.92	
	4.672	31.47	0.42	31.89	56.00	24.11	
	5.774	20.44	0.48	20.92	60.00	39.08	
	15.885	33.28	0.74	34.02	60.00	25.98	
	0.150	50.60	0.13	50.73	56.00	5.27	AV
	0.239	34.00	0.11	34.11	52.13	18.02	
	0.564	16.81	0.17	16.98	46.00	29.02	
	4.672	20.89	0.42	21.31	46.00	24.69	
	5.774	10.19	0.48	10.67	50.00	39.33	
	15.885	23.20	0.74	23.94	50.00	26.06	

TEST ENGINEER: SAWEN LI

EUT : LCD Monitor Temperature : 22°C

Model No. : E2742VA Humidity : 48%RH

Serial No. : E12091172-01/01 Date of Test : Oct 23, 2012

Test Mode : HDMI 1920*1080@60Hz

Test Line	Frequency (MHz)	Meter Reading dB(μV)	Factor (dB)	Emission Level dB(μV)	Limits dB(μV)	Margin (dB)	Remark
Line	0.150	59.57	0.23	59.80	66.00	6.20	QP
	0.234	44.29	0.25	44.54	62.30	17.76	
	0.564	26.01	0.31	26.32	56.00	29.68	
	4.622	31.43	0.50	31.93	56.00	24.07	
	5.419	21.99	0.52	22.51	60.00	37.49	
	15.552	32.88	0.84	33.72	60.00	26.28	
	0.150	48.90	0.23	49.13	56.00	6.87	AV
	0.234	34.20	0.25	34.45	52.30	17.85	
	0.564	15.81	0.31	16.12	46.00	29.88	
	4.622	21.20	0.50	21.70	46.00	24.30	
	5.419	11.90	0.52	12.42	50.00	37.58	
	15.552	22.60	0.84	23.44	50.00	26.56	
Neutral	0.150	59.56	0.13	59.69	66.00	6.31	QP
	0.242	44.10	0.11	44.21	62.04	17.83	
	0.564	27.52	0.17	27.69	56.00	28.31	
	4.622	33.63	0.42	34.05	56.00	21.95	
	5.419	20.95	0.44	21.39	60.00	38.61	
	16.055	33.18	0.74	33.92	60.00	26.08	
	0.150	49.20	0.13	49.33	56.00	6.67	AV
	0.242	34.20	0.11	34.31	52.04	17.73	
	0.564	17.33	0.17	17.50	46.00	28.50	
	4.622	23.39	0.42	23.81	46.00	22.19	
	5.419	10.20	0.44	10.64	50.00	39.36	
	16.055	23.10	0.74	23.84	50.00	26.16	

TEST ENGINEER: SAWEN LI

EUT : LCD Monitor Temperature : 22°C

Model No. : E2742VA Humidity : 48%RH

Serial No. : E12091172-01/01 Date of Test : Oct 23, 2012

Test Mode : HDMI 1080P

Test Line	Frequency (MHz)	Meter Reading dB(μV)	Factor (dB)	Emission Level dB(μV)	Limits dB(μV)	Margin (dB)	Remark
Line	0.150	59.07	0.23	59.30	66.00	6.70	QP
	0.242	42.93	0.25	43.18	62.04	18.86	
	0.561	25.24	0.32	25.56	56.00	30.44	
	4.721	31.39	0.50	31.89	56.00	24.11	
	7.368	20.78	0.66	21.44	60.00	38.56	
	15.718	34.26	0.84	35.10	60.00	24.90	
	0.150	48.50	0.23	48.73	56.00	7.27	AV
	0.242	32.20	0.25	32.45	52.04	19.59	
	0.561	15.20	0.32	15.52	46.00	30.48	
	4.721	21.20	0.50	21.70	46.00	24.30	
	7.368	10.91	0.66	11.57	50.00	38.43	
	15.718	24.21	0.84	25.05	50.00	24.95	
Neutral	0.150	59.14	0.13	59.27	66.00	6.73	QP
	0.242	43.51	0.11	43.62	62.04	18.42	
	0.561	26.21	0.17	26.38	56.00	29.62	
	4.672	30.63	0.42	31.05	56.00	24.95	
	5.774	20.05	0.48	20.53	60.00	39.47	
	15.718	34.19	0.73	34.92	60.00	25.08	
	0.150	48.20	0.13	48.33	56.00	7.67	AV
	0.242	33.10	0.11	33.21	52.04	18.83	
	0.561	16.11	0.17	16.28	46.00	29.72	
	4.672	19.89	0.42	20.31	46.00	25.69	
	5.774	9.99	0.48	10.47	50.00	39.53	
	15.718	24.01	0.73	24.74	50.00	25.26	

TEST ENGINEER: SAWEN LI

EUT : LCD Monitor Temperature : 22°C

Model No. : E2742VA Humidity : 48%RH

Serial No. : E12091172-01/01 Date of Test : Oct 23, 2012

Test Mode : DVI 1680*1050@60Hz

Test Line	Frequency (MHz)	Meter Reading dB(μV)	Factor (dB)	Emission Level dB(μV)	Limits dB(μV)	Margin (dB)	Remark
Line	0.150	59.44	0.23	59.67	66.00	6.33	QP
	0.239	43.49	0.25	43.74	62.13	18.39	
	0.561	25.25	0.32	25.57	56.00	30.43	
	4.672	31.71	0.50	32.21	56.00	23.79	
	7.329	21.72	0.66	22.38	60.00	37.62	
	15.718	33.52	0.84	34.36	60.00	25.64	
	0.150	48.90	0.23	49.13	56.00	6.87	AV
	0.239	33.20	0.25	33.45	52.13	18.68	
	0.561	15.10	0.32	15.42	46.00	30.58	
	4.672	21.60	0.50	22.10	46.00	23.90	
	7.329	11.40	0.66	12.06	50.00	37.94	
	15.718	22.91	0.84	23.75	50.00	26.25	
Neutral	0.152	59.15	0.13	59.28	65.91	6.63	QP
	0.239	43.76	0.11	43.87	62.13	18.26	
	0.561	26.99	0.17	27.16	56.00	28.84	
	4.672	31.28	0.42	31.70	56.00	24.30	
	5.419	20.20	0.44	20.64	60.00	39.36	
	15.552	33.05	0.73	33.78	60.00	26.22	
	0.152	49.00	0.13	49.13	55.91	6.78	AV
	0.239	33.60	0.11	33.71	52.13	18.42	
	0.561	16.81	0.17	16.98	46.00	29.02	
	4.672	21.09	0.42	21.51	46.00	24.49	
	5.419	10.00	0.44	10.44	50.00	39.56	
	15.552	23.20	0.73	23.93	50.00	26.07	

TEST ENGINEER: SAWEN LI

EUT : LCD Monitor Temperature : 22°C

Model No. : E2742VA Humidity : 48%RH

Serial No. : E12091172-01/01 Date of Test : Oct 23, 2012

Test Mode : DVI 1280*1024@75Hz

Test Line	Frequency (MHz)	Meter Reading dB(μV)	Factor (dB)	Emission Level dB(μV)	Limits dB(μV)	Margin (dB)	Remark
Line	0.152	58.81	0.23	59.04	65.91	6.87	QP
	0.239	43.28	0.25	43.53	62.13	18.60	
	0.564	25.14	0.31	25.45	56.00	30.55	
	4.622	31.72	0.50	32.22	56.00	23.78	
	7.446	21.24	0.66	21.90	60.00	38.10	
	15.885	33.68	0.85	34.53	60.00	25.47	
	0.152	48.10	0.23	48.33	55.91	7.58	AV
	0.239	33.10	0.25	33.35	52.13	18.78	
	0.564	15.21	0.31	15.52	46.00	30.48	
	4.622	20.30	0.50	20.80	46.00	25.20	
	7.446	11.21	0.66	11.87	50.00	38.13	
	15.885	22.90	0.85	23.75	50.00	26.25	
Neutral	0.150	59.15	0.13	59.28	66.00	6.72	QP
	0.239	43.99	0.11	44.10	62.13	18.03	
	0.579	26.04	0.18	26.22	56.00	29.78	
	4.574	30.65	0.42	31.07	56.00	24.93	
	5.419	20.03	0.44	20.47	60.00	39.53	
	16.055	32.28	0.74	33.02	60.00	26.98	
	0.150	48.60	0.13	48.73	56.00	7.27	AV
	0.239	33.25	0.11	33.36	52.13	18.77	
	0.579	15.90	0.18	16.08	46.00	29.92	
	4.574	20.39	0.42	20.81	46.00	25.19	
	5.419	10.00	0.44	10.44	50.00	39.56	
	16.055	22.60	0.74	23.34	50.00	26.66	

TEST ENGINEER: SAWEN LI

EUT : LCD Monitor Temperature : 22°C

Model No. : E2742VA Humidity : 48%RH

Serial No. : E12091172-01/01 Date of Test : Oct 23, 2012

Test Mode : DVI 640*480@60Hz

Test Line	Frequency (MHz)	Meter Reading dB(μV)	Factor (dB)	Emission Level dB(μV)	Limits dB(μV)	Margin (dB)	Remark
Line	0.150	59.44	0.23	59.67	66.00	6.33	QP
	0.239	43.49	0.25	43.74	62.13	18.39	
	0.561	25.25	0.32	25.57	56.00	30.43	
	4.672	31.71	0.50	32.21	56.00	23.79	
	7.329	21.72	0.66	22.38	60.00	37.62	
	15.718	33.52	0.84	34.36	60.00	25.64	
	0.150	48.90	0.23	49.13	56.00	6.87	AV
	0.239	33.60	0.25	33.85	52.13	18.28	
	0.561	15.20	0.32	15.52	46.00	30.48	
	4.672	21.60	0.50	22.10	46.00	23.90	
	7.329	11.40	0.66	12.06	50.00	37.94	
	15.718	23.11	0.84	23.95	50.00	26.05	
Neutral	0.150	59.29	0.13	59.42	66.00	6.58	QP
	0.242	43.66	0.11	43.77	62.04	18.27	
	0.573	26.15	0.18	26.33	56.00	29.67	
	4.622	32.96	0.42	33.38	56.00	22.62	
	5.653	20.99	0.46	21.45	60.00	38.55	
	16.226	32.75	0.74	33.49	60.00	26.51	
	0.150	49.00	0.13	49.13	56.00	6.87	AV
	0.242	33.20	0.11	33.31	52.04	18.73	
	0.573	16.20	0.18	16.38	46.00	29.62	
	4.622	21.49	0.42	21.91	46.00	24.09	
	5.653	10.20	0.46	10.66	50.00	39.34	
	16.226	22.60	0.74	23.34	50.00	26.66	

TEST ENGINEER: SAWEN LI

4 RADIATED EMISSION TEST


4.1 Test Equipment

The following test equipments are used during the radiated emission test in a semi-anechoic chamber:

Item	Type	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1.	Test Receiver	R&S	ESVS10	844594/001	Mar 22, 2012	Mar 22, 2013
2.	Preamplifier	Agilent	8447D	2944A10548	Mar 18, 2012	Sep 18, 2012
3.	Preamplifier	HP	8449B	3008A00864	Mar 22, 2012	Mar 22, 2013
4.	Bi-log Antenna	TESEQ	CBL6112D	23192	Dec 01, 2011	Dec 01, 2012
5.	Horn Antenna	EMCO	3115	9607-4878	May 03, 2012	May 03, 2013
6.	Spectrum	Agilent	E7405A	MY45106600	Mar 22, 2012	Mar 22, 2013
7.	50Ω Coaxial Switch	Anritsu	MP59B	6200426390	Sep 18, 2012	Mar 18, 2013
8.	Software	Audix	E3	SET00200 9912M295-2	--	--

4.2 Block Diagram of Test Setup


4.2.1 EUT and Peripherals



■ : Ferrite core


4.2.2 Radiated emission test setup

4.2.2.1 Below 1GHz



■ : 50 ohm Coaxial Switch

4.2.2.2 Above 1GHz



■ : 50 ohm Coaxial Switch

4.3 Radiated Emission Limit [FCC Part 15 Subpart B 15.109(a)]

Frequency (MHz)	Distance (m)	Field strength limits	
		($\mu\text{V/m}$)	dB ($\mu\text{V/m}$)
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
Above 960	3	500	54.0
NOTE 1 - Emission Level dB ($\mu\text{V/m}$) = 20 log Emission Level ($\mu\text{V/m}$) NOTE 2 - The tighter limit applies at the band edges. NOTE 3 - Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system. NOTE 4 - The limits shown are based on Quasi-peak value detector below or equal to 1GHz and Average value detector above 1GHz. NOTE 5 - Above 1 GHz, the limit on peak emission is 20 dB above the maximum permitted average emission limit applicable to the EUT.			

4.4 Test Configuration

The configuration of the EUT and peripherals are same as those used in conducted emission test.

Please refer to Sec.3.4.

4.5 Operating Condition of EUT

Same as conducted emission test which is listed in Sec.3.5, except for the test setup replaced by Sec.4.2.

4.6 Test Procedures

The EUT and peripherals were placed on a FRP turntable that is 0.8 meter above ground. The FRP turntable rotated 360 degrees to determine the position of the maximum emission level. The EUT was set 3 meters away from the receiving antenna, which was mounted on an antenna tower. Broadband antenna (Calibrated Bilog Antenna) or Horn Antenna was used as receiving antenna. The antenna moved up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarizations of the antenna were set on measurement. In order to find the maximum emission, all of the interference cables were manipulated according to ANSI C63.4:2003 requirements during radiated emission test.

The I.F. bandwidth of Test Receiver R&S ESVS10 was set at 120 kHz below 1GHz and The Spectrum Agilent E7405A was set at 1MHz above 1GHz.

The frequency range from 30 MHz to 1000MHz was checked for all test modes.

The frequency range from 1 GHz to 2 GHz was checked for worst test mode in 30 - 1000 MHz test.

The test modes were done on radiated disturbance test and all the test results are listed in Sec.4.7.

4.7 Test Results

<PASS>

The frequency and amplitude of the highest radiated emission relative the limit is reported. All the emissions not reported below are too low against the FCC limit.

Test Mode	Data Page
D-Sub 1920*1080@60Hz	P25 – P26
DVI 1920*1080@60Hz	P27
HDMI 1920*1080@60Hz	P28
HDMI 1080P	P29
D-Sub 1680*1050@60Hz	P30
D-Sub 1280*1024@75Hz	P31
D-Sub 640*480@60Hz	P32

NOTE 1 – **The bold test mode** listed above means the worst test mode.

NOTE 2 – Emission Level = Antenna Factor + Cable Loss + Meter Reading.(< 1GHz)

NOTE 3 – Emission Level = Antenna Factor + Cable Loss – Preamp Factor + Meter Reading.(> 1GHz)

NOTE 4 – All readings are Quasi-Peak values below or equal to 1GHz, Peak and average values above 1GHz.

NOTE 5 – The emission levels that are 20dB below the official limit are not reported.

NOTE 6 – 0° was the table front facing the antenna. Degree is calculated from 0° clockwise facing the antenna.

NOTE 7 – The worst case is for D-Sub 1920*1080@60Hz test mode. The worst emission at horizontal polarization was detected at 94.990 MHz with corrected signal level of 39.53 dB (μV/m) (limit is 43.50 dB (μV/m)), when the antenna was 1.10 m height and the turntable was at 158°. The worst emission at vertical polarization was detected at 436.430 MHz with corrected signal level of 37.40 dB (μV/m) (limit is 46.00 dB (μV/m)), when the antenna was 1.20 m height and the turntable was at 247°.

EUT : LCD Monitor Temperature : 22°C

Model No. : E2742VA Humidity : 60%RH

Serial No. : E12091172-01/01 Date of Test : Oct 24, 2012

Test Mode : D-Sub 1920*1080@60Hz

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
Horizontal	41.640	19.17	11.78	0.47	--	31.42	40.00	8.58	QP
	53.280	21.56	8.70	0.55	--	30.81	40.00	9.19	
	67.830	15.90	9.70	0.67	--	26.27	40.00	13.73	
	94.990	27.45	11.18	0.90	--	39.53	43.50	3.97	
	140.580	21.24	10.60	1.01	--	32.85	43.50	10.65	
	318.090	19.59	14.19	1.31	--	35.09	46.00	10.91	
	1075.000	50.88	22.16	5.27	38.04	40.27	74.00	33.73	PK
	1180.000	41.35	23.49	5.34	37.81	32.37	74.00	41.63	
	1250.000	48.46	24.05	5.42	37.65	40.28	74.00	33.72	
	1365.000	46.43	24.80	5.55	37.33	39.45	74.00	34.55	
	1595.000	42.72	26.41	5.93	36.77	38.29	74.00	35.71	
	1760.000	45.18	26.96	6.17	36.49	41.82	74.00	32.18	
	1075.000	37.88	22.16	5.27	38.04	27.27	54.00	26.73	AV
	1180.000	34.35	23.49	5.34	37.81	25.37	54.00	28.63	
	1250.000	35.46	24.05	5.42	37.65	27.28	54.00	26.72	
	1365.000	33.43	24.80	5.55	37.33	26.45	54.00	27.55	
	1595.000	32.72	26.41	5.93	36.77	28.29	54.00	25.71	
	1760.000	31.18	26.96	6.17	36.49	27.82	54.00	26.18	

TEST ENGINEER: RAVEN JIN

EUT : LCD Monitor Temperature : 22°C

Model No. : E2742VA Humidity : 60%RH

Serial No. : E12091172-01/01 Date of Test : Oct 24, 2012

Test Mode : D-Sub 1920*1080@60Hz

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
Vertical	80.440	19.18	10.56	0.78	--	30.52	40.00	9.48	QP
	94.990	14.96	11.18	0.90	--	27.04	43.50	16.46	
	133.790	19.44	10.74	1.00	--	31.18	43.50	12.32	
	318.090	19.89	14.19	1.31	--	35.39	46.00	10.61	
	436.430	19.06	16.79	1.55	--	37.40	46.00	8.60	
	516.940	15.16	17.70	1.81	--	34.67	46.00	11.33	
	1080.000	49.01	22.24	4.50	38.03	37.72	74.00	36.28	PK
	1275.000	46.59	24.25	4.53	37.57	37.80	74.00	36.20	
	1365.000	46.67	24.80	4.54	37.33	38.68	74.00	35.32	
	1600.000	47.89	26.40	4.56	36.76	42.09	74.00	31.91	
	1760.000	49.67	26.96	4.58	36.49	44.72	74.00	29.28	
	1850.000	43.62	26.52	4.64	36.37	38.41	74.00	35.59	
	1080.000	40.01	22.24	4.50	38.03	28.72	54.00	25.28	AV
	1275.000	31.59	24.25	4.53	37.57	22.80	54.00	31.20	
	1365.000	33.67	24.80	4.54	37.33	25.68	54.00	28.32	
	1600.000	35.89	26.40	4.56	36.76	30.09	54.00	23.91	
	1760.000	36.67	26.96	4.58	36.49	31.72	54.00	22.28	
	1850.000	29.62	26.52	4.64	36.37	24.41	54.00	29.59	

TEST ENGINEER: RAVEN JIN

EUT : LCD Monitor Temperature : 22°C

Model No. : E2742VA Humidity : 60%RH

Serial No. : E12091172-01/01 Date of Test : Oct 24, 2012

Test Mode : DVI 1920*1080@60Hz

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)
Horizontal	80.440	16.13	10.56	0.78	27.47	40.00	12.53
	133.790	15.68	10.74	1.00	27.42	43.50	16.08
	198.780	22.97	9.81	1.11	33.89	43.50	9.61
	318.090	17.25	14.19	1.31	32.75	46.00	13.25
	436.430	16.73	16.79	1.55	35.07	46.00	10.93
	516.940	13.28	17.70	1.81	32.79	46.00	13.21
Vertical	41.640	14.10	11.78	0.47	26.35	40.00	13.65
	53.280	16.44	8.70	0.55	25.69	40.00	14.31
	80.440	19.40	10.56	0.78	30.74	40.00	9.26
	94.990	18.32	11.18	0.90	30.40	43.50	13.10
	198.780	20.04	9.81	1.11	30.96	43.50	12.54
	318.090	14.28	14.19	1.31	29.78	46.00	16.22

TEST ENGINEER: RAVEN JIN

EUT : LCD Monitor Temperature : 22°C

Model No. : E2742VA Humidity : 60%RH

Serial No. : E12091172-01/01 Date of Test : Oct 24, 2012

Test Mode : HDMI 1920*1080@60Hz

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)
Horizontal	41.640	12.34	11.78	0.47	24.59	40.00	15.41
	80.440	18.15	10.56	0.78	29.49	40.00	10.51
	94.990	16.26	11.18	0.90	28.34	43.50	15.16
	138.640	12.92	10.65	1.00	24.57	43.50	18.93
	198.780	16.97	9.81	1.11	27.89	43.50	15.61
	480.080	14.11	17.37	1.71	33.19	46.00	12.81
Vertical	80.440	16.38	10.56	0.78	27.72	40.00	12.28
	145.430	17.83	10.50	1.02	29.35	43.50	14.15
	187.140	21.73	9.92	1.09	32.74	43.50	10.76
	279.290	19.00	13.09	1.23	33.32	46.00	12.68
	318.090	19.82	14.19	1.31	35.32	46.00	10.68
	436.430	17.48	16.79	1.55	35.82	46.00	10.18

TEST ENGINEER: RAVEN JIN

EUT : LCD Monitor Temperature : 22°C

Model No. : E2742VA Humidity : 60%RH

Serial No. : E12091172-01/01 Date of Test : Oct 24, 2012

Test Mode : HDMI 1080P

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)
Horizontal	80.440	17.49	10.56	0.78	28.83	40.00	11.17
	94.990	12.79	11.18	0.90	24.87	43.50	18.63
	133.790	19.38	10.74	1.00	31.12	43.50	12.38
	187.140	21.66	9.92	1.09	32.67	43.50	10.83
	318.090	18.51	14.19	1.31	34.01	46.00	11.99
	436.430	15.76	16.79	1.55	34.10	46.00	11.90
Vertical	41.640	17.44	11.78	0.47	29.69	40.00	10.31
	80.440	23.96	10.56	0.78	35.30	40.00	4.70
	94.990	21.11	11.18	0.90	33.19	43.50	10.31
	198.780	23.02	9.81	1.11	33.94	43.50	9.56
	318.090	19.52	14.19	1.31	35.02	46.00	10.98
	352.040	20.10	15.17	1.37	36.64	46.00	9.36

TEST ENGINEER: RAVEN JIN

EUT : LCD Monitor Temperature : 22°C

Model No. : E2742VA Humidity : 60%RH

Serial No. : E12091172-01/01 Date of Test : Oct 24, 2012

Test Mode : D-Sub 1680*1050@60Hz

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)
Horizontal	41.640	23.31	11.78	0.47	35.56	40.00	4.44
	53.280	21.36	8.70	0.55	30.61	40.00	9.39
	80.440	23.56	10.56	0.78	34.90	40.00	5.10
	94.990	20.82	11.18	0.90	32.90	43.50	10.60
	140.580	20.95	10.60	1.01	32.56	43.50	10.94
	198.780	23.48	9.81	1.11	34.40	43.50	9.10
Vertical	80.440	19.98	10.56	0.78	31.32	40.00	8.68
	145.430	19.76	10.50	1.02	31.28	43.50	12.22
	198.780	26.43	9.81	1.11	37.35	43.50	6.15
	250.190	21.22	11.99	1.18	34.39	46.00	11.61
	318.090	19.39	14.19	1.31	34.89	46.00	11.11
	516.940	13.74	17.70	1.81	33.25	46.00	12.75

TEST ENGINEER: RAVEN JIN

EUT : LCD Monitor Temperature : 22°C

Model No. : E2742VA Humidity : 60%RH

Serial No. : E12091172-01/01 Date of Test : Oct 24, 2012

Test Mode : D-Sub 1280*1024@75Hz

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)
Horizontal	80.440	19.52	10.56	0.78	30.86	40.00	9.14
	145.430	20.19	10.50	1.02	31.71	43.50	11.79
	235.640	17.50	11.32	1.16	29.98	46.00	16.02
	318.090	19.03	14.19	1.31	34.53	46.00	11.47
	528.580	6.18	17.77	1.85	25.80	46.00	20.20
	640.130	9.01	18.74	2.24	29.99	46.00	16.01
Vertical	53.280	23.34	8.70	0.55	32.59	40.00	7.41
	67.830	18.10	9.70	0.67	28.47	40.00	11.53
	140.580	21.12	10.60	1.01	32.73	43.50	10.77
	198.780	23.84	9.81	1.11	34.76	43.50	8.74
	252.130	20.17	12.09	1.18	33.44	46.00	12.56
	352.040	21.25	15.17	1.37	37.79	46.00	8.21

TEST ENGINEER: RAVEN JIN

EUT : LCD Monitor Temperature : 22°C

Model No. : E2742VA Humidity : 60%RH

Serial No. : E12091172-01/01 Date of Test : Oct 24, 2012

Test Mode : D-Sub 640*480@60Hz

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)
Horizontal	53.280	22.23	8.70	0.55	31.48	40.00	8.52
	67.830	17.94	9.70	0.67	28.31	40.00	11.69
	106.630	14.09	11.24	0.95	26.28	43.50	17.22
	198.780	23.15	9.81	1.11	34.07	43.50	9.43
	256.980	20.65	12.27	1.19	34.11	46.00	11.89
	528.580	11.45	17.77	1.85	31.07	46.00	14.93
Vertical	80.440	19.13	10.56	0.78	30.47	40.00	9.53
	94.990	12.72	11.18	0.90	24.80	43.50	18.70
	145.430	19.10	10.50	1.02	30.62	43.50	12.88
	247.280	17.98	11.85	1.17	31.00	46.00	15.00
	305.480	13.33	13.87	1.29	28.49	46.00	17.51
	516.940	12.24	17.70	1.81	31.75	46.00	14.25

TEST ENGINEER: RAVEN JIN

5 DEVIATION TO TEST SPECIFICATIONS

None.