

Standalone SAR test exclusion considerations

March 20, 2013

- Min. transmitting frequency = **2401.2497** MHz
- Min. test separation distance = **5** mm
- Max. power with turn-up tolerance = **-0.45** dBm = **1** mW
Typical Power: **-0.45** dBm ± dB
Measured Power: **-0.45** dBm

Step 1) SAR test exclusion thresholds for 100MHz to 6GHz at test separationn distances ≤ 50 mm = **Used**

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$

= $[1.00 / 5] \cdot [\sqrt{2.40125}]$

= **0.31** ≤ 3, for 1g SAR

Thus SAR for this device is not required.

Step 2-1) SAR test exclusion thresholds for 100MHz to 1500MHz at test separationn distances > 50 mm = **N/A**

$[\text{Threshold at 50 mm in step 1}) + (\text{test separation distance} - 50 \text{ mm}) \cdot (f(\text{MHz})/150)] \text{ mW}$

Step 2-2) SAR test exclusion thresholds for 1500MHz to 6GHz at test separationn distances > 50 mm = **N/A**

$[\text{Threshold at 50 mm in step 1}) + (\text{test separation distance} - 50 \text{ mm}) \cdot 10] \text{ mW}$