



FCC TEST REPORT

According to

47 CFR, Part 2, Part 15 and CISPR PUB. 22

Applicant	: LG Electronics USA
Address	: 1000 Sylvan Avenue Englewood Cliffs New Jersey United States
Equipment	: LCD Monitor
Model No.	: IPS234TA
FCC ID	: BEJIPS234TA

This is a series report. The original report No. is SEFD1203063.

- The test result refers exclusively to the test presented test model / sample.
- Without written approval of **CerpPASS Technology Corp.** the test report shall not be reproduced except in full.
- The test report must not be used by the clients to claim product certification approval by **NVLAP** or any agency of the Government.



Contents

1. Summary of Test Procedure and Test Result	5
2. Test Configuration of Equipment under Test.....	6
2.1. Manufacturer	6
2.2. Feature of Equipment under Test	6
2.3. Test Manner	8
2.4. Description of Support Unit	10
2.5. General Information of Test	11
2.6. Measurement Uncertainty	11
3. Test of Conducted Emission	12
3.1. Test Limit	12
3.2. Test Procedures.....	12
3.3. Typical test Setup	13
3.4. Measurement equipment.....	13
3.5. Test Result and Data	14
4. Test of Radiated Emission	16
4.1. Test Limit	16
4.2. Test Procedures.....	17
4.3. Typical test Setup	17
4.4. Measurement equipment.....	18
4.5. Test Result and Data (30MHz ~ 1000MHz).....	19
4.6. Test Result and Data (1000MHz ~ 18000MHz).....	21



History of this test report

☐ ORIGINAL.

☐ Additional attachment as following record:

Attachment No.	Date	Description
SEFD1203063	Mar 19, 2012	the original report
SEFD1209066	Sep 24, 2012	Second edition (Add six adapters, update the prototype lable)



FCC TEST REPORT

According to

47 CFR, Part 2, Part 15 and CISPR PUB. 22

Applicant	: LG Electronics USA
Address	: 1000 Sylvan Avenue Englewood Cliffs New Jersey United States
Equipment	: LCD Monitor
Model No.	: IPS234TA
FCC ID	: BEJIPS234TA

I **HEREBY** CERTIFY THAT :

The measurements shown in this test report were made in accordance with the procedures given in **ANSI C63.4 – 2003** and the energy emitted by this equipment was ***passed*** **CISPR PUB. 22 and FCC Part 15** in both radiated and conducted emission class B limits. Testing was carried out on Sep 21, 2012 at ***CerpPASS Technology Corp.***

Signature

Miro Chueh/ Technical director



1. Summary of Test Procedure and Test Result

Test Item	Normative References	Test Result
Conducted Emission	ANSI C63.4-2003 FCC Part 15 Subpart B	PASS
Radiated Emission	ANSI C63.4-2003 FCC Part 15 Subpart B	PASS



2. Test Configuration of Equipment under Test

2.1. Manufacturer

LG Electronics Nanjing Display Co.,Ltd.

No.346,Yaoxin Road Economic & Technical Development Zone Nanjing China

2.2. Feature of Equipment under Test

LCD Monitor	Model No:	IPS234TA
Adapter #1	Manufacturer:	Lien Chang Electronic Enterprise Co.,Ltd.
	Model No.:	LCAP21A
	Input Rating:	100-240V~ 50-60Hz,1.1 A
	Output Rating:	19V  1.7A
DC Cable	Non-shielded, 1.5m with one ferrite cores bonded	
Adapter #2	Manufacturer:	SHENZHEN HONOR ELECTRONIC CO.,LTD.
	Model No.:	ADS-40SG-19-3 19032G
	Input Rating:	100-240V~ 50/60Hz,1.0A
	Output Rating:	19V  1.7A
DC Cable	Non-shielded, 1.5m	
Adapter #3	Manufacturer:	SHENZHEN HONOR ELECTRONIC CO.,LTD.
	Model No.:	ADS-40FSG-19 19032G***-1(*** can be PG,PBR,PI,PCU (direct plug-in type) represents different plug types, ADS-40FSG-19 19032GPG-1 was selected as the test model)
	Input:	100-240V~ 50/60Hz 1.0A max
	Output:	19V  1.7A
DC Cable	Non-Shielded, 1.5m	
Adapter #4	Manufacturer:	Lien Chang Electronic Enterprise Co.,Ltd.
	Model No.:	LCAP26A-* (* can be A,E,I,B direct plug-in type) represents different plug types, LCAP26A-C was selected as the test model)
	Input:	100-240V~50-60Hz 1.1A
	Output:	19V  1.7A
DC Cable	Non-Shielded, 1.5m	
VGA Cable	Shielded, 1.5m	
DVI Cable	Shielded, 1.5m	
※ the EUT Photos of 36~39 Just a publicity.		

Panel Manufacturer	Panel Model No.
LG	LM230WF3



Add six adapters:

Adapter #5	Manufacturer:	LG Innotek Co.,Ltd.
	Model No.:	PSAB-L203A
	Input:	100-240V~50-60Hz 1.1A
	Output:	19V  1.3A
DC Cable	Non-shielded, 1.5m, with one ferrite core bonded	
Adapter #6	Manufacturer:	LG Innotek Co.,Ltd.
	Model No.:	PSAB-L202*(* can be A,B,C,D direct plug-in type) represents different plug types, PSAB-L202A was selected as the test model)
	Input:	100-240V~ 50/60Hz 1.1A
	Output:	19V  1.3A
DC Cable	Non-shielded, 1.5m, with one ferrite core bonded	
Adapter #7	Manufacturer:	Lien Chang Electronic Enterprise Co.,Ltd.
	Model No.:	LCAP21
	Input Rating:	100-240V~ 50-60Hz,1.1 A
	Output Rating:	19V  1.3A
DC Cable	Non-shielded, 1.5m with one ferrite core bonded	
Adapter #8	Manufacturer:	SHENZHEN HONOR ELECTRONIC CO.,LTD.
	Model No.:	ADS-40SG-19-3 19025G
	Input Rating:	100-240V~ 50/60Hz,1.0A
	Output Rating:	19V  1.3A
DC Cable	Non-shielded, 1.5m	
Adapter #9	Manufacturer:	SHENZHEN HONOR ELECTRONIC CO.,LTD.
	Model No.:	ADS-40FSG-19 19025G***-1(*** can be PG,PBR,PI,PCU,PB-2 (direct plug-in type) represents different plug types, ADS-40FSG-19 19025GPG-1 was selected as the test model)
	Input:	100-240V~ 50/60Hz 1.0A max
	Output:	19V  1.3A
DC Cable	Non-shielded, 1.5m	
Adapter #10	Manufacturer:	Lien Chang Electronic Enterprise Co.,Ltd.
	Model No.:	LCAP26A-* (* can be A,E,I,B direct plug-in type) represents different plug types, LCAP26-C was selected as the test model)
	Input:	100-240V~50-60Hz 1.1A
	Output:	19V  1.3A
DC Cable	Non-shielded, 1.5m	
Remark:	The evaluation test of power supply is adapter #8 . ※ the EUT Photos of 43~45, 50~54 Just a publicity.	



2.3. Test Manner

Test Software

- a During testing, the interface cables and equipment positions were varied according to ANSI C63.4.
- b The complete test system included the PC, Printer, USB Keyboard, USB Mouse, and EUT for EMI test.
- c During the test, setup up the EUT and all system, turn on the power of all Equipments, run the EMC test software “H”, set the contrast control to maximum, set the brightness control to maximum, use white letters on a black background to represent all colors, make the EUT at the test mode and it is normal operation, and then test.



The pre-test modes

Test Mode 1: Full system (VGA mode 1920*1080@60Hz)With Adapter#8
Test Mode 2: Full system (VGA mode 1024*768@75Hz) With Adapter#8
Test Mode 3: Full system (VGA mode 720*400@70Hz) With Adapter#8
Test Mode 4: Full system (DVI mode 1920*1080@60Hz)With Adapter#8
Test Mode 5: Full system (DVI mode 1024*768@75Hz) With Adapter#8
Test Mode 6: Full system (DVI mode 720*400@70Hz) With Adapter#8
Test Mode 7: Full system (VGA mode 1920*1080@60Hz)With Adapter#5
Test Mode 8: Full system (VGA mode 1024*768@75Hz) With Adapter#5
Test Mode 9: Full system (VGA mode 720*400@70Hz) With Adapter#5
Test Mode 10: Full system (DVI mode 1920*1080@60Hz)With Adapter#5
Test Mode 11: Full system (DVI mode 1024*768@75Hz) With Adapter#5
Test Mode 12: Full system (DVI mode 720*400@70Hz) With Adapter#5
Test Mode 13: Full system (VGA mode 1920*1080@60Hz)With Adapter#6
Test Mode 14: Full system (VGA mode 1024*768@75Hz) With Adapter#6
Test Mode 15: Full system (VGA mode 720*400@70Hz) With Adapter#6
Test Mode 16: Full system (DVI mode 1920*1080@60Hz)With Adapter#6
Test Mode 17: Full system (DVI mode 1024*768@75Hz) With Adapter#6
Test Mode 18: Full system (DVI mode 720*400@70Hz) With Adapter#6
Test Mode 19: Full system (VGA mode 1920*1080@60Hz)With Adapter#7
Test Mode 20: Full system (VGA mode 1024*768@75Hz) With Adapter#7
Test Mode 21: Full system (VGA mode 720*400@70Hz) With Adapter#7
Test Mode 22: Full system (DVI mode 1920*1080@60Hz)With Adapter#7
Test Mode 23: Full system (DVI mode 1024*768@75Hz) With Adapter#7
Test Mode 24: Full system (DVI mode 720*400@70Hz) With Adapter#7
Test Mode 25: Full system (VGA mode 1920*1080@60Hz)With Adapter#9
Test Mode 26: Full system (VGA mode 1024*768@75Hz) With Adapter#9
Test Mode 27: Full system (VGA mode 720*400@70Hz) With Adapter#9
Test Mode 28: Full system (DVI mode 1920*1080@60Hz)With Adapter#9
Test Mode 29: Full system (DVI mode 1024*768@75Hz) With Adapter#9
Test Mode 30: Full system (DVI mode 720*400@70Hz) With Adapter#9
Test Mode 31: Full system (VGA mode 1920*1080@60Hz)With Adapter#10
Test Mode 32: Full system (VGA mode 1024*768@75Hz) With Adapter#10
Test Mode 33: Full system (VGA mode 720*400@70Hz) With Adapter#10
Test Mode 34: Full system (DVI mode 1920*1080@60Hz)With Adapter#10
Test Mode 35: Full system (DVI mode 1024*768@75Hz) With Adapter#10
Test Mode 36: Full system (DVI mode 720*400@70Hz) With Adapter#10

Select the worst case of the pre-test modes as the final test mode

Test Mode 1: Full system (VGA mode 1920*1080@60Hz)With Adapter#8

**2.4. Description of Support Unit**

No.	Device	Manufacturer	Model No.	Description
1	PC	Dell	Vostro200	Graphic: ASUS EAH6570
2	USB Keyboard	DELL	SK-8115	N/A
3	USB Mouse	DELL	G0K02XYK	N/A
4	USB Printer	HP	VCVRA-1001	N/A

No.	Cable	Quantity	Description
A	VGA Cable	1	Shielded, 1.5m
B	DVI Cable	1	Shielded, 1.5m,
C	USB Cable	1	Shielded, 1.8m, with one ferrite core bonded
D	USB Cable	1	Shielded, 1.5m
E	USB Cable	1	Shielded, 1.5m, with one ferrite core bonded



2.5. General Information of Test

Test Site:	CerpPASS Technology Corp.
Performand Location :	No.66,Tangzhuang Road, Suzhou Industrial Park, Jiangsu 215006, China
NVLAP LAB Code :	200814-0
FCC Registration Number :	916572, 331395
IC Registration Number :	7290A-1, 7290A-2
VCCI Registration Number :	T-1945 for Telecommunication Test C-2919 for Conducted emission test R-2670 for Radiated emission test below 1GHz G-227 for Radiated emission test above 1GHz
Frequency Range Investigated :	Conducted Emission Test: from 150kHz to 30 MHz Radiated Emission Test: from 30 MHz to 1,000 MHz Radiated Emission Test: from 1GHz to 18GHz
Test Distance :	The test distance of radiated emission below 1GHz from antenna to EUT is 3 M. The test distance of radiated emission above 1GHz from antenna to EUT is 3 M.

LABORATORY ACCREDITATION



2.6. Measurement Uncertainty

Conducted Emission		
The measurement uncertainty is evaluated as ± 2.71 dB.		
Radiated Emission		
(30MHz -1000MHz)	Horizontal	The measurement uncertainty is evaluated as ± 3.59 dB.
	Vertical	The measurement uncertainty is evaluated as ± 3.89 dB
(1G-18GHz)	Horizontal	The measurement uncertainty is evaluated as ± 2.31 dB.
	Vertical	The measurement uncertainty is evaluated as ± 2.15 dB.



3. Test of Conducted Emission

3.1. Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz on the 120 VAC power and return leads of the EUT according to the methods defined in ANSI C63.4-2003 Section 3.1. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane as shown in section 2.2. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.


Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50

3.2. Test Procedures

- The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- Connect EUT to the power mains through a line impedance stabilization network (LISN).
- All the support units are connecting to the other LISN.
- The LISN provides 50 ohm coupling impedance for the measuring instrument.
- The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
- Both sides of AC line were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched.
- Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.



3.3. Typical test Setup




3.4. Measurement equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date.
Test Receiver	R&S	ESCI	100565	2012.03.12	2013.03.11
AMN	R&S	ESH2-Z5	100182	2012.03.12	2013.03.11
Two-Line V-Network	R&S	ENV216	100325	2012.03.12	2013.03.11
ISN	FCC	FCC-TLISN-T2-02	20379	2011.12.09	2012.12.08
ISN	FCC	FCC-TLISN-T4-02	20380	2011.12.09	2012.12.08
ISN	FCC	FCC-TLISN-T8-02	20381	2011.12.09	2012.12.08
ISN	TESEQ	ISN ST08	30175	2012.09.13	2013.09.12
Current Probe	R&S	EZ-17	100303	2012.03.12	2013.03.11
Passive Voltage Probe	R&S	ESH2-Z3	100026	2012.03.12	2013.03.11
Attenuator	R&S	ESH3-Z2	100529	2012.03.12	2013.03.11
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-004	2012.03.12	2013.03.11



3.5. Test Result and Data

Test Mode :	Test Mode 1: Full system (VGA mode 1920*1080@60Hz)With Adapter#8		
AC Power :	AC 120V/60Hz	Phase :	LINE
Temperature :	22°C	Humidity :	50%
Pressure(mbar) :	1002	Date:	2012/09/21




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.3379	9.87	33.07	42.94	59.25	-16.31	QP
2	0.3379	9.87	32.43	42.30	49.25	-6.95	AVG
3	0.6740	9.85	30.90	40.75	56.00	-15.25	QP
4	0.6740	9.85	26.02	35.87	46.00	-10.13	AVG
5	1.2500	9.74	31.02	40.76	56.00	-15.24	QP
6	1.2500	9.74	15.41	25.15	46.00	-20.85	AVG
7	2.6940	9.71	41.03	50.74	56.00	-5.26	QP
8	2.6940	9.71	28.74	38.45	46.00	-7.55	AVG
9	4.3300	9.71	40.81	50.52	56.00	-5.48	QP
10	4.3300	9.71	28.47	38.18	46.00	-7.82	AVG
11	4.9220	9.72	39.25	48.97	56.00	-7.03	QP
12	4.9220	9.72	28.14	37.86	46.00	-8.14	AVG

Note: Measurement Level = Reading Level + Correct Factor



Test Mode :	Test Mode 1: Full system (VGA mode 1920*1080@60Hz)With Adapter#8		
AC Power :	AC 120V/60Hz	Phase :	NEUTRAL
Temperature :	22°C	Humidity :	50%
Pressure(mbar) :	1002	Date:	2012/09/21



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.6740	9.50	31.09	40.59	56.00	-15.41	QP
2	0.6740	9.50	25.79	35.29	46.00	-10.71	AVG
3	2.0620	9.51	33.82	43.33	56.00	-12.67	QP
4	2.0620	9.51	20.27	29.78	46.00	-16.22	AVG
5	2.7340	9.54	41.88	51.42	56.00	-4.58	QP
6	2.7340	9.54	28.83	38.37	46.00	-7.63	AVG
7	4.0140	9.59	41.46	51.05	56.00	-4.95	QP
8	4.0140	9.59	29.20	38.79	46.00	-7.21	AVG
9	4.2820	9.61	41.04	50.65	56.00	-5.35	QP
10	4.2820	9.61	28.52	38.13	46.00	-7.87	AVG
11	4.9060	9.65	39.97	49.62	56.00	-6.38	QP
12	4.9060	9.65	29.55	39.20	46.00	-6.80	AVG

Note: Measurement Level = Reading Level + Correct Factor

Test engineer: Seben



4. Test of Radiated Emission

4.1. Test Limit

Radiated emissions from 30 MHz to 1,000 MHz were measured with a bandwidth of 120 kHz according to the methods defines in ANSI C63.4-2003. The EUT was placed on a nonmetallic stand in the open-field site, 0.8 meter above the ground plane, as shown in section 3.2. The interface cables and equipment positions were varied within limits of reasonable applications to determine the positions producing maximum radiated emissions.

For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency (MHz)	Distance (m)	Level (dBuV/m)	Level (dBuV/m)
30 - 88	3	40(QP)	N/A
88 - 216	3	43(QP)	N/A
216-960	3	46(QP)	N/A
960-1000	3	54(QP)	N/A
1000-18000	3	74(PK)	54(AV)

For unintentional device, according to CISPR PUB.22, for Class B digital devices, the general requirement of field strength of radiated emissions from intentional radiators at a distance of 10 meters shall not exceed the below table.

Frequency (MHz)	Distance Meters	Radiated (dB μ V/ M)
30-230	10	30
230-1000	10	37





4.2. Test Procedures

- a. The EUT was placed on a Rota table top 0.8 meter above ground.
- b. The EUT and its simulators are placed on the ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
- c. The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.
- d. Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated on radiated measurement.
- e. Radiated emissions were investigated over the frequency range from 30MHz to 1GHz using a receiver bandwidth of 120KHz and the frequency range from 1GHz to 18GHz using a receiver bandwidth of 1MHz.

4.3. Typical test Setup

Below 1GHz Test Setup




**Above 1GHz Test Setup****4.4. Measurement equipment**

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date.
EMI Test Receiver	R&S	ESCI	100563	2012.03.12	2013.03.11
H64 Preamplifier	HP	8447F	3113A05582	2012.03.12	2013.03.12
Preamplifier	Agilent	8449B	3008A02342	2012.03.12	2013.03.11
Ultra Broadband Antenna	R&S	HL562	100362	2012.05.03	2013.05.02
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	9120D-619	2012.05.03	2013.05.02
Broad-Band Horn Antenna	Schwarzbeck	BBHA9170	9170-347	2012.05.15	2013.05.15
Spectrum Analyzer	R&S	FSP40	100324	2012.03.12	2013.03.12
Temperature/ Humidity Meter	Zhicheng	ZC1-11	CEP-TH-002	2012.03.12	2013.03.11



4.5. Test Result and Data (30MHz ~ 1000MHz)

Test Mode :	Test Mode 1: Full system (VGA mode 1920*1080@60Hz)With Adapter#8		
AC Power :	AC 120V/60Hz	Ant. Polarization:	Horizontal
Temp :	23°C	Humidity :	52%
Pressure(mbar) :	1002	Date :	2012/09/21




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	118.2699	-13.72	41.91	28.19	43.50	-15.31	QP	200	23
2	136.6999	-14.77	44.79	30.02	43.50	-13.48	QP	200	310
3	208.4798	-14.89	50.18	35.29	43.50	-8.21	QP	100	279
4	278.3199	-11.69	45.87	34.18	46.00	-11.82	QP	100	99
5	343.3100	-9.42	42.94	33.52	46.00	-12.48	QP	105	0
6	933.0700	3.47	28.87	32.34	46.00	-13.66	QP	100	159

Note: Measurement Level = Reading Level + Correct Factor



Test Mode :	Test Mode 1: Full system (VGA mode 1920*1080@60Hz)With Adapter#8		
AC Power :	AC 120V/60Hz	Ant. Polarization:	Vertical
Temp :	23°C	Humidity :	52%
Pressure(mbar) :	1002	Date :	2012/09/21




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	119.2400	-13.68	45.94	32.26	43.50	-11.24	QP	100	335
2	136.7000	-14.77	51.36	36.59	43.50	-6.91	QP	100	285
3	208.4800	-14.89	50.17	35.28	43.50	-8.22	QP	196	0
4	274.4400	-11.83	48.72	36.89	46.00	-9.11	QP	200	194
5	343.3100	-9.42	44.64	35.22	46.00	-10.78	QP	154	0
6	845.7700	1.97	34.18	36.15	46.00	-9.85	QP	100	175

Note: Measurement Level = Reading Level + Correct Factor



4.6. Test Result and Data (1000MHz ~ 18000MHz)

Test Mode :	Test Mode 1: Full system (VGA mode 1920*1080@60Hz)With Adapter#8		
AC Power :	AC 120V/60Hz	Ant. Polarization:	Horizontal
Temp :	23℃	Humidity :	52%
Pressure(mbar) :	1002	Date :	2012/09/21




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	1085.000	-6.52	57.27	50.75	74.00	-23.25	peak	100	360
2	1085.000	-6.52	35.02	28.50	54.00	-25.50	AVG	100	360
3	1238.000	-5.88	50.65	44.77	74.00	-29.23	peak	200	83
4	1238.000	-5.88	39.05	33.17	54.00	-20.83	AVG	200	83
5	1595.000	-4.39	50.06	45.67	74.00	-28.33	peak	100	247
6	1595.000	-4.39	38.45	34.06	54.00	-19.94	AVG	100	247
7	2071.000	-2.46	49.73	47.27	74.00	-26.73	peak	100	13
8	2071.000	-2.46	36.29	33.83	54.00	-20.17	AVG	100	13
9	2394.000	-1.38	45.80	44.42	74.00	-29.58	peak	200	319
10	2394.000	-1.38	33.10	31.72	54.00	-22.28	AVG	200	319
11	2785.000	-0.07	44.67	44.60	74.00	-29.40	peak	100	148
12	2785.000	-0.07	30.56	30.49	54.00	-23.51	AVG	100	148

Note: Measurement Level = Reading Level + Correct Factor



Test Mode :	Test Mode 1: Full system (VGA mode 1920*1080@60Hz)With Adapter#8		
AC Power :	AC 120V/60Hz	Ant. Polarization:	Vertical
Temp :	23°C	Humidity :	52%
Pressure(mbar) :	1002	Date :	2012/09/21



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	1102.000	-6.44	58.57	52.13	74.00	-21.87	peak	100	27
2	1102.000	-6.44	41.03	34.59	54.00	-19.41	AVG	100	27
3	1170.000	-6.16	53.71	47.55	74.00	-26.45	peak	100	356
4	1170.000	-6.16	39.43	33.27	54.00	-20.73	AVG	100	356
5	1595.000	-4.39	47.61	43.22	74.00	-30.78	peak	200	162
6	1595.000	-4.39	37.23	32.84	54.00	-21.16	AVG	200	162
7	1986.000	-2.76	45.06	42.30	74.00	-31.70	peak	100	304
8	1986.000	-2.76	33.38	30.62	54.00	-23.38	AVG	100	304
9	2428.000	-1.27	44.42	43.15	74.00	-30.85	peak	200	19
10	2428.000	-1.27	30.43	29.16	54.00	-24.84	AVG	200	19
11	5437.000	7.58	40.19	47.77	74.00	-26.23	peak	100	133
12	5437.000	7.58	29.84	37.42	54.00	-16.58	AVG	100	133

Note: Measurement Level = Reading Level + Correct Factor

Test engineer: Seben