




PCTEST ENGINEERING LABORATORY, INC.

6660-B Dobbin Road, Columbia, MD 21045 USA
Tel. 410.290.6652 / Fax 410.290.6554
<http://www.pctestlab.com>



RF EXPOSURE EVALUATION (MAXIMUM PERMISSIBLE EXPOSURE)

Applicant Name:

LG Electronics USA
1000 Sylvan Avenue
Englewood Cliffs, NJ 07632
United States

Date of Testing:

June 2 - 3, 2009

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Test Report Serial No.:

0906021138.BEJ

FCC ID: BEJM13

APPLICANT: LG Electronics USA

EUT Type: Cellular/PCS CDMA/EvDO and 700MHz LTE Device

FCC Rule Part(s): FCC Part 1 (§1.1310) and Part 2 (§2.1091)

FCC Classification: PCS Licensed Transmitter (PCB)

Test Procedure: OET Bulletin 65

The device bearing the FCC Identifier specified above has been shown to comply with the applicable technical standards as indicated in the measurement report and has been tested in accordance with the measurement procedures specified in FCC OET Bulletin 65 (See Test Report). These measurements were performed with no deviation from the standards. Test results reported herein relate only to the item(s) tested.

I authorize and attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.


Randy Ortanez
President



FCC ID: BEJM13		MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		Reviewed by: Quality Manager
Test Report S/N: 0906021138.BEJ	Test Dates: June 2 - 3, 2009	EUT Type: Cellular/PCS CDMA/EvDO and 700MHz LTE Device		Page 1 of 7

TABLE OF CONTENTS

1.0	RF EXPOSURE EVALUATION – MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	3
1.1	INTRODUCTION	3
1.2	EUT DESCRIPTION	3
1.3	MPE REQUIREMENTS OVERVIEW.....	4
1.4	PROCEDURE.....	5
1.5	SUMMARY OF RESULTS.....	6
2.0	CONCLUSION.....	7

FCC ID: BEJM13		MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		Reviewed by: Quality Manager
Test Report S/N: 0906021138.BEJ	Test Dates: June 2 - 3, 2009	EUT Type: Cellular/PCS CDMA/EvDO and 700MHz LTE Device		Page 2 of 7

1.0 RF EXPOSURE EVALUATION – MAXIMUM PERMISSIBLE EXPOSURE (MPE)

1.1 Introduction

This document is prepared on behalf of LG Electronics USA to show compliance with the RF Exposure requirements as required in §1.1310 of the FCC Rules and Regulations and RSS-102 of Industry Canada.

The limit for Maximum Permissible Exposure (MPE), specified in FCC §1.1310, is listed in Table 1-1. According to FCC §1.1310 and RSS-102: the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b).

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits For Occupational / Control Exposures (f = frequency)				
30-300	61.4	0.163	1.0	6
300-1500	...	...	f/300	6
1500-100,000	...	...	5.0	6
(B) Limits For General Population / Uncontrolled Exposure (f = frequency)				
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

Table 1-1. Limits for Maximum Permissible Exposure (MPE)

1.2 EUT Description

The LGE Cellular/PCS CDMA/EvDO and 700MHz LTE Device Model: M13 is a device containing CDMA and 700MHz LTE transmitters. For this MPE evaluation the device is set to transmit from the antenna of each transmitter and the RF exposure of each transmitter is evaluated individually.

EUT:

Model: M13

Grantee: LG Electronics USA

FCC ID: BEJM13

Tx Frequency Ranges: 776 – 788MHz (LTE)
824 – 849MHz (Cellular CDMA)
1850 – 1910MHz (PCS CDMA)

Maximum Radiated Powers: 23.01dBm ERP (LTE)
20.62dBm ERP (Cellular CDMA)
25.85dBm EIRP (PCS CDMA)

FCC ID: BEJM13		MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		Reviewed by: Quality Manager
Test Report S/N: 0906021138.BEJ	Test Dates: June 2 - 3, 2009	EUT Type: Cellular/PCS CDMA/EvDO and 700MHz LTE Device		Page 3 of 7

1.3 MPE Requirements Overview

Three different categories of transmitters are defined by the FCC in OET Bulletin 65. These categories are fixed installation, mobile, and portable and are defined as follows:

- **Fixed Installations:** fixed location means that the device, including its antenna, is physically secured at a permanent location and is not able to be easily moved to another location. Additionally, distance to humans from the antenna is maintained to at least 2 meters.
- **Mobile Devices:** a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to be generally used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structures and the body of the user or nearby persons. Transmitters designed to be used by consumers or workers that can be easily re-located, such as a wireless modem operating in a laptop computer, are considered mobile devices if they meet the 20 centimeter separation requirement. The FCC rules for evaluating mobile devices for RF compliance are found in 47 CFR §2.1091.
- **Portable Devices:** a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user. Portable device requirements are found in Section 2.1093 of the FCC's Rules (47 CFR§2.1093).

The FCC also categorizes the use of the device as based upon the user's awareness and ability to exercise control over his or her exposure. The two categories defined are Occupational/ Controlled Exposure and General Population/Uncontrolled Exposure. These two categories are defined as follows:

- **Occupational/Controlled Exposure:** In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means. Awareness of the potential for RF exposure in a workplace or similar environment can be provided through specific training as part of a RF safety program. If appropriate, warning signs and labels can also be used to establish such awareness by providing prominent information on the risk of potential exposure and instructions on methods to minimize such exposure risks.
- **General Population/Uncontrolled Exposure:** The general population / uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

The LGE Cellular/PCS CDMA/EvDO and 700MHz LTE Device FCC ID: BEJM13 is evaluated to the Mobile Device requirements and is considered a device to be used by the General Population/Uncontrolled Exposure.

FCC ID: BEJM13		MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		Reviewed by: Quality Manager
Test Report S/N: 0906021138.BEJ	Test Dates: June 2 - 3, 2009	EUT Type: Cellular/PCS CDMA/EvDO and 700MHz LTE Device		Page 4 of 7

1.4 Procedure

The procedure used to determine the RF power density was based upon a calculation for determining compliance with the MPE requirements.

The power generated by each transmitter used in this product was initially measured by a base station simulator and the powers were recorded. Through use of the Friis transmission formula and the maximum measured EIRP, the power density level is calculated at a distance of 20cm. For the 835MHz and 700MHz LTE bands, the measured ERP was converted to its equivalent EIRP value by adding 2.15dB.

Friis Transmission Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4\pi r^2) = EIRP / (4\pi r^2)$

Where,

P_d = Power Density (mW/cm²)

EIRP = Equivalent Isotropic Radiated Power

P_{out} = output power to antenna (mW)

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator (cm)

Calculated MPE

The power density limit for General Population/Uncontrolled Exposure at each frequency is determined based on the information in Table 1-1.

There is no co-location between the electric fields of any two transmitters therefore following power densities are calculated for each individual transmitter by frequency at 20cm spacing:

Frequency	836.52 MHz	
Limit	0.558 mW/cm ²	
Distance (cm), R =	20 cm	
ERP (dBm), P =	20.62 dBm	115.35 mW
EIRP (dBm), P =	22.77 dBm	189.23 mW
Power Density (S) =	0.038 mW/cm ² (at 20cm)	
Minimum Distance =	5.2 cm	

Table 1-2. Calculated MPE Data for Cellular Band

Frequency	782 MHz	
Limit	0.521 mW/cm ²	
Distance (cm), R =	20 cm	
ERP (dBm), P =	23.01 dBm	199.99 mW
EIRP (dBm), P =	25.16 dBm	328.10 mW
Power Density (S) =	0.065 mW/cm ² (at 20cm)	
Minimum Distance =	7.1 cm	

Table 1-3. Calculated MPE Data for 700MHz LTE Band

FCC ID: BEJM13		MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		Reviewed by: Quality Manager
Test Report S/N: 0906021138.BEJ	Test Dates: June 2 - 3, 2009	EUT Type: Cellular/PCS CDMA/EvDO and 700MHz LTE Device	Page 5 of 7	

Frequency:	1880 MHz	
Limit:	1.000 mW/cm ²	
Distance (cm), R =	20 cm	
EIRP (dBm), P =	25.85 dBm	384.59 mW
Power Density (S) =	0.0765 mW/cm ²	(at 20cm)
Minimum Distance =	5.5 cm	

Table 1-4. Calculated MPE Data for PCS Band

1.5 Summary of Results

Frequency Band [MHz]	Maximum Measured EIRP [dBm]	MPE @ 20cm (mW/cm ²)	Test Result
824 – 849	22.77	0.038	PASS
776 – 788	25.16	0.065	PASS
1850 – 1910	25.85	0.0765	PASS

Table 1-5. Maximum Permissible Exposure Summary Table

FCC ID: BEJM13		MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		Reviewed by: Quality Manager
Test Report S/N: 0906021138.BEJ	Test Dates: June 2 - 3, 2009	EUT Type: Cellular/PCS CDMA/EvDO and 700MHz LTE Device		Page 6 of 7

2.0 CONCLUSION

The device meets the mobile RF exposure limit at a 20cm separation distance as specified in §2.1091 of the FCC Rules and Regulations and Health Canada Safety Code 6. An appropriate RF exposure compliance statement will be placed in the user's manual.

FCC ID: BEJM13	 PCTEST ENGINEERING LABORATORY, INC.	MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT	 LG	Reviewed by: Quality Manager
Test Report S/N: 0906021138.BEJ	Test Dates: June 2 - 3, 2009	EUT Type: Cellular/PCS CDMA/EvDO and 700MHz LTE Device		Page 7 of 7