

Standalone SAR test exclusion considerations

March 5, 2013

- Min. transmitting frequency = **2441** MHz
- Min. test separation distance = **5** mm
- Max. power with turn-up tolerance = **6.00** dBm = **4** mW
 Typical Power: **5.00** dBm ± **1.00** dB
 Measured Power: **4.97** dBm

Step 1) SAR test exclusion thresholds for 100MHz to 6GHz at test separationn distances ≤ 50 mm = **Used**

$$\begin{aligned}
 & [(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \\
 & = [4.00 / 5] \cdot [\sqrt{2.441}] \\
 & = \mathbf{1.25} \leq 3, \text{ for } 1\text{g SAR}
 \end{aligned}$$

[Thus SAR for this device is not required.](#)

Step 2-1) SAR test exclusion thresholds for 100MHz to 1500MHz at test separationn distances > 50 mm = **N/A**

$$[\text{Threshold at 50 mm in step 1}) + (\text{test separation distance} - 50 \text{ mm}) \cdot (f(\text{MHz})/150)] \text{ mW}$$

Step 2-2) SAR test exclusion thresholds for 1500MHz to 6GHz at test separationn distances > 50 mm = **N/A**

$$[\text{Threshold at 50 mm in step 1}) + (\text{test separation distance} - 50 \text{ mm}) \cdot 10] \text{ mW}$$