

TEST REPORT

of

FCC CFR 47 part 1, 1.1307(b), 1.1310

FCC ID: BEJTM05GTJN

Equipment Under Test : Car Telematics Device
Model Name : TA4HEB-N
Applicant : LG Electronics USA
Manufacturer : LG Electronics USA
Date of Receipt : 2018.08.01
Date of Test(s) : 2018.08.02 ~ 2019.03.22
Date of Issue : 2019.03.28

In the configuration tested, the EUT complied with the standards specified above.

Tested By:



Nancy Park

Date:

2019.03.28

Technical
Manager:



Hyunhae Youn

Date:

2019.03.28

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

INDEX

<u>Table of Contents</u>	Page
1. General Information -----	3
2. RF Exposure Evaluation -----	5

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

1. General Information

1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- Designation number: KR0150

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>.

Telephone : +82 31 688 0901

FAX : +82 31 688 0921

1.2. Details of Applicant

Applicant : LG Electronics USA

Address : 1000 Sylvan Avenue, Englewood Cliffs, New Jersey, United States, 07632

Contact Person : Han, Kyung-su

Phone No. : +2 201 472 2623

1.3. Details of Manufacturer

Company : LG Electronics Inc.

Address : 10, Magokjungang 10-ro, Gangseo-gu, Seoul, Korea, 07796

1.4. Description of EUT

Kind of Product	Car Telematics Device
Model Name	TA4HEB-N
Power Supply	DC 12 V
Frequency Range	GSM 850: 824 MHz ~ 849 MHz GSM 1 900: 1 850 MHz ~ 1 910 MHz WCDMA 2: 1 850 MHz ~ 1 910 MHz WCDMA 4: 1 710 MHz ~ 1 755 MHz WCDMA 5: 824 MHz ~ 849 MHz LTE Band 2: 1 850 MHz ~ 1 910 MHz LTE Band 4: 1 710 MHz ~ 1 755 MHz LTE Band 5: 824 MHz ~ 849 MHz LTE Band 7: 2 500 MHz ~ 2 570 MHz LTE Band 12: 699 MHz ~ 716 MHz LTE Band 26: 814 MHz ~ 849 MHz WLAN 2.4G (11b/g/n_HT20, HT40): 2 412 MHz ~ 2 462 MHz WLAN 5G Band 1 (11a/n_HT20, 11ac_VHT20): 5 180 MHz ~ 5 240 MHz WLAN 5G Band 1 (11n_HT40, 11ac_VHT40): 5 190 MHz ~ 5 230 MHz WLAN 5G Band 1 (11ac_VHT80): 5 210 MHz WLAN 5G Band 3 (11a/n_HT20, 11ac_VHT20): 5 745 MHz ~ 5 825 MHz WLAN 5G Band 3 (11n_HT40, 11ac_VHT40): 5 755 MHz ~ 5 795 MHz WLAN 5G Band 3 (11ac_VHT80): 5 775 MHz

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

1.5. Test report revision

Revision	Report number	Date of Issue	Description
0	F690501/RF-RTL013641	2019.03.28	Initial

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2017.07.10)(0)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

2. RF Exposure Evaluation

2.1. Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(b), 1.1310

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength(V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1 500	-	-	f/300	6
1 500-100 000	-	-	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
<u>300-1 500</u>	-	-	<u>f/1500</u>	<u>30</u>
<u>1 500-100 000</u>	-	-	<u>1.0</u>	<u>30</u>

2.1.1. Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2017.07.10)(0)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

2.1.2. Test Result of RF Exposure Evaluation

Test Item : RF Exposure Evaluation Data

Test Mode : Normal Operation

2.1.3. Test information of Cable Loss and Antenna Gain

Test Item	Frequency Range (MHz)	Cable Loss (dB)	Antenna Gain of EUT (dB i)	Final Antenna Gain (dB i)
GSM 850	824 ~ 849	-1.12	-2.45	-3.57
GSM 1900	1 850 ~ 1 910	-1.12	1.13	0.01
WCDMA 2	1 850 ~ 1 910	-1.12	1.13	0.01
WCDMA 4	1 710 ~ 1 755	-1.12	1.45	0.33
WCDMA 5	824 ~ 849	-1.12	-2.45	-3.57
LTE 2	1 850 ~ 1 910	-1.12	1.13	0.01
LTE 4	1 710 ~ 1 755	-1.12	1.45	0.33
LTE 5	824 ~ 849	-1.12	-2.45	-3.57
LTE 7	2 500 ~ 2 570	-1.94	-1.67	-3.61
LTE 12	699 ~ 716	-0.76	-1.85	-2.61
LTE 26	814 ~ 824	-1.12	-3.18	-4.30
LTE 26	824 ~ 849	-1.12	-2.45	-3.57

Note;

-Final Antenna Gain = Cable Loss(dB) + Antenna Gain of EUT(dB i)

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2017.07.10)(0)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

2.1.4. Output Power into Antenna & RF Exposure Evaluation Distance

WLAN (2.4G)

- Maximum tune up tolerance

Frequency (MHz)	Output Average Power to Antenna (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
2 412 ~ 2 462	18.5	2.55	0.025 336	1

WLAN (5G)

- Maximum tune up tolerance

Frequency (MHz)	Output Average Power to Antenna (dB m)	Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
5 180 ~ 5 240	11.0	3.96	0.006 233	1
5 745 ~ 5 825	11.0	6.31	0.010 709	1

GSM 850

- Maximum tune up tolerance

Frequency Range (MHz)	Output Average Power to Antenna (dB m)	Final Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
824 ~ 849	33.5	-3.57	0.195 763	0.55

GSM 1 900

- Maximum tune up tolerance

Frequency Range (MHz)	Output Average Power to Antenna (dB m)	Final Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
1 850 ~ 1 910	30.5	0.01	0.223 733	1

WCDMA Band 2

- Maximum tune up tolerance

Frequency Range (MHz)	Output Average Power to Antenna (dB m)	Final Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
1 850 ~ 1 910	25.0	0.01	0.063 057	1

WCDMA Band 4

- Maximum tune up tolerance

Frequency Range (MHz)	Output Average Power to Antenna (dB m)	Final Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
1 710 ~ 1 755	25.0	0.33	0.067 878	1

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

WCDMA Band 5
- Maximum tune up tolerance

Frequency Range (MHz)	Output Average Power to Antenna (dB m)	Final Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
824 ~ 849	25.5	-3.57	0.031 026	0.55

LTE - Band 2
- Maximum tune up tolerance

Frequency Range (MHz)	Output Average Power to Antenna (dB m)	Final Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
1 850 ~ 1 910	25.5	0.01	0.070 751	1

LTE - Band 4
- Maximum tune up tolerance

Frequency Range (MHz)	Output Average Power to Antenna (dB m)	Final Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
1 710 ~ 1 755	25.5	0.33	0.076 161	1

LTE - Band 5
- Maximum tune up tolerance

Frequency Range (MHz)	Output Average Power to Antenna (dB m)	Final Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
824 ~ 849	25.5	-3.57	0.031 026	0.55

LTE - Band 7
- Maximum tune up tolerance

Frequency Range (MHz)	Output Average Power to Antenna (dB m)	Final Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
2 500 ~ 2 570	25.5	-3.61	0.030 742	1

LTE - Band 12
- Maximum tune up tolerance

Frequency Range (MHz)	Output Average Power to Antenna (dB m)	Final Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
699 ~ 716	25.5	-2.61	0.038 702	0.47

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

LTE - Band 26**- Maximum tune up tolerance**

Frequency Range (MHz)	Output Average Power to Antenna (dB m)	Final Antenna Gain (dB i)	Power Density at 20 cm (mW/cm ²)	Limits (mW/cm ²)
814 ~ 824	25.5	-4.30	0.026 226	0.54
824 ~ 849	25.5	-3.57	0.031 026	0.55

Note;

- The power density Pd (5th column) at a distance of 20 cm calculated from the friis transmission formula is far below the limit of 1 mW/cm².
- This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment.
- This equipment should be installed and operated with minimum 20 cm between the radiator and your body.
- The antenna gain of this transmitter is less than 6 dBi and must not be collocated or operating in conjunction with any other antenna or transmitter unless authorized to do so by the FCC.

Simultaneous transmission of MPE test exclusion for worst case configuration.

WLAN: the ratio is 0.025 336 / 1

WWAN: the ratio is 0.195 763 / 0.55

Confirm the sum result of individual MPEs ratio is ≤ 1.0 ;

WLAN + WWAN: $(0.025\ 336 / 1) + (0.195\ 763 / 0.55)$

= 0.381 269 ≤ 1.0

So this device meets the KDB447498 D01 v06 section 7.2 requirement of "Simultaneous transmission MPE test exclusion"

- End of the Test Report -

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2017.07.10)(0)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)