

Application for FCC Certificate
On Behalf of
LG Electronics U.S.A Inc.

LCD Monitor

Model No.: W2242TT, W2242ST

Serial No.: E07102401, E07102402

FCC ID : BEJW2242TT

Prepared For : LG Electronics U.S.A., Inc.
1000 Sylvan Avenue, Englewood Cliffs,
NJ 07632

Prepared By : Audix Technology (Shanghai) Co., Ltd.
3F 34Bldg 680 Guiping Rd,
Caohejing Hi-Tech Park,
Shanghai, China 200233

Tel: +86-21-64955500
Fax: +86-21-64955491

Report No. : ACI-F07045
Date of Test : Oct 25 – 29, 2007
Date of Report : Oct 31, 2007

TABLE OF CONTENTS

	Page
1 SUMMARY OF STANDARDS AND RESULTS	4
1.1 Description of Standards and Results.....	4
2 GENERAL INFORMATION	5
2.1 Description of Equipment Under Test.....	5
2.2 Supported Simulators	6
2.3 Description of Test Facility	7
2.4 Measurement Uncertainty	7
3 CONDUCTED EMISSION TEST	8
3.1 Test Equipment.....	8
3.2 Block Diagram of Test Setup	8
3.3 Conducted Emission Limit [FCC Part 15 Subpart B 15.107(a)].....	9
3.4 Test Configuration.....	9
3.5 Operating Condition of EUT	10
3.6 Test Procedures	11
3.7 Test Results	11
4 RADIATED EMISSION TEST	21
4.1 Test Equipment.....	21
4.2 Block Diagram of Test Setup	21
4.3 Radiated Emission Limit [FCC Part 15 Subpart B 15.109(a)].....	22
4.4 Test Configuration.....	22
4.5 Operating Condition of EUT	22
4.6 Test Procedures	23
4.7 Test Results	24
5 DEVIATION TO TEST SPECIFICATIONS	37
6 DEBUG DESCRIPTION	38

TEST REPORT FOR FCC CERTIFICATE

Applicant : LG Electronics U.S.A., Inc.
Manufacturer : LG Electronics Nanjing Display Co., Ltd..
EUT Description : LCD Monitor
(A) Model No. : W2242TT, W2242ST
(B) Serial No. : E07102401, E07102402
(C) Power Supply : 120V/60Hz

Test Procedure Used:

*FCC RULES AND REGULATIONS PART 15 SUBPART B CLASS B 2007.05
AND ANSI C63.4-2003*

The device described above is tested by Audix Technology (Shanghai) Co., Ltd. to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart B (Class B) and ICES-003, Issue 4 February 2004 (CISPR 22:2002) limits both radiated and conducted emissions.

The test results are contained in this test report and Audix Technology (Shanghai) Co., Ltd. is assumed full responsibility for the accuracy and completeness of these measurements. This report shows that the EUT (M/N: W2242TT, W2242ST; S/N: E07102401, E07102402) which was tested in 3m anechoic chamber on Oct 25 – 29, 2007 is technically compliance with the FCC official limits also.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of Audix Technology (Shanghai) Co., Ltd.

This report contains data that are not covered by the NVLAP accreditation.

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

Date of Test : Oct 25 – 29, 2007

Prepared By:

Kathy Wong 2007.11.06
KATHY WANG / Assistant

Reviewer:

Sammy Chen 2007.11.06
SAMMY CHEN / Deputy Assistant Manager

AUDIX® For and on behalf of
Audix Technology (Shanghai) Co., Ltd.

Approved Signatory:

Alan Chien 2007.11.06
Authorized Signature EMCIAN CHIEN / Assistant Manager

1 SUMMARY OF STANDARDS AND RESULTS

1.1 Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Description / Test Item	Test Standard	Results	Meets Limit
EMISSION			
Conducted Disturbance At main terminal	FCC RULES AND REGULATIONS PART 15 SUBPART B 2007.05 AND ANSI C63.4-2003	Pass	15.107(a) Class B
Radiated Disturbance	FCC RULES AND REGULATIONS PART 15 SUBPART B 2007.05 AND ANSI C63.4-2003	Pass	15.109(a) Class B

2 GENERAL INFORMATION

2.1 Description of Equipment Under Test

Description : LCD Monitor

Type of EUT : ☒ Production ☐ Pre-product ☐ Pro-type

Model No. : W2242TT, W2242ST

Serial No. : E07102401, E07102402

Note : The difference between the above two models are as follows:

	W2242TT	W2242ST
D-Sub Port	○	○
DVI Port	○	--
NOTE 1 – “○” means the item is applicable. NOTE 2 – “--” means the item is no applicable.		

Real Power : W2242TT: 36.5W
W2242ST: 35.7W

Applicant : LG Electronics U.S.A Inc.
1000 Sylvan Avenue, Englewood Cliffs,
NJ 07632

Manufacturer : LG Electronics Nanjing Display Co., Ltd.
No.346, Yao Xin Road, Economic&Technical
Development Zone, Nanjing, China

LCD Panel : Manufacturer: LG. PHILIPS LCD
M/N : LM220WE1 (TL) (D1)

D-Sub Cable : Shielded, Detachable, 1.85m, with two cores

DVI Cable : Shielded, Detachable, 1.90m, with two cores

Remark:

The EUT is a LCD Monitor which input/output ports as follows:

- (1) One D-Sub Input Port :Connected with PC
- (2) One DVI Input Port :Connected with PC
- (3) AC In Port :Connected with Power

2.2 Supported Simulators

2.2.1 PC

Manufacturer : HP
Model Number : dx6120MT
Serial Number : CNG53004J2
Power Cable : Unshielded, Detachable ,1.8m
Certificate : FCC DoC; CE/EMC; VCCI; C-Tick; UL
BSMI (R33001) 3C (A000111)
MIC (E-A011-04-2659(B))

2.2.2 Keyboard

Manufacturer : Microsoft
Model Number : RT2300
Serial Number : 7668200662248
Data Cable : Unshielded, Detachable ,1.8m
Certificate : CE/EMC, FCC DoC, VCCI, MIC, C-Tick,
BSMI

2.2.3 Mouse

Manufacturer : Microsoft
Model Number : RT2300
Serial Number : 6965712071551
Data Cable : Unshielded ,Undetachable, 1.85m.
Certificate : FCC DoC, VCCI, CE/EMC, MIC, GS

2.2.4 Printer

Manufacturer : HP
Model Number : C3990A
Serial Number : JPZX020487
Data Cable : Unshielded, Detachable, 1.5m
Certificate : GS, CE/EMC, C-Tick, FCC DoC

2.2.5 Modem

Manufacturer : Aceex
Model Number : 1414
Serial Number : 980013576
Data Cable : Unshielded, Detachable, 1.8m
Certificate : FCC ID: IFAXDM1414

2.3 Description of Test Facility

Site Description (Semi-Anechoic Chamber) : Sept. 17, 1998 file on
July 26, 2006 Renewed
Federal Communications Commission
FCC Engineering Laboratory
7435 Oakland Mills Road
Columbia, MD 21046, USA

Name of Firm : Audix Technology (Shanghai) Co., Ltd.

Site Location : 3F 34Bldg 680 Guiping Rd,
Caohejing Hi-Tech Park,
Shanghai, China 200233

NVLAP Lab Code : 200371-0

2.4 Measurement Uncertainty

Conducted Emission Expanded Uncertainty: U = 1.84 dB
Radiated Emission Expanded Uncertainty : U = 2.96 dB

3 CONDUCTED EMISSION TEST


3.1 Test Equipment

The following test equipment are used during the conducted emission test in a shielded room:

Item	Type	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1.	Test Receiver	R&S	ESHS10	830223/007	Apr 08, 2007	Apr 08, 2008
2.	Line Impedance Stabilization Network (LISN)	Kyoritsu	KNW-407	8-1280-5	Apr 06, 2007	Apr 06, 2008
3.	AMN	R&S	ESH2-Z5	843890/011	Apr 06, 2007	Apr 06, 2008
4.	50 Ω Coaxial Switch	Anritsu	MP59B	6200426389	Sep 18, 2007	Mar 18, 2008
5.	Software	Audix	E3	SET00200 9804M592	--	--


3.2 Block Diagram of Test Setup

3.2.1 EUT & Supported Simulators



■ : Ferrite core

3.2.2 Conducted Disturbance Test Setup



3.3 Conducted Emission Limit [FCC Part 15 Subpart B 15.107(a)]

Frequency Range (MHz)	Limits dB (μV)	
	Quasi-peak	Average
0.15 ~ 0.5	66~56	56~46
0.5 ~ 5	56	46
5 ~ 30	60	50

NOTE 1 – The lower limit shall apply at the transition frequencies.
 NOTE 2 – The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz~0.50 MHz
 NOTE 3 – If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with the average detector is unnecessary.

3.4 Test Configuration

The EUT (listed in Sec.2.1) and the simulators (listed in Sec 2.2) were installed as shown on Sec.3.2 to meet FCC requirement and operating in a manner that tends to maximize its emission level in a normal application.

3.5 Operating Condition of EUT

- 3.5.1 Setup the EUT and simulators as shown in Sec. 3.2.
- 3.5.2 Turn on the power of all equipment and the EUT.
- 3.5.3 Set the contrast control to maximum.
- 3.5.4 Set the brightness control to maximum or at raster extinction if raster extinction occurs at less than maximum brightness.
- 3.5.5 For color monitors, use white letters on a black background to represent all color.
- 3.5.6 Select the worse case of positive or negative video if both alternatives are available.
- 3.5.7 Set character size and number of characters per line so that typically the greatest number of characters per screen is displayed.
- 3.5.8 For monitors with graphics capabilities, a pattern consisting of all scrolling Hs should be displayed. For monitors with text only capability, a pattern consisting of random text shall be displayed. If neither of the above is applied, use a typical display.
- 3.5.9 Set the EUT on the test modes in turn, and then test it.
- 3.5.10 The test modes are as follows:

Model Number	Test Mode
W2242TT	VGA 640*480@60Hz
	VGA 1024*768@60Hz
	VGA 1680*1050@60Hz
	DVI 640*480@60Hz
	DVI 1024*768@60Hz
	DVI 1680*1050@60Hz
W2242ST	VGA 640*480@60Hz
	VGA 1024*768@60Hz
	VGA 1680*1050@60Hz

3.6 Test Procedures

The EUT was connected to the power mains through a Line Impedance Stabilization Network (LISN). This provided a 50 ohm coupling impedance for the measuring equipment.

Both sides of AC line (VA & VB) were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables were changed or manipulated according to ANSI C63.4:2003 during conducted emission test.

The bandwidth of R&S Test Receiver ESHS10 was set at 10 kHz.

The frequency range from 150 kHz to 30 MHz was checked.

The test modes were done on conducted disturbance test and all the test results are listed in Sec. 3.7.

3.7 Test Results

< **PASS** >

The frequency and amplitude of the highest conducted emission relative to the limit is reported. All emissions not reported below are too low against the prescribed limits.

Model Number	Test Mode	Data Page
W2242TT	VGA 640*480@60Hz	P12
	VGA 1024*768@60Hz	P13
	VGA 1680*1050@60Hz	P14
	DVI 640*480@60Hz	P15
	DVI 1024*768@60Hz	P16
	DVI 1680*1050@60Hz	P17
W2242ST	VGA 640*480@60Hz	P18
	VGA 1024*768@60Hz	P19
	VGA 1680*1050@60Hz	P20

NOTE 1 – Factor = Cable Loss + LISN Factor.

NOTE 2 – Emission Level = Meter Reading + Factor.

NOTE 3 – All reading are Quasi-Peak values and Average values.

NOTE 4 – The worst case is for VGA 640*480@60Hz mode (M/N: W2242ST).
The worst emission is detected at 0.657 MHz with corrected signal level of 39.10 (μV) (limit is 46.00 dB (μV)), when the VB (Average Value) of the EUT is connected to LISN.

EUT : LCD Monitor Temperature : 22°C

Model No. : W2242TT Humidity : 60%

Serial No. : E07102401 Date of Test : Oct 25, 2007

Test Mode : VGA 640*480@60Hz

Test Line	Frequency (MHz)	Meter Reading dB(μV)	Factor (dB)	Emission Level dB(μV)	Limits dB(μV)	Margin (dB)	Remark
VA	0.15	51.80	0.66	52.46	66.00	13.54	QP
	0.223	41.90	0.73	42.63	62.71	20.08	
	0.371	34.80	0.68	35.48	58.48	23.00	
	3.66	40.10	0.61	40.71	56.00	15.29	
	4.03	39.60	0.62	40.22	56.00	15.78	
	12.988	39.80	0.86	40.66	60.00	19.34	
	0.15	43.30	0.66	43.96	56.00	12.04	AV
	0.223	36.90	0.73	37.63	52.71	15.08	
	0.371	33.00	0.68	33.68	48.48	14.80	
	3.66	32.30	0.61	32.91	46.00	13.09	
	4.03	31.20	0.62	31.82	46.00	14.18	
	12.988	30.10	0.86	30.96	50.00	19.04	
VB	0.15	51.40	0.53	51.93	66.00	14.07	QP
	0.22	42.29	0.67	42.96	62.82	19.86	
	3.66	35.70	0.54	36.24	56.00	19.76	
	3.8	35.30	0.54	35.84	56.00	20.16	
	4.03	36.31	0.53	36.84	56.00	19.16	
	12.988	36.40	0.82	37.22	60.00	22.78	
	0.15	42.70	0.53	43.23	56.00	12.77	AV
	0.22	34.89	0.67	35.56	52.82	17.26	
	3.66	27.80	0.54	28.34	46.00	17.66	
	3.8	27.00	0.54	27.54	46.00	18.46	
	4.03	29.31	0.53	29.84	46.00	16.16	
	12.988	30.10	0.82	30.92	50.00	19.08	

TEST ENGINEER: RAVEN JIN

EUT : LCD Monitor Temperature : 22°C

Model No. : W2242TT Humidity : 60%

Serial No. : E07102401 Date of Test : Oct 25, 2007

Test Mode : VGA 1024*768@60Hz

Test Line	Frequency (MHz)	Meter Reading dB(μV)	Factor (dB)	Emission Level dB(μV)	Limits dB(μV)	Margin (dB)	Remark
VA	0.15	51.90	0.66	52.56	66.00	13.44	QP
	0.22	40.10	0.73	40.83	62.82	21.99	
	0.37117	36.40	0.68	37.08	58.47	21.39	
	3.43	37.90	0.60	38.50	56.00	17.50	
	3.66	40.30	0.61	40.91	56.00	15.09	
	21.147	35.40	0.91	36.31	60.00	23.69	
	0.15	43.30	0.66	43.96	56.00	12.04	AV
	0.22	35.10	0.73	35.83	52.82	16.99	
	0.37117	27.10	0.68	27.78	48.47	20.69	
	3.43	31.60	0.60	32.20	46.00	13.80	
	3.66	30.40	0.61	31.01	46.00	14.99	
	21.147	30.10	0.91	31.01	50.00	18.99	
VB	0.15	51.50	0.53	52.03	66.00	13.97	QP
	0.226	40.19	0.67	40.86	62.60	21.74	
	0.659	38.51	0.59	39.10	56.00	16.90	
	3.58	34.50	0.54	35.04	56.00	20.96	
	4.03	36.51	0.53	37.04	56.00	18.96	
	6.186	36.11	0.69	36.80	60.00	23.20	
	0.15	42.80	0.53	43.33	56.00	12.67	AV
	0.226	35.39	0.67	36.06	52.60	16.54	
	0.659	38.21	0.59	38.80	46.00	7.20	
	3.58	26.00	0.54	26.54	46.00	19.46	
	4.03	29.51	0.53	30.04	46.00	15.96	
	6.186	26.11	0.69	26.80	50.00	23.20	

TEST ENGINEER: RAVEN JIN

EUT : LCD Monitor Temperature : 22°C

Model No. : W2242TT Humidity : 60%

Serial No. : E07102401 Date of Test : Oct 25, 2007

Test Mode : VGA 1680*1050@60Hz

Test Line	Frequency (MHz)	Meter Reading dB(μV)	Factor (dB)	Emission Level dB(μV)	Limits dB(μV)	Margin (dB)	Remark
VA	0.15	52.20	0.66	52.86	66.00	13.14	QP
	0.223	42.20	0.73	42.93	62.71	19.78	
	0.51824	35.40	0.65	36.05	56.00	19.95	
	1.269	35.10	0.53	35.63	56.00	20.37	
	3.87	41.21	0.61	41.82	56.00	14.18	
	4.1	41.31	0.62	41.93	56.00	14.07	
	0.15	43.40	0.66	44.06	56.00	11.94	AV
	0.223	37.10	0.73	37.83	52.71	14.88	
	0.51824	29.10	0.65	29.75	46.00	16.25	
	1.269	26.10	0.53	26.63	46.00	19.37	
	3.87	32.31	0.61	32.92	46.00	13.08	
	4.1	31.41	0.62	32.03	46.00	13.97	
VB	0.15	51.60	0.53	52.13	66.00	13.87	QP
	0.224	41.79	0.67	42.46	62.67	20.21	
	0.657	38.21	0.59	38.80	56.00	17.20	
	3.86	41.10	0.54	41.64	56.00	14.36	
	4.027	42.11	0.53	42.64	56.00	13.36	
	13.408	35.10	0.82	35.92	60.00	24.08	
	0.15	42.90	0.53	43.43	56.00	12.57	AV
	0.224	37.09	0.67	37.76	52.67	14.91	
	0.657	38.11	0.59	38.70	46.00	7.30	
	3.86	34.10	0.54	34.64	46.00	11.36	
	4.027	36.11	0.53	36.64	46.00	9.36	
	13.408	26.90	0.82	27.72	50.00	22.28	

TEST ENGINEER: RAVEN JIN

EUT : LCD Monitor Temperature : 22°C

Model No. : W2242TT Humidity : 60%

Serial No. : E07102401 Date of Test : Oct 25, 2007

Test Mode : DVI 640*480@60Hz

Test Line	Frequency (MHz)	Meter Reading dB(μV)	Factor (dB)	Emission Level dB(μV)	Limits dB(μV)	Margin (dB)	Remark
VA	0.15	52.10	0.66	52.76	66.00	13.24	QP
	0.2162	47.40	0.73	48.13	62.96	14.83	
	0.28782	39.91	0.70	40.61	60.59	19.98	
	0.36338	38.91	0.68	39.59	58.65	19.06	
	3.985	43.10	0.62	43.72	56.00	12.28	
	20.594	36.90	0.91	37.81	60.00	22.19	
	0.15	40.96	0.66	41.62	56.00	14.38	AV
	0.2162	39.90	0.73	40.63	52.96	12.33	
	0.28782	30.11	0.70	30.81	50.59	19.78	
	0.36338	29.91	0.68	30.59	48.65	18.06	
	3.985	40.10	0.62	40.72	46.00	5.28	
	20.594	29.90	0.91	30.81	50.00	19.19	
VB	0.15	54.10	0.53	54.63	66.00	11.37	QP
	0.2162	47.39	0.67	48.06	62.96	14.90	
	0.36338	40.30	0.65	40.95	58.65	17.70	
	0.6372	37.40	0.60	38.00	56.00	18.00	
	3.985	41.11	0.53	41.64	56.00	14.36	
	4.361	40.10	0.54	40.64	56.00	15.36	
	0.15	46.10	0.53	46.63	56.00	9.37	AV
	0.2162	40.09	0.67	40.76	52.96	12.20	
	0.36338	33.90	0.65	34.55	48.65	14.10	
	0.6372	30.10	0.60	30.70	46.00	15.30	
	3.985	36.61	0.53	37.14	46.00	8.86	
	4.361	35.90	0.54	36.44	46.00	9.56	

TEST ENGINEER: RAVEN JIN

EUT : LCD Monitor Temperature : 22°C

Model No. : W2242TT Humidity : 60%

Serial No. : E07102401 Date of Test : Oct 25, 2007

Test Mode : DVI 1024*768@60Hz

Test Line	Frequency (MHz)	Meter Reading dB(μV)	Factor (dB)	Emission Level dB(μV)	Limits dB(μV)	Margin (dB)	Remark
VA	0.15	47.10	0.66	47.76	66.00	18.24	QP
	0.217	45.41	0.73	46.14	62.93	16.79	
	0.363	37.61	0.68	38.29	58.66	20.37	
	3.84	41.11	0.61	41.72	56.00	14.28	
	4.05	42.20	0.62	42.82	56.00	13.18	
	21.95	33.00	0.91	33.91	60.00	26.09	
	0.15	35.10	0.66	35.76	56.00	20.24	AV
	0.217	40.00	0.73	40.73	52.93	12.20	
	0.363	36.01	0.68	36.69	48.66	11.97	
	3.84	35.01	0.61	35.62	46.00	10.38	
	4.05	36.00	0.62	36.62	46.00	9.38	
	21.95	26.00	0.91	26.91	50.00	23.09	
VB	0.15	47.20	0.53	47.73	66.00	18.27	QP
	0.217	45.39	0.67	46.06	62.93	16.87	
	0.363	38.00	0.65	38.65	58.66	20.01	
	4.05	40.01	0.53	40.54	56.00	15.46	
	6.59	29.99	0.75	30.74	60.00	29.26	
	24.01	35.99	1.01	37.00	60.00	23.00	
	0.15	37.90	0.53	38.43	56.00	17.57	AV
	0.217	39.99	0.67	40.66	52.93	12.27	
	0.363	35.40	0.65	36.05	48.66	12.61	
	4.05	35.01	0.53	35.54	46.00	10.46	
	6.59	19.99	0.75	20.74	50.00	29.26	
	24.01	29.99	1.01	31.00	50.00	19.00	

TEST ENGINEER: RAVEN JIN

EUT : LCD Monitor Temperature : 22°C

Model No. : W2242TT Humidity : 60%

Serial No. : E07102401 Date of Test : Oct 25, 2007

Test Mode : DVI 1680*1050@60Hz

Test Line	Frequency (MHz)	Meter Reading dB(μV)	Factor (dB)	Emission Level dB(μV)	Limits dB(μV)	Margin (dB)	Remark
VA	0.15	47.30	0.66	47.96	66.00	18.04	QP
	0.217	47.00	0.73	47.73	62.93	15.20	
	0.29	39.21	0.70	39.91	60.52	20.61	
	0.363	38.31	0.68	38.99	58.66	19.67	
	3.69	39.40	0.61	40.01	56.00	15.99	
	4.11	42.51	0.62	43.13	56.00	12.87	
	0.15	39.00	0.66	39.66	56.00	16.34	AV
	0.217	43.00	0.73	43.73	52.93	9.20	
	0.29	33.11	0.70	33.81	50.52	16.71	
	0.363	35.01	0.68	35.69	48.66	12.97	
	3.69	33.40	0.61	34.01	46.00	11.99	
	4.11	33.61	0.62	34.23	46.00	11.77	
VB	0.15	47.50	0.53	48.03	66.00	17.97	QP
	0.217	45.89	0.67	46.56	62.93	16.37	
	3.55	33.50	0.54	34.04	56.00	21.96	
	4.11	38.31	0.53	38.84	56.00	17.16	
	6.29	37.80	0.71	38.51	60.00	21.49	
	21.26	36.00	1.01	37.01	60.00	22.99	
	0.15	38.00	0.53	38.53	56.00	17.47	AV
	0.217	40.39	0.67	41.06	52.93	11.87	
	3.55	26.40	0.54	26.94	46.00	19.06	
	4.11	33.61	0.53	34.14	46.00	11.86	
	6.29	32.20	0.71	32.91	50.00	17.09	
	21.26	25.00	1.01	26.01	50.00	23.99	

TEST ENGINEER: RAVEN JIN

EUT : LCD Monitor Temperature : 22°C

Model No. : W2242ST Humidity : 60%

Serial No. : E07102402 Date of Test : Oct 25, 2007

Test Mode : VGA 640*480@60Hz

Test Line	Frequency (MHz)	Meter Reading dB(μV)	Factor (dB)	Emission Level dB(μV)	Limits dB(μV)	Margin (dB)	Remark
VA	0.15	51.80	0.66	52.46	66.00	13.54	QP
	0.223	41.90	0.73	42.63	62.71	20.08	
	0.371	34.80	0.68	35.48	58.48	23.00	
	3.44	35.00	0.60	35.60	56.00	20.40	
	3.66	40.10	0.61	40.71	56.00	15.29	
	4.03	39.60	0.62	40.22	56.00	15.78	
	0.15	43.30	0.66	43.96	56.00	12.04	AV
	0.223	36.90	0.73	37.63	52.71	15.08	
	0.371	33.00	0.68	33.68	48.48	14.80	
	3.44	29.00	0.60	29.60	46.00	16.40	
	3.66	32.30	0.61	32.91	46.00	13.09	
	4.03	31.20	0.62	31.82	46.00	14.18	
VB	0.15	51.40	0.53	51.93	66.00	14.07	QP
	0.22	42.29	0.67	42.96	62.82	19.86	
	0.657	38.61	0.59	39.20	56.00	16.80	
	3.66	35.70	0.54	36.24	56.00	19.76	
	3.8	35.30	0.54	35.84	56.00	20.16	
	4.03	36.31	0.53	36.84	56.00	19.16	
	0.15	42.70	0.53	43.23	56.00	12.77	AV
	0.22	34.89	0.67	35.56	52.82	17.26	
	0.657	38.51	0.59	39.10	46.00	6.90	
	3.66	27.80	0.54	28.34	46.00	17.66	
	3.8	27.00	0.54	27.54	46.00	18.46	
	4.03	29.31	0.53	29.84	46.00	16.16	

TEST ENGINEER: RAVEN JIN

EUT : LCD Monitor Temperature : 22°C

Model No. : W2242ST Humidity : 60%

Serial No. : E07102402 Date of Test : Oct 25, 2007

Test Mode : VGA 1024*768@60Hz

Test Line	Frequency (MHz)	Meter Reading dB(μV)	Factor (dB)	Emission Level dB(μV)	Limits dB(μV)	Margin (dB)	Remark
VA	0.15	51.90	0.66	52.56	66.00	13.44	QP
	0.22	40.10	0.73	40.83	62.82	21.99	
	0.297	34.30	0.70	35.00	60.33	25.33	
	0.371	35.00	0.68	35.68	58.48	22.80	
	3.43	37.90	0.60	38.50	56.00	17.50	
	3.66	40.30	0.61	40.91	56.00	15.09	
	0.15	43.30	0.66	43.96	56.00	12.04	AV
	0.22	35.10	0.73	35.83	52.82	16.99	
	0.297	29.00	0.70	29.70	50.33	20.63	
	0.371	33.30	0.68	33.98	48.48	14.50	
	3.43	31.60	0.60	32.20	46.00	13.80	
	3.66	30.40	0.61	31.01	46.00	14.99	
VB	0.15	51.50	0.53	52.03	66.00	13.97	QP
	0.226	40.19	0.67	40.86	62.60	21.74	
	0.659	38.51	0.59	39.10	56.00	16.90	
	3.58	34.50	0.54	35.04	56.00	20.96	
	4.03	36.51	0.53	37.04	56.00	18.96	
	4.33	34.90	0.54	35.44	56.00	20.56	
	0.15	42.80	0.53	43.33	56.00	12.67	AV
	0.226	35.39	0.67	36.06	52.60	16.54	
	0.659	38.21	0.59	38.80	46.00	7.20	
	3.58	26.00	0.54	26.54	46.00	19.46	
	4.03	29.51	0.53	30.04	46.00	15.96	
	4.33	29.50	0.54	30.04	46.00	15.96	

TEST ENGINEER: RAVEN JIN

EUT : LCD Monitor Temperature : 22°C

Model No. : W2242ST Humidity : 60%

Serial No. : E07102402 Date of Test : Oct 25, 2007

Test Mode : VGA 1680*1050@60Hz

Test Line	Frequency (MHz)	Meter Reading dB(μV)	Factor (dB)	Emission Level dB(μV)	Limits dB(μV)	Margin (dB)	Remark
VA	0.15	52.20	0.66	52.86	66.00	13.14	QP
	0.223	42.20	0.73	42.93	62.71	19.78	
	0.373	35.10	0.68	35.78	58.43	22.65	
	3.57	37.20	0.60	37.80	56.00	18.20	
	3.87	41.21	0.61	41.82	56.00	14.18	
	4.1	41.31	0.62	41.93	56.00	14.07	
	0.15	43.40	0.66	44.06	56.00	11.94	AV
	0.223	37.10	0.73	37.83	52.71	14.88	
	0.373	33.40	0.68	34.08	48.43	14.35	
	3.57	30.40	0.60	31.00	46.00	15.00	
	3.87	32.31	0.61	32.92	46.00	13.08	
	4.1	31.41	0.62	32.03	46.00	13.97	
VB	0.15	51.60	0.53	52.13	66.00	13.87	QP
	0.224	41.79	0.67	42.46	62.67	20.21	
	0.657	38.21	0.59	38.80	56.00	17.20	
	3.73	36.00	0.54	36.54	56.00	19.46	
	3.87	37.30	0.54	37.84	56.00	18.16	
	4.02	36.61	0.53	37.14	56.00	18.86	
	0.15	42.90	0.53	43.43	56.00	12.57	AV
	0.224	37.09	0.67	37.76	52.67	14.91	
	0.657	38.11	0.59	38.70	46.00	7.30	
	3.73	27.60	0.54	28.14	46.00	17.86	
	3.87	29.60	0.54	30.14	46.00	15.86	
	4.02	29.41	0.53	29.94	46.00	16.06	

TEST ENGINEER: RAVEN JIN

4 RADIATED EMISSION TEST


4.1 Test Equipment

The following test equipment are used during the radiated emission test in a semi-anechoic chamber:

Item	Type	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1.	Test Receiver	R&S	ESVS10	844594/001	Apr 06, 2007	Apr 06, 2008
2.	Preamplifier	Agilent	8447D	2944A10548	Sep 19, 2007	Mar 19, 2008
3.	Preamplifier	HP	8449B	3008A00864	Apr 06, 2007	Apr 06, 2008
4.	Bi-log Antenna	Chase	CBL6111	1145	Sep 18, 2007	Mar 18, 2008
5.	Horn Antenna	EMCO	3115	9607-4878	Apr 06, 2007	Apr 06, 2008
6.	Spectrum	Agilent	E7405A	MY45106600	Apr 06, 2007	Apr 06, 2008
7.	Software	Audix	E3	SET00200 9912M295-2	--	--


4.2 Block Diagram of Test Setup

4.2.1 EUT and simulators



■ : Ferrite Core

4.2.2 Radiated emission test setup



■ : 50 ohm Coaxial Switch

4.3 Radiated Emission Limit [FCC Part 15 Subpart B 15.109(a)]

Frequency (MHz)	Distance (m)	Field strength limits	
		($\mu\text{V/m}$)	dB ($\mu\text{V/m}$)
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
Above 960	3	500	54.0

NOTE 1 - Emission Level dB ($\mu\text{V/m}$) = $20 \log$ Emission Level ($\mu\text{V/m}$)
 NOTE 2 - The tighter limit applies at the band edges.
 NOTE 3 - Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
 NOTE 4 - The limits shown are based on Quasi-peak value detector below or equal to 1GHz and Peak value detector above 1GHz.

4.4 Test Configuration

The configuration of the EUT and simulators are same as those used in conducted emission test.

Please refer to Sec.3.4.

4.5 Operating Condition of EUT

Same as conducted emission test which is listed in Sec.3.5, except the test setup replaced by Sec.4.2.

4.6 Test Procedures

The EUT and simulators were placed on a turntable that is 0.8 meter above ground. The turntable rotated 360 degrees to determine the position of the maximum emission level. The EUT was set 3 meters away from the receiving antenna, which was mounted on an antenna tower. The broadband antenna (Calibrated antenna) was used as receiving antenna below 1000MHz. The horn antenna was used as receiving antenna above 1000MHz. The antenna moved up and down between 1 meter and 4 meters to find out the maximum emission level. The broadband antenna (Calibrated Bilog Antenna) or the horn antenna was used as receiving antenna. Both horizontal and vertical polarizations of the antenna were set on measurement. In order to find the maximum emission, all of the interference cables were manipulated according to ANSI C63.4:2003 requirements during radiated emission test.

The bandwidth of Test Receiver R&S ESVS10 was set at 120 kHz below 1GHz and The Spectrum Agilent E7405A was set at 1MHz above 1GHz.

The frequency range from 30 MHz to 2000 MHz was checked.

The frequency range from 1 GHz to 2 GHz was checked for VGA 1680*1050@60Hz and DVI 1680*1050@60Hz mode.

The test modes were done on radiated disturbance test and all the test results are listed in Sec.4.7.

4.7 Test Results

<PASS>

The frequency and amplitude of the highest radiated emission relative the limit is reported. All the emissions not reported below are too low against the FCC limit.

Model Number	Test Mode	Data Page
W2242TT	VGA 640*480@60Hz	P25
	VGA 1024*768@60Hz	P26
	VGA 1680*1050@60Hz	P27 – P28
	DVI 640*480@60Hz	P29
	DVI 1024*768@60Hz	P30
	DVI 1680*1050@60Hz	P31 – P32
W2242ST	VGA 640*480@60Hz	P33
	VGA 1024*768@60Hz	P34
	VGA 1680*1050@60Hz	P35 – P36

NOTE 1 – Emission Level = Antenna Factor + Cable Loss + Meter Reading.($< 1\text{GHz}$)

NOTE 2 – Emission Level = Antenna Factor + Cable Loss – Preamp Factor + Meter Reading.($> 1\text{GHz}$)

NOTE 3 – The emission levels that are 20dB below the official limit are not reported.

NOTE 4 – 0° was the table front facing the antenna. Degree is calculated from 0° clockwise facing the antenna.

NOTE 5 – All reading are Quasi-Peak values below or equal to 1GHz and Peak values above 1GHz.

NOTE 6 – The worst case is for VGA 640*480@60Hz (M/N: W2242TT). The worst emission at horizontal polarization was detected at 35.82 MHz with corrected signal level of 35.30 dB ($\mu\text{V/m}$) (limit is 40.00 dB ($\mu\text{V/m}$)), when the antenna was 1.20 m height and the turntable was at 335° . The worst emission at vertical polarization was detected at 34.85 MHz with corrected signal level of 34.71 dB ($\mu\text{V/m}$) (limit is 40.00 dB ($\mu\text{V/m}$)), when the antenna was 1.00 m height and the turntable was at 300° .

EUT : LCD Monitor Temperature : 22°C

Model No. : W2242TT Humidity : 60%

Serial No. : E07102401 Date of Test : Oct 29, 2007

Test Mode : VGA 640*480@60Hz

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)
Horizontal	35.82	23.65	10.71	0.94	35.30	40.00	4.70
	110.51	11.82	11.34	1.79	24.95	43.50	18.55
	189.08	14.31	12.30	2.28	28.89	43.50	14.61
	313.24	9.75	13.92	3.20	26.87	46.00	19.13
	533.43	8.04	20.36	4.07	32.47	46.00	13.53
	692.51	10.23	21.18	4.78	36.19	46.00	9.81
Vertical	34.85	21.78	12.00	0.93	34.71	40.00	5.29
	110.51	17.81	11.34	1.79	30.94	43.50	12.56
	191.99	15.24	12.50	2.30	30.04	43.50	13.46
	279.29	16.60	13.47	3.00	33.07	46.00	12.93
	441.28	10.19	18.89	3.77	32.85	46.00	13.15
	648.86	13.66	21.07	4.53	39.26	46.00	6.74

TEST ENGINEER: KEN XU

EUT : LCD Monitor Temperature : 22°C

Model No. : W2242TT Humidity : 60%

Serial No. : E07102401 Date of Test : Oct 29, 2007

Test Mode : VGA 1024*768@60Hz

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)
Horizontal	34.85	21.98	12.00	0.93	34.91	40.00	5.09
	121.18	10.36	11.88	1.87	24.11	43.50	19.39
	181.32	13.21	11.70	2.24	27.15	43.50	16.35
	300.63	12.66	13.22	3.11	28.99	46.00	17.01
	423.82	8.39	18.50	3.70	30.59	46.00	15.41
	527.61	10.94	20.30	4.06	35.30	46.00	10.70
Vertical	34.85	19.40	12.00	0.93	32.33	40.00	7.67
	121.18	14.93	11.88	1.87	28.68	43.50	14.82
	300.63	19.52	13.22	3.11	35.85	46.00	10.15
	465.53	12.76	19.38	3.87	36.01	46.00	9.99
	659.53	15.00	21.09	4.60	40.69	46.00	5.31
	847.71	9.36	23.38	5.52	38.26	46.00	7.74

TEST ENGINEER: KEN XU

EUT : LCD Monitor Temperature : 22°C

Model No. : W2242TT Humidity : 60%

Serial No. : E07102401 Date of Test : Oct 29, 2007

Test Mode : VGA 1680*1050@60Hz

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)
Horizontal	34.85	21.03	12.00	0.93	33.96	40.00	6.04
	85.29	10.64	11.51	1.57	23.72	40.00	16.28
	178.41	12.99	11.46	2.23	26.68	43.50	16.82
	238.55	19.02	13.68	2.71	35.41	46.00	10.59
	526.64	10.97	20.29	4.06	35.32	46.00	10.68
	662.44	14.20	21.10	4.60	39.90	46.00	6.10
Vertical	34.85	18.86	12.00	0.93	31.79	40.00	8.21
	119.24	16.08	11.79	1.86	29.73	43.50	13.77
	298.69	21.59	13.24	3.11	37.94	46.00	8.06
	355.92	16.42	16.01	3.40	35.83	46.00	10.17
	534.4	15.41	20.36	4.08	39.85	46.00	6.15
	715.79	9.29	21.70	4.90	35.89	46.00	10.11

TEST ENGINEER: KEN XU

EUT : LCD Monitor Temperature : 22°C

Model No. : W2242TT Humidity : 60%

Serial No. : E07102401 Date of Test : Oct 29, 2007

Test Mode : VGA 1680*1050@60Hz

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
Horizontal	1016.00	51.91	24.17	6.73	37.66	45.15	74.00	28.85	PK
	1065.00	55.68	24.42	6.82	37.52	49.40	74.00	24.60	
	1237.00	47.14	25.18	7.24	37.09	42.47	74.00	31.53	
	1326.00	48.04	25.53	7.66	36.89	44.34	74.00	29.66	
	1496.00	51.59	26.13	8.43	36.54	49.61	74.00	24.39	
	1666.00	47.19	26.68	8.92	36.23	46.56	74.00	27.44	
Vertical	1065.00	48.54	24.42	6.82	37.52	42.26	74.00	31.74	PK
	1155.00	44.91	24.83	7.01	37.28	39.47	74.00	34.53	
	1257.00	48.28	25.25	7.41	37.04	43.90	74.00	30.10	
	1424.00	46.28	25.88	8.09	36.68	43.57	74.00	30.43	
	1593.00	46.20	26.45	8.71	36.36	45.00	74.00	29.00	
	1849.00	44.80	27.21	9.48	35.93	45.56	74.00	28.44	

TEST ENGINEER: KEN XU

EUT : LCD Monitor Temperature : 22°C

Model No. : W2242TT Humidity : 60%

Serial No. : E07102401 Date of Test : Oct 29, 2007

Test Mode : DVI 640*480@60Hz

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)
Horizontal	33.88	33.07	13.12	0.93	19.02	40.00	6.93
	126.03	25.54	12.02	1.91	11.61	43.50	17.96
	188.11	30.50	12.25	2.28	15.97	43.50	13.00
	279.29	27.44	13.47	3.00	10.97	46.00	18.56
	439.34	29.02	18.83	3.77	6.42	46.00	16.98
	689.6	36.06	21.17	4.75	10.14	46.00	9.94
Vertical	34.85	17.70	12.00	0.93	30.63	40.00	9.37
	94.02	16.31	10.84	1.64	28.79	43.50	14.71
	126.03	21.94	12.02	1.91	35.87	43.50	7.63
	189.08	17.84	12.30	2.28	32.42	43.50	11.08
	315.18	16.88	14.03	3.20	34.11	46.00	11.89
	687.66	11.82	21.17	4.75	37.74	46.00	8.26

TEST ENGINEER: KEN XU

EUT : LCD Monitor Temperature : 22°C

Model No. : W2242TT Humidity : 60%

Serial No. : E07102401 Date of Test : Oct 29, 2007

Test Mode : DVI 1024*768@60Hz

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)
Horizontal	33.88	15.88	13.12	0.93	29.93	40.00	10.07
	121.18	10.95	11.88	1.87	24.70	43.50	18.80
	181.32	17.00	11.70	2.24	30.94	43.50	12.56
	300.63	13.80	13.22	3.11	30.13	46.00	15.87
	530.52	14.75	20.32	4.07	39.14	46.00	6.86
	666.32	9.95	21.11	4.64	35.70	46.00	10.30
Vertical	34.85	17.47	12.00	0.93	30.40	40.00	9.60
	91.11	15.87	10.89	1.62	28.38	43.50	15.12
	190.05	15.68	12.35	2.29	30.32	43.50	13.18
	300.63	21.22	13.22	3.11	37.55	46.00	8.45
	533.43	12.40	20.36	4.07	36.83	46.00	9.17
	649.83	13.36	21.07	4.53	38.96	46.00	7.04

TEST ENGINEER: KEN XU

EUT : LCD Monitor Temperature : 22°C

Model No. : W2242TT Humidity : 60%

Serial No. : E07102401 Date of Test : Oct 29, 2007

Test Mode : DVI 1680*1050@60Hz

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)
Horizontal	33.88	30.56	16.51	13.12	0.93	40.00	9.44
	119.24	25.61	11.96	11.79	1.86	43.50	17.89
	179.38	28.02	14.22	11.56	2.24	43.50	15.48
	296.75	34.38	18.02	13.26	3.10	46.00	11.62
	533.43	38.63	14.20	20.36	4.07	46.00	7.37
	639.16	37.11	11.59	21.03	4.49	46.00	8.89
Vertical	31.94	13.29	15.50	0.92	29.71	40.00	10.29
	90.14	16.43	10.90	1.61	28.94	43.50	14.56
	180.35	17.99	11.66	2.24	31.89	43.50	11.61
	296.75	21.95	13.26	3.10	38.31	46.00	7.69
	533.43	15.91	20.36	4.07	40.34	46.00	5.66
	639.16	11.85	21.03	4.49	37.37	46.00	8.63

TEST ENGINEER: KEN XU

EUT : LCD Monitor Temperature : 22°C

Model No. : W2242TT Humidity : 60%

Serial No. : E07102401 Date of Test : Oct 29, 2007

Test Mode : DVI 1680*1050@60Hz

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
Horizontal	1065.00	48.28	24.42	6.82	37.52	42.00	74.00	32.00	PK
	1299.00	48.00	25.43	7.58	36.95	44.06	74.00	29.94	
	1383.00	52.95	25.73	7.92	36.76	49.84	74.00	24.16	
	1449.00	55.28	25.97	8.18	36.63	52.80	74.00	21.20	
	1598.00	46.69	26.46	8.71	36.35	45.51	74.00	28.49	
	1849.00	44.77	27.21	9.48	35.93	45.53	74.00	28.47	
Vertical	1065.00	54.74	24.42	6.82	37.52	48.46	74.00	25.54	PK
	1171.00	47.36	24.90	7.04	37.24	42.06	74.00	31.94	
	1330.00	46.60	25.54	7.66	36.88	42.92	74.00	31.08	
	1496.00	51.25	26.13	8.43	36.54	49.27	74.00	24.73	
	1556.00	51.54	26.33	8.57	36.42	50.02	74.00	23.98	
	1598.00	48.38	26.46	8.71	36.35	47.20	74.00	26.80	
	1693.00	45.72	26.75	8.99	36.18	45.28	74.00	28.72	

TEST ENGINEER: KEN XU

EUT : LCD Monitor Temperature : 22°C

Model No. : W2242ST Humidity : 60%

Serial No. : E07102402 Date of Test : Oct 29, 2007

Test Mode : VGA 640*480@60Hz

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)
Horizontal	30.00	14.81	18.02	0.91	33.74	40.00	6.26
	100.81	12.32	10.81	1.70	24.83	43.50	18.67
	189.08	21.20	12.30	2.28	35.78	43.50	7.72
	532.46	8.90	20.34	4.07	33.31	46.00	12.69
	750.71	7.04	22.62	5.11	34.77	46.00	11.23
	881.66	8.14	23.04	5.62	36.80	46.00	9.20
Vertical	30.00	11.52	18.02	0.91	30.45	40.00	9.55
	100.81	18.73	10.81	1.70	31.24	43.50	12.26
	126.03	22.23	12.02	1.91	36.16	43.50	7.34
	189.08	21.61	12.30	2.28	36.19	43.50	7.31
	377.26	19.75	16.99	3.50	40.24	46.00	5.76
	513.06	17.00	20.17	4.03	41.20	46.00	4.80

TEST ENGINEER: KEN XU

EUT : LCD Monitor Temperature : 22°C

Model No. : W2242ST Humidity : 60%

Serial No. : E07102402 Date of Test : Oct 29, 2007

Test Mode : VGA 1024*768@60Hz

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)
Horizontal	181.32	22.11	11.70	2.24	36.05	43.50	7.45
	212.36	20.70	13.29	2.46	36.45	43.50	7.05
	362.71	17.09	16.35	3.43	36.87	46.00	9.13
	526.64	13.71	20.29	4.06	38.06	46.00	7.94
	646.92	9.69	21.06	4.53	35.28	46.00	10.72
	814.73	9.14	23.71	5.42	38.27	46.00	7.73
Vertical	74.62	13.88	12.30	1.46	27.64	40.00	12.36
	121.18	20.52	11.88	1.87	34.27	43.50	9.23
	181.32	23.91	11.70	2.24	37.85	43.50	5.65
	279.29	18.58	13.47	3.00	35.05	46.00	10.95
	360.77	15.29	16.24	3.43	34.96	46.00	11.04
	527.61	10.65	20.30	4.06	35.01	46.00	10.99

TEST ENGINEER: KEN XU

EUT : LCD Monitor Temperature : 22°C

Model No. : W2242ST Humidity : 60%

Serial No. : E07102402 Date of Test : Oct 29, 2007

Test Mode : VGA 1680*1050@60Hz

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)
Horizontal	35.82	21.16	10.71	0.94	32.81	40.00	7.19
	178.41	22.23	11.46	2.23	35.92	43.50	7.58
	235.64	15.39	13.65	2.68	31.72	46.00	14.28
	354.95	11.97	16.01	3.40	31.38	46.00	14.62
	525.67	11.81	20.29	4.06	36.16	46.00	9.84
	648.86	9.21	21.07	4.53	34.81	46.00	11.19
Vertical	34.85	22.31	12.00	0.93	35.24	40.00	4.76
	119.24	20.19	11.79	1.86	33.84	43.50	9.66
	178.41	24.94	11.46	2.23	38.63	43.50	4.87
	274.44	18.71	13.53	2.96	35.20	46.00	10.80
	529.55	11.00	20.32	4.07	35.39	46.00	10.61
	648.86	11.93	21.07	4.53	37.53	46.00	8.47

TEST ENGINEER: KEN XU

EUT : LCD Monitor Temperature : 22°C

Model No. : W2242ST Humidity : 60%

Serial No. : E07102402 Date of Test : Oct 29, 2007

Test Mode : VGA 1680*1050@60Hz

Polarization	Frequency (MHz)	Meter Reading dB (μV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level dB (μV/m)	Limits dB (μV/m)	Margin (dB)	Remark
Horizontal	1065.00	48.72	24.42	6.82	37.52	42.44	74.00	31.56	PK
	1140.00	46.46	24.76	6.98	37.32	40.88	74.00	33.12	
	1251.00	47.35	25.22	7.33	37.05	42.85	74.00	31.15	
	1364.00	46.22	25.66	7.84	36.80	42.92	74.00	31.08	
	1459.00	47.16	26.01	8.26	36.61	44.82	74.00	29.18	
	1849.00	45.44	27.21	9.48	35.93	46.20	74.00	27.80	
Vertical	1066.00	45.53	51.81	24.42	6.82	37.52	74.00	28.47	PK
	1172.00	42.68	47.98	24.90	7.04	37.24	74.00	31.32	
	1260.00	40.64	44.99	25.27	7.41	37.03	74.00	33.36	
	1385.00	45.67	48.76	25.75	7.92	36.76	74.00	28.33	
	1565.00	46.33	47.73	26.36	8.64	36.40	74.00	27.67	
	1746.00	43.50	43.53	26.91	9.15	36.09	74.00	30.50	

TEST ENGINEER: KEN XU

5 DEVIATION TO TEST SPECIFICATIONS

None.

6 DEBUG DESCRIPTION

Name	M/N	Specifications (mm)	Manufacturer	Location
Aluminum foil	T-308	50mm*30mm	DAEHUNG SUBSIDIARY MATERIALS	See Internal photos Figure 1, 17, 19, 35
Gasket	3940TKK 091Z	45mm*80mm*0.5mm	Yisipan	See Internal photos Figure 18, 36