

APPLICANT: TAEKWANG INDUSTRIAL CO., LTD.

FCC ID: BESTKP-910A

TABLE OF CONTENTS

TEST REPORT CONTAINING:

PAGE 1.....15.214(d) - SECURITY CODING INFORMATION AND TEST PROC.
PAGE 2.....TEST PROCEDURE CONTINUED
PAGE 3-4.....CIRCUIT DESCRIPTIONS
PAGE 5.....RADIATION INTERFERENCE TEST DATA - BASE
PAGE 6.....RADIATION INTERFERENCE TEST DATA - HANDSET
PAGE 7.....OCCUPIED BANDWIDTH TEST DATA
PAGE 8.....POWERLINE CONDUCTED TEST DATA

EXHIBITS CONTAINING:

EXHIBIT 1.....POWER OF ATTORNEY LETTER
EXHIBIT 2.....BLOCK DIAGRAM - BASE
EXHIBIT 3.....BLOCK DIAGRAM - HANDSET
EXHIBIT 4.....SCHEMATIC - BASE
EXHIBIT 5.....SCHEMATIC - HANDSET
EXHIBIT 6.....FCC ID LABEL SAMPLES
EXHIBIT 7.....SKETCH OF FCC ID LABEL LOCATION - BASE/HANDSET
EXHIBIT 8.....EXTERNAL PHOTO FRONT VIEW BASE/HANDSET
EXHIBIT 9.....EXTERNAL PHOTO REAR VIEW BASE/HANDSET
EXHIBIT 10.....INTERNAL PHOTO - SOLDER BASE/HANDSET
EXHIBIT 11.....INTERNAL PHOTO - COMPONENT BASE/HANDSET
EXHIBIT 12A-12L...INSTRUCTION MANUAL
EXHIBIT 13A-13B...POWERLINE CONDUCTED INTERFERENCE PLOTS
EXHIBIT 14A-14B...OCCUPIED BANDWIDTH PLOTS - HANDSET
EXHIBIT 15A-15B...OCCUPIED BANDWIDTH PLOTS - BASE4

APPLICANT: TAEKWANG INDUSTRIAL CO., LTD.

FCC ID: BESTKP-910A

REPORT #: T:\CUS\T\TIC\TIC127A0\TIC127A0.RPT

PAGE: TABLE OF CONTENTS

SECURITY CODING INFORMATION

15.214(d) - THIS DEVICE COMPLIES WITH THE SECURITY CODE REQUIREMENTS OF 5.214(d)(1)(2) AND (3) BY MEANS OF THE FOLLOWING:

THIS PHONE IS EQUIPPED WITH A DIGITAL SECURITY SYSTEM WITH OVER 1 MILLION CODE COMBINATIONS. WHEN MAKING A CALL, THE TELEPHONE SEARCHES THROUGH ITS 60 AVAILABLE CHANNELS AUTO CHANNEL SCAN TO FIND THE CLEAREST ONE. THE RECEIVER PORTION OF THIS TELEPHONE, FCC ID: BESTKP-910A, WAS TESTED WITH PASSING RESULTS. A VERIFICATION REPORT HAS BEEN ISSUED PER FCC RULES PART 15.107.

TEST EQUIPMENT LIST

1. X Spectrum Analyzer: HP 8566B-Opt 462, S/N 3138A07786, w/ preselector HP 85685A, S/N 3221A01400, Quasi-Peak Adapter HP 85650A, S/N 3303A01690 & Preamplifier HP 8449B-OPT H02, S/N 3008A00372 Cal. 10/17/99
2. X Biconical Antenna: Eaton Model 94455-1, S/N 1057
3. X Log-Periodic Antenna: Electro-Metrics Model EM-6950, S/N 632
4. X Double-Ridged Horn Antenna: Electro-Metrics Model RGA-180, 1-18 GHz, S/N 2319 Cal. 4/27/99
5. Horn 40-60GHz: ATM Part #19-443-6R
6. Line Impedance Stabilization Network: Electro-Metrics Model ANS-25/2, S/N 2604 Cal. 2/9/00
7. Temperature Chamber: Tenney Engineering Model TTRC, S/N 11717-7
8. Frequency Counter: HP Model 5385A, S/N 3242A07460 Cal 10/6/99
9. Peak Power Meter: HP Model 8900C, S/N 2131A00545 Cal 7/19/99
10. Open Area Test Site #1-3meters Cal. 12/22/99
11. Signal Generator: HP 8640B, S/N 2308A21464 Cal. 9/23/99
12. Signal Generator: HP 8614A, S/N 2015A07428 Cal. 5/29/99
13. Passive Loop Antenna: EMCO Model 6512, 9KHz to 30MHz, S/N 9706-1211 Cal. 6/23/97
14. Dipole Antenna Kit: Electro-Metrics Model TDA-30/1-4, S/N 153 Cal. 11/24/99
15. AC Voltmeter: HP Model 400FL, S/N 2213A14499 Cal. 9/21/99
16. Digital Multimeter: Fluke Model 8012A, S/N 4810047 Cal 9/21/99
17. Digital Multimeter: Fluke Model 77, S/N 43850817 Cal 9/21/99
18. Oscilloscope: Tektronix Model 2230, S/N 300572 Cal 9/23/99

APPLICANT: TAEKWANG INDUSTRIAL CO., LTD.

FCC ID: BESTKP-910A

REPORT #: T:\CUS\T\TIC\TIC127A0\TIC127A0.RPT

PAGE #: 1

TEST PROCEDURE

GENERAL: This report shall NOT be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-1992 using a HEWLETT PACKARD spectrum analyzer with a preselector. The bandwidth of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100KHz and the video bandwidth was 300KHz up to 1.0GHz. Above 1.0GHz the RBW = 1.0MHz and the VBW=3.0MHz. The ambient temperature of the UUT was 53oF with a humidity of 70%.

ANSI STANDARD C63.4-1992 10.1.7 MEASUREMENT PROCEDURES: The UUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The UUT was placed flush with the back of the table (1.5m side). The table used for radiated measurements is capable of continuous rotation.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

The situation was similar for the conducted measurement except that the table did not rotate. The EUT was setup as described in ANSI C63.4-1992 with the EUT 40 cm from the vertical ground wall.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz)	METER READING + ACF = FS
33	20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

POWER LINE CONDUCTED INTERFERENCE: The procedure used was ANSI STANDARD C63.4-1992 using a 50uH LISN. Both lines were observed. The bandwidth of the spectrum analyzer was 10kHz with an appropriate sweep speed. The ambient temperature of the UUT was 53oF with a humidity of 70%.

APPLICANT: TAEKWANG INDUSTRIAL CO., LTD.

FCC ID: BESTKP-910A

REPORT #: T:\CUS\T\TIC\TIC127A0\TIC127A0.RPT

PAGE #: 2

APPLICANT: TAEKWANG INDUSTRIAL CO., LTD.
FCC ID: BESTKP-910A

CIRCUIT DESCRIPTION:

BASE UNIT

The incoming signal comes in on the antenna and is fed through the duplexer to the LNA, Q500 and then to a SAW bandpass filter, FL501. The frequency range of the base receiver is 926-928MHz. From the bandpass filter the signal is fed to the mixer, Q501 which converts the signal down to 26.05MHz. From Q501 the signal is fed to the IF filter FL502 and then to the integrated circuit U500. In the U500 the signal is converted down to 450KHz and then to the detector for FM signal. From the detector the audio is fed to a low pass filter and to the Channel Detector Indicator. From the low pass filter the audio is fed into another low pass filter and shaper and then to the CPU, U311. From the CPU, U311, the audio is fed to a speaker amplifier and the telephone line depending which is selected. From the CPU the line audio is fed to U305A and then to U305B then to the telephone coupling transformer, T301. The CPU also compares the SECURITY CODES and provides the outgoing SECURITY CODE.

On the transmitting side, when a ring signal is detected the transmitter is turned on by photo coupler integrated circuit U301 and the ring detect signal is fed into the CPU, U306, which in turn triggers the transmitter and send a ring signal to the handset. The base transmit frequency range is 902-904MHz. When the handset answers the base unit connects to the phone line and telephone line audio is fed into the speech network and then to an audio amplifier, Q304. The audio is then fed into the compressor U311. From U311 the audio is fed into the VCO, VT which modulated the outgoing carrier. From the VCO the signal is fed through a series of amplifiers, Q508 & Q509. From Q508 the signal is fed to the antenna.

APPLICANT: TAEKWANG INDUSTRIAL CO., LTD.
FCC ID: BESTKP-910A
REPORT #: T:\CUS\T\TIC\TIC127A0\TIC127A0.RPT
PAGE #: 3

APPLICANT: TAEKWANG INDUSTRIAL CO., LTD.
FCC ID: BESTKP-910A

CIRCUIT DESCRIPTIONS CONTD.

HANDSET

The incoming signal comes in on the antenna and is fed through the duplexer to the LNA, Q100 and then to a SAW 903MHz bandpass filter. The frequency range of the handset receiver is 902-904MHz. From the bandpass filter the signal is fed to the mixer, Q101 which converts the signal down to 26.05MHz. From Q101 the signal is fed to the IF filter FL102 and then to the integrated circuit U100. In the U100 the signal is converted down to 450KHz and then to the detector for FM signal. From the detector, p/o U100 the audio is fed to a low pass filter and to the RING Detector Indicator. From the low pass filter the audio is fed simultaneously to the earphone element and to the CPU, U101. The earphone audio is fed into U2 and then to U4 then to the receiver element, RC1. The CPU uses the data to continuously monitor the security code.

The transmitter frequency range is 926-928MHz. The outgoing audio is picked up by the microphone and fed to the audio integrated circuit U2. This audio integrated circuit feeds a low pass filter then feed the signal to the VCO, VT. From the VCO the signal is fed in to the amplifier Q107 and Q108 to the duplexer and then to the antenna.

ANTENNA AND GROUND CIRCUITRY

This unit makes use of a short, antenna. The antenna is inductively coupled. The antenna is self contained, no provision is made for an external antenna.

No ground connection is provided. The unit relies on the ground tract of the printed circuit board.

APPLICANT: TAEKWANG INDUSTRIAL CO., LTD.
FCC ID: BESTKP-910A
REPORT #: T:\CUS\T\TIC\TIC127A0\TIC127A0.RPT
PAGE #: 4

APPLICANT: TAEKWANG INDUSTRIAL CO., LTD.
 FCC ID: BESTKP-910A (BASE)
 NAME OF TEST: RADIATION INTERFERENCE
 RULES PART NO.: 15.249
 REQUIREMENTS: Carrier frequency will not exceed 94.0 dBuV/m

	FREQUENCY MHz	LEVEL dBuV/M
902- 928	MHz:	54.0 dBuV/M
ABOVE 960	MHz:	54.0 dBuV/M

BASE FREQUENCY RANGE: 902.10-905.00 MHz

TEST DATA:

EMISSION FREQUENCY MHz	METER READING AT 3 METERS dBuV	COAX LOSS dB	ANTENNA CORRECTION FACTOR	FIELD STRENGTH dBuV/m@3m	MARGIN dB	ANT. POL.
BASE TUNED FREQUENCY 903.00MHz						
903.00	55.00	2.90	24.19	82.09	11.91	H
1806.20	15.70	1.00	27.22	43.93	10.07	V
2709.10	10.70	1.14	29.77	41.61	12.39	V
3612.20	19.00	1.27	32.03	52.30	1.70	V
4515.20	17.60	1.41	33.58	52.59	1.41	V
5418.30	14.70	1.54	34.60	50.84	3.16	V
BASE TUNED FREQUENCY 904.74MHz						
904.74	59.70	2.90	24.18	86.78	7.22	V
1809.50	15.10	1.00	27.24	43.34	10.66	H
2714.30	11.00	1.14	29.79	41.92	12.08	V
3619.00	19.70	1.27	29.85	53.02	0.78	V
4523.70	18.10	1.41	33.59	53.10	0.90	V
5428.50	14.30	1.54	34.61	50.45	3.55	V

SAMPLE CALCULATION: $FSdBuV/m = MR(dBuV) + ACFdB$.

METHOD OF MEASUREMENT: The procedure used was ANSI STANDARD. Measurements were made at Timco Engineering, Inc. 849 N.W. State Road 45, Newberry, FL 32669.

TEST RESULTS: The unit DOES meet the FCC requirements.

PERFORMED BY: _____ DATE: APRIL 17, 2000

REPORT #: T:\CUS\T\TIC\TIC127A0\TIC127A0.RPT
 PAGE #: 5

APPLICANT: TAEKWANG INDUSTRIAL CO., LTD.

FCC ID: BESTKP-910A (HANDSET)

NAME OF TEST: RADIATION INTERFERENCE PAGE 1 OF 1

RULES PART NO.: 15.249

REQUIREMENTS: Carrier frequency will not exceed 94.0 dBuV/m

	FREQUENCY	LEVEL
	MHz	dBuV/M
902- 928	MHz:	54.0 dBuV/M
ABOVE 960	MHz:	54.0 dBuV/M

HANDSET FREQUENCY RANGE: 924.00-927.00 MHz

TEST DATA:

EMISSION FREQUENCY MHz	METER READING AT 3 METERS dBuV	COAX LOSS dB	ANTENNA CORRECTION FACTOR	FIELD STRENGTH dBuV/m@3m	MARGIN dB	ANT. POL.
HANDSET TUNED FREQUENCY 925.56MHz						
925.56	58.50	2.90	24.10	85.50	8.50	V
1851.10	14.20	1.01	27.40	42.61	11.39	V
2776.60	2.80	1.15	29.94	33.89	20.11	V
3702.20	8.70	1.29	32.26	42.24	11.76	H
4627.70	1.60	1.42	33.71	36.73	17.27	H
5553.30	3.10	1.56	34.75	39.41	14.59	H
HANDSET TUNED FREQUENCY 927.00MHz						
927.00	56.00	2.90	24.12	83.02	10.98	V
1854.50	10.60	1.01	27.42	39.03	14.97	V
2781.70	2.30	1.15	29.95	33.40	20.60	V
3709.00	7.90	1.29	32.27	41.46	12.54	V
4636.00	3.50	1.43	33.72	38.64	15.36	H
5563.00	7.40	1.57	34.76	43.72	10.28	V

SAMPLE CALCULATION: $FSdBuV/m = MR(dBuV) + ACFdB$.

METHOD OF MEASUREMENT: The procedure used was ANSI STANDARD C63.4-1992 with the following exception: the unit was operated into its own antenna with the antenna at a height of four feet. Measurements were made at Timco Engineering, Inc. 849 N.W. State Road 45, Newberry, FL 32669.

TEST RESULTS: The unit DOES meet the FCC requirements.

PERFORMED BY: _____ DATE: APRIL 17, 2000

REPORT #: T:\CUS\T\TIC\TIC127A0\TIC127A0.RPT
PAGE #: 6

APPLICANT: TAEKWANG INDUSTRIAL CO., LTD.

FCC ID: BESTKP-910A

NAME OF TEST: Occupied Bandwidth

RULES PART NO.: 15.233

REQUIREMENTS: The field strength of any emissions appearing between the band edges and up to 10 kHz above and below the band edges shall be attenuated at least 26 dB below the level of the unmodulated carrier or to the general limits of 15.209, whichever permits the higher emission levels.

THE GRAPHS IN EXHIBITS REPRESENT THE EMISSIONS TAKEN FOR THIS DEVICE.

METHOD OF MEASUREMENT: A small sample of the transmitter output was fed into the spectrum analyzer and the above photo was taken. The vertical scale is set to -10 dBm per division. The horizontal scale is set to 5 kHz per division.

TEST RESULTS: The unit DOES meet the FCC requirements.

PERFORMED BY: _____ APRIL 17, 2000

APPLICANT: TAEKWANG INDUSTRIAL CO., LTD.

FCC ID: BESTKP-910A

REPORT #: T:\CUS\T\TIC\TIC127A0\TIC127A0.RPT

PAGE #: 7

APPLICANT: TAEKWANG INDUSTRIAL CO., LTD.

FCC ID: BESTKP-910A

NAME OF TEST: POWER LINE CONDUCTED INTERFERENCE

RULES PART NUMBER: 15.207

MINIMUM REQUIREMENTS:	FREQUENCY MHz	LEVEL uV
	0.450-30	250

TEST PROCEDURE: ANSI STANDARD C63.4-1992

THE HIGHEST EMISSION READ FOR LINE 1 WAS 20.9uV @ 28.82mhz.

THE HIGHEST EMISSION READ FOR LINE 2 WAS 14.8uV @ 28.82mhz.

THE GRAPHS IN EXHIBITS 15-16 REPRESENT THE EMISSIONS READ FOR POWERLINE CONDUCTED FOR THIS DEVICE.

TEST RESULTS: Both lines were observed. The measurements indicate that the unit DOES appear to meet the FCC requirements for this class of equipment.

PERFORMED BY: _____ DATE: APRIL 17, 2000

APPLICANT: TAEKWANG INDUSTRIAL CO., LTD.

FCC ID: BESTKP-910A

REPORT #: T:\CUS\T\TIC\TIC127A0\TIC127A0.RPT

PAGE #: 8