

Specific Absorption Rate (SAR) Test Report
for

Shintom Co., Ltd.
on the
TriBand Cellular Phone
Model Number: GDX2002
FCC ID: BFYM5030

Test Report: 30264981
Date of Report: June 17, 2002

Job #: 3026498
Date of Test: June 4 to 5, 2002

Total No of Pages Contained in this Report: 62



Warnock Hersey



Tested by:		Suresh Kondapalli
Reviewed by:		David Chernomordik, Ph.D., EMC Technical Manager

All services undertaken are subject to the following general policy: Reports are submitted for exclusive use of the client to whom they are addressed. Their significance is subject to the adequacy and representative character of the samples and to the comprehensiveness of the tests, examinations or surveys made. This report shall not be reproduced except in full, without written consent of Intertek Testing Services, NA Inc.

emc



Intertek Testing Services NA, Inc.

1365 Adams Court, Menlo Park, CA 94025

Telephone 650-463-2900 Fax 650-463-2910 Home Page www.etlsemko.com



TABLE OF CONTENTS

STATEMENT OF COMPLIANCE.....	3
1.0 JOB DESCRIPTION	4
1.1 Client Information	4
1.2 Equipment under test (EUT)	4
1.3 Test Plan Reference	5
1.4 System Test Configuration	6
1.4.1 System Block Diagram & Support equipment	6
1.4.2 Test Position for Brain	7
1.4.3 Test Position for Muscle.....	9
1.4.4 Test Condition	10
1.5 Modifications required for compliance.....	10
1.6 Additions, deviations and exclusions from standards.....	10
2.0 SAR EVALUATION.....	11
2.1 SAR Limits.....	11
2.2 Configuration Photographs	12
2.3 System Verification	21
2.4 Evaluation Procedures	21
2.5 Test Results	22
3.0 TEST EQUIPMENT.....	25
3.1 Equipment List	25
3.2 Tissue Simulating Liquid	26
3.3 E-Field Probe Calibration	27
3.4 Measurement Uncertainty	28
3.5 Measurement Tractability	28
4.0 WARNING LABEL INFORMATION - USA.....	29
5.0 REFERENCES	30
5.0 DOCUMENT HISTORY.....	31
APPENDIX A - SAR Evaluation Data.....	32
APPENDIX B - E-Field Probe Calibration Data.....	50

Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

STATEMENT OF COMPLIANCE

The Shintom Co., Ltd., sample device, model # GDX2002, FCC ID: Not Labeled was evaluated in accordance with the requirements for compliance testing defined in FCC OET Bulletin 65, Supplement C (Edition 01-01). Testing was performed at the Intertek Testing Services facility in Menlo Park, California.

For the evaluation, the dosimetric assessment system DASY3 was used. The phantom employed was the "Generic Twin Phantom". The total uncertainty for the evaluation of the spatial peak SAR values averaged over a cube of 1g tissue mass had been assessed for this system to be $\pm 23.5\%$.

The device was tested at their maximum output power declared by the Shintom Co., Ltd..

In summary, the maximum spatial peak SAR value for the Sample device averaged over 1g for left-hand, right-hand and body- worn usage was found to be:

Phantom	SAR_{1g}, mW/g
Right-hand Tilt Position	1.25
Body worn Position	1.28

In conclusion, the tested Sample device was found to be in compliance with the requirements defined in OET Bulletin 65, Supplement C (Edition 01-01) for head and body configurations.

Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

1.0 JOB DESCRIPTION

1.1 Client Information

The GDX2002 has been tested at the request of:

Company: Shintom Co., Ltd.
1-19-20 Shin-Yokohama, Kohoku-ku
Yokohama, Yokohama 222-0033
Japan

Name of contact: Mr. Shuichi Oomomo
Telephone: +81-45-476-3541
Fax: +81-45-476-3540

1.2 Equipment under test (EUT)

Product Descriptions:

Equipment	TriBand Celluar Phone		
Trade Name	Matsushita Electric Works, Ltd.	P/N.	GDX2002
FCC ID	BFYM5030	S/N No.	Not Labeled
Category	Portable	RF Exposure	Uncontrolled Environment
Frequency Band	1850 - 1910 MHz	System	GSM/GPRS

EUT Antenna Description			
Type	Monopole	Configuration	Fixed
Dimensions	16.7 mm	Gain	0 dBi
Location	Right Side		

Use of Product : Wireless communication

Manufacturer: Shintom Co., Ltd.

Production is planned: Yes, No

EUT receive date: June 4, 2002

EUT received condition: Good working condition prototype. As declared by Shintom Co., Ltd. the device tested is identical to the production units.

Test start date: June 4, 2002

Test end date: June 5, 2002

Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

1.3 Test Plan Reference

FCC Rule: Part 2.1093, FCC OET Bulletin 65, Supplement C (Edition 01-01)


Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

1.4 System Test Configuration

1.4.1 System Block Diagram & Support equipment

The diagram shown below details test configuration of the equipment under test.



No Support Equipment was used. The test sample was operated in a test mode that allows control of the transmitter without the need to place actual phone calls. For the purposes of this test the device is commanded to test mode and manually set to the proper channel, transmitter power levels and transmit mode of operation. The device was then placed in the SAR Measurement System with a fully charged battery.

Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

1.4.2 Test Position for Brain

The GDX2002 was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in C95.1 (1992) and Supplement C of OET 65 (2001). The GDX2002 was placed against the head phantom in 2 test positions as detailed in Figures 1 and 2 below.

Test Configuration for SAR




Figure 1 – Phone position 1, “cheek” or “touch” position. The reference points for the right ear (RE), left ear (LE) and mouth (M), which define the reference plane for phone positioning, are indicated.



Figure 2 – Phone position 2, “tilted” position. The reference points for the right ear (RE), left ear (LE) and mouth (M), which define the reference plane for phone positioning, are indicated.

Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

The positioning procedure is described below.

The EUT was positioned in a normal operating position with the “test device reference point” located along the “vertical centerline” on the front of the device aligned to the “ear reference point”. The “test device reference point” is located at the same level as the center of the earpiece region. The “vertical centerline” is bisecting the front surface of the handset at its top and bottom edges. A “ear reference point” is located on the outer surface of the head phantom on each ear spacer. It is located 1.5 cm above the center of the ear canal entrance in the “phantom reference plane” defined by the three lines joining the center of each “ear reference point” (left and right) and the tip of the mouth.

The EUT is initially positioned with the earpiece region pressed against the ear spacer of a head phantom in “initial ear position”. The “test device reference point” was aligned to the “ear reference point” on the head phantom and the “vertical centerline” was aligned to the “phantom reference plane”. While maintaining these three alignments, the body of the handset is gradually adjusted to each of the following positions for evaluating SAR:

1. “Cheek/Touch Position” – the device is brought toward the mouth of the head phantom by pivoting against the “ear reference point”. This test position is established:
 - i) When any point on the display, keypad or mouthpiece portions of the handset is in contact with the phantom.

or
 - ii) When any portion of a foldout, sliding or similar keypad cover opened to its intended self-adjusting normal use position is in contact with the cheek or mouth of the phantom.
2. “Ear/Tilt Position” – With the handset aligned in the “Cheek/Touch Position”:
 - i) If the earpiece of the handset is not in full contact with the phantom’s ear spacer (in the “Cheek/Touch position”) and the peak SAR location for the “Cheek/Touch” position is located at the ear spacer region or corresponds to the earpiece region of the handset, the device is returned to the “initial ear position” by rotating it away from the mouth until the earpiece is in full contact with the ear spacer.

otherwise
 - ii) The handset is moved (translated) away from the cheek perpendicular to the line passes through both “ear reference points” for approximate 2-3 cm. While it is in this position, the handset is tilted away from the mouth with respect to the “test device reference point” by 15°. After the tilt, it is then moved (translated) back toward the head perpendicular to the line passes through both “ear reference points” until the device touches the phantom or the ear spacer. If the antenna touches the head first, the positioning process is repeated with a tilt angle less than 15° so that the device and its antenna would touch the phantom simultaneously.

Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

1.4.3 Test Position for Muscle

The GDX2002 was placed against the flat phantom in the test position as detailed in Figure 3 below. As the belt clip and holster were not supplied with the device, the GDX2002 was positioned 2.5mm from phantom (worst case position).




Figure 3 – Intended use position for Muscle SAR (Body Worn)

Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

1.4.4 Test Condition

During tests, the worst case data (max RF coupling) was determined with following conditions:

EUT Antenna	Fixed length	Orientation	On the top
Usage	Right hand, Left hand and body worn.	Distance between antenna and the phantom surface:	<u>Left Side:</u> 12.6 mm, tilt position 15.2 mm, check position <u>Right Side:</u> 17.7 mm, tilt position 23.9 mm, check <u>position</u> <u>7.7 mm, body worn position</u>
Simulating human Body/hand	Body	EUT Battery	LI-ION battery
Conducted Peak Output Power		Frequency MHz	Output Power dBm
		1850	28.3
		1880	28.4
		1910	28.4

The spatial peak SAR values were accessed for lowest, middle and highest operating channels defined by the manufacturer.

Antenna port power measurement was performed, with the HP 435A power meter, before and after the SAR tests to ensure that the GDX2002 operated at the highest power level.

1.5 Modifications required for compliance

No modifications were implemented by Intertek Testing Services.

1.6 Additions, deviations and exclusions from standards

No additions, deviations or exclusions have been made from standard.

Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

2.0 SAR EVALUATION

2.1 SAR Limits

The following FCC limits for SAR apply to devices operate in General Population/Uncontrolled Exposure environment:

EXPOSURE (General Population/Uncontrolled Exposure environment)	SAR (W/kg)
Average over the whole body	0.08
Spatial Peak (1g)	1.60
Spatial Peak for hands, wrists, feet and ankles (10g)	4.00


Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

2.2 Configuration Photographs

SAR Measurement Test Setup

Left Cheek



Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

2.2 Configuration Photographs (Continued)

SAR measurement Test Setup

Left Tilt




Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

2.2 Configuration Photographs (Continued)

SAR measurement Test Setup

Right Cheek




Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

2.2 Configuration Photographs (Continued)

SAR measurement Test Setup

Right Tilt




Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

2.2 Configuration Photographs (Continued)

SAR measurement Test Setup

Body-worn Position (2.5mm from Phantom)



Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

2.2 Configuration Photographs (Continued)

EUT Photo



Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

2.2 Configuration Photographs (Continued)

EUT Photo



Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

2.2 Configuration Photographs (Continued)

EUT Photo



Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

2.2 Configuration Photographs (Continued)

EUT Photo



Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

2.3 System Verification

Prior to the assessment, the system was verified to the $\pm 10\%$ of the specifications by using the system validation kit. The validation was performed at 1800 MHz.

Validation kit	Targeted SAR _{1g} (mW/g)	Measured SAR _{1g} (mW/g)	Plot #
D1800V2, S/N #: 224	9.77	9.91	16

2.4 Evaluation Procedures

The SAR evaluation was performed with the following procedures:

- a. SAR was measured at a fixed location above the reference point and used as a reference value for the assessing the power drop.
- b. The SAR distribution at the exposed side of the flat Phantom was measured at a distance of 30 mm from the inner surface of the shell. The area covered the entire dimension of the head and the horizontal grid spacing was 20 mm x 20 mm. Based on this data, the area of the maximum absorption was determined by spline interpolation.
- c. Around this point, a volume of 32 mm x 32 mm x 34 mm was assessed by measuring 5 x 5 x 7 points. On the basis of this data set, the spatial peak SAR value was evaluated with the following procedure:
 - i) The data at the surface were extrapolated, since the center of the dipoles is 2.7 mm away from the tip of the probe and the distance between the surface and the lowest measurement point is 1.6 mm. The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in Z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip.
 - ii) The maximum interpolated value was searched with a straightforward algorithm. Around this maximum, the SAR values averaged over the spatial volumes (1g or 10g) were computed using the 3-D spline interpolation algorithm. The 3-D spline is composed of three one-dimensional splines with the “Not a knot” condition (in x, y and z directions). The volume was integrated with the trapezoidal algorithm. 1000 points (10 x 10 x 10) were interpolated to calculate the average.
 - iii) All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
- d. Re-measurements of the SAR value at the same location as in step a. above. If the value changed by more than 5 %, the evaluation was repeated.

Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

2.5 Test Results

The results on the following page(s) were obtained when the device was tested in the condition described in this report. Detail measurement data and plots, which reveal information about the location of the maximum SAR with respect to the device, are reported in Appendix A.

Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

Measurement Results

Trade Name:	Shintom	Model No.:	GDX2002
Serial No.:	Not Labeled	Test Engineer:	Suresh Kondapalli

Brain 1800 MHz Band					
Ambient Temperature		23.5 °C		Relative Humidity	55 %
Liquid Temperature		$22^{\circ}\text{C} \pm 0.5^{\circ}\text{C}$		Liquid depth	14.8 cm
Test Signal Source		Test Mode		Signal Modulation	GSM
Output Power Before SAR Test		See Page 6		Output Power After SAR Test	Changes within $\pm 0.1\text{dB}$
Test Duration		20 Min. each test		Number of Battery Change	New battery for every scan
Plot No	Frequency MHz	Operating Mode	Crest Factor	Position	
1	1850	GSM	8	Left Hand, Cheek Position	
2	1850	GSM	8	Left Hand, Tilt Position	
3	1880	GSM	8	Left Hand, Cheek Position	
4	1880	GSM	8	Left Hand, Tilt Position	
5	1910	GSM	8	Left Hand, Cheek Position	
6	1910	GSM	8	Left Hand, Tilt Position	
7	1850	GSM	8	Right Hand, Cheek Position	
8	1850	GSM	8	Right Hand, Tilt Position	
9	1880	GSM	8	Right Hand, Cheek Position	
10	1880	GSM	8	Right Hand, Tilt Position	
11	1910	GSM	8	Right Hand, Cheek Position	
12	1910	GSM	8	Right Hand, Tilt Position	

Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

Muscle 1800 MHz Band					
Ambient Temperature		23.5 °C	Relative Humidity		55 %
Liquid Temperature		22°C ± 0.5 °C	Liquid depth		14.8 cm
Test Signal Source		Test Mode	Signal Modulation		GSM
Output Power Before SAR Test		See Page 6	Output Power After SAR Test		Changes within ±0.1dB
Test Duration		20 Min. each test	Number of Battery Change		New battery for every scan
Plot No	Frequency MHz	Operating Mode	Crest Factor	Position	Measured SAR _{1g} (mW/g)
13	1850	GSM	8	2.5 mm from Phantom	1.28
14	1880	GSM	8	2.5 mm from Phantom	1.27
15	1910	GSM	8	2.5 mm from Phantom	1.04
17	1880	GSM	8	Z Scan	

Dipole, System Verification					
Frequency MHz	Operating Mode	Crest Factor	Measured SAR _{1g} (mW/g)	Measured SAR _{10g} (mW/g)	Plot Number
1800	CW	1	9.91	5.13	16

Note: a) Worst case data were reported
b) Duty cycle factor included in the measured SAR data
c) Uncertainty of the system is not included

Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

3.0 TEST EQUIPMENT

3.1 Equipment List

The Specific Absorption Rate (SAR) tests were performed with the SPEAG model DASY 3 automated near-field scanning system, which is a package, optimized for dosimetric evaluation of mobile radios [3].

The following major equipment/components were used for the SAR evaluations:

SAR Measurement System			
EQUIPMENT	SPECIFICATIONS	S/N #	LAST CAL. DATE
Robot	Stäubi RX60L	597412-01	N/A
	Repeatability: $\pm 0.025\text{mm}$ Accuracy: 0.806×10^{-3} degree Number of Axes: 6		
E-Field Probe	ET3DV5	1333	04/13/01
	Frequency Range: 10 MHz to 3 GHz Linearity: ± 0.2 dB Directivity: ± 0.1 dB in brain tissue Probe outer diameter: 6.5 mm Length: 34.5 cm Distance between the probe tip and the dipole center: 2.7 mm		
Data Acquisition	DAE3	317	N/A
	Measurement Range: $1\mu\text{V}$ to $>200\text{mV}$ Input offset Voltage: $< 1\mu\text{V}$ (with auto zero) Input Resistance: 200 M		
Phantom	Generic Twin V3.0	N/A	N/A
	Type: Generic Twin, Homogenous Shell Material: Fiberglass Thickness: 2 ± 0.1 mm Capacity: 20 liter Ear spacer: 4 mm (between EUT ear piece and tissue simulating liquid)		
Device holder	Non-conductive holder supplied with DASY3, dielectric constant less than 5.0	N/A	N/A
Simulated Tissue	Mixture	N/A	06/04/02
	Please see section 6.2 for details		
Power Meter	HP 8900D w/ 84811A sensor	3607U00673	08/08/01
	Frequency Range: 100kHz to 18 GHz Power Range: $300\mu\text{W}$ to 3W		

Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

3.2 Tissue Simulating Liquid

Brain Ingredients Frequency (1800 MHz)	
Water	52.90 %
Salt	0.181%
DGBE Diethylene Glycol	44.92%
Tonit X-100 (Polyethylene Glycol Mono) Ether	0.1 %

The dielectric parameters were verified prior to assessment using the HP 85070A dielectric probe kit and the HP 8753C network Analyzer. The dielectric parameters were:

Frequency (MHz)	ϵ_r *	σ *(mho/m)	ρ **(kg/m³)
1800	42.2	1.40	1000

* Worst case uncertainty of the HP 85070A dielectric probe kit

** Worst case assumption

Muscle Ingredients Frequency (1800 MHz)	
DGBE Dilethylene Glycol	44.92%
Toniton X-100 (Polyethylene Glycol Mono) Ether	0.1%
Salt	0.18%
Water	54.8%

The dielectric parameters were verified prior to assessment using the HP 85070A dielectric probe kit and the HP 8753C network Analyzer. The dielectric parameters were:

Frequency (MHz)	ϵ_r *	σ *(mho/m)	ρ **(kg/m³)
1800	55.8	1.43	1000

* Worst case uncertainty of the HP 85070A dielectric probe kit

** Worst case assumption

Note: The amounts of each ingredient specified in the tables are not the exact amounts of the final test solution. The final test solution was adjusted by adding small amounts of water, sugar, and/or salt to calibrate the solution to meet the proper dielectric parameters.

Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

3.3 E-Field Probe Calibration

Probes were calibrated by the manufacturer in the TEM cell ifi 110. To ensure consistency, a strict protocol was followed. The conversion factor (ConF) between this calibration and the measurement in the tissue simulation solution was performed by comparison with temperature measurement and computer simulations. Probe calibration factors are included in Appendix C.

Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

3.4 Measurement Uncertainty

The uncertainty budget has been determined for the DASY3 measurement system according to the NIS81 [5] and the NIST 1297 [6] documents and is given in the following table. The extended uncertainty (K=2) was assessed to be 23.5 %

UNCERTAINTY BUDGET				
Uncertainty Description	Error	Distrib.	Weight	Std.Dev.
Probe Uncertainty				
Axial isotropy	±0.2 dB	U-shape	0.5	±2.4 %
Spherical isotropy	±0.4 dB	U-shape	0.5	±4.8 %
Isotropy from gradient	±0.5 dB	U-shape	0	
Spatial resolution	±0.5 %	Normal	1	±0.5 %
Linearity error	±0.2 dB	Rectang.	1	±2.7 %
Calibration error	±3.3 %	Normal	1	±3.3 %
SAR Evaluation Uncertainty				
Data acquisition error	±1 %	Rectang.	1	±0.6 %
ELF and RF disturbances	±0.25 %	Normal	1	±0.25 %
Conductivity assessment	±10 %	Rectang.	1	±5.8 %
Spatial Peak SAR Evaluation Uncertainty				
Extrapol boundary effect	±3 %	Normal	1	±3 %
Probe positioning error	±0.1 mm	Normal	1	±1 %
Integrat. and cube orient	±3 %	Normal	1	±3 %
Cube shape inaccuracies	±2 %	Rectang.	1	±1.2 %
Device positioning	±6 %	Normal	1	±6 %
Combined Uncertainties				±11.7 %

3.5 Measurement Tractability

All measurements described in this report are traceable to National Institute of Standards and Technology (NIST) standards or appropriate national standards.

Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

4.0 WARNING LABEL INFORMATION - USA

See Users Manual.

Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

5.0 REFERENCES

- [1] ANSI, *ANSI/IEEE C95.1-1991: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3kHz to 300 GHz*, The Institute of electrical and Electronics Engineers, Inc., New York, NY 10017, 1992
- [2] Federal Communications Commission, “Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields”, OET Bulletin 65, FCC, Washington, D.C. 20554, 1997
- [3] Thomas Schmid, Oliver Egger, and Niels Kuster, “Automated E-field scanning system for dosimetric assessments”, *IEEE Transaction on Microwave Theory and Techniques*, vol. 44, pp. 105-113, Jan. 1996.
- [4] Niels Kuster, Ralph Kastle, and Thomas Schmid, “Dosimetric evaluation of mobile communications equipment with known precision”, *IEICE Transactions on Communications*, vol. E80-B, no. 5, pp.645-652, May 1997.
- [5] NIS81, NAMAS, “The treatment of uncertainty in EMC measurement”, Tech. Rep., NAMAS Executive, National Physical Laboratory, Teddington, Middlesex, England, 1994.
- [6] Barry N. Taylor and Chris E. Kuyatt, “Guidelines for evaluating and expressing the uncertainty of NIST measurement results”, Tech. Rep., National Institute of Standards and Technology, 1994.

Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

5.0 DOCUMENT HISTORY

Revision/ Job Number	Writer Initials	Date	Change
1.0 /3024181	SS	June 17, 2002	Original document

Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002


APPENDIX A - SAR Evaluation Data

Please note that the graphical visualization of the phone position onto the SAR distribution gives only limited information on the current distribution of the device, since the curvature of the head results in graphical distortion. Full information can only be obtained either by H-field scans in free space or SAR evaluation with a flat phantom.

Powerdrift is the measurement of power drift of the device over one complete SAR scan.


Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002




Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002




Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002




Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002




Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002




Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002




Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002




Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002




Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002




Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002




Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002




Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002




Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002




Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002




Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002




Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002



Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002



Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

APPENDIX B - E-Field Probe Calibration Data

See attached.

Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

**Schmid & Partner
Engineering AG**

Zeughausstrasse 43, 8004 Zurich, Switzerland, Phone +41 1 245 97 00, Fax +41 1 245 97 79

Calibration Certificate

Dosimetric E-Field Probe

Type:

ET3DV6

Serial Number:

1576

Place of Calibration:

Zurich

Date of Calibration:

February 27, 2002

Calibration Interval:

12 months

Schmid & Partner Engineering AG hereby certifies, that this device has been calibrated on the date indicated above. The calibration was performed in accordance with specifications and procedures of Schmid & Partner Engineering AG.

Wherever applicable, the standards used in the calibration process are traceable to international standards. In all other cases the standards of the Laboratory for EMF and Microwave Electronics at the Swiss Federal Institute of Technology (ETH) in Zurich, Switzerland have been applied.

Calibrated by:

Mark Kj-

Approved by:

N. Nels

Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

**Schmid & Partner
Engineering AG**

Zeughausstrasse 43, 8004 Zurich, Switzerland, Telephone +41 1 245 97 00, Fax +41 1 245 97 79

Probe ET3DV6

SN:1576

Manufactured:	April 6, 2001
Last calibration:	April 20, 2001
Recalibrated:	February 27, 2002

Calibrated for System DASY3

Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

ET3DV6 SN:1576

February 27, 2002

DASY3 - Parameters of Probe: ET3DV6 SN:1576

Sensitivity in Free Space

NormX	1.77 $\mu\text{V}/(\text{V}/\text{m})^2$
NormY	1.81 $\mu\text{V}/(\text{V}/\text{m})^2$
NormZ	1.76 $\mu\text{V}/(\text{V}/\text{m})^2$

Diode Compression

DCP X	98	mV
DCP Y	98	mV
DCP Z	98	mV

Sensitivity in Tissue Simulating Liquid

Head	900 MHz	$\epsilon_r = 41.5 \pm 5\%$	$\sigma = 0.97 \pm 5\% \text{ mho/m}$
Head	835 MHz	$\epsilon_r = 41.5 \pm 5\%$	$\sigma = 0.90 \pm 5\% \text{ mho/m}$
	ConvF X	7.0 $\pm 9.5\% \text{ (k=2)}$	Boundary effect:
	ConvF Y	7.0 $\pm 9.5\% \text{ (k=2)}$	Alpha 0.30
	ConvF Z	7.0 $\pm 9.5\% \text{ (k=2)}$	Depth 2.51
Head	1800 MHz	$\epsilon_r = 40.0 \pm 5\%$	$\sigma = 1.40 \pm 5\% \text{ mho/m}$
Head	1800 MHz	$\epsilon_r = 40.0 \pm 5\%$	$\sigma = 1.40 \pm 5\% \text{ mho/m}$
	ConvF X	5.4 $\pm 9.5\% \text{ (k=2)}$	Boundary effect:
	ConvF Y	5.4 $\pm 9.5\% \text{ (k=2)}$	Alpha 0.45
	ConvF Z	5.4 $\pm 9.5\% \text{ (k=2)}$	Depth 2.30

Boundary Effect

Head 900 MHz Typical SAR gradient: 5 % per mm

Probe Tip to Boundary	1 mm	2 mm
SAR _{be} [%] Without Correction Algorithm	7.6	4.3
SAR _{be} [%] With Correction Algorithm	0.3	0.5

Head 1800 MHz Typical SAR gradient: 10 % per mm

Probe Tip to Boundary	1 mm	2 mm
SAR _{be} [%] Without Correction Algorithm	9.7	6.6
SAR _{be} [%] With Correction Algorithm	0.2	0.3

Sensor Offset

Probe Tip to Sensor Center	2.7	mm
Optical Surface Detection	1.9 ± 0.2	mm


Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

ET3DV6 SN:1576

February 27, 2002

Receiving Pattern (ϕ), $\theta = 0^\circ$




Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030


Date of Test: June 4 to 5, 2002

ET3DV6 SN:1576

February 27, 2002



Isotropy Error (ϕ), $\theta = 0^\circ$



Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030


Date of Test: June 4 to 5, 2002

ET3DV6 SN:1576

February 27, 2002

Frequency Response of E-Field

(TEM-Cell:ifi110, Waveguide R22)





Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

ET3DV6 SN:1576

February 27, 2002




Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

ET3DV6 SN:1576

February 27, 2002

Conversion Factor Assessment



Head	900 MHz	$\epsilon_r = 41.5 \pm 5\%$	$\sigma = 0.97 \pm 5\% \text{ mho/m}$
Head	835 MHz	$\epsilon_r = 41.5 \pm 5\%$	$\sigma = 0.90 \pm 5\% \text{ mho/m}$
ConvF X	7.0 $\pm 9.5\%$ (k=2)		Boundary effect:
ConvF Y	7.0 $\pm 9.5\%$ (k=2)		Alpha 0.30
ConvF Z	7.0 $\pm 9.5\%$ (k=2)		Depth 2.51

Head	1800 MHz	$\epsilon_r = 40.0 \pm 5\%$	$\sigma = 1.40 \pm 5\% \text{ mho/m}$
Head	1900 MHz	$\epsilon_r = 40.0 \pm 5\%$	$\sigma = 1.40 \pm 5\% \text{ mho/m}$
ConvF X	5.4 $\pm 9.5\%$ (k=2)		Boundary effect:
ConvF Y	5.4 $\pm 9.5\%$ (k=2)		Alpha 0.45
ConvF Z	5.4 $\pm 9.5\%$ (k=2)		Depth 2.30


Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

ET3DV6 SN:1576

February 27, 2002

Conversion Factor Assessment



Head 1750 MHz $\epsilon_r = 40.0 \pm 5\%$ $\sigma = 1.40 \pm 5\% \text{ mho/m}$

ConvF X	5.4 $\pm 8.9\%$ ($k=2$)	Boundary effect:	
ConvF Y	5.4 $\pm 8.9\%$ ($k=2$)	Alpha	0.45
ConvF Z	5.4 $\pm 8.9\%$ ($k=2$)	Depth	2.27


Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

ET3DV6 SN:1576

February 27, 2002

Conversion Factor Assessment



Body 915 MHz $\epsilon_r = 55.0 \pm 5\%$ $\sigma = 1.06 \pm 5\% \text{ mho/m}$

ConvF X	6.7 $\pm 8.9\%$ (k=2)	Boundary effect:	
ConvF Y	6.7 $\pm 8.9\%$ (k=2)	Alpha	0.45
ConvF Z	6.7 $\pm 8.9\%$ (k=2)	Depth	2.01

Body 835 MHz $\epsilon_r = 55.2 \pm 5\%$ $\sigma = 0.97 \pm 5\% \text{ mho/m}$

ConvF X	6.7 $\pm 8.9\%$ (k=2)	Boundary effect:	
ConvF Y	6.7 $\pm 8.9\%$ (k=2)	Alpha	0.34
ConvF Z	6.7 $\pm 8.9\%$ (k=2)	Depth	2.37


Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

ET3DV6 SN:1576

February 27, 2002

Conversion Factor Assessment



Body 1750 MHz $\epsilon_r = 53.3 \pm 5\%$ $\sigma = 1.52 \pm 5\% \text{ mho/m}$

ConvF X	$5.1 \pm 8.9\% \text{ (k=2)}$	Boundary effect:
ConvF Y	$5.1 \pm 8.9\% \text{ (k=2)}$	Alpha 0.51
ConvF Z	$5.1 \pm 8.9\% \text{ (k=2)}$	Depth 2.31

Body 1880 MHz $\epsilon_r = 53.3 \pm 5\%$ $\sigma = 1.52 \pm 5\% \text{ mho/m}$

ConvF X	$4.8 \pm 8.9\% \text{ (k=2)}$	Boundary effect:
ConvF Y	$4.8 \pm 8.9\% \text{ (k=2)}$	Alpha 0.63
ConvF Z	$4.8 \pm 8.9\% \text{ (k=2)}$	Depth 2.10

Shintom Co., Ltd., Model No: GDX2002
FCC ID: BFYM5030

Date of Test: June 4 to 5, 2002

ET3DV6 SN:1576

February 27, 2002

Deviation from Isotropy in HSL

Error (θ, ϕ), $f = 900$ MHz

