

FCC PART 15 SUBPART C MEASUREMENT AND TEST REPORT

For

Star Light Electronics Co., Ltd.

**5/F., Shing Dao Industrial Building, 232 Aberdeen Main Road, Aberdeen,
Hong Kong**

E.U.T.: Shower BT Speaker

Model Name: SMI438BT, SP-3397

Brand Name: SOUNDX, DERENS

FCC ID: BGRSMI438BT

Report Number: NTC1305572F

Test Date(s): May 13, 2013 to June 05, 2013

Report Date(s): June 07, 2013

Prepared by

Dongguan NTC Co., Ltd.

**Building D, Gaosheng Science and Technology Park, Hongtu Road,
Nancheng District, Dongguan City, Guangdong Province, China**

Tel: +86-769-22022444

Fax: +86-769-22022799

Prepared By

Approved & Authorized Signer


Rose Hu / Engineer


Sunm Lv / Q.A. Director

Note: This test report is for the customer shown above and their specific product only. It may not be duplicated or used in part without prior written consent from Dongguan NTC Co., Ltd. The test results referenced from this report are relevant only to the sample tested.

Table of Contents

1. GENERAL INFORMATION	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST	4
1.2 RELATED SUBMITTAL(S) / GRANT (S)	5
1.3 TEST METHODOLOGY	5
1.4 EQUIPMENT MODIFICATIONS	5
1.5 SUPPORT DEVICE	5
1.6 TEST FACILITY AND LOCATION	5
1.7 SUMMARY OF TEST RESULTS	6
2. SYSTEM TEST CONFIGURATION	7
2.1 EUT CONFIGURATION	7
2.2 SPECIAL ACCESSORIES	7
2.3 DESCRIPTION OF TEST MODES	7
2.4 EUT EXERCISE	7
3. RADIATED EMISSION TEST	8
3.1 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	8
3.2 MEASUREMENT PROCEDURE	9
3.3 LIMIT	10
3.4 MEASUREMENT RESULTS	11
4. CHANNEL SEPARATION TEST	15
4.1 MEASUREMENT PROCEDURE	15
4.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	15
4.3 MEASUREMENT RESULTS	15
5. 20DB BANDWIDTH	21
5.1 MEASUREMENT PROCEDURE	21
5.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	21
5.3 MEASUREMENT RESULTS	21
6. HOPPING CHANNEL NUMBER	27
6.1 MEASUREMENT PROCEDURE	27
6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	27
6.3 MEASUREMENT RESULTS	27
7. TIME OF OCCUPANCY (DWELL TIME)	29
7.1 MEASUREMENT PROCEDURE	29
7.2 MEASUREMENT RESULTS	29



8. MAXIMUM PEAK OUTPUT POWER 35

8.1 MEASUREMENT PROCEDURE 35

8.2 MEASUREMENT RESULTS..... 35

9. BAND EDGE 41

9.1 MEASUREMENT PROCEDURE 41

9.2 LIMIT 41

9.3 MEASUREMENT RESULTS..... 41

10. ANTENNA APPLICATION 48

10.1 ANTENNA REQUIREMENT 48

10.2 MEASUREMENT RESULTS..... 48

11. CONDUCTED SPURIOUS EMISSIONS 49

11.1 MEASUREMENT PROCEDURE 49

11.2 MEASUREMENT RESULTS..... 49

13. TEST EQUIPMENT LIST..... 53

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test

This device is a BT Speaker which is powered by 3* 1.5V AA batteries. For more details features, please refer to User's Manual.

Manufacturer	: Star Light Electronics Co., Ltd.
Address	: 5/F., Shing Dao Industrial Building, 232 Aberdeen Main Road, Aberdeen, Hong Kong
Frequency:	: 2402-2480MHz
Modulation	: GFSK, $\pi/4$ -DQPSK, 8DPSK
Number of Channel	: 79
Channel space	: 1MHz
Max RF Output Power	: 0.81dBm (1.21mW)
Antenna Type	: PCB
Antenna Gain	: 0dBi
Power Supply	: DC 4.5V
Model name	: SMI438BT, SP-3397
Note:	: Both of models have the same circuit schematic, construction and critical components except different power-supply, model number and trade mark.

1.2 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: BGRSMI438BT filing to comply with Section 15.247 of the FCC Part 15 (2012), Subpart C Rule.

1.3 Test Methodology

The radiated emission measurements were performed according to the procedures in ANSI C63.4 (2003) and DA 00-705. Radiated emission measurement was performed in semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters.

1.4 Equipment Modifications

Not available for this EUT intended for grant.

1.5 Support Device

None

1.6 Test Facility and Location

Listed by FCC, August 02, 2011
The Certificate Registration Number is 665078.

Listed by Industry Canada, July 01, 2011
The Certificate Registration Number is 9743A-1.

Dongguan NTC Co., Ltd.

Building D, Gaosheng Science and Technology Park,
Hongtu Road, Nancheng District, Dongguan City,
Guangdong Province, China

1.7 Summary of Test Results

FCC Rules	Description Of Test	Result
§15.247(a)(1)	Channel Separation test	Compliant
§15.247(a)(1)	20dB Bandwidth	Compliant
§15.247(a)(1)(iii)	Hopping Channel Number	Compliant
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliant
§15.247(b)	Max Peak output Power test	Compliant
§15.247(d)	Band edge test	Compliant
§15.207 (a)	AC Power Conducted Emission	N/A ^{see note}
§15.247(d), §15.209, §15.205	Radiated Emission	Compliant
§15.203	Antenna Requirement	Compliant
§15.247(d)	Conducted Spurious Emission	Compliant

Note : Due to this EUT is powered by battery only, the AC Power Conducted Emission is not applicable.

2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 Special Accessories

Not available for this EUT intended for grant.

2.3 Description of test modes

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and normal mode is programmed. The Lowest, middle and highest channel were chosen for testing, and all packets DH1, DH3 and DH5 mode in all modulation type GFSK, $\pi/4$ -DQPSK, 8DPSK were tested.


2.4 EUT Exercise

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements.


3. Radiated Emission Test

3.1 Test SET-UP (Block Diagram of Configuration)

3.1.1 Radiated Emission Test Set-Up, Frequency Below 30MHz



3.1.2 Radiated Emission Test Set-Up, Frequency above 1GHz



3.2 Measurement Procedure

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi- anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to peak detect function and specified bandwidth with maximum hold mode.

3.3 Limit

Frequency range MHz	Distance Meters	Field Strengths Limit (15.209)
		$\mu\text{V/m}$
0.009 ~ 0.490	300	$2400/F(\text{kHz})$
0.490 ~ 1.705	30	$24000/F(\text{kHz})$
1.705 ~ 30	30	30
30 ~ 88	3	100
88 ~ 216	3	150
216 ~ 960	3	200
Above 960	3	500

- Remark :
- (1) Emission level $(\text{dB})\mu\text{V} = 20 \log \text{Emission level } \mu\text{V/m}$
 - (2) The smaller limit shall apply at the cross point between two frequency bands.
 - (3) As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
 - (4) The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

3.4 Measurement Results

Operation Mode: TX
Frequency Range: 9KHz~1GHz
Test Result: PASS
Measured Distance: 3m
Test Date : May 24, 2013

Temperature : 27 °C
Humidity : 58 %
Test By: Sance

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV)	Limit 3m (dBuV/m)	Margin (dB)	Note
115.3599	V	24.70	43.50	-18.80	QP
127.9699	V	29.30	43.50	-14.20	QP
163.8600	V	25.10	43.50	-18.40	QP
175.5000	V	30.30	43.50	-13.20	QP
188.1100	V	32.90	43.50	-10.60	QP
203.6299	V	27.80	43.50	-15.70	QP
107.5999	H	26.50	43.50	-17.00	QP
143.4900	H	34.30	43.50	-9.20	QP
151.2500	H	35.70	43.50	-7.80	QP
175.5000	H	36.70	43.50	-6.80	QP
195.8700	H	36.60	43.50	-6.90	QP
207.5099	H	35.20	43.50	-8.30	QP

Other emissions are lower than 10dB below the allowable limit.

Note: (1) Quasi-Peak detector is used except for others stated.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss
(3) Measurement uncertainty : ± 3.7 dB.

Modulation: GFSK (the worst case)
(Low Frequency: 2402MHz)
Operation Mode: TX Mode (Low) Test Date : May 24, 2013
Frequency Range: 1-25GHz Temperature : 27 °C
Test Result: PASS Humidity : 58 %
Measured Distance: 3m Test By: Sance

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV	PK	AV	PK	AV
4804	V	51.69	38.19	74.00	54.00	-22.31	-15.81
7206	V	53.46	40.82	74.00	54.00	-20.54	-13.18
9608	V	52.24	40.38	74.00	54.00	-21.76	-13.62
12010	V	53.96	39.70	74.00	54.00	-20.04	-14.30
4804	H	52.46	39.33	74.00	54.00	-21.54	-14.67
7206	H	53.52	40.77	74.00	54.00	-20.48	-13.23
9608	H	53.75	40.88	74.00	54.00	-20.25	-13.12
12010	H	53.01	39.43	74.00	54.00	-20.99	-14.57

The other emissions are not founded.

Note: (1) All Readings are Peak Value and AV.
(2) Emission Level= Reading Level+Probe Factor +Cable Loss
(3) The average measurement was not performed when the peak measured data under the limit of average detection.
(4) Measurement uncertainty : $\pm 3.4\text{dB}$

Modulation: GFSK (the worst case)
(Mid Frequency: 2441MHz)
Operation Mode: TX Mode (Mid) Test Date : May 24, 2013
Frequency Range: 1-25GHz Temperature : 27 °C
Test Result: PASS Humidity : 58 %
Measured Distance: 3m Test By: Sance

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV	PK	AV	PK	AV
4882	V	52.31	39.60	74.00	54.00	-21.69	-14.40
7323	V	53.88	40.79	74.00	54.00	-20.12	-13.21
9764	V	53.46	40.30	74.00	54.00	-20.54	-13.70
12205	V	53.63	40.88	74.00	54.00	-20.37	-13.12
4882	H	52.42	39.30	74.00	54.00	-21.58	-14.70
7323	H	53.12	39.71	74.00	54.00	-20.88	-14.29
9764	H	52.76	40.46	74.00	54.00	-21.24	-13.54
12205	H	52.80	40.64	74.00	54.00	-21.20	-13.36

The other emissions are not founded.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) Measurement uncertainty : $\pm 3.4\text{dB}$

Modulation: GFSK (the worst case)
(High Frequency: 2480MHz)
Operation Mode: TX Mode (High) Test Date : May 24, 2013
Frequency Range: 1-25GHz Temperature : 27 °C
Test Result: PASS Humidity : 58 %
Measured Distance: 3m Test By: Sance

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV	PK	AV	PK	AV
4960	V	52.94	39.89	74.00	54.00	-21.06	-14.11
7440	V	54.37	40.67	74.00	54.00	-19.63	-13.33
9920	V	54.71	40.52	74.00	54.00	-19.29	-13.48
12400	V	52.35	41.54	74.00	54.00	-21.65	-12.46
4960	H	53.84	40.69	74.00	54.00	-20.16	-13.31
7440	H	54.68	40.10	74.00	54.00	-19.32	-13.90
9920	H	54.45	40.48	74.00	54.00	-19.55	-13.52
12400	H	53.33	40.97	74.00	54.00	-20.67	-13.03

The other emissions are not founded.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) Measurement uncertainty : $\pm 3.4\text{dB}$


4. Channel Separation test

4.1 Measurement Procedure

Minimum Hopping Channel Carrier Frequency Separation, FCC Rule 15.247(a)(1):

Connect EUT antenna terminal to the spectrum analyzer with a low loss cable, and using the MARKER and Max-Hold function to record the separation of two adjacent channels.

4.2 Test SET-UP (Block Diagram of Configuration)




4.3 Measurement Results

Modulation:	GFSK, $\pi/4$ -DQPSK, 8DPSK		
RBW:	100KHz	VBW:	300KHz
Packet:	DH5	Spectrum Detector:	PK
Test By:	Sance	Test Date :	May 24, 2013
Temperature :	27 °C	Humidity :	55 %
Test Result:	PASS		


Channel number	Channel frequency (MHz)	Separation Read Value (KHz)	Separation Limit (KHz)
GFSK			
Lowest	2402	1000	>746.7
Middle	2441	1000	>746.7
Highest	2480	1000	>746.7
$\pi/4$ -DQPSK			
Lowest	2402	1000	>953.3
Middle	2441	1000	>953.3
Highest	2480	1000	>953.3
8DPSK			
Lowest	2402	1000	>953.3
Middle	2441	1000	>953.3
Highest	2480	1000	>953.3

GFSK Lowest Channel




Date: 24.MAY.2013 16:51:18

GFSK Middle Channel




Date: 24.MAY.2013 16:53:43

GFSK Highest Channel




Date: 24.MAY.2013 16:55:32

$\pi/4$ -DQPSK Lowest Channel




Date: 24.MAY.2013 16:58:34

$\pi/4$ -DQPSK Middle Channel




Date: 24.MAY.2013 17:02:02

$\pi/4$ -DQPSK Highest Channel




Date: 24.MAY.2013 17:04:00

8DPSK Lowest Channel




Date: 24.MAY.2013 17:06:48

8DPSK Middle Channel



Date: 24.MAY.2013 17:09:25

8DPSK Highest Channel



Date: 24.MAY.2013 17:11:38


5. 20dB Bandwidth

5.1 Measurement Procedure

Maximum 20dB RF Bandwidth, FCC Rule 15.247(a)(1):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RBW was chosen so that the display was a result of the hopping channel modulation. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. Use the spectrum 20dB down delta function to measure the bandwidth.

5.2 Test SET-UP (Block Diagram of Configuration)




5.3 Measurement Results

Refer to attached data chart.

Modulation:	GFSK, $\pi/4$ -DQPSK, 8DPSK		
RBW:	100KHz	VBW:	300KHz
Packet:	DH5	Spectrum Detector:	PK
Test By:	Sance	Test Date :	May 24, 2013
Temperature :	27 °C	Humidity :	55 %
Test Result:	PASS		


Channel frequency (MHz)	20dB Down BW(kHz)
GFSK	
2402	1120
2441	1120
2480	1120
$\pi/4$ -DQPSK	
2402	1420
2441	1430
2480	1430
8DPSK	
2402	1430
2441	1420
2480	1430

GFSK Lowest Channel




Date: 24.MAY.2013 16:49:39

GFSK Middle Channel




Date: 24.MAY.2013 16:52:05

GFSK Highest Channel




Date: 24.MAY.2013 16:54:23

$\pi/4$ -DQPSK Lowest Channel




Date: 24.MAY.2013 16:57:26

$\pi/4$ -DQPSK Middle Channel




Date: 24.MAY.2013 16:59:18

$\pi/4$ -DQPSK Highest Channel




Date: 24.MAY.2013 17:02:47

8DPSK Lowest Channel




Date: 24.MAY.2013 17:05:07

8DPSK Middle Channel



Date: 24.MAY.2013 17:07:29

8DPSK Highest Channel



Date: 24.MAY.2013 17:10:07


6. Hopping Channel Number

6.1 Measurement Procedure

Minimum Number of Hopping Frequencies, FCC Rule 15.247(a)(1)(iii):

Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum, and the spectrum analyzer set to MAX HOLD readings were taken for 3-5 minutes. The channel peaks so recorded were added together, and the total number compared to the minimum number of channels required in the regulation.

6.2 Test SET-UP (Block Diagram of Configuration)



6.3 Measurement Results


Modulation	GFSK, $\pi/4$ -DQPSK, 8DPSK		
RBW:	100KHz	VBW:	300KHz
Packet:	DH5	Spectrum Detector:	PK
Test By:	Sance	Test Date :	May 24, 2013
Temperature :	27 °C	Humidity :	55 %
Test Result:	PASS		

Hopping Channel Frequency Range	Number of Hopping Channels	Limit
2402-2480	79	≥15

The worst case: GFSK



GFSK



Date: 24.MAY.2013 18:54:17

7. Time of Occupancy (Dwell Time)

7.1 Measurement Procedure

Average Channel Occupancy Time, FCC Ref:15.247(a)(1)(iii):

Connect EUT antenna terminal to the spectrum analyzer with a low loss cable. The spectrum analyzer center frequency was set to one of the known hopping channels. The Sweep was set to 10 ms, the SPAN was set to Zero SPAN. The time duration of the transmissions so captured was measured with the Marker Delta function

7.2 Measurement Results


The maximum number of hopping channels in 31.6s (0.4s/Channel x 79 Channel)

Refer to attached data chart.

Modulation :	GFSK, $\pi/4$ -DQPSK, 8DPSK		
RBW :	1MHz	VBW :	1MHz
Spectrum Detector:	PK	Test Result:	PASS
Test By:	Sance	Test Date :	May 24, 2013
Temperature :	27 °C	Humidity :	55 %


Packet	Frequency (MHz)	Result (msec)	Limit (msec)
GFSK			
DH1	2402	$0.415(\text{ms}) \times (1600 / (2 \times 79)) \times 31.6 = 132.8$	400
DH3	2402	$1.665(\text{ms}) \times (1600 / (4 \times 79)) \times 31.6 = 266.4$	400
DH5	2402	$2.925(\text{ms}) \times (1600 / (6 \times 79)) \times 31.6 = 312.0$	400
$\pi/4$ -DQPSK			
2-DH1	2402	$0.420(\text{ms}) \times (1600 / (2 \times 79)) \times 31.6 = 134.4$	400
2-DH3	2402	$1.680(\text{ms}) \times (1600 / (4 \times 79)) \times 31.6 = 268.8$	400
2-DH5	2402	$2.925(\text{ms}) \times (1600 / (6 \times 79)) \times 31.6 = 312.0$	400
8DPSK			
3-DH1	2402	$0.415(\text{ms}) \times (1600 / (2 \times 79)) \times 31.6 = 132.8$	400
3-DH3	2402	$1.675(\text{ms}) \times (1600 / (4 \times 79)) \times 31.6 = 268.0$	400
3-DH5	2402	$2.935(\text{ms}) \times (1600 / (6 \times 79)) \times 31.6 = 313.1$	400

GFSK DH1




Date: 24.MAY.2013 17:13:53

GFSK DH3




Date: 24.MAY.2013 17:14:31

GFSK DH5




Date: 24.MAY.2013 17:15:10

$\pi/4$ -DQPSK 2-DH1




Date: 24.MAY.2013 17:15:57

$\pi/4$ -DQPSK 2-DH3




Date: 24.MAY.2013 17:16:35

$\pi/4$ -DQPSK 2-DH5




Date: 24.MAY.2013 17:17:11

8DPSK 3-DH1



Date: 24.MAY.2013 17:17:41


8DPSK 3-DH3



Date: 24.MAY.2013 17:18:13



8DPSK 3-DH5



Date: 24.MAY.2013 17:18:43

8. MAXIMUM PEAK OUTPUT POWER

8.1 Measurement Procedure

Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b)(1):

Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum. The analyzer was set for RBW > 20dB bandwidth and power was read directly in dBm. Cable loss was considered during this measurement.


8.2 Measurement Results

Refer to attached data chart.

Modulation :	GFSK, $\pi/4$ -DQPSK, 8DPSK		
RBW :	3MHz	VBW :	3MHz
Spectrum Detector:	PK	Test Date :	May 24, 2013
Test By:	Sance	Test Result:	PASS
Temperature :	27 °C	Humidity :	55 %


Channel Frequency (MHz)	Cable Loss dB	Peak Power output(mW)	Peak Power output(dBm)	Peak Power Limit(dBm)	Pass/Fail
GFSK					
2402.00	1.5	0.40	-3.96	21	PASS
2441.00	1.5	0.96	-0.19	21	PASS
2480.00	1.5	1.21	0.81	21	PASS
$\pi/4$ -DQPSK					
2402.00	1.5	0.43	-3.68	21	PASS
2441.00	1.5	0.83	-0.82	21	PASS
2480.00	1.5	1.06	0.26	21	PASS
8DPSK					
2402.00	1.5	0.43	-3.70	21	PASS
2441.00	1.5	0.84	-0.74	21	PASS
2480.00	1.5	1.07	0.30	21	PASS

GFSK Lowest Channel




Date: 24.MAY.2013 17:20:59

GFSK Middle Channel




Date: 24.MAY.2013 17:21:20

GFSK Highest Channel




Date: 24.MAY.2013 17:21:37

$\pi/4$ -DQPSK Lowest Channel




Date: 24.MAY.2013 17:22:15

$\pi/4$ -DQPSK Middle Channel




Date: 24.MAY.2013 17:22:31

$\pi/4$ -DQPSK Highest Channel




Date: 24.MAY.2013 17:22:46

8DPSK Lowest Channel




Date: 24.MAY.2013 17:23:17

8DPSK Middle Channel



Date: 24.MAY.2013 17:23:35

8DPSK Highest Channel



Date: 24.MAY.2013 17:23:49

9. Band Edge

9.1 Measurement Procedure

Out of Band Conducted Emissions, FCC Rule 15.247(d):

- (1) For RF Conducted: The transmitter output is connected to spectrum analyzer. The resolution bandwidth is set to 100KHz, and the video bandwidth set to 300KHz.
- (2) For Radiated Emission: Same as 3.2 Radiated Emission Measurement procedure.

9.2 Limit

15.247(d) In any 100KHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100KHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.


9.3 Measurement Results

Please see below test table and plots.
 For Radiated Emission
 The worst case: GFSK


Frequency (MHz)	Polarity	Level		Limited		Margin		Result
		PK	AV	PK	AV	PK	AV	
GFSK								
2399.960	H	56.93	44.59	74.00	54.00	-17.07	-9.41	PASS
2399.140	V	50.52	38.33	74.00	54.00	-23.48	-15.67	PASS
2485.460	H	46.23	34.46	74.00	54.00	-27.77	-19.54	PASS
2485.420	V	43.70	30.62	74.00	54.00	-30.30	-23.38	PASS

For RF Conducted

GFSK Lowest Channel




Date: 24.MAY.2013 18:56:39




Date: 24.MAY.2013 18:58:32

GFSK Highest Channel




Date: 24.MAY.2013 19:00:00




Date: 24.MAY.2013 19:01:41

$\pi/4$ -DQPSK Lowest Channel




Date: 24.MAY.2013 19:03:49




Date: 24.MAY.2013 19:07:14



$\pi/4$ -DQPSK Highest Channel




Date: 24.MAY.2013 19:08:37




Date: 24.MAY.2013 19:11:14

8DPSK Lowest Channel




Date: 24.MAY.2013 19:12:47




Date: 24.MAY.2013 19:16:07

8DPSK Highest Channel



Date: 24.MAY.2013 19:17:14



Date: 24.MAY.2013 19:19:03

10. Antenna Application

10.1 Antenna requirement

According to of FCC part 15C section 15.203 and 15.240:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Systems operating in the 2400-2483.5MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

10.2 Measurement Results

The antenna is integrated on the main PCB and no consideration of replacement, and the best case gain of the antenna is 0dBi. So, the antenna is consider meet the requirement.

11. Conducted Spurious Emissions

11.1 Measurement Procedure


Out of Band Conducted Spurious Emissions, FCC Rule 15.247(d):

The transmitter output is connected to spectrum analyzer. All spurious emission and up to the tenth harmonic was measured and they were found to be at least 20dB below the highest level of the desired power in the passband.


11.2 Measurement Results

Please refer to following plots, the worst case (GFSK) was shown.

GFSK Lowest Channel




Date: 24.MAY.2013 17:57:12






GFSK Middle Channel




Date: 24.MAY.2013 17:56:33






GFSK Highest Channel



Date: 24.MAY.2013 17:57:44



13. Test Equipment List

Description	Manufacturer	Model Number	Serial Number	Calibration Date	Calibration Due Date
Test Receiver	Rohde & Schwarz	ESCI7	100837	Nov. 25, 2012	Nov. 24, 2013
Antenna	Schwarzbeck	VULB9162	9162-010	Nov. 28, 2012	Nov. 27, 2013
Positioning Controller	UC	UC 3000	N/A	N/A	N/A
Color Monitor	SUNSCO	SP-140A	N/A	N/A	N/A
Single Phase Power Line Filter	SAEMC	PF201A-32	110210	N/A	N/A
3 Phase Power Line Filter	SAEMC	PF401A-200	110318	N/A	N/A
DC Power Filter	SAEMC	PF301A-200	110245	N/A	N/A
Cable	Huber+Suhner	CBL2-NN-1M	22390001	Nov. 09, 2012	Nov. 08, 2013
Cable	Huber+Suhner	CIL02	N/A	Nov. 09, 2012	Nov. 08, 2013
Power Amplifier	HP	HP 8447D	1145A00203	Nov. 09, 2012	Nov. 08, 2013
Horn Antenna	Schwarzbeck	BBHA9170	9170-372	Oct.24, 2012	Oct.23, 2013
Horn Antenna	EMCO	3117	00062558	Oct. 19, 2012	Oct. 18, 2013
Loop antenna	Daze	ZA30900A	0708	Oct.16, 2012	Oct.15, 2013
Spectrum Analyzer	Agilent	E4408B	MY414407D	Apr. 29, 2013	Apr. 28, 2014
Pre-Amplifier	Agilent	8449B	3008A02964	Apr. 19, 2013	Apr. 18, 2014