



13. Radio Frequency Exposure

The measurements shown in this test report were made in accordance with the procedures given in FCC Part 2 (Section 2.1091)

KDB 447498

IEEE C95.1:2005

13.1 EUT Specification

Frequency band (Operating)	☐ WLAN: 2412MHz ~ 2462MHz ☒ Bluetooth: 2402MHz ~ 2480MHz
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation)
Exposure classification	☐ Occupational/Controlled exposure ☒ General Population/Uncontrolled exposure
Antenna diversity	☒ Single antenna ☐ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Evaluation applied	☒ MPE Evaluation* ☐ SAR Evaluation ☐ N/A
Remark: 1. The maximum conducted output power is <u>9.98dBm (9.954mW)</u> at <u>2441MHz</u> (with <u>2.3dBi antenna gain</u>.) 2. DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance. 3. For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is 1.0 mW/cm² even if the calculation indicates that the power density would be larger.	



13.2 Test Results

No non-compliance noted.

13.3 Calculation

$$\text{Given } E = \frac{\sqrt{30 \times P \times G}}{d} \quad \& \quad S = \frac{E^2}{3770}$$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²



13.4 Maximum Permissible Exposure

Modulation Type	Channel Frequency (MHz)	Max. Conducted output power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
GFSK	2402-2480	9.98	2.3	20	0.003	1
$\pi/4$ -DQPSK	2402-2480	9.52	2.3	20	0.003	1
8DPSK	2402-2480	9.90	2.3	20	0.003	1

Maximum Permissible Exposure(Co-location)

BT+Wifi 2.4G

Modulation Type	Channel Frequency (MHz)	Max. Conducted output power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	MPE Ratio
GFSK	2402-2480	9.98	2.3	20	0.003	1.00	0.003
11n HT20	2412-2462	27.47	2.38	20	0.192	1.00	0.192
Co-location Total							0.195
Σ MPE ratios Limit							1

BT+Wifi 5G

Modulation Type	Channel Frequency (MHz)	Max. Conducted output power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	MPE Ratio
GFSK	2402-2480	9.98	2.3	20	0.003	1.00	0.003
11ac VHT40	5500-5700	21.48	2	20	0.044	1.00	0.044
Co-location Total							0.047
Σ MPE ratios Limit							1