

## RF Exposure Evaluation Report

FCC ID : BKEHAC042  
Equipment : Wireless Game Device  
Brand Name : Nintendo®  
Model Name : HAC-042  
Applicant : Nintendo Co., Ltd.  
11-1, Kamitoba-Hokotate-cho, Minami-ku,  
Kyoto 601-8501, Japan  
Manufacturer : Nintendo Co., Ltd.  
11-1, Kamitoba-Hokotate-cho, Minami-ku,  
Kyoto 601-8501, Japan  
Standard : 47 CFR FCC Part 2 Subpart J, section 2.1093

The product was received on Apr. 25, 2019, and testing was started from May 22, 2019 and completed on May 22, 2019. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in KDB447498 D01 General RF Exposure Guidance v06 and shown compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Allen Lin

**SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory**

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)

## Table of Contents

<b>HISTORY OF THIS TEST REPORT .....</b>	<b>3</b>
<b>1. GENERAL DESCRIPTION .....</b>	<b>4</b>
1.1. EUT General Information .....	4
1.2. Testing Location Information .....	4
<b>2. RF EXPOSURE EVALUATION .....</b>	<b>5</b>
2.1. Applicable Standard .....	5
2.2. SAR evaluation .....	5

### Photographs of EUT V01

## History of This Test Report

Report No.	Version	Description	Issued Date
FA942538	01	Initial issue of report	Jul. 08, 2019

**Reviewed by: Sam Tsai**

**Report Producer: Ann Hou**

## 1. GENERAL DESCRIPTION

### 1.1. EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
Bluetooth	2400-2483.5	2402-2480	BR / EDR: FHSS (GFSK / $\pi/4$ -DQPSK / 8DPSK)

### 1.2. Testing Location Information

Testing Location			
<input checked="" type="checkbox"/>	HWA YA	ADD : No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL : 886-3-327-3456                      FAX : 886-3-327-0973	
Test site Designation No. TW1190 with FCC.			
<input type="checkbox"/>	JHUBEI	ADD : No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County, Taiwan (R.O.C.) TEL : 886-3-656-9065                      FAX : 886-3-656-9085	
Test site Designation No. TW0006 with FCC.			

## 2. RF EXPOSURE EVALUATION

### 2.1. Applicable Standard

In accordance with FCC 47 CFR part 2 (2.1093) this device has been defined as a portable device which is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

Portable devices must be evaluated using the specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003.

### 2.2. SAR evaluation

- Per FCC KDB 447498 D01 v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances*  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f_{(\text{GHz})}}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR

- $f_{(\text{GHz})}$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Max. Power (dBm)	Gain (dBi)	Tolerance (dB)	Tune-up Max. Power (dBm)	Test Distance (mm)	Frequency (GHz)	Exclusion Thresholds
3.21	2.9	0.5	6.61	4.58	5	2.441
						1.43

- Per FCC KDB 447498 D01 v06 exclusion thresholds is  $1.43 < 7.5$ , RF exposure evaluation is not required.

————THE END————