



**FCC CFR47 CERTIFICATION  
CLASS II PERMISSIVE CHANGE**

**TEST REPORT**

**NINTENDO DS**

**MODEL NUMBER: NTR-001**

**FCC ID: BKENTR001**

**REPORT NUMBER: 04I2987-3**

**ISSUE DATE: OCTOBER 22, 2004**

*Prepared for*  
**NINTENDO CO., LTD.**  
**11-1 KAMITOBABA-HOKOTATE-CHO**  
**MINAMI-KU, KYOTO**  
**JAPAN**

*Prepared by*  
**COMPLIANCE CERTIFICATION SERVICES**  
**561F MONTEREY ROAD,**  
**MORGAN HILL, CA 95037, USA**  
**TEL: (408) 463-0885**  
**FAX: (408) 463-0888**



## TABLE OF CONTENTS

<b>1. TEST RESULT DECLARATION .....</b>	<b>3</b>
<b>2. EUT DESCRIPTION _ CLASS II PERMISSIVE CHANGE .....</b>	<b>4</b>
<b>3. FACILITIES AND ACCREDITATION .....</b>	<b>5</b>
<b>4. CALIBRATION AND UNCERTAINTY.....</b>	<b>6</b>
4.1. <i>MEASURING INSTRUMENT CALIBRATION.....</i>	6
4.2. <i>MEASUREMENT UNCERTAINTY.....</i>	6
4.3. <i>TEST AND MEASUREMENT EQUIPMENT.....</i>	7
<b>5. SETUP OF EQUIPMENT UNDER TEST .....</b>	<b>8</b>
<b>6. APPLICABLE LIMITS AND TEST RESULTS .....</b>	<b>10</b>
6.1. <i>6 dB BANDWIDTH.....</i>	10
6.2. <i>99% BANDWIDTH .....</i>	14
6.3. <i>PEAK OUTPUT POWER.....</i>	18
6.4. <i>MAXIMUM PERMISSIBLE EXPOSURE .....</i>	23
6.5. <i>AVERAGE POWER.....</i>	26
6.6. <i>PEAK POWER SPECTRAL DENSITY .....</i>	27
6.7. <i>CONDUCTED SPURIOUS EMISSIONS.....</i>	31
6.8. <i>RADIATED EMISSIONS.....</i>	38
6.8.1. <i>TRANSMITTER RADIATED SPURIOUS EMISSIONS .....</i>	38
6.8.2. <i>TRANSMITTER RADIATED EMISSIONS ABOVE 1 GHZ .....</i>	41
6.9. <i>POWERLINE CONDUCTED EMISSIONS .....</i>	54
<b>7. SETUP PHOTOS .....</b>	<b>58</b>

## 1. TEST RESULT DECLARATION

**COMPANY NAME:** NINTENDO CO., LTD.  
11-1 KAMITOBIA-HOKOTATE-CHO  
MINAMI-KU, KYOTO  
JAPAN

**EUT DESCRIPTION:** NINTENDO DS

**MODEL:** NTR-001

**DATE TESTED:** OCTOBER 15 - 21, 2004

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 15 SUBPART C	NO NON-COMPLIANCE NOTED

Compliance Certification Services, Inc. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

**Note:** This document reports conditions under which testing was conducted and results of tests performed. This document may not be altered or revised in any way unless done so by Compliance Certification Services and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Compliance Certification Services will constitute fraud and shall nullify the document.

Approved & Released For CCS By:



---

FRANK IBRAHIM  
EMC SUPERVISOR  
COMPLIANCE CERTIFICATION SERVICES

Tested By:



---

CHIN PANG  
EMC TECHNICIAN  
COMPLIANCE CERTIFICATION SERVICES

## 2. EUT DESCRIPTION \_ CLASS II PERMISSIVE CHANGE

The EUT is a portable game machine with a Wireless 802.11 transceiver operating in the 2400-2483.5 MHz band with 13 channels.

The transmitter has a maximum peak conducted output power as follows:

Frequency Band (MHz)	Mode	Output Power (dBm)	Output Power (mW)
2412 - 2472	802.11	2.12	1.63

The radio utilizes a Dipole Antenna, with a maximum gain of 2.09 dBi.

The major change filed under this application is:

Change AC Adapter to model: NTR-002 (JPN/USA), Tabuchi Electronic Co., LTD

## TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4/2003, FCC CFR 47 Part 2 and FCC CFR 47 Part 15.

## 3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 561F Monterey Road, Morgan Hill, California, USA. The sites are constructed in conformance with the requirements of ANSI C63.4, ANSI C63.7 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

CCS is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsemc.com>.



No part of this report may be used to claim or imply product endorsement by NVLAP, NIST, or any government agency.

## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

### 4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Radiated Emission, 30 to 200 MHz	+/- 3.3 dB
Radiated Emission, 200 to 1000 MHz	+4.5 / -2.9 dB
Radiated Emission, 1000 to 2000 MHz	+4.5 / -2.9 dB
Power Line Conducted Emission	+/- 2.9 dB

Uncertainty figures are valid to a confidence level of 95%.

#### 4.3. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

TEST EQUIPMENT LIST				
Name of Equipment	Manufacturer	Model No.	Serial No.	Due Date
Spectrum Analyzer 20 Hz - 44 GHz	Agilent	E4446A	US42070220	1/13/2005
Amplifier 1-26GHz	MITEQ	NSP2600-SP	924341	4/25/205
Horn Antenna, 1-18 GHz	EMCO	3115	2238	2/4/2005
Horn Antenna, 18-26 GHz	ARA	SWH-28	1007	9/12/05
EMI Test Receiver	R & S	ESHS 20	827129/006	10/22/2005
Spectrum Analyzer, 26.5 GHz	HP	8593EM	3710A00205	10/1/2005
Line Filter	Lindgren	LMF-3489	497	CNR
LISN, 10 kHz ~ 30 MHz	FCC	LISN-50/250-25-2	2023	10/15/2005
EMI Receiver, 9 kHz ~ 2.9 GHz	HP	8542E	3942A00286	11/20/2004
RF Filter Section	HP	85420E	3705A00256	11/20/2004
Antenna, Bicon/Log, 25 ~ 2000 MHz	Sunol Sciences	JBL	A121003	12/22/2004
4.0GHz HPF	MicrTronic	HPM13351	1	CNR

## 5. SETUP OF EQUIPMENT UNDER TEST

### SUPPORT EQUIPMENT

PERIPHERAL SUPPORT EQUIPMENT LIST				
Description	Manufacturer	Model	Serial Number	FCC ID
AC ADAPTER	TABUCHI ELECTRIC	NTR-002 (JPN/USA)	N/A	N/A
DS CARD	NINTENDO	NTR-005	N/A	N/A


### I/O CABLES

I/O CABLE LIST						
Cable No.	Port	# of Identical Ports	Connector Type	Cable Type	Cable Length	Remarks
1	DC	1	DC	UNSHIELDED	2	N/A

### TEST SETUP

The EUT was set in continuous transmit mode. X, Y, and Z positions were investigated; "Z" position was deemed worst case. High channel was deemed worst case due to the highest output power.

**SETUP DIAGRAM FOR TESTS**



## 6. APPLICABLE LIMITS AND TEST RESULTS

### 6.1. 6 dB BANDWIDTH

#### LIMIT

§15.247 (a) (2) For direct sequence systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

#### TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The RBW is set to 100 kHz and the VBW is set to 300 kHz. The sweep time is coupled.


#### RESULTS


No non-compliance noted:


802.11

Channel	Frequency (MHz)	6 dB Bandwidth (kHz)	Minimum Limit (kHz)	Margin (kHz)
Low	2412	10300	500	9800
Middle	2442	9870	500	9370
High	2472	9970	500	9470

**6 DB BANDWIDTH (802.11)**







## 6.2. 99% BANDWIDTH

### LIMIT

None; for reporting purposes only.

### TEST PROCEDURE

The transmitter output is connected to the spectrum analyzer. The RBW is set to 1% to 3% of the 99 % bandwidth. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.

### RESULTS


No non-compliance noted:

802.11

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2412	16.4086
Middle	2442	16.4471
High	2472	16.3803

**99% BANDWIDTH (802.11)**







### 6.3. PEAK OUTPUT POWER

#### **PEAK POWER LIMIT**

§15.247 (b) The maximum peak output power of the intentional radiator shall not exceed the following:

§15.247 (b) (3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz , and 5725-5850 MHz bands: 1 watt.

§15.247 (b) (4) Except as shown in paragraphs (b)(4) (i), (ii) and (iii) of this section, if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

§15.247 (b) (4) (i) Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

#### **TEST PROCEDURE**

The transmitter output is connected to a spectrum analyzer and the analyzer's internal channel power integration function is used to integrate the power over a bandwidth greater than or equal to the 99% bandwidth.


**RESULTS**


No non-compliance noted:


802.11

Channel	Frequency (MHz)	Peak Power (dBm)	Limit (dBm)	Margin (dB)
Low	2412	1.84	30	-28.16
Middle	2442	1.88	30	-28.12
High	2472	2.12	30	-27.88

**OUTPUT POWER (802.11)**







## 6.4. MAXIMUM PERMISSIBLE EXPOSURE

### LIMITS

§1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300	61.4	0.163	1.0	6
300–1500	.....	.....	f/300	6
1500–100,000	.....	.....	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)—Continued

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
30–300	27.5	0.073	0.2	30
300–1500	.....	.....	f/1500	30
1500–100,000	.....	.....	1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

## CALCULATIONS

Given

$$E = \sqrt{(30 * P * G) / d}$$

and

$$S = E^2 / 3770$$

where

E = Field Strength in Volts/meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power Density in milliwatts/square centimeter

Combining equations and rearranging the terms to express the distance as a function of the remaining variables yields:

$$d = \sqrt{((30 * P * G) / (3770 * S))}$$

Changing to units of Power to mW and Distance to cm, using:

$$P (\text{mW}) = P (\text{W}) / 1000 \text{ and}$$

$$d (\text{cm}) = 100 * d (\text{m})$$

yields

$$d = 100 * \sqrt{((30 * (P / 1000) * G) / (3770 * S))}$$

$$d = 0.282 * \sqrt{(P * G / S)}$$

where

d = distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power Density in mW/cm<sup>2</sup>

Substituting the logarithmic form of power and gain using:

$$P (\text{mW}) = 10^{(P (\text{dBm}) / 10)} \text{ and}$$

$$G (\text{numeric}) = 10^{(G (\text{dBi}) / 10)}$$

yields

$$d = 0.282 * 10^{(P + G) / 20} / \sqrt{S} \quad \text{Equation (1)}$$

where

d = MPE distance in cm

P = Power in dBm

G = Antenna Gain in dBi

S = Power Density Limit in mW/cm<sup>2</sup>

Equation (1) and the measured peak power is used to calculate the MPE distance.

**LIMITS**

From §1.1310 Table 1 (B), S = 1.0 mW/cm<sup>2</sup>

**RESULTS**

No non-compliance noted:

Mode	Power Density Limit (mW/cm <sup>2</sup> )	Output Power (dBm)	Antenna Gain (dBi)	MPE Distance (cm)
802.11b	1.0	2.12	2.09	0.46

NOTE: For mobile or fixed location transmitters, the minimum separation distance is 20 cm, even if calculations indicate that the MPE distance would be less.

## 6.5. AVERAGE POWER

### AVERAGE POWER LIMIT

None; for reporting purposes only.

### TEST PROCEDURE

The transmitter output is connected to a power meter.

### RESULTS

No non-compliance noted:

The cable assembly insertion loss of 1.0 dB was entered as an offset in the power meter to allow for direct reading of power

802.11

Channel	Frequency (MHz)	Power (dBm)
Low	2412	-0.93
Middle	2442	-0.94
High	2472	-0.73

## 6.6. PEAK POWER SPECTRAL DENSITY

### LIMIT

§15.247 (d) For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer, the maximum level in a 3 kHz bandwidth is measured with the spectrum analyzer using RBW = 3 kHz and VBW > 3 kHz, sweep time = span / 3 kHz, and video averaging is turned off. The PPSD is the highest level found across the emission in any 3 kHz band.


### RESULTS


No non-compliance noted:


802.11

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Margin (dB)
Low	2412	-21.95	8	-29.95
Middle	2442	-21.43	8	-29.43
High	2472	-21.62	8	-29.62

**PEAK POWER SPECTRAL DENSITY (802.11)**







## 6.7. CONDUCTED SPURIOUS EMISSIONS

### LIMITS

§15.247 (c) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions, which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.


The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

### RESULTS


No non-compliance noted:


**SPURIOUS EMISSIONS, LOW CHANNEL (802.11)**







**SPURIOUS EMISSIONS, MID CHANNEL (802.11)**





**SPURIOUS EMISSIONS, HIGH CHANNEL (802.11)**





## 6.8. RADIATED EMISSIONS

### 6.8.1. TRANSMITTER RADIATED SPURIOUS EMISSIONS

#### LIMITS

§15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	( <sup>2</sup> )
13.36 - 13.41			

<sup>1</sup> Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

<sup>2</sup> Above 38.6

§15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

§15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 - 88	100 **	3
88 - 216	150 **	3
216 - 960	200 **	3
Above 960	500	3

\*\* Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

§15.209 (b) In the emission table above, the tighter limit applies at the band edges.

### **TEST PROCEDURE**

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.4. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements.

The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.


The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.


### **RESULTS**

No non-compliance noted:


### 6.8.2. TRANSMITTER RADIATED EMISSIONS ABOVE 1 GHZ


#### RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)







**RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)**







**RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)**





**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)**





## HARMONICS AND SPURIOUS EMISSIONS

10/04/04 High Frequency Measurement Compliance Certification Services, Morgan Hill Open Field Site																																								
Test Engr: Chin Pang Project #: 04I2987-1 Company: Nintendo Co., LTD EUT Descrip.: Nintendo DS (2nd Class II) EUT M/N: NTR-001 Test Target: FCC class B Mode Oper: TX																																								
<b>Test Equipment:</b> <table border="1"> <tr> <td>EMCO Horn 1-18GHz</td> <td>Pre-amplifier 1-26 GHz</td> <td>Pre-amplifier 26-40GHz</td> <td colspan="3">Horn &gt; 18GHz</td> <td>Limit</td> </tr> <tr> <td>T60; S/N: 2238 @3m</td> <td>T86 Miteq 924341</td> <td></td> <td colspan="3"></td> <td>FCC 15.205</td> </tr> </table> Hi Frequency Cables <table border="1"> <tr> <td>2 foot cable</td> <td>3 foot cable</td> <td>4 foot cable</td> <td>12 foot cable</td> <td>HPF</td> <td>Reject Filter</td> </tr> <tr> <td>2_Chin</td> <td></td> <td></td> <td>12_Thanh</td> <td>HPF_4.0GHz</td> <td></td> </tr> </table>															EMCO Horn 1-18GHz	Pre-amplifier 1-26 GHz	Pre-amplifier 26-40GHz	Horn > 18GHz			Limit	T60; S/N: 2238 @3m	T86 Miteq 924341					FCC 15.205	2 foot cable	3 foot cable	4 foot cable	12 foot cable	HPF	Reject Filter	2_Chin			12_Thanh	HPF_4.0GHz	
EMCO Horn 1-18GHz	Pre-amplifier 1-26 GHz	Pre-amplifier 26-40GHz	Horn > 18GHz			Limit																																		
T60; S/N: 2238 @3m	T86 Miteq 924341					FCC 15.205																																		
2 foot cable	3 foot cable	4 foot cable	12 foot cable	HPF	Reject Filter																																			
2_Chin			12_Thanh	HPF_4.0GHz																																				
<b>Peak Measurements</b> RBW=VBW=1MHz																																								
<b>Average Measurements</b> RBW=1MHz ; VBW=10Hz																																								
f GHz	Dist (m)	Read Pk dBuV	Read Avg dBuV	AF dB/m	CL dB	Amp dB	D Corr dB	Fltr dB	Peak dBuV/m	Avg dBuV/m	Pk Lim dBuV/m	Avg Lim dBuV/m	Pk Mar dB	Avg Mar dB	Notes (V/H)																									
<b>Transmitting at low ch, 2412MHz</b>																																								
4.824	3.0	47.9	36.1	33.0	3.3	-44.0	0.0	0.6	40.8	29.0	74	54	-33.2	-25.0	V																									
12.060	3.0	48.5	36.3	38.4	5.6	-44.0	0.0	0.9	49.4	37.2	74	54	-24.6	-16.8	V																									
4.824	3.0	48.2	36.3	33.0	3.3	-44.0	0.0	0.6	41.1	29.2	74	54	-32.9	-24.8	H																									
12.060	3.0	48.3	36.2	38.4	5.6	-44.0	0.0	0.9	49.2	37.1	74	54	-24.8	-16.9	H																									
<b>Transmitting at mid ch, 2442MHz</b>																																								
4.884	3.0	47.5	35.7	33.0	3.3	-44.1	0.0	0.6	40.3	28.5	74	54	-33.7	-25.5	V																									
7.326	3.0	48.2	36.1	35.9	4.1	-45.0	0.0	0.6	43.8	31.7	74	54	-30.2	-22.3	V																									
12.210	3.0	49.3	36.5	38.5	5.6	-44.2	0.0	0.9	50.0	37.2	74	54	-24.0	-16.8	V																									
4.884	3.0	48.0	36.0	33.0	3.3	-44.1	0.0	0.6	40.8	28.8	74	54	-33.2	-25.2	H																									
7.326	3.0	48.7	36.3	35.9	4.1	-45.0	0.0	0.6	44.3	31.9	74	54	-29.7	-22.1	H																									
12.210	3.0	50.1	36.7	38.5	5.6	-44.2	0.0	0.9	50.8	37.4	74	54	-23.2	-16.6	H																									
<b>Transmitting at high ch, 2472MHz</b>																																								
4.944	3.0	47.3	35.6	33.0	3.3	-44.2	0.0	0.6	40.1	28.4	74	54	-33.9	-25.6	V																									
7.416	3.0	48.9	36.3	36.1	4.1	-45.0	0.0	0.6	44.7	32.1	74	54	-29.3	-21.9	V																									
12.360	3.0	49.1	36.4	38.5	5.6	-44.5	0.0	0.9	49.6	36.9	74	54	-24.4	-17.1	V																									
4.944	3.0	47.6	35.7	33.0	3.3	-44.2	0.0	0.6	40.4	28.5	74	54	-33.6	-25.5	H																									
7.416	3.0	49.3	36.5	36.1	4.1	-45.0	0.0	0.6	45.1	32.3	74	54	-28.9	-21.7	H																									
12.360	3.0	49.5	36.5	38.5	5.6	-44.5	0.0	0.9	50.0	37.0	74	54	-24.0	-17.0	H																									
<b>Note: No other emissions were detected above the system noise floor.</b>																																								
f Measurement Frequency Dist Distance to Antenna Read Analyzer Reading AF Antenna Factor CL Cable Loss								Amp Preamp Gain D Corr Distance Correct to 3 meters Avg Average Field Strength @ 3 m Peak Calculated Peak Field Strength HPF High Pass Filter																																
								Avg Lim Average Field Strength Limit Pk Lim Peak Field Strength Limit Avg Mar Margin vs. Average Limit Pk Mar Margin vs. Peak Limit																																

WORST-CASE RADIATED EMISSIONS BELOW 1 GHz


**SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, HORIZONTAL)**

HORIZONTAL PLOT



561F Monterey Road  
Morgan Hill, CA 95037  
Tel: (408) 463-0888  
Fax: (408) 463-0885

Data#: 6 File#: nintendo test.EMI Date: 10-21-2004 Time: 16:03:00



(Audit ATC)

Trace: 5

Ref Trace:

Condition: FCC CLASS-B HORIZONTAL  
Test Operator: : Chin Pang  
Project #: : 004I2987-3  
Company: : Nintendo Co., LTD  
EUT: : Nintendo DS  
Model No: : NTR-001  
Configuration: : EUT/AC Adapter  
Target of Test: : FCCClass B  
Mode of Operation: TX ( Worse Case )  
: New AC Adapter #2

HORIZONTAL DATA

Page: 1

Freq	Remark	Read	Factor	Limit	Over	Limit	
		Level		Line	dB		
MHz		dBuV		dB	dBuV/m	dBuV/m	dB
1	30.970	Peak	8.78	23.32	32.10	40.00	-7.90
2	121.180	Peak	13.39	15.40	28.79	43.50	-14.71
3	131.850	Peak	10.79	15.89	26.67	43.50	-16.83
4	502.390	Peak	12.29	21.02	33.31	46.00	-12.69
5	744.890	Peak	11.95	24.68	36.63	46.00	-9.37


**SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, VERTICAL)**

VERTICAL PLOT



561F Monterey Road  
Morgan Hill, CA 95037  
Tel: (408) 463-0888  
Fax: (408) 463-0885

Data#: 8 File#: nintendo test.EMI Date: 10-21-2004 Time: 16:06:27



(Audix ATC)  
Trace: 7

Ref Trace:

Condition: FCC CLASS-B VERTICAL  
Test Operator: : Chin Pang  
Project #: : 004I2987-3  
Company: : Nintendo Co., LTD  
EUT: : Nintendo DS  
Model No: : NTR-001  
Configuration: : EUT/AC Adapter  
Target of Test: : FCCClass B  
Mode of Operation: TX ( Worse Case )  
: New AC Adapter #2

VERTICAL DATA

Page: 1

Freq	Remark	Read	Level	Limit	Over	Limit	
		Level		Factor	Line		Limit
MHz		dBuV	dB	dBuV/m	dBuV/m	dB	
1	30.000	Peak	8.92	23.32	32.24	40.00	-7.76
2	53.280	Peak	21.39	9.38	30.77	40.00	-9.23
3	65.890	Peak	16.36	9.66	26.02	40.00	-13.98
4	470.380	Peak	14.52	20.29	34.81	46.00	-11.19
5	477.170	Peak	14.57	20.46	35.02	46.00	-10.98
6	814.730	Peak	12.30	25.51	37.81	46.00	-8.19

## 6.9. POWERLINE CONDUCTED EMISSIONS

### LIMIT

§15.207 (a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal.

The lower limit applies at the boundary between the frequency ranges.

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56 <sup>*</sup>	56 to 46 <sup>*</sup>
0.5-5	56	46
5-30	60	50

<sup>\*</sup> Decreases with the logarithm of the frequency.

### TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.4.

The resolution bandwidth is set to 9 kHz for both peak detection and quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

Line conducted data is recorded for both NEUTRAL and HOT lines.


### RESULTS

No non-compliance noted:

**6 WORST EMISSIONS**

CONDUCTED EMISSIONS DATA (115VAC 60Hz)									
Freq. (MHz)	Reading			Closs (dB)	Limit QP	EN_B AV	Margin		Remark
	PK (dBuV)	QP (dBuV)	AV (dBuV)				QP (dB)	AV (dB)	
0.19	43.37	--	33.81	0.00	64.97	54.97	-21.60	-21.16	L1
0.93	50.14	--	33.39	0.00	56.00	46.00	-5.86	-12.61	L1
5.68	50.92	--	25.08	0.00	60.00	50.00	-9.08	-24.92	L1
0.42	42.43	--	34.08	0.00	58.37	48.37	-15.94	-14.29	L2
0.85	46.65	--	36.04	0.00	56.00	46.00	-9.35	-9.96	L2
5.99	45.26	--	21.47	0.00	60.00	50.00	-14.74	-28.53	L2
6 Worst Data									

**LINE 1 RESULTS**



LINE 2 RESULTS

