

# Seiko Epson Corporation

# TEST REPORT

**SCOPE OF WORK**

FCC TESTING – WXT2AM2101

**REPORT NUMBER**

250106059SZN-002

**ISSUE DATE**

21 April 2025

**[REVISED DATE]**

[-----]

**PAGES**

34

**DOCUMENT CONTROL NUMBER**

FCC ID 247\_b

© 2017 INTERTEK



## Seiko Epson Corporation

Application  
For  
Certification

**FCC ID: BKMAE-WXT2AM**

**WLAN BT Module**

**Model: WXT2AM2101**

**Brand Name: EPSON  
2.4GHz Transceiver**

Report No.: 250106059SZN-002

We hereby certify that the sample of the above item is considered to comply with the  
requirements of FCC Part 15, Subpart C for Intentional Radiator,  
mention 47 CFR [10-1-23]

**Prepared and Checked by:**

**Allen Qin  
Engineer**

**Approved by:**

---

**Johnny Wang  
Project Engineer  
Date: 21 April 2025**

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

**Intertek Testing Services Shenzhen Ltd. Longhua Branch**

101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, Shenzhen, P.R. China.  
Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6751

## MEASUREMENT/TECHNICAL REPORT

This report concerns (check one)      Original Grant       Class II Change

Equipment Type: DTS - Part 15 Digital Transmission Systems

---

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)?      Yes       No

If yes, defer until: \_\_\_\_\_  
date

Company Name agrees to notify the Commission by: \_\_\_\_\_  
date

of the intended date of announcement of the product so that the grant can be issued on  
that date.

---

Transition Rules Request per 15.37?      Yes       No

If no, assumed Part 15, Subpart C for intentional radiator - the new 47 CFR [10-1-23]  
Edition] provision.

---

Report prepared by:

**Allen Qin**  
**Intertek Testing Services Shenzhen Ltd. Longhua Branch**  
101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing  
Community, GuanHu Subdistrict, LongHua District, Shenzhen,  
P.R. China.  
Tel: (86 755) 8614 0743 Fax: (86 755) 8601 6661

## Table of Contents

<b>1.0</b>	<b>Summary of Test results</b>	<b>4</b>
<b>2.0</b>	<b><u>General Description</u></b>	<b>5</b>
2.1	Product Description .....	5
2.2	Related Submittal(s) Grants .....	5
2.3	Test Methodology .....	5
2.4	Test Facility .....	5
<b>3.0</b>	<b><u>System Test Configuration</u></b>	<b>6</b>
3.1	Justification .....	6
3.2	EUT Exercising Software .....	6
3.3	Special Accessories .....	6
3.4	Measurement Uncertainty .....	7
3.5	Equipment Modification .....	7
3.6	Support Equipment List and Description .....	7
<b>4.0</b>	<b><u>Measurement Results</u></b>	<b>8</b>
4.1	Maximum Conducted Output Power at Antenna Terminals .....	8
4.2	Minimum 6 dB RF Bandwidth .....	9
4.3	Maximum Power Density Reading .....	11
4.4	Out of Band Conducted Emissions .....	13
4.5	Out of Band Radiated Emissions .....	18
4.6	Transmitter Radiated Emissions in Restricted Bands .....	19
4.7	Field Strength Calculation .....	21
4.8	Radiated Spurious Emission .....	22
4.9	Conducted Emission .....	28
4.10	Radiated Emissions from Digital Section of Transceiver .....	31
4.11	Transmitter Duty Cycle Calculation and Measurements .....	32
<b>5.0</b>	<b><u>Equipment Photographs</u></b>	<b>33</b>
<b>6.0</b>	<b><u>Product Labelling</u></b>	<b>33</b>
<b>7.0</b>	<b><u>Technical Specifications</u></b>	<b>33</b>
<b>8.0</b>	<b><u>Instruction Manual</u></b>	<b>33</b>
<b>9.0</b>	<b><u>Confidentiality Request</u></b>	<b>33</b>
<b>10.0</b>	<b><u>Discussion of Pulse Desensitization</u></b>	<b>33</b>
<b>11.0</b>	<b><u>Test Equipment List</u></b>	<b>34</b>

## **1.0 Summary of Test results**

Applicant: Seiko Epson Corporation

Applicant Address: 3-3-5 Owa Suwa-shi Nagano-Ken 392-8502, Japan

Manufacturer: Seiko Epson Corporation

Manufacturer Address: 3-3-5 Owa Suwa-shi Nagano-Ken 392-8502, Japan

Model: WXT2AM2101

FCC ID: BKMAE-WXT2AM

TEST ITEM	REFERENCE	RESULTS
Max. Output power	15.247(b)(3)	Pass
6 dB Bandwidth	15.247(a)(2)	Pass
Max. Power Density	15.247(e)	Pass
Out of Band Antenna Conducted Emission	15.247(d)	Pass
Radiated Emission in Restricted Bands	15.247(d), 15.209, FCC 15.205	Pass
AC Conducted Emission	15.207	Pass
Antenna Requirement	15.203	Pass (See Notes)

Notes:

1. The EUT uses an Integral Antenna which in accordance to Section 15.203 is considered sufficient to comply with the provisions of this section.

## **2.0 General Description**

### **2.1 Product Description**

The equipment under test (EUT) is a WLAN BT Module with Bluetooth (dual-mode) function operating in 2402-2480MHz, 2.4G WIFI function operating in 2412-2462MHz, 5G WIFI function operating in 5150MHz~5250 MHz, 5250MHz~5350MHz, 5470MHz-5725MHz, 5725MHz~5850MHz and 6G WIFI function operating in 5925MHz~7125MHz.. The EUT is powered by DC 3.3V. For more detail information pls. refer to the user manual.

Software Version: V2.39

Hardware Version: V1.3B

Type of Modulation: GFSK (BLE)

Antenna Type: FPC Antenna

Antenna Gain: -1.01dBi (This information is provided by manufacturer, and the manufacturer is responsible for the authenticity of the provided information.)

Bluetooth Version: 5.4

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

### **2.2 Related Submittal(s) Grants**

This is an application for certification of a transceiver for the WLAN BT Module which has BT BLE function.

For the classic Bluetooth function was tested and demonstrated in report 250106059SZN-001.

For the 2.4GHz WIFI function was tested and demonstrated in report 250106059SZN-003.

For the 5GHz WIFI function was tested and demonstrated in report 250106059SZN-004.

For the 6GHz WIFI function was tested and demonstrated in report RF250116007-01-001.

### **2.3 Test Methodology**

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.10 (2013) and KDB 558074 D01 v05r02. Radiated emission measurement was performed in semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst-case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

### **2.4 Test Facility**

The Semi-anechoic chamber and shielded room used to collect the radiated data and conducted data are **Intertek Testing Services Shenzhen Ltd. Longhua Branch** and located at 101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, Shenzhen, P.R. China. This test facility and site measurement data have been fully placed on file with File Number: CN1188.

### **3.0 System Test Configuration**

#### **3.1 Justification**

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, all cables were manipulated to produce worst case emissions. The EUT was powered by DC 3.3V from the laptop during the test.

For maximizing emissions, the EUT was rotated through 360°, the EUT was placed on the styrene turntable with 0.8m up to 1GHz and 1.5 m above 1GHz. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

The rear of unit shall be flushed with the rear of the table.

Radiated emission measurement were performed the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

#### **3.2 EUT Exercising Software**

The EUT exercise program (provided by client) used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use. The worst-case configuration is used in all specified testing.

The parameters of test software setting:

During the test, Channel and power controlling software provided by the applicant was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the application and is going to be fixed on the firmware of the end product.

Test software: WCN Combo tool

#### **3.3 Special Accessories**

N/A.

### 3.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

### 3.5 Equipment Modification

Any modifications installed previous to testing by Seiko Epson Corporation will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Longhua Branch.

### 3.6 Support Equipment List and Description

Description	Manufacturer	Remark
Laptop (Provided by Intertek)	DELL	Latitude 3480
USB Cable (Provided by Intertek)	N/A	unshielded, 55cm

Applicant: Seiko Epson Corporation  
Date of Test: 13 January 2025


Model: WXT2AM2101

#### 4.0 Measurement Results

##### 4.1 Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b)(3):

The antenna power of the EUT was connected to the input of a broadband peak RF power meter. The power meter has a video bandwidth that is greater than DTS bandwidth and utilize a fast-responding diode detector. Power was read directly at the EUT antenna terminals with cable loss added.

Block Diagram:



Power meter

For antennas with gains of 6 dBi or less, maximum allowed Transmitter output is 1 watt (+30 dBm).

BLE 1MHz

Frequency (MHz)	Output in dBm (Peak Reading)	Output in mWatt
Low Channel: 2402	2.70	1.86
Middle Channel: 2440	2.43	1.75
High Channel: 2480	2.39	1.73

BLE 2MHz

Frequency (MHz)	Output in dBm (Peak Reading)	Output in mWatt
Low Channel: 2402	2.74	1.88
Middle Channel: 2440	2.43	1.75
High Channel: 2480	2.39	1.73

Cable loss: 0.5 dB    External Attenuation: 0 dB

Cable loss, external attenuation has been included in OFFSET function

For RF Exposure, the information is saved with filename: RF exposure.pdf.


Applicant: Seiko Epson Corporation  
Date of Test: 13 January 2025

Model: WXT2AM2101

#### 4.2 Minimum 6 dB RF Bandwidth, FCC Rule 15.247(a) (2):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RES BW was set to 100 KHz according to FCC KDB 558074 D01 v05r02. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK output reading was taken, a DISPLAY line was drawn 6 dB lower than PEAK level. The 6dB bandwidth was determined from where the channel output spectrum intersected the display line.

Block Diagram:



Spectrum Analyzer

Limit: The 6 dB Bandwidth is at least 500 kHz.

Worst case data:

Frequency (MHz)	6 dB Bandwidth (MHz)
2402	0.668
2440	0.672
2480	0.668

The test plots are attached as below.



Applicant: Seiko Epson Corporation  
Date of Test: 13 January 2025

Model: WXT2AM2101

#### 4.3 Maximum Power Density Reading, FCC Rule 15.247(e):

The Measurement Procedure PKPSD was set according to the FCC KDB 558074 D01 v05r02.

Antenna output of the EUT was coupled directly to spectrum analyzer; if an external attenuator and/or cable was used, these losses are compensated for with the analyzer OFFSET function.  
Block Diagram:




Spectrum Analyzer


Limit: The Power Density does not exceed 8dBm/3 kHz.

Worst case data:

Frequency (MHz)	Power Density with RBW 3KHz
2402	-14.42
2440	-14.6
2480	-14.76

The test plots are attached as below.





Applicant: Seiko Epson Corporation  
Date of Test: 13 January 2025

Model: WXT2AM2101

#### 4.4 Out of Band Conducted Emissions, FCC Rule 15.247(d)


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. The Measurement Procedure was set according to the FCC KDB 558074 D01 v05r02.

All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the passband.

Refer to the attached test plots for out of band conducted emissions data with rate of 1Mbps for BLE.

The test plots showed all spurious emission up to the tenth harmonic were measured and they were found to be at least 20 dB below the highest level of the desired power in the passband.

Block Diagram:



Spectrum Analyzer


Worst case data:


Test Result:


TestMode	Channel	FreqRange [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	2402	Reference	2.50	2.50	---	PASS
		0.009~2400	2.50	-56.61	<=-17.5	PASS
		2483.5~25000	2.50	-52.12	<=-17.5	PASS
	2440	Reference	2.11	2.11	---	PASS
		0.009~2400	2.11	-56.93	<=-17.89	PASS
		2483.5~25000	2.11	-52.57	<=-17.89	PASS
	2480	Reference	1.89	1.89	---	PASS
		0.009~2400	1.89	-57.1	<=-18.11	PASS
		2483.5~25000	1.89	-52.48	<=-18.11	PASS


TestMode	ChName	Channel	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Low	2402	2.28	-58.32	<=-17.72	PASS
	High	2480	1.87	-57.3	<=-18.13	PASS

The test plots are attached as below.









Applicant: Seiko Epson Corporation  
Date of Test: 13 January 2025

Model: WXT2AM2101

**4.5 Out of Band Radiated Emissions (for emissions in 4.4 above that are less than 20dB below carrier), FCC Rule 15.247(d):**

For out of band emissions that are close to or that exceed the 20dB attenuation requirement described in the specification, radiated measurements were performed at a 3m separation distance to determine whether these emissions complied with the general radiated emission requirement.

- Not required, since all emissions are more than 20dB below fundamental
- See attached data sheet

Applicant: Seiko Epson Corporation  
Date of Test: 21 January 2025



Model: WXT2AM2101


#### 4.6 Transmitter Radiated Emissions in Restricted Bands, FCC Rule 15.35(b) (c):

Data is included of the worst-case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included. All measurements were performed with peak detection unless otherwise specified.

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

The Diagram below shows the test setup, which is utilized to make these measurements.





Test set-up of radiated disturbance (Above 1GHz)

Radiated emission measurements were performed from 9kHz to tenth harmonic or 40GHz. The EUT for testing is arranged on a styrene turntable. If some peripherals apply to the EUT, the peripherals will be connected to EUT and the whole system. During the test, all cables were arranged to produce worst-case emissions. The signal is maximized through rotation. The height of antenna and polarization is changing constantly for exploring for maximum signal level. The height of antenna can be up to 4 meters and down to 1 meter.

Applicant: Seiko Epson Corporation  
Date of Test: 21 January 2025

Model: WXT2AM2101

#### 4.7 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD$$

Where            FS = Field Strength in dB $\mu$ V/m

                  RA = Receiver Amplitude (including preamplifier) in dB $\mu$ V

                  CF = Cable Attenuation Factor in dB

                  AF = Antenna Factor in dB

                  AG = Amplifier Gain in dB

                  PD = Pulse Desensitization in dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD$$

#### Example

Assume a receiver reading of 62.0 dB $\mu$ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB. The net field strength for comparison to the appropriate emission limit is 42 dB $\mu$ V/m. This value in dB $\mu$ V/m was converted to its corresponding level in  $\mu$ V/m.

$$RA = 62.0 \text{ dB}\mu\text{V}$$

$$AF = 7.4 \text{ dB}$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$PD = 0 \text{ dB}$$

$$FS = 62 + 7.4 + 1.6 - 29 + 0 = 42 \text{ dB}\mu\text{V/m}$$

Level in mV/m = Common Antilogarithm  $[(42 \text{ dB}\mu\text{V/m})/20] = 125.9 \mu\text{V/m}$

Applicant: Seiko Epson Corporation  
Date of Test: 21 January 2025

Model: WXT2AM2101

#### 4.8 Radiated Spurious Emission

Worst Case Radiated Spurious Emission  
at 2483.500MHz  
is passed by 5.4dB margin.

For the electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf. Simultaneous transmission was considered during the test, only the worst-case data is recorded in this report.

Applicant: Seiko Epson Corporation

Date of Test: 21 January 2025


Worst Case Operating Mode:

Model: WXT2AM2101

Transmit (2402MHz)

ANT Polarity: Horizontal

FCC Part 15



Frequency (MHz)	Quasi Peak (dB $\mu$ V/m)	Meas. Time (ms)	Bandwidth (kHz)	Polarization	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dB $\mu$ Vm)
241.783333	25.9	1000.0	120.000	H	18.8	20.1	46.0
351.167000	26.8	1000.0	120.000	H	22.9	19.2	46.0
559.005667	29.2	1000.0	120.000	H	29.0	16.8	46.0

## Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Quasi Peak (dB $\mu$ V/m) = Corr. (dB/m) + Read Level (dB $\mu$ V)
3. Margin (dB) = Limit Line (dB $\mu$ V/m) – Level (dB $\mu$ V/m)

Applicant: Seiko Epson Corporation

Date of Test: 21 January 2025


Worst Case Operating Mode:

Model: WXT2AM2101

Transmit (2402MHz)

ANT Polarity: Vertical

FCC Part 15



Frequency (MHz)	Quasi Peak (dB $\mu$ V/m)	Meas. Time (ms)	Bandwidth (kHz)	Polarization	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dB $\mu$ V/m)
273.696333	19.6	1000.0	120.000	V	19.8	26.4	46.0
424.434333	31.5	1000.0	120.000	V	25.4	14.5	46.0
729.919667	35.4	1000.0	120.000	V	31.0	10.6	46.0

Remark:

1. Corr. = Antenna Factor (dB/m) + Cable Loss (dB)
2. Quasi Peak (dB $\mu$ V/m) = Corr. (dB/m) + Read Level (dB $\mu$ V)
3. Margin (dB) = Limit Line (dB $\mu$ V/m) – Level (dB $\mu$ V/m)

Applicant: Seiko Epson Corporation

Date of Test: 21 January 2025

Worst Case Operating Mode:

Model: WXT2AM2101

Transmitting (Channel 0)

**Radiated Emissions (above 1GHz)**

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	*9608.000	52.6	36.8	33.5	49.3	74.0	-24.7
Vertical	*2390.000	67.3	36.4	29.1	60.0	74.0	-14.0

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	*9608.000	44.8	36.8	33.5	41.5	54.0	-12.5
Vertical	*2390.000	55.7	36.4	29.1	48.4	54.0	-5.6

## NOTES:

1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz/VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.

\* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: Seiko Epson Corporation

Date of Test: 21 January 2025

Worst Case Operating Mode:

Model: WXT2AM2101

Transmitting (Channel 19)

**Radiated Emissions (above 1GHz)**

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	*7320.000	50.6	36.7	33.4	47.3	74.0	-26.7
Vertical	*9760.000	52.0	36.6	35.8	51.2	74.0	-22.8

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	*7320.000	37.1	36.7	33.4	33.8	54.0	-20.2
Vertical	*9760.000	43.1	36.6	35.8	42.3	54.0	-11.7

## NOTES:

1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.

\* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: Seiko Epson Corporation

Date of Test: 21 January 2025

Worst Case Operating Mode:

Model: WXT2AM2101

Transmitting (Channel 39)

**Radiated Emissions (above 1GHz)**

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	*7440.000	51.7	36.8	33.3	48.2	74.0	-25.8
Vertical	*9920.000	58.8	36.5	29.3	51.6	74.0	-22.4
Vertical	*2483.500	68.7	36.4	29.3	61.6	74.0	-12.4

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB/m)	Net at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
Vertical	*7440.000	39.2	36.8	33.3	35.7	54.0	-18.3
Vertical	*9920.000	45.6	36.5	29.3	38.4	54.0	-15.6
Vertical	*2483.500	55.7	36.4	29.3	48.6	54.0	-5.4


## NOTES:

1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- \* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Applicant: Seiko Epson Corporation  
Date of Test: 27 March 2025  
Model: WXT2AM2101

#### 4.9 Conducted Emission

Block Diagram:



For tabletop equipment, the EUT along with its peripherals were placed on a 1.0m(W)×1.5m(L) and 0.8m in height wooden table. The EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane. The EUT was connected to power mains through a line impedance stabilization network (LISN), which provided 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room. The excess power cable between the EUT and the LISN was bundled.

Simultaneous transmission was considered during the test, only the worst-case data is recorded in this report.

Worst Case Conducted Emission  
at 0.154MHz  
is passed by 23.4dB margin.

For the electronic filing, the worst case radiated emission configuration photographs are saved with filename: conducted photos.pdf.

Applicant: Seiko Epson Corporation

Date of Test: 27 March 2025

Model: WXT2AM2101


Worst Case Operating Mode: Transmit (2402MHz)

Phase: Live

## Graphic / Data Table

### Conducted Emissions Pursuant to FCC 15.207: Emissions Requirement

Conducted Emission Test FCC Part 15



### Limit and Margin QP

Frequency (MHz)	Quasi Peak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.154000	42.4	9.000	L1	9.6	23.4	65.8
0.178000	38.1	9.000	L1	9.6	26.5	64.6
0.750000	17.1	9.000	L1	9.6	38.9	56.0
3.846000	16.5	9.000	L1	9.7	39.5	56.0
15.526000	22.2	9.000	L1	10.4	37.8	60.0
19.302000	15.5	9.000	L1	10.2	44.5	60.0

### Limit and Margin AV

Frequency (MHz)	Average (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.154000	19.0	9.000	L1	9.6	36.8	55.8
0.178000	16.2	9.000	L1	9.6	38.4	54.6
0.750000	6.1	9.000	L1	9.6	39.9	46.0
3.846000	6.0	9.000	L1	9.7	40.0	46.0
15.526000	14.4	9.000	L1	10.4	35.6	50.0
19.302000	5.6	9.000	L1	10.2	44.4	50.0

Remark:

1. Corr. Factor (dB) = LISN Factor (dB) + Cable Loss (dB)

2. Margin (dB) = Limit (dBµV) – Level (dBµV)

Applicant: Seiko Epson Corporation

Date of Test: 27 March 2025

Model: WXT2AM2101

Worst Case Operating Mode: Transmit (2402MHz)


Phase: Neutral

### Graphic / Data Table

#### Conducted Emissions

#### Pursuant to FCC 15.207: Emissions Requirement

Conducted Emission Test FCC Part 15



#### Limit and Margin QP

Frequency (MHz)	Quasi Peak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.182000	36.7	9.000	N	9.6	27.7	64.4
0.210000	32.1	9.000	N	9.6	31.1	63.2
1.778000	17.9	9.000	N	9.7	38.1	56.0
3.934000	18.4	9.000	N	9.7	37.6	56.0
15.686000	22.0	9.000	N	10.4	38.0	60.0
26.702000	18.8	9.000	N	10.9	41.2	60.0

#### Limit and Margin AV

Frequency (MHz)	Average (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.182000	16.2	9.000	N	9.6	38.2	54.4
0.210000	13.8	9.000	N	9.6	39.4	53.2
1.778000	9.6	9.000	N	9.7	36.4	46.0
3.934000	10.0	9.000	N	9.7	36.0	46.0
15.686000	14.6	9.000	N	10.4	35.4	50.0
26.702000	5.9	9.000	N	10.9	44.1	50.0

Remark:

1. Corr. Factor (dB) = LISN Factor (dB) + Cable Loss (dB)

2. Margin (dB) = Limit (dBµV) – Level (dBµV)

Applicant: Seiko Epson Corporation  
Date of Test: 13 January 2025  
Model: WXT2AM2101

4.10 Radiated Emissions from Digital Section of Transceiver, FCC Ref: 15.109

- [ ] Not required - No digital part
- [ ] Test results are attached
- [ x ] Included in the separated report.

Applicant: Seiko Epson Corporation  
Date of Test: 13 January 2025  
Model: WXT2AM2101

#### 4.11 Transmitter Duty Cycle Calculation and Measurements, FCC Rule 15.35(b), (c)

The EUT antenna output port was connected to the input of the spectrum analyzer. The analyzer center frequency was set to EUT RF channel carrier. The SWEP function on the analyzer was set to ZERO SPAN. The Transmitter ON time was determined from the resultant time-amplitude display:

	See attached spectrum analyzer chart (s) for Transmitter timing
	See Transmitter timing diagram provided by manufacturer
x	Not applicable, duty cycle was not used.

## **5.0 Equipment Photographs**

For electronic filing, the photographs are saved with filename: external photos.pdf & internal photos.pdf.

## **6.0 Product Labeling**

For electronic filing, the FCC ID label artwork and location is saved with filename: label.pdf.

## **7.0 Technical Specifications**

For electronic filing, the block diagram and circuit diagram are saved with filename: block.pdf and circuit.pdf respectively.

## **8.0 Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

## **9.0 Confidentiality Request**

For electronic filing, the confidentiality request of the tested EUT is saved with filename: request.pdf.

## **10.0 Discussion of Pulse Desensitization**

The determination of pulse desensitivity was made in accordance with Hewlett Packard Application Note 150-2, *Spectrum Analysis ... Pulsed RF*.

Pulse desensitivity is not applicable for this device since the transmitter transmits the RF signal continuously.

**11.0 Test Equipment List**

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ182-02	RF Power Meter	Anritsu	ML2496A	1302005	2024-04-22	2025-04-22
SZ182-02-01	Power Sensor	Anritsu	MA2411B	1207429	2024-04-22	2025-04-22
SZ061-13	BiConiLog Antenna	ETS	3142E	00217919	2022-07-13	2025-07-13
SZ185-03	EMI Receiver	R&S	ESCI	101975	2024-04-23	2025-04-23
SZ061-08	Horn Antenna	ETS	3115	00092346	2024-09-13	2027-09-13
SZ061-06	Active Loop Antenna	Electro-Metrics	EM-6876	217	2024-05-05	2027-05-05
SZ056-03	Spectrum Analyzer	R&S	FSP 30	101148	2024-04-22	2025-04-22
SZ056-08	Signal Analyzer	R&S	FSV 40	101430	2024-12-06	2025-12-06
SZ181-04	Preamplifier	Agilent	8449B	3008A02474	2024-04-22	2025-04-22
SZ188-01	Anechoic Chamber	ETS	RFD-F/A-100	4102	2021-12-12	2026-12-12
SZ062-24	RF Cable	RADIALL	RG 213U	--	2024-09-30	2025-09-30
SZ062-25	RF Cable	RADIALL	0.04-26.5GHz	--	2024-09-30	2025-09-30
SZ062-38	RF Cable	RADIALL	0.04-26.5GHz	--	2024-09-30	2025-09-30
SZ067-04	Notch Filter	Micro-Tronics	BRM50702-02	--	2024-04-23	2025-04-23
SZ185-02	EMI Test Receiver	R&S	ESCI	100692	2024-07-09	2025-07-09
SZ187-02	Two-Line V-Network	R&S	ENV216	100073	2024-10-24	2025-10-24
SZ188-03	Shielding Room	ETS	RFD-100	4100	2022-12-20	2025-12-20

\*\*\*\*\* End of Report\*\*\*\*\*