



RF Exposure Compliance Requirement

1. Standard requirement

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

(a) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm ²)	Averaging Times $ E ^2, H ^2$ or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100000			5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm ²)	Averaging Times $ E ^2, H ^2$ or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/500	30
1500-100000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density



2. MPE Calculation Method

$$E (V/m) = (30 \cdot P \cdot G)^{0.5} / d \quad \text{Power Density: } Pd(W/m^2) = E^2 / 377$$

E=Electric Field (V/m)

P=Peak RF output Power (W)

G=EUT Antenna numeric gain (numeric)

d= Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = (30 \cdot P \cdot G) / (377 \cdot d^2)$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

3. Calculated Result and Limit

Normal:

Frequency (MHz)	Antenna Gain (Numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
2402	1.0	1.36	1.3677	0.0002721	1	Compliance
2441	1.0	0.70	1.1749	0.0002337	1	Compliance
2480	1.0	-0.35	0.9226	0.0001835	1	Compliance

EDR:

Frequency (MHz)	Antenna Gain (Numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
2402	1.0	0.89	1.2274	0.0002441	1	Compliance
2441	1.0	0.20	1.0471	0.0002083	1	Compliance
2480	1.0	-1.07	0.7816	0.0001555	1	Compliance