

Recognized by the
Federal Communications Commission
Anechoic chamber registration no.: 90462 (FCC)
Anechoic chamber registration no.: 3463 (IC)
TCB ID: DE 0001



Accredited by the
German Accreditation Council
DAR-Registration Number
TTI-P-G 081/94-DO



Independent ETSI
compliance test house



Accredited Bluetooth™ Test Facility (BQTF)

Test report no.: 2-3649-01-03/04
FCC Part 15.247 / CANADA RSS-210
FCC ID: BOUPSA260
psa260

CETECOM – ICT Services GmbH
Untertürkheimerstr. 6-10
D-66117 Saarbrücken, Germany

Telephone: + 49 (0) 681 / 598-0
Fax: + 49 (0) 681 / 598-9075

BLUETOOTH is a trademark owned by Bluetooth SIG, Inc. and licensed to Cetecom

SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 2 of 59

Table of contents

1. ADMINISTRATIVE DATA.....	3
1.1. ADMINISTRATIVE DATA OF THE TEST FACILITY	3
1.1.1 Identification of the testing laboratory	3
1.1.2 Organizational items	3
1.1.3 Applicant's details	4
1.2 ADMINISTRATIVE DATA OF MANUFACTURER / MEMBER	4
1.3 DESCRIPTION OF THE EQUIPMENT UNDER TEST (EUT)	5
1.3.1 EUT: Type, S/N etc.	5
1.3.2 If RF component testing only, description of additional used HW/SW	5
1.3.3 Additional EUT information For IC Canada (appendix 2).....	6
1.3.4 EUT operating modes	7
1.3.5 Extreme conditions testing values.....	7
2. TESTSTANDARD & SUMMARY LIST OF ALL PERFORMED TEST CASES	8
3. RF MEASUREMENT TESTING	9
3.1 DESCRIPTION OF TEST SET-UP.....	9
3.1.1 Radiated measurements	9
3.1.2 Conducted measurements	9
3.2 REFERENCED DOCUMENTS.....	10
3.3 ADDITIONAL COMMENTS	10
3.4 ANTENNA GAIN	10
3.5 CARRIER FREQUENCY SEPARATION §15.247(A1).....	11
3.6 NUMBER OF HOPPING CHANNELS §15.247(A1)	12
3.7 TIME OF OCCUPANCY (DWEIL TIME) §15.247(A1 III).....	14
3.8 POWER SPECTRAL DENSITY (HYBRID SYSTEM IN INQUIRY MODE/PAGE SCAN) §15.247(D).....	15
3.9 SPECTRUM BANDWIDTH OF A FHSS SYSTEM / 20dB BANDWITH §15.247(A1).....	16
3.10 MAXIMUM OUTPUT POWER (CONDUCTED) § 15.247 (B) (1)	19
3.11 MAX. PEAK OUTPUT POWER (RADIATED) § 15.247 (B) (1).....	22
3.12 BAND-EDGE COMPLIANCE OF CONDUCTED EMISSIONS §15.247 (C).....	23
3.13 BAND-EDGE COMPLIANCE OF RADIATED EMISSIONS §15.205	27
3.14 SPURIOUS EMISSIONS - CONDUCTED (TRANSMITTER) § 15.247 (C) (1)	32
3.15 SPURIOUS EMISSIONS - RADIATED (TRANSMITTER) § 15.247 (C) (1)	34
3.16 SPURIOUS EMISSIONS - RADIATED (RECEIVER) § 15.109.....	41
3.17 SPURIOUS EMISSIONS - RADIATED <30 MHz § 15.109.....	43
3.18 CONDUCTED EMISSIONS <30 MHz § 15.107/207	44
4 PHOTOGRAPHS	48

ANNEX 1: TECHNICAL PRODUCT DESCRIPTION

SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date: 2004-07-15

Page 3 of 59

1. Administrative data

1.1. Administrative data of the test facility


1.1.1 Identification of the testing laboratory

Company name:	Cetecom ICT Services GmbH
Address:	Untertürkheimerstr. 6-10 D-66117 Saarbruecken Germany
Laboratory accreditation:	DAR-Registration No. TTI-P-G 081/94-DO Bluetooth Qualification Test Facility (BQTF)
Responsible for testing laboratory:	Michael Berg / Dirk Hausknecht Phone: +49 681 598 0 Fax: +49 681 598 9075 email: info@ict.cetecom.de

 / 
.....
Responsible for testing laboratory
(Michael Berg / Dirk Hausknecht)

1.1.2 Organizational items

Reference No.:	2-3649-01-03/04
Order No.:	
Responsible for test report and project leader:	Dirk Hausknecht , Michael Berg
Receipt of EUT:	2004-07-08
Date(s) of test:	2004-07-08 to 2004-07-09
Date of report:	2004-07-15
Number of report pages:	59
Number of diagram pages (annex):	
Version of template:	1.6

 / 
.....
Responsible for test report
(Michael Berg / Dirk Hausknecht)

SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 4 of 59

Note:

The test results of this test report relate exclusively to the item tested as specified in this report. The CETECOM ICT Services GmbH does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item.

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of the CETECOM ICT Services GmbH.

During the test no hardware and software changes are allowed to be performed at the EUT.

1.1.3 Applicant's details

Applicant's name:	PHILIPS INNOVATIVE TECHNOLOGY SOLUTIONS NV
Address:	Interleuvenlaan 80 B-3001 Heverlee - Leuven Belgium
Contact person:	Mr. Francois Dupont Phone: +32 16 390 683 Fax: +32 16 390 601 e-mail: francois.Dupont@philips.com

1.2 Administrative data of manufacturer / member

Manufacturer's name:
Address:

SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 5 of 59

1.3 Description of the Equipment under test (EUT)

1.3.1 EUT: Type, S/N etc.

Product name	Product ID	Description	S/N serial number	HW hardware status	SW software status
psa260	psa260	FM radio / MP3 player with <i>Bluetooth</i>	TR unit 46	Main PCB version 0.4 Key PCB version 0.2	Firmware version 1.4
Frequency Band [MHz]	Type of Modulation	Number of channels	Antenna	Power Supply	Temperature Range
ISM 2.400 - 2.483,5	FHSS	79	integral	Li Ion-Battery 3.6 V	-10 to +55° C

Max. power radiated: - 4.67dBm

Max. power conducted: -1.61 dBm

FCC ID: BOUPSA260

IC:

Used Charger (rad. Tests):

Philips Model : AY4102/17

100 – 240V ~ / 50 – 60 Hz 300 mA

5V DC 1000 mA

1.3.2 If RF component testing only, description of additional used HW/SW

	Product name	Product ID	Description	S/N serial number	HW hardware status	SW software status
1						
2						
3						
4						

SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 6 of 59

1.3.3 Additional EUT information For IC Canada (appendix 2)

Company Number:	
Model Number:	psa260
Product Name:	MP3Run
Manufacturer:	Philips
Tested to Radio Standards Specification (RSS) No.:	RSS-210
Open Area Test Site Industry Canada Number:	3463
Frequency Range (or fixed frequency) [MHz]:	2400 – 2483.5 MHz
RF: Power [W] (max):	Rad. EIRP: 0.34 mW Conducted : 0.77 mW
Field Strength [dBμV/m in 3m]:	96.3
Occupied Bandwidth (99% BW) [kHz]:	832.3
Type of Modulation:	FSK
Emission Designator (TRC-43):	IM00FXD / 79M0FXD (FHSS)
Transmitter Spurious (worst case) [μV/m in 3m]:	140.8 (noise floor at 12 – 25 GHz)
Receiver Spurious (worst case) [μV/m in 3m]:	143.2 (noise floor at 24.9 GHz)

ATTESTATION: I attest that the testing was performed or supervised by me; that the test measurements were made in accordance with the above-mentioned departmental standard(s), and that the radio equipment identified in this application has been subject to all the applicable test conditions specified in the departmental standards and all of the requirements of the standards have been met.

Signature: |

Michael Berg Testengineer

Note: This form must be completed and provided with the submission.

SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 7 of 59

1.3.4 EUT operating modes

EUT operating mode no.*)	Description of operating modes	Additional information
Op. 0	Normal mode	Normal temperature and power source conditions
Op. 1		low temperature, low power source conditions
Op. 2		low temperature, high power source conditions
Op. 3		high temperature, low power source conditions
Op. 4		high temperature, high power source conditions

*) EUT operating mode no. is used to simplify the testplan

1.3.5 Extreme conditions testing values

Description	Shortcut	Unit	Value
Nominal Temperature / humidity	T _{nom}	°C / %	24,8 / 45
Low Temperature	T _{low}	°C	-10
High Temperature	T _{high}	°C	55
Nominal Power Source	V _{nom}	V	3.7
Low Power Source	V _{low}	V	3.4
High Power Source	V _{high}	V	4.0

Type of powersource: V DC

Deviations from this values are reported in chapter 2

SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 8 of 59

2. Teststandard & summary list of all performed test cases

TC identifier	Description	verdict	date	Remark
RF-Testing	FCC Part 15 §15.247 - CANADA RSS-210	PASS		

Test Specification Clause	Test Case	Pass	Fail	Not applicable	Not performed
None	Antenna Gain	Yes			
§15.247(a1)	Carrier frequency separation	Yes			
§15.247(a1)	Number of hopping channels	Yes			
§15.247(a1 iii)	Time of occupancy (dwell time)	Yes			
§15.247(d)	Power Spectral density (Hybrid system in Inquiry mode/Page scan)	Yes			
§15.247(a1)	Spectrum Bandwidth of a FHSS System / 20dB Bandwith	Yes			
§ 15.247 (b) (1)	Maximum output power (conducted)	Yes			
§ 15.247 (b) (1)	Max. peak output power (radiated)	Yes			
§15.247 (c)	Band-edge compliance of conducted emissions	Yes			
§15.205	Band-edge compliance of radiated emissions	Yes			
§ 15.247 (c) (1)	Spurious Emission - conducted (Transmitter)	Yes			
§ 15.247 (c) (1)	Spurious Emission - radiated (Transmitter)	Yes			
§ 15.109	Spurious Emissions - radiated (Receiver)	Yes			
§ 15.109	Spurious Emissions - radiated <30 MHz	Yes			
§ 15.107/207	Conducted Emissions <30 MHz	Yes			

SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 9 of 59

3. RF measurement testing

3.1 Description of test set-up

3.1.1 Radiated measurements

The radiated measurements are performed in vertical and horizontal plane in the frequency range from 9 kHz to 25 GHz in semi-anechoic chambers. The EUT is positioned on a non-conductive support with a height of 0.80 m above a conductive ground plane that covers the whole chamber. The receiving antennas are conform with specifications ANSI C63.2-1987 clause 15 and ANSI C63.4-1992 clause 4.1.5. These antennas can be moved over the height range between 1.0 m and 4.0 m in order to search for maximum field strength emitted from EUT. The measurement distances between EUT and receiving antennas are indicated in the test setups for the various frequency ranges. For each measurement, the EUT is rotated in all three axes until the maximum field strength is received. The wanted and unwanted emissions are received by spectrum analysers where the detector modes and resolution bandwidths over various frequency ranges are set according to requirement ANSI C63-4-1992 clause 4.2.

Antennas are conform with ANSI C63.2-1996 item 15.

150 kHz - 30 MHz: Quasi Peak measurement, 9kHz Bandwidth, passive loop antenna.

30 MHz - 200 MHz: Quasi Peak measurement, 120KHz Bandwidth, biconical antenna

200MHz - 1GHz: Quasi Peak measurement, 120KHz Bandwidth, log periodic antenna


1GHz: Average, RBW 1MHz, VBW 10 MHz, waveguide horn

All measurements are done in accordance with the Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems DA 00-705 and Appendix A "BLUETOOTH APPROVALS"

The EUT is powered by an external power supply with nominal voltage. The signaling is performed from outside the chamber with a signaling unit (CMU200 or other) by airlink using signaling antenna.

3.1.2 Conducted measurements

The EUT's RF signal is coupled out by the antenna connector which is supplied by the manufacturer. The signal is first 10dB attenuated before it is power divided (~6dB loss per branch). One of the signal path is connected to the communication base Station (CMU200 or other), the other one is connected to the spectrum analyzer. The specific losses for both signal paths are first checked within a calibration. The measurement readings on the signaling unit/spectrum analyzer are corrected by the specific test set-up loss. The attenuator, power divider, signaling unit and the spectrum analyzer are impedance matched on 50 Ohm.



SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 10 of 59

3.2 Referenced documents

none

3.3 Additional comments

Hardware / software changes during testing (only for pretesting)

Setup revision	Description of change	Change referenced to setup revision	Already perf. testcases influenced yes (reaped) / no
1.0	Start setup	-	-

3.4 Antenna gain

The antenna gain of the complete system is calculated by the difference of conducted power of the module and the radiated power in EIRP.

	low channel	mid channel	high channel
Conducted power [dBm]	-1.61	-1.16	-1.35
Radiated power [dBm]	-5.04	-4.67	-4.97
Gain [dB]	-3.43	-3.51	-3.62

SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany




Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 11 of 59

3.5 Carrier frequency separation §15.247(a1)

Plot 1 of 1:



Date: 8.JUL.2004 14:04:22

Result : Channel separation is: ~ 1 MHz

Limits :

Under normal test conditions only	Minimum 25 kHz or 20 dB Bandwidth of the hopping system
-----------------------------------	---

SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany


Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 12 of 59

3.6 Number of hopping channels §15.247(a1)

Plot 1 of 2:



Date: 8.JUL.2004 14:06:40

SRD-Testreport


CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 13 of 59

Plot 2 of 2:



Date: 8. JUL. 2004 14:08:17

Result : The number of hopping channels is: 79

Limits :

Under normal test conditions only	at least 15 non-overlapping channels
-----------------------------------	--------------------------------------

SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 14 of 59

3.7 Time of occupancy (dwell time) §15.247(a1 iii)

For Bluetooth devives:

The dwell time of 0.3797s within a 30 second period in data mode is independent from the packet type (packet length).
The calculation for a 30 second period is a follows:

Dwell time = time slot length * hop rate / number of hopping channels *30s

Example for a DH1 packet (with a maximum length of one time slot)

Dwell time = $625 \mu s * 1600 \text{ 1/s} / 79 * 30s = 0.3797s$ (in a 30s period)

For multi-slot packet the hopping is reduced according to the length of the packet.

Example for a DH5 packet (with a maximum length of five time slots)

Dwell time = $5 * 625 \mu s * 1600 * 1/5 * 1/s / 79 * 30s = 0.3797s$ (in a 30s period)

This is according the Bluetooth Core Specification V 1.0B (+ critical errata) for all Bluetooth devices. Therefore, all Bluetooth devices comply with the FCC dwell timerequirement in the data mode.

This was checked during the Bluetooth Qualification tests.

The Dwell time in hybrid mode is approximately 2.6 mS (in a 12.8s period)

SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany


Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 15 of 59

3.8 Power Spectral density (Hybrid system in Inquiry mode/Page scan) §15.247(d)

Plot 1 of 1:



Date: 8. JUL. 2004 14:35:18

Result: Power density : - 47.45dBm/Hz = - 12.65dBm / 3 KHz
Correction factor from dBm/Hz to dBm/3KHz is +34,8 dB

Limits :

Under normal test conditions only	For digitally modulated systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 KHz band during any time interval of continuous transmission
-----------------------------------	---

SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany


Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 16 of 59

3.9 Spectrum Bandwidth of a FHSS System / 20dB Bandwith §15.247(a1)

Plot 1 of 3



Date: 8.JUL.2004 15:12:44

SRD-Testreport


CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 17 of 59

Plot 2 of 3



Date: 8.JUL.2004 15:10:30

SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 18 of 59

Plot 3 of 3



Date: 8.JUL.2004 15:17:51

Results:

Test conditions		20 dB BANDWIDTH [KHz]		
Frequency [MHz]		2402	2441	2480
T _{nom}	V _{nom}	832.3	832.3	829.7
Measurement uncertainty		±1kHz		

RBW / VBW as provided in the „Measurement Guidelines“ (DA 00-705, March 30, 2000)

RBW: 10 kHz / VBW 100 kHz

Limits :

Under normal test conditions only	< 1000 KHz
-----------------------------------	------------

SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany


Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 19 of 59

3.10 Maximum output power (conducted) § 15.247 (b) (1)

Plot 1 of 3



Date: 8.JUL.2004 14:00:37

SRD-Testreport


CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 20 of 59

Plot 2 of 3



Date: 8.JUL.2004 13:59:36

SRD-Testreport


CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 21 of 59

Plot 3 of 3



Date: 8.JUL.2004 14:01:48

Results:

Test conditions		Max. peak output power [dBm]		
Frequency [MHz]		2402	2442	2480
T _{nom}	V _{nom}	PK	-1.16 / 0.77 mW	-1.35 / 0.73 mW
Measurement uncertainty		±3dB		

RBW / VBW : 3 MHz

Limits:

Under normal test conditions only, for frequency range 2400-2483.5 MHz	Max. 1.0 Watt
--	---------------

SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 22 of 59

3.11 Max. peak output power (radiated) § 15.247 (b) (1)

Results:

Test conditions		Max. peak output power EIRP [dBm]		
Frequency [MHz]		2402	2442	2480
T _{nom}	V _{nom}	-5.04 / 0.31 mW	-4.67 / 0.34 mW	-4.97 / 0.32 mW
Measurement uncertainty		±3dB		

RBW / VBW : 3 MHz

Measured at a distance of 3m

Limits:

Under normal test conditions only, for frequency range 2400-2483.5 MHz	Max. 1.0 Watt
---	---------------

SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 23 of 59

3.12 Band-edge compliance of conducted emissions §15.247 (c)

Plot 1 of 4 (hopping off, lowest frequency):



Date: 8.JUL.2004 14:13:38

SRD-Testreport


CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 24 of 59

Plot 2 of 4 (hopping on, lowest frequency):



Date: 8.JUL.2004 14:12:13

SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 25 of 59

Plot 3 of 4 (hopping off, highest frequency):



Date: 8. JUL. 2004 14:14:41

SRD-Testreport


CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 26 of 59

Plot 4 of 4 (hopping on, highest frequency):



Date: 8.JUL.2004 14:17:45

Results:


SZENARIO	DELTA VALUE [DB]
hopping off, lowest frequency	48.12
hopping on, lowest frequency	48.64
hopping off, highest frequency	43.77
hopping on, highest frequency	45.49
Measurement uncertainty	±1,5dB

Limits:

Under normal test conditions only	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 5.205(c)).
-----------------------------------	--

3.13 Band-edge compliance of radiated emissions §15.205


Plot 1 : Max field strength in 3m distance (single frequency)



Result: SA Reading + Antenna factor – Amp. Gain + Cable loss = Fieldstrength
 Antenna factor – Amp. Gain + Cable loss = -4.45 dB

92.4 dBuV/m –4.45 dB = 87.95 dBuV/Mm in 3m distance

Plot 2: Marker-Delta Method (single carrier)




Result:

Marker-Delta-Value : 43.1 dB

This measurement was made to show that the behavior of the system is conform to FCC 15.205 (restricted bands)

Plot 3: Marker-Delta Method (hopping)



Result:

Marker-Delta-Value : 43.80 dB

This measurement was made to show that the behavior of the system is conform to FCC 15.205 (restricted bands)

SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany




Test report No.: 2-3649-01-03/04


Date:2004-07-15

Page 30 of 59

Plot 4: Restricted Bands low



Plot 5: Restricted Bands high



SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 31 of 59

Results & Limits:

Radiated field strength

The field strength was measured with an EMI measuring receiver and 1 MHz RBW / VBW for peak and with 1MHz RBW / 10Hz VBW for average at a distance of 3m.

high channel	setup	measured value (3m)	correction factor (3m)	calculated value (3m)
Max. peak value	1 MHz RBW 1 MHz VBW	92.40 dB μ V/m	-4.45 dB	87.95 dB μ V/m
Max. average value	Calculated with duty cycle correction factor	87.95 dB μ V/m peak	-1,07dB duty cycle correction factor (worst case DH5)	86.88 dB μ V/m
Delta value	Peak 30 kHz RBW/VBW	43.10 dB (single carrier) 43.80 dB (hopping mode)	-	-
Value at band edge	limit 54 dB μ V/m			43.78 dB μ V/m (single carrier) 43.08 dB μ V/m (hopping mode)
Statement:				Complies

SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany


Test report No.: 2-3649-01-03/04

Date: 2004-07-15

Page 32 of 59


3.14 Spurious Emissions - conducted (Transmitter) § 15.247 (c) (1)

Plot 1 of 3: highest channel



Date: 8.JUL.2004 14:27:05

Plot 2 of 3: middle channel



Date: 8.JUL.2004 14:29:44

SRD-Testreport


CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 33 of 59

Plot 3 of 3: lowest channel



Date: 8.JUL.2004 15:28:03

Result & Limits:

Emission Limitations					
f [MHz]		amplitude of emission [dBm]	limit max. allowed emission power	actual attenuation below frequency of operation [dB]	results
2402	-	-1.61	30 dBm	-	Operating frequency
1202.4		-48.60	-20 dBc	46.99	complies
2441	-	-1.16	30 dBm	-	Operating frequency
1202.4		-47.97	-20 dBc	46.81	complies
2480	-	-1.35	30 dBm		Operating frequency
1252.5		-48.55	-20 dBc	47.20	complies
Measurement uncertainty		± 3dB			

RBW : 100 kHz VBW: 100 MHz

Under normal test conditions only	In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
-----------------------------------	--

Note: For emissions that fall into restricted bands you find the radiated emissions later in the report.

SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany


Test report No.: 2-3649-01-03/04

Date:2004-07-15


Page 34 of 59

3.15 Spurious Emissions - radiated (Transmitter) § 15.247 (c) (1)

Plot : 0.03 - 4 GHz vertical/horizontal (lowest channel)



Plot : 4- 12 GHz vertical/horizontal (lowest channel)



SRD-Testreport


CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 35 of 59

Plot : 12- 25 GHz vertical/horizontal (lowest channel)



Date: 8.JUL.2004 11:56:40

SRD-Testreport


CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04


Date:2004-07-15

Page 36 of 59

Plot : 0.03 - 4 GHz vertical/horizontal (middle channel)



Plot : 4- 12 GHz vertical/horizontal (middle channel)



SRD-Testreport


CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 37 of 59

Plot : 12- 25 GHz vertical/horizontal (middle channel)



Date: 8.JUL.2004 11:56:40

SRD-Testreport


CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04


Date:2004-07-15

Page 38 of 59

Plot : 0.03 - 4 GHz vertical/horizontal (highest channel)



Plot : 4- 12 GHz vertical/horizontal (highest channel)



SRD-Testreport


CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 39 of 59

Plot : 12- 25 GHz vertical/horizontal (highest channel)



Date: 8.JUL.2004 11:55:37

Results:

SPURIOUS EMISSIONS LEVEL ($\mu\text{V/m}$)								
2402 MHz			2441 MHz			2480 MHz		
F [MHz]	Detector	Level [$\mu\text{V/m}$]	F [MHz]	Detector	Level [$\mu\text{V/m}$]	F [MHz]	Detector	Level [$\mu\text{V/m}$]
4804	PK	20.7	4882	PK	25.7	4960	PK	28.8
Measurement uncertainty			$\pm 3 \text{ dB}$					

 $f < 1 \text{ GHz} : \text{RBW/VBW: } 100 \text{ kHz}$

f ≥ 1GHz : RBW/VBW: 1 MHz

Limits: § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Limits: § 15.209

Frequency [MHz]	Field strength [$\mu\text{V/m}$]	Measurement distance (m)
30 - 88	100 (40 dB $\mu\text{V/m}$)	3
88 - 216	150 (43.5 dB $\mu\text{V/m}$)	3
216 - 960	200 (46 dB $\mu\text{V/m}$)	3
above 960	500 (54 dB $\mu\text{V/m}$)	3

SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany


Test report No.: 2-3649-01-03/04

Date:2004-07-15


Page 41 of 59

3.16 Spurious Emissions - radiated (Receiver) § 15.109

Plot : 0.03 - 4 GHz vertical/horizontal (receiver)



Plot : 4- 12 GHz vertical/horizontal (receiver)



SRD-Testreport


CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 42 of 59

Plot : 12- 25 GHz vertical/horizontal (receiver)



Date: 8.JUL.2004 11:58:54

Spurious Emissions level [μV/m]								
CH 1 / 2 / 3								
f[MHz]	Detector	Level [μV/m]	f[MHz]	Detector	Level [μV/m]	f[MHz]	Detector	Level [μV/m]
No traceable peak detected								
Measurement uncertainty			±3 dB					

f < 1 GHz : RBW/VBW: 100 kHz

f ≥ 1GHz : RBW/VBW: 1 MHz

see above plots

Measurement distance see table

Limits : § 15.109

Frequency (MHz)	Field strength (μV/m)	Measurement distance (m)
30 - 88	100 (40 dBμV/m)	3
88 - 216	150 (43.5 dBμV/m)	3
216 - 960	200 (46 dBμV/m)	3
above 960	500 (54 dBμV/m)	3

SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15


Page 43 of 59

3.17 Spurious Emissions - radiated <30 MHz § 15.109

Measured at 10 m distance.

Values recalculated with 40 dB/decade according to FCC rules.

Plot 1:



Limits:

Frequency (MHz)	Field strength (µV/m)	Measurement distance (m)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30 / 29.5 dBµV/m	30
30 - 88	100 / 40 dBµV/m	3
88 - 216	150 / 43.5 dBµV/m	3
216 - 960	200 / 46 dBµV/m	3
above 960	500 / 54 dBµV/m	3

SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15


Page 44 of 59

3.18 Conducted Emissions <30 MHz § 15.107/207

Plot 1:

FCC 15.107/207

EUT: PSA260
 Manufacturer: Philips Nike
 Operating Condition: Rx mode
 Test Site: Room 006 (Shielded chamber)
 Operator: Berg M.
 Test Specification: CISPR 22 (EN 55022)
 Comment: 115V / 60 Hz
 Start of Test: 09.07.04 / 07:19:27



SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04


Date:2004-07-15

Page 45 of 59

Plot 2:

FCC 15.107/207

EUT: PSA260
 Manufacturer: Philips-Nike
 Operating Condition: Tx mode
 Test Site: Room 006 (Shielded chamber)
 Operator: Berg M.
 Test Specification: CISPR 22 (EN 55022)
 Comment: 115V / 60 Hz
 Start of Test: 09.07.04 / 07:10:16



MEASUREMENT RESULT: "55022 V AC_fin QP"

09.07.04 07:12

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Line	PE
0.255000	49.60	11.0	62	12.0	N	FLO

Limits :

Under normal test conditions only	See plots
-----------------------------------	-----------

SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 46 of 59

3.19 Used Testequipment

Anachoic chamber C:

Device	Manufacturer	Type	S/N Number	Inv. No. Cetecom
Spektrum Analyser	HP	8566B	2747A05306	300001000
Spektrum Analyser Display	HP	85662A	2816A16541	300002297
Quasi-Peak-Adapter	HP	85650A	2811A01131	300000999
Power Supply	HP	6032A	2818A03450	300001040
Power Attenuator	Byrd	8325	1530	300001595
Bikonical Antenna	EMCO	3104	3758	300001602
Log. Period. Antenna	EMCO	3146	2130	300001603
Double Ridged Antenna	EMCO	HP 3115P	3088	300001032
Active Loop Antenna	EMCO	6502	2210	300001015
Antenna VDE/FCC		HP11965B		300002298
SRM-Drive	HP	9144A	2823e46556	300001044
Software	HP	EMI		300000983
Busisolator	Kontron			300001056
Absorberhalle	MWB		87400/02	300000996
Salzsäule	Kontron			300001055
Antenna	R&S	HMO20	832211/003	300002243
Indukt. Tast Antenna	R&S	HFH 2 Z4	881468/026	300001464
System-Rack	HP I.V.	85900	*	300000222
Spectrum Analyzer	HP	8566B	2747A05275	300000219
Quasi-Peak-Adapter	HP	85650A	2811A01135	300000216
RF-Preselector	HP	85685A	2837A00779	300000218
Rahmen Antenne	R&S	HFH2-Z2	891847-35	300001169
Leitungsteiler	HP	11850C		300000997
Breitband-Hornantenne EMI	HP	35155P		300002300
PC	HP	Vectra VL		300001688
VHF Meßantenne	Schwarzbeck	VHA 9103		300001778
Spectrum Analyzer Display	HP	85662A	2816A16497	300001690
VHF Meßantenna	Schwarzbeck	VHA 9103		300001780
Biconical Antenna	EMCO	3104 C	9909-4868	300002590

SRD Laboratory: (Bluetooth System)

No	Equipment/Type	Manufact.	Serial Nr.	Inv. No. Cetecom
1	System Controller PSM 12	R&S	835259/007	3000002681
2	Memory Extension PSM-K10	R&S	To 1	3000002681
3	Operating Software PSM-B2	R&S	To 1	3000002681
4	19'' Monitor		22759020-ED	3000002681
5	Mouse		LZE 0095/6639	3000002681
6	Keyboard		G00013834L461	3000002681
7	Spectrum Analyser FSIQ 26	R&S	835540/018	3000002681
8	Tracking Generator FSIQ-B10	R&S	835107/015	3000002681
10	RF-Generator SMIQ03 (B1 Signal)	R&S	835541/056	3000002681
11	Modulation Coder SMIQ-B20	R&S	To 10	3000002681
12	Data Generator SMIQ-B11	R&S	To 10	3000002681
13	RF Rear Connection SMIQ-B19	R&S	To 10	3000002681
14	Fast CPU SM-B50	R&S	To 10	3000002681
15	FM Modulator SM-B5	R&S	835676/033	3000002681

SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 47 of 59

16	RF-Generator SMIQ03 (B2 Signal)	R&S	835541/055	3000002681
17	Modulation Coder SMIQ-B20	R&S	To 16	3000002681
18	Data Generator SMIQ-B11	R&S	To 16	3000002681
19	RF Rear Connection SMIQ-B19	R&S	To 16	3000002681
20	Fast CPU SM-B50	R&S	To 16	3000002681
21	FM Modulator SM-B5	R&S	836061/022	3000002681
22	RF-Generator SMP03 (B3 Signal)	R&S	835133/011	3000002681
23	Attenuator SMP-B15	R&S	835136/014	3000002681
24	RF Rear Connection SMP-B19	R&S	834745/007	3000002681
25	Power Meter NRVD	R&S	835430/044	3000002681
26	Power Sensor NRVD-Z1	R&S	833894/012	3000002681
27	Power Sensor NRVD-Z1	R&S	833894/011	3000002681
28	Rubidium Standard RUB	R&S	6197	3000002681
29	Switching and Signal Conditioning Unit SSCU	R&S	338864/003	3000002681
30	Laser Printer HP Deskjet 2100	HP	N/A	3000002681
31	19'' Rack	R&S	11138363000004	3000002681
32	RF-cable set	R&S	N/A	3000002681
33	IEEE-cables	R&S	N/A	3000002681
34	Sampling System FSIQ-B70	R&S	835355/009	3000002681
35	RSP programmable attenuator	R&S	834500/010	3000002681
36	Signalling Unit	R&S	838312/011	3000002681
37	NGPE programmable Power Supply for EUT	R&S	192.033.41	3000002681

SRD Laboratory:

Device	Manufacturer	Type	S/N Number	Inv. No. Cetecom
Climatic box	Heraeus Vötsch	VT 4002	--	300003019
Signaling Unit	R&S	CMU200	832221/0055	300002862
Power Splitter	Inmet Corp.	6005-3	none	300002841
SMA Cables	Insulated Wire	SPS-1151-985-SPS	different	different

4 Photographs

Radiated test site



SRD-Testreport


CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04


Date:2004-07-15

Page 49 of 59

Radiated test site



Radiated test site



SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 51 of 59

AC conducted test



SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 52 of 59

Photographs of the testsamples: (rad./cond.)



SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 53 of 59



SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 54 of 59



SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 55 of 59



SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 56 of 59



the yellow cables are only for testing


SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date: 2004-07-15

Page 57 of 59



SRD-Testreport

CETECOM ICT Services GmbH Saarbruecken, Germany

Test report No.: 2-3649-01-03/04

Date:2004-07-15

Page 58 of 59



