
FCC Test Report

Report No.: AGC00119141002FE08

FCC ID : BRCPC1011

APPLICATION PURPOSE : Original Equipment

PRODUCT DESIGNATION : tablet pc

BRAND NAME : Kinwei, Titan

TEST MODEL : Refer to page 4.

CLIENT : Kintech Co., Ltd.

DATE OF ISSUE : Nov.18,2014

STANDARD(S) : FCC Part 15 Rules

REPORT VERSION : V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd



CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.

REPORT REVISE RECORD

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Nov.18,2014	Valid	Original Report

TABLE OF CONTENTS

1. VERIFICATION OF COMPLIANCE	4
2. PRODUCT INFORMATION.....	5
3. TEST FACILITY	6
4. SUPPORT EQUIPMENT LIST	7
5. SYSTEM DESCRIPTION.....	7
6 SUMMARY OF TEST RESULTS	8
7. FCC LINE CONDUCTED EMISSION TEST	9
7.1. TEST EQUIPMENT OF LINE CONDUCTED EMISSION TEST.....	9
7.2 .LIMITS OF LINE CONDUCTED EMISSION TEST	9
7.3. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST	9
7.4. PROCEDURE OF LINE CONDUCTED EMISSION TEST	10
7.5 TEST RESULT OF LINE CONDUCTED EMISSION TEST	11
8. FCC RADIATED EMISSION TEST	13
8.1. TEST EQUIPMENT OF RADIATED EMISSION	13
8.2. LIMITS OF RADIATED EMISSION TEST	13
8.3 BLOCK DIAGRAM OF RADIATED EMISSION TEST	13
8.4 PROCEDURE OF RADIATED EMISSION TEST	13
8.4 PROCEDURE OF RADIATED EMISSION TEST	14
8.5 TEST RESULT OF RADIATED EMISSION TEST	15
APPENDIX 1	19
PHOTOGRAPHS OF TEST SETUP.....	19
APPENDIX 2	20
PHOTOGRAPHS OF EUT	20

1. VERIFICATION OF COMPLIANCE

Applicant	Kintech Co., Ltd.
Address	1F-5F, Bldg 22, Chen Tian Industrial Zone, Xi Xiang Bao An District, Shenzhen, Guang Dong, China
Manufacturer	Kintech Co., Ltd.
Address	1F-5F, Bldg 22, Chen Tian Industrial Zone, Xi Xiang Bao An District, Shenzhen, Guang Dong, China
Product Designation	tablet pc
Brand name:	Kinwei, Titan
Test Model	PC1011
Series Model	PC1011B, PC1011ME, PC10XX(XX represents 00~99), PC10XXB(XX represents 00~99), PC10XXME(XX represents 00~99), KW-PC1011T, KW-PC1011, KW-PC10XXT(XX represents 00~99), KW-PC10XX(XX represents 00~99)
Difference description	All the same except for the model name.
Date of test:	Nov.13, 2014 to Nov.17, 2014
Deviation:	None
Condition of Test Sample	Normal

The above equipment was tested by Attestation Of Global Compliance Co., Ltd. for compliance with the requirements set forth in the FCC Rules and Regulations Part 15, the measurement procedure according to ANSI C63.4:2003. This said equipment in the configuration described in this report shows the maximum emission levels emanating from equipment are within the compliance requirements.

The test results of this report relate only to the tested sample identified in this report.

Prepared By

Max Zhang

Max Zhang Nov.18,2014

Checked By

Kidd Yang

Kidd Yang Nov.18,2014

Authorized By

Solger Zhang

Solger Zhang Nov.18,2014

2. PRODUCT INFORMATION

Housing Type: Plastic

EUT Rating Voltage: DC 3.7V by battery or USB Operated

I/O Port Information (Applicable Not Applicable)

I/O Port of EUT			
I/O Port Type	Q'TY	Cable	Tested with
USB	1	N/A	1
DC In	1	N/A	1
Headset Port	1	N/A	1

3. TEST FACILITY

Facility	Attestation of Global Compliance (Shenzhen) Co., Ltd
Location:	B112-B113, Building 12, Baoan Building Materials Center, No.1 of Xixiang Inner Ring Road, Baoan District, Shenzhen, Guangdong, P.R.China
Description:	The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2003.
Site Filing:	The FCC Registration Number is 259865
Instrument Tolerance:	All measuring equipment is in accord with ANSI C63.4 requirements that meet industry regulatory agency and accreditation agency requirement.

4. SUPPORT EQUIPMENT LIST

Device Type	Manufacturer	Model Name	Serial No.	Data Cable	Power Cable
PC	Dell	INSPIRON	N/A	N/A	1.5m unshielded

**Note: All the above equipment/cables were placed in worse case positions to maximize emission signals during emission test.

5. SYSTEM DESCRIPTION

EUT test procedure:

1. Connect EUT and peripheral devices.
2. Power on the EUT, the EUT begins to work.
3. Running data transmission and make sure the EUT normal working.

Test Mode

1. USB (Data transmitting)

NOTE: Other modes have reflected in VOC program.

6 SUMMARY OF TEST RESULTS

FCC Rules	Description Of Test	Result
§15.107	Conduction Emission	Compliant
§15.109	Radiated Emission	Compliant

7. FCC LINE CONDUCTED EMISSION TEST

7.1. TEST EQUIPMENT OF LINE CONDUCTED EMISSION TEST

Description	Manufacturer	Model	Cal. Date	Cal. Due
EMI Test Receiver	Rohde & Schwarz	ESHS 30	07/30/2014	07/29/2015
LISN	Rohde & Schwarz	ESH2-Z5	09/05/2014	09/04/2015


7.2 .LIMITS OF LINE CONDUCTED EMISSION TEST

Frequency	Maximum RF Line Voltage	
	Q.P.(dBuV)	Average(dBuV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

**Note: 1. The lower limit shall apply at the transition frequency.

2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz

7.3. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



7.4. PROCEDURE OF LINE CONDUCTED EMISSION TEST


- 1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2) Support equipment, if needed, was placed as per ANSI C63.4.
- 3) All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4) The EUT received DC 5V power by PC. All support equipments received AC 120V/60Hz power from socket under the turntable, if any.
- 5) The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 6) Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 7) During the above scans, the emissions were maximized by cable manipulation.
- 8) A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions.
- 9) Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.

The test data of the worst case condition (mode 1) was reported on the following Data page.

7.5 TEST RESULT OF LINE CONDUCTED EMISSION TEST

LINE CONDUCTED EMISSION - L

SCAN TABLE: "Voltage (150K-30M) FIN"
Short Description: 9k-30M Voltage



MEASUREMENT RESULT:


Frequency	Level	Transd	Limit	Margin	Detector	Line	PE	AUX STATE
MHz	dBuV	dB	dBuV	dB				
0.150000	4.60	0.2	66	61.4	QP	L1	FLO	ON
0.202000	4.80	0.2	64	58.7	QP	L1	FLO	ON
0.850000	37.30	0.2	56	18.7	QP	L1	FLO	ON
1.414000	-1.00	0.2	56	57.0	QP	L1	FLO	ON
2.118000	39.00	0.3	56	17.0	QP	L1	FLO	ON
3.798000	36.30	0.3	56	19.7	QP	L1	FLO	ON

MEASUREMENT RESULT:

Frequency	Level	Transd	Limit	Margin	Detector	Line	PE	AUX STATE
MHz	dBuV	dB	dBuV	dB				
0.150000	-13.00	0.2	56	69.0	AV	L1	FLO	ON
0.202000	-13.20	0.2	54	66.7	AV	L1	FLO	ON
0.250000	18.20	0.2	52	33.6	AV	L1	FLO	ON
0.550000	27.00	0.2	46	19.0	AV	L1	FLO	ON
0.610000	26.40	0.2	46	19.6	AV	L1	FLO	ON
0.762000	-12.50	0.2	46	58.5	AV	L1	FLO	ON

LINE CONDUCTED EMISSION - N

SCAN TABLE: "Voltage (150K-30M) FIN"
Short Description: 9k-30M Voltage



MEASUREMENT RESULT:

Frequency	Level	Transd	Limit	Margin	Detector	Line	PE	AUX STATE
MHz	dBuV	dB	dBuV	dB				
0.182000	45.90	0.2	64	18.5	QP	N	FLO	ON
0.242000	45.00	0.2	62	17.0	QP	N	FLO	ON
0.842000	45.20	0.2	56	10.8	QP	N	FLO	ON
0.846000	44.80	0.2	56	11.2	QP	N	FLO	ON
0.906000	44.30	0.2	56	11.7	QP	N	FLO	ON
2.586000	37.90	0.3	56	18.1	QP	N	FLO	ON

MEASUREMENT RESULT:

Frequency	Level	Transd	Limit	Margin	Detector	Line	PE	AUX STATE
MHz	dBuV	dB	dBuV	dB				
0.182000	44.40	0.2	54	10.0	AV	N	FLO	ON
0.302000	38.70	0.2	50	11.5	AV	N	FLO	ON
0.482000	37.70	0.2	46	8.6	AV	N	FLO	ON
0.542000	39.50	0.2	46	6.5	AV	N	FLO	ON
0.662000	38.60	0.2	46	7.4	AV	N	FLO	ON
0.726000	32.10	0.2	46	13.9	AV	N	FLO	ON
0.846000	32.10	0.2	46	13.9	AV	N	FLO	ON
0.906000	35.90	0.2	46	10.1	AV	N	FLO	ON

8. FCC RADIATED EMISSION TEST

8.1. TEST EQUIPMENT OF RADIATED EMISSION


Description	Manufacturer	Model	Cal. Date	Cal. Due
PSA SERIES SPECTRUM ANALYZER	AGILENT	E4440A	02/17/2014	02/16/2015
Double-Ridged Waveguide Horn	ETS LINDGREN	3117	08/17/2014	08/16/2015
WIDEBAND FREQUENCY ANTENNA	SCHWARZBECK	VULB9168	07/21/2014	07/20/2015
Broadband Preamplifier	SCHWARZBECK	BBV 9718	07/26/2014	07/26/2015
Multi-Device Controller	EMCO	2090	07/30/2014	07/30/2015

8.2. LIMITS OF RADIATED EMISSION TEST

Frequency (MHz)	Distance (m)	Maximum Field Strength Limit (dBuV/m/ Q.P.)
30~88	3	40.0
88~216	3	43.5
216~960	3	46.0
Above 960	3	54.0

**Note: The lower limit shall apply at the transition frequency.

8.3 BLOCK DIAGRAM OF RADIATED EMISSION TEST




8.4 PROCEDURE OF RADIATED EMISSION TEST

- 1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2) Support equipment, if needed, was placed as per ANSI C63.4.
- 3) All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
- 4) The EUT received DC 5V by PC. All support equipments received AC 120V/60Hz power from socket under the turntable, if any.
- 5) The antenna was placed at 3 meter away from the EUT as stated in FCC Part 15. The antenna connected to the Analyzer via a cable and at times a pre-amplifier would be used.
- 6) The Analyzer / Receiver quickly scanned from 30MHz to 1000MHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- 7) The test mode(s) were scanned during the test:
- 8) Recorded at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit and Q.P./Peak reading is presented.

The test data of the worst case condition(mode 1) was reported on the following Data page


8.5 TEST RESULT OF RADIATED EMISSION TEST

Radiated Emission Test –Horizontal -3m




Frequency MHz	Polarization	Reading dB(uV)	Factor dB (1/m)	Level dB(uV/m) PK	Limit dB(uV/m) QP	Margin dB	Pass/Fail	Height cm	Angle deg
283.655	H	27.8	15.2	43.0	46.0	3.0	Pass	100.0	356.9
600.360	H	14.0	23.0	37.0	46.0	9.0	Pass	100.0	356.9
471.835	H	14.2	20.1	34.3	46.0	11.7	Pass	100.0	223.3
135.245	H	15.1	14.6	29.7	43.5	13.8	Pass	100.0	356.9
32.425	H	15.1	15.1	30.2	40.0	9.8	Pass	100.0	75.9
557.195	H	11.8	21.8	33.6	46.0	12.4	Pass	100.0	356.9

Radiated Emission Test –Vertical -3m




Frequency MHz	Polarization	Reading dB(uV)	Factor dB (1/m)	Level dB(uV/m) PK	Limit dB(uV/m) QP	Margin dB	Pass/Fail	Height cm	Angle deg
32.425	V	16.5	15.1	31.6	40.0	8.4	Pass	100.0	203.4
171.135	V	16.0	14.7	30.7	43.5	12.8	Pass	100.0	357.1
283.655	V	17.2	15.2	32.4	46.0	13.6	Pass	100.0	46.9
600.360	V	11.6	23.0	34.6	46.0	11.4	Pass	100.0	334.9
814.730	V	10.2	25.6	35.8	46.0	10.2	Pass	100.0	127.2
557.195	V	11.7	21.8	33.5	46.0	12.5	Pass	100.0	348.3

RADIATED EMISSION ABOVE 1GHZ – HORIZONTAL



Frequency MHz	Polarization	Reading dB(uV)	Factor dB (1/m)	Level dB(uV/m) PK	Limit dB(uV/m) PK	Margin dB PK	Pass/Fail	Height cm	Angle deg
1187.500	H	43.3	-6.3	37.0	74.0	37.0	Pass	200.0	39.0
2000.000	H	36.5	-2.7	33.8	74.0	40.2	Pass	100.0	199.2
3762.500	H	37.2	5.7	42.9	74.0	31.1	Pass	200.0	217.6

RADIATED EMISSION ABOVE 1GHZ - VERTICAL




Frequency MHz	Polarization	Reading dB(uV)	Factor dB (1/m)	Level dB(uV/m) PK	Limit dB(uV/m) PK	Margin dB PK	Pass/Fail	Height cm	Angle deg
1187.500	V	48.7	-6.3	42.4	74.0	31.6	Pass	100.0	215.0
3337.500	V	36.4	3.8	40.2	74.0	33.8	Pass	200.0	236.8
4725.000	V	35.5	8.1	43.6	74.0	30.4	Pass	100.0	287.2

APPENDIX 1
PHOTOGRAPHS OF TEST SETUP

FCC LINE CONDUCTED EMISSION TEST SETUP



FCC RADIATED EMISSION TEST SETUP



APPENDIX 2
PHOTOGRAPHS OF EUT

TOTAL VIEW OF EUT



TOP VIEW OF EUT



BOTTOM VIEW OF EUT




FRONT VIEW OF EUT




BACK VIEW OF EUT



LEFT VIEW OF EUT



RIGHT VIEW OF EUT




OPEN VIEW OF EUT-1




OPEN VIEW OF EUT-2




INTERNAL VIEW OF EUT-1




INTERNAL VIEW OF EUT-2



INTERNAL VIEW OF EUT-3



INTERNAL VIEW OF EUT-4



----END OF REPORT----