



Engineering and Testing for EMC and Safety Compliance



Accredited under A2LA Testing Certificate # 2653.01

Class II Permissive Change Report

Model: CS-803 Control Station

M/A-COM, Inc.
221 Jefferson Ridge Parkway
Lynchburg, VA 24501
Daryl Popowitch
Phone: (434) 455-9527

FCC ID: BV8CS803

October 31, 2008

Standards Referenced for this Report	
Part 2: 2007	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
Part 90: 2007	Private Land Mobile Radio Services
ANSI TIA-603-C-2004	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards
ANSI/TIA/EIA – 102.CAAA; 2002	Digital C4FM/CQPSK Transceiver Measurement Methods

Report Prepared by Test Engineer: Daniel Baltzell

Document Number: 2008184

This report may not be reproduced, except in full, without the written approval of Rhein Tech Laboratories, Inc. and M/A-COM, Inc. Test results relate only to the product tested.

Frequency Range (MHz)	Power (W) Conducted*	Rated Frequency Tolerance (ppm)	Emission Designator
806-824	17.4*	1.5	16K5F7D
806-824	17.4*	1.5	16K5F7E
809-824	17.4	1.5	16K0F1D
854-869	11.0	1.5	16K0F1D
806-809	17.4*	1.5	14K0F1D
851-854	11.0	1.5	14K0F1D
809-824	17.4*	1.5	16K0F1E
854-869	11.0	1.5	16K0F1E
806-809	17.4*	1.5	14K0F1E
851-854	11.0	1.5	14K0F1E
809-824	17.4*	1.5	16K0F3E
854-869	11.0	1.5	16K0F3E
806-809	17.4*	1.5	14K0F3E
851-854	11.0	1.5	14K0F3E
806-824	17.4*	1.5	8K40F1D
851-869	11.0	1.5	8K40F1D
806-824	17.4*	1.5	8K40F1E
851-869	11.0	1.5	8K40F1E
806-824	11.0	1.5	12K8F9W

* granted power on original filing

Table of Contents

1	General Information	5
1.1	Test Facility.....	5
1.2	Related Submittal(s)/Grant(s)	5
2	Tested System Details	6
3	FCC Rules and Regulations Part 2 §2.1046(a): RF Power Output: Conducted; Part 90 §90.541(c): Transmitting Power Limits.....	8
3.1	Test Procedure	8
3.2	Test Data	8
4	FCC Rules and Regulations Part 2 §2.1051: Spurious Emissions at Antenna Terminals; Part 90 §90.543(b): Out of Band Emissions Limit	9
4.1	Test Procedure	9
4.2	Test Data	9
5	FCC Rules and Regulations Part 2 §2.1053(a): Field Strength of Spurious Radiation; Part 90 §90.543(b): Out of Band Emissions Limit.....	11
5.1	Test Procedure	11
5.2	Test Data	11
6	FCC Rules and Regulations Part 2 §2.1049(c)(1): Occupied Bandwidth; Part 90 §90.543(d): Authorized Bandwidth	12
6.1	Test Procedure	12
6.2	Test Data	12
7	FCC Rules and Regulations Part 2 §2.202: Added Necessary Bandwidth and Emission Bandwidth	13
8	Conclusion	13

Table of Figures

Figure 2-1: Configuration of Tested System	7
--	---

Table of Tables

Table 2-1: Equipment Under Test (EUT).....	6
Table 3-1: RF Power Output: Carrier Output Power.....	8
Table 3-2: RF Power Output (Rated Power)	8
Table 3-3: Test Equipment Used For Testing RF Power Output - Conducted.....	8
Table 4-1: Test Equipment Used For Testing Conducted Spurious Emissions	10
Table 5-1: Test Equipment Used For Testing Field Strength of Spurious Radiation	11
Table 6-1: Test Equipment Used For Testing Occupied Bandwidth	13

Table of Plots

Plot 6-1: Occupied Bandwidth; 820.9875 MHz; OTP WB; High Power; Mask G	12
--	----

Table of Appendixes

Appendix A: Change Description.....	14
Appendix B: Agency Authorization Letter	15
Appendix C: Test Configuration Photographs.....	16

Table of Photographs

Photograph 1: Radiated Emissions – Front View.....	16
Photograph 2: Radiated Emissions – Back View	17

1 General Information

The following Class II Permissive Change report is prepared on behalf of **M/A-COM, Inc.** in accordance with the Federal Communications Commission Rules and Regulations. The Equipment Under Test (EUT) was the **CS-803 Control Station; FCC ID: BV8CS803**. The test results reported in this document relate only to the item that was tested.

All measurements contained in this application were conducted in accordance with the applicable FCC Rules and Regulations. Calibration checks are performed regularly on the instruments, and all accessories including high pass filter, coaxial attenuator, preamplifier and cables.

1.1 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located on the parking lot of Rhein Tech Laboratories, Inc. 360 Herndon Parkway, Suite 1400, Herndon, Virginia 20170. This site has been fully described in a report submitted to and approved by the Federal Communications Commission to perform AC line conducted and radiated emissions testing.

1.2 Related Submittal(s)/Grant(s)

The purpose of this Class II Permissive Change is to document and demonstrate continued compliance of the CS-803 Control Station following the addition of emission designator 12K8F9W. No hardware has been changed nor added. Radio deviation has been enhanced in firmware on an existing mode of operation for the new emission designator.

The original FCC grant was issued May 27, 2003; a permissive change grant was issued January 18, 2007.

2 Tested System Details

The test sample was received on October 17, 2008. Listed below are the identifiers and descriptions of all equipment, cables, and internal devices used with the EUT for this test, as applicable. The device was programmed for multiple modes of operation and modulation types.

Table 2-1: Equipment Under Test (EUT)

Part	Manufacturer	Model	Serial Number	FCC ID	Cable	RTL Bar Code
Radio	M/A-COM, Inc.	CS-803 Control Station	A40058000B01	BV8CS803	9m unshielded I/O (CAN)	18667
Microphone	M/A-COM, Inc	1000005928-0001	N/A	N/A	0.7m coiled unshielded I/O	18647
Speaker	M/A-COM, Inc	LS102824V10R1A	N/A	N/A	1.4m unshielded I/O	18658
Power Supply	Samlex America, Inc.	SEC-1212	03051-7F03-00875	N/A	1.7m unshielded	18665




Figure 2-1: Configuration of Tested System

3 FCC Rules and Regulations Part 2 §2.1046(a): RF Power Output: Conducted; Part 90 §90.541(c): Transmitting Power Limits

3.1 Test Procedure

ANSI/TIA/EIA-603-2002, section 2.2.1

The EUT was connected to a coaxial attenuator having a 50 ohm load impedance.

3.2 Test Data

Table 3-1: RF Power Output: Carrier Output Power

Frequency (MHz)	High Power (dBm)	High Power (W)
806.0125	40.23	10.54
813.4875	40.05	10.12
816.3625	40.19	10.45
820.9875	40.33	10.79
821.0125	40.33	10.79
822.5125	40.20	10.47
823.9875	40.05	10.12

* Measurement accuracy: +/- .02 dB (logarithmic mode)


Table 3-2: RF Power Output (Rated Power)

Rated Power High Power (W)
17.4/11.0

Table 3-3: Test Equipment Used For Testing RF Power Output - Conducted

RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Date
901356	Agilent Technologies	E9323A	Power Sensor	31764-264	10/24/08
901184	Agilent Technologies	E4416A	EPM-P Power Meter, single channel	GB41050573	10/24/08
901396	MCE Weinschel	48-40-34	Attenuator, 40 dB, DC-18 GHz, 100 W	93453	1/13/09

Test Personnel:

Daniel Baltzell		October 24, 2008
Test Engineer	Signature	Date Of Test


4 FCC Rules and Regulations Part 2 §2.1051: Spurious Emissions at Antenna Terminals; Part 90 §90.543(b): Out of Band Emissions Limit

4.1 Test Procedure

ANSI/TIA/EIA-603-2002, Section 2.2.13

The transmitter is terminated with a 50 ohm load and interfaced with a spectrum analyzer. Device with digital modulation: Modulated to its maximum extent using a pseudo random data sequence – 19,200 bps for OTP and 9,600 bps for P25 and EDACS modes. The following data are the only frequencies found within 20 dB of the limit, all others are below 20 dBc.

4.2 Test Data



Rhein Tech Laboratories, Inc.
360 Herndon Parkway
Suite 1400
Herndon, VA 20170
<http://www.rheintech.com>

Client: M/A-COM, Inc.
FCC ID: BV8CS803
Model: CS-803 Control Station
Standard: FCC Part 90
RTL Report #: 2008184

Table 4-1: Test Equipment Used For Testing Conducted Spurious Emissions

RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Date
901413	Agilent Technologies	E4448A	Spectrum Analyzer	US44020346	7/31/09
900957	MCE Weinschel	68-20-43	Attenuator 20 dB	LT394	1/13/09
901424	Insulated Wire Inc.	KPS-1503-360-KPS	RF cable 36"	NA	10/5/09
901128	Par Electronics	806-902 (25W)	UHF Notch Filter	N/A	2/1/09

Test Personnel:

Daniel Baltzell		October 24, 2008
Test Engineer	Signature	Date Of Test

5 FCC Rules and Regulations Part 2 §2.1053(a): Field Strength of Spurious Radiation; Part 90 §90.543(b): Out of Band Emissions Limit

5.1 Test Procedure

ANSI/TIA/EIA-603-2002, section 2.2.12

Analog Modulation: The transmitter is terminated with a 50 ohm load and is modulated with a 2,500 Hz sine wave at an input level 16 dB greater than that required to produce 50% of the rated system deviation at 1,000 Hz.

Device with digital modulation: Modulated to its maximum extent using a pseudo random data sequence – 19,200 bps for OTP and 9,600 bps for P25 and EDACS modes.

The spurious emissions levels were measured, and the device under test was replaced by a substitution antenna connected to a signal generator. The signal generator level was then corrected by subtracting the cable loss from the substitution antenna to the signal generator, and the gain of the antenna was further corrected to a half wave dipole.

5.2 Test Data

All emissions were attenuated more than 20 dB below the FCC limit and per FCC 2.1057(c), are not reported.

Table 5-1: Test Equipment Used For Testing Field Strength of Spurious Radiation

RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Date
901053	Schaffner-Chase	CBL6112	Antenna (25 MHz–2 GHz)	2648	12/20/08
900772	EMCO	3161-02	Horn Antenna (2-4 GHz)	9804-1044	6/14/10
900321	EMCO	3161-03	Horn Antenna (4.0-8.2 GHz)	9508-1020	6/14/10
901365	MITEQ	JS4-00102600-41-5P	Amplifier, 0.1-26 GHz, 30dB gain	N/A	10/8/09
901413	Agilent Technologies	E4448A	Spectrum Analyzer	US44020346	7/31/09
901424	Insulated Wire Inc.	KPS-1503-360-KPS	RF cable 36"	NA	10/5/09
901425	Insulated Wire, Inc.	KPS-1503-2400-KPS	RF cable, 20'	NA	10/5/09
901426	Insulated Wire Inc.	KPS-1503-3600-KPS	RF cable, 30'	NA	10/5/09
900928	Hewlett Packard	83752A	Synthesized Sweeper, 0.01 to 20 GHz	3610A00866	12/7/08
901158	Compliance Design, Inc.	Roberts Dipole Antenna	Adjustable Elements Dipole 25-1000MHz Antennas	00401	2/4/09

Test Personnel:

Daniel Baltzell		October 27, 2008
Test Engineer	Signature	Date Of Test

6 FCC Rules and Regulations Part 2 §2.1049(c)(1): Occupied Bandwidth; Part 90 §90.543(d): Authorized Bandwidth

Occupied Bandwidth - Compliance with the emission masks


6.1 Test Procedure

ANSI/TIA/EIA-603-2002, section 2.2.11 and TIA/EIA-102.CAAA-2002 section 2.2.5

Device with digital modulation: Modulated to its maximum extent using a pseudo random data sequence – 19,200 bps for OTP mode, and 9600 bps for P25 and EDACS modes.

6.2 Test Data

Plot 6-1: Occupied Bandwidth; 820.9875 MHz; OTP WB; High Power; Mask G



Rhein Tech Laboratories, Inc.
360 Herndon Parkway
Suite 1400
Herndon, VA 20170
<http://www.rheintech.com>

Client: M/A-COM, Inc.
FCC ID: BV8CS803
Model: CS-803 Control Station
Standard: FCC Part 90
RTL Report #: 2008184

Table 6-1: Test Equipment Used For Testing Occupied Bandwidth

RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Date
901413	Agilent Technologies	E4448A	Spectrum Analyzer	US44020346	7/31/09
900957	MCE Weinschel	68-20-43	Attenuator 20 dB	LT394	1/13/09

Test Personnel:

Daniel Baltzell		October 24, 2008
Test Engineer	Signature	Date Of Test

7 FCC Rules and Regulations Part 2 §2.202: Added Necessary Bandwidth and Emission Bandwidth

806-809, 809-821, 821-824 MHz SMR Trunked

Calculation:

Data rate in bps (R) = 19,200

Deviation of carrier (D) = 3900 Hz

Number of state in each symbol (S) = 4

K = 0.415

Bn = [R/log₂(4) + 2(D)(K)] = 12.8 kHz

Emission designator: 12K8F9W

8 Conclusion

The data in this measurement report shows that the **M/A-COM, Inc. Model CS-803 Control Station; FCC ID: BV8CS803**, complies with all the applicable requirements of Parts 90 and 2 of the FCC Rules and meets the requirements of a Class II Permissive Change.