

**Processing Gain
Test - CH1**

96876

**Measured by
Richard Abrahams**

Frequency Offset (kHz)	Jammer/Signal Ratio (dB)	Processing Gain (dB)		
-8500	5.0	17.3		
-8450	4.9	17.2		
-8400	4.9	17.2		
-8350	4.8	17.1		
-8300	4.8	17.1		
-8250	4.7	17.0		
-8200	4.6	16.9		
-8150	4.3	16.6		
-8100	4.0	16.3		
-8050	3.9	16.2		
-8000	3.6	15.9		
-7950	3.5	15.8		
-7900	3.4	15.7		
-7850	3.4	15.7		
-7800	3.6	15.9		
-7750	3.7	16.0		
-7700	4.0	16.3		
-7650	4.1	16.4		
-7600	4.1	16.4		
-7550	4.1	16.4		
-7500	4.1	16.4		
-7450	3.9	16.2		
-7400	3.9	16.2		
-7350	3.7	16.0		
-7300	3.7	16.0		
-7250	3.6	15.9		
-7200	2.8	15.1		
-7150	2.7	15.0		
-7100	2.7	15.0		
-7050	2.8	15.1		
-7000	2.8	15.1		
-6950	2.8	15.1		
-6900	3.5	15.8		
-6850	3.5	15.8		
-6800	3.6	15.9		
-6750	3.6	15.9		
-6700	3.6	15.9		
-6650	3.6	15.9		
-6600	3.5	15.8		
-6550	3.4	15.7		
-6500	3.2	15.5		
-6450	3.0	15.3		
-6400	2.8	15.1		
-6350	2.7	15.0		

**Processing Gain
Test - CH1**

96876

**Measured by
Richard Abrahams**

-6300	2.6	14.9		
-6250	2.7	15.0		
-6200	2.9	15.2		
-6150	3.2	15.5		
-6100	3.5	15.8		
-6050	3.8	16.1		
-6000	4.0	16.3		
-5950	4.2	16.5		
-5900	4.5	16.8		
-5850	4.6	16.9		
-5800	4.7	17.0		
-5750	4.7	17.0		
-5700	4.7	17.0		
-5650	4.5	16.8		
-5600	4.5	16.8		
-5550	4.5	16.8		
-5500	4.5	16.8		
-5450	4.5	16.8		
-5400	4.7	17.0		
-5350	4.9	17.2		
-5300	5.0	17.3		
-5250	4.9	17.2		
-5200	4.8	17.1		
-5150	4.5	16.8		
-5100	4.1	16.4		
-5050	3.7	16.0		
-5000	3.2	15.5		
-4950	2.8	15.1		
-4900	2.4	14.7		
-4850	2.3	14.6		
-4800	2.3	14.6		
-4750	2.3	14.6		
-4700	2.6	14.9		
-4650	2.9	15.2		
-4600	3.2	15.5		
-4550	3.6	15.9		
-4500	3.8	16.1		
-4450	3.8	16.1		
-4400	4.0	16.3		
-4350	4.0	16.3		
-4300	3.9	16.2		
-4250	3.7	16.0		
-4200	3.5	15.8		
-4150	3.3	15.6		
-4100	3.1	15.4		
-4050	3.0	15.3		
-4000	2.8	15.1		
-3950	2.7	15.0		
-3900	2.8	15.1		
-3850	2.8	15.1		
-3800	2.9	15.2		
-3750	3.0	15.3		

**Processing Gain
Test - CH1**

96876

**Measured by
Richard Abrahams**

-3700	3.0	15.3		
-3650	3.1	15.4		
-3600	3.1	15.4		
-3550	3.1	15.4		
-3500	3.1	15.4		
-3450	3.0	15.3		
-3400	2.8	15.1		
-3350	2.7	15.0		
-3300	2.7	15.0		
-3250	2.7	15.0		
-3200	2.8	15.1		
-3150	2.9	15.2		
-3100	3.0	15.3		
-3050	3.3	15.6		
-3000	3.4	15.7		
-2950	3.5	15.8		
-2900	3.5	15.8		
-2850	3.4	15.7		
-2800	3.2	15.5		
-2750	3.1	15.4		
-2700	3.0	15.3		
-2650	2.8	15.1		
-2600	2.6	14.9		
-2550	2.5	14.8		
-2500	2.4	14.7		
-2450	2.4	14.7		
-2400	2.5	14.8		
-2350	2.6	14.9		
-2300	2.8	15.1		
-2250	3.0	15.3		
-2200	3.1	15.4		
-2150	3.2	15.5		
-2100	3.2	15.5		
-2050	3.1	15.4		
-2000	2.9	15.2		
-1950	2.7	15.0		
-1900	2.4	14.7		
-1850	2.1	14.4		
-1800	1.9	14.2		
-1750	1.8	14.1		
-1700	1.9	14.2		
-1650	2.0	14.3		
-1600	2.3	14.6		
-1550	2.7	15.0		
-1500	3.0	15.3		
-1450	3.3	15.6		
-1400	3.4	15.7		
-1350	3.4	15.7		
-1300	3.3	15.6		
-1250	3.1	15.4		
-1200	2.9	15.2		
-1150	2.8	15.1		

**Processing Gain
Test - CH1**

96876

**Measured by
Richard Abrahams**

-1100	2.6	14.9		
-1050	2.4	14.7		
-1000	2.1	14.4		
-950	1.9	14.2		
-900	1.7	14.0		
-850	1.6	13.9		
-800	1.5	13.8		
-750	1.5	13.8		
-700	1.7	14.0		
-650	1.9	14.2		
-600	2.0	14.3		
-550	2.2	14.5		
-500	2.5	14.8		
-450	2.7	15.0		
-400	2.7	15.0		
-350	2.6	14.9		
-300	2.3	14.6		
-250	1.8	14.1		
-200	1.3	13.6		
-150	1.0	13.3		
-100	0.8	13.1		
-50	0.9	13.2		
0	1.2	13.5		
50	1.1	13.4		
100	1.3	13.6		
150	1.6	13.9		
200	1.9	14.2		
250	2.2	14.5		
300	2.4	14.7		
350	2.6	14.9		
400	2.5	14.8		
450	2.2	14.5		
500	1.8	14.1		
550	1.3	13.6		
600	1.0	13.3		
650	0.8	13.1		
700	0.8	13.1		
750	0.9	13.2		
800	1.1	13.4		
850	1.4	13.7		
900	1.7	14.0		
950	2.0	14.3		
1000	2.2	14.5		
1050	2.2	14.5		
1100	1.9	14.2		
1150	2.0	14.3		
1200	1.7	14.0		
1250	1.4	13.7		
1300	1.1	13.4		
1350	1.2	13.5		
1400	1.4	13.7		
1450	1.4	13.7		

**Processing Gain
Test - CH1**

96876

**Measured by
Richard Abrahams**

1500	1.4	13.7		
1550	1.2	13.5		
1600	1.7	14.0		
1650	1.8	14.1		
1700	1.8	14.1		
1750	1.8	14.1		
1800	1.8	14.1		
1850	1.8	14.1		
1900	1.6	13.9		
1950	1.3	13.6		
2000	1.5	13.8		
2050	1.4	13.7		
2100	1.3	13.6		
2150	1.2	13.5		
2200	1.1	13.4		
2250	0.8	13.1		
2300	0.5	12.8		
2350	0.7	13.0		
2400	1.1	13.4		
2450	1.4	13.7		
2500	1.4	13.7		
2550	1.3	13.6		
2600	1.2	13.5		
2650	1.0	13.3		
2700	0.3	12.6		
2750	-0.3	12.0		
2800	-0.5	11.8		
2850	0.1	12.4		
2900	0.4	12.7		
2950	0.2	12.5		
3000	0.8	13.1		
3050	0.9	13.2		
3100	0.6	12.9		
3150	0.3	12.6		
3200	1.6	13.9		
3250	1.3	13.6		
3300	1.9	14.2		
3350	1.9	14.2		
3400	1.8	14.1		
3450	1.6	13.9		
3500	1.3	13.6		
3550	1.0	13.3		
3600	0.5	12.8		
3650	0.2	12.5		
3700	-0.1	12.2		
3750	-0.4	11.9		
3800	-0.4	11.9		
3850	-0.3	12.0		
3900	-0.4	11.9		
3950	0.3	12.6		
4000	0.8	13.1		
4050	1.1	13.4		

**Processing Gain
Test - CH1**

96876

**Measured by
Richard Abrahams**

4100	1.2	13.5		
4150	1.2	13.5		
4200	1.1	13.4		
4250	1.0	13.3		
4300	0.9	13.2		
4350	0.8	13.1		
4400	0.7	13.0		
4450	0.7	13.0		
4500	0.6	12.9		
4550	0.4	12.7		
4600	0.4	12.7		
4650	0.5	12.8		
4700	0.0	12.3		
4750	0.0	12.3		
4800	0.5	12.8		
4850	0.5	12.8		
4900	0.5	12.8		
4950	0.6	12.9		
5000	0.6	12.9		
5050	0.9	13.2		
5100	0.9	13.2		
5150	1.1	13.4		
5200	1.0	13.3		
5250	0.6	12.9		
5300	0.7	13.0		
5350	0.6	12.9		
5400	0.7	13.0		
5450	0.7	13.0		
5500	1.9	14.2		
5550	1.9	14.2		
5600	1.8	14.1		
5650	1.8	14.1		
5700	1.8	14.1		
5750	1.7	14.0		
5800	1.5	13.8		
5850	1.2	13.5		
5900	0.9	13.2		
5950	0.6	12.9		
6000	0.2	12.5		
6050	-0.2	12.1		
6100	-0.4	11.9		
6150	-1.1	11.2		
6200	-0.9	11.4		
6250	-0.9	11.4		
6300	-0.9	11.4		
6350	-0.9	11.4		
6400	-0.9	11.4		
6450	-0.1	12.2		
6500	0.1	12.4		
6550	0.1	12.4		
6600	0.1	12.4		
6650	0.1	12.4		

Test - CH1

96876

Richard Abrahams

[illegible]

