

Rhein Tech Laboratories, Inc.  
360 Herndon Parkway  
Suite 1400  
Herndon, VA 20170  
<http://www.rheintech.com>

Client: M/A-Com, Inc.  
Model: VIDA Broadband Client  
Standards: FCC Part 90/IC RSS-111  
ID's: BV8VIDA-BB-CL/3670A-VIDABBCL  
Report Number: 2007133

## **Appendix A: RF Exposure Compliance**

Please refer to the following page.

### MPE Calculation

The Limit for **Uncontrolled Exposure Power Density (P<sub>d</sub>)** is 10 W/m<sup>2</sup> for fixed mounted device.

The M/A-COM 4.9 GHz VIDA Client is a fixed mounted radio. After installation and commissioning, the safe distance from the 9 dBi omni-directional antenna is greater than 20 cm (8-inches).

#### **MPE calculation for omni-directional antenna**

This MPE Minimum Distance Calculation is based on using a 9 dBi gain omni-directional antenna mounted directly to the Client RF port.

Basic M/A-COM 4.9 GHz Client specifications:

**P:** Maximum Peak Conducted Power = 27 dBm

**G:** Maximum Omni Antenna Gain = 9 dBi

Frequency Range = 4.94 to 4.99 GHz

**R:** Minimum Distance between User and Antenna = 0.2 m

#### **Equation from FCC:**

$$P_d = P * G / (4 * \pi * R^2)$$

$$P_d = 0.5 \text{ W} * 7.94 / (4 * 3.1415926 * 0.2^2) = 7.9 \text{ W} / \text{m}^2 < 10 \text{ W} / \text{m}^2$$

The calculation indicates that the minimum 0.2 meter distance between user and the omni-directional antenna (directly mounted to the Client RF port) is required when operating the M/A-COM 4.9 GHz VIDA Client.

#### **MPE Calculation for Directional Antenna**

This MPE Minimum Distance Calculation is based on using a directional antenna with more than 9 dBi antenna gain.

Basic M/A-COM 4.9 GHz VIDA Client specifications:

**P:** Maximum Peak Conducted Power = 27 dBm;

**G:** Maximum Antenna Gain – Cable Loss = 27 dBi – 1 dB = 26 dBi; (Use numerical G<sub>N</sub> value for the calculation): G<sub>N</sub> = 10<sup>(G/10)</sup>; For G = 26 dBi, G<sub>N</sub> = 10<sup>(26/10)</sup> = 398

Frequency Range = 4.94 to 4.99 GHz;

**R<sub>min</sub>:** Minimum Distance between user and antenna to comply with FCC MPE Level (10 W / m<sup>2</sup>);

#### **Equation from FCC:**

$$P_d = P * G / (4 * \pi * R_{min}^2)$$

$$R_{min} = \text{SQRT}(0.5 \text{ W} * G_N / (4 * 3.1415926 * 10 \text{ W/m}^2))$$

$$R_{min} = 1.26 \text{ m, for G = 26 (i.e., G_N = 398)}$$