

FCC Part 15D – Compliance Information

EUT AND PRODUCT INFORMATION

Type of Equipment	UPCS (DECT 6.0)
Applicant Name	Ascom (Sweden) AB
Address	Grimbodalen 2, 402 76 Gothenburg, Sweden
Contact	Johan Comstedt
Telephone	
Email	johan.comstedt@ascom.se
Brand Name	

	FP	PP	Repeater
EUT Type/System	☒	☐	☐
FCC ID	BXZDB1R2A		
Industry Canada ID	3724B-DB1R2A		
Model name	DB1-B3A; DB1-A3A; DB1-C3A; DB1-C5A		
HW Version	2A		
SW Version	2A		
Maximum Antenna Gain	+0.6 dB		
Can the EUT be Initiating Device	☐ YES	☐ YES	☐ YES
Does the EUT transmit signaling channels	☒ YES	☐ YES	☐ YES
Max. # of slots in use simultaneously	12		
Test standard:	☒ FCC part 15D	☒ RSS-213, Issue 2 / RSS-GEN, Issue 3	
Frequency Band	1921.536 – 1928.448 MHz		
Number of RF Channels	5		
Frame Period	10 ms		
Max. Burst length			
Min. Burst Length			
Min. # of System Channels	60 (12 duplex channels per RF carrier)		
Supported DECT Slot Types	☒ Full Slot	☐ Long Slot	☐ Double Slot
Operating Mode	☐ Simplex	☒ Duplex	

FCC Part 15D – Compliance Information

ANTENNAS				
Base (FP)	Antenna	Type	Internal	External
	1		☒	☐
	2		☒	☐
	3		☐	☐
	4		☐	☐
Does RX and TX use the same antenna(s)?			☒ Yes	☐ No
Handset (PP)	Antenna	Type	Internal	External
	1		☐	☐
	2		☐	☐
Does RX and TX use the same antenna(s)?			☐ Yes	☐ No

ANTENNA DIVERSITY			
	Antenna	Diversity Supported	
		TX	RX
Base (FP)	1	☒	☒
	2	☒	☒
	3	☐	☐
	4	☐	☐
Handset (PP)	1	☐	☐
	2	☐	☐

VOLTAGE AND TEMPERATURE RANGES			
VOLTAGES	FP	PP	Repeater
Nominal Voltage	48 VDC		
Cut-Off Voltage (if applicable)			
POWER SOURCE	Type	Manufacturer	
Base or Repeater	Powered from PBX		
Handset (PP) (charger)			
Data Connections	☐ PSTN ☒ Others (please specify): 4 wire proprietary digital		


FCC Part 15D – Compliance Information

ANCILLARY EQUIPMENT	
Description	
Type	
Manufacturer	

HOST DEVICE	
Description	
Type	
Manufacturer	

ADDITIONAL INFORMATION

FCC Part 15D – Compliance Information

MANUFACTURERS DECLARATIONS		
FCC part 15.323 (c)(5)		
The applicant declares that the system in this application has more than 20 duplex system access channels defined, and that the system is operating in Least Interfered Channel (LIC) mode in accordance with this section.		
Applicant Agrees	☒ Yes	☐ No
FCC part 15.323 (c)(5)		
No device or group of co-operating devices located within 1m of each other shall during any frame period occupy more than 6 MHz of aggregate bandwidth, or alternatively, more than one third of the time and spectrum windows defined by the system.		
Applicant Agrees	☒ Yes	☐ No
FCC part 15.323 (c)(10)		
The applicant hereby declares that the system in this application does use the criteria of (c)(10) of this section.		
Applicant Agrees	☒ Yes	☐ No
FCC part 15.323 (c)(11)		
The applicant hereby declares that system in this application does not use the criteria of (c)(11) of this section.		
Applicant Agrees	☒ Yes	☐ No
FCC part 15.323 (c)(12)		
The provisions of (c)(10) or (c)(11) of this section shall not be used to extend the range of spectrum occupied over space or time for the purpose of denying fair access to spectrum to other devices.		
Applicant Agrees	☒ Yes	☐ No
FCC part 15.307 (b)		
The Applicant is a participating member of UTAM, Inc. and will provide an affidavit from UTAM, Inc. certifying this.		
Confirmed By Applicant	☒ Yes	☐ No
ADDITIONAL REMARKS:		
>		
DECLARED BY:		
2015-03-09 Date	Tania Ottebrink Name (print)	 Signature

FCC Part 15D – Compliance Information

About this document

This document specifies the information that is needed to select the correct testcases and test procedures for testing to FCC Part 15D. The form must be completed by the applicant and submitted to Nemko before testing is started.

Preparation of Equipment for Testing

Note (a): Number of samples for testing

The following samples are needed for FCC 15D testing:

RF Conducted Tests:

One sample with a 50 ohm antenna connector (preferably SMA Female). Only one antenna connector is needed for these tests even if the equipment has more than one antenna.

Monitoring Tests:

One sample with 50 ohm antenna connectors fitted to all antennas (preferably SMA female). Additionally we need a companion device that will work together with the EUT, the companion device must also have antenna connectors on all antennas.

Radiated Tests:

One sample with integral antennas. This sample will be used to measure Antenna Gain, Part 15B and Power-Line Conducted tests.

Note (b): Monitoring Tests

Monitoring tests are performed by establishing a connection from the handset (or the initiating device) to the base station (or the responding device). Most tests are performed by establishing connections from the initiating device to the responding device and observing which channel and/or timeslot is used.

For monitoring tests we need a EUT and a Companion device that both have antenna connectors on all antennas (preferably SMA female, again). Additionally, we need access to the CLK100 signal on the Base Station, this is necessary because some of the tests require that the interferers are synced to the DECT frame.

Note (c): Connection to an external power supply

Means of connecting the equipment to an external power supply shall be supplied by the applicant together with the equipment to be tested.

Battery operated equipment shall be supplied with the necessary batteries and chargers. All tests on battery operated equipment will be performed with batteries.

Note (d): Burst Mode

Most RF tests are performed with the EUT in force transmit mode. Software and necessary programming tools must be submitted to Nemko together with the test samples before start of testing.

Note (e): Test-Mode (Loopback Mode)

Some FCC test may also be performed in Loopback Mode with a CMD60 or similar DECT tester. If loopback mode is implemented in the EUT, the method for setting the equipment in Loopback should be submitted to Nemko together with the test samples before start of testing.

