



TEST REPORT

Report Reference No. : CHTEW19030068

Report verification:



Project No..... : SHT1902011601EW

FCC ID..... : BXZSH2

Applicant's name..... : Ascom (Sweden) AB

Address..... : mailing address:Grimbodalen 2, SE-417 49 Göteborg, Sweden
P/O address: Grimbodalen 2 P.O. Box 8783,Gothenburg, SE-40276 Sweden

Manufacturer..... : Shenzhen Chuangwei Electronic Appliance Tech Co., Ltd.

Address..... : 4F & 6F, Overseas plant south, Skyworth Industrial Park, Shiyan Street, Bao'an District, Shenzhen, P.R. China

Test item description : Ascom Myco 3

Trade Mark : Ascom

Model/Type reference..... : SH2-ABAA

Listed Model(s) : SH2-XXXX("X"=A-Z represents different appearance colors, sales areas and sales channels,and is only used for propaganda purposes.The change of "X"does not affect product safety and electromagnetic compatibility)

Standard : FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of receipt of test sample..... : Feb 21, 2019

Date of testing..... : Feb 22, 2019- Mar 12, 2019

Date of issue..... : Mar 13, 2019

Result..... : PASS

Compiled by

(Position+Printed name+Signature): File administrators Silvia Li

Silvia Li

Supervised by

(Position+Printed name+Signature): Project Engineer Aaron Fang

Aaron.Fang

Approved by

(Position+Printed name+Signature): RF Manager Hans Hu

Hans Hu

Testing Laboratory Name : Shenzhen Huatongwei International Inspection Co., Ltd.

Address..... : 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

The test report merely correspond to the test sample.

Contents

<u>1.</u>	<u>TEST STANDARDS AND REPORT VERSION</u>	<u>3</u>
1.1.	Test Standards	3
1.2.	Report version	3
<u>2.</u>	<u>TEST DESCRIPTION</u>	<u>4</u>
<u>3.</u>	<u>SUMMARY</u>	<u>5</u>
3.1.	Client Information	5
3.2.	Product Description	5
3.3.	Operation state	6
3.4.	EUT configuration	6
3.5.	Modifications	6
<u>4.</u>	<u>TEST ENVIRONMENT</u>	<u>7</u>
4.1.	Address of the test laboratory	7
4.2.	Test Facility	7
4.3.	Environmental conditions	8
4.4.	Statement of the measurement uncertainty	8
4.5.	Equipments Used during the Test	9
<u>5.</u>	<u>TEST CONDITIONS AND RESULTS</u>	<u>11</u>
5.1.	Antenna requirement	11
5.2.	Conducted Emissions (AC Main)	12
5.3.	Conducted Peak Output Power	15
5.4.	20 dB Bandwidth	19
5.5.	Carrier Frequencies Separation	23
5.6.	Hopping Channel Number	25
5.7.	Dwell Time	27
5.8.	Pseudorandom Frequency Hopping Sequence	34
5.9.	Restricted band (radiated)	35
5.10.	Band edge and Spurious Emissions (conducted)	37
5.11.	Spurious Emissions (radiated)	53
<u>6.</u>	<u>TEST SETUP PHOTOS</u>	<u>57</u>
<u>7.</u>	<u>EXTERANAL AND INTERNAL PHOTOS</u>	<u>59</u>

1. TEST STANDARDS AND REPORT VERSION

1.1. Test Standards

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

[ANSI C63.10-2013](#): American National Standard for Testing Unlicensed Wireless Devices

1.2. Report version

Revision No.	Date of issue	Description
N/A	2019-03-13	Original

2. TEST DESCRIPTION

Test Item	Section in CFR 47	Result	Test Engineer
Antenna Requirement	15.203/15.247 (c)	PASS	Jiongsheng Feng
AC Power Line Conducted Emissions	15.207	PASS	Jiongsheng Feng
Conducted Peak Output Power	15.247 (b)(1)	PASS	Jiongsheng Feng
20 dB Bandwidth	15.247 (a)(1)	PASS	Jiongsheng Feng
Carrier Frequencies Separation	15.247 (a)(1)	PASS	Jiongsheng Feng
Hopping Channel Number	15.247 (a)(1)	PASS	Jiongsheng Feng
Dwell Time	15.247 (a)(1)	PASS	Jiongsheng Feng
Pseudorandom Frequency Hopping Sequence	15.247(b)(4)	PASS	Jiongsheng Feng
Restricted band	15.247(d)/15.205	PASS	Tony Duan
Radiated Emissions	15.247(d)/15.209	PASS	Tony Duan

Note: The measurement uncertainty is not included in the test result.

3. SUMMARY

3.1. Client Information

Applicant:	Ascom (Sweden) AB
Mailing Address	Grimbodalen 2, SE-417 49 Göteborg, Sweden
P/O Address:	Grimbodalen 2 P.O. Box 8783,Gothenburg, SE-40276 Sweden
Manufacturer:	Shenzhen Chuangwei Electronic Appliance Tech Co., Ltd.
Address:	4F & 6F, Overseas plant south, Skyworth Industrial Park, Shiyan Street, Bao'an District, Shenzhen, P.R. China

3.2. Product Description

Name of EUT:	Ascom Myco 3
Trade Mark:	Ascom
Model No.:	SH2-ABAA
Listed Model(s):	SH2-XXXX("X"=A-Z represents different appearance colors, sales areas and sales channels,and is only used for propaganda purposes.The change of"X"does not affect product safety and electromagnetic compatibility)
Power supply:	DC 3.8V
Hardware version:	AM500-MB-H8-V06
Software version:	Ascom.Myco3.ABAA.V1.0
Bluetooth	
Version:	Supported BT4.2+EDR
Modulation:	GFSK, $\pi/4$ DQPSK, 8DPSK
Operation frequency:	2402MHz~2480MHz
Channel number:	79
Channel separation:	1MHz
Antenna type:	LDS Antenna
Antenna gain:	2.0dBi

3.3. Operation state

➤ Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channel which were tested. the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the above gray bottom.

Channel	Frequency (MHz)
00	2402
01	2403
:	:
39	2441
:	:
77	2479
78	2480

➤ TEST MODE

For RF test items:
The engineering test program was provided and enabled to make EUT continuous transmit
For AC power line conducted emissions:
The EUT was set to connect with the Bluetooth instrument under large package sizes transmission.
For Radiated suprious emissions test item:
The engineering test program was provided and enabled to make EUT continuous transmit. The EUT in each of three orthogonal axis emissions had been tested ,but only the worst case (X axis) data recorded in the report.

3.4. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- - supplied by the manufacturer
- - supplied by the lab

Adapter	Manufacturer :	Shenzhen BaijunDa Electronic CO.,LTD.
	Model No. :	UT-090E-5065
Earphone	Manufacturer :	SHENZHEN ALLTHROUGH TECHNOLOGY CO.,LTD
	Model No. :	DC3.5 earphone
USB Cable	Length :	0.8m
	Shield :	Shield
	Type :	USB 2.0

3.5. Modifications

No modifications were implemented to meet testing criteria.

4. TEST ENVIRONMENT

4.1. Address of the test laboratory

Laboratory: Shenzhen Huatongwei International Inspection Co., Ltd.

Address: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

4.2. Test Facility

CNAS-Lab Code: L1225

Shenzhen Huatongwei International Inspection Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No.: 3902.01

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 762235

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files.

IC-Registration No.:5377B-1

Two 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No.: 5377B-1.

ACA

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

4.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35°C
Relative Humidity:	30~60 %
Air Pressure:	950~1050mba

4.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors in calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report according to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd. quality system according to ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Here after the best measurement capability for Shenzhen Huatongwei International Inspection Co., Ltd. is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.63 dB	(1)
Conducted spurious emissions 9kHz~40GHz	0.63 dB	(1)
Conducted Disturbance 150kHz~30MHz	3.35 dB	(1)
Radiated Emissions below 1GHz	4.28 dB	(1)
Radiated Emissions above 1GHz	5.16 dB	(1)
Occupied Bandwidth	69 Hz	(1)

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=1.96$.

4.5. Equipments Used during the Test

Conducted Emissions						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. (mm-dd-yy)	Next Cal. (mm-dd-yy)
1	EMI Test Receiver	R&S	ESCI	101247	10/27/2018	10/26/2019
2	Artificial Mains	SCHWARZBECK	NNLK 8121	573	10/27/2018	10/26/2019
3	Pulse Limiter	R&S	ESH3-Z2	101488	10/27/2018	10/26/2019
4	RF Connection Cable	HUBER+SUHNER	EF400	N/A	11/14/2017	11/13/2019
5	Test Software	R&S	ES-K1	N/A	N/A	N/A
6	Temperature and Humidity Meter	MIAOXIN	TH10R	N/A	10/30/2018	10/29/2019

Radiated Emissions(Below 1GHz)						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. (mm-dd-yy)	Next Cal. (mm-dd-yy)
1	Semi-Anechoic Chamber	Albatross projects	SAC-3m-02	C11121	09/30/2018	09/29/2021
2	EMI Test Receiver	R&S	ESCI	100900	10/28/2018	10/27/2019
3	Loop Antenna	R&S	HFH2-Z2	100020	04/02/2018	04/02/2021
4	Ultra-Broadband Antenna	SCHWARZBECK	VULB9163	546	04/05/2017	04/04/2020
5	Pre-amplifier	SCHWARZBECK	BBV 9742	N/A	11/15/2018	11/14/2019
6	RF Connection Cable	HUBER+SUHNER	N/A	N/A	09/28/2018	09/27/2019
7	RF Connection Cable	HUBER+SUHNER	SUCOFLEX104	501184/4	09/28/2018	09/27/2019
8	Test Software	R&S	ES-K1	N/A	N/A	N/A
9	Turntable	Maturo Germany	TT2.0-1T	N/A	N/A	N/A
10	Antenna Mast	Maturo Germany	TAM-4.0-P	N/A	N/A	N/A
11	Temperature and Humidity Meter	KEJIAN	KJ03	N/A	10/30/2018	10/29/2019

Radiated Emissions(Above 1GHz)						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. (mm-dd-yy)	Next Cal. (mm-dd-yy)
1	Anechoic Chamber	Albatross projects	SAC-3m-01	C11121	09/30/2018	09/29/2021
2	Horn Antenna	SCHWARZBECK	9120D	1011	03/27/2017	03/26/2020
3	Preamplifier	BONN	BLWA0160-2M	1811887	11/14/2018	11/13/2019
4	Broadband Pre-amplifier	SCHWARZBECK	BBV 9718	9718-248	04/28/2018	04/27/2019
5	Spectrum Analyzer	R&S	FSP40	100597	10/27/2018	10/26/2019
6	RF Connection Cable	HUBER+SUHNER	RE-7-FL	N/A	11/15/2018	11/14/2019
7	RF Connection Cable	HUBER+SUHNER	RE-7-FH	N/A	11/15/2018	11/14/2019
8	Test Software	Audix	E3	N/A	N/A	N/A
9	Turntable	Maturo Germany	TT2.0-1T	N/A	N/A	N/A
10	Antenna Mast	Maturo Germany	CAM-4.0-P-12	N/A	N/A	N/A
11	Temperature and Humidity Meter	MINGLE	YH101	N/A	10/30/2018	10/29/2019

RF Conducted Test						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. (mm-dd-yy)	Next Cal. (mm-dd-yy)
1	Spectrum Analyzer	R&S	FSV40	100048	10/28/2018	10/27/2019
2	EXA Signal Analyzer	Agilent	N9020A	MY5050187	09/29/2018	09/28/2019

5. TEST CONDITIONS AND RESULTS

5.1. Antenna requirement

Requirement

FCC CFR Title 47 Part 15 Subpart C Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.


FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):

(i) Systems operating in the 2400~2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Test Result:

☒ **Passed** ☐ **Not Applicable**

The directional gain of the antenna less than 6 dBi, please refer to the below antenna photo.



5.2. Conducted Emissions (AC Main)


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup according to ANSI C63.10:2013 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST RESULTS


☒ Passed ☐ Not Applicable

Note:

- 1) Transd= Cable lose + Pulse Limiter Factor + Artificial Mains Factor
- 2) Margin= Limit - Level

Test Line:

L

**MEASUREMENT RESULT: "GM1903055059_fin"**

3/5/2019 4:00PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.172500	50.20	10.1	65	14.6	QP	L1	GND
0.231000	41.90	10.2	62	20.5	QP	L1	GND
0.280500	39.90	10.2	61	20.9	QP	L1	GND
0.397500	38.40	10.1	58	19.5	QP	L1	GND
0.505500	36.60	10.0	56	19.4	QP	L1	GND
0.564000	38.70	10.0	56	17.3	QP	L1	GND


MEASUREMENT RESULT: "GM1903055059_fin2"

3/5/2019 4:00PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.168000	38.40	10.1	55	16.7	AV	L1	GND
0.285000	32.20	10.2	51	18.5	AV	L1	GND
0.397500	30.40	10.1	48	17.5	AV	L1	GND
0.451500	25.00	10.1	47	21.8	AV	L1	GND
0.510000	28.10	10.0	46	17.9	AV	L1	GND
0.564000	28.80	10.0	46	17.2	AV	L1	GND

Test Line:

N

**MEASUREMENT RESULT: "GM1903055060_fin"**

3/5/2019 4:02PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.172500	49.80	10.1	65	15.0	QP	N	GND
0.222000	40.30	10.2	63	22.4	QP	N	GND
0.285000	39.20	10.2	61	21.5	QP	N	GND
0.339000	36.30	10.1	59	22.9	QP	N	GND
0.519000	33.90	10.0	56	22.1	QP	N	GND
0.564000	35.00	10.0	56	21.0	QP	N	GND

MEASUREMENT RESULT: "GM1903055060_fin2"

3/5/2019 4:02PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.172500	37.80	10.1	55	17.0	AV	N	GND
0.285000	33.30	10.2	51	17.4	AV	N	GND
0.397500	31.70	10.1	48	16.2	AV	N	GND
0.456000	27.20	10.1	47	19.6	AV	N	GND
0.510000	29.10	10.0	46	16.9	AV	N	GND
0.573000	29.30	10.0	46	16.7	AV	N	GND

5.3. Conducted Peak Output Power


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(1):

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt.

For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the pathloss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
 Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
 RBW $\geq$ the 20 dB bandwidth of the emission being measured, VBW $\geq$ RBW
 Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.


TEST MODE:


Please refer to the clause 3.3


TEST RESULTS

☒ Passed ☐ Not Applicable

Modulation type	Channel	Output power (dBm)	Limit (dBm)	Result
GFSK	00	3.39	≤ 30.00	Pass
	39	4.00		
	78	3.01		
$\pi/4$ DQPSK	00	3.01	≤ 21.00	Pass
	39	3.59		
	78	2.66		
8DPSK	00	3.15	≤ 21.00	Pass
	39	3.78		
	78	2.83		








5.4. 20 dB Bandwidth

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel
RBW $\geq$ 1% of the 20 dB bandwidth, VBW $\geq$ RBW
Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.


TEST MODE:


Please refer to the clause 3.3


TEST RESULTS

☒ Passed ☐ Not Applicable

Modulation type	Channel	20 dB Bandwidth (MHz)	Limit (MHz)	Result
GFSK	00	0.93	-	Pass
	39	0.93		
	78	0.93		
$\pi/4$ DQPSK	00	1.29	-	Pass
	39	1.29		
	78	1.29		
8DPSK	00	1.28	-	Pass
	39	1.28		
	78	1.29		








5.5. Carrier Frequencies Separation

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels
RBW $\geq$ 1% of the span, VBW $\geq$ RBW
Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

☒ Passed ☐ Not Applicable


Modulation type	Channel	Carrier Frequencies Separation (MHz)	Limit (MHz) *	Result
GFSK	39	1.00	≥ 0.93	Pass
$\pi/4$ DQPSK	39	1.00	≥ 0.86	Pass
8DPSK	39	1.00	≥ 0.86	Pass

Note:

*: GFSK limit = The maximum 20 dB Bandwidth for GFSK modulation on the section 5.4.

$\pi/4$ DQPSK limit = $2/3$ * The maximum 20 dB Bandwidth for $\pi/4$ DQPSK modulation on the section 5.4.

8DPSK limit = $2/3$ * The maximum 20 dB Bandwidth for 8DPSK modulation on the section 5.4




5.6. Hopping Channel Number

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1): Frequency hopping systems in the 2400–2483.5 MHz band shall use at least **15** channels.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Span = the frequency band of operation
RBW $\geq$ 1% of the span, VBW $\geq$ RBW
Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.


TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

☒ Passed ☐ Not Applicable

Modulation type	Channel number	Limit	Result
GFSK	79	≥ 15.00	Pass
$\pi/4$ DQPSK	79		
8DPSK	79		




5.7. Dwell Time

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1): The average time of occupancy on any channel shall not be greater than 0.4 seconds within a pe-riod of 0.4 seconds multiplied by the number of hopping channels employed.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Span = zero span, centered on a hopping channel, RBW= 1 MHz, VBW $\geq$ RBW
Sweep = as necessary to capture the entire dwell time per hopping channel,
Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.


TEST MODE:




Please refer to the clause 3.3


TEST RESULTS




☒ Passed ☐ Not Applicable




Modulation type	Channel	Burst Width [ms/hop/ch]	Total Hops[hop*ch]	Dwell time (Second)	Limit (Second)	Result
GFSK	DH1	0.37	314.00	0.12	≤ 0.40	Pass
	DH3	1.63	157.00	0.26		
	DH5	2.87	109.00	0.31		
$\pi/4$ DQPSK	2DH1	0.38	315.00	0.12	≤ 0.40	Pass
	2DH3	1.63	163.00	0.27		
	2DH5	2.88	100.00	0.29		
8DPSK	3DH1	0.38	317.00	0.12	≤ 0.40	Pass
	3DH3	1.63	158.00	0.26		
	3DH5	2.88	109.00	0.31		






DH3 Burst number	 The screenshot shows a spectrum plot titled 'Spectrum'. The y-axis represents power in dBm, ranging from -30 to 20. The x-axis represents frequency in GHz, centered at 2.441 GHz. A red horizontal line indicates a trigger level at -0.300 dBm. The plot shows a dense, noisy signal. The status bar at the bottom indicates 'CF 2.441 GHz', '30001 pts', and a scale of '3.16 s/'.
DH5 Burst width	 The screenshot shows a spectrum plot titled 'Spectrum'. The y-axis represents power in dBm, ranging from -30 to 20. The x-axis represents frequency in GHz, centered at 2.441 GHz. A red horizontal line indicates a trigger level at -18.400 dBm. Two measurement cursors are visible: M1[1] at -5.47 dBm and D1[1] at 7.69 dB. The status bar at the bottom indicates 'CF 2.441 GHz', '8001 pts', and a scale of '1.0 ms/'.
DH5 Burst number	 The screenshot shows a spectrum plot titled 'Spectrum'. The y-axis represents power in dBm, ranging from -30 to 20. The x-axis represents frequency in GHz, centered at 2.441 GHz. A red horizontal line indicates a trigger level at -0.400 dBm. The plot shows a dense, noisy signal. The status bar at the bottom indicates 'CF 2.441 GHz', '30001 pts', and a scale of '3.16 s/'.



2DH3 Burst number	 The spectrum plot shows a signal centered at 2.441 GHz. The y-axis represents power in dBm, ranging from -30 to 20. The x-axis represents frequency in MHz, ranging from 3.16 to 3.17. A red trigger line is set at -1.200 dBm. The plot shows a dense signal with many narrow peaks.
2DH5 Burst width	 The spectrum plot shows a signal centered at 2.441 GHz. The y-axis represents power in dBm, ranging from -30 to 20. The x-axis represents frequency in MHz, ranging from 3.16 to 3.17. A red trigger line is set at -1.200 dBm. The plot shows a dense signal with many narrow peaks. The plot is zoomed in to show a specific burst.
2DH5 Burst number	 The spectrum plot shows a signal centered at 2.441 GHz. The y-axis represents power in dBm, ranging from -30 to 20. The x-axis represents frequency in MHz, ranging from 3.16 to 3.17. A red trigger line is set at -1.200 dBm. The plot shows a dense signal with many narrow peaks.

Modulation Type:	$\pi/4$ DQPSK
3DH1 Burst width	 Spectrum plot showing a single burst of signal. The y-axis represents power in dBm, ranging from -30 to 20. The x-axis represents time in ms, ranging from 0 to 1.0. A red trigger line is set at -18.700 dBm. The signal is a narrowband burst centered around 2.441 GHz. The plot shows a sharp peak at the burst center, with a power level of approximately -17.63 dBm. The burst width is 6.16 dB and 377.50 μs. The plot is titled 'Spectrum' and includes parameters: Ref Level 30.00 dBm, Att 40 dB, RBW 1 MHz, SWT 10 ms, VBW 3 MHz. The plot is also labeled 'IAP Clr' and 'SGL TRG:VID'.
3DH1 Burst number	 Spectrum plot showing a continuous signal. The y-axis represents power in dBm, ranging from -30 to 20. The x-axis represents time in s, ranging from 0 to 3.16. A red trigger line is set at -18.700 dBm. The signal is a narrowband signal centered around 2.441 GHz. The plot shows a continuous signal with a power level of approximately -18.700 dBm. The plot is titled 'Spectrum' and includes parameters: Ref Level 30.00 dBm, Att 40 dB, RBW 500 kHz, SWT 31.6 s, VBW 3 MHz. The plot is also labeled 'IAP Clr' and 'SGL TRG:VID'.
3DH3 Burst width	 Spectrum plot showing a single burst of signal. The y-axis represents power in dBm, ranging from -30 to 20. The x-axis represents time in ms, ranging from 0 to 1.0. A red trigger line is set at -18.800 dBm. The signal is a narrowband burst centered around 2.441 GHz. The plot shows a sharp peak at the burst center, with a power level of approximately -5.29 dBm. The burst width is 5.64 dB and 1.62750 ms. The plot is titled 'Spectrum' and includes parameters: Ref Level 30.00 dBm, Att 40 dB, RBW 1 MHz, SWT 10 ms, VBW 3 MHz. The plot is also labeled 'IAP Clr' and 'SGL TRG:VID'.

3DH3 Burst number	 The spectrum plot shows a dense, continuous signal across the frequency range. The y-axis represents power in dBm, ranging from -30 to 20. The x-axis represents frequency in GHz, centered at 2.441 GHz. The plot shows a high level of activity with many narrow peaks. A red trigger line is set at -0.900 dBm. The plot title is 'Spectrum' and the settings are: Ref Level 30.00 dBm, Att 40 dB, RBW 500 kHz, SGL TRG:VID, 1AP Clr, and VSW 3 MHz. The bottom status bar shows 'CF 2.441 GHz', '30001 pts', and '3.16 s'.
3DH5 Burst width	 The spectrum plot shows a burst of signal. The y-axis represents power in dBm, ranging from -30 to 20. The x-axis represents frequency in GHz, centered at 2.441 GHz. The plot shows a high level of activity with many narrow peaks. A red trigger line is set at -18.900 dBm. The plot title is 'Spectrum' and the settings are: Ref Level 30.00 dBm, Att 40 dB, RBW 1 MHz, SGL TRG:VID, 1AP Clr, and VSW 3 MHz. The bottom status bar shows 'CF 2.441 GHz', '8001 pts', and '1.0 ms'. Additional data points are shown: M1[1] -6.29 dBm, D1[1] 0.0000000 s, 6.24 dB, and 2.87875 ms.
3DH5 Burst number	 The spectrum plot shows a dense, continuous signal across the frequency range. The y-axis represents power in dBm, ranging from -30 to 20. The x-axis represents frequency in GHz, centered at 2.441 GHz. The plot shows a high level of activity with many narrow peaks. A red trigger line is set at -0.900 dBm. The plot title is 'Spectrum' and the settings are: Ref Level 30.00 dBm, Att 40 dB, RBW 500 kHz, SGL TRG:VID, 1AP Clr, and VSW 3 MHz. The bottom status bar shows 'CF 2.441 GHz', '30001 pts', and '3.16 s'.

5.8. Pseudorandom Frequency Hopping Sequence


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1): Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo-randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

TEST RESULTS


The pseudorandom frequency hopping sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first one of 9 consecutive ones, for example: the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: $2^9 - 1 = 511$ bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of pseudorandom frequency hopping sequence as follows:



Each frequency used equally on the average by each transmitter.

The system receiver has input bandwidths that match the hopping channel bandwidths of their corresponding transmitter and shift frequencies in synchronization with the transmitted signals.


5.9. Restricted band (radiated)

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, Radiated Emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the Radiated Emissions limits specified in §15.209(a) (see §15.205(c)).

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.
5. The receiver set as follow:
RBW=1 MHz, VBW=3 MHz Peak detector for Peak value
RBW=1 MHz, VBW=10 Hz Peak detector for Average value.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

☒ Passed ☐ Not Applicable

Note:

- 1) Final level= Read level + Antenna Factor+ Cable Loss- Preamp Factor
- 2) Have pre-scan all modulation mode, found the GFSK modulation which it was worst case, so only the worst case's data on the test report.
- 3) The peak level is lower than average limit(54 dBuV/m), this data is the too weak instrument of signal is unable to test.

Test channel:					CH00				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2310.00	31.08	28.05	6.62	37.59	28.16	74.00	-45.84	Horizontal	Peak
2390.00	30.88	27.65	6.75	37.59	27.69	74.00	-46.31	Horizontal	Peak
2310.00	30.16	28.05	6.62	37.59	27.24	74.00	-46.76	Vertical	Peak
2390.00	30.48	27.65	6.75	37.59	27.29	74.00	-46.71	Vertical	Peak
2310.00	19.04	28.05	6.62	37.59	16.12	54.00	-37.88	Horizontal	Average
2390.00	18.73	27.65	6.75	37.59	15.54	54.00	-38.46	Horizontal	Average
2310.00	18.92	28.05	6.62	37.59	16.00	54.00	-38.00	Vertical	Average
2390.00	18.58	27.65	6.75	37.59	15.39	54.00	-38.61	Vertical	Average


Test channel:					CH78				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2483.50	46.72	27.26	6.83	37.59	43.22	74.00	-30.78	Horizontal	Peak
2500.00	30.04	27.20	6.84	37.59	26.49	74.00	-47.51	Horizontal	Peak
2483.50	45.78	27.26	6.83	37.59	42.28	74.00	-31.72	Vertical	Peak
2500.00	30.24	27.20	6.84	37.59	26.69	74.00	-47.31	Vertical	Peak
2483.50	20.89	27.26	6.83	37.59	17.39	54.00	-36.61	Horizontal	Average
2500.00	17.84	27.20	6.84	37.59	14.29	54.00	-39.71	Horizontal	Average
2483.50	21.82	27.26	6.83	37.59	18.32	54.00	-35.68	Vertical	Average
2500.00	18.76	27.20	6.84	37.59	15.21	54.00	-38.79	Vertical	Average

5.10. Band edge and Spurious Emissions (conducted)

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
RBW = 100 kHz, VBW $\geq$ RBW, scan up through 10th harmonic.
Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

TEST MODE:


Please refer to the clause 3.3

TEST RESULTS

☒ Passed ☐ Not Applicable


Test Item:	Band edge	Modulation type:	GFSK																																										
CH00 No hopping mode	Spectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 1.1 ms VBW 300 kHz Mode Auto Sweep Count 500/500 1Pk Max 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm -70 dBm M1[1] M2[1] M3 M4 M5 2.86 dBm 2.402180 GHz -51.31 dBm 2.400000 GHz D1 -17.140 dBm Start 2.31 GHz 691 pts Stop 2.405 GHz Marker <table><thead><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr></thead><tbody><tr><td>M1</td><td>1</td><td></td><td>2.40218 GHz</td><td>2.86 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.4 GHz</td><td>-51.31 dBm</td><td></td><td></td></tr><tr><td>M3</td><td>1</td><td></td><td>2.39 GHz</td><td>-55.37 dBm</td><td></td><td></td></tr><tr><td>M4</td><td>1</td><td></td><td>2.31 GHz</td><td>-55.55 dBm</td><td></td><td></td></tr><tr><td>M5</td><td>1</td><td></td><td>2.399906 GHz</td><td>-53.05 dBm</td><td></td><td></td></tr></tbody></table>			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.40218 GHz	2.86 dBm			M2	1		2.4 GHz	-51.31 dBm			M3	1		2.39 GHz	-55.37 dBm			M4	1		2.31 GHz	-55.55 dBm			M5	1		2.399906 GHz	-53.05 dBm		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1	1		2.40218 GHz	2.86 dBm																																									
M2	1		2.4 GHz	-51.31 dBm																																									
M3	1		2.39 GHz	-55.37 dBm																																									
M4	1		2.31 GHz	-55.55 dBm																																									
M5	1		2.399906 GHz	-53.05 dBm																																									
CH00 Hopping mode	Spectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 1.1 ms VBW 300 kHz Mode Auto Sweep Count 500/500 1Pk Max 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm -70 dBm M1[1] M2[1] M3 M4 M5 3.02 dBm 2.404110 GHz -54.02 dBm 2.400000 GHz D1 -16.980 dBm Start 2.31 GHz 691 pts Stop 2.405 GHz Marker <table><thead><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr></thead><tbody><tr><td>M1</td><td>1</td><td></td><td>2.40411 GHz</td><td>3.02 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.4 GHz</td><td>-54.02 dBm</td><td></td><td></td></tr><tr><td>M3</td><td>1</td><td></td><td>2.39 GHz</td><td>-55.29 dBm</td><td></td><td></td></tr><tr><td>M4</td><td>1</td><td></td><td>2.31 GHz</td><td>-55.93 dBm</td><td></td><td></td></tr><tr><td>M5</td><td>1</td><td></td><td>2.340565 GHz</td><td>-53.54 dBm</td><td></td><td></td></tr></tbody></table>			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.40411 GHz	3.02 dBm			M2	1		2.4 GHz	-54.02 dBm			M3	1		2.39 GHz	-55.29 dBm			M4	1		2.31 GHz	-55.93 dBm			M5	1		2.340565 GHz	-53.54 dBm		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1	1		2.40411 GHz	3.02 dBm																																									
M2	1		2.4 GHz	-54.02 dBm																																									
M3	1		2.39 GHz	-55.29 dBm																																									
M4	1		2.31 GHz	-55.93 dBm																																									
M5	1		2.340565 GHz	-53.54 dBm																																									
CH78 No hopping mode	Spectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 56.9 μs VBW 300 kHz Mode Auto FFT Count 500/500 1Pk Max 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm -70 dBm M1[1] M2[1] M3 M4 2.75 dBm 2.4801490 GHz -57.76 dBm 2.4835000 GHz D1 -17.250 dBm Start 2.478 GHz 691 pts Stop 2.5 GHz Marker <table><thead><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr></thead><tbody><tr><td>M1</td><td>1</td><td></td><td>2.480149 GHz</td><td>2.75 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.4835 GHz</td><td>-57.76 dBm</td><td></td><td></td></tr><tr><td>M3</td><td>1</td><td></td><td>2.5 GHz</td><td>-60.08 dBm</td><td></td><td></td></tr><tr><td>M4</td><td>1</td><td></td><td>2.4839623 GHz</td><td>-56.64 dBm</td><td></td><td></td></tr></tbody></table>			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.480149 GHz	2.75 dBm			M2	1		2.4835 GHz	-57.76 dBm			M3	1		2.5 GHz	-60.08 dBm			M4	1		2.4839623 GHz	-56.64 dBm									
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1	1		2.480149 GHz	2.75 dBm																																									
M2	1		2.4835 GHz	-57.76 dBm																																									
M3	1		2.5 GHz	-60.08 dBm																																									
M4	1		2.4839623 GHz	-56.64 dBm																																									

CH78
Hopping mode




Test Item:	Band edge	Modulation type:	$\pi/4$ DQPSK																																										
CH00 No hopping mode	Spectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 1.1 ms VBW 300 kHz Mode Auto Sweep Count 500/500 1Pk Max 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm -70 dBm M1[1] M2[1] D1 -18.380 dBm M5 M3 1.62 dBm 2.402180 GHz -52.57 dBm 2.400000 GHz Start 2.31 GHz 691 pts Stop 2.405 GHz Marker <table><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr><tr><td>M1</td><td>1</td><td></td><td>2.40218 GHz</td><td>1.62 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.4 GHz</td><td>-52.57 dBm</td><td></td><td></td></tr><tr><td>M3</td><td>1</td><td></td><td>2.39 GHz</td><td>-56.36 dBm</td><td></td><td></td></tr><tr><td>M4</td><td>1</td><td></td><td>2.31 GHz</td><td>-54.63 dBm</td><td></td><td></td></tr><tr><td>M5</td><td>1</td><td></td><td>2.399906 GHz</td><td>-52.82 dBm</td><td></td><td></td></tr></table>			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.40218 GHz	1.62 dBm			M2	1		2.4 GHz	-52.57 dBm			M3	1		2.39 GHz	-56.36 dBm			M4	1		2.31 GHz	-54.63 dBm			M5	1		2.399906 GHz	-52.82 dBm		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1	1		2.40218 GHz	1.62 dBm																																									
M2	1		2.4 GHz	-52.57 dBm																																									
M3	1		2.39 GHz	-56.36 dBm																																									
M4	1		2.31 GHz	-54.63 dBm																																									
M5	1		2.399906 GHz	-52.82 dBm																																									
CH00 Hopping mode	Spectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 1.1 ms VBW 300 kHz Mode Auto Sweep Count 500/500 1Pk Max 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm -70 dBm M1[1] M2[1] D1 -18.900 dBm M5 M3 M2 1.10 dBm 2.404110 GHz -55.79 dBm 2.400000 GHz Start 2.31 GHz 691 pts Stop 2.405 GHz Marker <table><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr><tr><td>M1</td><td>1</td><td></td><td>2.40411 GHz</td><td>1.27 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.4 GHz</td><td>-55.79 dBm</td><td></td><td></td></tr><tr><td>M3</td><td>1</td><td></td><td>2.39 GHz</td><td>-54.88 dBm</td><td></td><td></td></tr><tr><td>M4</td><td>1</td><td></td><td>2.31 GHz</td><td>-54.21 dBm</td><td></td><td></td></tr><tr><td>M5</td><td>1</td><td></td><td>2.325007 GHz</td><td>-53.89 dBm</td><td></td><td></td></tr></table>			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.40411 GHz	1.27 dBm			M2	1		2.4 GHz	-55.79 dBm			M3	1		2.39 GHz	-54.88 dBm			M4	1		2.31 GHz	-54.21 dBm			M5	1		2.325007 GHz	-53.89 dBm		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1	1		2.40411 GHz	1.27 dBm																																									
M2	1		2.4 GHz	-55.79 dBm																																									
M3	1		2.39 GHz	-54.88 dBm																																									
M4	1		2.31 GHz	-54.21 dBm																																									
M5	1		2.325007 GHz	-53.89 dBm																																									
CH78 No hopping mode	Spectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 56.9 μs VBW 300 kHz Mode Auto FFT Count 500/500 1Pk Max 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm -70 dBm M1 M2[1] D1 -18.490 dBm M2 M4 M5 1.51 dBm 2.4798310 GHz -58.89 dBm 2.4835000 GHz Start 2.478 GHz 691 pts Stop 2.5 GHz Marker <table><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr><tr><td>M1</td><td>1</td><td></td><td>2.479831 GHz</td><td>1.51 dBm</td><td></td><td></td></tr><tr><td>M2</td><td>1</td><td></td><td>2.4835 GHz</td><td>-58.89 dBm</td><td></td><td></td></tr><tr><td>M3</td><td>1</td><td></td><td>2.5 GHz</td><td>-59.99 dBm</td><td></td><td></td></tr><tr><td>M4</td><td>1</td><td></td><td>2.4937188 GHz</td><td>-57.77 dBm</td><td></td><td></td></tr></table>			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1	1		2.479831 GHz	1.51 dBm			M2	1		2.4835 GHz	-58.89 dBm			M3	1		2.5 GHz	-59.99 dBm			M4	1		2.4937188 GHz	-57.77 dBm									
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1	1		2.479831 GHz	1.51 dBm																																									
M2	1		2.4835 GHz	-58.89 dBm																																									
M3	1		2.5 GHz	-59.99 dBm																																									
M4	1		2.4937188 GHz	-57.77 dBm																																									




CH78
Hopping mode




Test Item:	Band edge	Modulation type:	8DPSK																																										
CH00 No hopping mode	Spectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 1.1 ms VBW 300 kHz Mode Auto Sweep Count 500/500 1Pk Max 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm -70 dBm M1[1] M2[1] M3 M4 M5 1.66 dBm 2.402180 GHz -51.63 dBm 2.400000 GHz -57.07 dBm -56.24 dBm -52.08 dBm D1 -18.340 dBm Start 2.31 GHz 691 pts Stop 2.405 GHz Marker <table><thead><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr></thead><tbody><tr><td>M1</td><td></td><td>1</td><td>2.40218 GHz</td><td>1.66 dBm</td><td></td><td></td></tr><tr><td>M2</td><td></td><td>1</td><td>2.4 GHz</td><td>-51.63 dBm</td><td></td><td></td></tr><tr><td>M3</td><td></td><td>1</td><td>2.39 GHz</td><td>-57.07 dBm</td><td></td><td></td></tr><tr><td>M4</td><td></td><td>1</td><td>2.31 GHz</td><td>-56.24 dBm</td><td></td><td></td></tr><tr><td>M5</td><td></td><td>1</td><td>2.399906 GHz</td><td>-52.08 dBm</td><td></td><td></td></tr></tbody></table>			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1		1	2.40218 GHz	1.66 dBm			M2		1	2.4 GHz	-51.63 dBm			M3		1	2.39 GHz	-57.07 dBm			M4		1	2.31 GHz	-56.24 dBm			M5		1	2.399906 GHz	-52.08 dBm		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1		1	2.40218 GHz	1.66 dBm																																									
M2		1	2.4 GHz	-51.63 dBm																																									
M3		1	2.39 GHz	-57.07 dBm																																									
M4		1	2.31 GHz	-56.24 dBm																																									
M5		1	2.399906 GHz	-52.08 dBm																																									
CH00 Hopping mode	Spectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 1.1 ms VBW 300 kHz Mode Auto Sweep Count 500/500 1Pk Max 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm -70 dBm M1[1] M2[1] M3 M4 M5 -0.42 dBm 2.402040 GHz -54.78 dBm 2.400000 GHz -55.50 dBm -54.98 dBm -53.85 dBm D1 -20.420 dBm Start 2.31 GHz 691 pts Stop 2.405 GHz Marker <table><thead><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr></thead><tbody><tr><td>M1</td><td></td><td>1</td><td>2.40204 GHz</td><td>-0.42 dBm</td><td></td><td></td></tr><tr><td>M2</td><td></td><td>1</td><td>2.4 GHz</td><td>-54.78 dBm</td><td></td><td></td></tr><tr><td>M3</td><td></td><td>1</td><td>2.39 GHz</td><td>-55.50 dBm</td><td></td><td></td></tr><tr><td>M4</td><td></td><td>1</td><td>2.31 GHz</td><td>-54.98 dBm</td><td></td><td></td></tr><tr><td>M5</td><td></td><td>1</td><td>2.334232 GHz</td><td>-53.85 dBm</td><td></td><td></td></tr></tbody></table>			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1		1	2.40204 GHz	-0.42 dBm			M2		1	2.4 GHz	-54.78 dBm			M3		1	2.39 GHz	-55.50 dBm			M4		1	2.31 GHz	-54.98 dBm			M5		1	2.334232 GHz	-53.85 dBm		
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1		1	2.40204 GHz	-0.42 dBm																																									
M2		1	2.4 GHz	-54.78 dBm																																									
M3		1	2.39 GHz	-55.50 dBm																																									
M4		1	2.31 GHz	-54.98 dBm																																									
M5		1	2.334232 GHz	-53.85 dBm																																									
CH78 No hopping mode	Spectrum Ref Level 20.00 dBm Offset 1.00 dB RBW 100 kHz Att 30 dB SWT 56.9 μs VBW 300 kHz Mode Auto FFT Count 500/500 1Pk Max 10 dBm 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm -50 dBm -60 dBm -70 dBm M1[1] M2[1] M3 M4 M5 1.57 dBm 2.4801490 GHz -59.30 dBm 2.4835000 GHz -60.69 dBm -57.46 dBm D1 -18.430 dBm Start 2.478 GHz 691 pts Stop 2.5 GHz Marker <table><thead><tr><th>Type</th><th>Ref</th><th>Trc</th><th>X-value</th><th>Y-value</th><th>Function</th><th>Function Result</th></tr></thead><tbody><tr><td>M1</td><td></td><td>1</td><td>2.480149 GHz</td><td>1.57 dBm</td><td></td><td></td></tr><tr><td>M2</td><td></td><td>1</td><td>2.4835 GHz</td><td>-59.30 dBm</td><td></td><td></td></tr><tr><td>M3</td><td></td><td>1</td><td>2.5 GHz</td><td>-60.69 dBm</td><td></td><td></td></tr><tr><td>M4</td><td></td><td>1</td><td>2.4886812 GHz</td><td>-57.46 dBm</td><td></td><td></td></tr></tbody></table>			Type	Ref	Trc	X-value	Y-value	Function	Function Result	M1		1	2.480149 GHz	1.57 dBm			M2		1	2.4835 GHz	-59.30 dBm			M3		1	2.5 GHz	-60.69 dBm			M4		1	2.4886812 GHz	-57.46 dBm									
Type	Ref	Trc	X-value	Y-value	Function	Function Result																																							
M1		1	2.480149 GHz	1.57 dBm																																									
M2		1	2.4835 GHz	-59.30 dBm																																									
M3		1	2.5 GHz	-60.69 dBm																																									
M4		1	2.4886812 GHz	-57.46 dBm																																									

CH78
Hoppig mode




Test Item:	SE	Modulation type:	GFSK
CH00 Reference level			
CH00 30MHz~1000MHz			
CH00 1GHz~26GHz			


CH39
Reference level




CH39
30MHz~1000MHz




CH39
1GHz~26GHz




CH78
Reference level






CH78
30MHz~1000MHz




CH78
1GHz~26GHz




Test Item:	SE	Modulation type:	$\pi/4$ DQPSK
CH00 Reference level			
CH00 30MHz~1000MHz			
CH00 1GHz~26GHz			


CH39
Reference level




CH39
30MHz~1000MHz




CH39
1GHz~26GHz




CH78
Reference level






CH78
30MHz~1000MHz




CH78
1GHz~26GHz




Test Item:	SE	Modulation type:	8DPSK
CH00 Reference level			
CH00 30MHz~1000MHz			
CH00 1GHz~26GHz			


CH39
Reference level




CH39
30MHz~1000MHz




CH39
1GHz~26GHz




CH78
Reference level



CH78
30MHz~1000MHz



CH78
1GHz~26GHz



5.11. Spurious Emissions (radiated)


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209


Frequency	Limit (dBuV/m @3m)	Value
30 MHz ~ 88 MHz	40.00	Quasi-peak
88 MHz ~ 216 MHz	43.50	Quasi-peak
216 MHz ~ 960 MHz	46.00	Quasi-peak
960 MHz ~ 1 GHz	54.00	Quasi-peak
Above 1 GHz	54.00	Average
	74.00	Peak

TEST CONFIGURATION


➤ Below 30 MHz



➤ 30 MHz ~1000 MHz



➤ Above 1 GHz



TEST PROCEDURE

1. The EUT was tested according to ANSI C63.10:2013.
2. The EUT is placed on a turn table with 0.8 meter above ground for below 1GHz, 1.5 meter above ground for above 1GHz.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Below 1 GHz:
RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;
If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - (3) From 1 GHz to 10th harmonic:
RBW=1 MHz, VBW=3 MHz Peak detector for Peak value
RBW=1 MHz, VBW=10 Hz Peak detector for Average value.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

☒ Passed ☐ Not Applicable

Note:

- 1) Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2) The emission levels of other frequencies are very lower than the limit and not show in test report.
- 3) Below 1 GHz, Have pre-scan all modulation mode, found the GFSK modulation High channel which it was worst case, so only the worst case's data on the test report.
- 4) Above 1 GHz, Have pre-scan all modulation mode, found the GFSK modulation which it was worst case, so only the worst case's data on the test report
- 5) The peak level is lower than average limit (54 dBuV/m), this data is too weak instrument of signal is unable to test.


➤ 9 kHz ~ 30 MHz

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

➤ 30 MHz ~ 1 GHz

Polarization:

Vertical


**MEASUREMENT RESULT: "GM1903056200_red"**

3/6/2019 2:58AM

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
33.880000	20.40	-12.5	40.0	19.6	QP	100.0	45.00	VERTICAL
55.220000	17.80	-9.1	40.0	22.2	QP	100.0	0.00	VERTICAL
148.340000	18.90	-13.6	43.5	24.6	QP	100.0	34.00	VERTICAL
307.420000	22.80	-6.8	46.0	23.2	QP	100.0	69.00	VERTICAL
503.360000	27.10	-1.2	46.0	18.9	QP	100.0	10.00	VERTICAL
901.060000	35.40	7.6	46.0	10.6	QP	100.0	0.00	VERTICAL

Polarization:

Horizontal

**MEASUREMENT RESULT: "GM1903056201_red"**

3/6/2019 3:01AM

Frequency MHz	Level dBμV/m	Transd dB	Limit dBμV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
41.640000	18.80	-9.5	40.0	21.2	QP	100.0	205.00	HORIZONTAL
57.160000	17.90	-9.3	40.0	22.1	QP	100.0	34.00	HORIZONTAL
167.740000	18.00	-12.8	43.5	25.5	QP	100.0	69.00	HORIZONTAL
297.720000	22.80	-7.0	46.0	23.2	QP	100.0	160.00	HORIZONTAL
549.920000	27.90	-0.1	46.0	18.1	QP	100.0	185.00	HORIZONTAL
932.100000	35.50	8.0	46.0	10.5	QP	100.0	185.00	HORIZONTAL

➤ 1 GHz ~ 25 GHz

CH00									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
1809.61	31.78	25.39	5.97	37.42	25.72	74.00	-48.28	Vertical	Peak
3151.99	32.61	28.80	7.66	37.44	31.63	74.00	-42.37	Vertical	Peak
5204.40	30.61	31.49	9.84	34.98	36.96	74.00	-37.04	Vertical	Peak
7566.25	29.64	36.17	12.61	33.03	45.39	74.00	-28.61	Vertical	Peak
1746.25	37.96	25.29	5.86	37.35	31.76	74.00	-42.24	Horizontal	Peak
4159.93	31.71	29.96	8.91	36.60	33.98	74.00	-40.02	Horizontal	Peak
5732.97	31.20	31.77	10.48	34.29	39.16	74.00	-34.84	Horizontal	Peak
7508.69	30.39	36.11	12.42	33.02	45.90	74.00	-28.10	Horizontal	Peak

CH39									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
2151.59	31.21	27.12	6.40	37.60	27.13	74.00	-46.87	Vertical	Peak
3184.25	32.37	28.80	7.70	37.41	31.46	74.00	-42.54	Vertical	Peak
4278.06	30.60	30.16	9.01	36.49	33.28	74.00	-40.72	Vertical	Peak
6713.08	30.48	34.17	11.50	33.73	42.42	74.00	-31.58	Vertical	Peak
2298.80	30.84	28.09	6.60	37.59	27.94	74.00	-46.06	Horizontal	Peak
3561.64	32.64	29.19	8.21	37.09	32.95	74.00	-41.05	Horizontal	Peak
4883.52	31.09	31.43	9.59	35.58	36.53	74.00	-37.47	Horizontal	Peak
7451.57	29.85	36.20	12.24	33.10	45.19	74.00	-28.81	Horizontal	Peak


CH78									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	Test value
1663.80	33.40	25.09	5.69	37.26	26.92	74.00	-47.08	Vertical	Peak
3258.04	33.05	28.45	7.79	37.34	31.95	74.00	-42.05	Vertical	Peak
5420.74	29.92	31.58	10.14	34.57	37.07	74.00	-36.93	Vertical	Peak
7800.94	29.37	36.11	13.26	33.05	45.69	74.00	-28.31	Vertical	Peak
1908.97	36.54	25.39	6.13	37.51	30.55	74.00	-43.45	Horizontal	Peak
3160.03	32.96	28.80	7.67	37.43	32.00	74.00	-42.00	Horizontal	Peak
5352.19	30.76	31.40	10.06	34.69	37.53	74.00	-36.47	Horizontal	Peak
7981.72	30.12	37.03	12.39	33.07	46.47	74.00	-27.53	Horizontal	Peak

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The peak level is lower than average limit (54 dBuV/m), this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.


6. TEST SETUP PHOTOS

Conducted Emissions (AC Mains)



Radiated Emissions









7. EXTERANAL AND INTERNAL PHOTOS


External photos of the EUT











Internal photos of the EUT









-----End of Report-----