

# RF Exposure Evaluation

## of

E.U.T. : AMPLIFIED INDOOR HDTV ANTENNA WITH WIFI  
EXTENDER  
FCC ID. : C2SGTVWFAC  
Model No. : TRINITYXTAC,WITRIAC,WITRIACV,  
WIXXXXXX,TRXXXXXXXXXXXXXX,  
Where either X is could be A-Z, 0-9, or blank for  
packaging type only

## for

APPLICANT : Good Mind Industries, Co.,Ltd  
ADDRESS : No.22, Ta Yeou 2nd Street, Ta Fa Industrial  
District, Ta Liao District, Kaohsiung City  
83163 Taiwan (R.O.C.)

Prepared by

### **ELECTRONICS TESTING CENTER, TAIWAN**

NO. 34. LIN 5. DINGFU, LINKOU DIST.,  
NEW TAIPEI CITY, TAIWAN, 24442, R.O.C.  
Tel:(02)26023052 Fax:(02)26010910  
<http://www.etc.org.tw> ; e-mail: [emc@etc.org.tw](mailto:emc@etc.org.tw)  
Report Number : 16-08-RBF-041-MPE

# TEST REPORT CERTIFICATION

Applicant : Good Mind Industries, Co.,Ltd  
No.22, Ta Yeou 2nd Street, Ta Fa Industrial District, Ta Liao  
District, Kaohsiung City 83163 Taiwan (R.O.C.)

Manufacturer : Good Mind Industries, Co.,Ltd  
No.22, Ta Yeou 2nd Street, Ta Fa Industrial District, Ta Liao  
District, Kaohsiung City 83163 Taiwan (R.O.C.)

## Description of EUT

- a) Type of EUT : AMPLIFIED INDOOR HDTV ANTENNA WITH WIFI EXTENDER
- b) Trade Name : TERK
- c) Model No. : TRINITYXTAC
- d) Serial Model No. : WITRIAC,WITRIACV,WIXXXXXX,TRXXXXXXXXXXXXXX, Where  
either X is could be A-Z, 0-9, or blank for packaging type only
- e) Power Supply : Adapter Model:CS12N120100FUF  
I/P:100-240V, 50/60Hz, 500mA  
O/P:12.0V, 1.0A

Regulation Applied : FCC KDB447498 D01. The equipment fulfills the  
requirements on power density for general population/uncontrolled exposure and  
therefore fulfills the requirements of section 1.1310 of FCC 47 CFR Part 1.

Note: 1. The result of the testing report relate only to the item tested.

- 2. The testing report shall not be reproduced expect in full, without the written  
approval of ETC

Date Test Item Received : Aug. 18, 2016  
Date Test Campaign Completed : Sep. 22, 2016  
Date of Issue : Sep. 29, 2016

Test Engineer : Brian Huang  
(Brian Huang, Engineer )

Approve & Authorized Signer : S. S. Liou  
S. S. Liou, Section Manager  
EMC Dept. II of ELECTRONICS  
TESTING CENTER, TAIWAN

**Product Information:**

Type of EUT: AMPLIFIED INDOOR HDTV ANTENNA WITH WIFI EXTENDER

FCC ID: TERK

Model: TRINITYXTAC

Serial Model: WITRIAC,WITRIACV,WIXXXXXX,TRXXXXXXXXXXXXXX, Where either X is could be A-Z, 0-9, or blank for packaging type only

Description: AMPLIFIED INDOOR HDTV ANTENNA WITH WIFI (802.11a/b/g/n) EXTENDER

Model Only model number is different for marketing purpose. The device is difference: the same.

Maximum conducted output power: **18.02** dBm or **63.387**mW

Transmitter Maximum output power measured:

(1) 2.4GHz 802.11b/g/n

| Transmitter Mode | Output Power (dBm) | Output Power (mW) |
|------------------|--------------------|-------------------|
| 802.11b          | 18.02              | 63.387            |
| 802.11g          | 15.91              | 38.994            |
| 802.11n-HT20     | 17.08              | 51.055            |
| 802.11n-HT40     | 15.74              | 37.457            |

(2) 5.15~5.25GHz 802.11a/n/ac

| Transmitter Mode | Output Power (dBm) | Output Power (mW) |
|------------------|--------------------|-------------------|
| 802.11a          | 16.83              | 48.195            |
| 802.11an HT-20   | 15.24              | 33.420            |
| 802.11an HT-40   | 13.51              | 22.439            |
| 802.11an VHT-80  | 11.36              | 13.677            |

(3) 5.725~5.850GHz 802.11a/n/ac

| Transmitter Mode | Output Power (dBm) | Output Power (mW) |
|------------------|--------------------|-------------------|
| 802.11a          | 15.70              | 37.154            |
| 802.11an HT-20   | 13.78              | 23.878            |
| 802.11an HT-40   | 13.15              | 20.654            |
| 802.11an VHT-80  | 10.73              | 11.830            |

The following table lists the provided authorized antennas:

| Model        | Antenna Type | Antenna Gain |         |
|--------------|--------------|--------------|---------|
|              |              | (dBi)        | Numeric |
| HYW-06172459 | PCB Antenna  | 2.0          | 1.58    |

Below is an example of the RF Exposure Statement:

**IMPORTANT NOTE:** To comply with the FCC RF exposure compliance requirements, the antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter. No change to the antenna or the device is permitted. Any change to the antenna or the device could result in the device exceeding the RF exposure requirements and void user's authority to operate the device.

## Relative Requirement for Compliance

According to section 1.1310 of FCC 47 CFR Part 1, limits for maximum permissible exposure (MPE) are as following:

**TABLE 1 – LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

| Frequency Range<br>(MHz)                                       | Electric Field<br>Strength<br>(V/m) | Magnetic Field<br>Strength<br>(A/m) | Power Density<br>(mW/cm <sup>2</sup> ) | Averaging Time<br>(minutes) |
|----------------------------------------------------------------|-------------------------------------|-------------------------------------|----------------------------------------|-----------------------------|
| <b>(A) Limits for Occupational/Controlled Exposures</b>        |                                     |                                     |                                        |                             |
| 0.3-3.0 .....                                                  | 614                                 | 1.63                                | *(100)                                 | 6                           |
| 3-30 .....                                                     | 1842/f                              | 4.89/f                              | *(900/f <sup>2</sup> )                 | 6                           |
| 30-300 .....                                                   | 61.4                                | 0.163                               | 1.0                                    | 6                           |
| 300-1500 .....                                                 | .....                               | .....                               | f/300                                  | 6                           |
| 1500-100,000 .....                                             | .....                               | .....                               | 5                                      | 6                           |
| <b>(B) Limits for General Population/Uncontrolled Exposure</b> |                                     |                                     |                                        |                             |
| 0.3-1.34 .....                                                 | 614                                 | 1.63                                | *(100)                                 | 30                          |
| 1.34-30 .....                                                  | 824/f                               | 2.19/f                              | *(180/f <sup>2</sup> )                 | 30                          |
| 30-300 .....                                                   | 27.5                                | 0.073                               | 0.2                                    | 30                          |
| 300-1500 .....                                                 | .....                               | .....                               | f/1500                                 | 30                          |
| 1500-100,000 .....                                             | .....                               | .....                               | 1.0                                    | 30                          |

f = frequency in MHz

\* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational / controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

## RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0 mW/cm<sup>2</sup> uncontrolled exposure limit. The formula shown in OET Bulletin 65 is used in the calculation.

Equation from page 19 of OET Bulletin 65, Edition 97-01 is:

$$S = PG / 4 \pi R^2$$

where: S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

hence

$$R = (PG / 4 \pi S)^{1/2}$$

For our device

P = 63.387mW

G = 1.58

R = 20 cm

S = (63.387 \* 1.58) / (4 \*  $\pi$  \* 20<sup>2</sup>) = **0.020** mW/cm<sup>2</sup> < 1.0 mW/cm<sup>2</sup>

For complying the FCC limits for general population/uncontrolled exposure, the power density limit is 1.0 mW/cm<sup>2</sup>. The calculation result of the power density at a distance of 20 cm of our device is less than the limit.

This means that according to OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01), the equipment fulfills the requirements on power density for general population/uncontrolled exposure and therefore fulfills the requirements of section 1.1310 of FCC 47 CFR Part 1.